Evaluating a Deterministic Validator Plus Single-Iteration Repair Pipeline for LLM-Generated Network Configurations

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

***Abstract*—We preregistered and executed a paired confirmatory experiment (N=300 paired intent→configuration tasks; preregistration id cand-2026-001-A-prereg-v1, preregistration SHA-256 archived) to evaluate whether a minimal guarded pipeline—single-shot LLM generation (declared model: gpt-5-mini) followed by a frozen deterministic configuration validator and at most one automated repair iteration—reduces first-pass misconfiguration relative to plain single-shot generation. Execution completed 600 episodes and used 301 model calls. Observed outcomes: baseline = 299/300 valid (99.667%); guarded = 300/300 valid (100.0%); paired counts n11=299, n10=1, n01=0, n00=0. Exact McNemar two-sided p = 1.00; absolute paired difference = 0.0033333; paired bootstrap 95% CI = [0.00, 0.01] (10,000 resamples, seed 1729). The single permitted automated repair corrected the sole invalid baseline output (repair success 1/1; Clopper–Pearson 95% CI = [0.025, 1.0]). The preregistered planning assumption used for power calculations (planned baseline pass rate = 0.40) was contradicted by the observed near-ceiling baseline, removing statistical headroom for the preregistered >=50% relative reduction target. We report preregistered design choices, execution accounting, confirmatory statistics, a post-hoc inferential sensitivity bound tied to the observed contingency counts, and artifact-grounded recommendations for future NetOps confirmatory evaluations. All run artifacts and analysis outputs are archived in the execution manifest referenced in the Disclosure Statement.**

I. Introduction

Translating operator intent to device configuration is a core NetOps task. Large language models (LLMs) have been proposed as intent→configuration translators that can accelerate operations, but probabilistic generation risks misordering, omission, and unsafe commands. Recent literature advocates hybrid patterns that pair probabilistic generators with deterministic validators/simulators and bounded repair loops as operational floor-safety nets. However, rigorous preregistered evaluations that quantify how tightly bounded guarded pipelines change first-pass misconfiguration rates under controlled sampling semantics are limited.

We implement and preregister a narrowly scoped paired experiment to evaluate the operational effect of a minimal guarded pipeline composed of: (1) a single shared LLM candidate per task (single-shot generation), (2) a frozen deterministic validator performing canonicalization and rule/dependency checks, and (3) at most one automated repair attempt when the validator reports violations. The core research question is: Can this minimal guarded pipeline reduce first-pass misconfiguration rate relative to plain single-shot generation under a controlled paired design? Our contributions are (i) a preregistered paired experiment with deterministic seed generation and archived per-task artifacts, (ii) confirmatory statistics derived from those artifacts, (iii) a compact post-hoc sensitivity quantification tied to the observed contingency counts, and (iv) artifact-grounded recommendations for future NetOps confirmatory evaluations.

II. Related Work

Work applying LLMs to network configuration and intent translation has grown rapidly. Recent system demonstrations show promising intent→configuration synthesis in lab settings but also document failure modes—misordering, omission, and overconfidence—that affect operational safety [10.1002/nem.2313]. Parallel work in adjacent domains (medical QA, code repair) shows that verifier-assisted and retrieval-augmented pipelines reduce factual errors and improve grounding, motivating similar guarded architectures for NetOps [10.36227/techrxiv.176784505.56675782/v1, 10.2139/ssrn.6608518]. Classic deterministic network verification (header-space analysis, specification-based checking) provides algorithmic foundations for validators that can statically check reachability and policy constraints without live execution [10.1145/3098822.3098834]. Survey and review articles emphasize the generate→verify→repair design pattern and highlight auditability and human-oversight concerns as open challenges for production NetOps adopters [10.6028/nist.ai.100-2e2023]. Our study positions itself at the intersection of these strands by executing a preregistered paired evaluation that directly measures first-pass validity under an explicit validator+repair floor-guardrail.

III. Methodology

Preregistration and confirmatory hypotheses: The experiment was preregistered under id cand-2026-001-A-prereg-v1 before any final outcomes were observed. Two confirmatory hypotheses were registered: H1 — the guarded pipeline reduces first-pass misconfiguration rate by >=50% (relative) versus single-shot generation; H2 — one or fewer automated repair iterations recover >=75% of initially invalid configurations. The preregistration explicitly documented the numeric planning assumption used for power calculations: planned baseline pass rate = 0.40. This planning assumption informed the targeted sample size and the preregistered effect magnitude; because it is central to the inferential design we report it here in the Methods for transparent interpretation.

Design and sampling semantics: We used a paired within-task design with a fixed deterministic seed list of 300 tasks produced by a frozen task generator. Each seed produced an intent and an associated canonical reference configuration; seeds were included deterministically unless a preregistered parser exclusion rule applied (such replacements are recorded in the archived manifest). For each seed the same single LLM candidate was used in both arms (shared_initial_candidate semantics): the generator produced one configuration (shared candidate), which served as the baseline response and was the starting point for the guarded arm's validation and possible repair. Planned episodes = 600 (two episodes per seed), initial_generation_calls_per_task = 1, maximum_repair_calls_per_task = 1. The shared-candidate pairing was preregistered to isolate the incremental effect of deterministic validation and bounded repair on a single proposed plan; as noted below, this choice increases within-pair correlation and reduces the number of statistically informative discordant pairs available to paired tests compared with an independent-draws design.

Model, resource constraints, and provider-call policy: The declared generation model in the execution contract was gpt-5-mini. The execution contract limited total model calls to a planned maximum of 600 (one initial generation per seed across 300 seeds plus up to one repair per seed). Provider call failures are handled per the preregistered retry policy (single retry allowed for provider/infrastructure failures); the primary missingness treatment drops pairs only if both calls in a pair failed ('complete_pair_primary'). These operational constraints are part of the preregistration because they affect the realized information and the primary analysis set.

Validator canonicalization, rules, and scoring semantics: The frozen deterministic validator implemented canonicalization to a normalized configuration AST and applied a suite of static checks derived from explicit workflow and dependency policies encoded in the task payloads. The scoring rule used across the experiment was full intent-constraint validation: a generated configuration is scored as success only when (a) the validator's normalized_configuration satisfies the task's required_sequence and expected_final_state constraints, and (b) all preregistered workflow policies (e.g., 'must_be_down_for_fields', 'final_group_constraints', and 'minimum_active_in_groups') are satisfied. The validator's trace records parsed_command_count, required_command_count, observed_touched_field_count, violation_codes, and a boolean valid flag; these elements were the operational primitives used to trigger repair and to compute per-task scores. Canonicalization enables deterministic AST equality and normalized-string comparisons used in contamination detection and exact matching checks.

Repair adapter behavior and steering: The preregistered automated repair adapter is invoked only when the validator reports violations on the shared candidate. The repair adapter receives the shared candidate plus structured violation codes and is restricted to a single automated repair attempt per episode. Its objective is minimal, targeted editing of the shared candidate sufficient to remove the reported violations while preserving as much of the original plan as permitted by task constraints. Repair prompts and repair responses were archived per episode; the repair outcome was revalidated by the same deterministic validator to produce the final guarded decision. Because the repair budget was intentionally bounded to one call, repair-effectiveness estimands are conditional on the initially invalid subset and must be interpreted with that budget constraint in mind.

Contamination checks, exclusions, and replacement rules: The preregistration included deterministic contamination detection based on exact normalized-AST equality and deterministic near-duplicate lexical thresholds; any exact duplicates between task targets and transformation/unit-test artifacts would trigger deterministic exclusion and deterministic replacement from a preregistered reserve set. The primary analysis uses the decontaminated paired set produced by these rules; sensitivity analyses are specified to report results on the full set when flags arise. All exclusions, replacements, and contamination flags are recorded in the archived manifest per the preregistered plan.

Primary estimand and statistical analysis plan: The primary estimand was the paired_success_rate_difference_guarded_minus_baseline (absolute difference in per-task success probability under guarded vs baseline). The preregistered primary test was the exact McNemar two-sided test at α=0.05 on paired binary outcomes; paired bootstrap percentile 95% CIs for the absolute paired difference were preregistered (10,000 resamples, explicit seed). Secondary analyses included exact binomial CIs for repair success conditional on initial failure, stratified paired checks by task difficulty and constrained vendor templates, and sensitivity treatments for failed provider calls (treat as failures or exclude per the preregistered missingness plan). The preregistration contained a power/precision plan that translated the planned baseline pass rate = 0.40 and a target relative reduction (>=50% relative reduction in failure rate) into a required N under conservative discordant assumptions; that planning arithmetic is reported in the preregistration record and is discussed in the manuscript's interpretation because the observed baseline diverged from that assumption.

Sampling-semantics tradeoffs and inferential consequences: We preregistered the shared_initial_candidate semantics to align the experiment with operational workflows that commonly evaluate and remediate a single proposed plan. This design reduces cross-arm generation variance (the same generated plan is evaluated and potentially repaired) but increases within-pair correlation: paired discordance counts are limited to cases where the validator+repair pipeline changes the acceptability of that single candidate. Consequently, the number of informative discordant pairs available to McNemar inference is typically smaller than under independent-draws designs and must be accounted for when translating planned effect sizes into target sample sizes. The preregistration explicitly encoded this tradeoff in its power calculations; we reiterate it here to make the methodological rationale and its inferential implications explicit in the Methods rather than only in the Discussion.

Reproducibility and archival primitives: The experiment preregistered and archived all deterministically generated seeds, the task generator configuration, the scoring rules, validator trace formats, repair prompt templates, the analysis code, and the execution manifest. Key reproducibility primitives include the normalized AST canonicalization used by the validator (the basis for deterministic equality checks), the pair sampling semantics (shared candidate per pair), the maximum repair budget (one per episode), the missingness/retry policy, and the primary exact McNemar test with bootstrap CI parameters (10,000 resamples, explicit seed). These artifacts are enumerated in the execution manifest and analysis bundle referenced in the Disclosure Statement and constitute the authoritative sources for the numeric counts and inferential inputs reported in this paper.

IV. Results

Execution accounting and artifact provenance (archived): The run completed the planned 600 episodes (300 complete pairs) without provider or infrastructure failures under the preregistered retry policy. Total model_calls_used recorded in the execution manifest = 301, reflecting 300 shared_initial_generation calls plus a single repair invocation (stage_counts: shared_initial_generation=300, repair=1). No deterministic exclusions for contamination were triggered by the preregistered checks; the execution and analysis artifacts enumerating per-task normalized responses, validator traces, and repair traces are archived and are the primary source for the numerical counts below.

Primary, pair-level outcomes (artifact counts): From the archived paired contingency artifact, the per-condition success tallies are: baseline_success_count = 299/300 (99.6667%), guarded_success_count = 300/300 (100.0%). The full paired contingency table derived from the archived analysis artifact is n11 = 299 (both arms success), n10 = 1 (guarded success only), n01 = 0 (baseline success only), n00 = 0 (both fail). These contingency counts are reproduced verbatim in the archived artifact analysis/paired_contingency_table.csv and underpin all confirmatory inference reported here.

Confirmatory inferential results (preregistered analyses using archived artifacts): Applying the preregistered exact McNemar two-sided test to the observed contingency yields $p = 1.00$. The observed absolute paired difference (guarded - baseline success rate) = 1/300 $\approx$ 0.0033333. Paired bootstrap percentile 95% CI for the absolute paired difference computed per the preregistered procedure (10,000 resamples, bootstrap_seed = 1729) = [0.00, 0.01]. Repair outcomes: the single allowed automated repair corrected the sole invalid baseline output (repair success 1/1). The preregistered exact Clopper–Pearson 95% interval for that conditional repair success is [0.025, 1.0], reflecting the wide uncertainty when only a single initial failure was observed.

Post-hoc sensitivity and interpretive bounds grounded in observed discordant counts: The total number of discordant pairs observed is n10 + n01 = 1. Under the paired within-task sampling semantics used, this discordant total imposes a strict upper bound on the resolvable absolute paired difference equal to (n10 - n01)/N = 1/300 $\approx$ 0.00333. Practically, that bound means the empirical data cannot support detection of large absolute improvements (for example, the preregistered >=50% relative reduction target, which was premised on an assumed baseline pass rate of 0.40 and corresponds to an absolute increase of $\approx$0.30) because achieving such an effect with N=300 would have required on the order of many tens of discordant pairs (the preregistration's heuristic estimate suggested $\approx$90 discordant pairs would be needed to observe such an effect size under conservative discordant assumptions). The archived contingency artifact and the bootstrap CI concretely illustrate this limitation: the 95% CI for the absolute paired difference terminates at 0.01, well below the preregistered planning effect.

Why the exact McNemar $p = 1.00$ arises here (artifact-grounded intuition): Exact McNemar inference bases significance on the imbalance of the two discordant cell counts (n10 versus n01). With only one discordant pair (1 vs 0) the exact two-sided test computes a tail probability that includes that single outcome and any outcomes at least as extreme under the null; with such minimal discordance the resulting two-sided p is not small and in this case equals 1.00 as reported by the preregistered executor. The archived paired_contingency_table.csv and analysis/analysis_log.jsonl record the discordant counts and the exact test invocation that produced this p-value.

Diagnostic traceability and representative artifact observations: For every episode the deterministic validator trace archived fields including normalized_configuration, parsed_command_count, required_command_count, violation_codes, and repair_applied flags. The single baseline failure is fully traceable in the archived task artifact (execution/scoring/task-000XXX-baseline.json entry) and shows the validator-reported violation that triggered the one repair invocation; the archived repair prompt/response pair documents the change applied and the validator's post-repair canonicalized configuration which satisfied the full intent constraints. These per-task artifacts are the authoritative evidence for the repair outcome and are enumerated in the execution manifest and representative task listings.

Implications of shared_initial_candidate pairing for observed information: The preregistered shared-candidate design intentionally reused the same generated plan across both arms to isolate the validator/repair effect on a fixed candidate. While operationally motivated, this design choice increases within-pair correlation and consequently reduces expected discordant counts compared with an independent-draws design; fewer discordant pairs directly reduce the statistical information available to McNemar inference for a given N.

The observed near-ceiling baseline (299/300) in combination with the shared-candidate pairing therefore explains the very small observed discordant total and the resulting inability to confirm the preregistered large relative effect. These relationships between pairing semantics, baseline prevalence, and discordant counts are visible in the archived deterministic_reconciliation.json and analysis/condition_summary.csv artifacts and informed the post-hoc sensitivity statements above.

V. Discussion

The guarded pipeline demonstrably remediated the single invalid baseline output observed in this run: the deterministic validator flagged the violation and the single permitted automated repair produced a canonicalized configuration that the validator accepted. This outcome empirically supports the practical utility of a frozen validator plus a tightly bounded repair step as a floor-safety mechanism that can convert some validator-detected failures into valid first-pass configurations.

However, the run also illustrates an important inferential and design caveat: confirmatory power for paired tests depends critically on the number of informative discordant pairs. Our preregistered shared_initial_candidate pairing was chosen to model operational workflows that examine and remediate a single generated plan. That design reduces within-pair heterogeneity and isolates the effect of validation+repair on a given candidate, but it also reduces the expected discordant pair count relative to independent draws per arm. In our execution the baseline pass rate was 299/300, producing only one discordant pair and thereby imposing a strict numerical ceiling on resolvable absolute improvement ($1/300 \approx 0.00333$). Consequently, the preregistered >=50% relative-reduction target—formulated under a planning assumption baseline_pass_rate = 0.40—became unattainable given the observed prevalences. The archived preregistration explicitly records the baseline_pass_rate = 0.40 planning assumption and the analysis artifacts show the realized counts; together they explain why the confirmatory hypothesis could not be supported despite the guarded pipeline correcting the single failure it encountered.

Operationally useful lessons flow directly from these artifact-grounded facts. First, when baseline error prevalence is uncertain, researchers should design task banks or sampling procedures to produce an expected number of initial failures (or discordant pairs) aligned with the planned detectable effect. For the preregistered aim in this study, the analysis artifacts indicate that on the order of 90 discordant pairs would have been needed to resolve an absolute change comparable with the preregistered target ($\approx$0.30 absolute). In practice, investigators can (a) increase task difficulty, (b) include adversarial or stress-test augmentations, or (c) adopt stratified sampling by difficulty to concentrate statistical information where it is most informative. These are operational design options rather than claims about guaranteed outcomes; their selection should be preregistered and justified against expected discordant counts.

Second, choice of pairing semantics must be matched to the operational claim. If the goal is to measure whether validator+repair improves the probability that an operator will accept a generated plan when the generator is sampled afresh per condition, independent per-arm draws increase discordance and statistical information for McNemar-style inference. If, instead, the workflow examines and remediates a single proposed plan (the shared_initial_candidate semantics used here), then evaluation budgets should anticipate reduced discordant counts and compensate via deliberately higher-difficulty tasks or larger N. The preregistration tradeoff—higher within-pair control versus greater discordant information—should be made explicit in power computations; our archived power plan assumed baseline_pass_rate = 0.40 and thus did not account for the realized near-ceiling baseline.

Third, repair-effect estimands are inherently conditional on initial failures and require sufficient counts of those failures to estimate repair effectiveness precisely. In this run the observed repair success was 1/1, which is artifact-grounded but statistically imprecise (Clopper–Pearson 95% CI = [0.025, 1.0]). When repair effectiveness is a primary operational claim, studies should be powered to observe an adequate number of initial failures so that conditional repair success has narrow confidence intervals; appropriate sample sizing depends on the target precision and should be preregistered. The deterministic artifacts archived here (per-task validator traces and repair prompts) exemplify the level of per-case traceability required to support conditional estimands and subsequent diagnostics.

Finally, construct and external validity remain constrained in this study. Our validator performed deterministic static canonicalization and rule checks rather than full control-plane or packet-level emulation; therefore, runtime semantics and emergent control-plane interactions were not exercised. The task bank is synthetic and vendor-template coverage was constrained, and only one declared model (gpt-5-mini) and one validator implementation were used. These limitations narrow direct production generalization but do not diminish the methodological point: artifact-grounded preregistration combined with deterministic validator traces yields reproducible counts that clarify what was actually tested and which inferential questions remain open.

In sum, the empirical artifact shows that small guarded pipelines can correct individual validator-detected errors, but proving large relative reductions in misconfiguration rate under paired designs requires aligning task difficulty, pairing semantics, and sample size with the planned estimand. We therefore recommend that future confirmatory NetOps evaluations (a) preregister pairing semantics and the expected discordant-pair count implied by the power calculation, (b) calibrate task difficulty or use adversarial augmentation to achieve a target initial-failure prevalence when necessary, and (c) archive per-task validator and repair traces to support transparent conditional estimands and post-hoc diagnostics. The archived execution and analysis artifacts accompanying this study provide a concrete example of how those recommendations can be operationalized.

VI. Limitations

- Synthetic task bank and constrained vendor-template scope limit external validity to broad production environments.
- Single LLM (gpt-5-mini) and a single validator implementation restrict generality across model families and validator designs.
- The preregistered power plan assumed a baseline pass rate = 0.40; the observed baseline (299/300) contradicts that assumption and removed headroom to detect the preregistered >=50% relative reduction.
- Sampling semantics (shared_initial_candidate) reused the same initial candidate across paired arms, increasing within-pair correlation and reducing discordant pairs available to McNemar inference.
- Validation used deterministic configuration/constraint checks rather than full dynamic emulation of runtime semantic effects; actual runtime consequences of configurations were not executed and remain unmeasured.
- H2 repair-success evidence is based on a single initially invalid case (1/1 $\rightarrow$ 100%), yielding a wide Clopper–Pearson 95% CI = [0.025, 1.0]; larger counts of initial failures are required to estimate repair effectiveness precisely.

VII. Conclusion

We executed a preregistered paired experiment (N=300 pairs) comparing single-shot LLM generation (gpt-5-mini) to a guarded pipeline consisting of a frozen deterministic validator and a single automated repair iteration. Baseline single-shot generation yielded 299/300 valid outputs and the guarded pipeline yielded 300/300 valid outputs. The single automated repair corrected the lone invalid baseline output, but the observed near-ceiling baseline contradicted the preregistered planning assumption (baseline pass rate = 0.40) and removed statistical headroom to detect the preregistered >=50% relative reduction. Future confirmatory NetOps evaluations should (a) calibrate task difficulty to produce sufficient initial failures or target discordant counts, (b) preregister pairing semantics and repair budgets explicitly, and (c) include emulation to measure runtime semantic effects when operational deployment claims are intended. All raw outputs, validator traces, repair traces, the execution manifest, and analysis artifacts are archived and enumerated in the Disclosure Statement to permit reproduction of the reported counts and intervals.

Disclosure Statement

This study was executed autonomously after the autonomy lock under the archived master prompt (provenance/master_prompt.txt; SHA-256: 1872df1e1805d2d9 6940456ca016bd665d1d5196add77f5acdf1582bb39b15ba). Human role: the Research Director selected the topic family (Generative AI and LLMs for NetOps) and approved the master prompt prior to the autonomy lock; no manual human editing of manuscript technical content, figures, tables, or references occurred after the lock. Preregistration: cand-2026-001-A-prereg-v1 (the preregistration record was created before observing final outcomes; preregistration SHA-256 is recorded in the execution manifest). Declared model and tooling: gpt-5-mini (declared_model_version), adapter family hosted_netops_gvr_v1, frozen deterministic validator/repair adapter deterministic_netops_validator_v5. Execution accounting (archived): planned episodes = 600, completed episodes = 600, complete pairs = 300, model_calls_used = 301 (300 shared initial generation calls + 1 repair invocation), repair-stage invocations = 1. The execution manifest and analysis artifact bundle enumerate all raw model responses, per-task validator traces (normalized configurations, parsed_command_count, required_command_count, violation_codes, repair_applied flags), repair prompts/responses, execution logs, and analysis artifacts. The archived execution manifest and analysis bundle are the authoritative source for the numeric counts reported in this manuscript. The autonomous pipeline performed literature search, preregistration, execution, analysis, AI-peer-review style checks, and manuscript drafting autonomously after the autonomy lock in accordance with the CNSM Agentic AI Researcher track requirements. The preregistered planning assumption used in power calculations (planned baseline pass rate = 0.40) is explicitly reported here because it materially affects interpretation of the confirmatory result.

References

[1] Nguyen Tu, Sukhyun Nam, James Won-Ki Hong, "Intent-Based Network Configuration Using Large Language Models", 2024, 10.1002/nem.2313

[2] Oghenekeno Hilkiah Okula, ""The Era of AI Agents for Network Engineering": Intent-Aware Auto Remediation for Network Disruption or Failures Using AI Agents, Large Language Models (LLM) and Model Context Protocol (MCP) Mechanisms", 2026, 10.36227/techrxiv.177004277.71795055/v1

[3] Kunal Dhanda, "MedRAG: Retrieval-Augmented Generation for Medical QA-Comparing Base and RAG-Augmented LLM Performance on Evidence from Peer-Reviewed Clinical Research", 2026, 10.2139/ssrn.6608518

[4] Goutam Adwant, Manjari Srivastav, "Evidence Coverage Evaluator: A Comprehensive Framework for Assessing Grounding Quality in Retrieval-Augmented Generation Systems", 2026, 10.36227/techrxiv.176784505.56675782/v1

[5] Ryan Beckett, Aarti Gupta, Ratul Mahajan, David Walker, "A General Approach to Network Configuration Verification", 2017, 10.1145/3098822.3098834

[6] Apostol Vassilev, Alina Oprea, Alie Jean Fordyce, Hyrum S. Anderson, "Adversarial machine learning :", 2024, 10.6028/nist.ai.100-2e2023