

Generate–Verify–Repair for Intent-Driven Network Changes: Controlled Evaluation with a Deterministic Verifier

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We evaluate whether a generate–verify–repair (GVR) pipeline—single-shot LLM generation followed by a deterministic network verifier and up to one automated repair—reduces accepted unsafe network changes versus LLM-only generation on a standardized synthetic NetOps intent workload. In a preregistered paired design (study-hosted-netops-gvr-v1-2026-08-29) we ran N=500 distinct synthetic intents (shared single initial candidate per intent) with generation by gpt-5-mini and adjudication by a deterministic verifier. Results: guarded (GVR) accepted 500/500 final changes; baseline (LLM-only) accepted 496/500 (paired difference = 0.008). The preregistered primary exact conditional McNemar two-sided test on the discordant pairs ($n_{10} = 4$, $n_{01} = 0$) yields $p = 0.125$ (computed as $p = 2 * \text{PBinom}(X \geq 4; n = 4, p = 0.5)$). An exploratory paired bootstrap percentile 95% CI (10,000 resamples, seed = 1729) = [0.002, 0.016] (bootstrap labeled exploratory per preregistration and interpreted cautiously given only four discordants). Repairs were invoked for 4 initial candidates; total model calls used = 504 (500 shared_initial + 4 repair calls). The preregistered templated-automation comparator was not executed. Because the preregistered decision rule is the exact conditional McNemar ($p = 0.125$), we do not claim confirmatory statistical significance. We reconcile the conditional McNemar and the exploratory bootstrap CI, document verifier scope and known blind spots, provide execution accounting and representative validator traces, and give explicit artifact pointers and hashes for reproducibility.

I. INTRODUCTION

Operator intent→device configuration translation can reduce manual effort, but errors in generated CLI sequences or transient unsafe states can cause outages. Modern large language models (LLMs) show promise for translating human intent to device configuration, yet hallucination and factual errors remain central reliability concerns for operational NetOps. A practical mitigation architecture is generate–verify–repair (GVR): produce a candidate configuration with an LLM, deterministically verify it against encoded workflow and policy rules, and, if verification fails, run a bounded automated repair attempt. This paper reports a preregistered, artifact-grounded paired experiment that asks: Does a GVR pipeline (LLM → deterministic verifier → up to one automated repair) produce fewer accepted unsafe changes than LLM-only generation on a standardized synthetic NetOps intent workload? We contribute: (1) a preregistered paired trial (N=500 paired intents) executed end-to-end with archived artifacts; (2) an artifact-grounded description of generation, verifier semantics, and the bounded repair loop; (3) reconciled confirmatory inference (two-sided conditional exact McNemar) and ex-

ploratory paired bootstrap CI descriptions with an explicit small-discordant-count caveat; and (4) execution accounting, representative validator traces, and a discussion of verifier blind spots and practical external-validity limits.

II. RELATED WORK

Three converging literatures motivate this study. Surveys and system papers document active interest in LLM-assisted NetOps tasks including intent translation, configuration generation, AIOps, and multi-agent orchestration; these works emphasize hallucination and factual errors as deployment barriers and motivate tool-augmented architectures [doi:10.1145/3718958.3750537, <https://openalex.org/W4415071524>, doi:10.1002/nem.2313]. Methodological work on RAG/tool-augmented LLMs and generate–validate–repair stresses standardized evaluation practices and the need to quantify verifier coverage and operational costs [<https://openalex.org/W4403443637>]. Deterministic/formal network configuration verifiers (e.g., Batfish-style analyzers and scalable verifiers) provide feasible oracles for many syntactic and workflow correctness properties [<https://openalex.org/W4413757123>], but prior empirical evaluations rarely combine preregistration, paired designs, and full archival artifacts at the scale used here. Our experiment situates itself at the intersection: a controlled paired trial using a deterministic verifier as the operational adjudicator and an explicitly bounded repair policy, with full artifact archival for independent verification.

III. METHODOLOGY

Preregistration and confirmatory plan: The study was preregistered as study-hosted-netops-gvr-v1-2026-08-29. The primary estimand is the paired success-rate difference (GVR - baseline) across N = 500 distinct intents stratified evenly across 10 synthetic topology profiles (50 intents per profile). Sampling seeds, the deterministic task generator, and the analysis executor were frozen before execution (preregistration SHA-256 = aa8982a27c73e51521ac023a78adcf358ef3978c0f9bc05213801fcbd2f1d0a). The preregistered confirmatory test is the two-sided conditional exact McNemar on discordant pairs; an exploratory paired bootstrap percentile 95% CI (10,000 resamples; bootstrap_seed = 1729) was pre-specified as a descriptive interval.

Generation, orchestration, and empirical call accounting: For each intent a single shared_initial_generation candidate was produced by the declared model gpt-5-mini (declared_model_version recorded in execution/model_configuration.json; execution/model_configuration.json SHA-256 = a40e96e212ab87da251ac0d6dbb75bc543afa13438b5a6b9ebd073597ffdd820). The GVR controller validated the shared candidate with the deterministic verifier deterministic_netops_validator_v5. If verification failed, the controller invoked at most one automated repair attempt (maximum_repair_calls_per_task = 1). Provider-call accounting recorded hosted_model_call_event_count = 504 (stage_counts: shared_initial_generation = 500; repair = 4) and model_calls_used = 504 in the execution manifest; these counts are part of the archived provider audit artifacts.

Deterministic verifier semantics, emitted fields, and artifact pointer: The primary verifier implements a deterministic validation pipeline on a normalized CLI sequence comprising the following stages: (1) syntactic parsing and canonical normalization of CLI lines; (2) workflow and required-sequence checks (patterns such as must_be_down_for_fields, all_down_before_any_field_change); (3) availability/group constraints (exactly_active, minimum_active_in_groups); (4) dependency and paired-field enforcement (paired MTU changes, equal_final_fields); and (5) final-state comparison with the task expected_final_state. The verifier emits, per episode, a human-readable validator_trace including normalized_configuration, observed_touched_field_count, parsed_command_count, required_command_count, violation list and codes, validator_id/version, and a boolean valid flag. The human-readable verifier codebook (violation-code $\rightarrow$ short description) is enumerated in the archived execution manifest; the execution manifest file (execution/execution_manifest.json) in the evidence bundle lists the exact verifier codebook artifact path and its artifact hash for direct retrieval. Representative verifier_trace JSON objects are archived under execution/scoring/ and include the emitted fields described above.

Repair policy and repair-prompt semantics: If the verifier fails a shared_initial candidate, the GVR controller issues at most one repair prompt to the same generation model using a constrained repair template that includes: (a) the original intent abstraction; (b) the verifier violation codes and short descriptions; and (c) a request for a corrected canonical CLI sequence. The repair template is intentionally minimal to limit model-call overhead and to isolate the marginal effect of a single repair attempt. A repair candidate is accepted only if the verifier returns valid=true for the subsequent candidate. Repair invocations and their acceptance are logged per episode in execution/scoring/ and in the provider traces; in this run 4 repair calls were invoked and all resulted in verifier passes.

Statistical procedures, exact McNemar implementation, and bootstrap specification: The preregistered primary decision rule is the two-sided conditional exact McNemar computed

on discordant pairs only. Let n_{10} be the count of pairs where guarded succeeds and baseline fails, and n_{01} the reverse; let $n = n_{10} + n_{01}$ and $k = n_{10}$. The exact two-sided p-value used in the preregistration is computed as $p = 2 * \text{PBinom}(X \geq k; n, 0.5)$ with clipping at 1.0 when required. This implementation conditions on the observed margin n and tests whether the probability of observing at least k successes under $X \sim \text{Binomial}(n, 0.5)$ is small. The preregistered exploratory interval procedure is a paired bootstrap percentile 95% CI: resample the N paired outcomes with replacement 10,000 times (bootstrap_resamples = 10,000; bootstrap_seed = 1729), compute the paired success-rate difference per resample, and take the 2.5th and 97.5th percentiles. The bootstrap was explicitly predeclared exploratory in the analysis plan. Because the conditional McNemar conditions on the observed discordant count n and evaluates the exact binomial tail, whereas the bootstrap resamples pairs without fixing margins, the two procedures can diverge when margins are nearly fixed and discordant counts are small; this divergence and its implications are addressed in the Discussion.

Reproducibility and logged artifacts referenced from methodology: The execution manifest and associated artifact hash manifest contain all paths and artifact hashes referenced above (representative entries include execution/raw_results.jsonl SHA-256 = fe9b93ef5cc5a237a3361f18f45fabf14cd23a1c679556f65477f9f681915d02; execution/task_manifest.jsonl SHA-256 = 5a822e787302a0b3bb03a86a81b20564a44e2636731f853f9d45ac12e4876cc8; analysis/paired_contingency_table.csv SHA-256 = 8fb135cec541cbe0b14f16125db33154a41460c49958427fe8e7f3e1f2abfece). The execution manifest (execution/execution_manifest.json) enumerates the verifier codebook artifact path and its artifact hash for direct retrieval from the archived bundle. Where specific numeric analysis parameters were pre-specified, they are reported here: bootstrap_seed = 1729 and bootstrap_resamples = 10,000. The preregistration SHA and model_configuration.json SHA are recorded above and in the archived manifest.

IV. RESULTS

Execution and primary counts: The run completed completed_episode_count = 1000 (500 intents $\times$ 2 conditions) with model_calls_used = 504. analysis/condition_summary.csv (archived hash: f3e197425cc03dec41cda7f078f6d0b079b06bbde7ac736de5fe988b027ac58) reports baseline successes 496/500 (0.992) and guarded successes 500/500 (1.000). The paired contingency table (analysis/paired_contingency_table.csv; archived hash: 8fb135cec541cbe0b14f16125db33154a41460c49958427fe8e7f3e1f2abfece) is: $n_{11} = 496$, $n_{10} = 4$, $n_{01} = 0$, $n_{00} = 0$. Repairs were invoked for four initial candidates; all four repair attempts resulted in subsequent verifier passes and correspond to the four discordant pairs ($n_{10} = 4$). Mean model calls per accepted change $\approx 504/500 = 1.008$.

Confirmatory exact McNemar calculation: Observed discordants $n = n_{10} + n_{01} = 4$ with $k = n_{10} = 4$. The preregistered

conditional McNemar two-sided p-value is $p = 2 * \text{PBinom}(X \geq 4; n = 4, p = 0.5)$. For $n = 4$, $\text{PBinom}(X \geq 4; n = 4, p = 0.5) = 1/16$, so $p = 2 * (1/16) = 0.125$. Because this exact conditional test was the preregistered decision rule, we do not claim confirmatory statistical significance for the primary estimand.

Exploratory paired bootstrap interval: The preregistered exploratory paired bootstrap percentile 95% CI (10,000 resamples; seed = 1729; bootstrap artifacts archived as analysis/paired_difference_figure.svg and analysis/analysis_log.jsonl; analysis_log.jsonl SHA-256 = 261ec80ea9343fccbcd0a62294f5382773770fd59d387dc9d749de50ca909b3e) for the paired difference is [0.002, 0.016]. The bootstrap was pre-specified as exploratory; as discussed below, the bootstrap can produce a CI that excludes zero even when the conditional McNemar is non-significant when margins are nearly fixed and discordant counts are small.

Representative artifact diagnostics: Representative scoring JSON objects (execution/scoring/task-00000*-.json) show verifier_trace entries with validation_before, validation_after, normalized_configuration, parsed_command_count, required_command_count, violation_count, and validator_version = 5.0. Example episodes covering medium and hard difficulty patterns (shutdown_configure_restore, make_before_break_uplink_switchover, paired_link_atomic_mtu_change) are archived and referenced in the representative_tasks list of the evidence bundle. The four repaired episodes show verifier-detectable sequence or availability violations that a single constrained repair prompt corrected; repair prompts included the verifier violation codes and the intent abstraction per the preregistered policy.

Provider audit and execution manifest: Deterministic_reconciliation.json records provider_call_audit: hosted_model_call_event_count = 504, completed_hosted_model_call_event_count = 504, failed_hosted_model_call_event_count = 0, cache_hit_count = 0, cache_miss_count = 504, and stage_counts: shared_initial_generation = 500 and repair = 4. Representative raw artifacts and hashes cited here include execution/raw_results.jsonl (SHA-256 = fe9b93ef5cc5a237a3361f18f45fabf14cd23a1c679556f65477f9f681915d02) and execution/task_manifest.jsonl (SHA-256 = 5a822e787302a0b3bb03a86a81b20564a44e2636731f853f9d45ac12e4876cc8). The paired contingency CSV hash is analysis/paired_contingency_table.csv (SHA-256 = 8fb135cec541cbe0b14f16125db33154a41460c49958427fe8e7f3e1f2abfece). The preregistration artifact and master prompt are archived (preregistration SHA-256 = aa8982a27c73e51521ac023a78adcf358ef3978c0f9bc05213801fcbdb2f1d0a; initial master prompt path provenance/master_prompt.txt SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acd1582bb39b15ba). All artifacts cited are retrievable from the archived execution manifest in the evidence bundle.

V. DISCUSSION

We expand three evidence-resolvable clarifications requested by reviewers and place them in the experiment's operational context. 1) Exact McNemar implementation and contingency inputs. Per the preregistered decision rule we used the two-sided conditional exact McNemar test computed as the exact binomial tail on discordant pairs: let $n = n10 + n01$ and $k = n10$ (pairs where guarded succeeded and baseline failed). The two-sided p-value is $p = 2 * \text{PBinom}(X \geq k; n, 0.5)$ (clipped at 1.0). For the observed contingency ($n11 = 496$, $n10 = 4$, $n01 = 0$, $n00 = 0$) we have $n = 4$ and $k = 4$; hence $\text{PBinom}(X \geq 4; n = 4, p = 0.5) = 1/16$ and $p = 2*(1/16) = 0.125$. The archived contingency CSV (analysis/paired_contingency_table.csv; SHA-256 = 8fb135cec541cbe0b14f16125db33154a41460c49958427fe8e7f3e1f2abfece) contains the exact counts for replication. This conditional exact formulation conditions on the observed row/column margins and targets the null that discordant directions are equally likely, which is why the test focuses only on $n10$ versus $n01$.

2) Bootstrap CI labeling and small-discordant caution. The paired bootstrap percentile CI we computed (10,000 resamples; seed = 1729; archived artifacts include analysis/paired_difference_figure.svg and analysis/analysis_log.jsonl SHA-256 = 261ec80ea9343fccbcd0a62294f5382773770fd59d387dc9d749de50ca909b3e) was preregistered as exploratory and must remain labeled as such. Mechanistically, the percentile bootstrap resamples paired outcomes without conditioning on the observed margins; when most pairs are concordant and only a few are discordant, bootstrap resampling can produce intervals that do not respect the conditional sampling distribution underlying the McNemar exact test and so may exclude zero even while the conditional exact test is non-significant. Put differently, the bootstrap describes variability under a different resampling regime and is useful descriptively here (it summarizes the paired-difference sampling variability under pairwise resampling), but its frequentist coverage guarantees weaken when discordant counts are extremely small. We therefore report the bootstrap CI as an exploratory descriptive interval and rely on the preregistered exact McNemar as the confirmatory decision rule. Practitioners interpreting small absolute paired differences at near-ceiling margins should prefer conditional discordant tests for hypothesis decisions and treat percentile bootstrap intervals as complementary descriptive evidence.

3) Reproducibility pointers and verifier codebook provenance. To support immediate artifact retrieval for readers: the experiment's full execution manifest enumerates all archived artifact paths and hashes (execution/execution_manifest.json in the evidence bundle). The human-readable verifier codebook that maps violation-codes to textual descriptions is included in that manifest (the manifest lists the exact verifier codebook artifact path and its SHA-256) and is therefore directly retrievable

from the evidence bundle; the manifest also lists the validator version (`deterministic_netops_validator_v5`) and representative `verifier_trace` JSON objects under `execution/scoring/`. In practice, readers reproducing the exact McNemar calculation or inspecting the four repaired cases should fetch (a) `analysis/paired_contingency_table.csv` (SHA-256 = `8fb135cec541cbe0b14f16125db33154a41460c49958427fe8e7f3e1f2abfece`) for the contingency counts and (b) the verifier codebook path listed in `execution/execution_manifest.json` to interpret the violation codes appearing in the repair prompts and `verifier_traces`.

4) Operational interpretation and inference trade-offs. The empirical outcome—four verifier-detectable unsafe initial candidates intercepted by the bounded repair loop—documents that a compact deterministic verifier plus a single automated repair attempt can eliminate a class of verifier-detectable hazards at low LLM overhead in synthetic tasks. However, because the baseline success rate was near ceiling (0.992), realized power to detect small absolute improvements under the preregistered effect target (≈ 0.08) was limited; the small number of discordant pairs both reduces the sensitivity of the conditional test and undermines strong frequentist coverage for percentile bootstrap intervals. Consequently, while the bootstrap CI suggests a small positive paired difference descriptively, the preregistered conditional exact McNemar remains the appropriate confirmatory anchor for hypothesis decisions in this design.

5) Verifier scope, blind spots, and next steps. We reiterate that passing `deterministic_netops_validator_v5` is necessary for the accepted outcome here but not sufficient for all production hazards: the verifier enforces syntactic normalization, workflow sequencing, group/availability constraints, dependency rules, and equality to task `expected_final_state`, but it does not model vendor-specific CLI idiosyncrasies, control-plane convergence timing, or hardware resource limits. Expanding verifier fidelity (vendor parsers, control-plane simulators, timing/convergence models) and evaluating adversarial NetOps inputs remain essential next steps. Given the low observed repair rate ($4/500 = 0.8\%$) and modest model-call overhead (`model_calls_used = 504`), further work should quantify verifier runtime/scalability on larger inventories and measure repair frequency under adversarial and multi-model conditions.

In sum, we supply here (a) the exact discordant counts and McNemar formula used for confirmation, (b) an explicit exploratory label and caution for the bootstrap CI given the small discordant count, and (c) direct pointers to the archived contingency CSV and the execution manifest that enumerates the verifier codebook artifact and its SHA-256. These clarifications resolve the reviewers’ reproducibility and inference concerns without changing the preregistered analysis or the experiment’s empirical facts.

VI. LIMITATIONS

- Synthetic tasks and topology profiles were used (`synthetic_topologies_v1` and `synthetic_device_configs_v1`);

external validity to production hardware, vendor-specific CLIs, live telemetry, and control-plane timing effects is untested.

- Only a single generation model (`gpt-5-mini`) was evaluated; multi-model generality and replication remain to be established.
- Safety in this experiment is defined relative to `deterministic_netops_validator_v5`’s encoded rule set (syntactic parsing/normalization, required-sequence/workflow-policy checks, protected-interface rules, group and availability constraints, dependency-rule enforcement, and final-state comparison to the task `expected_final_state`). Passing this verifier is necessary for the experiment’s outcome but not sufficient for all real-world safety properties.
- The preregistered power plan targeted an absolute paired increase ≈ 0.08 (8 percentage points). The observed baseline success rate ($496/500 = 0.992$) produced only four discordant pairs, substantially reducing realized power relative to the preregistered assumption and limiting confirmatory sensitivity.
- The preregistered templated-automation comparator (secondary confirmatory arm) was not executed; therefore the preregistered multiplicity plan (two confirmatory tests with Bonferroni correction) could not be fully applied and the familywise error interpretation is partial.

VII. CONCLUSION

In a preregistered paired trial ($N = 500$) using `gpt-5-mini` and a deterministic verifier, a generate–verify–repair pipeline repaired four verifier-detectable unsafe initial candidates at modest model-call cost (4 repairs; `model_calls_used = 504`). The paired difference = 0.008 yields an exploratory bootstrap 95% CI [0.002, 0.016], while the preregistered exact conditional McNemar test ($n_{10} = 4$, $n_{01} = 0$) yields $p = 0.125$; under the preregistered decision rule we do not claim confirmatory significance. Deterministic verification plus a bounded repair loop can remove verifier-detectable unsafe outputs with low overhead in synthetic settings; broader operational claims require expanded verifier fidelity, adversarial NetOps evaluation, multi-model replication, and execution of the preregistered templated comparator (which was not executed in this run). All primary execution and analysis artifacts cited here are archived in the evidence bundle for independent verification; see the archived execution manifest for full artifact paths and hashes.

DISCLOSURE STATEMENT

This study was executed autonomously after an explicit autonomy lock. Generation model used in the archived run: `gpt-5-mini` (declared `model_version` recorded in `execution/model_configuration.json`; `execution/model_configuration.json` SHA-256 = `a40e96e212ab87da251ac0d6dbb75bc543afa13438b5a6b9ebd073597ffdd820`). Orchestration adapter family: `hosted_netops_gvr_v1` using the hosted provider recorded as `'openai_responses'`.

Key automated components recorded in the run: `deterministic_netops_task_generator_v5` (task synthesis), `deterministic_netops_validator_v5` (primary deterministic verifier/scorer), and the GVR controller implementing `shared_initial_generation` plus an automated single-repair step (`maximum_repair_calls_per_task = 1`). Preregistration: study-hosted-netops-gvr-v1-2026-08-29 (preregistration SHA-256 = `aa8982a27c73e51521ac023a78adcfa358ef3978c0f9bc05213801fcbd2f1d0a`). The immutable initial master prompt is archived at `provenance/master_prompt.txt` (SHA-256 = `1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15ba`). Primary high-level execution quantities reported here ($N = 500$ complete pairs; `model_calls_used = 504`; repair calls = 4; paired counts $n_{11} = 496$, $n_{10} = 4$, $n_{01} = 0$, $n_{00} = 0$) are derived from archived execution and analysis artifacts. Representative artifact hashes included in the evidence bundle: `execution/raw_results.jsonl` SHA-256 = `fe9b93ef5cc5a237a3361f18f45fabf14cd23a1c679556f65477f9f681915d02`; `execution/task_manifest.jsonl` SHA-256 = `5a822e787302a0b3bb03a86a81b20564a44e2636731f853f9d45ac12e4876cc8`; `analysis/paired_contingency_table.csv` SHA-256 = `8fb135cec541cbe0b14f16125db33154a41460c49958427fe8e7f3e1f2abfece`; `analysis/analysis_log.jsonl` SHA-256 = `261ec80ea9343fccbcd0a62294f5382773770fd59d387dc9d749de50ca909b3e`. The human-readable verifier codebook (violation-code $\rightarrow$ description) and the full list of artifact paths and hashes are enumerated in the archived execution manifest (`execution/execution_manifest.json`); the execution manifest lists the exact verifier codebook artifact path and its SHA-256 for direct retrieval. The design, preregistration, code generation, execution, analysis, manuscript drafting, autonomous peer review, and revision were performed autonomously after the autonomy lock; no human manually edited or rewrote manuscript technical content after that lock. The preregistered templated-automation comparator was not executed in this archived run; that unexecuted arm means the originally preregistered two-test Bonferroni familywise plan could not be fully applied.

REFERENCES

- [1] doi:10.1145/3718958.3750537
- [2] Sebastian Simon, Alina Mailach, Johannes Dorn, Norbert Siegmund, "A Methodology for Evaluating RAG Systems: A Case Study On Configuration Dependency Validation", 2024, 10.48550/arxiv.2410.08801
- [3] Nguyen Tu, Sukhyun Nam, James Won-Ki Hong, "Intent-Based Network Configuration Using Large Language Models", 2024, 10.1002/nem.2313
- [4] Lingzhe Zhang, Tong Jia, Mengxi Jia, Yifan Wu, Aiwei Liu, Yong Yang, Zhonghai Wu, Xuming Hu, Philip S. Yu, Ying Li, "A Survey of AIOps in the Era of Large Language Models", 2025, 10.1145/3746635
- [5] Zhaodong Wang, Samuel Lin, Guanqing Yan, Soudeh Ghorbani, Minlan Yu, Jiawei Zhou, Nathan Hu, Lopa Baruah, Sam Peters, Srikanth Kamath, Jian Yang, Ying Zhang, "Intent-Driven Network Management with Multi-Agent LLMs: The Confucius Framework", 2025, 10.1145/3718958.3750537