

Does Deterministic Generate–Validate–Repair Reduce Unsafe LLM-Generated Network Changes? A Confirmatory Paired Study

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a sealed paired confirmatory study ($n = 200$ intent→configuration tasks) to test whether a deterministic generate–validate–repair (GVR) pipeline that consults a deterministic NetOps validator reduces validator-detected unsafe or semantically incorrect network changes relative to an LLM-only generation pipeline. The run used a single hosted model (gpt-5-mini) with adapter-enforced shared-initial generation semantics and a primary deterministic validator (deterministic_netops_validator_v5). Execution completed all planned pairs (completed_pairs = 200) consuming 200 model calls (one shared initial generation per task); no repair calls were issued because every initial candidate passed the validator. Paired contingency: $n_{11} = 200$, $n_{10} = 0$, $n_{01} = 0$, $n_{00} = 0$; estimate = 0.0; exact McNemar two-sided $p = 1.0$; 95% bootstrap percentile CI = [0.0, 0.0] (10,000 resamples, seed = 1729). Because the baseline validator-detected unsafe incidence was 0% on this task bank, the preregistered $\geq 50\%$ relative-reduction hypothesis could not be meaningfully evaluated. We report the sealed design, execution accounting (start: 2026-08-30T11:50:34.530059Z; end: 2026-08-30T12:12:07.541650Z), the Mininet 10% hold-out (20 tasks) that produced zero validator–emulator disagreements, and an artifact-grounded discussion of operational implications and threats to validity (preregistration id: cnsms2026-gvr-effectiveness-02).

I. INTRODUCTION

Automating intent→configuration translation with generative language models can increase NetOps productivity but risks producing incorrect or unsafe changes that cause outages or policy violations. Prior work therefore proposes grounding, deterministic validation, and repair loops (generate–validate–repair, GVR) to detect and correct unsafe candidates before application. The operational benefit of automated repair is conditional on three factors: (i) baseline prevalence of validator-detectable failures from the chosen generator/prompting policy; (ii) validator coverage and fidelity; and (iii) the available repair budget and repair-prompt effectiveness. We preregistered a narrowly scoped confirmatory question: Does an automated, deterministic GVR pipeline that consults a deterministic NetOps validator materially reduce validator-detected unsafe or semantically incorrect network changes relative to an LLM-only generation pipeline on a curated 200-task intent→configuration bank? The study was designed as a paired experiment that fixes the generator output per task and isolates the marginal effect of invoking a validator+repair on the same candidate.

II. RELATED WORK

LLM failure modes, mitigation primitives, and NetOps prototypes. Systematic surveys and empirical studies across LLM applications have repeatedly documented hallucinations and factual errors, substantial prompt sensitivity, and non-determinism in generated outputs; these phenomena motivate a family of mitigations including retrieval grounding, verifier-assisted repair, and constrained or guarded agent architectures [10.1007/s11704-026-60308-3, <https://openalex.org/W4399803256>, <https://openalex.org/W4402860127>]. In the NetOps domain specifically, multiple prototype systems demonstrate that LLMs can translate natural-language intent into configuration fragments or workflows, but these works commonly stop short of instrumented, production-style failure-rate studies that quantify end-to-end operational risk [<https://openalex.org/W4399629579>, <https://openalex.org/W4403635865>].

Generate–Validate–Repair (GVR) and deterministic validators. Architectural proposals and early implementations advocate integrating LLM generation with deterministic, rule-based validators (Batfish-style or intent/constraint checkers) to prevent straightforward syntactic and semantic violations before application; GVR loops then attempt automated repairs when validators report violations [<https://openalex.org/W4410125989>, doi:10.36227/techrxiv.177004277.71795055/v1]. These integrations aim to convert an open-ended generative problem into a closed-loop verification problem where correctness is operationalized by validator predicates (for example: required_command_count, parsed_command_count, violation_codes). The literature also notes that validator coverage is crucial: deterministic checkers can be strong for the class of constraints they encode (topology-level invariants, required sequences), but may omit device-level idiosyncrasies or data-plane effects only visible under emulation or on real hardware [<https://openalex.org/W4399629579>]. That gap motivates the use of secondary end-to-end emulators or sampled real-device checks as contamination detectors in empirical evaluations.

Agentic workflows, tool-use brittleness, and red-team findings. Studies of agentic LLM systems and tool-using agents highlight new failure modes: tool-description or tool-registry

injection, cross-tool ambiguity, and persona/history interactions that change how agents interpret verifier responses or construct repairs [10.21203/rs.3.rs-10646209/v1, 10.2139/ssrn.7203631]. Red-team and audit reports show that apparently secure tool-assisted pipelines can be manipulated by adversarially crafted tool definitions or chained actions, producing dangerous configuration changes even when individual components seem benign. These findings imply that GVR effectiveness depends not only on validator logic but on the larger tool and agent context in which repair prompts and validator outputs are framed.

Evaluation gaps and the external-validation problem. Recent meta-analyses and reviews emphasize a recurring external-evaluation gap: many NetOps prototypes and LLM evaluations use synthetic or narrowly curated tasks and do not measure how validator-detected safety maps to real end-to-end risk across vendor devices, multi-vendor behaviors, or adversarial inputs [https://openalex.org/W4411523078, https://openalex.org/W4411735779]. That gap motivates three experimental priorities: (1) instrumented paired studies that fix generator sampling to isolate validator/repair effects, (2) inclusion of emulator or real-device holdouts to detect validator blind spots, and (3) reporting of repair budgets and model-call costs so practitioners can assess operational tradeoffs.

Prompt sensitivity, sampling semantics, and experimental design implications. Empirical work on prompt sensitivity and generation non-determinism shows that sampling policy (temperature, number of samples) and prompt templates materially affect observed correctness rates and the opportunities available to a repair loop [https://openalex.org/W4402860127]. Consequently, a paired shared-initial design—where the same initial candidate is reused across baseline and guarded arms—removes sampling variance and isolates the marginal effect of validation+repair on a fixed generator output. This design choice trades generality for controlled inference and is appropriate when the research question targets the marginal utility of repair for fixed generator behavior.

Synthesis and positioning. The prior work corpus collectively supports GVR as a promising architectural pattern but leaves unresolved empirical questions about when deterministic repair provides measurable operational benefit versus when efforts should focus on improving validator fidelity, diversifying generator sampling, or hardening agents against tool-description attacks. Our preregistered paired study was designed to address this specific empirical gap by fixing generator outputs (shared-initial semantics), enforcing a single-repair budget, and instrumenting a randomized emulator holdout as a contamination detector; the study therefore complements prior prototype and audit work by producing an externally auditable, artifact-grounded datum about GVR’s marginal effect under a constrained but clearly specified operational regime.

III. METHODOLOGY

Preregistration and inferential plan. We froze the experimental plan under preregistration id

cnsms2026-gvr-effectiveness-02 before any model calls. The confirmatory design was paired and deterministic: $n = 200$ tasks (four topology clusters $\times$ 50 tasks), one shared deterministic initial LLM generation per task, and a repair budget of at most one automated repair call per task. The primary estimand was the `paired_success_rate_difference_guarded_minus_baseline` and the prespecified test was an exact two-sided McNemar test ($\alpha = 0.05$). Confidence intervals for the paired difference were computed by the bootstrap percentile method with 10,000 resamples and `bootstrap_seed = 1729`. The analysis executor was `paired_binary_analysis_v1` as recorded in the analysis artifacts.

Adapter, model, and sampling semantics. The run used a single hosted model declared as `gpt-5-mini` (provider label: `openai_responses`). Model configuration metadata (`execution/model_configuration.json`) records `requested_model = "gpt-5-mini"`, `max_output_tokens = 2000`, `maximum_attempts_per_call = 1`, and `temperature = null` (deterministic sampling enforced by the adapter). Crucially, the `hosted_netops_gvr_v1` adapter enforced `shared_initial` generation semantics: for each task the system generated exactly one initial candidate which was deterministically reused for both the baseline (LLM-only) and guarded (GVR) conditions. This shared-initial design eliminates per-condition sampling variance and isolates the incremental effect of invoking validation and an allowed repair step on the identical generator output. Adapter accounting in `deterministic_reconciliation.json` documents `hosted_model_call_event_count = 200`, `stage_counts = {shared_initial_generation: 200}`, and `model_calls_used = 200`, confirming the enforced single shared invocation per task and that no separate condition-specific sampling occurred.

Task bank, validators, and holdout emulator. The task bank is a curated, machine-checkable intent→configuration set (200 tasks) in which each task encodes initial and expected final states plus workflow policies (e.g., `make_before_break_uplink_switchover`, `must_be_down_for_fields`). The primary deterministic checker (`deterministic_netops_validator_v5`, `validator_version = "5.0"`) runs syntactic parsing, intent/constraint enforcement, and structured diagnostics (fields available in validator traces include `valid_flag`, `violation_count`, `violation_codes`, `parsed_command_count`, `required_command_count`, and difficulty annotations). A Mininet-based data-plane emulator was preregistered as a secondary disagreement detector applied to a randomized 10% holdout (20 tasks) to detect validator–emulator mismatches; the executed `contamination_summary` artifact reports zero disagreement flags for that holdout. The preregistration specified deterministic treatment rules: pairs flagged for validator–emulator disagreement would be excluded from the primary analysis per the `contamination_plan`; sensitivity analyses for alternative treatments were preregistered but not invoked because no flags occurred.

Repair policy, budgeting, and missingness handling. Per the preregistration, when the primary validator reported violations

the pipeline was permitted to issue up to one automated repair prompt to the same LLM for that task (maximum repair calls across the sample = 200). Repair prompts, if used, would be captured in `repair_provider_trace` fields in the episode artifacts; none appear in the archived episodes because no repairs were applied. Missingness and exclusion rules were deterministic: pairs where neither condition completed because of infrastructure failures would be excluded and logged; pairs with contamination flags (validator-emulator disagreement) would be excluded from the primary confirmatory test. The execution manifest and missingness_summary show `complete_pair_count` = 200 and zero failed episodes, so the planned missingness handling was not invoked in practice.

Execution accounting and artifact capture. The autonomous run executed between 2026-08-30T11:50:34.530059Z and 2026-08-30T12:12:07.541650Z. The adapter enforced the preregistered maximum model calls (`maximum_model_calls` = 400) and per-task caps (initial generation = 1 call; repair calls $\leq$ 1). The run consumed 200 model calls (one shared initial generation per task), with `cache_miss_count` = 200 and `cache_hit_count` = 0 as recorded in the deterministic reconciliation artifacts. All model calls, prompts, raw responses, validator traces, provider traces, and analysis artifacts (`execution/raw_results.jsonl`, `analysis/paired_contingency_table.csv`, `analysis/condition_summary.csv`, `analysis/contamination_summary.csv`, `analysis/analysis_log.jsonl`, `execution/model_configuration.json`) were archived; representative per-task artifacts (e.g., `execution/scoring/task-000001-baseline.json`) show `validator_trace` fields and scoring outcomes. The analysis pipeline executed the exact McNemar test and bootstrap CI generation exactly as preregistered; `analysis/analysis_log.jsonl` records `bootstrap_resamples` = 10000 and `bootstrap_seed` = 1729.

Design rationale and implications for internal validity. The shared_initial paired design was chosen to isolate the pure marginal effect of validation+repair on a fixed generator output; this reduces variance attributable to stochastic sampling and makes the confirmatory test focused on whether repair can convert a validator-failing candidate into a validator-passing one for the same initial output. The trade-off is explicit: the design sacrifices generality across multiple independent generator draws for stronger internal control. Preregistration, deterministic adapter semantics, and frozen stopping rules were used to avoid post-hoc analytic choices. Deterministic reconciliation artifacts confirm `pair_accounting_consistent` = true and `all_deterministic_consistency_checks_passed` = true.

Limitations baked into the methodology. The methodology intentionally restricts scope: a single model, a deterministic prompt/sampling policy, a one-repair budget, and a curated task bank. These constraints reflect an explicit confirmatory question about marginal GVR effect under a tightly controlled generator policy rather than an evaluation of alternative sampling, multi-step repair strategies, or cross-model generality. When interpreting outcomes, readers should account for these preregistered methodological choices documented in the

archived plan.

IV. RESULTS

Execution outcomes. The run completed all planned episodes: `completed_episode_count` = 400 (shared initial generation reused across conditions) and `complete_pair_count` = 200. Adapter accounting shows `model_calls_used` = 200 (one shared initial generation per task) and `cache_miss_count` = 200. No repair calls were issued because every initial candidate passed `deterministic_netops_validator_v5`. Condition summaries (`analysis/condition_summary.csv`) show baseline successes = 200/200 and guarded successes = 200/200 (`success_rate` = 1.0 for both). The paired contingency (`analysis/paired_contingency_table.csv`) is `n11` = 200, `n10` = 0, `n01` = 0, `n00` = 0.

Primary inferential analysis. With zero discordant pairs the observed paired difference estimate = 0.0. The exact McNemar two-sided p = 1.0. The bootstrap percentile 95% CI (10,000 resamples; seed = 1729) is [0.0, 0.0]. Under the preregistered estimand and test the prespecified $\geq 50\%$ relative-reduction hypothesis is logically untestable on this sample because there were no baseline validator failures to reduce.

Representative diagnostics. Representative per-task artifacts (for example, `pair-000001`) confirm that the shared initial generator outputs matched the task required_sequence and that `validator_trace.validation_after.valid` = true with `violation_count` = 0. Difficulty annotations in validator traces (examples: `make_before_break_uplink_switchover`, `paired_link_atomic_mtu_change`) and `parsed_command_count/required_command_count` show that tasks exercised medium-to-very_hard workflow constraints despite generating validator-satisfying candidates. The Mininet 10% holdout (20 tasks) executed as preregistered; `analysis/contamination_summary.csv` reports zero validator-emulator disagreements, and deterministic reconciliation artifacts report all consistency checks passed (`pair_accounting_consistent` = true).

Unexecuted branches. Planned sensitivity branches for flagged contamination treatments and alternative missingness handling were not invoked because no tasks were flagged and no episodes failed. Secondary exploratory estimands (average repair iterations, GVR-introduced failure rate, model-call cost per successful repair) are empty in the analysis bundle because no repair attempts occurred; the analysis artifacts record these `secondary_results` as empty.

V. DISCUSSION

Conditional interpretation. The degenerate null outcome demonstrates a logical constraint: when the chosen generator, prompt template, and sampling policy produce validator-passing candidates for every item in a workload, an added validator-coupled repair step cannot reduce validator-detected failures. This artifact-grounded observation clarifies that GVR's marginal utility is a function of baseline validator failure prevalence and validator coverage rather than a universally guaranteed safety gain.

Task and prompt alignment. Archived validator traces and representative task artifacts show that tasks encoded explicit required sequences and workflow constraints, and that the deterministic prompts and adapter-enforced shared-initial semantics produced outputs conforming to those constraints. Because the task bank was curated with machine-checkable intent representations, the generator had a narrow, high-signal mapping from intent to commanded sequence—reducing semantic ambiguity and making validator-passing outputs more likely. Difficulty annotations (e.g., patterns labeled `make_before_break_uplink_switchover` or `paired_link_atomic_mtu_change`) indicate that the workload exercised nontrivial coordination constraints; the absence of validator failures therefore reflects alignment between task formalization, prompt semantics, and validator checks rather than trivial task simplicity.

Validator fidelity and emulator coverage. Deterministic `netops_validator_v5` enforces a defined set of syntactic and intent constraints; the preregistered Mininet secondary check (10% holdout = 20 tasks; see `analysis/contamination_summary.csv`) executed and reported zero disagreements, supporting the internal consistency of validator verdicts on the sampled holdout. Nevertheless, the limited scope of the holdout and the disclosed absence of an explicit labeled seed for holdout selection constrain claims about broader emulator coverage: the artifact bundle shows no validator–emulator mismatches for the tested subset, but this does not prove absence of validator blind spots across all production conditions. Practitioners should therefore treat validator pass rates as conditional on validator completeness and the representativeness of any emulation checks used to validate that completeness.

Design choices that shaped outcomes. The preregistered `shared_initial` paired design intentionally removes per-condition resampling as a lever to create discordant cases; it isolates the incremental effect of invoking a repair step on a fixed generator output. That controlled isolation is scientifically valuable for measuring the marginal effect of repair on the exact same candidate, but it also reduces the experimental pathways by which GVR could yield observed improvements in a different design (for example, multi-sample generation where a repair step might solicit alternative formulations). Similarly, the single-model, deterministic sampling policy reduces stochastic variance but limits generality: different sampling temperatures, multi-sample strategies, or model ensembles may produce nonzero baseline failure rates and thus different measured GVR benefits.

Implications for operational design and future studies. The empirical datum—zero baseline validator failures under these controlled, curated conditions—suggests concrete operational guidance: teams considering automated repair should first instrument representative workloads to measure baseline validator failure prevalence and then evaluate validator completeness via targeted emulation or real-device checks. If baseline validator failures are rare under the planned generator/prompt policy, investments that raise validator fidelity (vendor-specific

behavior models, richer device semantics) or that increase input diversity (adversarial testing, multi-sample generation, multi-model ensembles) may provide greater marginal safety returns than adding an automated repair stage with a small repair budget. Conversely, when baseline failures are nontrivial, a well-engineered GVR pipeline with adequate repair budget and high-quality repair prompts can reduce validator-detected issues; future experiments should measure repair iterations and model-call cost per successful repair when such failures are present.

Recommended experimental refinements. To quantify GVR effectiveness in settings where it can act, future confirmatory runs should (a) target task banks or prompt variants with nonzero baseline validator failures (for example, by introducing realistic ambiguity or controlled perturbations), (b) evaluate multi-sample generation and multi-model ensembles as baselines, (c) increase repair budgets and test multi-step repair strategies including human-in-the-loop handoff, and (d) expand emulator or real-device coverage and record explicit, reproducible holdout selection seeds so that contamination checks are fully reconstructable. The archived artifacts show that `secondary_results` were empty because no repairs occurred; capturing repair-cost and iteration metrics requires a design where repairs are invoked in practice.

Threats to validity revisited. Construct validity: validator pass/fail outcomes reflect the formalized constraints encoded in `deterministic_netops_validator_v5`; absent richer device modeling, some operationally relevant failures may not be detected. External validity: a single hosted model (`gpt-5-mini`), deterministic sampling, `shared_initial` semantics, and a curated task bank constrain generalizability. Internal validity: pre-registration and deterministic adapter enforcement strengthen causal interpretation in the paired comparison, but the controlled choices also narrow the space of behaviors observed. Reproducibility: the execution bundle archives model calls, validator traces, and the contamination summary showing zero Mininet disagreements, but the missing labeled Mininet holdout seed prevents deterministic reconstruction of the exact holdout sample—this gap is disclosed in the Disclosure Statement.

Concluding synthesis. The completed artifacts and diagnostic traces make clear that the preregistered GVR pipeline, as instantiated here, produced no measurable reduction in validator-detected failures because there were no such failures to reduce. That operationally informative null result highlights that the safety value of automated repair is not universal but workload- and validator-dependent. Future work should deliberately select or construct workloads with nontrivial baseline failure rates and expand validator fidelity and sampling strategies to empirically quantify when GVR provides practical safety gains.

VI. LIMITATIONS

- Task-bank scope: the confirmatory sample used a curated synthetic/public intent→configuration bank ($n = 200$); re-

sults therefore reflect this bank and may not generalize to broader production workloads or adversarial distributions.

- Single-model and shared-initial setting: only gpt-5-mini (hosted) with adapter-enforced shared-initial generation was tested (execution artifacts record `hosted_model_call_event_count = 200` and `stage_counts shared_initial_generation = 200`). Outcomes may differ across model families, independent per-condition sampling, nonzero temperature sampling, or larger repair budgets.
- Validator coverage and oracle limitations: the primary deterministic validator enforces a defined set of syntax/intent constraints; validators can fail to capture real device idiosyncrasies, vendor-specific behaviors, or emergent failure modes detectable only by end-to-end deployment.
- Adversarial robustness untested: this confirmatory run did not include active adversarial injection or red-team tool-description attacks; prior audits indicate such vectors can bypass naive defenses and remain a separate concern.
- Reproducibility gap for contamination check: the randomized holdout selection seed for the Mininet contamination check is absent from the labeled artifacts, preventing exact reconstruction of the holdout selection.
- Single repair budget: the GVR pipeline allowed at most one automated repair prompt per task; multi-step repair strategies, different repair budgets, or human-in-the-loop approvals were not exercised here.

VII. CONCLUSION

We preregistered and executed a sealed paired study comparing LLM-only generation to a deterministic GVR pipeline on 200 NetOps intent→configuration tasks using gpt-5-mini and `deterministic_netops_validator_v5`. Both pipelines produced validator-passing configurations for every task ($n_{11} = 200$; no discordant pairs), resulting in an observed paired difference of 0.0, exact McNemar $p = 1.0$, and bootstrap 95% CI = [0.0, 0.0]. The preregistered $\geq 50\%$ relative-reduction hypothesis could not be evaluated because baseline validator failures were absent. The artifact-grounded outcome clarifies that GVR’s marginal value is workload dependent: when baseline validator-detectable failures are rare, automated repair yields no measured benefit for those validator-detected errors. Future studies should target workloads with nontrivial baseline failure rates, expand validator fidelity with richer emulation or real-device checks, evaluate multi-sample and multi-model policies, and explore multi-step or human-in-the-loop repair budgets to characterize practical operational gains. All execution artifacts and analysis outputs are archived for independent inspection under the preregistration id cited above.

DISCLOSURE STATEMENT

Disclosure (mandatory). This study executed under the autonomous post-lock preregistration `cnsms2026-gvr-effectiveness-02`. Declared model: gpt-5-mini (provider label: `openai_responses`) invoked via the

`hosted_netops_gvr_v1` adapter. The exact initial master prompt is archived at `provenance/master_prompt.txt` (SHA-256: 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15ba). Topic constraints: the human Research Director limited the study to Generative AI and LLMs for NetOps focusing on safety/reliability of generated network changes. Frameworks and tools: orchestration used `hosted_netops_gvr_v1` and the deterministic task generator `deterministic_netops_task_generator_v5`. Primary deterministic validator: `deterministic_netops_validator_v5` (intent/constraint checks). A Mininet-based emulator was preregistered and executed as a secondary disagreement detector on a randomized 10% holdout (20 tasks); the artifact analysis/contamination_summary.csv shows zero disagreements for that holdout. Preregistration and freeze: the experimental plan (estimand, sample size $n = 200$, paired design, stopping rules, max model calls = 400, repair budget = 1 per task, shared-initial generation semantics) was frozen before any model calls. Autonomous execution and artifacts: the run executed autonomously under the frozen plan (start: 2026-08-30T11:50:34.530059Z; end: 2026-08-30T12:07:54.1650Z); model calls, prompts, seeds, validator traces, emulator traces, logs, and the artifact manifest are archived in the execution bundle. Model-call budget and usage: 200 model calls were used (one shared initial generation per task); up to 200 repair calls were allowed but none were applied because initial candidates passed the validator. Human involvement: the human Research Director selected the topic family and pre-lock constraints; no human manual editing or selective rewriting of technical manuscript content occurred after the autonomy lock. Deviations and restarts: no post-preregistration design changes or technical restarts occurred. Known reproducibility gap: the explicit randomized selection seed used to draw the Mininet 10% holdout is not present as a labeled artifact in the archive; this absence prevents exact deterministic reconstruction of the drawn holdout despite the contamination summary reporting no disagreements. The master prompt archive reference above is the immutable prompt required by the track.

REFERENCES

- [1] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Zican Dong, Yupeng Hou, Beichen Zhang, Yingqian Min, Junjie Zhang, Peiyu Liu, Xiaolei Wang, Yifan Du, Yushuo Chen, Yushuo Chen, Zhipeng Chen, Jinhao Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Peiyu Liu, Yiwen Hu, Jian-Yun Nie, Ji-Rong Wen, "A Survey of Large Language Models", 2026, 10.1007/s11704-026-60308-3
- [2] Changjie Wang, Mariano Scazzariello, Alireza Farshin, Simone Ferlin, Dejan Kostić, Marco Chiesa, "NetConfEval: Can LLMs Facilitate Network Configuration?", 2024, 10.1145/3656296
- [3] Oscar G. Lira, Oscar Mauricio Caicedo Rendón, Nelson L. S. da Fonseca, "Large Language Models for Zero Touch Network Configuration Management", 2024, 10.1109/mcom.001.2400368
- [4] Chirag Shah, Ryen W. White, Reid Andersen, Georg Buscher, Scott Counts, Sarkar Snigdha Sarathi Das, Ali MontazerAlghaem, Sathish Manivannan, J. Neville, Nagu Rangan, Tara Safavi, Siddharth Suri, Mengting Wan, Leijie Wang, Longqi Yang, "Using Large Language Models to Generate, Validate, and Apply User Intent Taxonomies", 2025, 10.1145/3732294

- [5] omar altawil, Dr. Mustafa Al-Fayoumi, "Configuration-Level Semantic Brittleness in Tool-Using LLM Agents: A Factor-Ranking Study of Persona, History, and Tool Definition", 2026, 10.2139/ssrn.7203631
- [6] Mohammadreza Rashidi, "Measuring How LLM Tool Descriptions, Cross-Tool Ambiguity, and Action Chains Compose into Excessive Agency Exploits", 2026, 10.21203/rs.3.rs-10646209/v1
- [7] Yoshihiro Ando, "Secure-by-Default Guardrails for MCP-Based Tool Use in Multi-Modal LLM Agents", 2026, 10.36227/techrxiv.177006109.97957916/v1
- [8] Sebastian Farquhar, Jannik Kossen, Lorenz Kuhn, Yarin Gal, "Detecting hallucinations in large language models using semantic entropy", 2024, 10.1038/s41586-024-07421-0
- [9] Shuyin Ouyang, Jie M. Zhang, Mark Harman, Meng Wang, "An Empirical Study of the Non-Determinism of ChatGPT in Code Generation", 2024, 10.1145/3697010
- [10] Oghenekeno Hilkhiah Okula, ""The Era of AI Agents for Network Engineering": Intent-Aware Auto Remediation for Network Disruption or Failures Using AI Agents, Large Language Models (LLM) and Model Context Protocol (MCP) Mechanisms", 2026, 10.36227/techrxiv.177004277.71795055/v1