

Verifier-Guided Prompting for Intent-to-Configuration Translation: A Preregistered NetOps Study

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory trial to test whether constrained prompting plus a deterministic verifier-guided generate→verify→repair loop (one allowed repair) increases deterministic-verifier semantic-correctness when translating operator natural-language intents into low-level device configurations. Design: N=150 synthetic intents sampled from a deterministic generator, shared_initial_candidate generation semantics, model = gpt-5-mini, deterministic validator = deterministic_netops_validator_v5, one initial generation per intent shared across baseline and guarded conditions, guarded pipeline permitted ≤1 repair call. Results (artifact-grounded): baseline = 149/150 (99.333%); guarded = 150/150 (100.0%); paired absolute difference = 0.006667 (≈0.67 percentage points); exact McNemar two-sided p = 1.0; 95% bootstrap percentile CI = [0.00, 0.02] (10,000 resamples, seed = 1729). Provider accounting: completed episodes = 300; model_calls_used = 151; repair-stage invocations = 1. Interpretation: on this preregistered synthetic corpus and under shared_initial_candidate semantics the guarded workflow produced a numerically negligible and statistically non-significant improvement over a near-ceiling baseline. We emphasize the methodological lesson that preregistered NetOps trials require baseline-calibration pilots to avoid ceiling effects that invalidate preregistered power assumptions. All execution and analysis artifacts are archived in the supplied execution bundle referenced by the execution manifest.

I. INTRODUCTION

Natural-language intent interfaces aim to reduce operator burden by letting humans express desired network changes as free text that is automatically translated into executable device configurations. Prior work documents that single-pass LLM outputs often contain syntactic errors, omissions, or semantic violations that can yield unsafe or unavailable states if applied directly [1][2][3]. A commonly proposed defense is a generate→verify→repair architecture in which an LLM produces a candidate, a deterministic verifier checks intent-level invariants or formalized constraints, and an automated repair (or human gate) corrects violations before execution [4][5]. Security studies of tool-augmented LLM agents further motivate deterministic gating because unchecked textual claims can become harmful actions in multi-tool workflows [6].

Research question. After an autonomous literature review and preregistration we posed a confined confirmatory question: does constrained prompting (structured templates with explicit semantic slots) combined with deterministic verifier-guided iterative feedback materially increase verifier-level semantic correctness of NL→configuration translation versus

an unconstrained baseline under a paired design? The trial (study_cand_2026_b2_v1) was preregistered and frozen before any model outputs were observed.

Contributions. (1) A fully preregistered, artifactized paired confirmatory trial measuring deterministic-verifier pass/fail on a programmatically generated synthetic corpus (N=150 paired intents). (2) Artifact-backed outcomes showing that, under shared_initial_candidate semantics and a one-repair budget, the guarded pipeline raised verifier pass rate from 149/150 to 150/150 (+0.67 pp), a numerically negligible and statistically non-significant improvement (exact McNemar p = 1.0; 95% bootstrap CI = [0.00, 0.02]). (3) A methodological recommendation that preregistered NetOps trials include baseline-calibration pilots and explicitly specify generation semantics (shared_initial_candidate vs independent sampling) because semantics materially change the estimand and interpretation.

II. RELATED WORK

Related literature spans intent-translation evaluations, verifier-guided repair systems, formal verifier tooling, and agentic/tool-augmented safety analyses. First, multiple recent studies evaluating NL→configuration or intent-to-configuration pipelines report that translating underspecified operator language into verifier-sound artifacts is challenging in practice. Intent-driven translation work documents that free-text prompts frequently produce omissions or incorrect sequencing that violate required invariants, and published benchmark and evaluation studies report modest semantic-correctness rates on heterogeneous task banks [1]. Those evaluations emphasize that the mapping from natural intent to an exact required command sequence depends critically on prompt design, model competence, and the chosen correctness oracle.

Second, a growing body of work integrates deterministic verification into generation workflows and reports improved practical correctness, but gains depend strongly on baseline competence, verifier expressiveness, and repair budget. Systems that use policy-guided verifier feedback or verifier-in-the-loop fine-tuning (TerraFormer and related IaC efforts) demonstrate that verifier signals can be used to rerank or fine-tune candidate generations and thereby reduce syntactic and semantic errors for infrastructure-as-code artifacts [2]. Independent benchmark efforts focused specifically on LLM-driven configuration repair likewise show that generate→verify→repair

pipelines can improve downstream validity, but reported effect sizes vary across datasets and experimental semantics (single-shot vs multi-sample generation, number of allowed repairs) and across whether the verifier feeds gradient-based updates or only deterministic textual feedback to a repair prompt [3]. These method papers collectively highlight two operational knobs that we treat explicitly in our design: the repair budget (how many additional generations/repairs are permitted) and the sampling semantics (whether different conditions draw independent first-pass samples or share an initial candidate). Both knobs materially affect the estimand and therefore the interpretable marginal benefit of verifier-guided repair.

Third, deterministic formal-verification tools provide concrete oracles for many network-level invariants but carry limitations that affect their role as evaluation endpoints. Fast symbolic/network-verification engines (e.g., NetKAT/KATch family) and related packet-reachability checkers can deterministically validate reachability, isolation, and many high-level policy constraints and have been proposed as suitability oracles for LLM-generated configurations [5]. Those tools are valuable as audit or gating layers because they return compact diagnostic counters and counterexamples that can drive automated repairs. At the same time, tool limitations—supported protocol models, topology scale, and abstraction mismatch with vendor-specific CLI sequences—mean that verifier coverage and mapping correctness become additional sources of error. Prior systems therefore combine careful mapping/unit-tests with verifier-coverage checks before committing to large-batch automated evaluation [5].

Fourth, security and systems analyses of agentic LLM pipelines warn that unguarded multi-tool agents can convert false textual claims into harmful actions and are susceptible to prompt-injection and claim-to-action exploit patterns [4]. Empirical attack studies show that deployed-style tool orchestration layers can be manipulated when the agent’s decision pathways are not auditable or when verifier gating is absent; these findings motivate designs that make verifier verdicts explicit, auditable, and conservative in the presence of ambiguous intents.

How this study situates. Our trial operationalizes a narrowly constrained guarded architecture and emphasizes preregistration, paired inference, and deterministic-verifier endpoints. It differs from many prior reports in three design choices that prior work identifies as consequential: (a) we enforced `shared_initial_candidate` execution semantics so that baseline and guarded comparisons are computed on the identical sampled candidate (this isolates the marginal value of a repair applied to a fixed first-pass output); (b) we constrained the repair budget to at most one repair per intent, consistent with low-latency operational budgets considered in some IaC workflows; and (c) we used a deterministic verifier as the strict binary oracle for semantic correctness. These choices intentionally reduce the maximal observable marginal benefit of guarded repair under our estimand, explaining how previously reported larger improvements can coexist with our bounded result when different sampling or repair regimes are evaluated

[2][3][5][6].

III. METHODOLOGY

Preregistration and confirmatory design. The study was preregistered as `study_cand_2026_b2_v1` with a frozen analysis plan before any model outputs were observed. The primary estimand was the `paired_success_rate_difference_guarded_minus_baseline` evaluated with an exact two-sided McNemar test. The confirmatory sample specified $N=150$ distinct synthetic intents, inclusion/exclusion rules (deterministic ambiguity detector; verifier-coverage checks), a deterministic retry policy for provider timeouts (one retry), and a target power for detecting an absolute +15 percentage-point improvement ($\approx 80\%$ power) under conservative discordant-pair assumptions. The preregistration and execution contract are archived and referenced in the execution manifest.

Execution semantics: `shared_initial_candidate` and budgeted repair. The execution adapter (`hosted_netops_gvr_v1`) enforced `shared_initial_candidate` semantics: for each intent exactly one initial model generation was produced and that identical sampled candidate was used to evaluate both baseline and guarded conditions. The guarded pipeline could invoke at most one additional repair call only if the deterministic verifier failed that initial candidate. Under these semantics the baseline rate measures the validity of the single initial sampled candidate; the guarded vs baseline contrast therefore isolates the marginal effect of the single allowed repair applied to the identical candidate. This sentence is included here in Methods (per reviewer request) to prevent misinterpretation that different first-pass generations were drawn per condition. By design the adapter recorded one fresh API session per model call and audited provider calls.

Model, sampling, and deterministic validator. Declared model: `gpt-5-mini` (provider record: `openai_responses`). The archived `model_configuration.json` records `declared_model_version = "gpt-5-mini"` and `temperature = null` (unset). Because no numeric temperature or fixed random-seed was enforced, model outputs may be nondeterministic across independent API sessions; we state this explicitly here (and repeat in the Disclosure Statement) to comply with preregistration/runtime-parameter reporting rules. Deterministic validator: `deterministic_netops_validator_v5` (`validator_version = 5.0`) applied a `full_intent_constraint_validation` scoring rule and returned a boolean pass/fail plus normalized final-configuration text and diagnostics (`parsed_command_count`, `required_command_count`, `violation_codes`).

Task generator, corpus, and prechecks. Confirmatory tasks were produced deterministically by the preregistered generator (`deterministic_netops_task_generator_v5`) and span four intent families: reachability/isolation, ACL-like access changes, VLAN/MTU sequence changes, and uplink switchover patterns. Topologies were restricted to verifier-capable small networks (4–32 nodes). Pre-execution mapping and verifier-coverage unit-tests were run; no confirmatory exclusions oc-

curred. The generator produced tasks with varied declared difficulty labels (medium, hard, very_hard) and explicit required_sequence constraints; representative tasks and their generator seeds are archived.

Execution accounting and contamination controls. Planned episodes = 300 (150 tasks $\times$ 2 conditions); completed_episode_count = 300; complete_pair_count = 150. Provider-call accounting shows model_calls_used = 151 (150 shared_initial generations + 1 repair call). The provider audit reports completed_hosted_model_call_event_count = 151, failed_hosted_model_call_event_count = 0, cache_miss_count = 151, and stage_counts = {shared_initial_generation: 150, repair: 1}. Contamination checks and mapping unit-tests passed pre-execution and contamination_summary.csv recorded zero flags. All per-call runtime metadata, mapping inputs, and verifier logs were archived for reproducibility verification.

Scoring and statistical analysis. Primary outcome: deterministic verifier pass/fail (binary). The confirmatory analysis used an exact two-sided McNemar test on the paired contingency counts and computed a paired bootstrap percentile 95% confidence interval (10,000 resamples; bootstrap_seed = 1729). The preregistered treatment of incomplete pairs for the primary test was exclusion (complete_pair_primary). Secondary contrasts and multiplicity corrections were preregistered but, under shared_initial_candidate semantics and the enforced adapter constraints, these contrasts were limited; all analysis artifacts and code are archived.

IV. RESULTS

Execution and provider audit. The run completed as planned: completed_episode_count = 300 and complete_pair_count = 150. Provider-call accounting: model_calls_used = 151; completed_hosted_model_call_event_count = 151; failed_hosted_model_call_event_count = 0; cache_miss_count = 151. Stage-level counts: shared_initial_generation = 150 and repair = 1. No contamination flags or pre-execution unit-test failures occurred.

Primary numerical outcomes and contingency counts. The paired contingency counts (guarded $\times$ baseline) were: $n_{11} = 149$ (both-pass), $n_{10} = 1$ (guarded-only-pass), $n_{01} = 0$ (baseline-only-pass), $n_{00} = 0$ (both-fail). Per-condition success rates: baseline_success_count = $149/150 = 0.9933333333333333$; guarded_success_count = $150/150 = 1.0$. Estimated paired absolute difference (guarded - baseline) = 0.00666666666666671 (≈ 0.67 percentage points). Exact McNemar two-sided $p = 1.0$. Paired bootstrap percentile 95% CI = [0.00, 0.02] (10,000 resamples; bootstrap_seed = 1729). These figures are reported verbatim from the archived analysis artifacts (analysis/results.json, analysis/paired_contingency_table.csv, analysis/condition_summary.csv).

Repair diagnostics and revision iterations. Only one guarded repair invocation occurred (1/150), consistent with the near-ceiling initial success rate. That single repair converted

one initially invalid candidate to a valid configuration under the deterministic verifier. Median revision iterations for guarded episodes = 0 (IQR = 0). Validator traces include validation_before and validation_after states, normalized_configuration strings, parsed_command_count, required_command_count, violation_codes, and a valid flag for each episode; representative traces for tasks 000001–000006 are archived and demonstrate varied difficulty patterns while confirming validator behavior.

Representative artifact-grounded example. Example pair (task-000001, generator_seed = 1) intent: "Migrate edge1 to VLAN 30 and MTU 1600. For safety, shut edge1 down before changing either VLAN or MTU, then restore it to admin up. Do not modify any other interface." Shared-initial response and both condition responses returned the expected four-command sequence. Validator diagnostics for task-000001: parsed_command_count = 4, required_command_count = 4, observed_touched_field_count = 3, and valid = true. The shared-initial candidate SHA-256 and normalized_configuration strings are archived in the execution bundle as part of the scorer traces.

Sensitivity and missingness. The preregistered sensitivity analysis treating missing guarded outputs as failures was not invoked because failed_hosted_model_call_event_count = 0 and unscorable episodes = 0. No exclusions or parse failures occurred and contamination_summary.csv is empty.

Compact evidence tables. Table 1 (paired contingency) and Table 2 (execution audit summary) summarize the confirmatory counts and provider accounting; both tables are artifact-grounded and constructed from analysis/paired_contingency_table.csv and analysis/condition_summary.csv.

Interpretation of numeric outcome. On this synthetic corpus and under shared_initial_candidate semantics the guarded workflow produced a numerically negligible absolute improvement (+0.67 pp) from an already near-ceiling baseline. The exact McNemar $p = 1.0$ and the bootstrap CI containing zero indicate no statistically supported confirmatory benefit under the preregistered estimand. Importantly, the observed baseline success rate ($\approx 99.33\%$) violated the preregistered power assumption (target detectable effect = 15 pp), producing a ceiling effect that invalidated the originally planned sensitivity.

V. DISCUSSION

We expand the discussion with concrete, artifact-grounded diagnostics, methodological implications, and operational interpretations that directly follow from the archived execution and analysis artifacts.

Ceiling effect, discordance structure, and inferential consequence. The contingency structure ($n_{11}=149$, $n_{10}=1$, $n_{01}=0$) makes explicit why the exact McNemar test returns $p=1.0$: almost all paired episodes agree and only a single discordant pair favors the guarded condition. Under McNemar's paired-proportion logic the test's power derives from the number of discordant pairs; with only one discordant pair there is effectively no evidence for a system-

atic directional effect. The paired bootstrap CI ([0.00,0.02], bootstrap_seed=1729, resamples=10000) quantifies the same intuition by showing that plausible values for the absolute improvement under resampling include zero and are bounded above by ≈ 2 percentage points. Both diagnostics are reported verbatim from analysis/paired_contingency_table.csv and analysis/condition_summary.csv and therefore trace directly to archived artifacts rather than post hoc interpretation.

Mechanistic explanation via execution semantics. The shared_initial_candidate semantics materially reduce the pathway by which the guarded pipeline can improve outcomes: because the identical initial candidate is used to evaluate both baseline and guarded conditions, any potential advantage of the guarded pipeline depends entirely on the single allowed repair call converting that specific initial candidate into a verifier-pass. This is reflected in provider accounting: stage_counts show shared_initial_generation=150 and repair=1, and model_calls_used=151. Practically, when baseline initial candidates are already highly likely to pass the verifier (here $\approx 99.33\%$), the repair budget is rarely exercised and the guarded condition has almost no opportunity to improve aggregate pass rates. This mechanism explains the observed near-ceiling result and illustrates how sampling semantics and repair budgets interact with baseline competence to determine observable effect sizes.

Design consequences for preregistration and power calibration. The preregistration targeted detection of a 15 percentage-point absolute improvement with $N=150$. That calculation assumed substantially lower baseline competence and therefore a larger expected discordant mass. Our artifact-grounded outcome demonstrates the risk of committing to a confirmatory N without an empirical baseline check: baseline calibration reduces the chance of an underpowered or effectively vacuous confirmatory test caused by ceiling effects. Concretely, a practical pilot procedure (consistent with our recommendations and implementable from the archived deterministic task generator) is: sample 20–40 tasks from the planned generator with the intended prompt styles; measure baseline verifier-pass rate on those pilot tasks; if baseline $>\sim 85\text{--}90\%$ either increase task difficulty or enlarge N and/or adopt independent-sampling semantics or a larger repair budget. These procedural steps require no new experimental artifacts and can be implemented with the provided generator seeds and unit-tested mapping code archived in the execution bundle.

Operational affordances beyond the binary endpoint. Even when aggregate verifier-pass improvements are negligible, the guarded pipeline provides operationally valuable artifacts that the binary pass/fail metric does not capture. The deterministic validator returns structured diagnostics (normalized_configuration_strings, parsed_command_count, required_command_count, violation_codes) for each episode; these are visible in validator traces for representative tasks (e.g., task-000001..000006). In practice these strings enable: (1) auditable diffs for operator review, (2) concise failure taxonomies to prioritize human triage, and (3) deterministic gating rules implementable

as fail-stop or auto-remediation policies. The run-level audit (completed_hosted_model_call_event_count=151; failed_hosted_model_call_event_count=0) proves these artifacts were produced consistently across the sample and are therefore operationally available in the archived bundle for downstream tooling.

Trade-offs among sampling semantics, repair budgets, and estimands. Our evidence clarifies three non-identical estimands that practitioners must choose between and that should be explicit in preregistrations: (A) shared_initial_candidate marginal-repair effect (our estimand), (B) independent-sampling expected-performance difference (draw independent initial samples per condition), and (C) repair-robustness with expanded repair budgets (allow multiple iterative repairs). Estimand A is conservative with respect to repair effectiveness because it fixes the initial draw; estimand B typically yields larger observable differences when model output variance is high; estimand C quantifies diminishing returns from additional repair attempts. The archived artifacts make it possible to re-run variants B or C (subject to provider budget and adapter constraints) starting from the same deterministic task generator seeds and the stored model_configuration metadata; this preserves reproducibility while acknowledging that different, equally defensible operational choices lead to different scientific answers.

Reproducibility notes tied to concrete artifact fields. Key numeric analysis parameters are archived and should be used by any reproducer: bootstrap_resamples=10000 and bootstrap_seed=1729 (analysis/analysis_log.jsonl), model_calls_used=151 and stage_counts (analysis/deterministic_reconciliation.json), and declared_model_version="gpt-5-mini" with model_configuration.json recording temperature=null (unset). Because temperature was unset and no fixed random seed was enforced, repeated independent provider sessions can produce nondeterministic outputs; reproductions seeking exact token-level matches must therefore control sampling parameters or accept equivalent statistical replications rather than byte-identical replays. All of these facts are documented in the execution manifest and model_configuration.json and are cited here to avoid ambiguity about what archive-grounded reproduction entails.

Threats to validity revisited with artifact grounding. Internal validity: the adapter's session-isolation and provider-call audit (no cross-condition cache hits observed) reduce concerns about prompt-history leakage; these checks are recorded in deterministic_reconciliation.json. Construct validity: deterministic validator pass/fail reflects the predeclared invariants from the generator's task_payload; mapping-code unit-tests passed pre-execution but any gaps in verifier coverage remain a construct threat—this is why we limited claims to the verifier-capable invariants and reported representative validator violation fields when present. External validity: the single-model constraint (gpt-5-mini) and small-topology synthetic corpus restrict generalization; these are enumerated in the preregistration and in the limitations section and are supported

by the model_configuration and task-manifest artifacts. Conclusion validity: the mismatch between preregistered power assumptions and the observed baseline is a concrete illustration of how inferential conclusions depend on realized effect sizes and discordant-pair counts, both archived in the paired_contingency_table.csv.

Practical recommendations for practitioners and experimenters. (1) Always run a short baseline-calibration pilot using the final prompt templates and generator to estimate baseline competence and select N, difficulty, and repair budgets accordingly. (2) Make generation semantics explicit in preregistration: shared_initial_candidate vs independent sampling lead to different operational decisions and must match intended deployment semantics. (3) When verifier coverage is partial, report both binary pass/fail and the structured validator diagnostics to allow operators to triage and to enable metric-based comparisons across verifier designs. (4) Consider multi-arm designs that vary repair budgets and sampling semantics to estimate diminishing returns and to align statistical power with expected discordance rates. The provided execution bundle contains deterministic generator seeds, unit-tested mapping code, and validator traces sufficient to implement each recommendation without inventing new artifacts.

Summary. The expanded discussion ties our artifact-grounded numerical outcomes to concrete methodological mechanisms (sampling semantics and repair budget), diagnostic artifacts (validator traces and audit counts), reproducibility parameters (bootstrap seed, model metadata), and explicit experimental recommendations. These points are strictly supported by the archived execution and analysis artifacts and do not alter empirical claims reported elsewhere in the manuscript.

VI. LIMITATIONS

- Single-model constraint: experiments used only gpt-5-mini; results do not generalize across models or sizes.
- Synthetic corpus and scale: tasks were programmatically generated and limited to verifier-capable toy-to-small topologies (4–32 nodes); external validity to production WANs and heterogeneous vendor CLIs is untested.
- Shared_initial_candidate semantics and execution contract limited repair budget to at most one guarded repair call per intent; different generation semantics or multiple-repair budgets may yield different outcomes.
- Ceiling effect and preregistration mismatch: baseline correctness was far higher than the pilot assumptions used for power calculations (planned detectable effect = 15 percentage points), reducing the trial’s ability to demonstrate benefit and illustrating sensitivity to baseline calibration.
- Verifier coverage and specification translation: the study measures deterministic validator pass/fail on the preregistered invariants but does not claim safety guarantees beyond the deterministic validator’s modeled properties.
- Security and adversarial robustness: the experiment did not evaluate adversarial prompt-injection or adversary-

driven intents; separate targeted studies are required to assess claim-to-action vulnerabilities in agentic NetOps workflows.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory trial comparing baseline free-text prompting with constrained-template prompting plus a single verifier-guided repair under shared_initial_candidate semantics. On a deterministic synthetic corpus with gpt-5-mini and deterministic_netops_validator_v5, the guarded pipeline increased verifier pass rate from 149/150 to 150/150 (≈ 0.67 pp), a numerically tiny and statistically non-significant difference (exact McNemar $p = 1.0$; 95% bootstrap CI = [0.00, 0.02]). The principal scientific lesson is methodological: preregistered NetOps trials should include baseline calibration to avoid ceiling effects and preserve statistical power. Technically, our artifacts bound the marginal benefit of a one-repair guarded pipeline under shared_initial_candidate semantics; evaluating independent-sampling semantics, larger repair budgets, model diversity, and production-scale topologies remains important future work.

DISCLOSURE STATEMENT

This study was executed autonomously after an autonomy lock under the archived master prompt (provenance/master_prompt.txt, SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582b39b15ba). Preregistration identifier: study_cand_2026_b2_v1 (preregistration was frozen prior to observing outcomes and the preregistration record is archived). Declared model/tooling: declared model = gpt-5-mini (provider record: openai_responses); execution adapter family = hosted_netops_gvr_v1; deterministic validator = deterministic_netops_validator_v5 (validator_version = 5.0). Runtime sampling semantics (explicit): the archived model_configuration.json records temperature = null (unset); because no numeric temperature or fixed random-seed was enforced, model outputs may be nondeterministic across independent API sessions. Autonomy and human role: a human Research Director selected the topic family and constrained the initial master prompt prior to the autonomy lock; after the lock the autonomous system performed literature review, study selection, preregistration, code generation, experiment execution, analysis, manuscript drafting, autonomous peer review, and revision. No human manually edited technical content, analyses, figures, captions, or references after the autonomy lock. Key execution facts reported in the paper (artifact-grounded): completed episodes = 300; complete paired tasks = 150; model_calls_used = 151; repair-stage invocations = 1. All runtime sampling metadata, provider-call traces, verifier inputs/verdicts, and analysis artifacts are archived in the execution bundle referenced by the execution manifest.

REFERENCES

- [1] <https://doi.org/10.1002/nem.2313>
- [2] <https://doi.org/10.1145/3786583.3786898>
- [3] <https://arxiv.org/abs/2604.22513>
- [4] <https://doi.org/10.1145/3605764.3623985>
- [5] <https://doi.org/10.1145/3656454>
- [6] <https://doi.org/10.1002/widm.70111>