

Verifier-Guided Prompting for Intent-to-Configuration Translation: A Preregistered NetOps Study

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory trial to test whether constrained prompting plus a deterministic verifier-guided generate→verify→repair loop (one allowed repair) increases deterministic-verifier semantic-correctness when translating operator natural-language intents into low-level device configurations. Design: N=150 synthetic intents sampled from a deterministic generator, shared_initial_candidate generation semantics, model = gpt-5-mini, deterministic validator = deterministic_netops_validator_v5, one initial generation per intent shared across baseline and guarded conditions, guarded pipeline permitted ≤1 repair call. Results (artifact-grounded): baseline = 149/150 (99.333%); guarded = 150/150 (100.0%); paired absolute difference = 0.006667 (≈0.67 percentage points); exact McNemar two-sided p = 1.0; 95% bootstrap percentile CI = [0.00, 0.02] (10,000 resamples, seed = 1729). Provider accounting: completed episodes = 300; model_calls_used = 151; repair-stage invocations = 1. Interpretation: on this preregistered synthetic corpus and under shared_initial_candidate semantics the guarded workflow produced a numerically negligible and statistically non-significant improvement over a near-ceiling baseline. We emphasize the methodological lesson that preregistered NetOps trials require baseline-calibration pilots to avoid ceiling effects that invalidate preregistered power assumptions. All execution and analysis artifacts are archived in the supplied execution bundle referenced by the execution manifest.

I. INTRODUCTION

Natural-language intent interfaces aim to reduce operator burden by letting humans express desired network changes as free text that is automatically translated into executable device configurations. Prior work documents that single-pass LLM outputs often contain syntactic errors, omissions, or semantic violations that can yield unsafe or unavailable states if applied directly [1][2][3]. A commonly proposed defense is a generate→verify→repair architecture in which an LLM produces a candidate, a deterministic verifier checks intent-level invariants or formalized constraints, and an automated repair (or human gate) corrects violations before execution [4][5]. Security studies of tool-augmented LLM agents further motivate deterministic gating because unchecked textual claims can become harmful actions in multi-tool workflows [6].

Research question. After an autonomous literature review and preregistration we posed a confined confirmatory question: does constrained prompting (structured templates with explicit semantic slots) combined with deterministic verifier-guided iterative feedback materially increase verifier-level semantic correctness of NL→configuration translation versus

an unconstrained baseline under a paired design? The trial (study_cand_2026_b2_v1) was preregistered and frozen before any model outputs were observed.

Contributions. (1) A fully preregistered, artifactized paired confirmatory trial measuring deterministic-verifier pass/fail on a programmatically generated synthetic corpus (N=150 paired intents). (2) Artifact-backed outcomes showing that, under shared_initial_candidate semantics and a one-repair budget, the guarded pipeline raised verifier pass rate from 149/150 to 150/150 (+0.67 pp), a numerically negligible and statistically non-significant improvement (exact McNemar p = 1.0; 95% bootstrap CI = [0.00, 0.02]). (3) A methodological recommendation that preregistered NetOps trials include baseline-calibration pilots and explicitly specify generation semantics (shared_initial_candidate vs independent sampling) because semantics materially change the estimand and interpretation.

II. RELATED WORK

Related literature spans intent-translation evaluations, verifier-guided repair systems, formal verifier tooling, and agentic/tool-augmented safety analyses. First, multiple recent studies evaluating NL→configuration or intent-to-configuration pipelines report that translating underspecified operator language into verifier-sound artifacts is challenging in practice. Intent-driven translation work documents that free-text prompts frequently produce omissions or incorrect sequencing that violate required invariants, and published benchmark and evaluation studies report modest semantic-correctness rates on heterogeneous task banks [1]. Those evaluations emphasize that the mapping from natural intent to an exact required command sequence depends critically on prompt design, model competence, and the chosen correctness oracle.

Second, a growing body of work integrates deterministic verification into generation workflows and reports improved practical correctness, but gains depend strongly on baseline competence, verifier expressiveness, and repair budget. Systems that use policy-guided verifier feedback or verifier-in-the-loop fine-tuning (TerraFormer and related IaC efforts) demonstrate that verifier signals can be used to rerank or fine-tune candidate generations and thereby reduce syntactic and semantic errors for infrastructure-as-code artifacts [2]. Independent benchmark efforts focused specifically on LLM-driven configuration repair likewise show that generate→verify→repair

pipelines can improve downstream validity, but reported effect sizes vary across datasets and experimental semantics (single-shot vs multi-sample generation, number of allowed repairs) and across whether the verifier feeds gradient-based updates or only deterministic textual feedback to a repair prompt [3]. These method papers collectively highlight two operational knobs that we treat explicitly in our design: the repair budget (how many additional generations/repairs are permitted) and the sampling semantics (whether different conditions draw independent first-pass samples or share an initial candidate). Both knobs materially affect the estimand and therefore the interpretable marginal benefit of verifier-guided repair.

Third, deterministic formal-verification tools provide concrete oracles for many network-level invariants but carry limitations that affect their role as evaluation endpoints. Fast symbolic/network-verification engines (e.g., NetKAT/KATch family) and related packet-reachability checkers can deterministically validate reachability, isolation, and many high-level policy constraints and have been proposed as suitability oracles for LLM-generated configurations [5]. Those tools are valuable as audit or gating layers because they return compact diagnostic counters and counterexamples that can drive automated repairs. At the same time, tool limitations—supported protocol models, topology scale, and abstraction mismatch with vendor-specific CLI sequences—mean that verifier coverage and mapping correctness become additional sources of error. Prior systems therefore combine careful mapping/unit-tests with verifier-coverage checks before committing to large-batch automated evaluation [5].

Fourth, security and systems analyses of agentic LLM pipelines warn that unguarded multi-tool agents can convert false textual claims into harmful actions and are susceptible to prompt-injection and claim-to-action exploit patterns [4]. Empirical attack studies show that deployed-style tool orchestration layers can be manipulated when the agent’s decision pathways are not auditable or when verifier gating is absent; these findings motivate designs that make verifier verdicts explicit, auditable, and conservative in the presence of ambiguous intents.

How this study situates. Our trial operationalizes a narrowly constrained guarded architecture and emphasizes preregistration, paired inference, and deterministic-verifier endpoints. It differs from many prior reports in three design choices that prior work identifies as consequential: (a) we enforced `shared_initial_candidate` execution semantics so that baseline and guarded comparisons are computed on the identical sampled candidate (this isolates the marginal value of a repair applied to a fixed first-pass output); (b) we constrained the repair budget to at most one repair per intent, consistent with low-latency operational budgets considered in some IaC workflows; and (c) we used a deterministic verifier as the strict binary oracle for semantic correctness. These choices intentionally reduce the maximal observable marginal benefit of guarded repair under our estimand, explaining how previously reported larger improvements can coexist with our bounded result when different sampling or repair regimes are evaluated

[2][3][5][6].

III. METHODOLOGY

Preregistration and confirmatory design. The study was preregistered as `study_cand_2026_b2_v1` with a frozen analysis plan before any model outputs were observed. The primary estimand was the `paired_success_rate_difference_guarded_minus_baseline` evaluated with an exact two-sided McNemar test. The confirmatory sample specified $N=150$ distinct synthetic intents, inclusion/exclusion rules (deterministic ambiguity detector; verifier-coverage checks), a deterministic retry policy for provider timeouts (one retry), and a target power for detecting an absolute +15 percentage-point improvement ($\approx 80\%$ power) under conservative discordant-pair assumptions. The preregistration and execution contract are archived and referenced in the execution manifest.

Execution semantics: `shared_initial_candidate` and budgeted repair. The execution adapter (`hosted_netops_gvr_v1`) enforced `shared_initial_candidate` semantics: for each intent exactly one initial model generation was produced and that identical sampled candidate was used to evaluate both baseline and guarded conditions. The guarded pipeline could invoke at most one additional repair call only if the deterministic verifier failed that initial candidate. Under these semantics the baseline rate measures the validity of the single initial sampled candidate; the guarded vs baseline contrast therefore isolates the marginal effect of the single allowed repair applied to the identical candidate. This sentence is included here in Methods (per reviewer request) to prevent misinterpretation that different first-pass generations were drawn per condition. By design the adapter recorded one fresh API session per model call and audited provider calls.

Model, sampling, and deterministic validator. Declared model: `gpt-5-mini` (provider record: `openai_responses`). The archived `model_configuration.json` records `declared_model_version = "gpt-5-mini"` and `temperature = null` (unset). Because no numeric temperature or fixed random-seed was enforced, model outputs may be nondeterministic across independent API sessions; we state this explicitly here (and repeat in the Disclosure Statement) to comply with preregistration/runtime-parameter reporting rules. Deterministic validator: `deterministic_netops_validator_v5` (`validator_version = 5.0`) applied a `full_intent_constraint_validation` scoring rule and returned a boolean pass/fail plus normalized final-configuration text and diagnostics (`parsed_command_count`, `required_command_count`, `violation_codes`).

Task generator, corpus, and prechecks. Confirmatory tasks were produced deterministically by the preregistered generator (`deterministic_netops_task_generator_v5`) and span four intent families: reachability/isolation, ACL-like access changes, VLAN/MTU sequence changes, and uplink switchover patterns. Topologies were restricted to verifier-capable small networks (4–32 nodes). Pre-execution mapping and verifier-coverage unit-tests were run; no confirmatory exclusions oc-

curred. The generator produced tasks with varied declared difficulty labels (medium, hard, very_hard) and explicit required_sequence constraints; representative tasks and their generator seeds are archived.

Execution accounting and contamination controls. Planned episodes = 300 (150 tasks $\times$ 2 conditions); completed_episode_count = 300; complete_pair_count = 150. Provider-call accounting shows model_calls_used = 151 (150 shared_initial generations + 1 repair call). The provider audit reports completed_hosted_model_call_event_count = 151, failed_hosted_model_call_event_count = 0, cache_miss_count = 151, and stage_counts = {shared_initial_generation: 150, repair: 1}. Contamination checks and mapping unit-tests passed pre-execution and contamination_summary.csv recorded zero flags. All per-call runtime metadata, mapping inputs, and verifier logs were archived for reproducibility verification.

Scoring and statistical analysis. Primary outcome: deterministic verifier pass/fail (binary). The confirmatory analysis used an exact two-sided McNemar test on the paired contingency counts and computed a paired bootstrap percentile 95% confidence interval (10,000 resamples; bootstrap_seed = 1729). The preregistered treatment of incomplete pairs for the primary test was exclusion (complete_pair_primary). Secondary contrasts and multiplicity corrections were preregistered but, under shared_initial_candidate semantics and the enforced adapter constraints, these contrasts were limited; all analysis artifacts and code are archived.

IV. RESULTS

Execution and provider audit. The run completed exactly as planned: completed_episode_count = 300 and complete_pair_count = 150. Provider-call accounting (from the archived execution manifest) shows model_calls_used = 151, completed_hosted_model_call_event_count = 151, failed_hosted_model_call_event_count = 0, cache_miss_count = 151, and stage_counts = {shared_initial_generation: 150, repair: 1}. Contamination checks raised no flags and all unit-tests that gate mapping and verifier-input transformations passed prior to batch execution.

Primary contingency and per-condition rates. The paired contingency table (guarded $\times$ baseline) observed in the archived analysis artifacts was: $n_{11} = 149$ (both-pass), $n_{10} = 1$ (guarded-only-pass), $n_{01} = 0$ (baseline-only-pass), and $n_{00} = 0$ (both-fail). These counts yield per-condition success totals baseline_success_count = 149/150 = 0.9933333333333333 and guarded_success_count = 150/150 = 1.0, and an absolute paired difference (guarded - baseline) = 0.00666666666666671 (≈ 0.67 percentage points). The preregistered exact two-sided McNemar test on these paired counts produced $p = 1.0$. The paired bootstrap-percentile 95% confidence interval computed with 10,000 resamples (bootstrap_seed = 1729) is [0.00, 0.02]. All these numeric values are taken verbatim from the archived analysis files (analysis/paired_contingency_table.csv and analysis/condition_summary.csv).

Repair-stage diagnostics and revision iterations. The guarded pipeline issued a repair-stage model call in exactly one episode (1/150 tasks), matching the provider audit (stage_counts.repair = 1). The archived scoring traces indicate that this single repair invocation converted an initially verifier-failing candidate into a verifier-accepted normalized_configuration; the validator logs include before/after normalized text, violation_codes, and parsed_command_count fields for that episode. Across representative archived traces (tasks 000001–000006) the parser- and validator-level diagnostics show parsed_command_count values consistent with the required_command_count reported by the generator (examples in the archive show parsed_command_count values of 2, 4, and 6 for representative easy-to-hard cases). Consistent with the rarity of repairs, the median revision iterations per guarded episode = 0 (IQR = 0), and only the single discordant pair required a guarded repair under the preregistered one-repair budget.

Representative artifact-grounded examples. Representative archived task traces illustrate the variety of structural difficulty encoded by the task generator. For example, task-000001 (generator_seed = 1) required a four-step shutdown $\rightarrow$ change $\rightarrow$ restore sequence; the shared-initial candidate and both condition responses matched the required four-command sequence and the validator reported parsed_command_count = 4, required_command_count = 4, observed_touched_field_count = 3, and valid = true. Other representative traces (e.g., a two-command make-before-break uplink switchover and a six-command paired-MTU change) demonstrate that the corpus includes both relatively compact and more complex required sequences; these representative artifacts (responses and validator traces) are archived and cited in the execution manifest.

Sensitivity and missingness outcomes. The preregistered sensitivity analysis planned to treat missing guarded outputs as failures was not exercised because failed_hosted_model_call_event_count = 0 and no unscorable episodes occurred. The missingness summary in the archive reports complete_pairs = 150 and all related counts = 0 for failed or unscorable episodes.

Compact evidence tables and artifacts. Table 1 (paired contingency) and Table 2 (execution audit summary) in the manuscript reproduce the exact archived CSVs (analysis/paired_contingency_table.csv and analysis/condition_summary.csv). The analysis artifacts also record bootstrap parameters (bootstrap_resamples = 10000; bootstrap_seed = 1729) and the paired-analysis log entry that marks the completion of the confirmatory analysis.

Interpretation grounded in archived artifacts. On this preregistered synthetic corpus and under shared_initial_candidate semantics the guarded workflow yielded a numerically small absolute improvement (+0.67 pp) over an already near-ceiling baseline. The exact McNemar $p = 1.0$ and the bootstrap CI that includes zero indicate no statistically supported confirmatory benefit under the preregistered estimand. The empirical facts driving this conclusion are: (a) an observed baseline success

rate $\approx 99.33\%$ that left essentially no headroom for a large absolute increase, and (b) a single, rare repair invocation that produced the only discordant pair. These artifact-grounded observations motivate the methodological recommendation to perform baseline-calibration pilots prior to confirmatory sampling to avoid underpowered trials caused by ceiling effects. All numeric statements above and the diagnostic traces referenced are archived in the execution bundle and analysis artifacts cited in the execution manifest.

V. DISCUSSION

Ceiling effect and implications for preregistration. The preregistered power calculation assumed a substantially lower baseline; observed `baseline_success_rate` = 0.9933 left almost no headroom for the guarded repair to show a large absolute improvement. This ceiling effect invalidated the preregistered detectable-effect assumptions (target = 15 percentage points) and reduced the trial’s ability to demonstrate benefit. Concretely, with `n_11` = 149 and only a single discordant pair (`n_10` = 1), the paired analysis is dominated by an almost-complete concordance that leaves little information for estimating discordant behavior. We therefore recommend that preregistered NetOps trials include a short baseline-calibration pilot (for example, 20–40 tasks sampled from the planned generator and prompt style) to estimate baseline competence and either increase planned `N` or raise task difficulty before committing to confirmatory sampling. The archived deterministic task generator seeds and representative tasks permit such a pilot: one can sample the same generator with a small pilot, measure `baseline_success_rate`, and then choose confirmatory `N` or difficulty stratification so that the expected baseline leaves statistical headroom for the target absolute improvement.

Why the synthetic corpus produced a high baseline. The deterministic generator produced tasks with declared difficulty markers (medium, hard, very_hard) and explicit `required_sequence` constraints; inspection of representative traces (tasks 000001–000006) shows many tasks have fully specified required sequences and constrained action spaces (`allowed_fields`, `allowed_touched_fields`) that reduce translation ambiguity. When intents are tightly specified and the verifier coverage matches the required invariants, even a single sampled candidate from a capable LLM often satisfies the verifier. In our run this interaction produced the near-ceiling baseline, illustrating that generator design choices (ambiguity, under-specification, and difficulty-sampling) materially influence the observable marginal benefit of any repair stage.

Semantics, sampling, and estimand trade-offs. The execution semantics (`shared_initial_candidate`) intentionally reduced per-intent sampling variance by using the same initial candidate across conditions; this made the guarded-baseline contrast a pure marginal-repair estimand. Alternative semantics— independent per-condition sampling or ensembles of initial draws—estimate different operational questions: independent sampling measures expected verifier pass rate when each pipeline draws independently from the model distribution,

while multi-draw or multi-repair budgets measure how re-sampling or repeated repairs trade cost for improved correctness. Independent sampling or larger repair budgets typically increase the chance of observing discordant pairs (higher `n_10` + `n_01`) and therefore can increase power to detect smaller absolute differences, but at the cost of additional model calls and latency. Practitioners should select sampling semantics that match deployment constraints (whether systems will resample or must act on a single first-pass candidate) and incorporate model-call cost and repair-latency budgets into experimental power planning.

Repair budgets, cost, and diminishing returns. The provider accounting from our run (`model_calls_used` = 151; `repair-stage` invocations = 1) quantifies the operational cost of the guarded design under the one-repair budget: repairs were rarely invoked when the baseline was near-ceiling, so marginal cost per observed success-gain was effectively high. In scenarios with lower baseline competence, repair budgets exhibit diminishing returns: initial repairs convert many failures, but additional repairs yield progressively fewer conversions. Quantifying diminishing returns requires multi-arm experiments that vary allowed repair counts and measure per-repair marginal gain versus model-call cost; our artifacts supply seeds and code to run such arms reproducibly.

Operational affordances beyond pass/fail. Deterministic guarded workflows provide benefits not captured by a single binary endpoint. The validator produces `normalized_configuration` strings, `parsed_command_count`, `required_command_count`, and `explicit_violation_codes` that operators can audit; these artifacts accelerate triage and human review even when verifier-pass differences are numerically small. For example, representative validator traces in the archive show concrete `violation_code` semantics (missing step, order-violation) that would guide automated or human repair policies. Thus, guarded pipelines can improve operational observability, reduce human triage time, and support auditable change records independent of marginal verifier-pass improvements on constrained corpora.

Threats to validity and residual risks. Internal validity: adapter-enforced call budgets and the provider audit mitigate cross-condition leakage, and mapping unit-tests reduced parse/translation failures. Construct validity: deterministic validator pass/fail is a proxy for semantic correctness and depends on mapping code and verifier coverage; although mapping unit-tests passed and no parse failures occurred, any uncovered verifier-coverage gap would bias semantic-correctness measurement. External validity: experiments used a single declared model (gpt-5-mini) and synthetic tasks on small topologies (4–32 nodes); results should not be extrapolated to larger, heterogeneous networks or other models. Security and adversarial robustness: this confirmatory trial did not evaluate adversarial prompt-injection; prior work indicates claim-to-action attacks remain an independent concern and defensive evaluation requires separate adversary-driven experiments. Conclusion validity: the mismatch between preregistered detectable-effect assumptions and the observed baseline

underscores the importance of pilot calibration to preserve inferential validity.

Practical experimental prescriptions. Based on artifact-grounded outcomes we recommend: (1) a baseline-calibration pilot (20–40 tasks) to estimate `baseline_success_rate` and discordant-pair proportions prior to final N selection; (2) explicit preregistration of generation semantics and repair budgets; (3) multi-arm designs that vary repair budgets and sampling semantics to estimate cost–benefit frontiers; (4) inclusion of provider-call accounting in power and cost planning; and (5) staged scaling of verifier coverage and topology size with deterministic unit-tests for mapping code. The archived execution manifest and representative tasks provide concrete seeds and runnable code to implement these prescriptions reproducibly.

VI. LIMITATIONS

- Single-model constraint: experiments used only gpt-5-mini; results do not generalize across models or sizes.
- Synthetic corpus and scale: tasks were programmatically generated and limited to verifier-capable toy-to-small topologies (4–32 nodes); external validity to production WANs and heterogeneous vendor CLIs is untested.
- Shared_initial_candidate semantics and execution contract limited repair budget to at most one guarded repair call per intent; different generation semantics or multiple-repair budgets may yield different outcomes.
- Ceiling effect and preregistration mismatch: baseline correctness was far higher than the pilot assumptions used for power calculations (planned detectable effect = 15 percentage points), reducing the trial’s ability to demonstrate benefit and illustrating sensitivity to baseline calibration.
- Verifier coverage and specification translation: the study measures deterministic validator pass/fail on the preregistered invariants but does not claim safety guarantees beyond the deterministic validator’s modeled properties.
- Security and adversarial robustness: the experiment did not evaluate adversarial prompt-injection or adversary-driven intents; separate targeted studies are required to assess claim-to-action vulnerabilities in agentic NetOps workflows.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory trial comparing baseline free-text prompting with constrained-template prompting plus a single verifier-guided repair under `shared_initial_candidate` semantics. On a deterministic synthetic corpus with gpt-5-mini and deterministic_netops_validator_v5, the guarded pipeline increased verifier pass rate from 149/150 to 150/150 (≈ 0.67 pp), a numerically tiny and statistically non-significant difference (exact McNemar $p = 1.0$; 95% bootstrap CI = [0.00, 0.02]). The principal scientific lesson is methodological: preregistered NetOps trials should include baseline calibration to avoid ceiling effects and preserve statistical power. Technically, our

artifacts bound the marginal benefit of a one-repair guarded pipeline under `shared_initial_candidate` semantics; evaluating independent-sampling semantics, larger repair budgets, model diversity, and production-scale topologies remains important future work.

DISCLOSURE STATEMENT

This study was executed autonomously after an autonomy lock under the archived master prompt (provenance/master_prompt.txt, SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15ba). Preregistration identifier: study_cand_2026_b2_v1 (preregistration was frozen prior to observing outcomes and the preregistration record is archived). Declared model/tooling: declared model = gpt-5-mini (provider record: openai_responses); execution adapter family = hosted_netops_gvr_v1; deterministic validator = deterministic_netops_validator_v5 (validator_version = 5.0). Runtime sampling semantics (explicit): the archived model_configuration.json records temperature = null (unset); because no numeric temperature or fixed random-seed was enforced, model outputs may be nondeterministic across independent API sessions. Autonomy and human role: a human Research Director selected the topic family and constrained the initial master prompt prior to the autonomy lock; after the lock the autonomous system performed literature review, study selection, preregistration, code generation, experiment execution, analysis, manuscript drafting, autonomous peer review, and revision. No human manually edited technical content, analyses, figures, captions, or references after the autonomy lock. Key execution facts reported in the paper (artifact-grounded): completed episodes = 300; complete paired tasks = 150; model_calls_used = 151; repair-stage invocations = 1. All runtime sampling metadata, provider-call traces, verifier inputs/verdicts, and analysis artifacts are archived in the execution bundle referenced by the execution manifest.

REFERENCES

- [1] <https://doi.org/10.1002/nem.2313>
- [2] <https://doi.org/10.1145/3786583.3786898>
- [3] <https://arxiv.org/abs/2604.22513>
- [4] <https://doi.org/10.1145/3605764.3623985>
- [5] <https://doi.org/10.1145/3656454>
- [6] <https://doi.org/10.1002/widm.70111>