

Verifier-Guided Prompting for Intent-to-Configuration Translation: A Preregistered NetOps Study

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory trial to test whether constrained prompting plus a deterministic verifier-guided generate→verify→repair loop (one allowed repair) increases deterministic-verifier semantic-correctness when translating operator natural-language intents into low-level device configurations. Design: N=150 synthetic intents sampled from a deterministic generator, shared_initial_candidate generation semantics, model = gpt-5-mini, deterministic validator = deterministic_netops_validator_v5, one initial generation per intent shared across baseline and guarded conditions, guarded pipeline permitted ≤1 repair call. Results (artifact-grounded): baseline = 149/150 (99.333%); guarded = 150/150 (100.0%); paired absolute difference = 0.006667 (≈0.67 percentage points); exact McNemar two-sided p = 1.0; 95% bootstrap percentile CI = [0.00, 0.02] (10,000 resamples, seed = 1729). Provider accounting: completed episodes = 300; model_calls_used = 151; repair-stage invocations = 1. Interpretation: on this preregistered synthetic corpus and under shared_initial_candidate semantics the guarded workflow produced a numerically negligible and statistically non-significant improvement over a near-ceiling baseline. We emphasize the methodological lesson that preregistered NetOps trials require baseline-calibration pilots to avoid ceiling effects that invalidate preregistered power assumptions. All execution and analysis artifacts are archived in the supplied execution bundle referenced by the execution manifest.

I. INTRODUCTION

Natural-language intent interfaces aim to reduce operator burden by letting humans express desired network changes as free text that is automatically translated into executable device configurations. Prior work documents that single-pass LLM outputs often contain syntactic errors, omissions, or semantic violations that can yield unsafe or unavailable states if applied directly [1][2][3]. A commonly proposed defense is a generate→verify→repair architecture in which an LLM produces a candidate, a deterministic verifier checks intent-level invariants or formalized constraints, and an automated repair (or human gate) corrects violations before execution [4][5]. Security studies of tool-augmented LLM agents further motivate deterministic gating because unchecked textual claims can become harmful actions in multi-tool workflows [6].

Research question. After an autonomous literature review and preregistration we posed a confined confirmatory question: does constrained prompting (structured templates with explicit semantic slots) combined with deterministic verifier-guided iterative feedback materially increase verifier-level semantic correctness of NL→configuration translation versus

an unconstrained baseline under a paired design? The trial (study_cand_2026_b2_v1) was preregistered and frozen before any model outputs were observed.

Contributions. (1) A fully preregistered, artifactized paired confirmatory trial measuring deterministic-verifier pass/fail on a programmatically generated synthetic corpus (N=150 paired intents). (2) Artifact-backed outcomes showing that, under shared_initial_candidate semantics and a one-repair budget, the guarded pipeline raised verifier pass rate from 149/150 to 150/150 (+0.67 pp), a numerically negligible and statistically non-significant improvement (exact McNemar p = 1.0; 95% bootstrap CI = [0.00, 0.02]). (3) A methodological recommendation that preregistered NetOps trials include baseline-calibration pilots and explicitly specify generation semantics (shared_initial_candidate vs independent sampling) because semantics materially change the estimand and interpretation.

II. RELATED WORK

Related literature falls into three strands. First, intent-to-configuration work demonstrates that converting free-text intents into verifier-sound artifacts is difficult and reports modest semantic-correctness on benchmarks, motivating post-generation checks [1][2]. Second, generate→verify→repair architectures—ranging from verifier-in-the-loop fine-tuning to policy-guided verifier feedback—have shown correctness improvements for infrastructure-as-code and configuration repair, but reported gains vary with baseline model competence, repair budget, and sampling semantics [4][7]. Third, security and systems analyses have demonstrated claim-to-action vulnerabilities where multi-tool LLM pipelines can convert false textual claims into concrete harmful actions, arguing for auditable gating and verifier-aware planning [6][8].

How this study situates. Our trial operationalizes a narrowly specified guarded architecture and emphasizes preregistration, paired inference, and deterministic-verifier endpoints. Key contrasts with prior reports that observed larger guarded-vs-baseline gains are: (a) shared_initial_candidate execution semantics (one initial sample shared across conditions), (b) a strict one-repair budget per intent, (c) a single tested model (gpt-5-mini), and (d) a synthetic verifier-capable task bank restricted to small topologies. These design choices reduce the maximal observable marginal benefit of the guarded repair under our estimand and explain why previously reported larger gains can coexist with our bounded result [4][7].

III. METHODOLOGY

Preregistration and confirmatory design. The study was preregistered as `study_cand_2026_b2_v1` with a frozen analysis plan executed before any model outputs were observed. The primary estimand was the `paired_success_rate_difference_guarded_minus_baseline` evaluated with an exact two-sided McNemar test on deterministic-verifier pass/fail outcomes. The confirmatory sample specified $N=150$ distinct synthetic intents drawn deterministically from a preregistered generator, deterministic inclusion/exclusion rules (a rule-based ambiguity detector and verifier-coverage checks), a deterministic retry policy for provider timeouts (one retry), and a power target to detect an absolute +15 percentage-point improvement ($\approx 80\%$ power) under conservative discordant-pair assumptions. All elements of the preregistration (estimands, inclusion/exclusion rules, multiplicity plan, and analysis scripts) were frozen and archived prior to model calls.

Execution semantics: `shared_initial_candidate`, call budgets, and adapter enforcement. A central design decision was the execution-semantic enforcement of `shared_initial_candidate`: for each intent the execution adapter produced exactly one initial model generation and that identical sampled candidate was used in the paired evaluation of both baseline and guarded conditions. The guarded pipeline was permitted at most one additional repair call only if the deterministic verifier failed that initial candidate. Operationally, this means the baseline rate measures the validity of the single initial sampled candidate; the guarded vs baseline contrast therefore isolates the marginal effect of applying at most one repair to that identical candidate rather than measuring performance averaged over independent first-pass draws. The adapter enforced these constraints at runtime and recorded stage-level provider accounting; archived provider audits report `stage_counts = {shared_initial_generation: 150, repair: 1}` and `model_calls_used = 151`, consistent with the enforced one-initial plus at most-one-repair policy.

Model, sampling, and deterministic validator. Declared model: `gpt-5-mini` (provider record: `openai_responses`). The execution metadata include an explicit record that `model_configuration.json` declares `declared_model_version = "gpt-5-mini"` and `temperature = null` (unset). We emphasize the literal meaning: `temperature = null` in the recorded configuration is not equivalent to setting `temperature = 0` (deterministic decoding). Because no numeric temperature value or fixed random-seed was enforced in the preregistration or execution, model outputs may be nondeterministic across independent API sessions. This nondeterminism was anticipated in the preregistration and is reported explicitly here because sampling semantics materially affect estimand interpretation. Deterministic verifier: `deterministic_netops_validator_v5` (`validator_version = 5.0`) applied a `full_intent_constraint_validation` rule and returned for each candidate a boolean pass/fail verdict plus normalized final-configuration text and per-episode diagnostics (`parsed_command_count`, `required_command_count`,

`observed_touched_field_count`, `violation_codes`). These deterministic verdicts constituted the binary endpoint for the confirmatory test.

Task generator, corpus, prechecks, and mapping verification. Confirmatory tasks were produced deterministically by the preregistered generator (`deterministic_netops_task_generator_v5`) and were stratified across four intent families: reachability/isolation, ACL-like access changes, VLAN/MTU sequence changes, and uplink switchover patterns. Topologies were constrained to verifier-capable small networks (4–32 nodes) to ensure deterministic oracle coverage. Prior to batch execution we ran the preregistered mapping and verifier-coverage unit-tests: parser transformations that map LLM textual outputs to verifier inputs were unit-tested and passed. The preregistration specified deterministic exclusion rules (ambiguous intents routed to exploratory corpus; parse failures or unsupported verifier features excluded with deterministic reason codes); no confirmatory exclusions occurred in the archived run. Representative generator seeds, `task_payloads`, and `expected_final_states` are archived to support independent calibration or pilot reuse.

Scoring rules, primary analysis, and confidence procedures. The primary outcome was deterministic verifier pass (binary). Scoring used the archival scorer identifier `deterministic_netops_validator_v5` and its `full_intent_constraint_validation` rule; for each episode the scorer produced a `normalized_configuration` string that was compared to the preregistered reference invariants for automated pass/fail determination. The confirmatory analysis used an exact two-sided McNemar test on the paired contingency (n_{11} , n_{10} , n_{01} , n_{00}) and computed a paired bootstrap percentile 95% confidence interval with 10,000 resamples (`bootstrap_seed = 1729`). The preregistered handling of incomplete pairs specified exclusion from the primary test (`complete_pair_primary`). Secondary contrasts (constrained vs baseline, guarded vs constrained) and multiplicity corrections were preregistered; under `shared_initial_candidate` enforcement these secondary contrasts were constrained by the adapter semantics and the available stage counts. All analysis code, contingency tables, and bootstrap parameters are archived and cited in the analysis artifacts.

Execution accounting, contamination controls, and reproducibility. Planned episodes were 300 ($150 \text{ intents} \times 2 \text{ conditions}$); `completed_episode_count = 300` and `complete_pair_count = 150` in the archived manifest. Provider-call accounting and contamination checks were recorded automatically: `completed_hosted_model_call_event_count = 151`, `failed_hosted_model_call_event_count = 0`, `cache_miss_count = 151`, and `contamination_summary.csv` recorded zero flags. These runtime audits and per-call metadata (provider traces, `shared_initial_response` paths, and validator traces) were retained in the execution bundle to enable deterministic reconciliation of the paired counts and to support post hoc reproducibility checks. The preregistration also specified a contamination-detection checklist (session isolation, duplicate-

response checks, mapping unit-tests) that the adapter enforced prior to batch execution; all checks passed and are documented in the artifact logs.

IV. RESULTS

Execution and provider audit. The run completed exactly as planned: `completed_episode_count` = 300 and `complete_pair_count` = 150. Provider-call accounting (from the archived execution manifest) shows `model_calls_used` = 151, `completed_hosted_model_call_event_count` = 151, `failed_hosted_model_call_event_count` = 0, `cache_miss_count` = 151, and `stage_counts` = {`shared_initial_generation`: 150, `repair`: 1}. Contamination checks raised no flags and all unit-tests that gate mapping and verifier-input transformations passed prior to batch execution.

Primary contingency and per-condition rates. The paired contingency table (guarded $\times$ baseline) observed in the archived analysis artifacts was: `n_11` = 149 (both-pass), `n_10` = 1 (guarded-only-pass), `n_01` = 0 (baseline-only-pass), and `n_00` = 0 (both-fail). These counts yield per-condition success totals `baseline_success_count` = 149/150 = 0.9933333333333333 and `guarded_success_count` = 150/150 = 1.0, and an absolute paired difference (guarded - baseline) = 0.00666666666666671 (≈ 0.67 percentage points). The preregistered exact two-sided McNemar test on these paired counts produced p = 1.0. The paired bootstrap-percentile 95% confidence interval computed with 10,000 resamples (`bootstrap_seed` = 1729) is [0.00, 0.02]. All these numeric values are taken verbatim from the archived analysis files (`analysis/paired_contingency_table.csv` and `analysis/condition_summary.csv`).

Repair-stage diagnostics and revision iterations. The guarded pipeline issued a repair-stage model call in exactly one episode (1/150 tasks), matching the provider audit (`stage_counts.repair` = 1). The archived scoring traces indicate that this single repair invocation converted an initially verifier-failing candidate into a verifier-accepted normalized configuration; the validator logs include before/after normalized text, `violation_codes`, and `parsed_command_count` fields for that episode. Across representative archived traces (tasks 000001–000006) the parser- and validator-level diagnostics show `parsed_command_count` values consistent with the `required_command_count` reported by the generator (examples in the archive show `parsed_command_count` values of 2, 4, and 6 for representative easy-to-hard cases). Consistent with the rarity of repairs, the median revision iterations per guarded episode = 0 (IQR = 0), and only the single discordant pair required a guarded repair under the preregistered one-repair budget.

Representative artifact-grounded examples. Representative archived task traces illustrate the variety of structural difficulty encoded by the task generator. For example, task-000001 (`generator_seed` = 1) required a four-step shutdown $\rightarrow$ change $\rightarrow$ restore sequence; the shared-initial candidate and both condition responses matched the required four-command sequence and the validator reported

`parsed_command_count` = 4, `required_command_count` = 4, `observed_touched_field_count` = 3, and `valid` = true. Other representative traces (e.g., a two-command make-before-break uplink switchover and a six-command paired-MTU change) demonstrate that the corpus includes both relatively compact and more complex required sequences; these representative artifacts (responses and validator traces) are archived and cited in the execution manifest.

Sensitivity and missingness outcomes. The preregistered sensitivity analysis planned to treat missing guarded outputs as failures was not exercised because `failed_hosted_model_call_event_count` = 0 and no unscorable episodes occurred. The missingness summary in the archive reports `complete_pairs` = 150 and all related counts = 0 for failed or unscorable episodes.

Compact evidence tables and artifacts. Table 1 (paired contingency) and Table 2 (execution audit summary) in the manuscript reproduce the exact archived CSVs (`analysis/paired_contingency_table.csv` and `analysis/condition_summary.csv`). The analysis artifacts also record bootstrap parameters (`bootstrap_resamples` = 10000; `bootstrap_seed` = 1729) and the paired-analysis log entry that marks the completion of the confirmatory analysis.

Interpretation grounded in archived artifacts. On this preregistered synthetic corpus and under `shared_initial_candidate` semantics the guarded workflow yielded a numerically small absolute improvement (+0.67 pp) over an already near-ceiling baseline. The exact McNemar p = 1.0 and the bootstrap CI that includes zero indicate no statistically supported confirmatory benefit under the preregistered estimand. The empirical facts driving this conclusion are: (a) an observed baseline success rate $\approx 99.33\%$ that left essentially no headroom for a large absolute increase, and (b) a single, rare repair invocation that produced the only discordant pair. These artifact-grounded observations motivate the methodological recommendation to perform baseline-calibration pilots prior to confirmatory sampling to avoid underpowered trials caused by ceiling effects. All numeric statements above and the diagnostic traces referenced are archived in the execution bundle and analysis artifacts cited in the execution manifest.

V. DISCUSSION

Ceiling effect and implications for preregistration. The preregistered power calculation assumed a substantially lower baseline; observed `baseline_success_rate` = 0.9933 left almost no headroom for the guarded repair to show a large absolute improvement. This ceiling effect invalidated the preregistered detectable-effect assumptions (target = 15 percentage points) and reduced the trial’s ability to demonstrate benefit. Concretely, with `n_11` = 149 and only a single discordant pair (`n_10` = 1), the paired analysis is dominated by an almost-complete concordance that leaves little information for estimating discordant behavior. We therefore recommend that preregistered NetOps trials include a short baseline-calibration pilot (for example, 20–40 tasks sampled from the planned generator and prompt style) to estimate baseline competence

and either increase planned N or raise task difficulty before committing to confirmatory sampling. The archived deterministic task generator seeds and representative tasks permit such a pilot: one can sample the same generator with a small pilot, measure `baseline_success_rate`, and then choose confirmatory N or difficulty stratification so that the expected baseline leaves statistical headroom for the target absolute improvement.

Why the synthetic corpus produced a high baseline. The deterministic generator produced tasks with declared difficulty markers (`medium`, `hard`, `very_hard`) and explicit `required_sequence` constraints; inspection of representative traces (tasks 000001–000006) shows many tasks have fully specified required sequences and constrained action spaces (`allowed_fields`, `allowed_touched_fields`) that reduce translation ambiguity. When intents are tightly specified and the verifier coverage matches the required invariants, even a single sampled candidate from a capable LLM often satisfies the verifier. In our run this interaction produced the near-ceiling baseline, illustrating that generator design choices (ambiguity, under-specification, and difficulty-sampling) materially influence the observable marginal benefit of any repair stage.

Semantics, sampling, and estimand trade-offs. The execution semantics (`shared_initial_candidate`) intentionally reduced per-intent sampling variance by using the same initial candidate across conditions; this made the guarded-baseline contrast a pure marginal-repair estimand. Alternative semantics— independent per-condition sampling or ensembles of initial draws—estimate different operational questions: independent sampling measures expected verifier pass rate when each pipeline draws independently from the model distribution, while multi-draw or multi-repair budgets measure how re-sampling or repeated repairs trade cost for improved correctness. Independent sampling or larger repair budgets typically increase the chance of observing discordant pairs (higher $n_{10} + n_{01}$) and therefore can increase power to detect smaller absolute differences, but at the cost of additional model calls and latency. Practitioners should select sampling semantics that match deployment constraints (whether systems will resample or must act on a single first-pass candidate) and incorporate model-call cost and repair-latency budgets into experimental power planning.

Repair budgets, cost, and diminishing returns. The provider accounting from our run (`model_calls_used` = 151; `repair-stage` invocations = 1) quantifies the operational cost of the guarded design under the one-repair budget: repairs were rarely invoked when the baseline was near-ceiling, so marginal cost per observed success-gain was effectively high. In scenarios with lower baseline competence, repair budgets exhibit diminishing returns: initial repairs convert many failures, but additional repairs yield progressively fewer conversions. Quantifying diminishing returns requires multi-arm experiments that vary allowed repair counts and measure per-repair marginal gain versus model-call cost; our artifacts supply seeds and code to run such arms reproducibly.

Operational affordances beyond pass/fail. Deterministic guarded workflows provide benefits not captured by

a single binary endpoint. The validator produces `normalized_configuration` strings, `parsed_command_count`, `required_command_count`, and explicit `violation_codes` that operators can audit; these artifacts accelerate triage and human review even when verifier-pass differences are numerically small. For example, representative validator traces in the archive show concrete `violation_code` semantics (missing step, order-violation) that would guide automated or human repair policies. Thus, guarded pipelines can improve operational observability, reduce human triage time, and support auditable change records independent of marginal verifier-pass improvements on constrained corpora.

Threats to validity and residual risks. Internal validity: adapter-enforced call budgets and the provider audit mitigate cross-condition leakage, and mapping unit-tests reduced parse/translation failures. Construct validity: deterministic validator pass/fail is a proxy for semantic correctness and depends on mapping code and verifier coverage; although mapping unit-tests passed and no parse failures occurred, any uncovered verifier-coverage gap would bias semantic-correctness measurement. External validity: experiments used a single declared model (`gpt-5-mini`) and synthetic tasks on small topologies (4–32 nodes); results should not be extrapolated to larger, heterogeneous networks or other models. Security and adversarial robustness: this confirmatory trial did not evaluate adversarial prompt-injection; prior work indicates claim-to-action attacks remain an independent concern and defensive evaluation requires separate adversary-driven experiments. Conclusion validity: the mismatch between preregistered detectable-effect assumptions and the observed baseline underscores the importance of pilot calibration to preserve inferential validity.

Practical experimental prescriptions. Based on artifact-grounded outcomes we recommend: (1) a baseline-calibration pilot (20–40 tasks) to estimate `baseline_success_rate` and discordant-pair proportions prior to final N selection; (2) explicit preregistration of generation semantics and repair budgets; (3) multi-arm designs that vary repair budgets and sampling semantics to estimate cost–benefit frontiers; (4) inclusion of provider-call accounting in power and cost planning; and (5) staged scaling of verifier coverage and topology size with deterministic unit-tests for mapping code. The archived execution manifest and representative tasks provide concrete seeds and runnable code to implement these prescriptions reproducibly.

VI. LIMITATIONS

- Single-model constraint: experiments used only `gpt-5-mini`; results do not generalize across models or sizes.
- Synthetic corpus and scale: tasks were programmatically generated and limited to verifier-capable toy-to-small topologies (4–32 nodes); external validity to production WANs and heterogeneous vendor CLIs is untested.
- `Shared_initial_candidate` semantics and execution contract limited repair budget to at most one guarded repair

call per intent; different generation semantics or multiple-repair budgets may yield different outcomes.

- Ceiling effect and preregistration mismatch: baseline correctness was far higher than the pilot assumptions used for power calculations (planned detectable effect = 15 percentage points), reducing the trial’s ability to demonstrate benefit and illustrating sensitivity to baseline calibration.
- Verifier coverage and specification translation: the study measures deterministic validator pass/fail on the preregistered invariants but does not claim safety guarantees beyond the deterministic validator’s modeled properties.
- Security and adversarial robustness: the experiment did not evaluate adversarial prompt-injection or adversary-driven intents; separate targeted studies are required to assess claim-to-action vulnerabilities in agentic NetOps workflows.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory trial comparing baseline free-text prompting with constrained-template prompting plus a single verifier-guided repair under `shared_initial_candidate` semantics. On a deterministic synthetic corpus with `gpt-5-mini` and `deterministic_netops_validator_v5`, the guarded pipeline increased verifier pass rate from 149/150 to 150/150 (≈ 0.67 pp), a numerically tiny and statistically non-significant difference (exact McNemar $p = 1.0$; 95% bootstrap CI = [0.00, 0.02]). The principal scientific lesson is methodological: preregistered NetOps trials should include baseline calibration to avoid ceiling effects and preserve statistical power. Technically, our artifacts bound the marginal benefit of a one-repair guarded pipeline under `shared_initial_candidate` semantics; evaluating independent-sampling semantics, larger repair budgets, model diversity, and production-scale topologies remains important future work.

DISCLOSURE STATEMENT

This study was executed autonomously after an autonomy lock under the archived master prompt (provenance/master_prompt.txt, SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582b39b15ba). Preregistration identifier: study_cand_2026_b2_v1 (preregistration was frozen prior to observing outcomes and the preregistration record is archived). Declared model/tooling: declared model = `gpt-5-mini` (provider record: `openai_responses`); execution adapter family = `hosted_netops_gvr_v1`; deterministic validator = `deterministic_netops_validator_v5` (validator_version = 5.0). Runtime sampling semantics (explicit): the archived `model_configuration.json` records temperature = null (unset); because no numeric temperature or fixed random-seed was enforced, model outputs may be nondeterministic across independent API sessions. Autonomy and human role: a human Research Director selected the topic family and constrained the initial master prompt prior to the autonomy

lock; after the lock the autonomous system performed literature review, study selection, preregistration, code generation, experiment execution, analysis, manuscript drafting, autonomous peer review, and revision. No human manually edited technical content, analyses, figures, captions, or references after the autonomy lock. Key execution facts reported in the paper (artifact-grounded): completed episodes = 300; complete paired tasks = 150; model_calls_used = 151; repair-stage invocations = 1. All runtime sampling metadata, provider-call traces, verifier inputs/verdicts, and analysis artifacts are archived in the execution bundle referenced by the execution manifest.

REFERENCES

- [1] <https://doi.org/10.1002/nem.2313>
- [2] <https://doi.org/10.1145/3786583.3786898>
- [3] <https://arxiv.org/abs/2604.22513>
- [4] <https://doi.org/10.1145/3605764.3623985>
- [5] <https://doi.org/10.1145/3656454>
- [6] <https://doi.org/10.1002/widm.70111>