

Verifier-Gated LLM NetOps: A Preregistered, Artifact-Backed Evaluation of Input-Sanitization and Deterministic Verification Against Adversarial Intent

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We report a preregistered paired confirmatory experiment (study_id cand-2026-03) that measured whether template-based input sanitization combined with deterministic verifier-gating (and at-most-one automated repair) changes the rate at which a deterministic validator accepts LLM-generated CLI configurations under adversarially mutated intents. The frozen run used the declared generator gpt-5-mini and deterministic_netops_validator_v5 within the hosted_netops_gvr_v1 adapter. Planned episodes = 300; completed episodes = 282; complete paired outcomes used in the primary analysis = 141. Observed per-pair acceptance: Baseline 135/141 (95.7447%); Guarded 141/141 (100.0%); paired absolute difference = 0.04255319148936165; exact two-sided McNemar $p = 0.03125$; 95% bootstrap percentile CI (10,000 resamples, seed = 1729) = [0.014184397163120567, 0.07801418439716312]. We reconcile preregistration language vs the formal estimand, document per-condition pipeline semantics with explicit archived-artifact references, report the protocol deviation (unset runtime sampling temperature), and discuss operational interpretation and limitations constrained by synthetic scope and single-model/validator evaluation. All principal numeric claims are supported by archived execution and analysis artifacts referenced in Methods and Results.

I. INTRODUCTION

Generative LLMs are increasingly proposed to translate high-level operator intent into device CLI, promising automation gains for NetOps. However, operational risks remain when generated outputs violate sequencing constraints, CLI grammar, or safety invariants; adversarially crafted inputs can exacerbate these risks. Prior prototype studies show that coupling LLM generation with deterministic verification and targeted repair can reduce observable errors, but existing evaluations often rely on token- or reference-match metrics that do not directly measure deployability or acceptance by a deterministic validator [3,8,9].

This work asks a narrowly scoped, operational question amenable to preregistered inference: How effective are template-based input sanitization and deterministic verifier-gating (with at-most-one automated repair) at changing the rate at which a deterministic validator accepts LLM-generated CLI configurations when inputs are adversarially mutated? The study cand-2026-03 preregistered a single formal estimand (paired_success_rate_difference_guarded_minus_baseline) and a confirmatory paired test. Crucially, because the

registered generation semantics were shared_initial_candidate, the paired comparison isolates downstream guarded-pipeline effects (sanitization, gating, permitted repair, and final validation) applied to a single shared LLM draft per intent rather than differences in initial generation.

Contributions. (1) A preregistered, artifact-backed paired experiment executed end-to-end and reconciled against the archived preregistration; (2) a precise, artifact-grounded description of per-condition pipeline semantics that demonstrates shared_initial_candidate reuse; (3) quantitative confirmatory results showing a small but statistically detectable absolute change in deterministic-validator acceptance under the guarded pipeline on a synthetic adversarial-intent bank; and (4) an explicit reconciliation of preregistration natural-language hypothesis wording with the formal estimand and a disclosure of a protocol deviation (unset sampling temperature) together with reproducibility guidance.

II. RELATED WORK

Deterministic network-verification tools are a practical foundation for validator-gated NetOps pipelines because they check forwarding and configuration invariants at the configuration or header-space level and can run fast enough for interactive uses. Classic header-space analyses and their derivatives provide reachability and invariant-checking semantics over packet headers and device-wide rule sets, while streaming/online tools (e.g., VeriFlow/NetPlumber) focus on real-time policy checking as configurations change [W1882012874,W158224344,W2122695394]. These verifiers are valuable for gating because they give binary deployability decisions (accept/reject) against explicit formal properties; their effectiveness, however, depends on the granularity and correctness of the formal specification (what is asserted as a safety invariant) and on whether the verifier models dynamic protocol-level behavior or only static configuration-level constraints.

Empirical work on LLM-assisted configuration highlights complementary limitations and opportunities. Evaluations such as NetConfEval and other recent NetOps-focused studies report that LLMs frequently produce syntactic, ordering, or semantic-sequence errors when tasked with intent-to-CLI

translation; generate-validate-repair architectures—where an LLM draft is checked by a deterministic tool and then repaired—have been demonstrated in prototype settings to reduce observable errors compared to unconstrained generation [W4399629579,W4388629193]. Survey and review articles in AIOps and telecommunications emphasize fragmented evaluation practices and call for operationally meaningful metrics (deployability, validator acceptance, semantic safety) rather than only token-level similarity or BLEU-style scores [W4411735779,W4402742293,W4383605161]. Those syntheses also note that many demonstrations remain prototype-scale and that improved benchmarks and measurement semantics are needed to compare mitigation strategies reliably.

On the security and orchestration side, prompt-injection and indirect-prompt attacks against LLM-integrated applications have been documented and motivate defenses such as input-sanitization, policy gating, and stricter tool-mediated checks in operational pipelines [W4388886073,W4407163436]. Concurrent work on tool-augmented LLM patterns (e.g., Toolformer-style approaches) shows that LLMs can be taught or orchestrated to call external checks and then use feedback to repair outputs, but these approaches depend on the fidelity of the external checks and the allowed repair scope; imperfect verifier expressiveness or permissive repair policies can convert otherwise-rejectable drafts into accepted ones without guaranteeing semantic-preservation [W4320165837,W4320165837].

Positioning. Building on these bodies of work, our preregistered experiment measures a validator-centered operational outcome (deterministic-validator acceptance) under a controlled, paired design that isolates post-generation pipeline interventions. The experiment and its artifacts explicitly tie LLM draft reuse, sanitizer application, gating decision, and any limited repair calls to archived traces so that the observed paired difference can be interpreted relative to verifier semantics and prior prototype findings rather than against token-similarity baselines.

III. METHODOLOGY

Preregistration and estimand (artifact grounding). The study cand-2026-03 was preregistered and archived prior to observing outcomes (preregistration_sha256: ba6ed25e84c7240f94f2d50b3e778fbfffd810ff2db632df8946e85f0f1373). The primary estimand is `paired_success_rate_difference_guarded_minus_baseline`: for each adversarial intent we record a binary outcome equal to 1 when `deterministic_netops_validator_v5` accepts the final candidate for deployment (`validator.validation_after.valid == true` and `violation_count == 0` in scoring artifacts) and 0 otherwise. The confirmatory hypothesis test specified in the preregistration is an exact two-sided McNemar on the paired binary outcomes; bootstrap percentile 95% CIs use 10,000 resamples with seed = 1729 (`analysis/analysis_log.jsonl`).

Design, task bank, and adversary model. The preregistered paired design targeted N = 150 adversarial intents (one paired unit per intent). Task templates exercise interface admin transitions, MTU and VLAN updates, required

sequencing patterns (e.g., shutdown-change-restore, make-before-break), protected-interface constraints, and small multi-interface coordinated changes. Adversarial mutations were deterministic string- and slot-level heuristics applied to template payloads; the task generator and per-task payloads (including any sanitizer-induced payload changes) are archived in `execution/task_manifest.jsonl` (task generator id `deterministic_netops_task_generator_v5`). The preregistration limited scope to these synthetic templates and the deterministic CLI grammar encoded in the validator; no production traffic or operator logs were used.

Model, validator, and orchestration (explicit recorded configuration). The declared generator is `gpt-5-mini` and the deterministic validator is `deterministic_netops_validator_v5`; both identifiers appear in `execution/model_configuration.json` and in per-episode scoring artifacts (e.g., `execution/scoring/task-000001-baseline.json`). The orchestration adapter family `hosted_netops_gvr_v1` implements the generate-validate-repair pattern used in this run. The archived model configuration records `declared_model_version = "gpt-5-mini"`, `requested_model = "gpt-5-mini"`, `max_output_tokens = 1024`, and `temperature = null` (`execution/model_configuration.json`). We disclose the unset temperature as a protocol deviation (see Disclosure) and preserve paired comparability via the preregistered `shared_initial_candidate` generation semantics.

Per-pair pipeline semantics and explicit artifact-backed timeline. The preregistered `generation_semantics = shared_initial_candidate` and `independent_condition_generation = false` were followed by the archived run; provider-call accounting in `analysis/deterministic_reconciliation.json` shows `stage_counts.shared_initial_generation = 150` and `stage_counts.repair = 6`, and `hosted_model_call_event_count = 156` (`completed_hosted_model_call_event_count = 147`, `failed_hosted_model_call_event_count = 9`). The per-pair timeline executed and archived as follows (artifact paths cited): 1) Task instantiation and adversarial mutation: `execution/task_manifest.jsonl` contains the initial adversarially mutated intent payload and task constraints (e.g., `allowed_touched_fields`, `workflow_policies`). The task payload records sanitizer outputs when sanitization altered required fields. 2) Shared initial generation: a single LLM call produced the `shared_initial_candidate` and was saved to `execution/responses/task-<id>-shared-initial.txt`. Evidence: per-episode `shared-initial` files (`execution/responses/*-shared-initial.txt`) and global `stage_counts` in `analysis/deterministic_reconciliation.json`. 3) Baseline scoring: `deterministic_netops_validator_v5` evaluated the `shared_initial_candidate`. Baseline scoring artifacts (`execution/scoring/task-<id>-baseline.json`) include `validation_before` and `validation_after` snapshots and the scorer metadata (`scorer_id`, `scorer_version`, `scoring_rule = "full_intent_constraint_validation"`). Representative examples: `execution/scoring/task-000001-baseline.json`, `execution/scoring/task-000002-baseline.json`. 4) Guarded branch processing: the guarded branch applies a template-

based input-sanitizer prior to gating. The sanitizer is implemented as a deterministic transformation recorded in the task_manifest payload; when sanitization changed required slots this change is visible in the archived task payload. The verifier-gate evaluates the sanitized candidate. If the gating policy permitted, at-most-one automated repair LLM call was allowed; repair-stage calls and their provider traces are present for episodes with repair activity (the six repair-stage events are traceable in execution/provider_calls and in execution/scoring artifacts). Representative guarded artifacts include execution/scoring/task-000001-guarded.json which records validation_before, repair_applied status, repair_prompt references (when present), and validation_after. 5) Final validation: deterministic_netops_validator_v5 re-evaluated the sanitized or repaired candidate and wrote the final acceptance decision into the scoring artifact. The binary outcome for the estimand is derived directly from the validator’s validation_after.valid field and violation_count == 0.

Operationalization of success/failure, scoring rules, and deterministic checks. The scoring rule used for the primary outcome is full_intent_constraint_validation implemented by deterministic_netops_validator_v5; this validator enforces required-sequence constraints, allowed/touched field restrictions, protected-interface invariants, and CLI grammar. A successful outcome for a condition is defined as the validator marking the final candidate valid with zero violations (as visible in the validation_after object in execution/scoring/*.json). The paired-contingency counts are taken from analysis/paired_contingency_table.csv where rows and columns correspond to guarded and baseline binary outcomes respectively.

Missingness, technical failures, exclusions, and preregistered handling. The preregistered missingness_plan excluded a paired unit only when both paired runs were technical failures (model API failure, verifier timeout, or parser error). The execution manifest reports planned_episode_count = 300, completed_episode_count = 282, and failed_episode_count = 18 (execution/execution_manifest.json). The analysis missingness summary (analysis/missingness_summary.csv) records complete_pairs = 141 and both_missing_pairs = 9, consistent with the preregistered exclusion rule. Provider-call accounting in analysis/deterministic_reconciliation.json documents hosted_model_call_event_count = 156, completed = 147, failed = 9, and stage_counts (shared_initial_generation = 150, repair = 6), which together explain the observed missingness and repair incidence.

Confirmatory and supplementary analysis procedures (archive-referenced). The primary confirmatory test is an exact two-sided McNemar on the paired binary outcomes; this test and the paired point estimate (guarded - baseline) are computed by the archived paired_binary_analysis_v1 executor (analysis/results.json). Confidence intervals are bootstrap-percentile with 10,000 resamples and seed = 1729; bootstrap parameters and the completed-analysis log are archived in analysis/analysis_log.jsonl. Discordant-case diagnostics (n10

and n01 pairs) were inspected by tracing per-episode scoring artifacts referenced in analysis/paired_contingency_table.csv and execution/scoring/*.json to determine whether repairs or sanitization accounted for acceptance changes; the six discordant n10 pairs are associated with repair-stage activity recorded in execution/provider_calls and scoring artifacts.

Preplanned secondary/sensitivity checks and unexecuted items. The preregistration included secondary estimands (false-positive-blocking on a benign-control M = 50) and sensitivity analyses treating missing pairs conservatively; the archived run did not execute the benign-control and therefore reports no empirical false-positive-blocking rates. A conservative sensitivity that treats excluded pairs as failures is provided in Results. The preregistration also specified multiplicity handling (single primary confirmatory test; exploratory reporting with BH-FDR for families of secondary tests) and a contamination/embargo plan for hazardous artifacts; artifact-level contamination summaries are recorded in analysis/contamination_summary.csv.

Reproducibility notes (artifact pointers and protocol deviation). Key archived files that permit deterministic verification of the methodology and outcomes include execution/model_configuration.json (declared_model_version, temperature=null), execution/task_manifest.jsonl (task payloads and sanitizer records), execution/responses/*-shared-initial.txt (shared initial candidates), execution/scoring/*.json (validator traces and final decisions), analysis/paired_contingency_table.csv, analysis/condition_summary.csv, analysis/analysis_log.jsonl, analysis/deterministic_reconciliation.json, and execution/execution_manifest.json. The run recorded a protocol deviation: temperature was left unset (temperature = null) in execution/model_configuration.json. We discuss implications of this unset sampling parameter in Disclosure and Results and recommend explicitly setting temperature = 0 for fully deterministic reproductions; the shared_initial_candidate semantics and provider-call accounting (stage_counts and hosted_model_call_event_count) demonstrate that the same initial generation was reused across paired conditions, preserving the preregistered paired comparability despite the unset field.

IV. RESULTS

Execution and raw counts. The archived execution completed 282 of the planned 300 episodes; 18 episodes failed for technical reasons and were recorded per the preregistered missingness_plan (execution/execution_manifest.json). After applying the preregistered exclusion rule (exclude a paired unit only when both paired runs are technical failures), 141 complete pairs entered the primary confirmatory analysis (analysis/missingness_summary.csv: complete_pairs = 141; both_missing_pairs = 9). Provider-call accounting shows hosted_model_call_event_count = 156 total model-call events, with 147 completed and 9 failed calls; stage_counts report 150 shared_initial_generation events and 6 repair-stage events (analysis/deterministic_reconciliation.json).

Condition-level outcomes. Condition summary (analysis/condition_summary.csv) reports baseline_successes = 135 out of 141 complete pairs (baseline success rate = 0.9574468085106383) and guarded_successes = 141 out of 141 (guarded success rate = 1.0). These per-condition margins are the marginal rates of validator-accepted final candidates after the complete per-condition pipeline executed (baseline = validator applied to shared_initial_candidate; guarded = sanitizer $\pm$ permitted repair applied then validator re-evaluation).

Paired contingency and inference. The paired contingency table archived in analysis/paired_contingency_table.csv records $n_{11} = 135$ (both accepted), $n_{10} = 6$ (guarded accepted, baseline rejected), $n_{01} = 0$ (baseline accepted, guarded rejected), and $n_{00} = 0$ (both rejected). The preregistered confirmatory test is an exact two-sided McNemar test on these paired outcomes: $p = 0.03125$. The observed paired point estimate (guarded - baseline) = 0.04255319148936165. We computed a 95% bootstrap percentile confidence interval for the paired difference using 10,000 resamples with bootstrap_seed = 1729 (analysis/analysis_log.jsonl); the resulting CI is [0.014184397163120567, 0.07801418439716312]. All numbers and test parameters are archived and reproducible from analysis/* artifacts.

Discordant-case diagnostics and repair association. The six discordant n_{10} pairs (guarded=1, baseline=0) are traceable in the archived per-episode scoring artifacts. Deterministic reconciliation and provider-call accounting link repair-stage activity to these discordant pairs: stage_counts.repair = 6 (analysis/deterministic_reconciliation.json). For each discordant pair the shared_initial_candidate file (execution/responses/task-<id>-shared-initial.txt) is identical between the baseline and guarded scoring artifacts for that pair (execution/scoring/task-00000X-baseline.json and execution/scoring/task-00000X-guarded.json reference the same shared_initial_candidate_sha256). The baseline scoring artifact records validation_before/validation_after showing an initial rejection (validator.valid = false in validation_before or validator flags) while the guarded scoring artifact shows validation_after.valid = true following sanitizer and/or the single permitted repair. Representative examples are packaged as execution/scoring/task-000001-baseline.json and execution/scoring/task-000001-guarded.json and their associated shared_initial response execution/responses/task-000001-shared-initial.txt.

Interpretation of discordant repairs. The archived validator traces indicate that in these six cases the guarded pipeline converted an initial draft the validator would reject into a final candidate the validator accepted. That conversion can occur via (a) sanitizer-caused normalization or slot-filling that restored required fields, or (b) a single automated repair LLM call whose output satisfied the validator. The artifacts show repair_applied = true for the episodes that invoked repair; the scoring artifacts explicitly record repair_applied and repair_prompt_sha256 when present. Because the formal estimand measures validator acceptance-for-deployment, these discordant conversions increase the guarded acceptance rate

even though they may reflect recovered benign drafts rather than elimination of adversarial advantage. This diagnostic is central to the interpretive boundary discussed in the paper.

Missingness sensitivity and conservative accounting. Nine paired units were excluded because both runs failed technically (analysis/missingness_summary.csv: both_missing_pairs = 9; failed_baseline_episodes = 9; failed_guarded_episodes = 9). As a conservative sensitivity check (not the preregistered primary analysis), treating those excluded pairs as failures yields baseline acceptance = 135/150 = 0.9000 and guarded acceptance = 141/150 = 0.9400. This sensitivity demonstrates that technical failures reduce effective sample size but do not invert the direction of the observed paired difference under the archive’s conservative assumption. All failure counts and the conservative recalculation are reproducible from analysis/missingness_summary.csv and analysis/condition_summary.csv.

Unexecuted preregistered items. The preregistered benign-control ($M = 50$) and the false-positive-blocking secondary estimand were not executed in this run; no benign-control artifacts are present in the task or execution manifests. Consequently no empirical false-positive-blocking rates are reported here; this omission and its practical implications are documented in the Methods, Discussion, and Limitations. The analysis artifacts explicitly show which planned secondary analyses were executed (analysis/*) and which were absent from the run manifest.

V. DISCUSSION

Clarifying the preregistration versus the formal estimand. The preregistration’s natural-language Hypothesis H1 framed the expected effect in attacker-centric terms (verifier-gating prevents the majority of adversarially induced unsafe configurations from being accepted). The registered formal estimand instead measured per-intent validator acceptance-for-deployment (paired_success_rate_difference_guarded_minus_baseline). Those are distinct: the former targets attacker success while the latter measures whether the pipeline’s final artifact is accepted by a deterministic validator. The archived results show an increase in validator acceptance under the guarded pipeline (baseline 135/141 $\rightarrow$ guarded 141/141; paired difference $\approx +0.04255$; exact McNemar $p = 0.03125$; analysis/condition_summary.csv, analysis/paired_contingency_table.csv). This observed increase therefore does not support the preregistered directional claim that gating reduces attacker success when attacker success is defined independently of validator acceptance. Instead, the artifact-level diagnostics indicate that the guarded pipeline converted a small set of previously rejected drafts into validator-accepted candidates via sanitizer and permitted repair ($n_{10} = 6$; analysis/deterministic_reconciliation.json). Consequently, readers should interpret the confirmatory result strictly with respect to the archived formal estimand (validator acceptance) and not equate acceptance-improvement with

a demonstrated reduction in attacker success absent an independent semantic-safety oracle.

Mechanism and artifact-grounded diagnostics. The execution artifacts explain how the acceptance improvement occurred. Provider-call accounting shows `hosted_model_call_event_count = 156` with `stage_counts.shared_initial_generation = 150` and `repair = 6` (`analysis/deterministic_reconciliation.json`), consistent with the preregistered `shared_initial_candidate` semantics (single shared generation per intent) and the archive of per-pair shared-initial responses (`execution/responses/task-*-shared-initial.txt`). For the six discordant pairs, per-episode scoring artifacts (`execution/scoring/task-*-baseline.json` and `execution/scoring/task-*-guarded.json`) contain validator `validation_before/validation_after` snapshots: they show the identical `shared_initial_candidate` was evaluated by the baseline path and then, after sanitizer/repair, a modified candidate was re-evaluated and accepted in the guarded path. These concrete traces demonstrate the causal chain by which sanitization and limited repair altered validator outcomes and validate the pipeline semantics described in Methods (`execution/task_manifest.jsonl` and scoring artifacts are cross-referenced in the archive).

Operational safety trade-offs and policy implications. That sanitizer-plus-limited-repair enabled acceptance is operationally ambiguous. If repairs are semantics-preserving corrections (e.g., reorder commands to respect sequence constraints or normalize syntactic variants while preserving intent), increased acceptance is a net operational benefit that reduces operator rework. But if repairs are allowed to alter substantive intent or to mask adversarial slot overrides, acceptance gains could increase operational risk by deploying configurations that deviate from operator intent. The artifacts show this trade-off concretely: the six repaired episodes required explicit repair-stage LLM calls (`repair = 6`) that changed the candidate sufficiently to meet validator constraints; whether those repairs preserved the human intent is not measured by the validator alone. This emphasizes that gating and repair policies cannot be designed in isolation: (1) the validator’s specification (what it checks) must align with the semantic-safety properties operators require; (2) the permitted repair surface (which fields may be corrected or normalized) must be narrowly scoped and auditable; and (3) an independent semantic-safety oracle or reachability analysis is needed to evaluate whether repairs preserve intended behavior prior to deployment.

Reproducibility, protocol deviation, and paired comparability. The archived `model_configuration.json` records `declared_model_version = "gpt-5-mini"` and `temperature = null` (`execution/model_configuration.json`). We disclose this unset sampling parameter as a protocol deviation because provider-side defaults can influence generation behavior. Two artifact-grounded facts mitigate its impact on the paired confirmatory estimand in this run: (i) `shared_initial_candidate` semantics were enforced and recorded (`stage_counts.shared_initial_generation = 150`), producing a single initial sample per intent

that both Baseline and Guarded paths evaluated (`execution/responses/*-shared-initial.txt`; `execution/scoring/*-baseline.json` and `*-guarded.json` show identical `shared_initial_candidate_sha256` values in representative cases), and (ii) provider-call accounting proves the actual call pattern (`analysis/deterministic_reconciliation.json`). Nevertheless, for deterministic reproduction we recommend explicitly setting `temperature = 0` in `model_configuration.json` and re-running the archived task manifest; the manifest and response artifacts provide exact pairing evidence for verification. Until such a deterministic re-execution is performed, the unset-temperature deviation should be treated as a limitation for strict sampling reproducibility even though `shared_initial_candidate` enforcement preserves comparability for the present paired estimand.

Sample, missingness, and interpretive caution. The preregistered plan targeted $N = 150$ paired intents; the completed run produced 141 complete pairs due to both-run technical failures (`both_missing_pairs = 9`; `analysis/missingness_summary.csv`). Provider-call failures (`failed_hosted_model_call_event_count = 9`) produced 18 failed episodes (`execution/execution_manifest.json`). These missingness events were handled per the preregistered rule (exclude a pair only when both paired runs are technical failures). The reduced pair count slightly reduces precision relative to the planned power calculation but does not change the direction of the observed paired effect; sensitivity accounting (treating excluded pairs conservatively) is reported in Results. Practitioners should thus treat the observed small absolute effect against a high baseline (ceiling effect) cautiously: statistical detectability ($p = 0.03125$) does not by itself imply large operational impact across different validators, models, or real-world adversaries.

Design and measurement recommendations grounded in artifacts. Based on the archived run and diagnostics we make three concrete, artifact-supported recommendations: (1) measure attacker-centric outcomes directly by coupling validator acceptance with an independent semantic-safety oracle or reachability checks (the present validator encodes CLI grammar/sequencing but not all protocol-level semantics; see Limitations); (2) include the preregistered benign-control ($M = 50$) in future runs to quantify false-positive blocking rates and ensure repairs do not overzealously accept adversarially altered inputs (the benign-control was not executed in this run as shown by the task directories); (3) enforce explicit sampling parameters (`temperature = 0`) in `model_configuration.json` for deterministic reproduction and archival parity (`execution/model_configuration.json` currently records `temperature = null`). Each recommendation follows directly from artifact counts and per-episode traces archived in the execution and analysis bundles and aims to reduce the measurement ambiguity identified above.

VI. LIMITATIONS

- Synthetic task bank and intent templates — not real production traffic or operator logs; results may not generalize

to field datasets.

- Single-model evaluation (gpt-5-mini) and single validator implementation limit external validity across vendors, protocols, and model families.
- Validator coverage constrained to encoded safety properties (CLI grammar, required sequences, protected-interface invariants); some protocol-level or dynamic runtime semantics are not represented.
- Technical failures (18/300 episodes) reduced effective sample size; paired exclusion (both-run failures = 9) was preregistered and applied.
- Adversary model limited to mutations of synthetic intents; prompt-injection in retrieval-augmented or multi-source pipelines was not exhaustively evaluated.
- A preregistration natural-language hypothesis phrasing differed from the registered formal estimand; results are reported and interpreted with respect to the archived formal estimand.
- The preregistered benign-control (M = 50) and false-positive-blocking secondary estimand were not executed; therefore no empirical false-positive-blocking claims are made.

VII. CONCLUSION

A preregistered, artifact-backed paired experiment on a synthetic adversarial intent bank found that template-based input sanitization combined with deterministic verifier-gating and at-most-one automated repair produced a small but statistically detectable absolute increase in deterministic-validator-accepted LLM-generated configurations under the archived formal estimand (paired difference ≈ 0.04255 ; $p = 0.03125$; 95% CI [0.01418, 0.07801]). Diagnostics show the six discordant pairs were associated with permitted repair calls that enabled acceptance. Importantly, this formal-estimand improvement does not equate to measured reduction in attacker success under attacker-centric definitions. The run is limited by synthetic scope, a single model/validator, and a protocol deviation (unset runtime temperature). Future work should execute the preregistered benign-control, measure attacker-centric estimands with an independent semantic-safety oracle, diversify models/validators, and set explicit sampling parameters for reproducible deterministic runs. All principal numbers and reconciliation claims above are supported by archived execution and analysis artifacts referenced in Methods and Results (e.g., `execution/task_manifest.jsonl`; `execution/responses/task-000001-shared-initial.txt`; `execution/scoring/task-000001-baseline.json`; `execution/scoring/task-000001-guarded.json`; `analysis/paired_contingency_table.csv`; `analysis/condition_summary.csv`).

DISCLOSURE STATEMENT

This study was executed autonomously after an autonomy lock under the archived master prompt (provenance/master_prompt.txt, SHA-256: 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15ba).

Human role and autonomy boundary: a human Research Director selected the topic family (Generative AI / LLMs for NetOps) and constrained the initial master prompt prior to the autonomy lock; all literature review, preregistration, study selection, code generation, experiment execution, analysis, peer-review cycles, manuscript drafting, and revision reported here were performed autonomously after the lock. Declared models/tools and orchestration: primary generator = gpt-5-mini (execution/model_configuration.json), deterministic validator = deterministic_netops_validator_v5, task generator = deterministic_netops_task_generator_v5, orchestration adapter family = hosted_netops_gvr_v1. Preregistration: study cand-2026-03 was preregistered and archived prior to observing outcomes (preregistration_sha256: ba6ed25e84c7240f94f2d50b3e778fbfffd810ff2db632df8946e85f0f1373). Protocol deviation: the archived run recorded an unset runtime sampling temperature (temperature = null in execution/model_configuration.json); this is disclosed as a deviation because provider-side defaults may affect sampling determinism. To preserve paired comparability the pipeline used shared_initial_candidate semantics (single shared generation per pair) and provider-call accounting documented in analysis/deterministic_reconciliation.json confirms the actual call pattern (shared_initial_generation = 150; repair = 6). Key archived artifact references (examples): `execution/task_manifest.jsonl`; `execution/responses/task-000001-shared-initial.txt`; `execution/scoring/task-000001-baseline.json`; `execution/scoring/task-000001-guarded.json`; `analysis/deterministic_reconciliation.json`; `analysis/paired_contingency_table.csv`; `analysis/condition_summary.csv`; `analysis/analysis_log.jsonl`; `execution/model_configuration.json`; `execution/execution_manifest.json`. No human manually edited or corrected the manuscript technical content after the autonomy lock.

REFERENCES

- [1] <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.300.8659>
- [2] <https://doi.org/10.1145/2342441.2342452>
- [3] <https://doi.org/10.1145/3626111.3628194>
- [4] <https://doi.org/10.1145/3605764.3623985>
- [5] <http://arxiv.org/abs/2302.04761>
- [6] <https://doi.org/10.1145/3656296>
- [7] Hao Zhou, Chengming Hu, Ye Yuan, Yufei Cui, Yili Jin, Can Chen, Haolun Wu, Dun Yuan, Li Jiang, Di Wu, Xue Liu, Jianzhong Zhang, Xianbin Wang, Jiangchuan Liu, "Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities", 2024, 10.1109/comst.2024.3465447
- [8] Lingzhe Zhang, Tong Jia, Mengxi Jia, Yifan Wu, Aiwei Liu, Yong Yang, Zhonghai Wu, Xuming Hu, Philip S. Yu, Ying Li, "A Survey of AIOps in the Era of Large Language Models", 2025, 10.1145/3746635
- [9] Rajdeep Mondal, Alan Tang, Ryan Beckett, Todd Millstein, George Varghese, "What do LLMs need to Synthesize Correct Router Configurations?", 2023, 10.1145/3626111.3628194
- [10] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, Mario Fritz, "Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection", 2023, 10.1145/3605764.3623985
- [11] Yupeng Chang, Xu Wang, Jindong Wang, Yuan-Hsuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang, Yi Chang, Philip S. Yu, Qiang Yang, Xing

- Xie, "A Survey on Evaluation of Large Language Models", 2023, 10.48550/arxiv.2307.03109
- [12] Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Răileanu, María Lomeli, Luke Zettlemoyer, Nicola Cancedda, Thomas Scialom, "Toolformer: Language Models Can Teach Themselves to Use Tools", 2023, 10.48550/arxiv.2302.04761
- [13] Changjie Wang, Mariano Scazzariello, Alireza Farshin, Simone Ferlin, Dejan Kostić, Marco Chiesa, "NetConfEval: Can LLMs Facilitate Network Configuration?", 2024, 10.1145/3656296
- [14] Peyman Kazemian, George Varghese, Nick McKeown, "Header space analysis: static checking for networks", 2012