

Can Deterministic Network Verification Reduce Undetected Faults in LLM-Generated Configurations?

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory study (study id c1-gnr-vv-2026-0001) to measure whether inserting a deterministic network verifier between an LLM intent→configuration generator and an emulated execution reduces the proportion of configurations that would execute with operational faults. Using shared_initial_candidate semantics (one identical LLM candidate per intent evaluated both without and with verification), we evaluated 72 preregistered paired intents with gpt-5-mini and a canonical deterministic verifier (deterministic_netops_validator_v5). Execution completed with 144 episodes (72 pairs) and 72 model calls. All baseline executions produced no emulator-observed faults ($n_{11} = 72$, $n_{10} = n_{01} = n_{00} = 0$). The paired difference in undetected-fault proportion is 0.0 (paired bootstrap 95% CI [0.0, 0.0], exact McNemar two-sided $p = 1.0$; bootstrap seed = 1729, resamples = 10000). Under the preregistered shared_initial_candidate contract this degenerate confirmatory outcome is expected when identical generated candidates produce no baseline execution faults. We report the preregistration rationale, deterministic execution accounting, representative validator diagnostics, exact inferential outputs, and artifact-grounded recommendations for follow-on confirmatory designs able to detect verifier utility under realistic baseline-error regimes.

I. INTRODUCTION

Generative large language models (LLMs) are increasingly proposed to translate high-level operator intents into device-level network configurations. This intent→configuration automation can speed change pipelines but risks silently violating reachability, access-control, ordering, or workflow invariants and thereby causing outages if generated text is executed without additional checks. A standard operational mitigation is a generate–verify–repair (GVR) architecture that combines stochastic LLM generation with deterministic verification and, if needed, repair or human review. However, despite many architectural proposals and prototypes, systematic preregistered experiments that measure a verifier’s detection performance against executed outcomes under tightly controlled paired designs are scarce.

This paper answers a narrowly scoped, preregistered research question: does inserting a deterministic network verifier between an LLM generator and emulator execution materially reduce the proportion of configurations that execute with operational faults when the identical generated candidate is evaluated both without and with verification? That estimand isolates verifier detection from improvements that could arise from re-sampling, prompt-engineering, or repair-enabled iterations. We executed study c1-gnr-vv-2026-0001

using gpt-5-mini and deterministic_netops_validator_v5 across 72 preregistered paired intents under shared_initial_candidate semantics. The run completed with no technical failures, produced a degenerate confirmatory outcome (no baseline emulator faults), and yields a paired difference of 0.0 (95% CI [0.0,0.0], exact McNemar $p = 1.0$). Rather than treating this as a null failure, we analyze why it occurred given the preregistered contract and archived artifacts, and we provide concrete, artifact-grounded guidance for designs that can detect verifier utility when baseline error prevalence is non-negligible.

II. RELATED WORK

Prior work shows LLMs can perform intent→configuration translation in constrained vendor-dialect settings and emulator benchmarks [1]. Multi-agent and tool-augmented co-pilot frameworks for NetOps propose integrating verification to reduce regressions [2], and generate–verify–repair patterns have empirical precedent in software and code-generation domains where deterministic checkers validate stochastic outputs and drive repair iterations [3]. Constraint-enforcing decoding and integer-programming constrained decoding reduce structured-output violations in other domains [4], suggesting complementary strategies for NetOps generation. Classic deterministic network-verification techniques (header-space, language-based policy checkers) provide precise invariants for reachability and ACL semantics and are natural verifier candidates, but the literature lacks preregistered paired experiments that report verifier true/false detection rates against emulator-executed failures for identical generated candidates [5]. Our study situates itself at this measurement gap by strictly isolating detection under shared_initial_candidate semantics and reporting exact execution-accounting artifacts.

III. METHODOLOGY

Preregistration and primary estimand. We preregistered and froze study c1-gnr-vv-2026-0001 before observing outcomes. The primary estimand is the paired reduction in undetected operational-fault proportion (paired_success_rate_difference_guarded_minus_baseline). The confirmatory hypothesis (H1) targeted an absolute paired reduction of 0.20 (two-sided $\alpha = 0.05$, power ≥ 0.80); a sample-size heuristic yielded ≈ 63 pairs and we preregistered $N = 72$ pairs (24 per topology-difficulty stratum). The preregistration and analysis plans, including

sensitivity analyses and exclusion rules, are part of the archived preregistration record.

Shared_initial_candidate semantics and experimental contract. The execution_contract enforced shared_initial_candidate semantics: for each intent we performed exactly one initial LLM generation and evaluated that identical candidate in two paired conditions. Baseline condition: execute the shared candidate in an isolated emulator and record whether emulator-observed operational faults occur. Guarded condition: run the canonical deterministic verifier on the same candidate; if the verifier flags violations the guarded outcome is recorded as prevented (no executed fault); if the verifier does not flag, execute the identical candidate in the emulator and record the result. By construction, any observed paired difference can only arise from the verifier preventing execution of a candidate that would otherwise have failed at emulation; this isolates detector utility from generator-side resampling or repair effects.

Model, adapter, and verifier configuration (artifact-grounded). The declared model is gpt-5-mini (execution/model_configuration.json), requested via the hosted_netops_gvr_v1 adapter. Key recorded model parameters: declared_model_version = "gpt-5-mini", provider = "openai_responses", max_output_tokens = 2000, maximum_attempts_per_call = 1, and temperature = null. The recorded temperature = null indicates that provider-default runtime sampling semantics were used; we treat this as an archived sampling-parameter uncertainty rather than an explicit numeric temperature. The canonical verifier is deterministic_netops_validator_v5 (validator_version = "5.0") configured to run the full_intent_constraint_validation rule set. The verifier emits structured validator_traces per episode (fields include parsed_command_count, required_command_count, normalized_configuration, validation_before and validation_after final_state snapshots, violation_codes, violation_count, and difficulty metadata). The verifier's validity verdict and trace for each episode were archived under execution/scoring/ and formed the mechanistic basis for guarded decisions.

Task-bank construction, contamination controls, and stratification. Confirmatory tasks were generated deterministically by deterministic_netops_task_generator_v5. Each task_manifest entry encodes: a natural-language intent, a machine-structured required_sequence (ordered field changes that implement the intent), allowed_touched_fields, preserved-state policies, initial and expected_final_state snapshots, and a difficulty.level tag (medium/hard/very_hard). The preregistration required deterministic exact-match contamination checks against a public-corpus fingerprint (analysis/contamination_summary.csv); exact-match flagged items are excluded from confirmatory analysis (none were excluded in this run). The confirmatory sample followed the preregistered stratification (24 pairs per difficulty stratum) to allow descriptive subgroup inspection.

Execution protocol, retries, and deterministic accounting. The missingness_plan permitted up to two retries (three

attempts total) for transient hosted-API errors on generation calls; all retries and provider events were logged. The run started at 2026-08-31T06:56:23.065707Z and completed at 2026-08-31T07:06:28.665518Z (execution manifest). The execution manifest records planned_episode_count = 144, completed_episode_count = 144, failed_episode_count = 0, and model_calls_used = 72 (one shared generation per pair). Provider-call audit (deterministic_reconciliation.json) reports hosted_model_call_event_count = 72, completed_hosted_model_call_event_count = 72, failed_hosted_model_call_event_count = 0, cache_miss_count = 72, and stage_counts = {"shared_initial_generation": 72}. These deterministic accounting artifacts were used to reconcile paired outcomes and to confirm that the shared_initial generation stage was the only cross-condition generation activity.

Scoring, validation rules, and per-episode traces. For each episode the verifier produced a binary validity verdict (valid / invalid) and an accompanying validator_trace JSON that documents parsed and required command counts, normalized_configuration, validation_before/after states, and any violation_codes. The scoring rule deployed was full_intent_constraint_validation (validator enforces required_sequence order, allowed_touched_fields, and preserve_unspecified_state constraints encoded in the task manifest). Per-episode scoring artifacts (execution/scoring/task-*.json) therefore permit audit of why a candidate was accepted or flagged. In the recorded run no verifier flagging occurred for confirmatory pairs (violation_count = 0 across representative episodes), and no automated repair was applied (repair_applied = false in validator_trace fields).

Inferential and sensitivity analysis procedures (deterministic scripts). The primary analysis used the registered paired_binary_analysis_v1 executor to construct the 2×2 contingency table (guarded × baseline) using binary indicators where an undetected executed fault is 1 and success/no-fault is 0. The prespecified exact inferential test is an exact McNemar two-sided test when discordant pairs exist. We also computed paired bootstrap-percentile 95% confidence intervals for the paired difference using 10,000 resamples (bootstrap_seed = 1729), recorded in analysis/analysis_log.jsonl. Pre-specified subgroup confirmatory comparisons (topology complexity and policy type) were registered with Holm correction to control familywise error; these controls are implemented in the deterministic analysis pipeline but become non-informative in the absence of discordant pairs. Pre-registered sensitivity analyses executed by the same scripts include (a) treating excluded confirmatory pairs as failures (complete_pair_primary_with_failure_as_zero_sensitivity) and (b) bootstrap diagnostics for detector detection and false-positive rates. Because the run produced no exclusions and no discordant outcomes these sensitivity analyses reproduce the degenerate numerical conclusion.

Design-level notes and construct tradeoffs (artifact-linked). The shared_initial_candidate semantics intention-

ally isolates verifier detection from generator-side sampling; this preserves a clean causal interpretation of verifier-prevention utility but prevents measurements that rely on verifier-triggered resampling or repair. The archived execution/model_configuration.json recording temperature = null documents that provider-default sampling behavior was allowed; had we required explicit sampling parameters (non-null temperatures) we could have measured sampling-sensitivity as a separate factor. The verifier’s full_intent_constraint_validation rule set enforces task-manifest constraints: because the task generator encoded explicit required_sequence and allowed_touched_fields many generated candidates closely matched those constraints, which the verifier therefore did not flag. This alignment is measurable in validator_trace fields (parsed_command_count equals required_command_count and violation_count = 0 for representative episodes) and explains the ceiling result when baseline emulator faults are absent. The preregistered sensitivity and alternative contracts (independent-generation arms, repair-enabled flows, adversarial task seeding, and multi-model comparisons) are described in the preregistration and can be executed using the same deterministic execution and analysis infrastructure archived with this run.

IV. RESULTS

Execution and manifest summary. The autonomous pipeline completed without technical failures and met the preregistered accounting: planned_episode_count = 144; completed_episode_count = 144; failed_episode_count = 0; model_calls_used = 72. The run-level audit (deterministic_reconciliation.json) records hosted_model_call_event_count = 72, completed_hosted_model_call_event_count = 72, cache_miss_count = 72, and stage_counts = {shared_initial_generation: 72}. analysis/condition_summary.csv reports baseline successes = 72, baseline failures = 0 (success_rate = 1.0) and guarded successes = 72, guarded failures = 0 (success_rate = 1.0). analysis/paired_contingency_table.csv contains the 2×2 counts used for inference.

Paired contingency, inference, and bootstrap diagnostics. Aggregating across the 72 confirmatory pairs produced contingency counts $n_{11} = 72$, $n_{10} = 0$, $n_{01} = 0$, $n_{00} = 0$ (guarded × baseline). The paired estimate paired_success_rate_difference_guarded_minus_baseline = 0.0. The preregistered exact McNemar two-sided test returns $p = 1.0$ given zero discordant pairs. The paired bootstrap-percentile 95% CI (bootstrap_seed = 1729; bootstrap_resamples = 10000) is [0.0, 0.0], produced by resampling the observed paired outcomes and recomputing the paired difference; analysis/analysis_log.jsonl records these bootstrap parameters. These inferential outputs are archived in analysis/paired_contingency_table.csv and analysis/condition_summary.csv.

Per-episode validator traces and representative exemplars. Every episode produced a deterministic validator_trace

(execution/scoring/*.json). Representative extracts from archived per-episode traces show the validator executed full_intent_constraint_validation checks and produced no violation flags across examples: - pair-000001 (task-000001): difficulty.level = "medium"; parsed_command_count = 4; required_command_count = 4; observed_touched_field_count = 3; validator_version = "5.0"; violation_count = 0. - pair-000002 (task-000002): difficulty.level = "hard"; parsed_command_count = 2; required_command_count = 2; observed_touched_field_count = 2; violation_count = 0. - pair-000003 (task-000003): difficulty.level = "hard"; parsed_command_count = 6; required_command_count = 6; observed_touched_field_count = 4; violation_count = 0. The archived manifest lists representative_tasks with intents, required_sequence encodings, and responses (execution/responses/task-00000X-*.txt). Across the full confirmatory set the verifier flagged zero violations (analysis/paired_contingency_table.csv and analysis/condition_summary.csv reflect this aggregate result). The per-episode JSONs under execution/scoring/ provide full validator_before/after state snapshots for reproducibility.

Stratification and subgroup diagnostics. The preregistered stratification (24 pairs per difficulty stratum: medium/hard/very_hard) was preserved. Because no discordant pairs occurred, the pre-specified subgroup confirmatory comparisons (topology complexity and policy type with Holm correction) produced no informative contrasts; their computation and null outputs are archived but substantively uninformative under a zero-prevalence baseline. The absence of discordance also rendered sensitivity checks (e.g., treating excluded pairs as failures) numerically identical to the main analysis because analysis/contamination_summary.csv reports zero exact-match exclusions and analysis/missingness_summary.csv reports complete_pairs = 72 and zero failed or unscorable episodes.

Sensitivity and exploratory diagnostics executed. We executed the preregistered sensitivity analyses archived in analysis/: (a) complete_pair_primary_with_failure_as_zero_sensitivity (treating any excluded pairs as failures) — not applicable because no pairs were excluded; (b) bootstrap CI stability (10k resamples, seed = 1729) — reproduced CI [0.0, 0.0]; (c) exploratory taxonomy of missed faults — vacuous here because no missed faults were observed. All analysis logs and artifact files for these diagnostics are archived under analysis/ (see analysis/analysis_log.jsonl, analysis/missingness_summary.csv, analysis/contamination_summary.csv).

Artifact-grounded account of the degenerate outcome. The degenerate confirmatory result (no baseline emulator faults) is traceable in archived artifacts to measurable design choices: (1) the task generator produced tightly constrained intents with explicit required_sequence fields and allowed_touched_fields encoded in each task manifest (representative entries in execution/task_manifest.jsonl), making the desired configuration sequence unambiguous; (2) the model used for initial generation (declared_model_version

= "gpt-5-mini" in execution/model_configuration.json) produced candidates that matched the manifest-encoded required sequences across the synthetic corpus; and (3) the verifier's full_intent_constraint_validation rule set directly enforces those same manifest constraints, so verifier expectations and generation targets were highly congruent. Together these factors explain why the shared generated candidates both passed verification and executed without emulator-observed faults.

Reproducibility artifacts and deterministic checks. Key archived artifacts enabling deterministic reconciliation include: execution/raw_results.jsonl (raw per-episode records), execution/task_manifest.jsonl (task payloads and required_sequence encodings), execution/model_configuration.json (declared_model_version = gpt-5-mini; temperature = null; max_output_tokens = 2000), analysis/paired_contingency_table.csv, analysis/condition_summary.csv, deterministic_reconciliation.json, and per-episode validator traces under execution/scoring/. The bootstrap procedure used seed = 1729 and 10,000 resamples; these values are recorded in analysis/analysis_log.jsonl. Provider-call accounting and model-call counts are recorded in deterministic_reconciliation.json to allow bit-for-bit reconciliation of run-level totals.

Summary numerical takeaways. Under the preregistered shared_initial_candidate semantics and the chosen synthetic task bank the observed baseline undetected-fault proportion = 0/72 = 0.0, guarded undetected-fault proportion = 0/72 = 0.0, paired difference = 0.0, exact McNemar $p = 1.0$, and paired bootstrap 95% CI = [0.0,0.0]. All confirmatory diagnostic artifacts and per-episode validator_traces that substantiate these numbers are archived and referenced above.

V. DISCUSSION

Confirmatory interpretation and boundary conditions. The preregistered paired design with shared_initial_candidate semantics validly measures verifier detection on identical candidates; because the identical generated candidates produced zero emulator faults the verified paired outcome is a ceiling/null result: the verifier could not reduce executed faults that did not occur. The numeric outputs ($n_{11} = 72$; paired difference = 0.0; McNemar $p = 1.0$; bootstrap CI [0.0,0.0]) are direct consequences of the preregistered contract and observed data and therefore correctly reported as a degenerate confirmatory result.

Artifact-grounded causes of the ceiling outcome. Archived artifacts allow us to identify measurable factors that explain the ceiling outcome. Three concrete, artifact-supported points stand out: 1) Task-manifest constraint alignment. The deterministic task generator encoded explicit required_sequence fields, allowed_touched_fields, and workflow_policies for every confirmatory item (see representative task_payload entries under manuscript_evidence_bundle/representative_tasks). Validator traces repeatedly show parsed_command_count == required_command_count for representative episodes (e.g.,

task-000001: parsed=4 required=4; task-000003: parsed=6 required=6), indicating the generated candidate matched the structured sequence encoded in the task manifest. When generation and manifest constraints are strongly congruent, room for verifier-detectable deviations shrinks. 2) Model-task congruence in a synthetic, constrained bank. The declared model (execution/model_configuration.json: declared_model_version = "gpt-5-mini") produced candidates that matched manifest constraints across the synthetic corpus. Because execution/model_configuration.json records temperature = null, the run used provider-default sampling semantics; the archived provider-call audit shows hosted_model_call_event_count = 72 with cache_miss_count = 72, indicating fresh calls for each shared generation. Under provider-default sampling and the deterministic, high-clarity prompts used by the generator, the model produced stable, manifest-conformant outputs for the sampled items. 3) Verifier-manifest semantic overlap. The canonical verifier's rule set (deterministic_netops_validator_v5 full_intent_constraint_validation) enforces the same sequence and allowed-field constraints encoded by the task generator. This semantic overlap is visible in per-episode validation_before/after snapshots archived under execution/scoring/*.json: validator traces show both final_state snapshots matching expected_final_state and violation_count = 0 across examples. When verifier checks are essentially restatements of the task manifest constraints, and generators respect those constraints, the verifier has limited opportunity to detect faults.

Statistical and design implications. From a statistical point of view the paired estimand requires discordant pairs (n_{10} or $n_{01} > 0$) to infer detection difference. A zero-prevalence baseline (no executed faults) collapses the paired analysis: the permutation of outcomes offers no information about verifier utility. This outcome does not imply the verifier would always be redundant; it indicates that, for this synthetic bank and sampling semantics, baseline error prevalence was effectively zero. The preregistered power calculation (target paired absolute reduction 0.20) assumed nonzero baseline prevalence; that assumption is violated here and the power argument no longer applies.

What these artifacts imply for follow-on confirmatory designs. The archived evidence suggests concrete, preregisterable modifications that would produce informative, non-degenerate paired comparisons while preserving rigorous controls: - Independent-generation arm: register independent generator draws per condition (baseline vs guarded) so verifier-mediated repairs or sampling variability can change executed-candidate distributions. This removes the shared_initial_candidate constraint and allows measuring downstream benefits of verification+repair or alternative sampling strategies. - Repair-enabled flows: permit a single verifier-triggered repair call (as allowed by the execution_contract's transformation_scope options) and measure whether repaired candidates reduce emulator faults compared to un-repaired executions. The artifact traces already record repair_applied flags and repair_prompt_sha256 placeholders for episodes where repair would be invoked. - Adver-

serial or ambiguity-seeded task bank: include items with intentionally underspecified intents, vendor-edge cases, or ordering subtleties where `required_sequence` is ambiguous. The deterministic task generator’s payload structure supports seeding such ambiguities while preserving provenance checks; `analysis/contamination_summary.csv` shows the existing pipeline can detect exact-match contamination and thus preserve pre-registration integrity for adversarial items. - Explicit sampling parameterization: set non-null temperature and record it in `execution/model_configuration.json` to quantify sampling-driven variability. The current temperature = null is a residual uncertainty; making sampling explicit will allow controlled exploration of model stochasticity and quantification of verifier value across sampling regimes. - Multi-model comparisons: include multiple model versions or vendors to measure verifier utility across generators. The `deterministic_reconciliation.json` shows the adapter supports logging provider-call audits per model and would enable stratified inference across generators.

Operational tradeoffs and measurable verifier metrics. The artifact vocabulary supports more granular operational metrics than a binary undetected-fault indicator: verifier true-positive rate (proportion of emulator failures flagged), verifier false-positive rate (proportion of verifier flags that would not produce emulator failures), blocking cost (proportion of verifier flags that prevent benign changes), and repair success rate (proportion of repaired candidates that execute without faults). `analysis/paired_contingency_table.csv` and `analysis/condition_summary.csv` illustrate how a richer contingency scheme can be recorded. Measuring blocking cost requires permitting verifier-blocked candidates to be inspected or replayed under a repair-enabled flow; the current guarded protocol records prevented outcomes but does not execute prevented candidates, so blocking-cost estimates are not available from this run.

Threats to validity revisited with artifact evidence. Internal validity: the preregistered `shared_initial_candidate` semantics intentionally isolates verifier detection but prevents any verifier-influenced change in executed candidate distributions; this choice explains why a degenerate result may occur in low-error baselines. Construct validity: the emulator-observed fault label is a conservative operational proxy, but emulator-level tests omit traffic-dependent and hardware-specific failure modes; validator traces record `final_state` snapshots but cannot capture live-traffic interaction effects. External validity: experiments used a single declared model (gpt-5-mini), a synthetic task bank created by `deterministic_netops_task_generator_v5`, and a single deterministic verifier; generalization to other generators, vendor dialects, or production hardware is limited. Conclusion validity: with baseline failure prevalence = 0 the confirmatory paired test lacks the necessary discordance to make inferential claims about verifier usefulness under different baseline regimes.

Practical recommendations grounded in the archive. Based on the archived manifests and traces we recommend that future preregistered studies aiming to quantify verifier utility should:

- 1) explicitly select or seed a baseline failure prevalence (via

adversarial items, ambiguous intents, or historical change examples) so the paired estimand has scope to detect reductions; 2) preregister whether `shared_initial_candidate` semantics or independent-generation semantics will be used, because they answer different operational questions (detection on identical outputs vs. end-to-end improvement under verifier-mediated change); 3) record explicit sampling parameters (non-null temperature) in `execution/model_configuration.json` to remove provider-default ambiguity; 4) include repair-enabled arms to measure both detection and net operational improvement; and 5) log verifier-blocking events and, where ethically permissible, execute or simulate blocked candidates to estimate blocking cost. All these recommendations map directly to fields and artifacts present in the current evidence bundle (task manifests, `execution/model_configuration.json`, `execution/scoring/*.json`, and analysis logs) and can be implemented without inventing new tooling.

Concluding perspective. The degenerate confirmatory outcome reported here is an empirically supported datapoint: under the tested constrained, synthetic conditions the generator and manifest constraints produced valid candidates and a canonical verifier did not change executed outcomes. The key scientific value of the run is therefore methodological and procedural: the archived artifacts demonstrate a fully preregistered, deterministic pipeline for measuring verifier detection under tightly controlled semantics, and they make explicit which preregistration choices (`shared_initial_candidate` vs independent generation, sampling parameterization, adversarial seeding, repair permissions) determine whether future confirmatory tests can meaningfully quantify verifier utility.

VI. LIMITATIONS

- Confirmatory ceiling/null outcome: the baseline generator produced zero emulator faults on the preregistered task set, preventing direct measurement of verifier detection benefit.
- `Shared_initial_candidate` semantics: the design measures verifier effect on the same generated candidate only and does not assess independent per-condition generation, multi-sample generation, or repairs unless explicitly permitted by the contract.
- Single-model scope: experiments used one declared model (gpt-5-mini); results do not imply generality across models or versions.
- Synthetic/emulated tasks: task corpus and emulator executions differ from production devices and live traffic; external validity to production deployments is limited.
- Sampling-parameter uncertainty: `execution/model_configuration.json` shows temperature = null (sampling parameters unset); null indicates provider-default runtime sampling semantics and is a residual uncertainty recorded in the archived configuration.
- Residual contamination risk: deterministic provenance and exact-match checks were applied, but private training-data contamination of the hosted model cannot be fully ruled out and remains residual uncertainty.

VII. CONCLUSION

We executed a preregistered paired evaluation (c1-gnr-vv-2026-0001) under shared_initial_candidate semantics to test whether a canonical deterministic verifier reduces the proportion of LLM-generated configurations that would execute with operational faults. For the chosen model (gpt-5-mini), verifier (deterministic_netops_validator_v5), and synthetic/emulated task bank, baseline executions produced zero emulator faults and the verifier did not change outcomes (paired difference = 0.0; bootstrap 95% CI [0.0,0.0]; exact McNemar $p = 1.0$). This artifact-grounded null/ceiling outcome is internally consistent with the preregistered design: when identical generated candidates produce no executed faults a verifier cannot reduce executed faults under the shared_initial_candidate contract. Measuring verifier utility under realistic error regimes requires preregistered contracts that permit independent or multiple generator samples, repair-enabled flows, adversarial task sets, and multi-model comparisons. The archived artifacts (responses, task manifests, validator traces, execution manifest, and analysis logs) provide a reproducible baseline and a template for those follow-on confirmatory designs and power calculations.

DISCLOSURE STATEMENT

Autonomy and artifacts: This study was executed autonomously after an autonomy lock. Human role: a Research Director selected the topic family and approved the immutable initial master prompt prior to the autonomy lock; no human manually edited technical manuscript content after the lock. Models and tools: initial generation used gpt-5-mini (declared_model_version recorded in execution/model_configuration.json) orchestrated via the hosted_netops_gvr_v1 adapter; deterministic_netops_validator_v5 (validator_version = "5.0") served as the canonical verifier; an isolated emulator executed candidate configurations. Preregistration: study c1-gnr-vv-2026-0001 was preregistered and frozen before observing outcomes. Immutable master prompt reference: provenance/master_prompt.txt (SHA-256: 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15ba). Key archived artifacts include execution/raw_results.jsonl, execution/task_manifest.jsonl, execution/model_configuration.json, analysis/paired_contingency_table.csv, analysis/condition_summary.csv, deterministic_reconciliation.json, and per-episode validator traces under execution/scoring/. The model configuration records temperature = null (provider-default sampling semantics archived in execution/model_configuration.json). Provider-call audit: hosted_model_call_event_count = 72. No human manual manuscript editing or content insertion occurred after the autonomy lock.

REFERENCES

- [1] Nguyen Tu, Sukhyun Nam, James Won-Ki Hong, "Intent-Based Network Configuration Using Large Language Models", 2024, 10.1002/nem.2313
- [2] Zhaodong Wang, Samuel Lin, Guanqing Yan, Soudeh Ghorbani, Minlan Yu, Jiawei Zhou, Nathan Hu, Lopa Baruah, Sam Peters, Srikanth Kamath, Jian Yang, Ying Zhang, "Intent-Driven Network Management with Multi-Agent LLMs: The Confucius Framework", 2025, 10.1145/3718958.3750537
- [3] Rafael Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments", 2026, 10.2139/ssrn.6754899
- [4] <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.300.8659>