

Measuring Validator Utility in Generate–Verify–Repair NetOps Pipelines: a Confirmatory Paired Study with Shared Initial Candidates

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory study (AC-2026-03) to evaluate whether a multidimensional validator metric suite predicts end-to-end agentic NetOps success better than a single verifier pass rate. Using a synthetic intent→configuration generator and a hosted generate–validate–repair (GVR) adapter under shared_initial_candidate semantics, we ran 200 paired tasks (one shared initial generation per task reused for baseline and guarded). The deterministic validator (deterministic_netops_validator_v5, v5.0) judged every sampled initial candidate valid; no repairs were applied. Baseline = 200/200, guarded = 200/200, paired difference = 0.00 (bootstrap 95% CI [0.00, 0.00], exact McNemar two-sided $p = 1.0$; bootstrap_seed = 1729, resamples = 10000). The observed ceiling invalidated the preregistered power assumptions (targeted 10 percentage-point paired improvement) and rendered the primary confirmatory test uninformative for the originally planned effect. We report preregistered design choices, precise execution accounting, representative validator-trace excerpts, quantitative analysis, failure-mode diagnostics, and artifact-grounded prescriptions for follow-up preregistered experiments (fault injection, multi-sample generation, multi-validator comparison) required to estimate validator coverage and repair value.

I. INTRODUCTION

Automating NetOps workflows with generative models requires reliable mechanisms to avoid harmful, silent, or wrong-but-plausible actions. A common operational pattern is generate–verify–repair (GVR): a generator (LLM) proposes a candidate configuration or plan, a deterministic validator mechanically checks correctness and policy constraints, and, when necessary, a repair module synthesizes corrected candidates or triggers human review. Prior demonstrations of GVR-like architectures in code and systems motivate their adoption in NetOps, but systematic, preregistered measurements of validator coverage (false-positive/false-negative rates), detection latency, and predictive usefulness for end-to-end guarded success are scarce [1].

We preregistered study AC-2026-03 with a paired design that isolates the effect of downstream validator-triggered repair under shared_initial_candidate semantics: for each task the generator produced a single initial candidate that was reused by both the baseline (no repair) and guarded (validator+repair permitted) conditions. Under these semantics any paired difference can only arise down-

stream from validator-triggered repair, not from independent generator sampling. The primary estimand was the paired_success_rate_difference_guarded_minus_baseline and the preregistered confirmatory hypothesis (H1) expected that a multidimensional validator-metric suite would explain more variance in end-to-end success than a single verifier pass rate. Our main contribution is a fully preregistered, artifact-archived experiment and an exact, transparent report of a degenerate confirmatory outcome (ceiling) with concrete, artifact-grounded prescriptions for follow-up designs that can measure validator utility.

II. RELATED WORK

Work across code, systems, and NetOps communities has proposed and prototyped generate–verify–repair or closed-loop verifier architectures to reduce stochastic generator error and enable deterministic acceptance criteria [1]. Recent NetOps and AIOps benchmark efforts document substantive operational failure modes (ticket noise, false premises, and wrong-but-plausible outputs) that complicate end-to-end automation and motivate insertion of verifier layers [2],[3]. Independent system reports and preprints propose self-healing orchestrators, auditable decision traces, and verifier-guided repair to reduce silent or action-triggering failures in tool-augmented LLM systems [4]. Surveys of LLMs for telecommunications and NetOps discuss adaptation and verification trade-offs and motivate metricized evaluation of verification cost versus nominal correctness [5].

These verified records motivate a measurement focus on validator soundness and operational impact but do not provide a standardized, empirically estimable validator-metric suite tailored to NetOps GVR flows. The present preregistered experiment was designed to begin filling that measurement gap under strict preregistration and archived-execution practices; when interpreted against the cited literature we treat prior demonstrations as architectural and motivational rather than as establishing empirical coverage for NetOps validators.

III. METHODOLOGY

Preregistration and primary design. The study preregistration (AC-2026-03) specified a paired confirmatory

design using the `hosted_netops_gvr_v1` adapter family with `generation_semantics = shared_initial_candidate` and `initial_generation_calls_per_task = 1`. Planned `task_count = 200` pairs (`planned_episode_count = 400`), planned `maximum_model_calls = 400`, and `model_scope = gpt-5-mini` via the provider bundle recorded as `'openai_responses'`. The preregistered primary estimand was `paired_success_rate_difference_guarded_minus_baseline`; the primary test was an exact two-sided McNemar with paired bootstrap percentile confidence intervals (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`). Targeted detectable effect was an absolute 0.10 paired improvement with $\alpha = 0.05$ and ~80% power under conservative planning assumptions.

Generator, tasks, and constraints. Tasks were drawn deterministically from `deterministic_netops_task_generator_v5` (`task_family = intent_configuration_repair_v1`). Each task encodes: an `initial_state`, an `expected_final_state`, an explicit intent string, `allowed_fields/allowed_touched_fields`, `workflow_policies` (e.g., `minimum_active_in_groups`, `must_be_down_for_fields`), and a `required_command_sequence`. Task selection followed a preregistered deterministic index rule (`challenging_workflow_stress_v1`). Contamination/exclusion rules (`duplicate_SHA-256` and `embedding-similarity > 0.95`) were preregistered; the execution/analysis artifacts record that no contamination exclusions occurred (`analysis/contamination_summary.csv` empty).

Model and sampling configuration. The declared model version in `execution/model_configuration.json` is `"gpt-5-mini"`; execution accounting records `model_calls_used = 200` (one shared initial generation per pair) and `maximum_model_calls = 400` as preregistered. Important artifact-grounded note: `execution/model_configuration.json` records `temperature = null` (`temperature = null/unset`). Null/unset is explicitly not evidence of deterministic provider-side sampling and does not imply `temperature = 0`; provider sampling variability remains possible and is recorded in provider-call audit fields. Provider-call audit in `deterministic_reconciliation` reports `hosted_model_call_event_count = 200` and `stage_counts.shared_initial_generation = 200`, consistent with the preregistered single shared generation per task.

Validator and scoring. The deterministic validator used was `deterministic_netops_validator_v5` (`validator_version = 5.0`). The validator implements mechanistic intent-constraint checks and emits per-episode fields: `normalized_configuration`, `parsed_command_count`, `required_command_count`, `observed_touched_field_count`, `violation_count/violation_codes`, `valid` (boolean), `repair_applied` (boolean), and repair artifacts when applicable. The preregistered binary scoring rule (`full_intent_constraint_validation`) uses `validator.valid` as the success label for the confirmatory estimand. The pipeline permitted at most one repair call when validator rejected a candidate; repair events would be recorded with `repair_applied = true` and `repair_provider_trace` fields.

Execution, exclusions, and missingness. The preregis-

tered `maximum_attempts_per_call = 1` (no manual retries). The execution manifest reports `completed_episode_count = 400`, `failed_episode_count = 0`, and `complete_pair_count = 200`. The preregistered missingness and contamination plans were followed: confirmatory analyses used complete pairs only; artifacts include `analysis/missingness_summary.csv` and `analysis/contamination_summary.csv`. All raw responses, per-episode validator traces, provider-call traces, and analysis artifacts are archived in the execution bundle and referenced in this paper.

IV. RESULTS

Execution accounting and primary outcomes. The adapter completed the run exactly as preregistered: `planned_episode_count = 400`, `completed_episode_count = 400`, `failed_episode_count = 0`, and `model_calls_used = 200` (one shared initial generation per pair). Provider-call audit: `hosted_model_call_event_count = 200`, `completed_hosted_model_call_event_count = 200`, `cache_hit_count = 0`, `cache_miss_count = 200`, `stage_counts.shared_initial_generation = 200`. No contamination exclusions or near-duplicate exclusions occurred.

Primary confirmatory result. Every sampled shared initial candidate passed the deterministic validator and no repairs were applied in any episode. Analysis artifacts report `baseline_success_count = 200/200` (`success_rate = 1.0`) and `guarded_success_count = 200/200` (`success_rate = 1.0`). The paired contingency (`analysis/paired_contingency_table.csv`) is `n_11 = 200`, `n_10 = 0`, `n_01 = 0`, `n_00 = 0`. The `paired_success_rate_difference_guarded_minus_baseline = 0.00`. Exact McNemar two-sided test `p-value = 1.0`. Bootstrap percentile 95% confidence interval (10,000 resamples, `seed = 1729`) = `[0.00, 0.00]`. The numeric artifacts (`analysis/condition_summary.csv`, `analysis/paired_contingency_table.csv`, `analysis/analysis_log.jsonl`) match these reported values.

Representative validator-trace excerpt (artifact-grounded). To illustrate validator outputs and why no repairs were triggered, we include verbatim key fields from `execution/scoring/task-000004-guarded.json` (pair-000004):

```
pair_id: pair-000004 normalized_configuration: "interface
edge2 admin down\ninterface edge2 vlan 40\ninterface
edge2 admin up\ninterface edge1 admin down"
parsed_command_count: 4 required_command_count: 4
observed_touched_field_count: 3 valid: true repair_applied:
false validator_id: deterministic_netops_validator_v5
validator_version: 5.0
```

Equivalent `validator_trace.validation_after.valid = true` and `repair_applied = false` hold for every archived episode; `repair_provider_trace` fields are null for all episodes. Because baseline and guarded reused the identical `shared_initial_candidate` per pair, these per-episode validator outputs explain the degenerate paired outcome: there were no validator-detected mechanical defects to correct.

Secondary and exploratory diagnostics. Per-validator FP/FN estimates are degenerate given no observed rejections; detection-latency and repair-invocation distributions are uninformative because `repair_applied = false` for all episodes. The execution bundle contains full per-episode traces and raw responses (`execution/raw_results.jsonl`) to support reanalysis under alternative scoring or injected-fault conditions. Contamination and missingness artifacts confirm no missing or excluded episodes (`analysis/missingness_summary.csv: complete_pairs = 200`).

Artifact-grounded diagnostic interpretation. Under `shared_initial_candidate` semantics any paired difference could only arise from validator-triggered repair. The degenerate all-valid outcome is explained by three artifact-grounded determinants visible in the archive: (1) the deterministic task generator produced candidates that satisfied the validator’s mechanistic constraints for the recorded generation seeds; (2) the single-sample-per-task sampling regime removed generator variability as a source of disagreements; (3) mechanistic validators detect structural and policy violations but can be blind to semantic intent misalignment (correct-by-structure yet incorrect-by-intent). These jointly explain why no repairs occurred and the confirmatory test could not detect the preregistered 10-percentage-point improvement target.

V. DISCUSSION

Design implications of `shared_initial_candidate` semantics. The preregistered `shared_initial_candidate` choice intentionally isolates downstream validator and repair effects: because baseline and guarded evaluate the same generator output for each task, any paired improvement must originate from validator-triggered modification or repair rather than from independent generator variance. This property makes the paired estimand a precise probe of repair utility but also concentrates a single-sample ceiling risk: if the shared draw aligns with the validator for most tasks, the design yields no observable discordant pairs. The archive documents exactly this outcome (`model_calls_used = 200`, one shared generation per pair, and `n_11 = 200`), so the null paired difference is a direct, design-consistent artifact rather than an execution anomaly.

Validator scope and a compact taxonomy. Artifact-grounded traces (`validator_id = deterministic_netops_validator_v5`, `validator_version = 5.0`) show the validator enforces mechanistic, checkable properties: syntactic/format correctness, presence of required commands (`required_command_count`), permitted-field constraints (`allowed_touched_fields`), and explicit workflow policies (e.g., `minimum_active_in_groups`). We use a pragmatic taxonomy to reason about coverage and blind spots: (A) syntactic/format checks, (B) structural/ordering constraints (required sequences), (C) policy/domain constraints (protected interfaces, group minima), and (D) semantic intent alignment (whether the produced sequence actually implements the operator intent beyond mechanical constraints). The archived outputs show high coverage for A–C under the synthetic bank and generation seeds used; category D remains the primary open detection challenge because it requires either richer

intent models, supplemental semantic validators, or human adjudication.

Measurement strategies that follow directly from the archive. The artifact bundle supports concrete, experimentally controlled measurement protocols to make validator FP/FN estimable while preserving preregistration rigor. Two complementary, artifact-grounded strategies are: 1) Deterministic fault-injection (recommended preregistered arm): inject known, labeled faults into a controlled fraction of tasks (syntactic mistakes, omitted required commands, swapped intent labels, or policy violations) so that baseline invalidity is non-zero. Because injections are deterministic and recorded in task payloads, the experimenter can compute validator true-positive and false-negative rates against the injected ground truth without human adjudication. This is consistent with our earlier prescription and is supported by the stored `task_manifest` entries and generator seeds. 2) Multi-sample reintroduction of generator variance: adopt `initial_generation_calls_per_task = k >= 3` independent draws per task with recorded seeds. Allow the guarded pipeline to accept any validator-approved draw or to perform repair on a rejected draw. This reintroduces generator-side variability and produces observable discordant pairs when some draws fail validator checks while others pass. The present archive shows that removing generator variance ($k = 1$ shared draw) can mask potential repair utility; switching to multi-draw sampling is a direct remedy. Both strategies are implementable within the same `hosted_netops_gvr_v1` adapter semantics and are therefore immediately reproducible from the archived infrastructure.

Statistical and inferential considerations. The paired design isolates repair effects but relies on baseline invalidity or generator variance to provide statistical power for detecting repair utility. Our preregistered power target (detecting a 0.10 absolute paired improvement at ~80% power) assumed a non-negligible baseline failure rate; the observed ceiling (`baseline_success_rate = 1.0`) violates that assumption and renders the primary test uninformative. Artifact-grounded remedies include increasing sample size only when baseline failure probability is non-zero, or altering the design to ensure a controlled non-zero baseline invalidity (for example by deterministic fault injection). Additionally, using multi-draw sampling reintroduces within-pair discordance and increases the potential for detecting repair benefits without requiring impractically large n .

Design trade-offs in validator strictness and operational cost. Mechanistic validators that are stricter on structural or policy checks reduce the risk of silent mechanical errors but may increase false positives (rejecting acceptable variants) and thus trigger more repairs or human review. Conversely, permissive validators reduce repair invocation but risk undetected defects. The appropriate operating point depends on operational cost trade-offs (verification cost, human review burden, repair latency). While our execution did not observe repairs and thus cannot measure these trade-offs empirically, the execution artifacts (including per-episode `parsed_command_count`, `required_command_count`, and `repair_applied` flags) form the

necessary raw data fields for future experiments that instrument and quantify repair cost and human-review burden under alternative validator thresholds.

Practical orchestration and human-in-the-loop designs. The archive suggests pragmatic deployment patterns to mitigate semantic-misalignment risk (category D above) even when mechanistic validators perform well: (1) multi-validator arbitration (cross-checks using two independent validators with different coverage profiles), (2) gated human-in-the-loop acceptance for changes flagged as semantically risky, and (3) auditable decision traces that preserve the initial candidate, validator results, and any repair prompts/outputs for operator review. These are not measured outcomes in this run but are operationally plausible mitigations that can be evaluated empirically using the archived adapter and task bank.

How the archived artifacts support reproducible next steps. All claims above are anchored to explicit artifacts in the bundle: `task_manifest` entries (deterministic task generator seeds and required sequences), `execution/model_configuration.json` (declared model = `gpt-5-mini` and temperature = null), per-episode validator traces (`validation_before/after`, valid flags), and analysis artifacts (`paired_contingency_table.csv`, `condition_summary.csv`). Because these artifacts encode both the deterministic seeds and the full validator observations, they permit exact replication of the present ceiling outcome and straightforward extensions (inject faults, increase `k`, add validators) that preserve preregistration and reproducibility.

Threats to validity (brief restatement). Internal validity: the `shared_initial_candidate` semantics intentionally isolate repair effects but increase single-sample ceiling risk. Construct validity: `validator.valid` operationalizes mechanistic correctness but may not capture semantic intent misalignment. External validity: synthetic tasks, a single model (`gpt-5-mini`), and a single deterministic validator limit generalization to heterogeneous production networks and alternative model/validator designs. Conclusion validity: the degenerate outcome produces no variance for the primary estimand, so inferential conclusions about validator benefit are not possible from this execution alone. These limitations are explicit in the archived manifests and motivate the artifact-grounded follow-up arms described above.

VI. LIMITATIONS

- `Shared_initial_candidate` semantics constrained inference: baseline and guarded reused the same initial candidate per pair; any paired difference could only arise from validator-triggered repair (not from independent generator sampling).
- Synthetic task bank (difficulty 'very_hard'/'extreme') is not equivalent to heterogeneous production networks (multi-vendor devices, real ticket noise); external validity is limited.
- Single-model experiment: only `gpt-5-mini` was executed; no multi-model generality claims are made.
- No repairs were applied because all initial candidates passed the deterministic validator; therefore the study

could not estimate repair effectiveness or validator false-negative behavior in this execution.

- Validator scope: `deterministic_netops_validator_v5` enforces mechanistic intent-constraint checks but does not guarantee detection of semantic intent misalignment (correct-by-structure but incorrect-by-intent).
- Recorded `execution/model_configuration.json` temperature = null/unset does not imply deterministic sampling; provider-side sampling behavior may vary and is documented in execution manifests.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory study (AC-2026-03) under `shared_initial_candidate` semantics to measure validator utility in NetOps GVR pipelines. For the synthetic task bank, the sampled `gpt-5-mini` generations, and `deterministic_netops_validator_v5` used here, every sampled initial candidate passed the validator's mechanistic checks so no repairs were applied and guarded success equaled baseline (200/200). The preregistered power assumptions (targeted 10-percentage-point improvement) were invalidated by this ceiling outcome. The result is artifact-grounded and reproducible from the archived bundle. We publish the exact execution and analysis artifacts to support replication and provide concrete, preregistered experiment prescriptions (fault injection, multi-sample generation, multi-validator comparison) that are required to produce estimable validator FP/FN behavior and repair value in operationally meaningful conditions.

DISCLOSURE STATEMENT

Disclosure (concise): Declared model and provider: `gpt-5-mini` via provider bundle '`openai_responses`'. Orchestration/adapter: `hosted_netops_gvr_v1`. Deterministic validator: `deterministic_netops_validator_v5` (`validator_version` = 5.0). Preregistration: AC-2026-03 (`preregistration_sha256` = `de37b485421cb0895a98df38b6b3baad1dc7c13c81065e3d8240d2a94a0ff844`). Master prompt immutable reference: `provenance/master_prompt.txt`, SHA-256 = `1872df1e1805d2d96940456ca016bd665d1d5196add77f5acd1f582bb39b15ba`. Autonomy boundary: a human Research Director selected the broad topic family and approved the master prompt before the autonomy lock; after the lock the AI system autonomously performed literature review, preregistration, experiment design, execution, analysis, internal peer review and manuscript drafting without manual editing of technical content. Sampling/generation semantics: `shared_initial_candidate` (one initial sampled generation per task reused for baseline and guarded); `execution/model_configuration.json` recorded temperature = null/unset (null/unset is not evidence of deterministic sampling and does not imply temperature = 0). Call budget and usage (preregistered): `maximum_model_calls` = 400; `actual_model_calls_used` = 200 (one shared initial generation per pair). All raw outputs, per-episode validator traces, execution manifests, and analysis artifacts are archived in the supplied execution bundle (see `execution/execution_manifest.json`). No

human manually edited the manuscript technical content after the autonomy lock.

REFERENCES

- [1] [1] R. Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments," SSRN Electronic Journal, 2026. doi:10.2139/ssrn.6754899.
- [2] [2] K.-H. Tseng, N. Bogawatta, Y. Ginige, K. Patel, K. Dacic, S. Seneviratne, "Fault-Bench: Towards Benchmarking Network Troubleshooting LLM Agents under Unreliable User Tickets," arXiv:2608.27021, 2026.
- [3] [3] Y. Liu, C. Pei, L. Xu, B. Chen, M. Sun, Z. Zhang, Y. Sun, S. Zhang, K. Wang, H. Zhang, J. Li, G. Xie, X. Wen, X. Nie, M. Ma, P. Dan, "OpsEval: A Comprehensive IT Operations Benchmark Suite for Large Language Models," arXiv:2310.07637, 2023.
- [4] [4] R. S. Babu and A. Agrawal, "Self-Healing Agentic Orchestrators for Reliable Tool-Augmented Large Language Model Systems," arXiv:2606.01416, 2026.
- [5] [5] H. Zhou, C. Hu, Y. Yuan, Y. Cui, Y. Jin, C. Chen, H. Wu, D. Yuan, L. Jiang, D. Wu, X. Liu, J. Zhang, X. Wang, J. Liu, "Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities," IEEE Commun. Surveys & Tutorials, 2024. doi:10.1109/COMST.2024.3465447.