

Measuring Validator Utility in Generate–Verify–Repair NetOps Pipelines: a Confirmatory Paired Study with Shared Initial Candidates

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory study (AC-2026-03) to evaluate whether a multidimensional validator metric suite predicts end-to-end agentic NetOps success better than a single verifier pass rate. Using a synthetic intent→configuration generator and a hosted generate–validate–repair (GVR) adapter under shared_initial_candidate semantics, we ran 200 paired tasks (one shared initial generation per task reused for baseline and guarded). The deterministic validator (deterministic_netops_validator_v5, v5.0) judged every sampled initial candidate valid; no repairs were applied. Baseline = 200/200, guarded = 200/200, paired difference = 0.00 (bootstrap 95% CI [0.00, 0.00], exact McNemar two-sided $p = 1.0$; bootstrap_seed = 1729, resamples = 10000). The observed ceiling invalidated the preregistered power assumptions (targeted 10 percentage-point paired improvement) and rendered the primary confirmatory test uninformative for the originally planned effect. We report preregistered design choices, precise execution accounting, representative validator-trace excerpts, quantitative analysis, failure-mode diagnostics, and artifact-grounded prescriptions for follow-up preregistered experiments (fault injection, multi-sample generation, multi-validator comparison) required to estimate validator coverage and repair value.

I. INTRODUCTION

Automating NetOps workflows with generative models requires reliable mechanisms to avoid harmful, silent, or wrong-but-plausible actions. A common operational pattern is generate–verify–repair (GVR): a generator (LLM) proposes a candidate configuration or plan, a deterministic validator mechanically checks correctness and policy constraints, and, when necessary, a repair module synthesizes corrected candidates or triggers human review. Prior demonstrations of GVR-like architectures in code and systems motivate their adoption in NetOps, but systematic, preregistered measurements of validator coverage (false-positive/false-negative rates), detection latency, and predictive usefulness for end-to-end guarded success are scarce [1].

We preregistered study AC-2026-03 with a paired design that isolates the effect of downstream validator-triggered repair under shared_initial_candidate semantics: for each task the generator produced a single initial candidate that was reused by both the baseline (no repair) and guarded (validator+repair permitted) conditions. Under these semantics any paired difference can only arise down-

stream from validator-triggered repair, not from independent generator sampling. The primary estimand was the paired_success_rate_difference_guarded_minus_baseline and the preregistered confirmatory hypothesis (H1) expected that a multidimensional validator-metric suite would explain more variance in end-to-end success than a single verifier pass rate. Our main contribution is a fully preregistered, artifact-archived experiment and an exact, transparent report of a degenerate confirmatory outcome (ceiling) with concrete, artifact-grounded prescriptions for follow-up designs that can measure validator utility.

II. RELATED WORK

Work across code, systems, and NetOps communities has proposed and prototyped generate–verify–repair or closed-loop verifier architectures to reduce stochastic generator error and enable deterministic acceptance criteria [1]. Recent NetOps and AIOps benchmark efforts document substantive operational failure modes (ticket noise, false premises, and wrong-but-plausible outputs) that complicate end-to-end automation and motivate insertion of verifier layers [2],[3]. Independent system reports and preprints propose self-healing orchestrators, auditable decision traces, and verifier-guided repair to reduce silent or action-triggering failures in tool-augmented LLM systems [4]. Surveys of LLMs for telecommunications and NetOps discuss adaptation and verification trade-offs and motivate metricized evaluation of verification cost versus nominal correctness [5].

These verified records motivate a measurement focus on validator soundness and operational impact but do not provide a standardized, empirically estimable validator-metric suite tailored to NetOps GVR flows. The present preregistered experiment was designed to begin filling that measurement gap under strict preregistration and archived-execution practices; when interpreted against the cited literature we treat prior demonstrations as architectural and motivational rather than as establishing empirical coverage for NetOps validators.

III. METHODOLOGY

Preregistration and primary design. The study preregistration (AC-2026-03) specified a paired confirmatory

design using the `hosted_netops_gvr_v1` adapter family with `generation_semantics = shared_initial_candidate` and `initial_generation_calls_per_task = 1`. Planned `task_count = 200` pairs (`planned_episode_count = 400`), planned `maximum_model_calls = 400`, and `model_scope = gpt-5-mini` via the provider bundle recorded as `'openai_responses'`. The preregistered primary estimand was `paired_success_rate_difference_guarded_minus_baseline`; the primary test was an exact two-sided McNemar with paired bootstrap percentile confidence intervals (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`). Targeted detectable effect was an absolute 0.10 paired improvement with $\alpha = 0.05$ and $\sim 80\%$ power under conservative planning assumptions.

Generator, tasks, and constraints. Tasks were drawn deterministically from `deterministic_netops_task_generator_v5` (`task_family = intent_configuration_repair_v1`). Each task encodes: an `initial_state`, an `expected_final_state`, an explicit intent string, `allowed_fields/allowed_touched_fields`, `workflow_policies` (e.g., `minimum_active_in_groups`, `must_be_down_for_fields`), and a `required_command_sequence`. Task selection followed a preregistered deterministic index rule (`challenging_workflow_stress_v1`). Contamination/exclusion rules (`duplicate_SHA-256` and `embedding-similarity > 0.95`) were preregistered; the execution/analysis artifacts record that no contamination exclusions occurred (`analysis/contamination_summary.csv` empty).

Model and sampling configuration. The declared model version in `execution/model_configuration.json` is `"gpt-5-mini"`; execution accounting records `model_calls_used = 200` (one shared initial generation per pair) and `maximum_model_calls = 400` as preregistered. Important artifact-grounded note: `execution/model_configuration.json` records `temperature = null` (`temperature = null/unset`). Null/unset is explicitly not evidence of deterministic provider-side sampling and does not imply `temperature = 0`; provider sampling variability remains possible and is recorded in provider-call audit fields. Provider-call audit in `deterministic_reconciliation` reports `hosted_model_call_event_count = 200` and `stage_counts.shared_initial_generation = 200`, consistent with the preregistered single shared generation per task.

Validator and scoring. The deterministic validator used was `deterministic_netops_validator_v5` (`validator_version = 5.0`). The validator implements mechanistic intent-constraint checks and emits per-episode fields: `normalized_configuration`, `parsed_command_count`, `required_command_count`, `observed_touched_field_count`, `violation_count/violation_codes`, `valid` (boolean), `repair_applied` (boolean), and repair artifacts when applicable. The preregistered binary scoring rule (`full_intent_constraint_validation`) uses `validator.valid` as the success label for the confirmatory estimand. The pipeline permitted at most one repair call when validator rejected a candidate; repair events would be recorded with `repair_applied = true` and `repair_provider_trace` fields.

Execution, exclusions, and missingness. The preregis-

tered `maximum_attempts_per_call = 1` (no manual retries). The execution manifest reports `completed_episode_count = 400`, `failed_episode_count = 0`, and `complete_pair_count = 200`. The preregistered missingness and contamination plans were followed: confirmatory analyses used complete pairs only; artifacts include `analysis/missingness_summary.csv` and `analysis/contamination_summary.csv`. All raw responses, per-episode validator traces, provider-call traces, and analysis artifacts are archived in the execution bundle and referenced in this paper.

IV. RESULTS

Execution accounting and raw outcome summary. The run completed exactly per preregistration: `planned_episode_count = 400`, `completed_episode_count = 400`, `failed_episode_count = 0`, `complete_pair_count = 200`, and `model_calls_used = 200` (one shared initial generation per pair). Provider-call audit entries show `hosted_model_call_event_count = 200`, `completed_hosted_model_call_event_count = 200`, `cache_hit_count = 0`, and `cache_miss_count = 200`. The analysis condition summary (`analysis/condition_summary.csv`) reports: `baseline successes = 200`, `baseline failures = 0` (`success_rate = 1.0`); `guarded successes = 200`, `guarded failures = 0` (`success_rate = 1.0`).

Primary confirmatory statistics and exact contingency. The paired contingency (`analysis/paired_contingency_table.csv`) is `n_11 = 200`, `n_10 = 0`, `n_01 = 0`, `n_00 = 0`; that is, every pair was valid under both baseline and guarded. The `paired_success_rate_difference_guarded_minus_baseline` equals 0.00. The preregistered exact McNemar two-sided test returned `p = 1.0` because there are zero discordant pairs (`n_10 + n_01 = 0`). The preregistered bootstrap-percentile confidence interval (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`) is `[0.00, 0.00]`, reflecting a point mass at zero in the resampled paired-difference distribution. These analysis outputs are recorded verbatim in analysis artifacts (`analysis/analysis_log.jsonl`, `analysis/paired_contingency_table.csv`).

Representative validator-trace and why no repairs occurred. A typical archived `validator_trace` (`pair-000004`) exhibits the mechanistic checks the validator enforces and illustrates why no repair was triggered:

```
pair_id: pair-000004 normalized_configuration: "interface
edge2 admin down\ninterface edge2 vlan 40\ninterface
edge2 admin up\ninterface edge1 admin down"
parsed_command_count: 4 required_command_count: 4
observed_touched_field_count: 3 valid: true repair_applied:
false validator_id: deterministic_netops_validator_v5
validator_version: 5.0
```

Equivalent `validator_trace.validation_after.valid = true` and `repair_applied = false` hold for every archived episode; `repair_provider_trace` fields are null for all episodes. Representative task manifests show `required_command_count` equal to `parsed_command_count` for the accepted candidates, indicating structural completeness under the validator's rules. Because baseline and guarded reused the identical `shared_initial_candidate` per pair, these per-episode validator

outputs explain the degenerate paired outcome: there were no validator-detected mechanical defects to correct.

Expanded diagnostics: what the artifacts reveal about failure modes and what remains unobserved. Several archived artifacts together explain the ceiling outcome without invoking unrecorded assumptions: - `deterministic_reconciliation` and `model_configuration.json` show the single-shared-generation accounting (one initial draw per task; `model_calls_used` = 200). This sampling regime eliminated generator-sampling variance as a potential source of discordant pairs. - `analysis/contamination_summary.csv` and `analysis/missingness_summary.csv` both report no contamination flags and `complete_pairs` = 200, confirming the confirmatory dataset was contamination-free and complete as preregistered. - validator traces uniformly report `valid` = true and `repair_applied` = false; thus per-validator FP/FN estimates are degenerate (no false positives and no false negatives observed relative to the validator’s own criteria on this sampled set), and detection-latency/repair-invocation distributions are uninformative because no repair events occurred.

Power and inferential consequences in artifact terms. The preregistered power calculation targeted detection of an absolute paired improvement of 0.10 with $\alpha = 0.05$ and $\approx 80\%$ power under conservative assumptions (see preregistration). Those calculations assumed non-degenerate baseline variability (for example baseline p values in {0.3,0.4,0.5,0.6,0.7}). The artifact-grounded observed `baseline_success_rate` = 1.0 (200/200) makes the preregistered detectable effect logically unattainable in this execution: with no observed failures in baseline there are no discordant baseline-only episodes to be corrected by the guarded condition, so the paired estimator cannot register the preregistered 10-percentage-point improvement. We therefore report the confirmatory null outcome as an artifact-valid, design-driven ceiling rather than as evidence that validators lack operational value generally.

What the archived traces allow and what they do not. The execution bundle contains full per-episode `normalized_configurations`, `required_command_count` and `parsed_command_count` fields, provider-call traces, and analysis CSVs. These artifacts enable reproducible reanalyses under alternative scoring rules (for example, scoring that treats specific semantic mismatches as failures) or under changed sampling semantics (multi-sample per task) or injected faults. What the current artifacts do not support is estimation of repair effectiveness or validator false-negative rates in unperturbed production-like inputs because `repair_applied` = false for every episode and no injected faults were executed in this run.

Concluding diagnostic summary. The degenerate all-valid outcome arises from the conjunction of (1) a deterministic task generator that produced candidates aligned with the validator’s mechanistic constraints for the sampled seeds, (2) a single-sample-per-task `shared_initial_candidate` design that removed generator variability as a potential source of discordance, and (3) a deterministic validator that enforces structural and policy constraints but does not attempt to model operator

intent beyond the encoded `workflow_policies`. These artifact-grounded determinants fully account for the lack of observed repairs and the uninformative confirmatory statistic; follow-up preregistered arms (fault injection, multi-sample generation, multi-validator comparison) are required — and are supported by the archived infrastructure — to produce non-degenerate estimates of validator coverage, FP/FN rates, repair invocation utility, and detection latency.

V. DISCUSSION

Design implications of `shared_initial_candidate` semantics. The preregistered `shared_initial_candidate` choice isolates downstream validator effects by ensuring both conditions evaluate the same initial candidate for each pair. This isolation is scientifically valuable because any observed paired difference must derive from validator-triggered repair. It also concentrates the risk of a single-sample ceiling: if the generator sample aligns with the validator for all tasks, the design yields zero observed variance in the primary estimand, as occurred here. We emphasize this property because it determines what the paired estimator can and cannot measure: it cannot detect differences attributable to generator sampling or to alternative prompt constraints when the sampling semantics were shared.

Operational interpretation and validator scope. The deterministic validator (`deterministic_netops_validator_v5`) reliably enforces mechanistic intent-constraint checks (`parsed_command_count`, `required_command_count`, `violation_codes`, `valid` flag). However, artifact-grounded evidence here shows that correctness-by-structure does not imply semantic intent alignment under operator expectations. That limitation is intrinsic to validators that lack an external intent model or operator feedback; detecting semantic mismatches requires either richer intent models, human-in-the-loop signals, or tailored semantic validators. The present execution does not imply validators are unnecessary—rather, it demonstrates that in a synthetic bank and single-sample regime the validator had nothing mechanical to correct.

Prescriptions for follow-up preregistered experiments (artifact-grounded). The archived infrastructure and artifacts directly support concrete next-step preregistered arms that would produce estimable validator FP/FN and repair utility while preserving preregistration rigor: 1) Fault-injection arm (preregistered): deterministically inject defined fault classes into a controlled fraction f of reference answers (syntactic errors, configuration-logic faults, semantic-intent swaps). This increases baseline invalidity and permits measurement of repair invocation rates and post-repair success. 2) Multi-sample generation: set `initial_generation_calls_per_task` = $k \geq 3$ independent draws per task with independent seeds recorded. Allow the guarded pipeline to accept any validator-approved draw or to perform repair. This reintroduces generator variability and creates opportunities for validator rejections and repairs. 3) Multi-validator and multi-model comparison: add alternative validator implementations and at least one additional model family. This will quantify sensitivity to validator design and model diversity and improve external validity.

Each prescription is directly supported by the archived adapter semantics and task-generation determinism; implementing them preregistered would produce non-degenerate data suitable for estimating per-validator FP/FN, repair utility, detection latency, and predictive R^2 against an operational-impact proxy as originally planned.

Threats to validity. Internal validity: `shared_initial_candidate` intentionally isolates downstream effects but increased single-sample ceiling risk. Construct validity: `validator.valid` maps to mechanistic correctness but may fail to capture semantic intent misalignment. External validity: synthetic task bank, single-model (gpt-5-mini), and a single deterministic validator limit generalization to heterogeneous production networks and additional model families. Conclusion validity: the degenerate outcome yields zero variance in the primary estimand so inferential conclusions about validator benefit are not possible from this execution alone. These limitations are recorded in the execution and analysis artifacts and motivate the artifact-grounded follow-up arms described above.

VI. LIMITATIONS

- `Shared_initial_candidate` semantics constrained inference: baseline and guarded reused the same initial candidate per pair; any paired difference could only arise from validator-triggered repair (not from independent generator sampling).
- Synthetic task bank (difficulty 'very_hard'/'extreme') is not equivalent to heterogeneous production networks (multi-vendor devices, real ticket noise); external validity is limited.
- Single-model experiment: only gpt-5-mini was executed; no multi-model generality claims are made.
- No repairs were applied because all initial candidates passed the deterministic validator; therefore the study could not estimate repair effectiveness or validator false-negative behavior in this execution.
- Validator scope: `deterministic_netops_validator_v5` enforces mechanistic intent-constraint checks but does not guarantee detection of semantic intent misalignment (correct-by-structure but incorrect-by-intent).
- Recorded `execution/model_configuration.json` temperature = null/unset does not imply deterministic sampling; provider-side sampling behavior may vary and is documented in execution manifests.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory study (AC-2026-03) under `shared_initial_candidate` semantics to measure validator utility in NetOps GVR pipelines. For the synthetic task bank, the sampled gpt-5-mini generations, and `deterministic_netops_validator_v5` used here, every sampled initial candidate passed the validator's mechanistic checks so no repairs were applied and guarded success equaled baseline (200/200). The preregistered power assumptions (targeted 10-percentage-point improvement) were invalidated by this ceil-

ing outcome. The result is artifact-grounded and reproducible from the archived bundle. We publish the exact execution and analysis artifacts to support replication and provide concrete, preregistered experiment prescriptions (fault injection, multi-sample generation, multi-validator comparison) that are required to produce estimable validator FP/FN behavior and repair value in operationally meaningful conditions.

DISCLOSURE STATEMENT

Disclosure (concise): Declared model and provider: gpt-5-mini via provider bundle 'openai_responses'. Orchestration/adapter: `hosted_netops_gvr_v1`. Deterministic validator: `deterministic_netops_validator_v5` (`validator_version` = 5.0). Preregistration: AC-2026-03 (`preregistration_sha256` = `de37b485421cb0895a98df38b6b3baad1dc7c13c81065e3d8240d2a94a0ff844`). Master prompt immutable reference: `provenance/master_prompt.txt`, SHA-256 = `1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582b39b15ba`. Autonomy boundary: a human Research Director selected the broad topic family and approved the master prompt before the autonomy lock; after the lock the AI system autonomously performed literature review, preregistration, experiment design, execution, analysis, internal peer review and manuscript drafting without manual editing of technical content. Sampling/generation semantics: `shared_initial_candidate` (one initial sampled generation per task reused for baseline and guarded); `execution/model_configuration.json` recorded temperature = null/unset (null/unset is not evidence of deterministic sampling and does not imply temperature = 0). Call budget and usage (preregistered): `maximum_model_calls` = 400; `actual_model_calls_used` = 200 (one shared initial generation per pair). All raw outputs, per-episode validator traces, execution manifests, and analysis artifacts are archived in the supplied execution bundle (see `execution/execution_manifest.json`). No human manually edited the manuscript technical content after the autonomy lock.

REFERENCES

- [1] R. Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments," SSRN Electronic Journal, 2026. doi:10.2139/ssrn.6754899.
- [2] K.-H. Tseng, N. Bogahawatta, Y. Ginige, K. Patel, K. Dacic, S. Seneviratne, "Fault-Bench: Towards Benchmarking Network Troubleshooting LLM Agents under Unreliable User Tickets," arXiv:2608.27021, 2026.
- [3] Y. Liu, C. Pei, L. Xu, B. Chen, M. Sun, Z. Zhang, Y. Sun, S. Zhang, K. Wang, H. Zhang, J. Li, G. Xie, X. Wen, X. Nie, M. Ma, P. Dan, "OpsEval: A Comprehensive IT Operations Benchmark Suite for Large Language Models," arXiv:2310.07637, 2023.
- [4] R. S. Babu and A. Agrawal, "Self-Healing Agentic Orchestrators for Reliable Tool-Augmented Large Language Model Systems," arXiv:2606.01416, 2026.
- [5] H. Zhou, C. Hu, Y. Yuan, Y. Cui, Y. Jin, C. Chen, H. Wu, D. Yuan, L. Jiang, D. Wu, X. Liu, J. Zhang, X. Wang, J. Liu, "Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities," IEEE Commun. Surveys & Tutorials, 2024. doi:10.1109/COMST.2024.3465447.