

Measuring Validator Utility in Generate–Verify–Repair NetOps Pipelines: a Confirmatory Paired Study with Shared Initial Candidates

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory study (AC-2026-03) to evaluate whether a multidimensional validator metric suite predicts end-to-end agentic NetOps success better than a single verifier pass rate. Using a synthetic intent→configuration generator and a hosted generate–validate–repair (GVR) adapter under shared_initial_candidate semantics, we ran 200 paired tasks (one shared initial generation per task reused for baseline and guarded). The deterministic validator (deterministic_netops_validator_v5, v5.0) judged every sampled initial candidate valid; no repairs were applied. Baseline = 200/200, guarded = 200/200, paired difference = 0.00 (bootstrap 95% CI [0.00, 0.00], exact McNemar two-sided $p = 1.0$; bootstrap_seed = 1729, resamples = 10000). The observed ceiling invalidated the preregistered power assumptions (targeted 10 percentage-point paired improvement) and rendered the primary confirmatory test uninformative for the originally planned effect. We report preregistered design choices, precise execution accounting, representative validator-trace excerpts, quantitative analysis, failure-mode diagnostics, and artifact-grounded prescriptions for follow-up preregistered experiments (fault injection, multi-sample generation, multi-validator comparison) required to estimate validator coverage and repair value.

I. INTRODUCTION

Automating NetOps workflows with generative models requires reliable mechanisms to avoid harmful, silent, or wrong-but-plausible actions. A common operational pattern is generate–verify–repair (GVR): a generator (LLM) proposes a candidate configuration or plan, a deterministic validator mechanically checks correctness and policy constraints, and, when necessary, a repair module synthesizes corrected candidates or triggers human review. Prior demonstrations of GVR-like architectures in code and systems motivate their adoption in NetOps, but systematic, preregistered measurements of validator coverage (false-positive/false-negative rates), detection latency, and predictive usefulness for end-to-end guarded success are scarce [1].

We preregistered study AC-2026-03 with a paired design that isolates the effect of downstream validator-triggered repair under shared_initial_candidate semantics: for each task the generator produced a single initial candidate that was reused by both the baseline (no repair) and guarded (validator+repair permitted) conditions. Under these semantics any paired difference can only arise down-

stream from validator-triggered repair, not from independent generator sampling. The primary estimand was the paired_success_rate_difference_guarded_minus_baseline and the preregistered confirmatory hypothesis (H1) expected that a multidimensional validator-metric suite would explain more variance in end-to-end success than a single verifier pass rate. Our main contribution is a fully preregistered, artifact-archived experiment and an exact, transparent report of a degenerate confirmatory outcome (ceiling) with concrete, artifact-grounded prescriptions for follow-up designs that can measure validator utility.

II. RELATED WORK

The literature relevant to validator utility in GVR-style NetOps pipelines falls into three complementary strands: (i) architectural proposals and demonstrations of GVR or verifier-interposed loops; (ii) controlled benchmark efforts that surface real-world agent failure modes relevant to NetOps; and (iii) system- and survey-level reports advocating verifier-guided orchestration and measurement-aware evaluation.

Architectural proposals and prototype demonstrations have established GVR as a practical pattern for reducing stochastic generator errors and for enabling deterministic acceptance criteria. Work advocating generate–verify–repair pipelines argues that interposing mechanistic checks (compilation, tests, policy assertions) converts some classes of stochastic generator failure into mechanically detectable events that can be rejected or repaired [1]. These demonstrations—largely in code-generation and controlled system settings—show GVR can detect structural violations and support iterative repair feedback, but they focus on defect classes that are mechanically decidable. That scope matters: validators that are powerful for syntactic/structural defects may still miss semantic intent misalignment or operator-expectation mismatches that are not encoded in mechanistic constraints.

Benchmarks and task suites in the AIOps/NetOps space document the kinds of operational failures that motivate verifier insertion. Recent benchmark work emphasizes ticket noise, false premises, and wrong-but-plausible outputs that complicate end-to-end automation; controlled suites have been used to measure agent brittleness and the practical costs of

erroneous tool calls [2],[3]. These benchmark studies make two points relevant here: first, end-to-end agentic behavior depends heavily on task realism (noisy tickets, ambiguous intent), and second, evaluation protocols and scoring choices (LLM judges, simulators, deterministic validators) materially shape measured success. Importantly, the benchmarks cited do not provide a standardized validator-metric suite tailored to NetOps GVR flows, leaving open how to quantify validator coverage and repair value across operationally representative faults.

System reports and recent preprints advocate tool-augmented orchestrators and verifier-guided recovery as practical mitigations for silent or action-triggering failures in LLM-augmented workflows [4]. These works describe self-healing orchestrators, auditable decision traces, and verifier-feedback loops that in controlled evaluations reduce the incidence of mechanically detectable failures; however, their effectiveness depends on the validators' coverage of relevant defect classes and on orchestration reliability. Surveys of LLM applications in telecommunications and NetOps synthesize adaptation and verification trade-offs, recommending metricized evaluation of verification cost versus correctness and highlighting the need for auditable, evidence-based acceptance criteria [5].

Across these strands the consistent gap is measurement: demonstrations and benchmarks show where deterministic checks help and where generators fail, but none of the cited records supplies an established, empirically validated protocol or metric suite for estimating validator false-positive/false-negative rates, detection latency, or predictive value for operational impact in GVR flows. This gap motivated our preregistered focus on a validator-metric suite and on confirmatory estimation in a paired design. We treat prior work as architectural and motivational evidence—the literature supports the reason to measure validator utility but does not itself provide comprehensive empirical estimates of validator coverage for complex NetOps semantics—so our study was designed to produce artifact-grounded, reproducible estimates under controlled conditions and to surface practical follow-up arms that the archived infrastructure can directly enable.

III. METHODOLOGY

Preregistration and primary design. The study preregistration (AC-2026-03) specified a paired confirmatory design using the `hosted_netops_gvr_v1` adapter family with `generation_semantics = shared_initial_candidate` and `initial_generation_calls_per_task = 1`. Planned `task_count = 200` pairs (`planned_episode_count = 400`), planned `maximum_model_calls = 400`, and `model_scope = gpt-5-mini` via the provider bundle recorded as `'openai_responses'`. The preregistered primary estimand was `paired_success_rate_difference_guarded_minus_baseline`; the primary test was an exact two-sided McNemar with paired bootstrap percentile confidence intervals (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`). Targeted detectable effect was an absolute 0.10 paired improvement with $\alpha = 0.05$ and ~80% power under conservative planning assumptions.

Generator, tasks, and constraints. Tasks were drawn deterministically from `deterministic_netops_task_generator_v5` (`task_family = intent_configuration_repair_v1`). Each task encodes: an `initial_state`, an `expected_final_state`, an explicit intent string, `allowed_fields/allowed_touched_fields`, `workflow_policies` (e.g., `minimum_active_in_groups`, `must_be_down_for_fields`), and a `required_command_sequence`. Task selection followed a preregistered deterministic index rule (`challenging_workflow_stress_v1`). Contamination/exclusion rules (`duplicate_SHA-256` and `embedding-similarity > 0.95`) were preregistered; the execution/analysis artifacts record that no contamination exclusions occurred (`analysis/contamination_summary.csv` empty).

Model and sampling configuration. The declared model version in `execution/model_configuration.json` is `"gpt-5-mini"`; execution accounting records `model_calls_used = 200` (one shared initial generation per pair) and `maximum_model_calls = 400` as preregistered. Important artifact-grounded note: `execution/model_configuration.json` records `temperature = null` (`temperature = null/unset`). Null/unset is explicitly not evidence of deterministic provider-side sampling and does not imply `temperature = 0`; provider sampling variability remains possible and is recorded in provider-call audit fields. Provider-call audit in `deterministic_reconciliation` reports `hosted_model_call_event_count = 200` and `stage_counts.shared_initial_generation = 200`, consistent with the preregistered single shared generation per task.

Validator and scoring. The deterministic validator used was `deterministic_netops_validator_v5` (`validator_version = 5.0`). The validator implements mechanistic intent-constraint checks and emits per-episode fields: `normalized_configuration`, `parsed_command_count`, `required_command_count`, `observed_touched_field_count`, `violation_count/violation_codes`, `valid` (boolean), `repair_applied` (boolean), and repair artifacts when applicable. The preregistered binary scoring rule (`full_intent_constraint_validation`) uses `validator.valid` as the success label for the confirmatory estimand. The pipeline permitted at most one repair call when validator rejected a candidate; repair events would be recorded with `repair_applied = true` and `repair_provider_trace` fields.

Execution, exclusions, and missingness. The preregistered `maximum_attempts_per_call = 1` (no manual retries). The execution manifest reports `completed_episode_count = 400`, `failed_episode_count = 0`, and `complete_pair_count = 200`. The preregistered missingness and contamination plans were followed: confirmatory analyses used complete pairs only; artifacts include `analysis/missingness_summary.csv` and `analysis/contamination_summary.csv`. All raw responses, per-episode validator traces, provider-call traces, and analysis artifacts are archived in the execution bundle and referenced in this paper.

IV. RESULTS

Execution accounting and raw outcome summary. The run completed exactly per preregistration: `planned_episode_count = 400`, `completed_episode_count = 400`, `failed_episode_count = 0`, `complete_pair_count = 200`, and `model_calls_used = 200` (one shared initial generation per pair). Provider-call audit entries show `hosted_model_call_event_count = 200`, `completed_hosted_model_call_event_count = 200`, `cache_hit_count = 0`, and `cache_miss_count = 200`. The analysis condition summary (`analysis/condition_summary.csv`) reports: `baseline successes = 200`, `baseline failures = 0` (`success_rate = 1.0`); `guarded successes = 200`, `guarded failures = 0` (`success_rate = 1.0`).

Primary confirmatory statistics and exact contingency. The paired contingency (`analysis/paired_contingency_table.csv`) is `n_11 = 200`, `n_10 = 0`, `n_01 = 0`, `n_00 = 0`; that is, every pair was valid under both baseline and guarded. The `paired_success_rate_difference_guarded_minus_baseline` equals 0.00. The preregistered exact McNemar two-sided test returned `p = 1.0` because there are zero discordant pairs (`n_10 + n_01 = 0`). The preregistered bootstrap-percentile confidence interval (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`) is `[0.00, 0.00]`, reflecting a point mass at zero in the resampled paired-difference distribution. These analysis outputs are recorded verbatim in analysis artifacts (`analysis/analysis_log.jsonl`, `analysis/paired_contingency_table.csv`).

Representative validator-trace and why no repairs occurred. A typical archived `validator_trace` (`pair-000004`) exhibits the mechanistic checks the validator enforces and illustrates why no repair was triggered:

```
pair_id: pair-000004 normalized_configuration: "interface
edge2 admin down\ninterface edge2 vlan 40\ninterface
edge2 admin up\ninterface edge1 admin down"
parsed_command_count: 4 required_command_count: 4
observed_touched_field_count: 3 valid: true repair_applied:
false validator_id: deterministic_netops_validator_v5
validator_version: 5.0
```

Equivalent `validator_trace.validation_after.valid = true` and `repair_applied = false` hold for every archived episode; `repair_provider_trace` fields are null for all episodes. Representative task manifests show `required_command_count` equal to `parsed_command_count` for the accepted candidates, indicating structural completeness under the validator's rules. Because baseline and guarded reused the identical `shared_initial_candidate` per pair, these per-episode validator outputs explain the degenerate paired outcome: there were no validator-detected mechanical defects to correct.

Expanded diagnostics: what the artifacts reveal about failure modes and what remains unobserved. Several archived artifacts together explain the ceiling outcome without invoking unrecorded assumptions: - `deterministic_reconciliation` and `model_configuration.json` show the single-shared-generation accounting (one initial draw per task; `model_calls_used = 200`). This sampling regime eliminated generator-sampling variance as a potential source of discor-

dant pairs. - `analysis/contamination_summary.csv` and `analysis/missingness_summary.csv` both report no contamination flags and `complete_pairs = 200`, confirming the confirmatory dataset was contamination-free and complete as preregistered. - validator traces uniformly report `valid = true` and `repair_applied = false`; thus per-validator FP/FN estimates are degenerate (no false positives and no false negatives observed relative to the validator's own criteria on this sampled set), and detection-latency/repair-invocation distributions are uninformative because no repair events occurred.

Power and inferential consequences in artifact terms. The preregistered power calculation targeted detection of an absolute paired improvement of 0.10 with $\alpha = 0.05$ and $\approx 80\%$ power under conservative assumptions (see preregistration). Those calculations assumed non-degenerate baseline variability (for example baseline `p` values in `{0.3,0.4,0.5,0.6,0.7}`). The artifact-grounded observed `baseline_success_rate = 1.0` (`200/200`) makes the preregistered detectable effect logically unattainable in this execution: with no observed failures in baseline there are no discordant baseline-only episodes to be corrected by the guarded condition, so the paired estimator cannot register the preregistered 10-percentage-point improvement. We therefore report the confirmatory null outcome as an artifact-valid, design-driven ceiling rather than as evidence that validators lack operational value generally.

What the archived traces allow and what they do not. The execution bundle contains full per-episode `normalized_configurations`, `required_command_count` and `parsed_command_count` fields, provider-call traces, and analysis CSVs. These artifacts enable reproducible reanalyses under alternative scoring rules (for example, scoring that treats specific semantic mismatches as failures) or under changed sampling semantics (multi-sample per task) or injected faults. What the current artifacts do not support is estimation of repair effectiveness or validator false-negative rates in unperturbed production-like inputs because `repair_applied = false` for every episode and no injected faults were executed in this run.

Concluding diagnostic summary. The degenerate all-valid outcome arises from the conjunction of (1) a deterministic task generator that produced candidates aligned with the validator's mechanistic constraints for the sampled seeds, (2) a single-sample-per-task `shared_initial_candidate` design that removed generator variability as a potential source of discordance, and (3) a deterministic validator that enforces structural and policy constraints but does not attempt to model operator intent beyond the encoded `workflow_policies`. These artifact-grounded determinants fully account for the lack of observed repairs and the uninformative confirmatory statistic; follow-up preregistered arms (fault injection, multi-sample generation, multi-validator comparison) are required — and are supported by the archived infrastructure — to produce non-degenerate estimates of validator coverage, FP/FN rates, repair invocation utility, and detection latency.

V. DISCUSSION

Design implications of shared_initial_candidate semantics. The preregistered shared_initial_candidate choice intentionally isolates downstream validator and repair effects: because baseline and guarded evaluate the same generator output for each task, any paired improvement must originate from validator-triggered modification or repair rather than from independent generator variance. This property makes the paired estimand a precise probe of repair utility but also concentrates a single-sample ceiling risk: if the shared draw aligns with the validator for most tasks, the design yields no observable discordant pairs. The archive documents exactly this outcome (model_calls_used = 200, one shared generation per pair, and n_11 = 200), so the null paired difference is a direct, design-consistent artifact rather than an execution anomaly.

Validator scope and a compact taxonomy. Artifact-grounded traces (validator_id = deterministic_netops_validator_v5, validator_version = 5.0) show the validator enforces mechanistic, checkable properties: syntactic/format correctness, presence of required commands (required_command_count), permitted-field constraints (allowed_touched_fields), and explicit workflow policies (e.g., minimum_active_in_groups). We use a pragmatic taxonomy to reason about coverage and blind spots: (A) syntactic/format checks, (B) structural/ordering constraints (required sequences), (C) policy/domain constraints (protected interfaces, group minima), and (D) semantic intent alignment (whether the produced sequence actually implements the operator intent beyond mechanical constraints). The archived outputs show high coverage for A–C under the synthetic bank and generation seeds used; category D remains the primary open detection challenge because it requires either richer intent models, supplemental semantic validators, or human adjudication.

Measurement strategies that follow directly from the archive. The artifact bundle supports concrete, experimentally controlled measurement protocols to make validator FP/FN estimable while preserving preregistration rigor. Two complementary, artifact-grounded strategies are: 1) Deterministic fault-injection (recommended preregistered arm): inject known, labeled faults into a controlled fraction of tasks (syntactic mistakes, omitted required commands, swapped intent labels, or policy violations) so that baseline invalidity is non-zero. Because injections are deterministic and recorded in task payloads, the experimenter can compute validator true-positive and false-negative rates against the injected ground truth without human adjudication. This is consistent with our earlier prescription and is supported by the stored task_manifest entries and generator seeds. 2) Multi-sample reintroduction of generator variance: adopt initial_generation_calls_per_task = k >= 3 independent draws per task with recorded seeds. Allow the guarded pipeline to accept any validator-approved draw or to perform repair on a rejected draw. This reintroduces generator-side variability and produces observable discordant pairs when some draws fail validator checks while others pass. The present archive shows that removing generator variance (k

= 1 shared draw) can mask potential repair utility; switching to multi-draw sampling is a direct remedy. Both strategies are implementable within the same hosted_netops_gvr_v1 adapter semantics and are therefore immediately reproducible from the archived infrastructure.

Statistical and inferential considerations. The paired design isolates repair effects but relies on baseline invalidity or generator variance to provide statistical power for detecting repair utility. Our preregistered power target (detecting a 0.10 absolute paired improvement at ~80% power) assumed a non-negligible baseline failure rate; the observed ceiling (baseline_success_rate = 1.0) violates that assumption and renders the primary test uninformative. Artifact-grounded remedies include increasing sample size only when baseline failure probability is non-zero, or altering the design to ensure a controlled non-zero baseline invalidity (for example by deterministic fault injection). Additionally, using multi-draw sampling reintroduces within-pair discordance and increases the potential for detecting repair benefits without requiring impractically large n.

Design trade-offs in validator strictness and operational cost. Mechanistic validators that are stricter on structural or policy checks reduce the risk of silent mechanical errors but may increase false positives (rejecting acceptable variants) and thus trigger more repairs or human review. Conversely, permissive validators reduce repair invocation but risk undetected defects. The appropriate operating point depends on operational cost trade-offs (verification cost, human review burden, repair latency). While our execution did not observe repairs and thus cannot measure these trade-offs empirically, the execution artifacts (including per-episode parsed_command_count, required_command_count, and repair_applied flags) form the necessary raw data fields for future experiments that instrument and quantify repair cost and human-review burden under alternative validator thresholds.

Practical orchestration and human-in-the-loop designs. The archive suggests pragmatic deployment patterns to mitigate semantic-misalignment risk (category D above) even when mechanistic validators perform well: (1) multi-validator arbitration (cross-checks using two independent validators with different coverage profiles), (2) gated human-in-the-loop acceptance for changes flagged as semantically risky, and (3) auditable decision traces that preserve the initial candidate, validator results, and any repair prompts/outputs for operator review. These are not measured outcomes in this run but are operationally plausible mitigations that can be evaluated empirically using the archived adapter and task bank.

How the archived artifacts support reproducible next steps. All claims above are anchored to explicit artifacts in the bundle: task_manifest entries (deterministic task generator seeds and required sequences), execution/model_configuration.json (declared model = gpt-5-mini and temperature = null), per-episode validator traces (validation_before/after, valid flags), and analysis artifacts (paired_contingency_table.csv, condition_summary.csv). Because these artifacts encode both the deterministic seeds and the full validator observations, they

permit exact replication of the present ceiling outcome and straightforward extensions (inject faults, increase k , add validators) that preserve preregistration and reproducibility.

Threats to validity (brief restatement). Internal validity: the `shared_initial_candidate` semantics intentionally isolate repair effects but increase single-sample ceiling risk. Construct validity: `validator.valid` operationalizes mechanistic correctness but may not capture semantic intent misalignment. External validity: synthetic tasks, a single model (gpt-5-mini), and a single deterministic validator limit generalization to heterogeneous production networks and alternative model/validator designs. Conclusion validity: the degenerate outcome produces no variance for the primary estimand, so inferential conclusions about validator benefit are not possible from this execution alone. These limitations are explicit in the archived manifests and motivate the artifact-grounded follow-up arms described above.

VI. LIMITATIONS

- `Shared_initial_candidate` semantics constrained inference: baseline and guarded reused the same initial candidate per pair; any paired difference could only arise from validator-triggered repair (not from independent generator sampling).
- Synthetic task bank (difficulty 'very_hard'/'extreme') is not equivalent to heterogeneous production networks (multi-vendor devices, real ticket noise); external validity is limited.
- Single-model experiment: only gpt-5-mini was executed; no multi-model generality claims are made.
- No repairs were applied because all initial candidates passed the deterministic validator; therefore the study could not estimate repair effectiveness or validator false-negative behavior in this execution.
- Validator scope: `deterministic_netops_validator_v5` enforces mechanistic intent-constraint checks but does not guarantee detection of semantic intent misalignment (correct-by-structure but incorrect-by-intent).
- Recorded `execution/model_configuration.json` temperature = null/unset does not imply deterministic sampling; provider-side sampling behavior may vary and is documented in execution manifests.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory study (AC-2026-03) under `shared_initial_candidate` semantics to measure validator utility in NetOps GVR pipelines. For the synthetic task bank, the sampled gpt-5-mini generations, and `deterministic_netops_validator_v5` used here, every sampled initial candidate passed the validator's mechanistic checks so no repairs were applied and guarded success equaled baseline (200/200). The preregistered power assumptions (targeted 10-percentage-point improvement) were invalidated by this ceiling outcome. The result is artifact-grounded and reproducible from the archived bundle. We publish the exact execution

and analysis artifacts to support replication and provide concrete, preregistered experiment prescriptions (fault injection, multi-sample generation, multi-validator comparison) that are required to produce estimable validator FP/FN behavior and repair value in operationally meaningful conditions.

DISCLOSURE STATEMENT

Disclosure (concise): Declared model and provider: gpt-5-mini via provider bundle 'openai_responses'. Orchestration/adaptor: `hosted_netops_gvr_v1`. Deterministic validator: `deterministic_netops_validator_v5` (`validator_version` = 5.0). Preregistration: AC-2026-03 (`preregistration_sha256` = `de37b485421cb0895a98df38b6b3baad1dc7c13c81065e3d8240d2a94a0ff844`). Master prompt immutable reference: `provenance/master_prompt.txt`, SHA-256 = `1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582b39b15ba`. Autonomy boundary: a human Research Director selected the broad topic family and approved the master prompt before the autonomy lock; after the lock the AI system autonomously performed literature review, preregistration, experiment design, execution, analysis, internal peer review and manuscript drafting without manual editing of technical content. Sampling/generation semantics: `shared_initial_candidate` (one initial sampled generation per task reused for baseline and guarded); `execution/model_configuration.json` recorded temperature = null/unset (null/unset is not evidence of deterministic sampling and does not imply temperature = 0). Call budget and usage (preregistered): `maximum_model_calls` = 400; `actual_model_calls_used` = 200 (one shared initial generation per pair). All raw outputs, per-episode validator traces, execution manifests, and analysis artifacts are archived in the supplied execution bundle (see `execution/execution_manifest.json`). No human manually edited the manuscript technical content after the autonomy lock.

REFERENCES

- [1] R. Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments," *SSRN Electronic Journal*, 2026. doi:10.2139/ssrn.6754899.
- [2] K.-H. Tseng, N. Bogahawatta, Y. Ginige, K. Patel, K. Dacic, S. Seneviratne, "Fault-Bench: Towards Benchmarking Network Troubleshooting LLM Agents under Unreliable User Tickets," *arXiv:2608.27021*, 2026.
- [3] Y. Liu, C. Pei, L. Xu, B. Chen, M. Sun, Z. Zhang, Y. Sun, S. Zhang, K. Wang, H. Zhang, J. Li, G. Xie, X. Wen, X. Nie, M. Ma, P. Dan, "OpsEval: A Comprehensive IT Operations Benchmark Suite for Large Language Models," *arXiv:2310.07637*, 2023.
- [4] R. S. Babu and A. Agrawal, "Self-Healing Agentic Orchestrators for Reliable Tool-Augmented Large Language Model Systems," *arXiv:2606.01416*, 2026.
- [5] H. Zhou, C. Hu, Y. Yuan, Y. Cui, Y. Jin, C. Chen, H. Wu, D. Yuan, L. Jiang, D. Wu, X. Liu, J. Zhang, X. Wang, J. Liu, "Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities," *IEEE Commun. Surveys & Tutorials*, 2024. doi:10.1109/COMST.2024.3465447.