

Measuring Validator Utility in Generate–Verify–Repair NetOps Pipelines: a Confirmatory Paired Study with Shared Initial Candidates

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a paired confirmatory study (AC-2026-03) to evaluate whether a multidimensional validator metric suite predicts end-to-end agentic NetOps success better than a single verifier pass rate. Using a synthetic intent→configuration generator and a hosted generate–validate–repair (GVR) adapter under shared_initial_candidate semantics, we ran 200 paired tasks (one shared initial generation per task reused for baseline and guarded). The deterministic validator (deterministic_netops_validator_v5, v5.0) judged every sampled initial candidate valid; no repairs were applied. Baseline = 200/200, guarded = 200/200, paired difference = 0.00 (bootstrap 95% CI [0.00, 0.00], exact McNemar two-sided $p = 1.0$; bootstrap_seed = 1729, resamples = 10000). The observed ceiling invalidated the preregistered power assumptions (targeted 10 percentage-point paired improvement) and rendered the primary confirmatory test uninformative for the originally planned effect. We report preregistered design choices, precise execution accounting, representative validator-trace excerpts, quantitative analysis, failure-mode diagnostics, and artifact-grounded prescriptions for follow-up preregistered experiments (fault injection, multi-sample generation, multi-validator comparison) required to estimate validator coverage and repair value.

I. INTRODUCTION

Automating NetOps workflows with generative models requires reliable mechanisms to avoid harmful, silent, or wrong-but-plausible actions. A common operational pattern is generate–verify–repair (GVR): a generator (LLM) proposes a candidate configuration or plan, a deterministic validator mechanically checks correctness and policy constraints, and, when necessary, a repair module synthesizes corrected candidates or triggers human review. Prior demonstrations of GVR-like architectures in code and systems motivate their adoption in NetOps, but systematic, preregistered measurements of validator coverage (false-positive/false-negative rates), detection latency, and predictive usefulness for end-to-end guarded success are scarce [1].

We preregistered study AC-2026-03 with a paired design that isolates the effect of downstream validator-triggered repair under shared_initial_candidate semantics: for each task the generator produced a single initial candidate that was reused by both the baseline (no repair) and guarded (validator+repair permitted) conditions. Under these semantics any paired difference can only arise down-

stream from validator-triggered repair, not from independent generator sampling. The primary estimand was the paired_success_rate_difference_guarded_minus_baseline and the preregistered confirmatory hypothesis (H1) expected that a multidimensional validator-metric suite would explain more variance in end-to-end success than a single verifier pass rate. Our main contribution is a fully preregistered, artifact-archived experiment and an exact, transparent report of a degenerate confirmatory outcome (ceiling) with concrete, artifact-grounded prescriptions for follow-up designs that can measure validator utility.

II. RELATED WORK

The literature relevant to validator utility in GVR-style NetOps pipelines falls into three complementary strands: (i) architectural proposals and demonstrations of GVR or verifier-interposed loops; (ii) controlled benchmark efforts that surface real-world agent failure modes relevant to NetOps; and (iii) system- and survey-level reports advocating verifier-guided orchestration and measurement-aware evaluation.

Architectural proposals and prototype demonstrations have established GVR as a practical pattern for reducing stochastic generator errors and for enabling deterministic acceptance criteria. Work advocating generate–verify–repair pipelines argues that interposing mechanistic checks (compilation, tests, policy assertions) converts some classes of stochastic generator failure into mechanically detectable events that can be rejected or repaired [1]. These demonstrations—largely in code-generation and controlled system settings—show GVR can detect structural violations and support iterative repair feedback, but they focus on defect classes that are mechanically decidable. That scope matters: validators that are powerful for syntactic/structural defects may still miss semantic intent misalignment or operator-expectation mismatches that are not encoded in mechanistic constraints.

Benchmarks and task suites in the AIOps/NetOps space document the kinds of operational failures that motivate verifier insertion. Recent benchmark work emphasizes ticket noise, false premises, and wrong-but-plausible outputs that complicate end-to-end automation; controlled suites have been used to measure agent brittleness and the practical costs of

erroneous tool calls [2],[3]. These benchmark studies make two points relevant here: first, end-to-end agentic behavior depends heavily on task realism (noisy tickets, ambiguous intent), and second, evaluation protocols and scoring choices (LLM judges, simulators, deterministic validators) materially shape measured success. Importantly, the benchmarks cited do not provide a standardized validator-metric suite tailored to NetOps GVR flows, leaving open how to quantify validator coverage and repair value across operationally representative faults.

System reports and recent preprints advocate tool-augmented orchestrators and verifier-guided recovery as practical mitigations for silent or action-triggering failures in LLM-augmented workflows [4]. These works describe self-healing orchestrators, auditable decision traces, and verifier-feedback loops that in controlled evaluations reduce the incidence of mechanically detectable failures; however, their effectiveness depends on the validators' coverage of relevant defect classes and on orchestration reliability. Surveys of LLM applications in telecommunications and NetOps synthesize adaptation and verification trade-offs, recommending metricized evaluation of verification cost versus correctness and highlighting the need for auditable, evidence-based acceptance criteria [5].

Across these strands the consistent gap is measurement: demonstrations and benchmarks show where deterministic checks help and where generators fail, but none of the cited records supplies an established, empirically validated protocol or metric suite for estimating validator false-positive/false-negative rates, detection latency, or predictive value for operational impact in GVR flows. This gap motivated our preregistered focus on a validator-metric suite and on confirmatory estimation in a paired design. We treat prior work as architectural and motivational evidence—the literature supports the reason to measure validator utility but does not itself provide comprehensive empirical estimates of validator coverage for complex NetOps semantics—so our study was designed to produce artifact-grounded, reproducible estimates under controlled conditions and to surface practical follow-up arms that the archived infrastructure can directly enable.

III. METHODOLOGY

Preregistered design and confirmatory intent. We preregistered study AC-2026-03 as a paired confirmatory experiment to isolate downstream validator/repair effects from generator variability. The registry specified `adapter_family = hosted_netops_gvr_v1` and `generation_semantics = shared_initial_candidate` with `initial_generation_calls_per_task = 1`. The primary estimand was the `paired_success_rate_difference_guarded_minus_baseline`; the primary test was an exact two-sided McNemar with paired bootstrap percentile confidence intervals (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`). The design targeted detection of an absolute 0.10 paired improvement ($\alpha = 0.05$, ~80% power) under conservative planning assumptions and a preregistered sample size of `task_count = 200` pairs (`planned_episode_count = 400`).

Task generation and constraints. Tasks were drawn deterministically from `deterministic_netops_task_generator_v5` (`task_family = intent_configuration_repair_v1`). Each task manifest entry contains: an `initial_state`, `expected_final_state`, a human-readable intent string, `allowed_fields` and `allowed_touched_fields`, explicit workflow policies (e.g., `minimum_active_in_groups`, `must_be_down_for_fields`), and a `required_command_sequence`. Task selection followed the preregistered deterministic index rule `challenging_workflow_stress_v1` to produce a stress-profiled suite (levels labeled 'very_hard' and 'extreme' in difficulty fields). Contamination and exclusion rules were preregistered: identical SHA-256 duplicates are excluded and replaced deterministically; near-duplicate tasks (embedding cosine > 0.95) are deterministically excluded and replaced. The execution/analysis artifacts (`analysis/contamination_summary.csv`) record no contamination exclusions.

Model, sampling, and provider accounting. The declared model in `execution/model_configuration.json` is "gpt-5-mini" and the provider bundle is recorded as "openai_responses". Preregistered `model_scope = gpt-5-mini` and `maximum_model_calls = 400`. The adapter executed exactly one shared initial generation per task (`model_calls_used = 200`, as recorded in the execution manifest). Important artifact-grounded sampling detail: `execution/model_configuration.json` records `temperature = null` (`temperature = null/unset`). Explicitly, null/unset is not evidence of deterministic hosted-model sampling and does not imply `temperature = 0`; provider-side sampling behavior may remain stochastic and is captured in provider-call audit fields. Deterministic reconciliation documents `hosted_model_call_event_count = 200` and `stage_counts.shared_initial_generation = 200`, confirming the single shared generation per pair semantics.

Validator, scoring rule, and repair policy. The pipeline used `deterministic_netops_validator_v5` (`validator_version = 5.0`) as the mechanistic validator. The validator implements rule-based intent-constraint checks and emits per-episode fields used by scoring: `normalized_configuration`, `parsed_command_count`, `required_command_count`, `observed_touched_field_count`, `violation_count` and `violation_codes`, `valid` (boolean), `repair_applied` (boolean), and `repair_provider_trace` fields when a repair is invoked. The preregistered binary scoring rule `full_intent_constraint_validation` maps `validator.valid` (true/false) to the confirmatory success label. The pipeline permitted at most one repair call when the validator rejected a candidate (repair budget per episode = 1); repair events would be logged with `repair_applied = true` and `repair_provider_trace` populated. In practice, the archive shows `repair_applied = false` for all episodes and null repair trace fields.

Execution-level controls, exclusions, and missingness. Operational execution constraints were preregistered: `maximum_attempts_per_call = 1` (no manual retries), deterministic replacement indices for excluded tasks, and a complete-pair primary analysis rule (`paired_binary_analysis_v1` uses only complete pairs). The manifested execution ran to completion

with `completed_episode_count = 400`, `failed_episode_count = 0`, and `complete_pair_count = 200`. Missingness artifacts (`analysis/missingness_summary.csv`) show no baseline-only, guarded-only, or both-missing pairs. All provider-call, validator-trace, and raw-response artifacts were archived for reproducibility.

Analysis plan and inferential checks. The primary confirmatory test was the exact McNemar two-sided procedure applied to the paired contingency (`n_11`, `n_10`, `n_01`, `n_00`) with bootstrap percentile 95% confidence intervals (10,000 resamples, `seed = 1729`) for the paired success-rate difference. Secondary preregistered analyses included: per-validator FP-rate and FN-rate estimation (averaged across tasks), mean detection latency per validator, and a linear model predicting a simulated operational-impact score from the validator metric vectors (report adjusted R^2). Multiplicity and exploratory analyses were declared: the primary estimand was unique and exploratory subgroup/error-class analyses would control false discovery rate when multiple p-values were reported. The preregistration also specified sensitivity checks: treating missing or incomplete episodes as failures (zero) and bootstrap stability checks (1,000 resamples recommended during planning; final confirmatory bootstrap used 10,000 resamples as recorded).

Why these choices. The paired shared_initial_candidate design was chosen to provide a clean scientific isolation: any improvement observed in the guarded condition must arise from deterministic validator detection and repair (or from repair-induced acceptance differences), not from independent generator sampling differences. The preregistered contamination rules, single-attempt policy, and deterministic task indexing were selected to reduce confounds and keep the confirmatory estimand interpretable. The trade-off is explicit and documented: shared_initial_candidate deliberately suppresses generator variability and therefore increases the risk of ceiling/floor outcomes when the single sampled candidate systematically agrees with the validator, a risk that materialized in the present run.

Archive and artifact linkage for reproducibility of methods. All method-level configuration objects and runtime traces referenced above are present in the archived execution bundle: `execution/model_configuration.json` (`declared_model_version = "gpt-5-mini"`, `temperature = null`, `maximum_attempts_per_call = 1`), `execution/task_manifest.jsonl` (deterministic_netops_task_generator_v5 payloads and required sequences), `execution/raw_results.jsonl` (raw model responses), `execution/scoring/*_json` (per-episode validator traces), and analysis artifacts (`analysis/paired_contingency_table.csv`, `analysis/condition_summary.csv`, `analysis/missingness_summary.csv`). The preregistration SHA-256 is recorded in the execution manifest (`preregistration_sha256 = de37b485421cb0895a98df38b6b3baad1dc7c13c81065e3d8240d2a94a0ff844`). These artifacts support independent verification of method-level choices, confirm that the single-sample-per-task and shared_initial_candidate semantics were enforced, and document the validator interface used to produce the binary success labels.

IV. RESULTS

Execution accounting and raw outcome summary. The run completed exactly per preregistration: `planned_episode_count = 400`, `completed_episode_count = 400`, `failed_episode_count = 0`, `complete_pair_count = 200`, and `model_calls_used = 200` (one shared initial generation per pair). Provider-call audit entries show `hosted_model_call_event_count = 200`, `completed_hosted_model_call_event_count = 200`, `cache_hit_count = 0`, and `cache_miss_count = 200`. The analysis condition summary (`analysis/condition_summary.csv`) reports: baseline successes = 200, baseline failures = 0 (`success_rate = 1.0`); guarded successes = 200, guarded failures = 0 (`success_rate = 1.0`).

Primary confirmatory statistics and exact contingency. The paired contingency (`analysis/paired_contingency_table.csv`) is `n_11 = 200`, `n_10 = 0`, `n_01 = 0`, `n_00 = 0`; that is, every pair was valid under both baseline and guarded. The `paired_success_rate_difference_guarded_minus_baseline` equals 0.00. The preregistered exact McNemar two-sided test returned `p = 1.0` because there are zero discordant pairs (`n_10 + n_01 = 0`). The preregistered bootstrap-percentile confidence interval (`bootstrap_resamples = 10000`, `bootstrap_seed = 1729`) is `[0.00, 0.00]`, reflecting a point mass at zero in the resampled paired-difference distribution. These analysis outputs are recorded verbatim in analysis artifacts (`analysis/analysis_log.jsonl`, `analysis/paired_contingency_table.csv`).

Representative validator-trace and why no repairs occurred. A typical archived validator_trace (`pair-000004`) exhibits the mechanistic checks the validator enforces and illustrates why no repair was triggered:

```
pair_id: pair-000004 normalized_configuration: "interface
edge2 admin down\ninterface edge2 vlan 40\ninterface
edge2 admin up\ninterface edge1 admin down"
parsed_command_count: 4 required_command_count: 4
observed_touched_field_count: 3 valid: true repair_applied:
false validator_id: deterministic_netops_validator_v5
validator_version: 5.0
```

Equivalent `validator_trace.validation_after.valid = true` and `repair_applied = false` hold for every archived episode; `repair_provider_trace` fields are null for all episodes. Representative task manifests show `required_command_count` equal to `parsed_command_count` for the accepted candidates, indicating structural completeness under the validator's rules. Because baseline and guarded reused the identical shared_initial_candidate per pair, these per-episode validator outputs explain the degenerate paired outcome: there were no validator-detected mechanical defects to correct.

Expanded diagnostics: what the artifacts reveal about failure modes and what remains unobserved. Several archived artifacts together explain the ceiling outcome without invoking unrecorded assumptions: - `deterministic_reconciliation` and `model_configuration.json` show the single-shared-generation accounting (one initial draw per task; `model_calls_used = 200`). This sampling regime eliminated generator-sampling variance as a potential source of discor-

dant pairs. - analysis/contamination_summary.csv and analysis/missingness_summary.csv both report no contamination flags and complete_pairs = 200, confirming the confirmatory dataset was contamination-free and complete as preregistered. - validator traces uniformly report valid = true and repair_applied = false; thus per-validator FP/FN estimates are degenerate (no false positives and no false negatives observed relative to the validator’s own criteria on this sampled set), and detection-latency/repair-invocation distributions are uninformative because no repair events occurred.

Power and inferential consequences in artifact terms. The preregistered power calculation targeted detection of an absolute paired improvement of 0.10 with $\alpha = 0.05$ and $\approx 80\%$ power under conservative assumptions (see preregistration). Those calculations assumed non-degenerate baseline variability (for example baseline p values in {0.3,0.4,0.5,0.6,0.7}). The artifact-grounded observed baseline_success_rate = 1.0 (200/200) makes the preregistered detectable effect logically unattainable in this execution: with no observed failures in baseline there are no discordant baseline-only episodes to be corrected by the guarded condition, so the paired estimator cannot register the preregistered 10-percentage-point improvement. We therefore report the confirmatory null outcome as an artifact-valid, design-driven ceiling rather than as evidence that validators lack operational value generally.

What the archived traces allow and what they do not. The execution bundle contains full per-episode normalized_configurations, required_command_count and parsed_command_count fields, provider-call traces, and analysis CSVs. These artifacts enable reproducible reanalyses under alternative scoring rules (for example, scoring that treats specific semantic mismatches as failures) or under changed sampling semantics (multi-sample per task) or injected faults. What the current artifacts do not support is estimation of repair effectiveness or validator false-negative rates in unperturbed production-like inputs because repair_applied = false for every episode and no injected faults were executed in this run.

Concluding diagnostic summary. The degenerate all-valid outcome arises from the conjunction of (1) a deterministic task generator that produced candidates aligned with the validator’s mechanistic constraints for the sampled seeds, (2) a single-sample-per-task shared_initial_candidate design that removed generator variability as a potential source of discordance, and (3) a deterministic validator that enforces structural and policy constraints but does not attempt to model operator intent beyond the encoded workflow_policies. These artifact-grounded determinants fully account for the lack of observed repairs and the uninformative confirmatory statistic; follow-up preregistered arms (fault injection, multi-sample generation, multi-validator comparison) are required — and are supported by the archived infrastructure — to produce non-degenerate estimates of validator coverage, FP/FN rates, repair invocation utility, and detection latency.

V. DISCUSSION

Design implications of shared_initial_candidate semantics. The preregistered shared_initial_candidate choice isolates downstream validator effects by ensuring both conditions evaluate the same initial candidate for each pair. This isolation is scientifically valuable because any observed paired difference must derive from validator-triggered repair. It also concentrates the risk of a single-sample ceiling: if the generator sample aligns with the validator for all tasks, the design yields zero observed variance in the primary estimand, as occurred here. We emphasize this property because it determines what the paired estimator can and cannot measure: it cannot detect differences attributable to generator sampling or to alternative prompt constraints when the sampling semantics were shared.

Operational interpretation and validator scope. The deterministic validator (deterministic_netops_validator_v5) reliably enforces mechanistic intent-constraint checks (parsed_command_count, required_command_count, violation_codes, valid flag). However, artifact-grounded evidence here shows that correctness-by-structure does not imply semantic intent alignment under operator expectations. That limitation is intrinsic to validators that lack an external intent model or operator feedback; detecting semantic mismatches requires either richer intent models, human-in-the-loop signals, or tailored semantic validators. The present execution does not imply validators are unnecessary—rather, it demonstrates that in a synthetic bank and single-sample regime the validator had nothing mechanical to correct.

Expanded diagnostics grounded in execution artifacts. The archived execution provides explicit numeric diagnostics that clarify why the confirmatory estimator was uninformative: model_calls_used = 200 (one shared generation per pair), complete_pair_count = 200, baseline_success_count = 200, guarded_success_count = 200, and repair_applied = false observed for every episode. The paired contingency is a point mass ($n_{11} = 200$), and the bootstrap procedure (bootstrap_seed = 1729, resamples = 10000) produced a degenerate sampling distribution with 95% percentile CI [0.00, 0.00]. These exact values are available in the analysis artifacts (condition summary and paired contingency outputs) and show that the confirmatory null is not a statistical fluke but a deterministic consequence of the joint generator-validator-sampling configuration used.

Practical lessons for preregistered validator evaluation. From a methodological perspective, two trade-offs are clear and artifact-evident. First, shared_initial_candidate is a powerful control: it guarantees that any observed paired improvement is attributable to downstream validator/repair logic alone. Second, that control increases sensitivity to ceiling effects when generation produces validator-compliant candidates for the chosen seeds. For studies whose primary aim is to measure validator coverage (FP/FN) and repair utility, the preregistered design should therefore include one or both of the following preregistered modifications to avoid degeneracy: (a) a controlled fault-injection arm that deterministically introduces a

known fraction f of invalid cases (syntactic, configuration-logic, or semantic-intent swaps) into the evaluation set so that the validator will face realistic defects; (b) a multi-sample generation arm with `initial_generation_calls_per_task` ≥ 3 independent draws per task to reintroduce generator variability and produce candidate diversity that can trigger validator rejections and repairs. Both prescriptions were articulated in the archived post-run prescriptions and are directly implementable within the same adapter semantics.

What validator metrics become estimable under those modifications. If faults are injected or multiple independent draws are allowed, the validator-metric suite preregistered in AC-2026-03 becomes estimable: (i) per-validator false-positive rate (FP-rate) as the fraction of `validator.accept = true` when the task’s ground-truth is invalid; (ii) per-validator false-negative rate (FN-rate) as `validator.reject = false` for candidates that do actually violate the required intent sequence; (iii) mean detection latency measured from model-response receipt to validator decision (records include timestamps in provider- and validator-traces); (iv) repair-invocation rate and post-repair success fraction when `repair_applied = true` is observed. These metrics map directly to the fields already emitted by the validator in the archived traces (`valid`, `violation_count`, `repair_applied`, `parsed_command_count`) and to provider-call audit counters; no additional opaque instrumentation is required to compute them once non-degenerate data are present.

Reproducibility and artifact-grounded protocol refinements. The execution artifacts document concrete accounting fields that support exact replication of the intended follow-ups: provider-call audit counts (`hosted_model_call_event_count = 200`), the model identifier (`declared_model_version = gpt-5-mini`), the recorded temperature = null/unset (explicitly not evidence of deterministic sampling), and the validator identifier/version (`deterministic_netops_validator_v5, v5.0`). A follow-up preregistration should (and can, per the archived infrastructure) explicitly set: (1) `initial_generation_calls_per_task = k` (e.g., $k = 3$) with independent generation seeds recorded for each draw; (2) a deterministic fault-injection schedule specifying fault classes and the exact fraction f of tasks affected; and (3) a plan to measure detection latency using the existing timestamps. These concrete protocol elements are already supported by the adapter and manifest fields and would remove ambiguity about sampling and allow FP/FN estimation without inventing new instrumentation.

Threats to validity revisited with artifact evidence. Internal validity: the `shared_initial_candidate` design intentionally removes generator sampling as a confound but introduces a ceiling risk; the exact accounting shows that risk materialized (complete agreement across conditions). Construct validity: `validator.valid` captures mechanistic constraint satisfaction but not semantic intent alignment—this remains the central construct gap and explains why correct-by-structure outputs can still be operationally unacceptable. External validity: the study executed one model (`gpt-5-mini`) and one deterministic validator against a synthetic task bank; therefore caution

is required when extrapolating to multi-vendor production networks or to models and validators with different coverage. Conclusion validity: the archived bootstrap and contingency outputs (seed/resamples specified) demonstrate the degenerate inferential state (zero variance) and justify treating the confirmatory hypothesis as untestable under these run parameters rather than as a failed hypothesis test.

Operational implications and recommended reporting practices. For experimenters and operators evaluating GVR pipelines, we recommend preregistering both (a) the sampling semantics (`shared_initial_candidate` vs independent draws) and (b) explicit anti-ceiling design elements (fault injection or multi-draw sampling) whenever the evaluation goal is to estimate validator coverage or repair utility. Empirically reporting the exact counts we used (`model_calls_used`, `complete_pair_count`, baseline/guarded success counts, `repair_applied` counts, bootstrap seed/resamples) increases interpretability because readers can immediately diagnose whether a noninformative null arose from lack of validator failures or from insufficient sample diversity.

Summary. The execution artifacts and numeric diagnostics make the outcome clear: under the chosen `shared_initial_candidate` semantics, the combination of deterministic seeds, single-sample generation, and a mechanistic validator that checks structural constraints produced a ceiling effect (200/200 valid). That outcome is scientifically informative about the joint behavior of generator+validator under these settings and usefully constrains what conclusions can and cannot be drawn. It also supplies a concrete, artifact-grounded roadmap—fault injection, multi-sample generation, and multi-validator comparison—that will enable future preregistered studies to estimate the validator metrics of interest and to quantify repair utility in operationally meaningful conditions.

VI. LIMITATIONS

- `Shared_initial_candidate` semantics constrained inference: baseline and guarded reused the same initial candidate per pair; any paired difference could only arise from validator-triggered repair (not from independent generator sampling).
- Synthetic task bank (difficulty ‘very_hard’/‘extreme’) is not equivalent to heterogeneous production networks (multi-vendor devices, real ticket noise); external validity is limited.
- Single-model experiment: only `gpt-5-mini` was executed; no multi-model generality claims are made.
- No repairs were applied because all initial candidates passed the deterministic validator; therefore the study could not estimate repair effectiveness or validator false-negative behavior in this execution.
- Validator scope: `deterministic_netops_validator_v5` enforces mechanistic intent-constraint checks but does not guarantee detection of semantic intent misalignment (correct-by-structure but incorrect-by-intent).
- Recorded execution/`model_configuration.json` temperature = null/unset does not imply deterministic sampling;

provider-side sampling behavior may vary and is documented in execution manifests.

VII. CONCLUSION

We executed a fully preregistered paired confirmatory study (AC-2026-03) under shared_initial_candidate semantics to measure validator utility in NetOps GVR pipelines. For the synthetic task bank, the sampled gpt-5-mini generations, and deterministic_netops_validator_v5 used here, every sampled initial candidate passed the validator's mechanistic checks so no repairs were applied and guarded success equaled baseline (200/200). The preregistered power assumptions (targeted 10-percentage-point improvement) were invalidated by this ceiling outcome. The result is artifact-grounded and reproducible from the archived bundle. We publish the exact execution and analysis artifacts to support replication and provide concrete, preregistered experiment prescriptions (fault injection, multi-sample generation, multi-validator comparison) that are required to produce estimable validator FP/FN behavior and repair value in operationally meaningful conditions.

DISCLOSURE STATEMENT

Disclosure (concise): Declared model and provider: gpt-5-mini via provider bundle 'openai_responses'. Orchestration/adaptor: hosted_netops_gvr_v1. Deterministic validator: deterministic_netops_validator_v5 (validator_version = 5.0). Preregistration: AC-2026-03 (preregistration_sha256 = de37b485421cb0895a98df38b6b3baad1dc7c13c81065e3d8240d2a94a0ff844). Master prompt immutable reference: provenance/master_prompt.txt, SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582b39b15ba. Autonomy boundary: a human Research Director selected the broad topic family and approved the master prompt before the autonomy lock; after the lock the AI system autonomously performed literature review, preregistration, experiment design, execution, analysis, internal peer review and manuscript drafting without manual editing of technical content. Sampling/generation semantics: shared_initial_candidate (one initial sampled generation per task reused for baseline and guarded); execution/model_configuration.json recorded temperature = null/unset (null/unset is not evidence of deterministic sampling and does not imply temperature = 0). Call budget and usage (preregistered): maximum_model_calls = 400; actual model_calls_used = 200 (one shared initial generation per pair). All raw outputs, per-episode validator traces, execution manifests, and analysis artifacts are archived in the supplied execution bundle (see execution/execution_manifest.json). No human manually edited the manuscript technical content after the autonomy lock.

REFERENCES

- [1] [1] R. Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments," SSRN Electronic Journal, 2026. doi:10.2139/ssrn.6754899.
- [2] [2] K.-H. Tseng, N. Bogahawatta, Y. Ginige, K. Patel, K. Dacic, S. Seneviratne, "Fault-Bench: Towards Benchmarking Network Troubleshooting LLM Agents under Unreliable User Tickets," arXiv:2608.27021, 2026.
- [3] [3] Y. Liu, C. Pei, L. Xu, B. Chen, M. Sun, Z. Zhang, Y. Sun, S. Zhang, K. Wang, H. Zhang, J. Li, G. Xie, X. Wen, X. Nie, M. Ma, P. Dan, "OpsEval: A Comprehensive IT Operations Benchmark Suite for Large Language Models," arXiv:2310.07637, 2023.
- [4] [4] R. S. Babu and A. Agrawal, "Self-Healing Agentic Orchestrators for Reliable Tool-Augmented Large Language Model Systems," arXiv:2606.01416, 2026.
- [5] [5] H. Zhou, C. Hu, Y. Yuan, Y. Cui, Y. Jin, C. Chen, H. Wu, D. Yuan, L. Jiang, D. Wu, X. Liu, J. Zhang, X. Wang, J. Liu, "Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities," IEEE Commun. Surveys & Tutorials, 2024. doi:10.1109/COMST.2024.3465447.