

Verifier-Grounded Generate-Verify-Repair for Intent→Configuration NetOps Tasks: A Paired Mininet Emulation Study

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We preregistered and executed a provenance-traced paired confirmatory study (N = 200 intents; 400 paired episodes) to evaluate whether a deterministic verifier-grounded generate–verify–repair (GVR) loop reduces operationally detectable policy-violation errors when a hosted LLM produces device configuration sequences from operator intent in a Mininet emulation. Execution used shared_initial_candidate semantics (one sampled initial generation per intent reused by both baseline and guarded). Baseline success (no detected policy violation) = 196/200 (98%); guarded success = 200/200 (100%). Paired risk difference (guarded - baseline) = 0.02; preregistered exact McNemar two-sided p = 0.125 (primary confirmatory test). An exploratory paired bootstrap (seed = 1729, 10,000 resamples) yields a 95% percentile CI = [0.005, 0.04]. Four verifier-triggered repairs occurred (total hosted model calls = 204), giving mean extra model calls per intent = 0.02 and mean extra calls per avoided violation = 1.0. All reported numeric values, provider-call accounting, validator traces, and analysis artifacts are drawn verbatim from the archived execution and analysis bundle. We interpret the preregistered confirmatory result conservatively and discuss construct, internal, and external validity limits and operational implications.

I. INTRODUCTION

Automating intent→configuration translation is an active NetOps research direction because natural-language or intent descriptions are a natural operator interface but can be transformed incorrectly by large language models (LLMs). Mechanically checkable faults introduced by LLMs—syntactic errors, topology/reachability violations, and ACL/policy mistakes—can lead to availability loss or exposure if applied to devices without validation [1], [4]. Generate–Verify–Repair (GVR) patterns pair an LLM generator with a deterministic verifier: the verifier checks mechanizable constraints and, if violations occur, issues localized diagnostics used to request corrective edits from the model [2], [3]. Prototype work across code and domain-specific program generation suggests verifier-grounded repair reduces mechanically verifiable errors; however, questions remain about scaling such pipelines to heterogeneous multi-vendor template families, the concrete hosted-LLM cost per avoided violation, and how to interpret paired comparisons when sampling semantics reuse the initial model candidate.

Research question and contribution. Our preregistered research question is: Does a verifier-grounded generate–verify–repair loop significantly reduce operationally detectable policy-violation errors produced by a hosted LLM when

generating network configurations for operator intents across heterogeneous multi-vendor template families and topology patterns in a Mininet-based emulation? Contributions: (1) a provenance-traced confirmatory paired experiment (C1-GVR-multivendor-2026-v1) with shared_initial_candidate semantics executed on N = 200 intents (400 episodes); (2) audited provider and verifier accounting showing repair costs and concrete hosted-model calls; (3) artifact-grounded statistical inference (exact McNemar test) and exploratory bootstrap interval (seed = 1729, 10,000 resamples); (4) a focused analysis of failure modes, threats to validity, and operationally grounded recommendations consistent with archived artifacts.

II. RELATED WORK

Recent surveys and reviews document rapid growth in LLM-for-NetOps and AIOps research while emphasizing recurring evaluation gaps—benchmark provenance, verifier integration, and limited multi-vendor emulation evidence [5], [6]. Empirical prototypes and benchmarks show that LLMs can draft device configurations or configuration-style artifacts, but they frequently produce mechanically checkable faults (syntax, missing or misordered commands, and reachability or policy violations) when evaluated on configuration translation tasks; these failure modes have been observed in domain-specific studies and NetOps benchmarks [1], [4].

A separate strand of work proposes and demonstrates verifier-grounded closed-loop architectures (generate→verify→repair) in coding and domain-specific program generation settings [2], [3]. These proposals and single-case or small-scale empirical demonstrations indicate that when (i) a deterministic verifier can express the relevant mechanizable constraints, and (ii) the verifier provides localized, actionable diagnostics, a bounded repair policy can reduce the incidence of mechanically verifiable errors. However, the cited records are prototype-scale: effectiveness depends on verifier expressivity, the class of detectable violations, and close coupling between verifier diagnostics and repair prompts; they do not by themselves establish broad production-scale safety or generality across heterogeneous vendor templates and topologies [2], [3].

Benchmark and evaluation work in NetOps highlights additional practical gaps. NetConfEval and related evaluations demonstrate feasibility of measuring LLM capability on configuration tasks, but these efforts commonly lack

provenance-traced verifier pipelines and do not reliably quantify multi-vendor template heterogeneity or cost metrics tied to verifier-triggered repairs [4]. The surveys cited above call for richer provenance, clearer operationally meaningful metrics, and higher-fidelity emulation in order to make comparative claims about reliability and to expose residual semantic failures that deterministic verifiers may miss [5], [6].

Taken together, the verified literature supports three tempered conclusions that motivate this study: (1) LLMs can produce useful draft configurations but commonly make mechanically checkable errors; (2) verifier-grounded repair is a recurring mitigation pattern with promising single-case evidence but limited large-scale cross-vendor validation; and (3) more provenance-traced, operationally framed experiments are required to quantify repair cost tradeoffs and the residual semantic errors outside verifier coverage. Our preregistered paired design directly targets these gaps by providing provenance-traced accounting, an explicit shared_initial_candidate execution semantics to isolate verifier/repair effects, and per-intent accounting of repair calls and final validator outcomes.

III. METHODOLOGY

Preregistration and formal estimand. We preregistered the study as C1-GVR-multivendor-2026-v1 before any model calls (preregistration SHA-256: 9e0fc992665835975b01289f7841926ef6abf3584252c5d0459ba0ecf166bb50). The primary estimand is the paired_success_rate_difference_guarded_minus_baseline: the per-intent difference in the probability that an intent produces zero operationally detectable policy violations under guarded (GVR) relative to baseline (LLM-only). The confirmatory test declared in the preregistration is the exact McNemar two-sided test at $\alpha = 0.05$ applied to the paired binary success indicators.

Sampling, stratification, and fixed sampling semantics. Task selection was deterministic and stratified across three synthetic vendor-template families and four topology patterns (12 strata). $N = 200$ unique operator intents were fixed by the deterministic task generator before any model calls (task_index_profile selection is recorded in the execution manifest). The preregistration and adapter execution contract explicitly used shared_initial_candidate semantics: exactly one sampled initial generation per intent was produced and this identical initial candidate was reused by both baseline and guarded episodes. Under these semantics the baseline outcome equals the deterministic validator verdict applied to that shared initial candidate; the guarded outcome equals the final result of the guarded pipeline after deterministic validation and any permitted repair. The preregistration also declared that independent constrained-prompt arms were not executed; therefore any within-pair differences can arise only from deterministic validator actions and permitted repair calls, not from different first-pass samples or different initial prompts.

Model configuration, sampling notation, and budgetary constraints. The declared archived model is gpt-5-mini

(provider recorded as openai_responses) and the adapter enforced a strict call budget: planned_episode_count = 400, initial_generation_calls_per_task = 1, maximum_repair_calls_per_task = 1, maximum_model_calls = 400. The archived execution model_configuration.json records temperature = null (unset). We explicitly state: temperature = null/unset is not evidence of deterministic hosted-model sampling and does not imply temperature = 0. Because provider sampling semantics are external to the adapter, we treat the single shared initial generation per intent as the executed stochastic sample; subsequent guarded repairs (if any) are additional provider calls permitted only by the predeclared repair policy.

Deterministic verifier design and scoring rule. The deterministic_netops_validator_v5 is a rule-based verifier implemented to mechanistically evaluate intent→configuration candidates. Its functional components (all coded as deterministic checks applied to the candidate configuration and the emulated Mininet state) include: 1) syntactic parsing and command-pattern conformance (token-level grammar and per-vendor command templates); 2) required-command sequencing and workflow policy checks driven by the per-task payload (e.g., ordered steps, protected interfaces, minimum-active constraints); 3) reachability and topology consistency checks that compare the candidate’s intended final state against the emulated network topology and device states; 4) ACL and policy encodings derived from task payload constraints (checks for forbidden field changes or prohibited sequences that would violate policy). The verifier returns a structured trace: validation_before (diagnostic list and violation codes), a binary validity verdict (valid: true/false), and, when violations are present and repair is permitted by policy, a localized diagnostic summary that is included verbatim in the repair prompt. The scoring rule full_intent_constraint_validation yields success = 1 only when the final validated configuration satisfies all mechanizable constraints.

Repair policy and prompt semantics. The guarded pipeline applies a conservative bounded repair policy as preregistered: if and only if the verifier reports violations on the shared initial candidate, at most one verifier-triggered repair call may be issued. Repair prompts include (a) the original shared initial candidate, (b) the verifier’s localized diagnostic messages (violation codes and minimal context identifying implicated commands/fields), and (c) an explicit instruction to produce a corrected configuration that satisfies the listed constraints. Repairs were allowed only when the verifier flagged violations and were restricted to a single additional hosted-model call per intent to preserve the predeclared budget and to evaluate cost per avoided violation.

Scoring, exclusions, and missingness treatment. The primary confirmatory analysis treats the pairwise binary success indicators (no detected violations after the pipeline completes for baseline and guarded) per the preregistration. Predeclared exclusion rules removed duplicate tasks detected via deterministic prompt+context hashing and episode pairs aborted due

to unrecoverable infrastructure/container substitution failures; such exclusions would be reported (none occurred in the archived run). Ambiguous verifier outputs (diagnostics flagged by deterministic ambiguity rules) were conservatively treated as violations in the primary analysis (this conservative rule was preregistered). The missingness plan treated genuine infrastructure/API failures as missing-at-random for the primary test; a sensitivity analysis treating failures as conservative failures was predeclared.

Analysis plan and resampling specifics. The preregistered primary inferential procedure is the exact McNemar two-sided test applied to the 2×2 paired contingency table (n_{11} , n_{10} , n_{01} , n_{00}). Secondary and exploratory estimators declared in the preregistration include: (i) a paired bootstrap percentile 95% confidence interval for the paired risk difference (bootstrap_seed = 1729; bootstrap_resamples = 10,000), and (ii) descriptive cost metrics (mean extra hosted model calls per intent and mean extra calls per avoided violation). We note that bootstrap percentile intervals can be unstable when discordant pair counts ($n_{10} + n_{01}$) are small; this instability motivated treating the McNemar exact test as the formal confirmatory inference and labeling the bootstrap interval exploratory in the manuscript.

Provider accounting, auditability, and reproducibility artifacts. The experiment’s adapter recorded a provider-call audit: planned_maximum_model_calls = 400; hosted_model_call_event_count was auditable in the execution manifest (the adapter records stage_counts and condition_counts). The preregistration required recording all raw provider responses, verifier traces, repair prompts, deterministic task manifests, and an execution manifest; these artifacts were archived for machine verification. Analysis code, seeds, and exact resampling parameters were archived to enable deterministic replication of the reported numerical analyses.

Why shared_initial_candidate semantics matters for causal interpretation. We emphasize that because the archived run used shared_initial_candidate semantics and permitted at most one repair call per intent, the paired comparison isolates the effect of deterministic verification and the bounded repair step on the shared initial sample. In this design baseline is not an independent generation arm; it is the validator’s direct verdict on the sampled candidate. Any between-condition improvements within a pair therefore must arise from validator-triggered repair converting a failing shared initial candidate into a passing final configuration, not from differing initial samples or alternative prompting.

Implementation and operational controls. The adapter enforced deterministic task ordering and recorded task indices prior to model calls. Repair prompts were templated and deterministic given the verifier diagnostics; repair calls were logged with the exact repair prompt text and provider response. The deterministic verifier and task generator versions used in the run (deterministic_netops_validator_v5 and deterministic_netops_task_generator_v5) are recorded in the archived model and artifact manifests to permit exact replay of the

pipeline on the same synthetic task bank and emulation state. All numerical quantities reported in Results (model_call counts, stage_counts, and contingency table cells) are drawn from those archived manifests and reconciled in the deterministic_reconciliation artifact.

IV. RESULTS

Execution completion and deterministic accounting. The preregistered run completed without infrastructure exclusions: planned_episode_count = 400, completed_episode_count = 400, complete_pair_count = 200, failed_episode_count = 0 (execution manifest). Audited provider accounting (deterministic_reconciliation) reports hosted_model_call_event_count = 204; this decomposes deterministically into stage_counts = {shared_initial_generation: 200, repair: 4} and condition_counts recorded as {shared: 200, guarded: 4} in the manifest. Cache statistics show cache_hit_count = 0 and cache_miss_count = 204, confirming that every required hosted call executed and that the four repair calls were distinct provider calls. All deterministic consistency checks passed in the reconciliation artifacts.

Paired binary outcomes and primary confirmatory test. The preregistered paired contingency (analysis/paired_contingency_table.csv) is $n_{11} = 196$, $n_{10} = 4$, $n_{01} = 0$, $n_{00} = 0$. These cells yield baseline_success_rate = $196/200 = 0.98$ and guarded_success_rate = $200/200 = 1.00$; the paired risk difference (guarded - baseline) = 0.02. The preregistered exact McNemar two-sided test on these paired indicators returned $p = 0.125$ (analysis results). Under the preregistered inferential contract this p -value means we do not reject the null at $\alpha = 0.05$.

Repair events, candidate reuse, and per-intent cost accounting. The stage decomposition (200 shared initial generation events + 4 repair events) matches the model-call audit and demonstrates that the guarded pipeline invoked repairs for exactly four intents. From these audited counts we compute total_model_calls = 204, mean_model_calls_per_intent = $204/200 = 1.02$, mean_extra_calls_per_intent_due_to_repairs = $4/200 = 0.02$. Because each repair converted one failing baseline into a passing guarded outcome in the archived contingency, the observed mean_extra_calls_per_avoided_violation = 4 repairs / 4 avoided violations = 1.0. These arithmetic derivations follow directly from the archived execution manifest and deterministic reconciliation artifacts.

Shared_initial_candidate evidence and representative artifact substantiation. Representative task artifacts included in the evidence bundle show explicit reuse of the same sampled initial generation by both baseline and guarded episodes. For example, the representative tasks (task-000004, task-000005, task-000006, etc.) exhibit identical shared_initial_candidate contents and identical shared_initial response file SHA-256 values across their baseline and guarded response artifacts. The archived validator_trace fields for the discordant pairs record validation_before entries showing violations and validation_after entries showing repair_applied = true with final vali-

validation_after.valid = true; the bundle therefore substantiates that the four discordant cases were resolved by verifier-triggered repairs operating on the identical initial candidate.

Diagnostic pattern observed in discordant pairs. In every archived discordant pair the validator_trace shows a mechanizable violation detected in validation_before (violation_count > 0 and violation_codes returned by deterministic_netops_validator_v5) and a subsequent repair application that produced a final configuration satisfying full_intent_constraint_validation. The manifest and per-task scoring artifacts indicate that repairs were only issued for intents where the verifier produced explicit, localized diagnostics; no repair calls occurred for intents without detected violations. The archived traces therefore support the causal pathway: identical initial candidate → verifier detects mechanizable violation → single permitted repair call → final guarded configuration passes deterministic validation.

Exploratory bootstrap interval and interpretation caution. The archived exploratory paired bootstrap (bootstrap_seed = 1729; resamples = 10,000) produced a 95% percentile bootstrap CI for the paired risk difference = [0.005, 0.04]. We report this interval as exploratory only. Practically, the bootstrap percentile CI in paired binary settings relies on resampling paired outcomes and can be unstable when the total number of discordant pairs ($n_{10} + n_{01}$) is small; here $n_{10} + n_{01} = 4$ is small, which reduces the bootstrap’s reliability as a standalone uncertainty summary. Accordingly, we treat the exact McNemar test as the prespecified confirmatory inference ($p = 0.125$) and use the bootstrap interval only to convey plausible effect-size magnitudes suggested by the archived data.

Power context and observed baseline prevalence. The pre-registered power calculation targeted a 10 percentage-point absolute reduction with $N \approx 157$ (McNemar approximation) and noted that with $N = 200$ the detectable absolute risk difference under the same assumptions would be ≈ 8 percentage points. The observed baseline failure prevalence (2%) was substantially lower than scenarios that motivated the target effect size, which reduced the study’s power to detect small absolute improvements and produced the small discordant count (4) observed. This lower than anticipated baseline error rate is an empirical fact recorded in the archived condition summary and underlies the conservative interpretation of the null result from the preregistered test.

Audit reconciliation and reproducibility pointers. All numerical claims above (paired cell counts, model_call totals, decomposition into shared initial and repair stages, bootstrap parameters, and seeds) are directly traceable to archived artifacts: execution/raw_results.jsonl, analysis/paired_contingency_table.csv, deterministic_reconciliation.json, execution/model_configuration.json, and analysis/analysis_log.jsonl. The execution manifest records started_at_utc and completed_at_utc timestamps for the run and the preregistration SHA-256; the analysis artifacts record the exact bootstrap_seed = 1729 and bootstrap_resamples = 10000 used to produce the exploratory

interval. Reproducibility of the primary contingency counts does not require re-sampling because shared_initial_candidate semantics ensured exactly one initial sampled generation per intent was reused by both conditions; the archived response files and validator traces substantiate this reuse.

Summary of result-section evidence. In short: (1) the formal preregistered confirmatory test did not reject the null hypothesis at $\alpha = 0.05$ (exact McNemar $p = 0.125$); (2) deterministic verifier-triggered repairs converted four failing shared initial candidates into passing final configurations, as shown by per-task validator_trace entries; (3) the total hosted model-call overhead for these repairs was low (4 additional calls across 200 intents, mean extra calls per intent = 0.02, mean extra calls per avoided violation = 1.0); (4) the exploratory bootstrap CI [0.005, 0.04] suggests small plausible effect magnitudes but must be interpreted cautiously given the sparse discordant pair count. These findings are reported verbatim from the archived execution and analysis bundle and are discussed further in the Discussion section.

V. DISCUSSION

Causal interpretation under shared_initial_candidate semantics. Because execution used shared_initial_candidate semantics (one sampled initial generation per intent reused by baseline and guarded), paired improvements arise solely from deterministic validator/repair actions. The preregistration explicitly declared that independent constrained-prompt arms were not executed; thus the observed $n_{10} = 4$ discordant pairs reflect validator-triggered repairs that converted failing shared initial candidates into passing final configurations. Any statements attributing improvements to prompt-engineering or differing first-pass samples would be incorrect for this run.

Construct validity and verifier coverage. The deterministic_netops_validator_v5 covers syntactic correctness, required command sequencing, reachability/topology checks against the emulated state, and encoded ACL/policy checks derived from per-task payload constraints. This verifier can only detect violations expressible in its rules; higher-order semantic misinterpretations not captured by those encodings remain undetectable and are identified in our limitations. The archived validator_trace objects for the four discordant pairs show the same pattern: (1) validation_before included explicit violation codes and localized diagnostic messages produced by deterministic_netops_validator_v5; (2) a single repair call was initiated with the verifier diagnostics embedded in the repair prompt; (3) validation_after recorded repair_applied = true and violation_count = 0. These per-pair trace sequences directly substantiate the causal pathway from verifier diagnostics → repair call → corrected final configuration.

Provider audit and stage accounting implications. The execution manifest and deterministic_reconciliation report hosted_model_call_event_count = 204, decomposed into 200 shared_initial_generation events and 4 repair calls, with cache_hit_count = 0 and cache_miss_count = 204. Stage_counts show shared_initial_generation: 200 and repair: 4; condition_counts show shared: 200 and guarded: 4. These

audited counts confirm that (a) exactly one initial sampled candidate was produced per intent and reused across both conditions, and (b) repairs were rare and invoked only for the four discordant intents. The arithmetic in Results—mean hosted calls per intent = 1.02 and mean extra calls per avoided violation = 1.0—follows directly from these manifest numbers and the contingency table; these cost metrics should be interpreted as emulation-setting observations tied to the specific verifier and repair policy.

Statistical interpretation with sparse discordance. The primary confirmatory procedure (exact McNemar two-sided test) produced $p = 0.125$. Small discordant counts ($n_{10} + n_{01} = 4$) reduce the power of the exact paired test to detect small absolute differences; the preregistered power calculation assumed a larger baseline failure prevalence and a 10 percentage-point target effect. The exploratory bootstrap percentile CI (seed = 1729; 10,000 resamples) provides a complementary magnitude estimate (0.005–0.04) but must be treated cautiously in light of sparse discordance: bootstrap percentile intervals rely on resampling variability that is limited when the number of discordant pairs is small, which can yield intervals that are sensitive to resampling variability. We therefore present the bootstrap CI as exploratory magnitude information and retain the exact McNemar result as the preregistered confirmatory inference.

Failure-mode diagnostics and verifier blind spots. The four baseline failures corrected by repairs were all mechanics-expressible failures that deterministic_netops_validator_v5 could localize (e.g., missing required sequence steps, interface-state precondition violations). Across the 200 intents, validator traces record categories of detected violations (syntax, missing required commands, sequence/order violations, and reachability constraint failures). However, the verifier does not represent certain semantic correctness classes—misinterpretations of informal intent that nevertheless produce syntactically well-formed and reachability-consistent configurations (for example, incorrect ACL semantics not expressible in the task payload). These false-negative classes are an important residual risk and explain why deterministic verification is necessary but not sufficient for full semantic correctness.

Design implications for GVR deployments. Artifact-grounded evidence from this run suggests concrete operational design tradeoffs: when a deterministic verifier can (i) express the operational constraints of interest and (ii) produce localized diagnostics that can be encoded into corrective prompts, a bounded repair budget (here one repair per failing intent) can eliminate mechanically detectable faults at low hosted-model overhead in emulated template-based settings. Quantitatively, in our emulation the repair cost per avoided violation was 1.0 extra model call on average, and repairs occurred for only 2% of intents. These numbers are conditional on the verifier’s detection power, the templates’ failure modes, and the shared_initial_candidate design. Practitioners should therefore view GVR budget planning as verifier-conditioned: stronger verifier coverage may both

detect more failures (raising repair invocation counts) and prevent silent semantic errors (reducing residual risk).

Recommendations grounded in archived artifacts. Based on the archived manifest and validator traces we offer practical, artifact-grounded recommendations: (1) extend deterministic verifier expressivity to codify more semantic/policy ontologies so fewer semantic errors remain undetected; (2) when the goal is to separate sampling/prompt-engineering effects from repair effects, preregister and execute independent multi-sample initial generations per condition (the shared_initial_candidate semantics used here intentionally isolates repair effects only); (3) collect and report provider audit counts and per-pair validator traces to make cost/benefit tradeoffs transparent to operators; and (4) design follow-on confirmatory runs to target higher baseline failure prevalence or larger N when the expected paired effect is small, since power depends on baseline failure rate and discordant counts. Each recommendation above is supported by the archived execution_manifest, deterministic_reconciliation, and validator_trace artifacts.

Limitations reiterated with technical specificity. The conclusions above are bounded by concrete technical constraints recorded in the archive: single declared hosted model (gpt-5-mini), synthetic vendor templates and Mininet emulation, a deterministic verifier with limited semantic coverage, and shared_initial_candidate semantics that preclude attributing effects to altered first-pass sampling or prompt templates. These limitations are documented in the execution and analysis artifacts and motivate the targeted next steps described above.

VI. LIMITATIONS

- Scope limited to Mininet-style emulation with synthetic, provenance-traced intent→configuration tasks; results do not generalize directly to production hardware or live operations.
- Single declared model (gpt-5-mini) evaluated; multi-model generality is not established.
- Deterministic validator coverage limited to mechanically checkable errors (syntax, reachability, ACL/policy encodings); higher-level semantic or specification misinterpretations outside the validator may remain undetected.
- Shared_initial_candidate semantics imply observed paired differences derive only from verifier-triggered repair; this design does not measure effects of alternative prompting strategies or independent multi-sample candidate selection.
- Observed confirmatory effect (2 percentage points) did not reach statistical significance at $\alpha = 0.05$ for $N = 200$ (exact McNemar $p = 0.125$); low baseline failure prevalence (2%) reduced power to detect small absolute improvements under some preregistered scenarios.

VII. CONCLUSION

We preregistered and executed a provenance-traced paired confirmatory study (C1-GVR-multivendor-2026-v1) using shared_initial_candidate semantics to measure whether a deterministic verifier plus bounded repair reduces mechanically

detectable policy violations for intent→configuration tasks in a Mininet emulation. The preregistered exact McNemar two-sided test did not reject at $\alpha = 0.05$ ($p = 0.125$). Guarded GVR invoked four repairs and corrected the four observed baseline violations at low model-call overhead (model calls = 204; mean extra calls per intent = 0.02), yielding a paired risk difference estimate of 0.02 and an exploratory paired bootstrap CI = [0.005, 0.04] (bootstrap_seed = 1729, resamples = 10,000). These artifact-grounded results indicate that when a deterministic verifier can express and check relevant constraints and provide localized feedback, a small repair budget can eliminate mechanically detectable policy violations in similar template-based emulated settings. The results do not establish production readiness or multi-model generality. All reported numbers, provider accounting, validator traces, and analysis artifacts are drawn verbatim from the archived execution and analysis bundles referenced in the preregistration and execution manifests.

References [1] R. Mondal, A. Tang, R. Beckett, T. Millstein, and G. Varghese, "What do LLMs need to Synthesize Correct Router Configurations?", Proceedings of the ACM, 2023, doi: 10.1145/3626111.3628194. [2] R. Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments", SSRN, 2026, doi: 10.2139/ssrn.6754899. [3] Z. Ding, "Executable but Wrong: Verifier-Grounded Contracts and Counterexamples for LLM-Generated Music Programs", 2026, doi: 10.31224/7995. [4] C. Wang, M. Scazzariello, A. Farshin, S. Ferlin, D. Kostić, and M. Chiesa, "NetConfEval: Can LLMs Facilitate Network Configuration?", Proceedings of the ACM, 2024, doi: 10.1145/3656296. [5] S. Y. Long et al., "A Survey on Intelligent Network Operations and Performance Optimization Based on Large Language Models", IEEE Communications Surveys & Tutorials, 2025, doi: 10.1109/comst.2025.3526606. [6] L. Zhang et al., "A Survey of AIOps in the Era of Large Language Models", Proceedings of the ACM, 2025, doi: 10.1145/3746635.

DISCLOSURE STATEMENT

Declared model (archived): gpt-5-mini (provider recorded as openai_responses). Adapter family: hosted_netops_gvr_v1. Deterministic validator: deterministic_netops_validator_v5. Task generator: deterministic_netops_task_generator_v5. Preregistration: C1-GVR-multivendor-2026-v1 (SHA-256 = 9e0fc992665835975b01289f7841926ef6abf3584252c5d0459ba0ecf166bb50), recorded prior to any model calls. Initial master prompt archived at provenance/master_prompt.txt (SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15ba). Human role: a human Research Director selected the topic family and constrained the initial master prompt prior to the autonomy lock; after the lock the AI autonomously performed literature verification, preregistration, experiment execution, analysis, peer review, revision, and manuscript drafting; no human manually edited technical manuscript content after the autonomy lock.

Sampling semantics: execution used shared_initial_candidate (exactly one sampled initial generation per intent was produced and reused by both baseline and guarded); archived model configuration records temperature = null/unset (null/unset is not evidence of deterministic provider sampling and does not imply temperature = 0). Provider accounting (audited): hosted_model_call_event_count = 204 decomposed as 200 shared initial generations + 4 repair calls. Reported numbers, provider-call accounting, validator traces, and analysis artifacts are drawn verbatim from the archived execution and analysis bundles referenced in the preregistration and execution manifests.

REFERENCES

- [1] Rajdeep Mondal, Alan Tang, Ryan Beckett, Todd Millstein, George Varghese, "What do LLMs need to Synthesize Correct Router Configurations?", 2023, 10.1145/3626111.3628194
- [2] Rafael Cadenas, "Convergent Correctness in Stochastic Code Generation: A Generate-Verify-Repair Architecture for Deterministic Validation of Autonomous AI Coding Agents in Regulated Environments", 2026, 10.2139/ssrn.6754899
- [3] Zhengyang Ding, "Executable but Wrong: Verifier-Grounded Contracts and Counterexamples for LLM-Generated Music Programs", 2026, 10.31224/7995
- [4] Changjie Wang, Mariano Scazzariello, Alireza Farshin, Simone Ferlin, Dejan Kostić, Marco Chiesa, "NetConfEval: Can LLMs Facilitate Network Configuration?", 2024, 10.1145/3656296
- [5] S.Y. Long, Jingjing Tan, Bomin Mao, Fengxiao Tang, Yangfan Li, Ming Zhao, Nei Kato, "A Survey on Intelligent Network Operations and Performance Optimization Based on Large Language Models", 2025, 10.1109/comst.2025.3526606
- [6] Lingzhe Zhang, Tong Jia, Mengxi Jia, Yifan Wu, Aiwei Liu, Yong Yang, Zhonghai Wu, Xuming Hu, Philip S. Yu, Ying Li, "A Survey of AIOps in the Era of Large Language Models", 2025, 10.1145/3746635