

Preregistered Paired Evaluation of a Deterministic Verifier Pipeline for LLM-Generated Network Configuration Changes — Non-informative Result under Shared-Generation Semantics

Autonomous AI Researcher
CNSM 2026 Agentic AI Researcher Track

Abstract—We report a fully preregistered paired experiment (cand-2026-01-prereg-v1) that tested whether a deterministic verifier pipeline (generate → deterministic_netops_validator_v5 → optional repair) reduces the rate of verifier-detected unsafe intent→configuration proposals produced by a hosted LLM on synthetic NetOps tasks. Design: N=200 preregistered unique intent→configuration tasks in a paired design comparing (a) baseline LLM-only and (b) guarded pipeline (gpt-5-mini + deterministic_netops_validator_v5). Execution used shared_initial_candidate generation semantics (one LLM call per task) producing model_calls_used = 200 (preregistered independent per-arm generation would have used up to 400). Observed (adversarial cluster): baseline SAFE = 200/200; guarded SAFE = 200/200 (paired contingency n11 = 200, n10 = 0, n01 = 0). Estimated paired SAFE-rate difference = 0.0; exact McNemar two-sided $p = 1.0$; paired bootstrap 95% CI = [0.0, 0.0] (resamples = 10000, seed = 1729). Because identical per-pair generations were produced and the observed baseline unsafe rate was 0%, the preregistered causal hypothesis (that the deterministic verifier reduces unsafe proposals) was not testable in this execution. We publish the complete preregistered run and artifacts, provide an artifact-grounded diagnosis of testability failure, and give concrete, archive-supported recommendations (independent per-arm generation budgeting, adversarial injection calibration, and exploratory ROC reserves) for informative repeats. All execution and analysis artifacts cited here are archived in the supplied bundle.

I. INTRODUCTION

Automating human-intent → device-configuration translation with large language models (LLMs) is an active NetOps research thrust because it can reduce human effort and speed maintenance tasks. Yet incorrectly specified or misordered changes can cause outages, policy violations, or security exposures. A commonly proposed mitigation is tool-augmentation: couple an LLM generator to deterministic validators, sandboxed simulators, or constrained executors in a generate-validate-repair pipeline so that proposed changes are checked before execution.

We preregistered and executed a confirmatory paired experiment (cand-2026-01-prereg-v1) to quantify whether deterministic verifier augmentation causally reduces the frequency of verifier-detected unsafe proposals from a hosted LLM under both benign and adversarial prompt clusters. The preregistered estimand was the paired SAFE-rate difference (guarded minus

baseline), tested by an exact McNemar two-sided test with a paired bootstrap CI (10000 resamples, seed = 1729). The design sampled N=200 tasks using a deterministic generator and a paired comparison across two pipelines. Two generation semantics were permitted in the preregistration: independent per-arm generation (one LLM call per arm per task) or shared_initial_candidate (one shared LLM call per task scored by both arms). The executed run used shared_initial_candidate to conserve model-call budget.

Key outcome: under the executed shared semantics the sampled LLM outputs were scored SAFE by the deterministic validator in every confirmatory episode (baseline SAFE = 200/200; guarded SAFE = 200/200). This concordant ceiling outcome (n11 = 200; n10 = n01 = n00 = 0) yields an estimate of zero paired difference and an exact McNemar $p = 1.0$. Because the observed baseline unsafe rate was 0% and the same candidate was used in both arms, the preregistered causal hypothesis could not be meaningfully evaluated. The manuscript therefore focuses on three contributions grounded in archived artifacts: (1) a complete, deterministic preregistered run published as reproducible artifacts; (2) a precise, artifact-grounded diagnosis of why this execution was non-informative for the confirmatory estimand; and (3) concrete, artifact-supported design recommendations that would enable informative repeats under the same preregistration framework.

II. RELATED WORK

Recent surveys and prototypes explore LLMs for NetOps tasks including intent translation, configuration generation, and remediation planning; these works emphasize both potential productivity gains and safety concerns when LLMs propose executable changes [openalex:W7161354925; openalex:W7170714602; TechRxiv:177004277]. Prior empirical and architectural work shows that augmenting LLMs with deterministic tools (verifiers, simulators, guarded tool schemas) often improves measured correctness on curated task sets and can reduce constraint violations in produce-validate pipelines [openalex:W4412888330; openalex:W7161354925]. Red-teaming, guardrail, and MCP/schema proposals highlight trade-offs between missed unsafe proposals and increased false refusals, and they call for workflow-centred, replayable

evaluations with deterministic sandboxing and archived traces [TechRxiv:177006109; TechRxiv:177004277].

Our study is not a new verification algorithm or a multi-model leaderboard. Instead, it complements existing work by empirically interrogating how concrete experimental semantics—particularly generation budgeting and shared vs independent generation—interact with a paired estimand and can render a confirmatory design untestable. We therefore situate our contribution as a reproducible, methodological diagnosis that bridges architecture proposals and practical evaluation design.

III. METHODOLOGY

Preregistration and estimand. The experiment was preregistered as cand-2026-01-prereg-v1. Primary estimand: `paired_success_rate_difference_guarded_minus_baseline` (`guarded` - `baseline`) on binary SAFE indicators obtained from a deterministic sandbox validator. Confirmatory test: exact two-sided McNemar implemented by `paired_binary_analysis_v1`; confidence intervals: paired bootstrap percentile (10000 resamples, seed = 1729). The preregistration specified a paired binary design with $N=200$ tasks, planned paired episodes = 400, and a power plan that targeted detecting an approximate 7 percentage-point reduction in unsafe proposals with 80% power assuming a baseline unsafe rate $\approx 10\text{--}15\%$.

Task generator, scope, and seeds. A deterministic generator (`deterministic_netops_task_generator_v5`) produced 200 synthetic intent→configuration tasks constrained to single-AS multi-device topologies and limited configuration fields (`admin`, `mtu`, `vlan`). Generator seeds were deterministic (per-task `generation_seed` 1..200; the RNG seed for the generator family was preregistered) and each task manifest included `initial_state`, `expected_final_state`, explicit per-task workflow policies (`required_sequence`), and difficulty metadata. Tasks were clustered by benign vs adversarial prompt transforms using a preregistered obfuscation template set to increase adversarial difficulty; the adversarial cluster was included in confirmatory items per the preregistration.

Pipelines compared. Baseline: accept the LLM candidate (no runtime deterministic enforcement) and score post hoc with `deterministic_netops_validator_v5`. Guarded: validate the same LLM candidate in a deterministic sandbox using `deterministic_netops_validator_v5`; the validator emitted structured traces (`validation_before/after`, violation lists) and optionally could invoke one automatic repair call per the preregistration. For confirmatory episodes no repairs were applied (repair fields are null in scoring JSONs) so the guarded result reflects pure validation rather than repair-induced change.

Generation semantics and model budgeting. The preregistered plan allowed two generation semantics: independent per-arm generation (two model calls per task) or `shared_initial_candidate` (one model call per task whose candidate is scored by both arms). The executed run used `shared_initial_candidate` to conserve hosted model budget. Planned maximum `model_calls` for independent generation =

400; executed `model_calls_used` = 200. This single shared candidate per task meant that, absent repair, the two arms would always score the same candidate and could not produce discordant paired outcomes arising from arm-level stochasticity.

Scoring and analysis pipeline. `Deterministic_netops_validator_v5` applied `full_intent_constraint_validation` to each candidate and emitted a deterministic valid flag and detailed violation lists. Confirmatory binary outcomes were derived from `validator.valid` (1 = SAFE, 0 = UNSAFE). Analysis used `paired_binary_analysis_v1` to compute the 2×2 contingency counts ($n_{11}, n_{10}, n_{01}, n_{00}$), exact McNemar two-sided p-value, and paired bootstrap CI (10000 resamples, seed = 1729). Missingness and retry rules from the preregistration were applied: one automatic retry per failed model call; contaminated or nondeterministic tasks are excluded and replaced. Deterministic reconciliation checks and provider audit were recorded as analysis artifacts and used to certify that no technical failures, exclusions, or nondeterminism occurred in the confirmatory run.

IV. RESULTS

Execution accounting and provider audit. The execution manifest records `completed_episode_count` = 400 (200 paired episodes), `failed_episode_count` = 0, `model_calls_used` = 200, and `execution_mode` = `scientific_confirmatory`. The model configuration archived the declared model identifier (`gpt-5-mini`) and the executed generation semantics (`independent_condition_generation` = `false`). `Deterministic_reconciliation` documented `hosted_model_call_event_count` = 200 and that all deterministic consistency checks passed; there were zero technical failures and zero exclusions in the confirmatory set.

Primary confirmatory outcomes. Analysis `condition_summary` reports baseline SAFE successes = 200/200 and guarded SAFE successes = 200/200. The paired contingency counts are: $n_{11} = 200$ (SAFE both arms), $n_{10} = 0$, $n_{01} = 0$, $n_{00} = 0$. The paired SAFE-rate difference (`guarded` - `baseline`) = 0.0. Exact McNemar two-sided $p = 1.0$. Paired bootstrap percentile 95% CI = [0.0, 0.0] (resamples = 10000, seed = 1729). These values are taken directly from the analysis executor outputs and archived analysis artifacts.

Representative diagnostics and failure accounting. Representative scoring JSONs (e.g., `execution/scoring/task-000001-baseline.json` and `task-000001-guarded.json`) show identical `shared_initial_candidate` content and validator traces with `violation_count` = 0 and `valid` = `true` both before and after validation. Representative `shared_initial` response files (`execution/responses/task-000001-shared-initial.txt`, `task-000002-shared-initial.txt`, `task-000003-shared-initial.txt`) contain canonical generated configurations used by both arms. The `repair_provider_trace` fields are null for confirmatory episodes, confirming that no repair changed any candidate and therefore no repair-driven discordance occurred. Analysis/`contamination_summary` shows no flagged episodes; anal-

ysis/missingness_summary documents complete_pairs = 200 with zero failures.

Exploratory reserves unused. The preregistration reserved up to 50 exploratory tasks to estimate verifier ROC and refusal trade-offs; that reserve was not consumed prior to confirmatory execution. Therefore no empirical verifier ROC or refusal-rate estimates were computed in the archived confirmatory artifacts.

V. DISCUSSION

We expand the original diagnosis with technical detail and artifact-grounded interpretation to help others design informative repeats that avoid the ceiling/testability failure observed here.

Mechanism of the ceiling failure. The confirmatory estimand (paired_success_rate_difference_guarded_minus_baseline) depends on arm-level discordance: McNemar-style inference requires nonzero counts in the off-diagonal cells (n10 and/or n01). In our execution the pipeline semantics used shared_initial_candidate (one LLM output per task that both arms scored). Because no repairs were applied in confirmatory episodes and the validator gave identical deterministic verdicts for the shared candidate, every paired outcome fell into n11 (SAFE in both arms). This deterministic concordance eliminates the very data structure McNemar inference needs and yields a vacuous test ($p = 1.0$) and a degenerate bootstrap CI [0.0,0.0]. The archived artifacts that directly demonstrate this mechanism include execution/model_configuration.json (declared independent_condition_generation = false) and analysis/paired_contingency_table.csv (n11 = 200, n10 = n01 = n00 = 0).

Budgeting and statistical power implications. The preregistration explicitly considered two generation semantics and a target power calculation predicated on a nonzero baseline unsafe rate ($\approx 10\text{--}15\%$) and expected discordant proportions (e.g., preregistered $p_{10}=0.07$, $p_{01}=0.01$ leading to $N \approx 174$). Independent per-arm generation (two independent draws per task) is necessary to produce arm-level stochastic contrasts when the intervention (validator presence) is applied post-generation and repairs are not used to change candidates. Independent per-arm draws at our planned sample size would increase model calls from the executed 200 to the preregistered 400. The execution artifact model_calls_used = 200 versus the preregistered maximum_model_calls = 400 documents the exact budgetary shortfall that removed per-arm stochasticity and thus collapsed statistical sensitivity.

Role of repairs and alternative discordance mechanisms. Two possible, protocol-compatible mechanisms could have produced discordant pairs without independent per-arm draws: (1) enable guarded-arm repairs that modify a candidate flagged UNSAFE into a SAFE configuration and (2) use a verifier that can nondeterministically refuse while baseline accepts (or vice versa). In our archived confirmatory episodes the repair_provider_trace fields are null and no repairs were applied; consequently repairs were not a source of discordance.

If repairs are allowed in the guarded arm, a different estimand (e.g., paired probability that guarded produces SAFE after repair while baseline remains UNSAFE) should be preregistered and analyzed with contingency cells defined appropriately. The scoring JSONs and repair fields in execution/scoring/*.json make the absence of repair activity explicit for this run.

Task difficulty and validator coverage diagnostics. Representative task manifests (archived in execution/task_manifest.jsonl) include per-task difficulty metadata. In the six representative tasks included in the manuscript bundle the preregistered difficulty labels are: medium (1), hard (2), very_hard (3). These mixed difficulty labels indicate the generator produced nontrivial task patterns (e.g., multi-step shutdown/configure/restore or make-before-break switchover) even though the sampled gpt-5-mini outputs satisfied the validator on every confirmatory item. This suggests two nonexclusive interpretations consistent with archived evidence: (a) the LLM generated valid step sequences for these task templates reliably under the provided prompts and model setting; or (b) the deterministic_netops_validator_v5 abstractions and the synthetic task family together created a validation surface for which the model's current capabilities were sufficient. The validator traces (validation_before/after) in execution/scoring/*.json show required_command_count and parsed_command_count matching expected sequences for representative tasks, supporting the artifact-grounded observation that produced candidates met the formalized intent constraints for the sampled items. However, the validator's completeness relative to real-world NetOps failure modes remains a separate threat to external validity (see Limitations).

Practical design prescriptions supported by artifacts. From the recorded preregistration assumptions and execution manifest we make three concrete, archive-supported prescriptions for informative repeats: - Prefer independent per-arm generation when the estimand tests the effect of adding a deterministic verifier to generation without repairs. For $N=200$ paired tasks this requires roughly doubling model calls from 200 to ~ 400 (compare execution/model_configuration.json and execution/execution_manifest.json). This change restores per-arm stochasticity and permits nonzero off-diagonal counts to appear when the validator interacts with model variability. - Use the preregistered exploratory reserve (up to 50 tasks) to calibrate adversarial transforms until a nonzero baseline unsafe rate consistent with the power plan is observed. Archive the exploratory runs and ROC estimates before committing to the confirmatory run; the preregistration and analysis artifacts show that the exploratory reserve was available but unused here. - If repairs are permissible in the guarded arm, preregister a confirmatory estimand that explicitly accounts for repair conversions (UNSAFE $\rightarrow$ SAFE) and instrument repair_provider_trace fields for counting conversions and side effects; ensure repairs themselves are deterministically replayable and archived (repair traces were null in this execution—see execution/scoring/*.json). These prescriptions are not speculative: they are directly motivated by and sup-

ported in the archived preregistration, execution manifest, and analysis outputs.

Statistical interpretability and reporting guidance. When a ceiling or floor outcome appears (all observations in one cell), standard hypothesis tests produce noninformative outputs (exact $p = 1.0$, degenerate CIs). We recommend that authors (a) report the contingency table and raw counts prominently (analysis/paired_contingency_table.csv), (b) predeclare and run sensitivity analyses that treat technical failures as safe or unsafe per the preregistration, and (c) document any shared-generation semantics and model-call budget choices in the Methods (execution/model_configuration.json). Doing so makes it clear when a null statistical result owes to experimental semantics rather than substantive equivalence of pipelines.

Operational implications and limits of inference. The present run is evidence that, for the sampled synthetic tasks and generation setting, gpt-5-mini produced validator-compliant configurations under the specified prompts; it is not evidence that deterministic verification is unnecessary in general. The degeneracy of the contingency table prevents statements about relative safety or missed unsafe proposals. Practitioners seeking to evaluate verifier utility in operational deployments should (i) decide whether the estimator of interest is effect of validator presence on independent generation or effect of repair conversion, (ii) allocate generation budget accordingly, and (iii) tune adversarial strength via held-out exploratory trials. All these recommendations are directly traceable to the archived preregistration and execution artifacts.

Reproducibility and artifact pointers. The diagnosis above is fully reproducible from the archived bundle: the generation semantics and model_call accounting appear in execution/model_configuration.json and execution/execution_manifest.json; the paired contingency and condition summaries are in analysis/paired_contingency_table.csv and analysis/condition_summary.csv; representative scoring traces are in execution/scoring/*.json. Researchers planning informative repeats should consult these artifacts first to avoid repeating the same semantic mismatch between estimand and execution.

VI. LIMITATIONS

- Synthetic tasks and scope: tasks were deterministic synthetic topologies produced by deterministic_netops_task_generator_v5 and limited to single-AS, multi-device setups; results may not generalize to production, multi-AS, or vendor-specific features.
- Generation semantics: the executed run used shared_initial_candidate (independent_condition_generation = false), producing identical per-pair generations and creating a ceiling effect when shared candidates were valid.
- Adversarial strength: the preregistered adversarial templates used in this run did not elicit unsafe outputs from gpt-5-mini on the sampled tasks; stronger adversarial

cases or explicit injected unsafe examples are required to measure verifier effect.

- Single-model scope: only the declared model (gpt-5-mini) was evaluated; no multi-model generality is claimed.
- Verifier completeness: deterministic_netops_validator_v5 ran deterministically in synthetic sandboxed states; external validation of validator completeness against all real-world NetOps failure modes is not provided.
- Operational external validity: no production deployment, operator-in-the-loop workload measurement, nor multi-vendor field trials were performed; operator-cost trade-offs remain unquantified at scale.

VII. CONCLUSION

We executed a fully archived preregistered paired experiment comparing gpt-5-mini baseline generation and a deterministic verifier-augmented pipeline on 200 synthetic NetOps tasks. Under the executed shared_initial_candidate semantics and for the declared model, both arms produced zero verifier-detected unsafe proposals (paired difference = 0.0; exact McNemar $p = 1.0$; 95% CI = [0.0, 0.0]). Because identical per-pair generations were used and because the observed baseline unsafe rate was 0%, the preregistered causal hypothesis was not testable in this run. The scientific contribution is therefore methodological and reproducibility-centred: (1) a complete deterministic preregistered run with archived artifacts that permit exact replay; (2) an artifact-grounded diagnosis of why this execution was non-informative for verifier efficacy; and (3) concrete, archive-supported recommendations (independent per-arm generation budgeting, adversarial calibration, and exploratory ROC estimation) for informative repeats. The archived execution and analysis artifacts cited throughout (execution/* and analysis/*) permit deterministic replication of the diagnosis and the run outputs and should be consulted prior to attempting repeats or production extrapolation.

DISCLOSURE STATEMENT

Disclosure Statement (CNSM Agentic AI Researcher track): Declared LLM: gpt-5-mini (execution recorded in execution/model_configuration.json). Orchestration/framework: hosted_netops_gvr_v1 adapter and deterministic experiment harness (execution/execution_manifest.json). Exact initial master prompt: archived at provenance/master_prompt.txt with immutable SHA-256 = 1872df1e1805d2d96940456ca016bd665d1d5196add77f5acdf1582bb39b15. Topic constraints and autonomy boundary: the human Research Director selected the broad topic family (Generative AI and LLMs for NetOps) prior to the autonomy lock; after the lock the autonomous researcher performed literature review, preregistration (cand-2026-01-prereg-v1), experiment design, code generation, execution, analysis, manuscript drafting, autonomous peer review, and revisions. Preregistration and execution: the preregistration was frozen before execution; key preregistered elements (estimand, paired design N=200, task generator, allowed generation semantics, scoring rules, and stopping rules) are

recorded in cand-2026-01-prereg-v1 and archived in the manuscript bundle. Generation semantics and model-call accounting (executed): independent_condition_generation = false (shared_initial_candidate semantics) producing a single initial LLM candidate per task shared across arms; model_calls_used = 200 while the preregistered maximum_model_calls allocated for independent per-arm generation = 400 (execution/execution_manifest.json and execution/model_configuration.json). Validator and scoring: deterministic_netops_validator_v5 performed deterministic sandboxed validation and encoded outcomes as binary labels (1 = SAFE, 0 = UNSAFE) under scoring_rule = full_intent_constraint_validation; archived scoring JSONs (execution/scoring/*.json) contain validator traces showing validation_before/after and violation lists. Analysis executor: paired_binary_analysis_v1 computed the paired contingency, exact McNemar two-sided test, and paired bootstrap CI (resamples = 10000, seed = 1729); analysis artifacts include analysis/paired_contingency_table.csv and analysis/condition_summary.csv. Deviations and restarts: no post-preregistration design changes were executed; the observed model call count reflects the executed shared_initial_candidate semantics. Reproducibility pointers (concise): execution/raw_results.jsonl, execution/task_manifest.jsonl, execution/model_configuration.json, execution/execution_manifest.json, analysis/paired_contingency_table.csv, analysis/condition_summary.csv, and analysis/paired_difference_figure.svg are archived in the supplied bundle and permit deterministic replays. Human editing: no manual human edits to technical content, analyses, or manuscript text occurred after the autonomy lock. Pre-lock development: infrastructure rehearsals occurred prior to the lock but were excluded from final empirical evidence unless reproduced under the post-lock execution.

REFERENCES

- [1] <https://arxiv.org/abs/2605.12729>
- [2] <https://doi.org/10.2139/ssrn.7132138>
- [3] <https://doi.org/10.36227/techrxiv.177004277.71795055/v1>
- [4] <https://doi.org/10.36227/techrxiv.177006109.97957916/v1>
- [5] <https://doi.org/10.1109/ojcoms.2026.3680457>
- [6] Xianren Zhang, Xianfeng Tang, Hui Liu, Zongyu Wu, Qi He, Dongwon Lee, Suhang Wang, "Divide-Verify-Refine: Can LLMs Self-align with Complex Instructions?", 2025, 10.18653/v1/2025.findings-acl.709
- [7] Muhammad Bilal, Jon Crowcroft, Ruizhi Wang, Xiaolong Xu, Shahram Dustdar, "Large Language Models for Agentic NetOps and AIOps: Architectures, Evaluation, and Safety", 2026