

ILP: CONTROL FLOW

Mahdi Nazm Bojnordi

Assistant Professor

School of Computing

University of Utah

Overview

- Announcement

 - Homework 2 submission deadline: Feb. 13th

- This lecture

 - Performance bottleneck

 - Program flow


 - Branch instructions

 - Branch prediction

Performance Bottleneck

- Key performance limitation
 - ▣ Number of instructions fetched per second is limited
- How to increase fetch performance?
 - ▣ Deeper fetch (multiple stages)
 - ▣ Wider fetch (multiple pipelines)

How to handle branches?



Impact of Branches

- Example C code
 - ▣ No structural/data hazards
 - ▣ What is fetch rate (IPS)?
- Five-stage pipeline
 - ▣ Cycle time = 10ns

```
do {  
    sum = sum + i;  
    i = i - 1;  
} while(i > 0);
```

Assembly code:

```
Loop: ADD  R1, R1, R2  
      ADDI R2, R2, #-1  
      BNEQ R2, R0, Loop  
      stall
```



Impact of Branches

- Example C code
 - ▣ No structural/data hazards
 - ▣ What is fetch rate (IPS)?
- Ten-stage pipeline
 - ▣ Cycle time = 5ns

```
do {  
    sum = sum + i;  
    i = i - 1;  
} while(i > 0);
```


Assembly code:

```
Loop: ADD  R1, R1, R2  
      ADDI R2, R2, #-1  
      BNEQ R2, R0, Loop  
      stall  
      stall  
      stall
```




Program Flow

- A program contains basic blocks
 - ▣ Only one entry and one exit point per basic block
- Branches
 - ▣ Conditional vs. unconditional
 - How to check conditions
 - Jumps, calls, and returns
 - ▣ Target address
 - Absolute address
 - Relative to the program counter



Branch Instructions

- Branch penalty due to unknown outcome
 - ▣ Direction and target
- How to reduce penalty



Branch Prediction

- How to predict the outcome of a branch
 - ▣ Profiling the entire program
 - ▣ Predict based on common cases

Example C/C++ code:

```
i = 10000;  
do {  
    r = i%4;  
=>    if(r != 0) {  
        sum = sum + i;  
    }  
    i = i - 1;  
=> } while(i > 0);
```

How many branches?

Branch Prediction

- How to predict the outcome of a branch
 - ▣ Profiling the entire program
 - ▣ Predict based on common cases

Assembly code:

```
    ADDI R1, R0, #10000
do:
    ANDI R2, R1, #3
    BEQ  R2, R0, skp
    ADD  R3, R3, R1
skp:  ADDI R1, R1, #-1
      BNEQ R1, R0, do
```

	TAKEN	NOT-TAKEN
branch-1	2500	7500
branch-2	9999	1

Branch Prediction

- The goal of branch prediction
 - ▣ To avoid stall cycles in fetch stage
- Types
 - ▣ Static prediction (based on direction or profile)
 - Always not-taken
 - Target = next PC
 - Always taken
 - Target = unknown
 - ▣ Dynamic prediction
 - Special hardware using PC

Which ones are influenced

- a. Performance
- b. Energy
- c. Power

Branch Prediction/Misprediction

□ Prediction accuracy?

▣ A: always not-taken

0.01

▣ B: always taken

0.99

```
i = 100;  
do {  
    sum = sum + i;  
    i = i - 1;  
} while(i > 0);
```

Problem


- Compute IPC of a scalar processor when there are
 - ▣ no data/structural hazards, only control hazards,
 - ▣ every 5th instruction is a branch, and
 - ▣ 90% branch prediction accuracy
- $IPC = 1 / (1 + \text{stalls per instruction})$
- $= 1 / (1 + 0.2 \times 0.1 \times 1) = 0.98$

Dynamic Branch Prediction

- Hardware unit capable of learning at runtime
 - ▣ 1. Prediction logic
 - Direction (taken or not-taken)
 - Target address (where to fetch next)
 - ▣ 2. Outcome validation and training
 - Outcome is computed regardless of prediction
 - ▣ 3. Recovery from misprediction
 - Nullify the effect of instructions on the wrong path

Simple Dynamic Predictors

- One-bit branch predictor
 - ▣ Keep track of and use the outcome of last executed branch



- Prediction accuracy

- A single predictor shared by multiple branches
- Two mispredictions for loops (1 entry and 1 exit)

```
while(1) {  
    for(i=0; i<10; i++) {  
    }  
    for(j=0; j<20; j++) {  
    }  
}
```

branch-1

branch-2