

Bus system AS-Interface


AC2515

Active ClassicLine module

AS-i interface to FC lower parts
Sockets M12 x 1

IR addressing possible
Version 2.1 with extended addressing
mode

Digital inputs



1: label
2: fixture infrared adapter

Made in Germany



Electrical design

Operating voltage [V]

Total current consumption from
AS-i [mA]

Inputs

Input circuit

Sensor supply

Voltage range [V]

Max. current load for all inputs
total [mA]

Short-circuit proof

Switching level High signal 1 [V]

Input current High/Low [mA]

AS-Interface / extended addressing
mode possible

4 inputs

26.5...31.6 DC

< 150

DC PNP

AS-i

18...30 DC *)

100

yes

>11

>6 / <2

version 2.1 / yes

AC2515

Ambient temperature	[°C]	-25...70				
Protection		IP 67				
AS-i version		2.1				
AS-i profile		S-0.A.E				
I/O configuration [hex]		0				
ID code [Hex]		A.E				
AS-i certificate		in preparation				
EMC		EN 50295				
Housing materials		PBT (Pocan)				
Function display						
Operation	LED	green				
Error	LED	red				
Function	LED	yellow				
Connection		contact pins on FC or SC lower module				
Data bits		Data bit	D0	D1	D2	D3
		Input	1	2	3	4
		Socket	I-1/2	I-1/2 I-2	I-3/4	I-3/4 I-4
		Pin	4	2 4	4	2 4
Weight	[kg]	0.112				
Remarks		Do not connect any of the points I-, I+, I-1/2, I-2, I-3/4, I-4 to an external potential since they are electrically connected to the AS-i cable. *) via flat cable				
Wiring		I-1/2  I-3/4  I-2  I-4  Inputs 1: sensor supply L+ 3: sensor supply L- 5:				