Better connections!

FESTO

Quick selection with our poster for tubing, fittings and flow control valves

Everything from a single source
Festo offers a precisely tailored and economical solution to all connection problems – plus reliability! Thanks to a wide variety of different resistance properties and characteristics we can meet virtually any requirement.

From flame-retardant to antistatic, from food industry compatibility to welding spatter resistance. You therefore only pay for the functions you need. Always included is the tried and tested Quick Star releasing principle based on Festo plug and work® – for quick, simple and reliable assembly.

For even greater safety:
Free of charge tubing selection software, media resistance information and Online Shop

Online Shop
- Quick and simple
- Find, compare and configure products
- Check prices and availability and order
- Transfer product from the catalogue into the shopping basket
- Import or copy and insert product lists
- Import part lists
- Save and call up shopping baskets again
- Track orders and re-order

Media resistance information
Which tubing is resistant to benzene?
Can elastomers withstand contact with glycol?
Which high-grade steel is suitable for use in acetic acid?
These and numerous other questions regarding the media resistance of different materials are answered quickly and easily here.

Tubing selection software
Simply enter your application-specific requirements and wait for the system to guide you quickly and reliably to the appropriate solution.

Process reliability and reduction in costs for low value items

Low value items have a significant influence on procurement and stock administration costs. In general, they represent a small proportion of total material costs but a large proportion of the material to be managed. Festo's Logistics Optimisation Service helps reduce the costs of stock administration and the ordering process while increasing process reliability at the same time. Festo supports your logistics concept by providing independent modules from the Logistics Optimisation Service.

Select the suitable solution for your processes from the Festo logistics products.

The benefit to you
- Reduced order costs thanks to optimised ordering processes
- Fewer quality defects due a lower error rate
- Avoid unnecessary financial outlay thanks to a perfect parts range

Module 1:
Analysis of the product range and the logistical process
- What products are ordered, how often and in what quantities?
- Simplifying or expanding the product range
- Finding potential for optimisation
- Planning of optimal storage and ordering quantities, as well as order cycles
- Annual statistics of your ordering behaviour

➔ For details, see PSI 912.13

Module 2:
Optimising product identification
- Stock labels with product illustrations make identification easier
- Coding user-specific information in all popular bar code and national languages facilitates integration into the customer's existing system

➔ For details, see PSI 912.11

Module 3:
Optimisation of the ordering process
- Compiling pre-defined ordering quantities using bar code scanners
- Simple importing of scanned data into the Festo Online Shop
- 1-step ordering process – no waiting between request, price information and order

➔ For details, see PSI 912.11

Festo stock labels – reliable, quick, individual

Standard specifications

Festo product designation
Festo type code
Festo part number
Optimised ordering quantity

Optional specifications

Image or outline drawing
Customer material number
Location
Bar code



Cleverly combined:
Tubing-fitting combinations for all applications!

The right choice of the correct tubing-fitting combination is largely based on knowing its precise place of installation. To gain a quick understanding of the application, this can often be quickly determined by a single characteristic. One glance at the overview of our most popular tubing-fitting combinations enables you to make a quick and targeted choice.

Tubing

	Polyurethan (PU)						Polyethylen (PE)		Polyamid (PA)			PFA**
Resistance and suitability	PUN/PUN-DUO	PUN-H/ PUN-H DUO	PUN-E	PUN-CM	PUN-V0	PUN-V0-C	PLN	PEN	PAN	PAN-R	PAN-V0	PFAN
Media	Compressed air, vacuum	Compressed air, vacuum water*	Compressed air, vacuum	Compressed air, vacuum	Compressed air, vacuum, water*	Compressed air, vacuum, water*	Compressed air, vacuum, water*, cleaning	Compressed air, vacuum	Compressed air, vacuum	Compressed air, vacuum	Compressed air, vacuum water*	Compressed air, vacuum water*, acid, alkalis agents
Temperature [°C]	-35...60	-35...60	-35...50	-35...60	-35...60	-35...60	-30...80	-30...60	-30...80	-30...80	-30...90	-20...150
Operating pressure, temperature dependent [bar]	-0.95...10	-0.95...10	-0.95...8	-0.95...10	-0.95...10	-0.95...10	-0.95...14	-0.95...10	-0.95...19	-0.95...35	-0.95...12	-0.95...16
Chemical resistant	+	+	+	+	+	+	++	++	++	++	–	+++
Hydrolysis resistant	+	+++	+++	+	+	+	+++	+++	++	++	+	+++
Antistatic	–	–	–	+++	–	–	–	–	–	–	–	–
Flame-retardant UL94 V0-V2	–	–	–	–	+++	+++	–	–	–	–	+++	+++
Food industry approval	–	+++	–	–	–	–	+++	–	–	–	–	+++
Halogen-free	+++	+++	+++	+++	+++	+++	+++	+++	–	–	–	–

** Perfluoralkoxy

Fitting

	Plastic/brass			All-metal	Stainless steel	Metal	Plastic
Resistance and suitability	QS(M)	QS(M)-B	QS-V0	QS-F	CRQS	NPQM	NPQP
Media	Compressed air, vacuum, water*	Compressed air, vacuum	Compressed air, vacuum, water*	Compressed air, vacuum, water*	Compressed air, vacuum, water* acid, alkalis	Compressed air, vacuum	Compressed air, vacuum
Temperature [°C]	-10 ... 80	-10 ... 60	0 ... 60	0 ... 150	-15 ... 120	-20 ... 70	-20 ... 60
Operating pressure, temperature dependent [bar]	-0.95 ... 14	-0.95 ... 10	-0.95 ... 10	-0.95 ... 16	-0.95 ... 10	-0.95 ... 16	-0.95 ... 10
Chemical resistant	+	+	+	++	+++	+	+++
Hydrolysis resistant	+	+	+	+++	+++	++	+++
Antistatic	–	–	–	+++	+++	+++	–
Flame-retardant UL94 V0-V2	–	–	+++	+++	+++	++	–
Food industry approval	–	–	–	++	+++	–	–
Halogen-free	+++	+++	+++	+++	+++	+++	+++

+++ very suitable ++ quite suitable + suitable – not suitable * water and other media on request



In all variants... always a quick... and reliable connection!

	Application	Tubing	Fitting	Details
	Economical I	PEN	QS-B GRLA-QS-B-20	The universally suitable combination at an attractive price. Can be widely used thanks to highly resistant materials. Easy to install thanks to optimised bending radii.
	Economical II	PEN	NPQM VFOC	The universal solution for metal fittings. Perfect for standard pneumatics applications in many different fields.
	Wide choice of variants	PUN	QS GRLA-QS-RS-D	More than 1000 types for maximum flexibility in standard applications.
	Hydrolysis resistant	PUN-H	QS GRLA-QS-RS-B	For applications in humid environments or in contact with water at up to 60 °C. PUN-H – microbe resistant thanks to modified material.
	Pressure resistant I	PAN	QS GRLA-QS-RS-B	Safe connection when used in pressure ranges of up to 14 bar. Economical in pneumatic installations operating in the high pressure range.
	Pressure resistant II	PAN-R	QS-F GRLA-F-QS-D	The high performance combination for applications in pressure ranges of up to 16 bar: For example, applications using the pressure booster DPA.
	Heat resistant	PFAN	QS-F GRLA-F-QS-D	For a reliable compressed air supply in high-temperature areas. Up to 10 bar at 80 °C or 6 bar at 150 °C – maximum process security at all times.
	**Antistatic**	PUN-CM	NPQM GRLA-F-QS-D	Electrically conductive tubing combined with an all-metal fitting.
	Food industry approved I	PUN-H	QS-F CRGRLA	FDA approval for use in the food industry – a hydrolysis resistant combination with enhanced functionality.
	Food industry approved II	PFAN	CRQS CRGRLA	Created for the highest standards, thanks to the highest corrosion resistance: this combination excels wherever maximum food hygiene is needed.
	Resistant to cleaning agents	PLN	NPQP	The cost-effective alternative to stainless steel is highly resistant to all usual cleaning agents and has maximum corrosion protection. That makes it perfect for critical environments such as splash zones.
	Media resistant	PFAN	NPQP	Completely resistant to all cleaning agents and lubricants and even permits the conveyance of acids and lyes without any problems.
	Flame retardant	PUN-VO	NPQM	Safe in areas where there is a risk of fire thanks to flame retardant properties to UL94.
	Resistant to welding spatter I	PUN-VO-C	QS-F GRLA-F-QS-D	The economical combination for applications in indirect proximity to welding applications. Safe thanks to a tubing wall thickness of 2 mm for all diameters.
	**Resistant to welding spatter II**	PAN-VO	QS-VO	Safe even in indirect proximity to welding spatter. Two-layer tubing and special fitting.

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	**Standard fittings** Part 1 von 2	• **Mini types** • **Standard types** • **Straight and L- shaped** • **Push-in bulkhead fittings** • **Push-in fittings, self-sealing**	• **Wide range of variants** • **Hydrolysis resistant** • **Pressure resistant**
QS	Poster **Standard fittings** Part 2 von 2	Types • **L, T, Y-shaped** • **Multiple distributor**	Applications • **Wide range of variants** • **Hydrolysis resistant** • **Pressure resistant**
QS	Poster **Standard connectors**	Types • **Straight, T, L, X, Y-shaped** • **With push-in sleeve** • **Push-in bulkhead fittings and push-in fittings, self-sealing**	Applications • **Wide range of variants** • **Hydrolysis resistant** • **Pressure resistant** • **Economical**
QS-B	Poster **Fittings connectors for core functions**	Types • **Mini types** • **Straight, T, L, X, Y-shaped**	Applications • **Economical**
NPQM	Poster **Metallic push-in fittings**	Types • **Push-in fittings with internal hex, thread, T, L-shaped** • **Plug connector straight, with sleeve, L, T, Y-shaped**	Applications • **Economical** • **Antistatic** • **Flame-retardant**
NPQP	Poster **Polypropylene fittings**	Types • **Plug connectors, L, T, Y-shaped** • **Plug connectors, L, T, Y-shaped** • **Bulkhead connector** • **Blanking plugs**	Applications • **Cleaning agent** • **Media resistant**
QS-F **CRQS** **QS-V0**	Poster **Metal and special fittings/connectors**	Types • **Metal, stainless steel,** • **Straight, L and T-shaped**	Applications • **Pressure/heat resistant** • **Antistatic, Food industry approved** • **Cleaning agent/media resistant** • **Flame-retardant** • **Welding spatter resistant**
PUN-... **PAN-...** **PEN** **PFAN** **PLN**	Poster **Plastic tubing**	Types • **Standard O.D.** • **Different materials** • **Standard and bulk packs**	Applications • **For all applications**
NPFB-... **GRLA-....** **GRLZ-...** **GRLO-...** **VFOC/VFOV-...**	Poster **Threaded fittings and flow control valves**	Types • **Threaded fittings,** • **Nickel-plated brass** • **Function fittings**	Applications • **For all applications**

QS standard – Part 1 of 2 – Push-in fittings

Here you will find the optimum fittings in polymer design for applications shown opposite.

With appropriate tubing from poster 6 you will always obtain the right tubing/fitting combination.

Wide range of variants: PUN/QS

Over 1000 types for maximum flexibility in standard applications.

Hydrolysis resistant: PUN-H/QS

For applications in damp environments or when in contact with water at up to 60°C. PUN-H – microbe resistant thanks to modified material.

Pressure resistant I: PAN/QS

Reliable connection with pressure ranges up to 14 bar. Economical with pneumatic installations in the high pressure range.

QS standard, Mini

Push-in fitting

Type	A	D2	PE	TN
QSM-...	M3	3	10	153301
QSM-...	M3	3	100	130775
QSM-...	M3	4	10	153303
QSM-...	M3	4	100	130776
QSM-...	M5	3	10	153302
QSM-...	M5	3	100	130777
QSM-...	M5	4	10	153304
QSM-...	M5	4	100	130778
QSM-...	M5	6	10	153306
QSM-...	M5	6	100	130779
QSM	M6	6	1	132600
QSM-...	R1/8	4	10	153305
QSM-...	R1/8	4	100	130755
QSM-...	R1/8	6	10	153307
QSM-...	R1/8	6	100	130756
QSM-...	G1/8	4	10	186264
QSM-...	G1/8	6	10	186265

Push-in L-fitting

Type	A	D2	PE	TN
QSML...	M3	3	10	153330
QSML...	M3	3	100	130768
QSML...	M3	4	10	153332
QSML...	M3	4	100	130769
QSML...	M5	3	10	153331
QSML...	M5	3	100	130770
QSML...	M5	4	10	153333
QSML...	M5	4	100	130771
QSML...	M5	6	10	153335
QSML...	M5	6	100	130772
QSML...	M7	4	10	186352
QSML...	M7	4	100	130773
QSML...	M7	6	10	186353
QSML...	M7	6	100	130774
QSML...	R1/8	4	10	153334
QSML...	R1/8	4	100	130764
QSML...	R1/8	6	10	153336
QSML...	R1/8	6	100	130765
QSML...	G1/8	4	10	186268
QSML	G1/8	4	100	132897

Push-in L-fitting

Type	A	D2	PE	TN
QSMLV-I...	M5	3	10	130830
QSMLV-I...	M5	4	10	130831
QSMLV-I...	M7	4	10	130832
QSMLV-I...	M7	6	10	130833

Push-in long L-fitting

Type	A	D2	PE	TN
QSMLLV-I...	M5	3	10	130834
QSMLLV-I...	M5	4	10	130835
QSMLLV-I...	M7	4	10	130836
QSMLLV-I...	M7	6	10	130837

Push-in fitting

Type	A	D2	PE	TN
QSM-I...	M3	3	10	153312
QSM-I...	M3	4	10	153314
QSM-I...	M5	3	10	153313
QSM-I...	M5	4	10	153315
QSM-I...	M5	6	10	153317
QSM-I...	M7	4	10	153319
QSM-I...	M7	6	10	153321
QSM-I...	R1/8	4	10	153316
QSM-I...	R1/8	6	10	153318
QSM-I...	G1/8	4	10	186266
QSM-I...	G1/8	6	10	186267

Push-in long L-fitting

Type	A	D2	PE	TN
QSMLL...	M3	3	10	153337
QSMLL...	M3	4	10	153338
QSMLL...	M5	3	10	130838
QSMLL...	M5	4	10	153339
QSMLL...	M5	6	10	153341
QSMLL...	M7	4	10	186354
QSMLL...	M7	6	10	186355
QSMLL...	R1/8	4	10	153340
QSMLL...	R1/8	6	10	153342
QSMLL...	G1/8	4	10	186270
QSMLL...	G1/8	6	10	186271

Push-in T-fitting

Type	A	D2	PE	TN
QSMT...	M3	3	10	153351
QSMT...	M3	4	10	153353
QSMT...	M5	3	10	153352
QSMT...	M5	4	10	153354
QSMT...	M5	4	100	130784
QSMT...	M5	6	10	153356
QSMT...	M5	6	100	130785
QSMT...	R1/8	4	10	153355
QSMT...	R1/8	6	10	153357
QSMT...	G1/8	4	10	186272
QSMT...	G1/8	6	10	186273

Push-in fitting

Type	A	D2	PE	TN
QSMF...	M3	3	10	153308
QSMF...	M3	4	10	153310
QSMF...	M5	3	10	153309
QSMF...	M5	4	10	153311

Push-in T-fitting

Type	A	D2	PE	TN
QSMTL...	M3	3	10	153358
QSMTL...	M3	4	10	153360
QSMTL...	M5	3	10	153359
QSMTL...	M5	4	10	153361
QSMTL...	M5	6	10	153363
QSMTL...	R1/8	4	10	153362
QSMTL...	R1/8	6	10	153364
QSMTL...	G1/8	4	10	186274
QSMTL...	G1/8	6	10	186275

Push-in fitting

Type	A	D2	PE	TN
QSMP...	M6x0,75	4	10	153320
QSMP...	M6x0,75	6	10	153322

QS standard

Push-in fitting

Type	A	D2	PE	TN
QS...	R1/8	4	10	153001
QS...	R1/8	4	100	130674
QS...	R1/8	6	10	153002
QS...	R1/8	6	100	130675
QS...	R1/8	8	10	153004
QS...	R1/8	8	50	130676
QS...	R1/8	10	10	190643
QS...	R1/4	4	10	190644
QS...	R1/4	6	10	153003
QS...	R1/4	6	100	130677
QS...	R1/4	8	10	153005
QS...	R1/4	8	50	130678
QS...	R1/4	10	10	153007
QS...	R1/4	10	50	130679
QS...	R1/4	12	10	164980
QS...	R1/4	12	20	130680
QS...	R3/8	6	10	190645
QS...	R3/8	8	10	153006
QS...	R3/8	8	50	130681
QS...	R3/8	10	10	153008
QS...	R3/8	10	50	130682
QS...	R3/8	12	10	153009
QS...	R3/8	12	20	130683
QS...	R3/8	16	1	164957
QS...	R1/2	10	10	190646
QS...	R1/2	12	1	153010
QS...	R1/2	12	20	130684
QS...	R1/2	16	1	153011
QS...	R1/2	16	20	130685

Push-in fitting

Type	A	D2	PE	TN
QS...	G1/8	4	10	186095
QS...	G1/8	4	100	132036
QS...	G1/8	6	10	186096
QS...	G1/8	6	100	132037
QS...	G1/8	8	10	186098
QS...	G1/8	8	50	132038
QS...	G1/4	6	10	186097
QS...	G1/4	6	100	132039
QS...	G1/4	8	10	186099
QS...	G1/4	8	50	132040
QS...	G1/4	10	10	186101
QS...	G1/4	10	50	132041
QS...	G1/4	12	10	186350
QS...	G1/4	12	20	132042
QS...	G3/8	8	10	186100
QS...	G3/8	8	50	132043
QS...	G3/8	10	10	186102
QS...	G3/8	10	50	132044
QS...	G3/8	12	10	186103
QS...	G3/8	12	20	132045
QS...	G3/8	16	1	186347
QS...	G1/2	12	1	186104
QS...	G1/2	12	20	132046
QS...	G1/2	16	1	186105

Push-in fitting

Type	A	D2	PE	TN
QSF...	G1/8	4	10	153022
QSF...	G1/8	4	100	130709
QSF...	G1/8	6	10	153023
QSF...	G1/8	6	100	130710
QSF...	G1/8	8	10	153025
QSF...	G1/8	8	50	130711
QSF...	G1/4	4	10	190650
QSF...	G1/4	6	10	153024
QSF...	G1/4	6	100	130712
QSF...	G1/4	8	10	153026
QSF...	G1/4	8	50	130713
QSF...	G1/4	10	10	153028
QSF...	G1/4	10	50	130714
QSF...	G1/4	12	10	190651
QSF...	G3/8	6	10	190652
QSF...	G3/8	8	10	153027
QSF...	G3/8	8	50	130715
QSF...	G3/8	10	10	153029
QSF...	G3/8	10	50	130716
QSF...	G3/8	12	10	153030
QSF...	G3/8	12	20	130717
QSF...	G1/2	12	1	190653
QSF...	G1/2	16	1	190654

Push-in L-fitting

Type	A	D2	PE	TN
QSLV-...-I	R1/8	6	10	153097
QSLV-...-I	R1/8	8	10	153099
QSLV-...-I	R1/4	6	10	153098
QSLV-...-I	R1/4	8	10	153100
QSLV-...-I	R1/4	10	10	153102
QSLV-...-I	R3/8	8	10	153101
QSLV-...-I	R3/8	10	10	153103
QSLV-...-I	R3/8	12	10	153104
QSLV-...-I	R1/2	12	1	153105
QSLV-...-I	G1/8	6	10	186148
QSLV-...-I	G1/8	8	10	186150
QSLV-...-I	G1/4	6	10	186149
QSLV-...-I	G1/4	8	10	186151
QSLV-...-I	G1/4	10	10	186153
QSLV-...-I	G3/8	8	10	186152
QSLV-...-I	G3/8	10	10	186154
QSLV-...-I	G3/8	12	10	186155
QSLV-...-I	G1/2	12	1	186156

Push-in bulkhead fitting

Type	A	D2	PE	TN
QSSF...	G1/8	4	10	153162
QSSF...	G1/8	6	10	153163
QSSF...	G1/8	8	10	153165
QSSF...	G1/4	4	10	190655
QSSF...	G1/4	6	10	153164
QSSF...	G1/4	8	10	153166
QSSF...	G1/4	10	10	153168
QSSF...	G3/8	6	10	190656
QSSF...	G3/8	8	10	153167
QSSF...	G3/8	10	10	153169
QSSF...	G3/8	12	10	153170
QSSF...	G1/2	12	1	153171
QSSF...	G1/2	16	1	190657

Push-in long L-fitting

Type	A	D2	PE	TN
QSLL...	G1/8F	4	10	556843
QSLL...	G1/8F	6	10	556844
QSLL...	G1/8F	8	10	556845
QSLL...	G1/4F	6	10	556846
QSLL...	G1/4F	8	10	556847
QSLL...	G1/4F	10	10	556848
QSLL...	G1/4F	12	10	556849
QSLL...	G3/8F	8	10	556850
QSLL...	G3/8F	10	10	556851
QSLL...	G3/8F	12	10	556852
QSLL...	G1/2F	10	10	556853
QSLL...	G1/2F	12	10	556854

Push-in fitting, self-sealing

Type	A	D2	PE	TN
QSK...	M5	4	1	153291
QSK...	M5	6	1	153292
QSK...	R1/8	4	1	153419
QSK...	R1/8	6	1	153420
QSK...	R1/8	8	1	153422
QSK...	R1/4	6	1	153421
QSK...	R1/4	8	1	153423
QSK...	R1/4	10	1	153425
QSK...	R3/8	8	1	153424
QSK...	R3/8	10	1	153426
QSK...	R3/8	12	1	153427
QSK...	R1/2	12	1	153428
QSK...	G1/8	4	1	186294
QSK...	G1/8	6	1	186295
QSK...	G1/8	8	1	186297
QSK...	G1/4	6	1	186269
QSK...	G1/4	8	1	186298
QSK...	G1/4	10	1	186300
QSK...	G3/8	8	1	186299
QSK...	G3/8	10	1	186301
QSK...	G3/8	12	1	186302
QSK...	G1/2	12	1	186303

Push-in L-fitting

Type	A	D2	PE	TN
QSL...	G1/8	4	10	186116
QSL...	G1/8	4	100	132048
QSL...	G1/8	6	10	186117
QSL...	G1/8	6	100	132049
QSL...	G1/8	8	10	186119
QSL...	G1/8	8	50	132050
QSL...	G1/4	6	10	186118
QSL...	G1/4	6	100	132051
QSL...	G1/4	8	10	186120
QSL...	G1/4	8	50	132052
QSL...	G1/4	10	10	186122
QSL...	G1/4	10	50	132053
QSL...	G1/4	12	10	186351
QSL...	G1/4	12	20	132054
QSL...	G3/8	8	10	186121
QSL...	G3/8	8	50	132055
QSL...	G3/8	10	10	186123
QSL...	G3/8	10	20	132056
QSL...	G3/8	12	10	186124
QSL...	G3/8	12	20	132057
QSL...	G3/8	16	1	186348
QSL...	G1/2	12	1	186125
QSL...	G1/2	12	20	132058
QSL...	G1/2	16	1	186126
QSL...	G1/2	16	20	132059

Push-in L-fitting

Type	A	D2	PE	TN
QSL...	R1/8	4	10	153045
QSL...	R1/8	4	100	130728
QSL...	R1/8	6	10	153046
QSL...	R1/8	6	100	130729
QSL...	R1/8	8	10	153048
QSL...	R1/8	8	50	130730
QSL...	R1/8	10	10	190658
QSL...	R1/4	4	10	190659
QSL...	R1/4	6	10	153047
QSL...	R1/4	6	100	130731
QSL...	R1/4	8	10	153049
QSL...	R1/4	8	50	130732
QSL...	R1/4	10	10	153051
QSL...	R1/4	10	50	130733
QSL...	R1/4	12	10	164981
QSL...	R1/4	12	20	130734
QSL...	R3/8	6	10	190660
QSL...	R3/8	8	10	153050
QSL...	R3/8	8	50	130735
QSL...	R3/8	10	10	153052
QSL...	R3/8	10	20	130736
QSL...	R3/8	12	10	153053
QSL...	R3/8	12	20	130737
QSL...	R3/8	16	1	164958
QSL...	R1/2	10	1	190661
QSL...	R1/2	12	1	153054
QSL...	R1/2	12	20	130738
QSL...	R1/2	16	1	153055
QSL...	R1/2	16	20	130739

Push-in long L-fitting

Type	A	D2	PE	TN
QSLL...	R1/8	4	10	153076
QSLL...	R1/8	6	10	153077
QSLL...	R1/8	8	10	153079
QSLL...	R1/4	4	10	190662
QSLL...	R1/4	6	10	153078
QSLL...	R1/4	8	10	153080
QSLL...	R1/4	10	10	153082
QSLL...	R3/8	6	10	190663
QSLL...	R3/8	8	10	153081
QSLL...	R3/8	10	10	153083
QSLL...	R3/8	12	10	153084
QSLL...	R1/2	10	1	190664
QSLL...	R1/2	12	1	153085
QSLL...	G1/8	4	10	186127
QSLL...	G1/8	6	10	186128
QSLL...	G1/8	8	10	186130
QSLL...	G1/4	6	10	186129
QSLL...	G1/4	8	10	186131
QSLL...	G1/4	10	10	186133
QSLL...	G3/8	8	10	186132
QSLL...	G3/8	10	10	186134
QSLL...	G3/8	12	10	186135
QSLL...	G1/2	12	1	186136
QSLL...	G1/2	16	1	190665

Push-in fitting

Type	A	D2	PE	TN
QS-...-I	R1/8	4	10	153012
QS-...-I	R1/8	6	10	153013
QS-...-I	R1/8	8	10	153015
QS-...-I	R1/8	10	10	190647
QS-...-I	R1/4	6	10	153014
QS-...-I	R1/4	8	10	153016
QS-...-I	R1/4	10	10	153018
QS-...-I	R1/4	12	10	190649
QS-...-I	R3/8	8	10	153017
QS-...-I	R3/8	10	10	153019
QS-...-I	R3/8	12	10	153020
QS-...-I	R1/2	10	1	190648
QS-...-I	R1/2	12	1	153021
QS-...-I	G1/8	4	10	186106
QS-...-I	G1/8	6	10	186107
QS-...-I	G1/8	8	10	186109
QS-...-I	G1/4	6	10	186108
QS-...-I	G1/4	8	10	186110
QS-...-I	G1/4	10	10	186112
QS-...-I	G3/8	8	10	186111
QS-...-I	G3/8	10	10	186113
QS-...-I	G3/8	12	10	186114
QS-...-I	G1/2	12	1	186115

Push-in L-fitting, self-sealing

Type	A	D2	PE	TN
QSKL...	M5	4	1	153294
QSKL...	M5	6	1	153295
QSKL...	R1/8	4	1	153429
QSKL...	R1/8	6	1	153430
QSKL...	R1/8	8	1	153432
QSKL...	R1/4	6	1	153431
QSKL...	R1/4	8	1	153433
QSKL...	R1/4	10	1	153435
QSKL...	R3/8	8	1	153434
QSKL...	R3/8	10	1	153436
QSKL...	R3/8	12	1	153437
QSKL...	R1/2	12	1	153438
QSKL...	G1/8	4	1	186304
QSKL...	G1/8	6	1	186305
QSKL...	G1/8	8	1	186307
QSKL...	G1/4	6	1	186306
QSKL...	G1/4	8	1	186308
QSKL...	G1/4	10	1	186310
QSKL...	G3/8	8	1	186309
QSKL...	G3/8	10	1	186311
QSKL...	G3/8	12	1	186312
QSKL...	G1/2	12	1	186313

Push-in fitting,
360° rotatable

Type	A	D2	PE	TN
QSR...	M5	4	1	153526
QSR...	M5	6	1	153527
QSR...	R1/8	4	1	153401
QSR...	R1/8	6	1	153402
QSR...	R1/8	8	1	153404
QSR...	R1/4	6	1	153403
QSR...	R1/4	8	1	153405
QSR...	R3/8	8	1	153406
QSR...	R3/8	10	1	153407
QSR...	R3/8	12	1	153408
QSR...	R1/2	12	1	153409
QSR...	G1/8	4	1	186276
QSR...	G1/8	6	1	186277
QSR...	G1/8	8	1	186279
QSR...	G1/4	6	1	186278
QSR...	G1/4	8	1	186280
QSR...	G3/8	8	1	186281
QSR...	G3/8	10	1	186282
QSR...	G3/8	12	1	186283
QSR...	G1/2	12	1	186284

Legend

A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment

All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	**Standard fittings** Part 2 von 2	**• L, T, Y-shaped** **• Multiple distributor**	**• Wide range of variants** **• Hydrolysis resistant** **• Pressure resistant**
QS	Standard connectors	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	Fittings connectors for core functions	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	Metallic push-in fittings	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	Polypropylene fittings	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	Metal and special fittings/connectors	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... PAN-... PEN PFAN PLN	Plastic tubing	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

QS standard – Part 2 of 2 – **Push-in fittings**

Here you will find the optimum fittings in polymer design for applications shown opposite.

With appropriate tubing from poster 6 you will always obtain the right tubing/fitting combination.

Wide range of variants: PUN/QS

Over 1000 types for maximum flexibility with standard applications.

Hydrolysis resistant: PUN-H/QS

For applications in damp environments or in contact with water up to 60°C. PUN-H – microbe resistant thanks to modified material.

Pressure resistant I: PAN/QS

Reliable connection with pressure ranges up to 14 bar. Economical with pneumatic installations in the high pressure range.

QS standard

Push-in L-fitting

Type	A	D2	PE	TN
QSLF...	G1/8	4	10	153273
QSLF...	G1/8	6	10	153274
QSLF...	G1/8	8	10	153276
QSLF...	G1/4	6	10	153275
QSLF...	G1/4	8	10	153277
QSLF...	G1/4	10	10	153279
QSLF...	G3/8	8	10	153278
QSLF...	G3/8	10	10	153280

Push-in L-fitting

Type	A	D2	PE	TN
QSLV...	M5	6	10	190666
QSLV...	R1/8	4	10	153086
QSLV...	R1/8	4	100	130749
QSLV...	R1/8	6	10	153087
QSLV...	R1/8	6	100	130750
QSLV...	R1/8	8	10	153089
QSLV...	R1/8	8	50	130751
QSLV...	R1/4	6	10	153088
QSLV...	R1/4	6	100	130752
QSLV...	R1/4	8	10	153090
QSLV...	R1/4	8	50	130753
QSLV...	R1/4	10	10	153092
QSLV...	R1/4	10	50	130754
QSLV...	R3/8	8	10	153091
QSLV...	R3/8	10	10	153093
QSLV...	R3/8	12	10	153094
QSLV...	R1/2	12	1	153095
QSLV...	R1/2	16	1	153096
QSLV...	G1/8	4	10	186137
QSLV...	G1/8	4	100	132060
QSLV...	G1/8	6	10	186138
QSLV...	G1/8	6	100	132061
QSLV...	G1/8	8	10	186140
QSLV...	G1/8	8	50	132062
QSLV...	G1/4	6	10	186139
QSLV...	G1/4	6	100	132063
QSLV...	G1/4	8	10	186141
QSLV...	G1/4	8	50	132064
QSLV...	G1/4	10	10	186143
QSLV...	G1/4	10	50	132065
QSLV...	G3/8	8	10	186142
QSLV...	G3/8	10	10	186144
QSLV...	G3/8	12	10	186145
QSLV...	G1/2	12	1	186146
QSLV...	G1/2	16	1	186147

Push-in L-fitting

Type	A	D2	PE	TN
QSRL...	M5	4	1	153529
QSRL...	M5	6	1	153530
QSRL...	R1/8	4	1	153410
QSRL...	R1/8	6	1	153411
QSRL...	R1/8	8	1	153413
QSRL...	R1/4	6	1	153412
QSRL...	R1/4	8	1	153414
QSRL...	R3/8	8	1	153415
QSRL...	R3/8	10	1	153416
QSRL...	R3/8	12	1	153417
QSRL...	R1/2	12	1	153418
QSRL...	G1/8	4	1	186285
QSRL...	G1/8	6	1	186286
QSRL...	G1/8	8	1	186288
QSRL...	G1/4	6	1	186287
QSRL...	G1/4	8	1	186289
QSRL...	G3/8	8	1	186290
QSRL...	G3/8	10	1	186291
QSRL...	G3/8	12	1	186292
QSRL...	G1/2	12	1	186293

Push-in T-fitting

Type	A	D2	PE	TN
QST...	R1/8	4	10	153106
QST...	R1/8	4	100	130793
QST...	R1/8	6	10	153107
QST...	R1/8	6	100	130794
QST...	R1/8	8	10	153109
QST...	R1/8	8	50	130795
QST...	R1/8	10	10	190667
QST...	R1/4	4	10	190668
QST...	R1/4	6	10	153108
QST...	R1/4	6	100	130796
QST...	R1/4	8	10	153110
QST...	R1/4	8	50	130797
QST...	R1/4	10	10	153112
QST...	R1/4	10	50	130798
QST...	R1/4	12	10	190669
QST...	R3/8	6	10	190670
QST...	R3/8	8	10	153111
QST...	R3/8	8	50	130799
QST...	R3/8	10	10	153113
QST...	R3/8	10	20	130800
QST...	R3/8	12	10	153114
QST...	R3/8	12	20	130801
QST...	R3/8	16	1	164959

Push-in T-fitting

Type	A	D2	PE	TN
QST...	G1/8	4	10	186157
QST...	G1/8	4	100	132066
QST...	G1/8	6	10	186158
QST...	G1/8	6	100	132067
QST...	G1/8	8	10	186160
QST...	G1/8	8	50	132068
QST...	G1/4	6	10	186159
QST...	G1/4	6	100	132069
QST...	G1/4	8	10	186161
QST...	G1/4	8	50	132070
QST...	G1/4	10	10	186163
QST...	G1/4	10	50	132071
QST...	G3/8	8	10	186162
QST...	G3/8	8	50	132072
QST...	G3/8	10	10	186164
QST...	G3/8	10	20	132073
QST...	G3/8	12	10	186165
QST...	G3/8	12	20	132074
QST...	G3/8	16	1	186349
QST...	G1/2	12	1	186166
QST...	G1/2	16	1	186167

Push-in T-fitting

Type	A	D2	PE	TN
QSTF...	R1/8	4	10	153182
QSTF...	R1/8	6	10	153183
QSTF...	R1/8	8	10	153185
QSTF...	R1/4	6	10	153184
QSTF...	R1/4	8	10	153186
QSTF...	R1/4	10	10	153188
QSTF...	R3/8	8	10	153187
QSTF...	R3/8	10	10	153189
QSTF...	R3/8	12	10	153190
QSTF...	R1/2	12	10	153191
QSTF...	G1/8	4	10	186199
QSTF...	G1/8	6	10	186200
QSTF...	G1/8	8	10	186202
QSTF...	G1/4	6	10	186201
QSTF...	G1/4	8	10	186203
QSTF...	G1/4	10	10	186205
QSTF...	G3/8	8	10	186204
QSTF...	G3/8	10	10	186206
QSTF...	G3/8	12	1	186207
QSTF...	G1/2	12	1	186208

Push-in T-fitting

Type	A	D2	PE	TN
QSTL...	R1/8	4	10	153117
QSTL...	R1/8	4	100	130824
QSTL...	R1/8	6	10	153118
QSTL...	R1/8	6	100	130825
QSTL...	R1/8	8	10	153120
QSTL...	R1/8	8	50	130826
QSTL...	R1/4	6	10	153119
QSTL...	R1/4	6	100	130827
QSTL...	R1/4	8	10	153121
QSTL...	R1/4	8	50	130828
QSTL...	R1/4	10	10	153123
QSTL...	R1/4	10	50	130829
QSTL...	R3/8	8	10	153122
QSTL...	R3/8	10	10	153124
QSTL...	R3/8	12	10	153125
QSTL...	R1/2	12	1	153126
QSTL...	R1/2	16	1	153127
QSTL...	G1/8	4	10	186168
QSTL...	G1/8	4	100	132075
QSTL...	G1/8	6	10	186169
QSTL...	G1/8	6	100	132076
QSTL...	G1/8	8	10	186171
QSTL...	G1/8	8	50	132077
QSTL...	G1/4	6	10	186170
QSTL...	G1/4	6	100	132078
QSTL...	G1/4	8	10	186172
QSTL...	G1/4	8	50	132079
QSTL...	G1/4	10	10	186174
QSTL...	G1/4	10	50	132080
QSTL...	G3/8	8	10	186173
QSTL...	G3/8	10	10	186175
QSTL...	G3/8	12	10	186176
QSTL...	G1/2	12	1	186177
QSTL...	G1/2	16	1	186178

Push-in fitting

Type	A	D2	PE	TN
QSW...	R1/8	4	10	130596
QSW...	R1/8	6	10	130597
QSW...	R1/8	8	10	130598
QSW...	R1/4	6	10	130599
QSW...	R1/4	8	10	130600
QSW...	R1/4	10	10	130601
QSW...	R3/8	8	10	130602
QSW...	R3/8	10	10	130603
QSW...	R1/2	12	1	130604
QSW...	R1/2	16	1	130605

Push-in Y-fitting

Type	A	D2	PE	TN
QSY...	M5	4	10	190673
QSY...	M5	6	10	190674
QSY...	R1/8	4	10	153138
QSY...	R1/8	6	10	153139
QSY...	R1/8	8	10	153141
QSY...	R1/4	4	10	190675
QSY...	R1/4	6	10	153140
QSY...	R1/4	8	10	153142
QSY...	R1/4	10	10	153144
QSY...	R3/8	8	10	153143
QSY...	R3/8	10	10	153145
QSY...	R3/8	12	10	153146
QSY...	R1/2	12	10	153147
QSY...	G1/8	4	10	186179
QSY...	G1/8	6	10	186180
QSY...	G1/8	8	10	186182
QSY...	G1/4	6	10	186181
QSY...	G1/4	8	10	186183
QSY...	G1/4	10	10	186185
QSY...	G3/8	8	10	186184
QSY...	G3/8	10	10	186186
QSY...	G3/8	12	10	186187

Push-in Y-fitting

Type	A	D2	PE	TN
QSYLV...	R1/8	6	1	153192
QSYLV...	R1/4	8	1	153193
QSYLV...	R3/8	10	1	153194
QSYLV...	R1/2	12	1	153195
QSYLV...	G1/8	6	1	186209
QSYLV...	G1/4	8	1	186210
QSYLV...	G3/8	10	1	186211
QSYLV...	G1/2	12	1	186212

Type	A	D2	PE	TN
QSYTF...	R1/8	6	1	153196
QSYTF...	R1/4	8	1	153197
QSYTF...	R3/8	10	1	153198
QSYTF...	R1/2	12	1	153199
QSYTF...	G1/8	6	1	186213
QSYTF...	G1/4	8	1	186214
QSYTF...	G3/8	10	1	186215
QSYTF...	G1/2	12	1	186216

Multiple distributor

Type	A	D2	PE	TN
QSLV3...	R1/8	4	1	153221
QSLV3...	R1/8	6	1	153222
QSLV3...	R1/8	8	1	153224
QSLV3...	R1/4	6	1	153223
QSLV3...	R1/4	8	1	153225
QSLV3...	R1/4	10	1	153227
QSLV3...	R3/8	8	1	153226
QSLV3...	R3/8	10	1	153228
QSLV3...	R3/8	12	1	153229
QSLV3...	R1/2	12	1	153230
QSLV3...	G1/8	4	1	186233
QSLV3...	G1/8	6	1	186234
QSLV3...	G1/8	8	1	186236
QSLV3...	G1/4	6	1	186235
QSLV3...	G1/4	8	1	186237
QSLV3...	G1/4	10	1	186239
QSLV3...	G3/8	8	1	186238
QSLV3...	G3/8	10	1	186240
QSLV3...	G3/8	12	1	186241
QSLV3...	G1/2	12	1	186242

Multiple distributor

Type	A	D2	PE	TN
QSLV6...	R1/8	4	1	153241
QSLV6...	R1/8	6	1	153242
QSLV6...	R1/8	8	1	153244
QSLV6...	R1/4	6	1	153243
QSLV6...	R1/4	8	1	153245
QSLV6...	R1/4	10	1	153247
QSLV6...	R3/8	8	1	153246
QSLV6...	R3/8	10	1	153248
QSLV6...	R3/8	12	1	153249
QSLV6...	R1/2	12	1	153250
QSLV6...	G1/8	4	1	186253
QSLV6...	G1/8	6	1	186254
QSLV6...	G1/8	8	1	186256
QSLV6...	G1/4	6	1	186255
QSLV6...	G1/4	8	1	186257
QSLV6...	G1/4	10	1	186259
QSLV6...	G3/8	8	1	186258
QSLV6...	G3/8	10	1	186260
QSLV6...	G3/8	12	1	186261
QSLV6...	G1/2	12	1	186262

Multiple distributor

Type	A	D2	PE	TN
QSQ...	R1/8	4	1	153206
QSQ...	R1/8	6	1	153208
QSQ...	R1/4	4	1	153207
QSQ...	R1/4	6	1	153288
QSQ...	G1/8	4	1	186220
QSQ...	G1/8	6	1	186222
QSQ...	G1/4	4	1	186221
QSQ...	G1/4	6	1	186263

Multiple distributor

Type	A	D2	PE	TN
QSLV2...	R1/8	4	1	153211
QSLV2...	R1/8	6	1	153212
QSLV2...	R1/8	8	1	153214
QSLV2...	R1/4	6	1	153213
QSLV2...	R1/4	8	1	153215
QSLV2...	R1/4	10	1	153217
QSLV2...	R3/8	8	1	153216
QSLV2...	R3/8	10	1	153218
QSLV2...	R3/8	12	1	153219
QSLV2...	R1/2	12	1	153220
QSLV2...	G1/8	4	1	186223
QSLV2...	G1/8	6	1	186224
QSLV2...	G1/8	8	1	186226
QSLV2...	G1/4	6	1	186225
QSLV2...	G1/4	8	1	186227
QSLV2...	G1/4	10	1	186229
QSLV2...	G3/8	8	1	186228
QSLV2...	G3/8	10	1	186230
QSLV2...	G3/8	12	1	186231
QSLV2...	G1/2	12	1	186232

Push-in Y-fitting

Type	A	D2	PE	TN
QSLV4...	R1/8	4	1	153231
QSLV4...	R1/8	6	1	153232
QSLV4...	R1/8	8	1	153234
QSLV4...	R1/4	6	1	153233
QSLV4...	R1/4	8	1	153235
QSLV4...	R1/4	10	1	153237
QSLV4...	R3/8	8	1	153236
QSLV4...	R3/8	10	1	153238
QSLV4...	R3/8	12	1	153239
QSLV4...	R1/2	12	1	153240
QSLV4...	G1/8	4	1	186243
QSLV4...	G1/8	6	1	186244
QSLV4...	G1/8	8	1	186246
QSLV4...	G1/4	6	1	186245
QSLV4...	G1/4	8	1	186247
QSLV4...	G1/4	10	1	186249
QSLV4...	G3/8	8	1	186248
QSLV4...	G3/8	10	1	186250
QSLV4...	G3/8	12	1	186251
QSLV4...	G1/2	12	1	186252

Multiple distributor

Type	A	D2	PE	TN
QST3...	R1/8	6	1	153200
QST3...	R1/4	8	1	153201
QST3...	R3/8	10	1	153202
QST3...	G1/8	6	1	186217
QST3...	G1/4	8	1	186218
QST3...	G3/8	10	1	186219

Legend

A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment

All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard fittings Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	**Poster** **Standard connectors**	**Types** **• Straight, T, L, X, Y-shaped** **• With push-in sleeve** **• Push-in bulkhead fittings and push-in fittings, self-sealing**	**Applications** **• Wide range of variants** **• Hydrolysis resistant** **• Pressure resistant** **• Economical**
QS-B	Fittings connectors for core functions	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	Metallic push-in fittings	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	Polypropylene fittings	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	Metal and special fittings/connectors	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... PAN-... PEN PFAN PLN	Plastic tubing	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

QS standard – Push-in connectors

Here you will find the optimum connectors in polymer design for applications shown opposite.

With appropriate tubing from poster 6 you will always obtain the right tubing/fitting combination.

Wide range of variants: PUN/QS

Over 1000 types for maximum flexibility with standard applications.

Hydrolysis resistant: PUN-H/QS

For applications in damp environments or in contact with water up to 60°C.
PUN-H – microbe resistant thanks to modified material.

Pressure resistant I: PAN/QS

Reliable connection with pressure ranges up to 14 bar. Economical with pneumatic installations in the high pressure range.

QS standard, Mini

Push-in connector

Type	D1	D2	PE	TN
QSM-...	3	3	10	153323
QSM-...	3	3	100	130757
QSM-...	4	4	10	153324
QSM-...	4	4	100	130758
QSM-...	6	6	10	153325
QSM-...	6	6	100	130759
reducing				
QSM-...	4	3	10	153326
QSM-...	4	3	100	130760
QSM-...	6	4	10	153327
QSM-...	6	4	100	130761

Push-in connector
with push-in sleeve

Type	D1	D2	PE	TN
QSM-...H	4	3	10	153328
QSM-...H	4	3	100	130762
QSM-...H	6	4	10	153329
QSM-...H	6	4	100	130763

Push-in L-connector

Type	D1	D2	PE	TN
QSML-...	3	3	10	153343
QSML-...	4	4	10	153344
QSML-...	4	4	100	130766
QSML-...	6	6	10	153345
QSML-...	6	6	100	130767
with push-in sleeve				
QSML-...H	3	3	10	153346
QSML-...H	4	4	10	153347
QSML-...H	6	6	10	153348
reducing				
QSML-...H	4	3	10	153349
QSML-...H	6	4	10	153350

Push-in T-connector

Type	D1	D2	PE	TN
QSMT-...	3	3	10	153365
QSMT-...	4	4	10	153366
QSMT-...	4	4	100	130782
QSMT-...	6	6	10	153367
QSMT-...	6	6	100	130783
reducing				
QSMT-...	4	3	10	153368
QSMT-...	6	4	10	153369

Push-in X-connector

Type	D1	D2	PE	TN
QSMX	3	3	10	153378
QSMX	4	4	10	153379
QSMX	6	6	10	153380

Push-in Y-connector

Type	D1	D2	PE	TN
QSMY	3	3	10	153370
QSMY	4	4	10	153371
QSMY	6	6	10	153372
reducing				
QSMY	4	3	10	153373
QSMY	6	4	10	153374

Blanking plug

Type	D1	PE	TN
QSC-...H	4	10	153267
QSC-...H	4	100	130699
QSC-...H	6	10	153268
QSC-...H	6	100	130700
QSC-...H	8	10	153269
QSC-...H	8	50	130701
QSC-...H	10	10	153270
QSC-...H	10	50	130702
QSC-...H	12	10	153271
QSC-...H	12	20	130703
QSC-...H	16	10	153272

QS standard

Push-in connector

Type	D1	D2	PE	TN
QS-...	4	4	10	153031
QS-...	4	4	100	130686
QS-...	6	6	10	153032
QS-...	6	6	100	130687
QS-...	8	8	10	153033
QS-...	8	8	50	130688
QS-...	10	10	10	153034
QS-...	10	10	50	130689
QS-...	12	12	10	153035
QS-...	12	12	20	130690
QS-...	16	16	1	153036
reducing				
QS-...	6	4	10	153037
QS-...	6	4	100	130691
QS-...	8	4	10	130606
QS-...	8	6	10	153038
QS-...	8	6	50	130692
QS-...	10	6	10	130607
QS-...	10	8	10	153039
QS-...	10	8	50	130693
QS-...	12	8	10	130608
QS-...	12	10	10	153040
QS-...	12	10	20	130694

Push-in cap

Type	D1	PE	TN
QSMC-...	3	10	153381
QSC-...	4	10	153262
QSC-...	4	100	130704
QSC-...	6	10	153263
QSC-...	6	100	130705
QSC-...	8	10	153264
QSC-...	8	50	130706
QSC-...	10	10	153265
QSC-...	10	50	130707
QSC-...	12	10	153266
QSC-...	12	20	130708

Locking srew

Type	D1	PE	TN
QSC-...-I	G1/8F	10	556855
QSC-...-I	G1/4F	10	556858
QSC-...-I	G3/8F	10	556859
QSC-...-I	G1/2F	10	556860

Push-in connector
with push-in sleeve

Type	D1	D2	PE	TN
QS-...H	4	6	10	153041
QS-...H	4	6	100	130695
QS-...H	4	8	10	130622
QS-...H	6	8	10	153042
QS-...H	6	8	50	130696
QS-...H	6	10	10	130623
QS-...H	8	10	10	153043
QS-...H	8	10	50	130697
QS-...H	8	12	10	130624
QS-...H	10	12	10	153044
QS-...H	10	12	20	130698

Push-in sleeve

Type	D1	D2	PE	TN
QSH-...	4	4	10	153251
QSH-...	4	4	100	130723
QSH-...	6	6	10	153252
QSH-...	6	6	100	130724
QSH-...	8	8	10	153253
QSH-...	8	8	50	130725
QSH-...	10	10	10	153254
QSH-...	10	10	50	130726
QSH-...	12	12	10	153255
QSH-...	12	12	20	130727
QSH-...	16	16	10	153256
reducing				
QSH-...	6	4	10	153257
QSH-...	6	4	100	130718
QSH-...	8	4	10	130625
QSH-...	8	6	10	153258
QSH-...	8	6	50	130719
QSH-...	10	6	10	130626
QSH-...	10	8	10	153259
QSH-...	10	8	50	130720
QSH-...	12	8	10	130627
QSH-...	12	10	10	153260
QSH-...	12	10	20	130721
QSH-...	16	12	1	153261
QSH-...	16	12	20	130722

Push-in bulkhead connector

Type	D1	D2	PE	TN
QSMS-...	3	3	10	153375
QSMS-...	4	4	10	153376
QSMS-...	4	4	100	130780
QSMS-...	6	6	10	153377
QSMS-...	6	6	100	130781

Push-in bulkhead connector

Type	D1	D2	PE	TN
QSS-...	4	4	10	153157
QSS-...	4	4	100	130788
QSS-...	6	6	10	153158
QSS-...	6	6	100	130789
QSS-...	8	8	10	153159
QSS-...	8	8	50	130790
QSS-...	10	10	10	153160
QSS-...	10	10	50	130791
QSS-...	12	12	10	153161
QSS-...	12	12	20	130792

Push-in bulkhead connector
with fixed collar

Type	D1	D2	PE	TN
QSS-F...	4	4	10	193950
QSS-F...	6	6	10	193951
QSS-F...	8	8	10	130642
QSS-F...	10	10	10	130643
QSS-F...	12	12	10	130644

Push-in connector, self-sealing

Type	D1	D2	PE	TN
QSK-...	4	4	10	153439
QSK-...	6	6	10	153440
QSK-...	8	8	10	153441
QSK-...	10	10	10	153442
QSK-...	12	12	10	153443

Push-in bulkhead connector
blocking

Type	D1	D2	PE	TN
QSSK...	4	4	10	130637
QSSK...	6	6	10	130638
QSSK...	8	8	10	130639
QSSK...	10	10	10	130640
QSSK...	12	12	10	130641

Push-in L-connector

Type	D1	D2	PE	TN
QSL-...	4	4	10	153070
QSL-...	4	4	100	130740
QSL-...	6	6	10	153071
QSL-...	6	6	100	130741
QSL-...	8	8	10	153072
QSL-...	8	8	50	130742
QSL-...	10	10	10	153073
QSL-...	10	10	50	130743
QSL-...	12	12	10	153074
QSL-...	12	12	20	130744
QSL-...	16	16	1	153075

Push-in L-connector
with push-in sleeve

Type	D1	D2	PE	TN
QSL-H-...	4	4	10	153056
QSL-H-...	4	4	100	130745
QSL-H-...	6	6	10	153057
QSL-H-...	6	6	100	130746
QSL-H-...	8	8	10	153058
QSL-H-...	8	8	50	130747
QSL-H-...	10	10	10	153059
QSL-H-...	10	10	50	130748
QSL-H-...	12	12	10	153060
reducing				
QSL-H-...	6	4	10	153061
QSL-H-...	8	6	10	153062
QSL-H-...	10	8	10	153063
QSL-H-...	12	10	10	153064

Push-in L-connector
with long push-in sleeve

Type	D1	D2	PE	TN
QSL-HL-...	4	4	10	153065
QSL-HL-...	6	6	10	153066
QSL-HL-...	8	8	10	153067
QSL-HL-...	10	10	10	153068
QSL-HL-...	12	12	10	153069

Push-in T-connector

Type	D1	D2	PE	TN
QST-...	4	4	10	153128
QST-...	4	4	100	130802
QST-...	6	6	10	153129
QST-...	6	6	100	130803
QST-...	8	8	10	153130
QST-...	8	8	50	130804
QST-...	10	10	10	153131
QST-...	10	10	50	130805
QST-...	12	12	10	153132
QST-...	12	12	20	130806
QST-...	16	16	1	153133
reducing				
QST-...	6	4	10	153134
QST-...	6	4	100	130820
QST-...	8	4	10	130613
QST-...	8	6	10	153135
QST-...	8	6	50	130821
QST-...	10	6	10	130614
QST-...	10	8	10	153136
QST-...	10	8	50	130822
QST-...	12	8	10	130615
QST-...	12	10	10	153137
QST-...	12	10	20	130823
QST-...	16	12	1	130616

Push-in connector
with push-in sleeve

Type	D1	D2	PE	TN
QSW-...HL	4	4	10	130617
QSW-...HL	6	6	10	130618
QSW-...HL	8	8	10	130619
QSW-...HL	10	10	10	130620
QSW-...HL	12	12	10	130621

Push-in X-connector

Type	D1	D2	PE	TN
QSX-...	8	8	10	153285
QSX-...	10	10	10	153286
QSX-...	12	12	10	153287

Multiple distributor reducing

Type	A	D2	PE	TN
QSQ...	6	4	1	153209
QSQ...	8	6	1	153210

Push-in Y-connector

Type	D1	D2	PE	TN
QSY-...	4	4	10	153148
QSY-...	4	4	100	130807
QSY-...	6	6	10	153149
QSY-...	6	6	100	130808
QSY-...	8	8	10	153150
QSY-...	8	8	50	130809
QSY-...	10	10	10	153151
QSY-...	10	10	20	130810
QSY-...	12	12	10	153152
QSY-...	12	12	20	130811
QSY-...	16	16	1	130609
reducing				
QSY-...	6	4	10	153153
QSY-...	6	4	100	130812
QSY-...	8	4	10	130610
QSY-...	8	6	10	153154
QSY-...	8	6	50	130813
QSY-...	10	6	10	130611
QSY-...	10	8	10	153155
QSY-...	10	8	20	130814
QSY-...	12	8	10	130612
QSY-...	12	10	10	153156
QSY-...	12	10	20	130815
QSY-...	16	12	1	190708

Push-in Y-connector
with push-in sleeve

Type	D1	D2	PE	TN
QSY-H...	4	4	10	130628
QSY-H...	6	6	10	130629
QSY-H...	8	8	10	130630
QSY-H...	10	10	10	130631
QSY-H...	12	12	10	130632
reducing				
QSY-H...	6	4	10	130633
QSY-H...	8	6	10	130634
QSY-H...	10	8	10	130635
QSY-H...	12	10	10	130636

Multiple distributor reducing

Type	A	D2	PE	TN
QST3...	6	4	1	153203
QST3...	8	6	1	153204
QST3...	10	8	1	153205

Legend
A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment
All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard fittings Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard connectors	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	**Fittings connectors for core functions**	**• Mini types • Straight, T, L, X, Y-shaped**	**• Economical**
NPQM	Metallic push-in fittings	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	Polypropylene fittings	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	Metal and special fittings/connectors	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... PAN-... PEN PFAN PLN	Plastic tubing	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

QS-B for core functions – Push-in fittings and connectors

Here you will find the optimum fittings in polymer design for applications shown opposite.

With appropriate tubing from poster 6 you will always obtain the right tubing/fitting combination.

Economical I:
PUN-E/QS-B

Core functions at an attractive price. Easy to install, thanks to inherent resilience in the case of tubing bends. Practical: Reels from 50 up to 500 m.

QS-B Mini

Push-in fitting

Type	A	D2	PE	TN
QSM-B	M3	3	20	132102
QSM-B	M3	4	20	130894
QSM-B	M5	3	20	132103
QSM-B	M5	4	20	130895
QSM-B	M5	6	20	130896
QSM-B	R1/8	4	20	132104
QSM-B	R1/8	6	20	132105

Push-in L-fitting

Type	A	D2	PE	TN
QSML-B	M3	3	20	132106
QSML-B	M3	4	20	130899
QSML-B	M5	3	20	132107
QSML-B	M5	4	20	130900
QSML-B	M5	6	20	130901
QSML-B	M7	4	20	132108
QSML-B	M7	6	20	132109
QSML-B	R1/8	4	20	132110
QSML-B	R1/8	6	20	132111

Push-in fitting
with internal hex

Type	A	D2	PE	TN
QSM-B-I	M3	3	20	132116
QSM-B-I	M3	4	20	130909
QSM-B-I	M5	3	20	132117
QSM-B-I	M5	4	20	130910
QSM-B-I	M5	6	20	130911
QSM-B-I	M7	4	20	130912
QSM-B-I	M7	6	20	130913
QSM-B-I	R1/8	4	20	132118
QSM-B-I	R1/8	6	20	132119

Push-in T-fitting

Type	A	D2	PE	TN
QSMT-B	M3	3	20	132112
QSMT-B	M3	4	20	130904
QSMT-B	M5	3	20	132113
QSMT-B	M5	4	20	130905
QSMT-B	M5	6	20	130906
QSMT-B	R1/8	4	20	132114
QSMT-B	R1/8	6	20	132115

QS-B fittings

Push-in fitting

Type	A	D2	PE	TN
QS-B	R1/8	4	20	130914
QS-B	R1/8	6	20	130915
QS-B	R1/8	8	20	130916
QS-B	R1/8	10	20	132120
QS-B	R1/4	4	20	130917
QS-B	R1/4	6	20	130918
QS-B	R1/4	8	20	130919
QS-B	R1/4	10	20	132121
QS-B	R1/4	12	20	132122
QS-B	R3/8	6	10	130920
QS-B	R3/8	8	10	130921
QS-B	R3/8	10	10	130922
QS-B	R3/8	12	10	132123
QS-B	R3/8	16	10	132124
QS-B	R1/2	10	10	130924
QS-B	R1/2	12	10	130925
QS-B	R1/2	16	10	132125

Push-in L-fitting

Type	A	D2	PE	TN
QSL-B	R1/8	4	20	130926
QSL-B	R1/8	6	20	130939
QSL-B	R1/8	8	20	130928
QSL-B	R1/8	10	20	132126
QSL-B	R1/4	4	20	130929
QSL-B	R1/4	6	20	130930
QSL-B	R1/4	8	20	130931
QSL-B	R1/4	10	20	132127
QSL-B	R1/4	12	20	132128
QSL-B	R3/8	6	10	130932
QSL-B	R3/8	8	10	130933
QSL-B	R3/8	10	10	130934
QSL-B	R3/8	12	10	132129
QSL-B	R3/8	16	10	132130
QSL-B	R1/2	10	10	130936
QSL-B	R1/2	12	10	130937
QSL-B	R1/2	16	10	132131

Push-in T-fitting

Type	A	D2	PE	TN
QST-B	R1/8	4	20	130938
QST-B	R1/8	6	20	130939
QST-B	R1/8	8	20	130940
QST-B	R1/8	10	20	132132
QST-B	R1/4	4	20	130941
QST-B	R1/4	6	20	130942
QST-B	R1/4	8	20	130943
QST-B	R1/4	10	20	132133
QST-B	R1/4	12	20	132134
QST-B	R3/8	6	10	130944
QST-B	R3/8	8	10	130945
QST-B	R3/8	10	10	130946
QST-B	R3/8	12	10	132135
QST-B	R3/8	16	10	132136
QST-B	R1/2	10	10	130948
QST-B	R1/2	12	10	130949
QST-B	R1/2	16	10	132137

Push-in T-fitting

Type	A	D2	PE	TN
QSTL-B	R1/8	4	20	130978
QSTL-B	R1/8	6	20	130979
QSTL-B	R1/8	8	20	130980
QSTL-B	R1/4	4	20	130981
QSTL-B	R1/4	6	20	130982
QSTL-B	R1/4	8	20	130983
QSTL-B	R3/8	6	10	130984
QSTL-B	R3/8	8	10	130985
QSTL-B	R3/8	10	10	130986
QSTL-B	R3/8	12	10	132149
QSTL-B	R1/2	10	10	130988
QSTL-B	R1/2	12	10	130989
QST-B	R1/2	16	10	132150

Push-in fitting

Type	A	D2	PE	TN
QS-B-I	R1/8	4	20	130990
QS-B-I	R1/8	6	20	130991
QS-B-I	R1/8	8	20	130992
QS-B-I	R1/8	10	20	132151
QS-B-I	R1/4	6	20	130994
QS-B-I	R1/4	8	20	130995
QS-B-I	R1/4	10	20	132152
QS-B-I	R1/4	12	20	132153
QS-B-I	R3/8	8	10	130997
QS-B-I	R3/8	10	10	130998
QS-B-I	R3/8	12	10	132154
QS-B-I	R1/2	10	10	132000
QS-B-I	R1/2	12	10	132001

Push-in long L-fitting

Type	A	D2	PE	TN
QSLL-B	R1/8	4	20	132002
QSLL-B	R1/8	6	20	132003
QSLL-B	R1/8	8	20	132004
QSLL-B	R1/4	6	20	132006
QSLL-B	R1/4	8	20	132007
QSLL-B	R3/8	6	10	132008
QSLL-B	R3/8	8	10	132009
QSLL-B	R3/8	10	10	132010
QSLL-B	R1/2	10	10	132012
QSLL-B	R1/2	12	10	132013

Push-in Y-fitting

Type	A	D2	PE	TN
QSY-B	R1/8	4	20	132014
QSY-B	R1/8	6	20	132015
QSY-B	R1/8	8	20	132016
QSY-B	R1/4	4	20	132017
QSY-B	R1/4	6	20	132018
QSY-B	R1/4	8	20	132019
QSY-B	R3/8	6	10	132020
QSY-B	R3/8	8	10	132021
QSY-B	R3/8	10	10	132022
QSY-B	R1/2	10	10	132024
QSY-B	R1/2	12	10	132025

QS-B connectors

Push-in connector

Type	D1	D2	PE	TN
QS-B	4	4	20	130964
QS-B	6	6	20	130965
QS-B	8	8	20	130966
QS-B	10	10	10	130967
QS-B	12	12	10	130968
QS-B	16	16	10	132144
reducing				
QS-B	6	4	20	130969
QS-B	8	4	20	132145
QS-B	8	6	20	130970
QS-B	10	6	10	132146
QS-B	10	8	10	130971
QS-B	12	8	10	132147
QS-B	12	10	10	130972

Push-in T-connector

Type	D1	D2	PE	TN
QST-B	4	4	20	130973
QST-B	6	6	20	130974
QST-B	8	8	20	130975
QST-B	10	10	10	130976
QST-B	12	12	10	130977
QST-B	16	16	10	132148

Push-in L-connector

Type	D1	D2	PE	TN
QSL-B	4	4	20	130950
QSL-B	6	6	20	130951
QSL-B	8	8	20	130952
QSL-B	10	10	10	130953
QSL-B	12	12	10	130954
QSL-B	16	16	10	132138

Push-in Y-connector

Type	D1	D2	PE	TN
QSY-B	4	4	20	130955
QSY-B	6	6	20	130956
QSY-B	8	8	20	130957
QSY-B	10	10	10	130958
QSY-B	12	12	10	130959
QSY-B	16	16	10	132139
reducing				
QSY-B	6	4	20	130960
QSY-B	8	4	20	132140
QSY-B	8	6	20	130961
QSY-B	10	6	10	132141
QSY-B	10	8	10	130962
QSY-B	12	8	10	132142
QSY-B	12	10	10	130963
QSY-B	16	12	10	132143

Economical combination with the suitable tube

PUN-E	PE 4	PE 6	PE 8	PE 10	PE 12
silver	50 535320	50 535321	50 535322	50 535323	50 535324
	500 534170	500 534172	400 534174	300 534176	200 534178
blue	50 535325	50 535326	50 535327	50 535328	50 535329
	500 534171	500 534173	400 534175	300 534177	200 534179
black	50 538465	50 538466	50 538467	50 538468	50 538469
	500 538460	500 538461	400 538462	300 538463	200 538464

PEN	PE 4	PE 6	PE 8	PE 10	PE 12	PE 16
nature	50 543246	50 543247	50 543248	50 543249	50 543250	50 543251
silver	50 551462	50 551463	50 551464	50 551465	50 551466	50 551467
	500 551450	500 551451	400 551452	300 551453	200 551454	100 551455
blue	50 551456	50 551457	50 551458	50 551459	50 551460	50 551461
	500 551444	500 551445	400 551446	300 551447	200 551448	100 551449
black	50 543240	50 543241	50 543242	50 543243	50 543244	50 543245
	500 551438	500 551439	400 551440	300 551441	200 551442	100 551443
green	50 551468	50 551469	50 551470	50 551471	50 551772	50 551473
red	50 551474	50 551475	50 551776	50 551477	50 551478	50 551479
yellow	50 551480	50 551481	50 551482	50 551483	50 551484	50 551485

Legend
A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment
All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard fittings Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard connectors	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	Fittings connectors for core functions	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	**Metallic push-in fittings**	**• Push-in fittings with internal hex, thread, T, L-shaped** **• Plug connector straight, with sleeve, L, T, Y-shaped**	**• Economical** **• Antistatic** **• Flame-retardant**
NPQP	Polypropylene fittings	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	Metal and special fittings/connectors	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... PAN-... PEN PFAN PLN	Plastic tubing	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

Metal push-in fittings

On this page, you can find the optimum metal fittings for the following applications.

You can locate the suitable tubing/fitting combination using the suitable tubes from poster 6 "Plastic tubing".

Economical:
PEN/NPQM

The universal solution for metal fittings. Perfect for standard pneumatics applications in many different fields.



Antistatic:
PUN-CM/NPQM

Electrically conductive tubing combined with an all-metal fitting.

Flame retardant:
PUN-V0/NPQM

Safe in areas where there is a risk of fire thanks to flame retardant properties to UL94.

NPQM

Push-in fitting
with internal hexagon socket

Type	A	D2	PE	TN
NPQM-DK	M5	4	10	558657
NPQM-DK	M5	6	10	558658
NPQM-DK	M7	4	10	558659
NPQM-DK	M7	6	10	558660

Push-in fitting
Female thread

Type	A	D2	PE	TN
NPQM-D	G1/8F	4	10	558674
NPQM-D	G1/8F	6	10	558675
NPQM-D	G1/8F	8	10	558676
NPQM-D	G1/4F	6	10	558678
NPQM-D	G1/4F	8	10	558679
NPQM-D	G1/4F	10	10	558680

Push-in fitting

Type	A	D2	PE	TN
NPQM-D	R1/8	4	10	558661
NPQM-D	R1/8	6	10	558662
NPQM-D	R1/8	8	10	558663
NPQM-D	R1/4	6	10	558664
NPQM-D	R1/4	8	10	558665
NPQM-D	R1/4	10	10	558666
NPQM-D	R1/4	12	10	558667
NPQM-D	R3/8	8	10	558668
NPQM-D	R3/8	10	10	558669
NPQM-D	R3/8	12	10	558670
NPQM-D	R1/2	10	10	558671
NPQM-D	R1/2	12	10	558672

Push-in L-fitting

Type	A	D2	PE	TN
NPQM-L	M5	4	10	558704
NPQM-L	M5	6	10	558705
NPQM-L	G1/8	4	10	558708
NPQM-L	G1/8	6	10	558709
NPQM-L	G1/8	8	10	558710
NPQM-L	G1/4	6	10	558711
NPQM-L	G1/4	8	10	558712
NPQM-L	G1/4	10	10	558713
NPQM-L	G1/4	12	10	558714
NPQM-L	G3/8	8	10	558715
NPQM-L	G3/8	10	10	558716
NPQM-L	G3/8	12	10	558717
NPQM-L	G1/2	10	10	558718
NPQM-L	G1/2	12	10	558719

Push-in T-fitting

Type	A	D2	PE	TN
NPQM-T	G1/8	4	10	558736
NPQM-T	G1/8	6	10	558737
NPQM-T	G1/8	8	10	558738
NPQM-T	G1/4	6	10	558739
NPQM-T	G1/4	8	10	558740
NPQM-T	G1/4	10	10	558741
NPQM-T	G3/8	8	10	558743
NPQM-T	G3/8	10	10	558744
NPQM-T	G3/8	12	10	558745
NPQM-T	G1/2	12	10	558747

Push-in L-fitting

Type	D1	D2	PE	TN
NPQM-LK	M5	3	10	558816
NPQM-LK	M5	4	10	558817
NPQM-LK	G1/8	4	10	558818
NPQM-LK	G1/8	6	10	558819
NPQM-LK	G1/8	8	10	558820
NPQM-LK	G1/4	6	10	558821
NPQM-LK	G1/4	8	10	558822
NPQM-LK	G1/4	10	10	558823
NPQM-LK	G3/8	12	10	558825

Push-in L-fitting

Type	D1	D2	PE	TN
NPQM-LH	M5	4	10	558827
NPQM-LH	M5	6	10	558828
NPQM-LH	G1/8	4	10	558829
NPQM-LH	G1/8	6	10	558830
NPQM-LH	G1/8	8	10	558831
NPQM-LH	G1/4	6	10	558832
NPQM-LH	G1/4	8	10	558833
NPQM-LH	G1/8	8	10	558834
NPQM-LH	G1/8	10	10	558835
NPQM-LH	G1/8	12	10	558836

Push-in sleeve

Type	D1	PE	TN
NPQM-D	4	10	558811
NPQM-D	6	10	558812
NPQM-D	8	10	558813
NPQM-D	10	10	558814
NPQM-D	12	10	558815

Multiple distributor

Type	D1	D2	PE	TN
NPQM-LFK	G1/8	4	10	558837
NPQM-LFK	G1/8	6	10	558838
NPQM-LFK	G1/8	8	10	558839
NPQM-LFK	G1/4	6	10	558840
NPQM-LFK	G1/4	8	10	558841

Push-in L-connector
with sleeve

Type	D1	D2	PE	TN
NPQM-L	4	4	10	558781
NPQM-L	6	6	10	558782
NPQM-L	8	8	10	558783
NPQM-L	10	10	10	558784

Push-in T-connector

Type	D1	D2	PE	TN
NPQM-T	4	4	10	558786
NPQM-T	6	6	10	558787
NPQM-T	8	8	10	558788
NPQM-T	10	10	10	558789
NPQM-T	12	12	10	558790

Straight plug connector
with sleeve

Type	D1	D2	PE	TN
NPQM-T	4	4	10	558791
NPQM-T	6	6	10	558792
NPQM-T	8	8	10	558793
NPQM-T	10	10	10	558794

Push-in Y-connector

Type	D1	D2	PE	TN
NPQM-Y	4	4	10	558798
NPQM-Y	6	6	10	558799
NPQM-Y	8	8	10	558800
NPQM-Y	10	10	10	558801
NPQM-Y	12	12	10	558802
reducing				
NPQM-Y	6	4	10	558803
NPQM-Y	8	6	10	558804
NPQM-Y	10	8	10	558805

Push-in L-connector

Type	D1	D2	PE	TN
NPQM-L	4	4	10	558776
NPQM-L	6	6	10	558777
NPQM-L	8	8	10	558778
NPQM-L	10	10	10	558779
NPQM-L	12	12	10	558780

Push-in bulkhead connector

Type	D1	D2	PE	TN
NPQM-H	4	4	10	558806
NPQM-H	6	6	10	558807
NPQM-H	8	8	10	558808
NPQM-H	10	10	10	558809
NPQM-H	12	12	10	558810

Straight plug connector

Type	D1	D2	PE	TN
NPQM-D	4	4	10	558760
NPQM-D	6	6	10	558761
NPQM-D	8	8	10	558762
NPQM-D	10	10	10	558763
NPQM-D	12	12	10	558764

Straight plug connector
with sleeve

Type	A	D2	PE	TN
NPQM-D	4	6	10	558765
NPQM-D	4	8	10	558766
NPQM-D	6	4	10	558767
NPQM-D	6	8	10	558768
NPQM-D	6	10	10	558769
NPQM-D	6	12	10	558770
NPQM-D	8	6	10	558771
NPQM-D	8	10	10	558772
NPQM-D	8	12	10	558773
NPQM-D	10	12	10	558774

Legend
A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment
All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard fittings Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard connectors	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	Fittings connectors for core functions	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	Metallic push-in fittings	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	**Polypropylene fittings**	**• Plug connectors, L, T, Y-shaped** **• Plug connectors, L, T, Y-shaped** **• Bulkhead connector** **• Blanking plugs**	**• Cleaning agent** **• Media resistant**
QS-F CRQS QS-V0	Metal and special fittings/connectors	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... PAN-... PEN PFAN PLN	Plastic tubing	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

Polypropylene fittings

On this page, you can find the optimum polypropylene fittings for the following applications.

You can locate the suitable tubing/fitting combination using the suitable tubes from poster 6 "Plastic tubing".

Resistant to cleaning agents: PLN/NPQP

The cost-effective alternative to stainless steel is highly resistant to all usual cleaning agents and has maximum corrosion protection. That makes it perfect for critical environments such as splash zones.

Media-resistant: PFAN/NPQP

Completely resistant to all cleaning agents and lubricants and even permits the conveyance of acids and lyes without any problems.

NPQP

FESTO

Push-in fitting

Type	A	D2	PE	TN
NPQP-D	R1/8	4	1	132417
NPQP-D	R1/8	6	1	132418
NPQP-D	R1/8	8	1	132419
NPQP-D	R1/4	4	1	132420
NPQP-D	R1/4	6	1	132421
NPQP-D	R1/4	8	1	132422
NPQP-D	R1/4	10	1	132423
NPQP-D	R3/8	10	1	132424
NPQP-D	R3/8	12	1	132425
NPQP-D	R1/2	12	1	132426

Push-in L-fitting

Type	A	D2	PE	TN
NPQP-L	R1/8	4	1	132428
NPQP-L	R1/8	6	1	132429
NPQP-L	R1/8	8	1	132430
NPQP-L	R1/4	4	1	132431
NPQP-L	R1/4	6	1	132432
NPQP-L	R1/4	8	1	132433
NPQP-L	R1/4	10	1	132434
NPQP-L	R3/8	10	1	132435
NPQP-L	R3/8	12	1	132436
NPQP-L	R1/2	12	1	132437

Push-in L-fitting

Type	A	D2	PE	TN
NPQP-LQ	R1/8	4	1	132439
NPQP-LQ	R1/8	6	1	132440
NPQP-LQ	R1/8	8	1	132441
NPQP-LQ	R1/4	4	1	132442
NPQP-LQ	R1/4	6	1	132443
NPQP-LQ	R1/4	8	1	132444
NPQP-LQ	R1/4	10	1	132445
NPQP-LQ	R3/8	10	1	132446
NPQP-LQ	R3/8	12	1	132447
NPQP-LQ	R1/2	12	1	132448

Push-in T-fitting

Type	A	D2	PE	TN
NPQP-T	R1/8	4	1	132450
NPQP-T	R1/8	6	1	132451
NPQP-T	R1/8	8	1	132452
NPQP-T	R1/4	4	1	132453
NPQP-T	R1/4	6	1	132454
NPQP-T	R1/4	8	1	132455
NPQP-T	R1/4	10	1	132456
NPQP-T	R3/8	10	1	132457
NPQP-T	R3/8	12	1	132458
NPQP-T	R1/2	12	1	132459

Push-in Y-fitting

Type	A	D2	PE	TN
NPQP-Y	R1/8	4	1	132461
NPQP-Y	R1/8	6	1	132462
NPQP-Y	R1/8	8	1	132463
NPQP-Y	R1/4	4	1	132464
NPQP-Y	R1/4	6	1	132465
NPQP-Y	R1/4	8	1	132466
NPQP-Y	R1/4	10	1	132467
NPQP-Y	R3/8	10	1	132468
NPQP-Y	R3/8	12	1	132469
NPQP-Y	R1/2	12	1	132470

Push-in fitting with sleeve

Type	D1	D2	PE	TN
NPQP-D...	6	4	1	132588
NPQP-D...	8	4	1	132589
NPQP-D...	8	6	1	132590
NPQP-D...	10	6	1	132591
NPQP-D...	10	8	1	132592
NPQP-D...	12	8	1	132593
NPQP-D...	12	10	1	132594

Blanking plug

Type	D1	D2	PE	TN
NPQP-P...	4		1	1132582
NPQP-P...	6		1	1132583
NPQP-P...	8		1	1132584
NPQP-P...	10		1	1132585
NPQP-P...	12		1	1132586

Push-in fitting

Type	D1	D2	PE	TN
NPQP-D	4	4	1	132537
NPQP-D	6	6	1	132538
NPQP-D	8	8	1	132539
NPQP-D	10	10	1	132540
NPQP-D	12	12	1	132541
reducing				
NPQP-D	6	4	1	132543
NPQP-D	8	6	1	132544
NPQP-D	10	8	1	132545
NPQP-D	12	10	1	132546

Push-in bulkhead connector

Type	D1	PE	TN
NPQM-H	4	1	132548
NPQM-H	6	1	132549
NPQM-H	8	1	132550
NPQM-H	10	1	132551
NPQM-H	12	1	132552

Push-in L-connector

Type	D1	D2	PE	TN
NPQP-L	4	4	1	132554
NPQP-L	6	6	1	132554
NPQP-L	8	8	1	132554
NPQP-L	10	10	1	132554
NPQP-L	12	12	1	132554

Push-in T-connector

Type	D1	D2	PE	TN
NPQP-L	4	4	1	132560
NPQP-L	6	6	1	132561
NPQP-L	8	8	1	132562
NPQP-L	10	10	1	132563
NPQP-L	12	12	1	132564
reducing				
NPQP-L	6	4	1	132566
NPQP-L	8	6	1	132567
NPQP-L	10	8	1	132568
NPQP-L	12	10	1	132569

Push-in Y-connector

Type	D1	D2	PE	TN
NPQP-Y...	4	4	1	132571
NPQP-Y...	6	6	1	132572
NPQP-Y...	8	8	1	132573
NPQP-Y...	10	10	1	132574
NPQP-Y...	12	12	1	132575
reducing				
NPQP-Y...	6	4	1	132577
NPQP-Y...	8	6	1	132578
NPQP-Y...	10	8	1	132579
NPQP-Y...	12	10	1	132580

Legend

A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment

All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard fittings Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard connectors	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	Fittings connectors for core functions	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	Metallic push-in fittings	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	Polypropylene fittings	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	**Metal and special fittings/connectors**	**• Metal, stainless steel, • Straight, L and T-shaped**	**• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant**
PUN-... PAN-... PEN PFAN PLN	Plastic tubing	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

Metal and special fittings/connectors

Suitable for the food industry, heat resistant, antistatic, flame-retardant, resistant to cleaning agents, pressure resistant, resistant to welding spatter

Resistant to welding spatter

Resistant to media

QS-F

Push-in fitting

Type	A	D2	PE	TN
QS-F	M5	4	10	533844
QS-F	M5	6	10	533845
QS-F	M7	4	10	533846
QS-F	M7	6	10	533847
QS-F	G1/8	4	10	193408
QS-F	G1/8	6	10	193409
QS-F	G1/8	8	10	193410
QS-F	G1/4	6	10	193411
QS-F	G1/4	8	10	193412
QS-F	G1/4	10	10	193413
QS-F	G1/4	12	10	533848
QS-F	G3/8	8	10	193414
QS-F	G3/8	10	10	193415
QS-F	G3/8	12	10	197487
QS-F	G1/2	10	10	193416
QS-F	G1/2	12	10	193417

Push-in fitting

Type	A	D2	PE	TN
QS-F-H	M5	4	10	533874
QS-F-H	M5	6	10	533875
QS-F-H	M7	4	10	533876
QS-F-H	M7	6	10	533877
QS-F-H	G1/8	4	10	533878
QS-F-H	G1/8	6	10	533879
QS-F-H	G1/8	8	10	533880
QS-F-H	G1/4	6	10	533881
QS-F-H	G1/4	8	10	533882
QS-F-H	G1/4	10	10	533883
QS-F-H	G1/4	12	10	533884
QS-F-H	G3/8	8	10	533885
QS-F-H	G3/8	10	10	533886
QS-F-H	G3/8	12	10	533887
QS-F-H	G1/2	10	10	533888
QS-F-H	G1/2	12	10	533889

Push-in L-fitting

Type	A	D2	PE	TN
QSL-F	M5	4	10	533849
QSL-F	M5	6	10	533850
QSL-F	M7	4	10	533851
QSL-F	M7	6	10	533852
QSL-F	G1/8	4	10	193418
QSL-F	G1/8	6	10	193419
QSL-F	G1/8	8	10	193420
QSL-F	G1/4	6	10	193421
QSL-F	G1/4	8	10	193422
QSL-F	G1/4	10	10	193423
QSL-F	G1/4	12	10	533853
QSL-F	G3/8	8	10	193424
QSL-F	G3/8	10	10	193425
QSL-F	G3/8	12	10	197486
QSL-F	G1/2	10	10	193426
QSL-F	G1/2	12	10	193427

Push-in T-fitting

Type	A	D2	PE	TN
QST-F	M5	4	10	533914
QST-F	M5	6	10	533915
QST-F	M7	4	10	533916
QST-F	M7	6	10	533917
QST-F	G1/8	4	10	193428
QST-F	G1/8	6	10	193429
QST-F	G1/8	8	10	193430
QST-F	G1/4	6	10	193431
QST-F	G1/4	8	10	193432
QST-F	G1/4	10	10	193433
QST-F	G1/4	12	10	533918
QST-F	G3/8	8	10	193434
QST-F	G3/8	10	10	193435
QST-F	G3/8	12	10	197485
QST-F	G1/2	10	10	193436
QST-F	G1/2	12	10	193437

Push-in fitting

Type	A	D2	PE	TN
QS-F-I	M5	4	10	533924
QS-F-I	M5	6	10	537014
QS-F-I	M7	4	10	533925
QS-F-I	M7	6	10	533926
QS-F-I	G1/8	4	10	533927
QS-F-I	G1/8	6	10	533928
QS-F-I	G1/8	8	10	533929
QS-F-I	G1/4	8	10	533930
QS-F-I	G1/4	10	10	533931
QS-F-I	G3/8	12	10	533932

Push-in sleeve

Type	D1	D2	PE	TN
QSH-F		4	10	533890
QSH-F	4	4	10	564892
QSH-F		6	10	533891
QSH-F	6	6	10	564893
QSH-F		8	10	533892
QSH-F	8	8	10	564894
QSH-F	10	10	10	533893
QSH-F	12	12	10	533894

Push-in fitting

Type	A	D2	PE	TN
QS-F-F	G1/8	4	10	533854
QS-F-F	G1/8	6	10	533856
QS-F-F	G1/8	8	10	533858
QS-F-F	G1/4	4	10	533855
QS-F-F	G1/4	6	10	533857
QS-F-F	G1/4	8	10	533859

Push-in connector with sleev

Type	A	D2	PE	TN
QS-F-H	4	6	10	533895
QS-F-H	4	8	10	533896
QS-F-H	6	8	10	533897
QS-F-H	4	10	10	533898
QS-F-H	6	10	10	533899
QS-F-H	8	10	10	533900
QS-F-H	6	12	10	533901
QS-F-H	8	12	10	533902
QS-F-H	10	12	10	533903

Push-in sleeve
with blanking plug

Type	D1	PE	TN
QSC-F-H	4	10	533904
QSC-F-H	6	10	533905
QSC-F-H	8	10	533906
QSC-F-H	10	10	533907
QSC-F-H	12	10	533908

Push-in L-connector

Type	D1	PE	TN
QSL-F	4	10	533860
QSL-F	6	10	533861
QSL-F	8	10	533862
QSL-F	10	10	533863
QSL-F	12	10	533864

Push-in Y-connector

Type	D1	D2	PE	TN
QSY-F	6	6	10	533933
QSY-F	8	8	10	533935
QSY-F	10	10	10	533937
reducing				
QSY-F	6	4	10	533934
QSY-F	8	6	10	533936
QSY-F	10	8	10	533938

Push-in connector

Type	D1	D2	PE	TN
QS-F	4	4	10	533939
QS-F	6	4	10	564889
QS-F	6	6	10	533940
QS-F	8	6	10	564890
QS-F	8	8	10	533941
QS-F	10	10	10	533942
QS-F	12	8	10	564891
QS-F	12	12	10	533943

Push-in bulkhead fitting

Type	A	D2	PE	TN
QSSF-F	G1/8	4	10	533919
QSSF-F	G1/8	6	10	533920
QSSF-F	G1/8	8	10	533922
QSSF-F	G1/4	6	10	533921
QSSF-F	G1/4	8	10	533923

Push-in bulkhead connector

Type	D1	PE	TN
QSS-F	4	10	533909
QSS-F	6	10	533910
QSS-F	8	10	533911
QSS-F	10	10	533912
QSS-F	12	10	533913

Push-in T-connector

Type	D1	PE	TN
QST-F	4	10	533865
QST-F	6	10	533866
QST-F	8	10	533867
QST-F	10	10	533868
QST-F	12	10	533869
reducing			
QST-F	4	10	533870
QST-F	6	10	533871
QST-F	8	10	533872
QST-F	10	10	533873

QS-VO

Push-in fitting

Type	A	D2	PE	TN
QS-VO	R1/8	6	10	160500
QS-VO	R1/8	8	10	160501
QS-VO	R1/4	6	10	160502
QS-VO	R1/4	8	10	160503
QS-VO	R1/4	10	10	160504
QS-VO	R1/4	12	10	160505
QS-VO	R3/8	8	10	160506
QS-VO	R3/8	10	10	160507
QS-VO	R3/8	12	10	160508
QS-VO	R1/2	10	10	160509
QS-VO	R1/2	12	10	160510

Push-in L-fitting

Type	A	D2	PE	TN
QSL-VO	R1/8	6	10	160511
QSL-VO	R1/8	8	10	160512
QSL-VO	R1/4	6	10	160513
QSL-VO	R1/4	8	10	160514
QSL-VO	R1/4	10	10	160515
QSL-VO	R1/4	12	10	160516
QSL-VO	R3/8	8	10	160517
QSL-VO	R3/8	10	10	160518
QSL-VO	R3/8	12	10	160519
QSL-VO	R1/2	10	10	160520
QSL-VO	R1/2	12	10	160521

Push-in T-fitting

Type	A	D2	PE	TN
QST-VO	R1/8	6	10	160522
QST-VO	R1/8	8	10	160523
QST-VO	R1/4	6	10	160524
QST-VO	R1/4	8	10	160525
QST-VO	R1/4	10	10	160526
QST-VO	R1/4	12	10	160527
QST-VO	R3/8	8	10	160528
QST-VO	R3/8	10	10	160529
QST-VO	R3/8	12	10	160530
QST-VO	R1/2	10	10	160531
QST-VO	R1/2	12	10	160532

Push-in fitting

Type	A	D2	PE	TN
QS-VO	G1/8	6	10	186314
QS-VO	G1/8	8	10	186315
QS-VO	G1/4	6	10	186316
QS-VO	G1/4	8	10	186317
QS-VO	G1/4	10	10	186318
QS-VO	G1/4	12	10	186319
QS-VO	G3/8	8	10	186320
QS-VO	G3/8	10	10	186321
QS-VO	G3/8	12	10	186322
QS-VO	G1/2	10	10	186323
QS-VO	G1/2	12	10	186324

Push-in L-fitting

Type	A	D2	PE	TN
QSL-VO	G1/8	6	10	186325
QSL-VO	G1/8	8	10	186326
QSL-VO	G1/4	6	10	186327
QSL-VO	G1/4	8	10	186328
QSL-VO	G1/4	10	10	186329
QSL-VO	G1/4	12	10	186330
QSL-VO	G3/8	8	10	186331
QSL-VO	G3/8	10	10	186332
QSL-VO	G3/8	12	10	186333
QSL-VO	G1/2	10	10	186334
QSL-VO	G1/2	12	10	186335

Push-in T-fitting

Type	A	D2	PE	TN
QST-VO	G1/8	6	10	186336
QST-VO	G1/8	8	10	186337
QST-VO	G1/4	6	10	186338
QST-VO	G1/4	8	10	186339
QST-VO	G1/4	10	10	186340
QST-VO	G1/4	12	10	186341
QST-VO	G3/8	8	10	186341
QST-VO	G3/8	10	10	186342
QST-VO	G3/8	12	10	186343
QST-VO	G1/2	10	10	186344
QST-VO	G1/2	12	10	186345

Push-in connector

Type	D1	PE	TN
QS-VO	6	10	160546
QS-VO	8	10	160547
QS-VO	10	10	160548
QS-VO	12	10	160549

Push-in L-connector

Type	D1	PE	TN
QSL-VO	6	10	160540
QSL-VO	8	10	160541
QSL-VO	10	10	160542
QSL-VO	12	10	160543

Push-in T-connector

Type	D1	PE	TN
QST-VO	6	10	160533
QST-VO	8	10	160534
QST-VO	10	10	160535
QST-VO	12	10	160536

Resistant to media

CRQS, Stainless steel

Push-in bulkhead connector

Type	D1	D2	PE	TN
CRQSS	4	4	1	164210
CRQSS	6	6	1	164211
CRQSS	8	8	1	164213
CRQSS	10	10	1	164215
CRQSS	12	12	1	164217
CRQSS	16	16	1	164219

Push-in Y-connector

Type	D1	D2	PE	TN
CRQSY	4	4	1	130656
CRQSY	6	6	1	130657
CRQSY	8	8	1	130658
CRQSY	10	10	1	130659
CRQSY	12	12	1	130660
CRQSY	16	16	1	130661

Push-in L-connector

Type	D1	D2	PE	TN
CRQSL	4	4	1	130662
CRQSL	6	6	1	130663
CRQSL	8	8	1	130664
CRQSL	10	10	1	130665
CRQSL	12	12	1	130666
CRQSL	16	16	1	130667

CRQS, Stainless steel

Push-in L-fitting

Type	A	D2	PE	TN
CRQSL	M5	4	1	162870
CRQSL	M5	6	1	162871
CRQSL	R1/8	4	1	132598
CRQSL	R1/8	6	1	162872
CRQSL	R1/8	8	1	162873
CRQSL	R1/4	6	1	132599
CRQSL	R1/4	8	1	162874
CRQSL	R1/4	10	1	162875
CRQSL	R3/8	10	1	162876
CRQSL	R3/8	12	1	162877
CRQSL	R1/2	12	1	162878
CRQSL	R1/2	16	1	162879

Push-in T-fitting

Type	A	D2	PE	TN
CRQST	M5	4	1	164200
CRQST	M5	6	1	164201
CRQST	R1/8	6	1	164202
CRQST	R1/8	8	1	164203
CRQST	R1/4	8	1	164204
CRQST	R1/4	10	1	164205
CRQST	R3/8	10	1	164206
CRQST	R3/8	12	1	164207
CRQST	R1/2	12	1	164208
CRQST	R1/2	16	1	164209

Push-in fitting

Type	A	D2	PE	TN
CRQS	M5	4	1	162860
CRQS	M5	6	1	162861

Push-in T-connector

Type	D1	D2	PE	TN
CRQST	4	4	1	130668
CRQST	6	6	1	130669
CRQST	8	8	1	130670
CRQST	10	10	1	130671
CRQST	12	12	1	130672
CRQST	16	16	1	130673

Push-in fitting

Type	A	D2	PE	TN
CRQS	R1/8	4	1	132643
CRQS	R1/8	6	1	162862
CRQS	R1/8	8	1	162863
CRQS	R1/4	6	1	132644
CRQS	R1/4	8	1	162864
CRQS	R1/4	10	1	162865
CRQS	R3/8	10	1	162866
CRQS	R3/8	12	1	162867
CRQS	R1/2	12	1	162868
CRQS	R1/2	16	1	162869

Push-in fitting
with internal hex socket

Type	D1	D2	PE	TN
CRQS	M5	4	1	132328
CRQS	M5	6	1	132329
CRQS	R1/8	6	1	132330
CRQS	R1/8	8	1	132331
CRQS	R1/4	8	1	132332
CRQS	R1/4	10	1	132333
CRQS	R3/8	10	1	132334
CRQS	R3/8	12	1	132335
CRQS	R1/2	12	1	132336
CRQS	R1/2	16	1	132337

Push-in connector

Type	D1	D2	PE	TN
CRQS	4	4	1	130645
CRQS	6	6	1	130646
CRQS	8	8	1	130647
CRQS	10	10	1	130648
CRQS	12	12	1	130649
CRQS	16	16	1	130650
reducing				
CRQS	6	4	1	130651
CRQS	8	6	1	130652
CRQS	10	8	1	130653
CRQS	12	10	1	130654
CRQS	16	12	1	130655

Legend
A Connecting thread
D1 Tubing diameter, external
D2 Tubing diameter, external
PN Part number
PU Packaging unit

Comment
All L and T fittings rotatable 360°.

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	Standard fittings Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard fittings Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	Standard connectors	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	Fittings connectors for core functions	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	Metallic push-in fittings	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	Polypropylene fittings	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	Metal and special fittings/connectors	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... **PAN-...** **PEN** **PFAN** **PLN**	**Plastic tubing**	• **Standard O.D.** • **Different materials** • **Standard and bulk packs**	• **For all applications**
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	Threaded fittings and flow control valves	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

Plastic tubing, standard O.D.

Here you will find appropriate tubing for optimum tubing/fitting combinations.

Plastic tubing

Wide range of variants

PUN	PE	3	PE	4	PE	6	PE	8	PE	10	PE	12	PE	16
silver	50	152583	50	152584	50	152586	50	152587	50	152588	50	152589	50	152590
	500	525738	500	525739	500	525740	400	525741	300	525742	200	525743	100	525744
blue	50	159660	50	159662	50	159664	50	159666	50	159668	50	159670	50	159672
	500	525745	500	525746	500	525747	400	525748	300	525749	200	525750	100	525751
black	50	159661	50	159663	50	159665	50	159667	50	159669	50	159671	50	159673
	500	553936	500	553937	500	553938	400	553939	300	553940	200	553941	100	553942
yellow	50	178416	50	178417	50	178418	50	178419	50	178420	50	178421	50	178422
green	50	178423	50	178424	50	178425	50	178426	50	178427	50	178428	50	178429
red	50	178409	50	178410	50	178411	50	178412	50	178413	50	178414	50	178415

PUN-DUO	PE	4	PE	6	PE	8	PE	10
silver	50	152822	50	152823	50	152824	50	152825
blue/black	50	159674	50	159675	50	159676	50	159677

Economical I

for standard applications

PUN-E	PE	4	PE	6	PE	8	PE	10	PE	12
silver	50	535320	50	535321	50	535322	50	535323	50	535324
	500	534170	500	534172	400	534174	300	534176	200	534178
blue	50	535325	50	535326	50	535327	50	535328	50	535329
	500	534171	500	534173	400	534175	300	534177	200	534179
black	50	538465	50	538466	50	538467	50	538468	50	538469
	500	538460	500	538461	400	538462	300	538463	200	538464

Economical II

PEN	PE	4	PE	6	PE	8	PE	10	PE	12	PE	16
nature	50	543246	50	543247	50	543248	50	543249	50	543250	50	543251
black	50	543240	50	543241	50	543242	50	543243	50	543244	50	543245

Additional colours and packaging units see poster QS-B for core functions

Food industry approved

Hydrolysis-resistant



PUN-H	PE	3	PE	4	PE	6	PE	8	PE	10	PE	12	PE	16
nature	50	197375	50	197376	50	197377	50	197378	50	197379	50	197380	50	197381
	500	558263	500	558264	500	558265	400	558266	300	558267	200	558268	100	558269
blue	50	197382	50	197383	50	197384	50	197385	50	197386	50	197387	50	197388
	500	558256	500	558257	500	558258	400	558259	300	558260	200	558261	100	558262
black	50	197389	50	197390	50	197391	50	197392	50	197393	50	197394	50	197395
	500	558249	500	558250	500	558251	400	558252	300	558253	200	558254	100	558255
silver	50	558277	50	558278	50	558279	50	558280	50	558281	50	558282	50	558283
	500	558270	500	558271	500	558272	400	558273	300	558274	200	558275	100	558276
red	50	558284	50	558285	50	558286	50	558287	50	558288	50	558289	50	558290
green	50	558291	50	558292	50	558293	50	558294	50	558295	50	558296	50	558297
yellow	50	558298	50	558299	50	558300	50	558301	50	558302	50	558303	50	558304

PUN-H-DUO	PE	4	PE	6	PE	8	PE	10
blue/black	50	197396	50	197397	50	197398	50	197399

Resistant to cleaning agents



PLN	PE	4	PE	6	PE	8	PE	10	PE	12	PE	16
nature	50	193403	50	193404	50	193405	50	193406	50	193407	50	539064
black	50	195280	50	195281	50	195282	50	195283	50	195284	50	539065
blue	50	558205	50	558206	50	558207	50	558208	50	558209	50	558210
silver	50	558211	50	558212	50	558213	50	558214	50	558215	50	558216
red	50	558217	50	558218	50	558219	50	558220	50	558221	50	558222

Media and heat-resistant

PFAN	PE	4	PE	6	PE	8	PE	10	PE	12
nature	50	197061	50	197062	50	197063	50	197064	50	197065

Antistatic

PUN-CM	PE	4	PE	6	PE	8	PE	10	PE	12
black	50	188882	50	188883	50	130816	50	130817	50	130818

Pressure resistant up to 14 bar

PAN	PE	4	PE	6	PE	8	PE	10	PE	12	PE	16
nature	50	546284	50	546285	50	546286	50	546287	50	546288	50	546289
silver	50	152697	50	152699	50	152700	50	152701	50	152702	50	152703
	500	553888	500	553889	400	553890	300	553891	200	553892	100	553893
blue	50	553906	50	553907	50	553908	50	553909	50	553910	50	553911
	500	553894	500	553895	400	553896	300	553897	200	553898	100	553899
black	50	553912	50	553913	50	553914	50	553915	50	553916	50	553917
	500	553900	500	553901	400	553902	300	553903	200	553904	100	553905
green	50	553918	50	553919	50	553920	50	553921	50	553922	50	553923
red	50	553924	50	553925	50	553926	50	553927	50	553928	50	553929
yellow	50	553930	50	553931	50	553932	50	553933	50	553934	50	553935

Pressure resistant up to 16 bar

PAN-R	PE	4	PE	6	PE	8	PE	10	PE	12	PE	16
nature	50	541674	50	541675	50	541676	50	541677	50	541678	50	541679

* Tubing PAN-R pressure resistant up to 35 bar, in combination with QS-F up to 16 bar

Flame-retardant

PUN-VO	PE	6	PE	8	PE	10	PE	12
black	50	525438	50	525439	50	525440	50	525441
blue	50	525442	50	525443	50	525444	50	525445
green	50	525446	50	525447	50	525448	50	525449
red	50	525450	50	525451	50	525452	50	525453
white	50	525454	50	525455	50	525456	50	525457
yellow	50	525458	50	525459	50	525460	50	525461
brown	50	525462	50	525463	50	525464	50	525465

Resistant to welding spatter I

PUN-VO-C	PE	6	PE	8	PE	10	PE	12
black	50	561698	50	561699	50	561700	50	561701
blue	50	561702	50	561703	50	561704	50	561705
green	50	561706	50	561707	50	561708	50	561709
red	50	561710	50	561711	50	561712	50	561713
white	50	561714	50	561715	50	561716	50	561717
yellow	50	561718	50	561719	50	561720	50	561721
brown	50	561722	50	561723	50	561724	50	561725

Resistant to welding spatter II

PAN-VO	PE	4	PE	6	PE	8	PE	10	PE	12
black			50	160550	50	160551	50	160552	50	160553
blue	50	132899	20	525466	20	525467	20	525468	20	525469
green			20	525470	20	525471	20	525472	20	525473
red			20	525474	20	525475	20	525476	20	525477
white			20	525478	20	525479	20	525480	20	525481
yellow			20	525482	20	525483	20	525484	20	525485
brown			20	525486	20	525487	50	525488	20	525489

Tubing cutter

Type	D1	TN
PAN-VOS	6/8	160554
PAN-VOS	10/12	160555

Pipe cutter

Type	TN
ZRS	7658
Spare blade	218606

Tubing connector

Type	Bundle-Ø (mm)	TN
PB	30	6741
PB	45	6742
PB	100	6743

Threaded sealing tape

Type	TN
GWB-0,1	9076

Tube support elbow NPAW

Type	Size	TN
NPAW-S-T3	small	554026
NPAW-S-T4	medium	554027
NPAW-S-T6	large	554028

Legend

PN Part number
PU Packaging unit

Please detach here

For quick and reliable selection at the office and in the workshop
This page provides an overview of all included posters!

	Poster	Types	Applications
QS	**Standard fittings** Part 1 von 2	• Mini types • Standard types • Straight and L- shaped • Push-in bulkhead fittings • Push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	**Standard fittings** Part 2 von 2	• L, T, Y-shaped • Multiple distributor	• Wide range of variants • Hydrolysis resistant • Pressure resistant
QS	**Standard connectors**	• Straight, T, L, X, Y-shaped • With push-in sleeve • Push-in bulkhead fittings and push-in fittings, self-sealing	• Wide range of variants • Hydrolysis resistant • Pressure resistant • Economical
QS-B	**Fittings connectors for core functions**	• Mini types • Straight, T, L, X, Y-shaped	• Economical
NPQM	**Metallic push-in fittings**	• Push-in fittings with internal hex, thread, T, L-shaped • Plug connector straight, with sleeve, L, T, Y-shaped	• Economical • Antistatic • Flame-retardant
NPQP	**Polypropylene fittings**	• Plug connectors, L, T, Y-shaped • Plug connectors, L, T, Y-shaped • Bulkhead connector • Blanking plugs	• Cleaning agent • Media resistant
QS-F CRQS QS-V0	**Metal and special fittings/connectors**	• Metal, stainless steel, • Straight, L and T-shaped	• Pressure/heat resistant • Antistatic, Food industry approved • Cleaning agent/media resistant • Flame-retardant • Welding spatter resistant
PUN-... PAN-... PEN PFAN PLN	**Plastic tubing**	• Standard O.D. • Different materials • Standard and bulk packs	• For all applications
NPFB-... GRLA-.... GRLZ-... GRLO-... VFOC/VFOV-...	**Threaded fittings and flow control valves**	• Threaded fittings, • Nickel-plated brass • Function fittings	• For all applications

Threaded fittings, one-way flow control valves and flow control valves

Diverse ...

Robust ...

Extensive range

Reliable application

Flow on demand

Threaded fittings NPFB

Push-in L-fitting

Type	D1	D2	TN
NPFB-L	M5	M5	547715
NPFB-L	G1/8	G1/8	547716
NPFB-L	G1/4	G1/4	547717
NPFB-L	G3/8	G3/8	547718
NPFB-L	G1/2	G1/2	547719
NPFB-L	G3/4	G3/4	547720
NPFB-L	G1	G1	547721

Type	D1	D2	TN
NPFB-L	M5	M5	547722
NPFB-L	R1/8	G1/8	547723
NPFB-L	R1/4	G1/4	547724
NPFB-L	R3/8	G3/8	547725
NPFB-L	R1/2	G1/2	547726
NPFB-L	R3/4	G3/4	547727
NPFB-L	R1	G1	547728

Type	D1	D2	TN
NPFB-L	M5	M5	547729
NPFB-L	R1/8	R1/8	547730
NPFB-L	R1/4	R1/4	547731
NPFB-L	R3/8	R3/8	547732
NPFB-L	R1/2	R1/2	547733
NPFB-L	R3/4	R3/4	547734
NPFB-L	R1	R1	547735

Push-in T-fitting

Type	D1	D2	TN
NPFB-T	M5	M5	547751
NPFB-T	R1/8	G1/8	547752
NPFB-T	R1/4	G1/4	547753
NPFB-T	R3/8	G3/8	547754
NPFB-T	R1/2	G1/2	547755
NPFB-T	R3/4	G3/4	547756
NPFB-T	R1	G1	547757

Type	D1	D2	TN
NPFB-T	M5	M5	547758
NPFB-T	G1/8	R1/8	547759
NPFB-T	G1/4	R1/4	547760
NPFB-T	G3/8	R3/8	547761
NPFB-T	G1/2	R1/2	547762
NPFB-T	G3/4	R3/4	547763
NPFB-T	G1	R1	547764

Type	D1	D2	TN
NPFB-T	R1/8	R1/8	547765
NPFB-T	R1/4	R1/4	547766
NPFB-T	R3/8	R3/8	547767
NPFB-T	R1/2	R1/2	547768
NPFB-T	R3/4	R3/4	547769
NPFB-T	R1	R1	547770

Push-in X-fitting

Type	D1	D2	TN
NPFB-X	G1/8	G1/8	547779
NPFB-X	G1/4	G1/4	547780
NPFB-X	G3/8	G3/8	547781
NPFB-X	G1/2	G1/2	547782

Type	D1	D2	TN
NPFB-X	R1/8	G1/8	547783
NPFB-X	R1/4	G1/4	547784
NPFB-X	R3/8	G3/8	547785
NPFB-X	R1/2	G1/2	547786

Push-in Y-fitting

Type	D1	D2	TN
NPFB-Y	G1/8	G1/8	547736
NPFB-Y	G1/4	G1/4	547737
NPFB-Y	G3/8	G3/8	547738
NPFB-Y	G1/2	G1/2	547739

Type	D1	D2	TN
NPFB-Y	R1/8	G1/8	547740
NPFB-Y	R1/4	G1/4	547741
NPFB-Y	R3/8	G3/8	547742
NPFB-Y	R1/2	G1/2	547743

Double nipple

Type	D1	D2	TN
NPFB-D	M7	G1/8	547799
NPFB-D	G1/8	G1/8	547800
NPFB-D	G1/8	G1/4	547801
NPFB-D	G1/8	G3/8	547802
NPFB-D	G1/4	G1/4	547803
NPFB-D	G1/4	G3/8	547804
NPFB-D	G1/4	G1/2	547805
NPFB-D	G3/8	G3/8	547806
NPFB-D	G3/8	G1/2	547807
NPFB-D	G1/2	G1/2	547808
NPFB-D	R1/8	R1/8	547787
NPFB-D	R1/8	R1/4	547788
NPFB-D	R1/8	R3/8	547789
NPFB-D	R1/4	R1/4	547790
NPFB-D	R1/4	R3/8	547791
NPFB-D	R1/4	R1/2	547792
NPFB-D	R3/8	R3/8	547793
NPFB-D	R3/8	R1/2	547794
NPFB-D	R1/2	R1/2	547795
NPFB-D	R1/2	R3/4	547796
NPFB-D	R3/4	R3/4	547797
NPFB-D	R1	R1	547798

Double nipple

Type	D1	D2	TN
NPFB-R	G1/8	M5	547817
NPFB-R	G1/4	G1/8	547818
NPFB-R	G3/8	G1/8	547819
NPFB-R	G3/8	G1/4	547820
NPFB-R	G1/2	G3/8	547821

Type	D1	D2	TN
NPFB-R	G1/8	M5	547831
NPFB-R	G1/4	G1/8	547832
NPFB-R	G3/8	G1/8	547833
NPFB-R	G3/8	G1/4	547834
NPFB-R	G1/2	G1/4	547835
NPFB-R	G1/2	G3/8	547836
NPFB-R	G3/4	G1/2	547837

Reducing sleeve

Type	D1	D2	TN
NPFB-R	G3/8	G1/8	547815
NPFB-R	G3/4	G1/2	547816

Push-in T-fitting

Type	D1	D2	TN
NPFB-T	M5	M5	547744
NPFB-T	G1/8	G1/8	547745
NPFB-T	G1/4	G1/4	547746
NPFB-T	G3/8	G3/8	547747
NPFB-T	G1/2	G1/2	547748
NPFB-T	G3/4	G3/4	547749
NPFB-T	G1	G1	547750

Type	D1	D2	TN
NPFB-T	G1/8	R1/8	547771
NPFB-T	G1/4	R1/4	547772
NPFB-T	G3/8	R3/8	547773
NPFB-T	G1/2	R1/2	547774

Type	D1	D2	TN
NPFB-Y	G1/8	G1/8	547736
NPFB-Y	G1/4	G1/4	547737
NPFB-Y	G3/8	G3/8	547738
NPFB-Y	G1/2	G1/2	547739

Push-in T-fitting

Type	D1	D2	TN
NPFB-T	R1/8	G1/8	547775
NPFB-T	R1/4	G1/4	547776
NPFB-T	R3/8	G3/8	547777
NPFB-T	R1/2	G1/2	547778

Sleeve

Type	D1	D2	TN
NPFB-S	M5	M5	547809
NPFB-S	G1/8	G1/8	547810
NPFB-S	G1/4	G1/4	547811
NPFB-S	G3/8	G3/8	547812
NPFB-S	G1/2	G1/2	547813
NPFB-S	G3/4	G3/4	547814

Extension

Type	D1	D2	TN
NPFB-E1	G1/8	G1/8	547822
NPFB-E1	G1/4	G1/4	547823
NPFB-E1	G3/8	G3/8	547824
NPFB-E1	G1/2	G1/2	547825
NPFB-E2	G1/8	G1/8	547826
NPFB-E2	G1/4	G1/4	547827
NPFB-E3	G1/8	G1/8	547828
NPFB-E3	G1/4	G1/4	547829
NPFB-E4	G1/8	G1/8	547830

One-way flow control valves and flow control valves

Standard application, D[1] series

Type	A	D1	qnN	TN
GRLA	M5	3	100/100	193137
4)	M5	4	100/110	193138
	M5	6	115/110	193139
	G1/8	3	130/130	193142
	G1/8	4	160/190	193143
	G1/8	6	185/240	193144
	G1/8	8	215/250	193445
	G1/8	6	400/420	537075
	G1/8	8	475/500	537076
	G1/4	6	400/420	193146
	G1/4	8	475/500	193147
	G1/4	10	480/500	193148
	G3/8	6	495/495	193149
	G3/8	8	820/850	193150
	G3/8	10	900/975	193151
	G1/2	12	1580/1605	193152
GRLZ	M5	3	100/100	193153
5)	M5	4	110/65	193154
	M5	6	115/70	193155
	G1/8	3	130/100	193156
	G1/8	4	160/120	193157
	G1/8	6	185/160	193158
	G1/8	8	215/175	193159

Type	A	D1	qnN	TN
GRLA	M5	3	100/100	197576
4)	M5	4	100/110	197577
	M5	6	115/110	197578
	G1/8	3	130/130	197579
	G1/8	4	160/190	197580
	G1/8	6	185/240	197581
	G1/8	6	400/420	537072
	G1/8	8	475/500	537073
	G1/4	6	400/420	534338
	G1/4	8	475/500	534339
	G1/4	10	480/500	534340
	G3/8	6	495/495	534341
	G3/8	8	820/850	534342
	G3/8	10	900/975	534343
	G1/2	12	1580/1605	534344

Type	A	D1	qnN	TN
GRXA[3]	M5	3	100/60	195806
4)	M5	4	100/65	195807
	M5	6	115/70	195808
	G1/8	3	130/100	195809
	G1/8	4	160/120	195810
	G1/8	6	185/160	195811
	G1/8	8	215/175	195812
	G1/4	6	400/290	195813
	G1/4	8	475/325	195814
	G1/4	10	480/345	195815

Standard application, B[2] series

Type	A	D1	qnN	TN
GRLA	G1/8	6	400/420	162965
4)	G1/8	8	475/500	162966
	G1/4	6	495/495	162967
	G1/4	8	820/850	162968
	G3/8	6	900/975	162969
	G3/8	8	1580/1605	162970

Bulk packs with 20 pieces PU each

Type	A	D1	qnN	TN
GRLA	G1/8	6	400/420	540358
4)	G1/8	8	475/500	540359
	G1/4	8	820/850	540360

Type	A	D1	TN
VFOV	G1/8	4	549155
4)	G1/8	6	549156
	G1/4	8	549157

Type	A	D1	TN
VFOC	Push-in sleeve	4	540362
4)	Push-in sleeve	6	540363
	Push-in sleeve	4	559723
	Push-in sleeve	6	559724

Type	A	D1	qnN	TN
GRLA	M5	M5	95/95	151160
4)	G1/8	G1/8	340/420	151165
	G1/4	G1/4	610/820	151172
	G3/8	G3/8	1450/1600	151178
	G1/2	G1/2	2100/2200	151179
	G3/4	G3/4	4320/4720	151180
GRLZ	M5	M5	95/95	151183
5)	G1/8	G1/8	340/420	151188
	G1/4	G1/4	610/820	151195
GRLO	M5	M5	95	151181

Bulk packs with 20 pieces PU each

Type	A	D1qnN	TN
GRLA	M5	M595/95	151163
4)	G1/8	G1/8340/420	151169
	G1/4	G1/4610/820	151175
GRLZ	M5	M51450/1600	151186
5)	G1/8	G1/82100/2200	151192
	G1/4	G1/44320/4720	151198

Mini flow control valve, female thread

Type	A	D1	qnN	TN
GRLA	M3	M3	18/20	175038
4)	M5	M5	40/75	175047
GRLZ	M3	M3	18/20	175040
5)	M5	M5	40/65	175049
GRLO	M3	M3	18	175039
	M5	M5	40	175048

Inline flow control valve
with QS Push-in connector

Type		D1	qnN	TN
GR		3	83/83	193965
4)	4	83/88		193967
		4	110/110	193966
		6	230/240	193968
		6	300/290	193969
		8	260,/260	193970
GRO		3	540/585	193971
(both ends)		4	83/83	193972
		5	83/88	193973

Standard inline flow control valve
with female thread

Type	A	qnN	TN
GR	M3	29/29	15899
4)	M5	94/115	151213
5)	G1/8	220/217	151215
	G3/8	1010/1150	6308
	G1/2	1620/2760	3720
	G3/4	3300/4800	2103
GRA	G1/4	420/720	6509

Special application
with scale

Type	A	D1	TN
GRLSA	G1/8	6	540661
4)	G1/4	8	540662

Special application, Function combination

Type	A	D1	qnN	TN
GRXA-HG	G1/8	4	130	525667
4)	G1/8	6	140	525668
	G1/4	6	280	525669
	G1/4	8	280	525670

Special application, Mini

Type	A	D1	qnN	TN
GRLA	M3	3	41/50	175041
4)	M5	3	40/70	175053
	M5	4	40/75	175056
GRLZ	M3	3	41/44	175043
5)	M5	3	48/52	175055
	M5	4	48/65	175058
GRLO	M3	3	18	175042
	M5	3	40	175054
	M5	4	40	175057

Type	A	D1	qnN	TN
GRGA	M3	3	41/50	175044
4)	M5	3	40/70	175062
	M5	4	40/75	175065
GRGZ	M3	3	41/44	175046
5)	M5	3	48/52	175064
	M5	4	48/65	175067
GRGO	M3	3	18	175045
	M5	3	40	175063
	M5	4	40	175066

Special application
High corrosion resistance and temperature range

Type	A	D1	qnN	TN
GRLA-F	G1/8	4	180/188	195597
4)	G1/8	6	255/280	195598
	G1/8	8	275/307	195599
	G1/4	6	430/478	195600
	G1/4	8	530/578	195601

Special application
High corrosion resistance

Type	A	D1	qnN	TN
CRGRLA	M5	M5	95/95	161403
	G1/8	G1/8	340/420	161404
	G1/4	G1/4	610/820	161405
	G3/8	G3/8	1450/1600	161406
	G1/2	G1/2	2100/2200	161407

Legend
- A Connecting thread
- D1 Tubing diameter, external
- D2 Tubing diameter, external
- PN Part number
- qnN Direction of flow control/ blocked direction in l/min
- 1) Die-cast zinc
- 2) Polybutylenterephthalat
- 3) Rotatable horizontally and vertically
- 4) Exhaust air
- 5) Supply air

Comment
Packaging unit (PU)
Threaded fittings: 10 pcs.
One-way flow control valves and flow control valves: 10 pcs.

Please detach here

Technical data for flow control valves

Designation		GRLA-(RS)-B	GRLA-PK-(RS)-B	GRLA-QS-RS-B	GRLA-QS-(RS)-D	VFOC	VFOV	GRLA-F-QS-D	CRGRLA
Function	Exhaust air flow control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Supply air flow control	Yes	Yes	-	Yes	-	Yes	-	-
	Without non-return function	-	-	-	-	-	-	-	-
Actuation	With tool	Yes	Yes	Yes	Yes	Yes	-	Yes	Yes
	Without tools	Yes	Yes	Yes	Yes	-	Yes	-	-
Media		Compressed air, Vacuum	Compressed air, Vacuum	Compressed air, Vacuum	Compressed air, Vacuum	Compressed air, Vacuum	Compressed air, Vacuum	Compressed air, Vacuum	Compressed air, Vacuum
Operating pressure [bar]		0.3 ... 10	0.3 ... 11	0.2 ... 10	0.2 ... 10	0.2 ... 10	0.2 ... 10	0.2 ... 10	0.3 ... 10
Operating temperature [°C]		-10 ... +60	-10 ... +60	-10 ... +60	-10 ... +60	-10 ... +60	-10 ... +60	0 ... +150	-20 ... 80
Mounting position		Any	Any	Any	Any	Any	Any	Any	Any
Hydrolysis resistant		++	++	+++	++	++	+++	+++	+++
Antistatic		++	++	-	++	++	-	+++	+++
Flame-retardant		++	++	-	-	-	-	+++	+++
Food industry		-	-	-	-	-	-	++	++

+++ very suitable ++ quite suitable + suitable – not suitable