



Data sheet: Proximity Sensor SME-8-S-LED-24 – 150857

FESTO

Function



Feature	values
Design	for T-slot
Conforms to standard	EN 60947-5-2
Authorisation	C-Tick
CE mark (see declaration of conformity)	to EU directive for EMC
Materials note	Free of copper and PTFE
Measuring principle	Reed magnetic
Ambient temperature	-40 - 70 °C
Switch output	with contact, bipolar
Switching element function	Normally open contact
Reproducibility of switching value	+/- 0,1 mm
Switch-on time	0.5 ms
Switch-off time	0.03 ms
Max. output current	500 mA
Max. contact rating AC	10 VA
Max. contact rating DC	10 W
Short circuit strength	No
Overload withstand capability	Not available
Operating voltage range AC	12 - 30 V
Operating voltage range DC	12 - 30 V
Polarity protected	No
Electrical connection	Cable with plug M8x1 3-pin
Connector exit direction	axial
Material information for crimp connectors	Brass Nickel plated
Cable length	0.3 m
Materials information, cable sheaths	PUR
Mounting type	Insertable into slot lengthwise Clamped in T-slot
Tightening torque	0.2 Nm
Product weight	8 g
Materials information, housing	Epoxy resin PC PET High alloy steel, non-corrosive
Operating status display	Yellow LED
Ambient temperature	-5 - 70 °C
Protection class	IP67
Insulation voltage	50 V
Surge strength	0.8 kV
Degree of contamination	3