

ROSHNI: 0832-CPD-0131
ROLP : 0832-CPD-0128
ROLP/SV : 0832-CPD-1651

	EN54-3 	
	RO & ROLP ROLP/SV	
	9 ~ 15VDC	18 ~ 28VDC
	32mA max	
	0.28mm ² ~ 2.5mm ²	
	-25 ℃ ~ +70 ℃	
	ABS V0	
	S = Type A = (IP54*) D/U = Type B = (IP65*)	
	6	

							Main Application	Roshni LP (ROLP)					
								mA	*12Vdc on axis @1M	EN54-3 15Vdc see notes	mA	*24Vdc on axis @1M	EN54-3 28Vdc see notes
1	14	11111	Pattern	Frequency Hz	Rate	Depiction		mA	dB(A)	dB(A)	mA	dB(A)	dB(A)
2	14	11110	Alternating	800 & 970	2Hz (250ms-250ms)		BS Fire	6	95	*	13	101	*
3	14	11101	Sweep	800 to 970	7Hz (7/s)		BS Fire	8	94	*	12	100	*
4	14	11100	Sweep	800 to 970	1Hz (1/s)		BS Fire	6	95	92	12	102	95
5	4	11011	Continuous	2850	Steady		General Purpose	16	99	*	32	105	*
6	4	11010	Sweep	2400 to 2850	7Hz		General Purpose	16	103	*	32	109	*
7	14	11001	Sweep	2400 to 2850	1Hz		General Purpose	16	105	*	32	112	*
8	14	11000	Slow whoop	500 to 1200	3s sweep, 0.5 s silence, then repeat		Dutch fire (NEN 2575)	6	97	93	12	103	97
9	4	10100	Sweep (DIN)	1200 to 500	1Hz		German fire (DIN 33 404)	7	96	93	15	103	94
10	4	10111	Alternating	2400 & 2850	2Hz (250ms-250ms)		General Purpose	15	99	*	31	105	*
11	14	10110	Intermittent	970	0.5Hz (1s On/1s Off)		PFEER alert	5	95	*	8	101	*
12	14	10101	Alternating	800 & 970	1Hz (500ms-500ms)		BS Fire	6	95	*	12	101	*
13	4	10100	Intermittent	2850	0.5Hz (1s On/1s Off)		General Purpose	9	99	*	17	105	*
14	14	10011	Intermittent	970	0.8Hz (250ms On/1s Off)		General Purpose	3	94	*	5	101	*
15	14	10010	Continuous	970	Steady		PFEER toxic gas	7	95	93	14	101	95
16	16	10000	Alternating	554 & 440	100ms-400ms		French fire (NFS 32-001)	8	96	*	17	102	*
17	17	01111	Intermittent	660	3.3Hz (150ms On/150msOff)		Swedish (Air Raid)	4	94	*	6	100	*
18	18	01110	Intermittent	660	0.28Hz(1.8s On/1.8s Off)		Swedish (Local warning)	4	95	*	7	101	*
19	18	01101	Intermittent	660	0.05Hz (13s Off / 6.5Hz On)		Swedish (Pre-mess)	3	95	*	6	101	*
20	19	01100	Continuous	660	Steady		Swedish (All clear)	5	95	*	10	101	*
21	20	01100	Alternating	554 & 440	0.5Hz (1s On/1s Off)		Swedish (Turn out)	7	96	*	16	102	*
22	21	01011	Intermittent	660	1Hz (500ms-500ms)		Swedish general purpose	4	94	*	6	101	*
23	14	01010	Intermittent	2850	4Hz (150ms On/100ms Off)		Pelican crossing	12	98	*	27	104	*
24	14	01001	Sweep	800 to 970	50Hz		BS Fire	6	93	*	12	100	*
25	4	01000	Sweep	2400 to 2850	50Hz		General Purpose	15	102	*	32	108	*
26	25	00111	Intermittent	970	3 x 500ms pulses, 1.5s silence, then repeat		ISO 8201	4	95	*	7	101	*
27	26	00110	Intermittent (1*)	800 to 970	3 x 500ms pulsed sweep, 1.5s silence, then repeat		ISO 8201	4	95	*	6	102	*
28	27	00101	Intermittent (1*)	970 & 800	3 x 500ms pulsed sweep, 1.5s silence, then repeat		ISO 8201	3	94	*	6	101	*
29	10	00100	Alternating	800 & 970	2Hz (250ms-250ms)		BS Fire	6	95	*	12	101	*
30	988Hz	00011	Alternating	990 & 650	2Hz (250ms-250ms) (Symphoni tones)		BS Fire	10	99	93	20	105	96
31	510Hz	00010	Alternating	510 & 610	2Hz (250ms-250ms) (Squashni Micro tones)		BS Fire	8	94	91	16	100	92
32	14	00001	Sweep	300 to 1200	1Hz		General Purpose	10	98	*	14	103	*
33	510Hz	00000	Alternating	510 & 610	1Hz (500mS-500mS)		BS Fire	8	95	*	16	100	*

- 25-10365-D