

Surge protection
VPU II 3 R 280V/40KA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

**Type II/III surge protection U_c : 280 V**
Suitable for 230/400 V mains systems

- Pluggable arrester
- Coded voltage level
- High energy absorption with short time to sparkover
- Insert can be rotated through 180°
- No follow-on current
- Installation in distribution board
- Thermal protection function
- Co-ordination with VPU Type I

General ordering data

Order No.	1352720000
Type	VPU II 3 R 280V/40KA
GTIN (EAN)	4050118157659
Qty.	1 pc(s).

Surge protection VPU II 3 R 280V/40KA

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	53.4 mm	Height	106 mm
Depth	69 mm	Mounting dimension - height	75 mm
Net weight	420 g		

Temperatures

Operating temperature	-40 °C...+70 °C	Storage temperature	-40 °C...+80 °C
-----------------------	-----------------	---------------------	-----------------

Discharge surge current of top part

Limiting discharge current (8/20 µs) $I_{\max}$	40 kA	Rated discharge current (8/20 µs) I_N	20 kA
---	-------	---	-------

General data

Colour	Black, Arrester red	Design	Installation housing; 3TE
Lightning arrester	No	Mounting rail	TS 35, TS 35 x 15, TS 35 x 7.5
Optical function display	green = OK; red = arrester is defective - replace	Protection degree	IP 20
Segment	Power distribution	UL 94 flammability rating	V-0

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

Technical data

Rated voltage (AC)	230 V / 400 V	Max. continuous voltage, U_c (AC)	280 V
Temporary surge voltage (over-voltage) - TOV	440 V	Limiting discharge current (8/20 µs) $I_{\max}$	40 kA
Combined pulse U_{OC}	10 kV	Rated discharge current (8/20 µs) I_N	20 kA
Fuse, max.	125 A gL	Short-circuit current rating I_{SCCR}	25 kA
Discharge current, nominal, per path, (8/20 µs)	20 kA	Total discharge current I_{total}	120 kA
Discharge current, max. (8/20 µs)	40 kA	Short-circuit strength with max. back-up fuse	25 kA _{eff}
Protection level U_p (typ.)	≤ 1.55 kV	Leakage current at U_n	30 µA
Signalling contact	250 V 1A 1CO	Standards	IEC61643-11, EN61643-11
Colour	Black, Arrester red	Humidity	0...95 % (no condensation)
Requirements class, acc. to EN 61643-11	T2, T3	Requirements category acc. to IEC 61643-11	Type II, Type III
Response time	≤ 25 ns		

Connection data

Clamping range, rated connection	16 mm ²	Clamping range, rated connection, min.	1.5 mm ²
Clamping range, rated connection, max.	50 mm ²	Wire connection cross section, stranded, rated connection, min.	1.5 mm ²
Wire connection cross section, stranded, rated connection, max.	50 mm ²	Tightening torque, min.	2 Nm
Tightening torque, max.	3 Nm	Stripping length, rated connection	15 mm
Wire connection cross section, finely stranded, max.	25 mm ²		

Surge protection
VPU II 3 R 280V/40KA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Connection data, remote alert**

Connection type [remote alert]	PUSH IN	Stripping length [remote alert]	8 mm
Cross-section for connected wire, solid core, min. [remote alert]	0.14 mm ²	Cross-section for connected wire, solid core, max. [remote alert]	1.5 mm ²

Classifications

ETIM 3.0	EC000941	UNSPSC	30-21-19-21
eClass 5.1	27-13-08-01	eClass 6.0	27-13-08-02
eClass 7.0	27-14-02-01		

Approvals

Approvals

**Downloads**


Package insert	Instruction sheet
Declaration of Conformity	K505_09_12.pdf
	3-D model

Surge protection
VPU II 3 R 280V/40KA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol



Circuit diagram