

Power supplies

AC1218


Power supply for AS-i networks
AS-i power supply 115/230 V AC

Integrated data decoupling
Jumper to deactivate the AS-i
communication

240 watts



Application	AS-i system voltage for masters, sensors, actuators and modules
Nominal voltage [V]	115 / 230 AC *)
Input voltage range [V]	85...132 / 184...264 AC
Output current [A]	8
Short-circuit protection	electronic deactivation after 2...5 s / reset via pushbutton
Overload protection	•
Nominal frequency [Hz]	47...63
Efficiency [%]	92
Output voltage [V]	29,5...31,6 DC to PELV
Power-on delay time [ms]	typ. 100
Derating	6W / K (+60...+70°C)
Mains buffering time [ms]	> 10
Fuse	T8A/250V, time-lag, integrated
Back-up fuse	10A (or higher)
Residual ripple [mV]	< 50
Operating temperature [°C]	-10...+70
Protection	IP 20
AS-i certificate	42101
EMC	EN 50081-1; EN 61000-6-2 / CE: IEC 60950; 1999
Housing material	aluminium steel sheet galvanised
Function display	LED 1 red (flashes in case of short circuit, overload (excess temperature))
Function LED	LED 2 red (IR-addressing)
	LED 3 green (goes off in case of overload U < 28V)
Connection	terminals up to 4 mm²
Wiring	



Remarks

*) selectable