

Attachment J-10

Senate CSS Data Interchange Format (SCDIF)

General Requirements

This document defines a common format for the information contained in Constituent Services Systems (CSS). This format will be used to transfer data from one CSS to another, and may also be used to transfer data from an outgoing Senator's CSS system to their designated archival repository (SCDIF archiving conversions).

Records will be variable length, and should utilize 8-bit character encoding that preserves accented characters with carriage return line feed (CRLF) at the end of each record. TAB characters will separate fields. Records will be filled out with extra TAB characters at the end so as to have the same number of TAB characters (fields) in each record. It is the responsibility of the vendor who creates the data to make sure that there are no TAB characters or CRLF in the data fields themselves. Any CRLF within data fields shall be replaced with a PIPE character (|). Fields may be any length but no record can be longer than 32K.

Information in the database will be classified into categories:

- | | |
|---|-----------------------------------|
| 1 | Person data |
| 2 | Communication data |
| 3 | Workflow data |
| 5 | Household data |
| 6 | Form Letter/Document Library data |
| 7 | Schedule data |
| 8 | Code tables |

Each record on the CSS data file will have a 2-byte Record Type field with the first byte being a number identifying one of the categories above and the second byte being a letter identifying the type of data within that category.

Complete conversion documentation will be provided to the SAA for approval three weeks (15 business days) prior to the start of the data conversion.

For exit conversions performed to facilitate the transfer of data from one CSS to another, the Contractor will provide the approved conversion documentation, along with an advance copy of the 8A/Code Table Data, to the receiving vendor no later than two weeks (10 business days) prior to the start of the conversion. (An advance copy of the 8A data is not required for SCDIF archiving conversions.) Additional details regarding this process are provided in the "Additional Requirements" section at the end of this document.

SCDIF archiving conversions will be customizable to the extent that the Member offices will have the option to include or exclude all or some of the category 3-workflow data. Offices will also have the option to include or exclude all of the category 7-schedule data. Additional details regarding this process are provided in the "Additional Requirements" section at the end of this document.

Attachment J-10

Person Data

1A Record – Name Data

Field No	Field Name	Comments
1	Record Type	"1A" - indicates that the record contains person name information
2	Person ID	A unique ID which identifies the person.
3	Person Type	A code that identifies the type of person in this record. Use the appropriate entry from the table below.
4	Prefix	Prefix of person such as "Mr.", "Mrs." or "The Honorable".
5	First Name	First name of person.
6	Middle Name	Middle name or initial of person.
7	Last Name	Last name of person.
8	Suffix	Suffix of person such as "Jr."
9	Appellation	Appellation of person such as "MD".
10	Organization Name	Name of the organization. This field is used if the record is not for an individual.
11	Salutation	Preferred salutation used for the person, such as "Bob" or "Senator Jones".
12	Date of Birth	The person's date of birth in the format YYYYMMDD.
13	No Mail Flag	"Y" if the person has requested that no mail be sent to them at any of their addresses.
14	Deceased Flag	"Y" if the person is deceased.
15	Spouse's Name	Name of the person's spouse.
16	Email Flag	"Y" if the person has requested that their preferred method of communication is via email.

Person Type Values

Value	Meaning
AG	Agency
CS	Constituent
MC	Member of Congress
OR	Organization
PRESS	Press
USER	Internal Staff

1B Record – Address Data

There may be multiple 1B records for a person, one for each address.

Field No	Field Name	Comments
1	Record Type	"1B" - indicates that the record contains person address information.
2	Person ID	ID which identifies the person. This ID field must be the same as the ID field in the associated 1A record for the person.
3	Address ID	Numeric ID or sequence number which identifies the address.
4	Address Type	The type of address. Enter the appropriate code from the table below.
5	Primary Flag	"Y" if this is the primary address for this address type, or the only address of this type. For example, if the address type is "BU" and this flag is "Y", then

Attachment J-10

Field No	Field Name	Comments
		this is the primary business address.
6	Default Address Flag	"Y" if this address is the default mailing address for the person.
7	Title	Title associated with an organization or business address. For example, "CEO" or "President".
8	Organization Name	Name of an organization or business such as "American Medical Association". This name is used if the person record is for an individual and this is his/her business address.
9	Address line 1	First line of address.
10	Address line 2	Second line of address.
11	Address line 3	Third line of address.
12	Address line 4	Fourth line of address.
13	City	City
14	State Code	2 letter state code such as "VA", "DC" or "MD".
15	Zip Code	9 digit zip code. Format for 9 digit zip code is XXXXX-XXXX. If only the 5-digit code is known, then the format is XXXXX. If international address, enter the appropriate zip code of the country.
16	Carrier Route	Carrier route.
17	County	County.
18	Country	If international address, enter the country.
19	District	Congressional district.
20	Precinct	Precinct.
21	No Mail Flag	"Y" if no mail should be sent to this address.
22	Deliverability	"U" if this address has been marked as undeliverable, "D" if marked as deliverable, "P" if marked as possibly deliverable, and NULL if address deliverability has not been verified. (Note: please see attachment XXX.)

Address Type Values

Additional "address types" may be added as needed, but the vendor must document all non-standard types that have been added.

Value	Meaning
BU	Business
HO	Home
IN	International/Foreign

1C Record – Person Codes

There may be multiple 1C records for a person.

Field No	Field Name	Comments
1	Record Type	"1C" - indicates that the record contains person code information.
2	Person ID	ID which identifies the person. This ID field should be the same as the ID field in the associated 1A record for the person.
3	Person Code Type	Type of code entered in the following field. Enter the appropriate code type from the table below. The same code type may be used more than once.
4	Code	Code to describe the person/agency. There must be an 8A record

Attachment J-10

Field No	Field Name	Comments
		containing this person or workflow code.

Person Code Type Values

Value	Meaning
PERS	Code to describe the person (e.g. DOCTOR, MAYOR, VIP, POI).
WORK	For agency records, code to describe the agency/workflow (e.g. SSA).

1D Record – Person Text (Comments or Notes)

There may be multiple 1D records for a person.

Field No	Field Name	Comments
1	Record Type	"1D" - indicates that the record contains comments or notes about the person.
2	Person ID	ID which identifies the person. This ID field must be the same as the ID field in the associated 1A record for the person.
3	1D Sequence Number	Sequence number that identifies the order of 1D records for a person. A sequence number must be provided if fields 5/Date and 6/Time are NULL.
4	Text	Freeform text containing comments or notes about the person.
5	Date	Date the text was added to the record. Must be in YYYYMMDD format.
6	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).
7	User ID	User ID of the staffer who entered the text. There must be an 8A record containing this staff user ID.

1E Record – Person Phone/Email

There may be multiple 1E records for a person.

Field No	Field Name	Comments
1	Record Type	"1E" - indicates that the record contains telephone numbers or email addresses for the person.
2	Person ID	ID which identifies the person. This ID field must be the same as the ID field in the associated 1A record for the person.
3	Person Phone or email Type	Type of code entered in the following field. Enter the appropriate type code from the table below. The same type may be used more than once. For example, the person may have multiple business phone numbers.
4	Phone Number, Email , or URL	A telephone number, email address, or associated website URL
5	Primary Flag	"Y" if this is the primary phone number or email address for this phone/email type, or the only phone number or email address of this type.. For example, if person phone or email type is "HOME" and the flag is "Y", then this is the primary home phone number.
6	Invalid Flag	"Y" if this person's phone/email address has been marked as

Attachment J-10

Field No	Field Name	Comments
		invalid/undeliverable.

Person Phone or Email Type Values

Additional types may be added as needed, but the vendor must document all non-standard types that have been used.

Value	Meaning
CELL	Cell phone
EMAIL	Email address
FAX	Fax number
HOME	Home phone number
PAGER	Pager number
PHONE	Phone number, cannot determine the type.
URL	Address of the person's web page
WORK	Work or business phone number

1F Record – Person Attachments

There may be multiple 1F records for a person.

Field No	Field Name	Comments
1	Record Type	"1F" - indicates that the record contains information about documents/files attached to the person record.
2	Person ID	ID which identifies the person. This ID field must be the same as the ID field in the associated 1A record for the person.
3	Document Name	Name of the document/file attached to the person record (for documents/files not stored in the form letter/document library). The name must include file path information to identify the location of the document/file.
4	Document ID	ID that identifies the document/file attached to the person record (for documents/files stored in the form letter/document library). This ID must be the same as the Document ID field in the associated 6A record.
5	User ID	User ID of the staffer who attached the document/file. There must be an 8A record containing this staff user ID.
6	Attached Date	Date when the document/file was attached to the person record. Must be in YYYYMMDD format
7	Text	Freeform text containing comments or notes about the attached document/file.

Communication Data

Communication records will be used to identify any way that a person contacts the office, and vice versa (including communications associated with workflows) For example, they might represent a phone call from a constituent, or an outgoing mailing that the office sends out.

Attachment J-10

Note: Workflow “action history” data is to be provided via 3D – Workflow Text (Comments or Notes)/Action Histories.

2A Record – Communication Data

There may be multiple 2A record for a person.

Field No	Field Name	Comments
1	Record Type	“2A” - Indicates that the record contains communication information.
2	Person ID	ID which identifies the person associated with the communication record. This ID must be the same as the Person ID in the associated 1A record for the person.
3	Communication ID	A unique ID that identifies the communication.
4	Workflow ID	ID that identifies the workflow associated with this communication. This ID must be the same as the Workflow ID field in the associated 3A record. NULL if the communication is not associated with a workflow.
5	Workflow Person ID	ID that identifies the person associated with the workflow identified in field 4/Workflow ID. This ID must be the same as the Person ID field in the associated 3A record. NULL if the communication is not associated with a workflow.
6	Communication Type	Identifies the type of communication or contact. For example, “LETTER”, “EMAIL”, “PHONE”, “NEWSLETTER”, “POST CARD”, “VISIT”, “DMAIL” (digital mail), etc.
7	User ID	User ID of the individual who handled the communication. There must be an 8A record containing this staff user ID.
8	Approved By	User ID of the staffer who approved this communication. There must be an 8A record containing this staff user ID. NULL if approval is not required, or if approval has not yet been granted.
9	Status*	Status of the communication (e.g. Pending, Completed, Request Approval). *All possible status values must be provided in the table below.
10	Date In	Date communication was received. Must be in YYYYMMDD format.
11	Date Out	Date communication was completed. Must be in YYYYMMDD format.
12	Reminder date	Reminder date for communication. Must be in YYYYMMDD format.
13	Update Date	Date the communication was last updated. Must be in YYYYMMDD format.
14	Response Type	Method of reply. For example, “LETTER”, “EMAIL”. etc.
15	Address ID	ID which identifies the address to which the communication was sent. This ID field must be the same as the address ID field in the associated 1B record.
16	Email Address	Email address to which the communication was sent.
17	Household Flag	“Y” if the communication was sent to a household. In this case there must also be a 5B record to define the members of the household.
18	Household ID	The household ID in the 5A record which identifies the household. There must be a 5A record containing the household ID.
19	Group Name	Name of the group or batch this communication is a part of.
20	Salutation	The salutation used in the communication.

*Communication Status Values

All possible Communication Status values must be documented in the table below as part of the outgoing vendor's conversion documentation.

Attachment J-10

Status Value	Closed Flag
(The status provided must be the value that is displayed to the user when viewing the record.)	("Y" if this status indicates that the office has finished/completed their work on this communication, NULL if the status indicates that work on this communication is not completed.)

2B Record – Communication Codes

There may be multiple 2B records for the communication, one for each communication code.

Field No	Field Name	Comments
1	Record Type	"2B" - indicates that the record contains a code associated with the communication.
2	Person ID	ID which identifies the person associated with the communication record. This ID must be the same as the Person ID in the associated 1A record for the person.
3	Communication ID	ID that identifies the communication. This ID must be the same as the Communication ID field in the associated 2A record.
4	Communication Code	A subject or interest code to describe the communication. It can describe the subject of the communication (such as "TAXES") or the constituent's position on a subject (such as "GUNCTRL"). . There must be an 8A record containing this communication subject code.
5	Position	A code that reflects the constituent's position on the subject. For example, "PRO", "CON", "NEUTRAL", or "NONE".

2C Record – Communication Documents

There may be multiple 2C records for the communication, one for each document/file associated with the communication.

Field No	Field Name	Comments
1	Record Type	"2C" - indicates that the record contains document/file name data for the communication.
2	Person ID	ID which identifies the person associated with the communication record. This ID must be the same as the Person ID in the associated 1A record for the person.
3	Communication ID	ID that identifies the communication. This ID must be the same as the Communication ID field in the associated 2A record.

Attachment J-10

Field No	Field Name	Comments
4	Document Type	Identifies whether the following document/file is the incoming document/file, outgoing document/file, or an attachment. See document type values in the table below.
5	Communication Document Name	Name of the communication document/file. The name must include path information to identify the location of the file. For example, "/docs/newsletters/oct99nl.doc". NULL if the document/file is in the Form Letter/Document Library, in which case the Document ID must be provided in field 6/Communication Document ID.
6	Communication Document ID	ID that identifies the document/file (for example, the ID of the form letter library item sent to the person). This ID must be the same as the Document ID in the associated 6A record. NULL if the document is not in the Form Letter/Document Library, in which case the document/file name/path must be provided in field 5/Communication Document Name.
7	File Location	Location of the document hardcopy (i.e., file cabinet location of the original letter).

Document Type Values

Value	Meaning
INCOMING	Incoming document (i.e. incoming communication from the person)
OUTGOING	Outgoing document (i.e. outgoing communication to the person)
AT_INn	Numbered attachment to the incoming communication, where "n" is the sequence number used to identify the order of the attachments. For example, "AT_IN1" identifies the first incoming attachment, "AT_IN2" identifies the second incoming attachment, etc.
AT_OUTn	Numbered attachment to the outgoing communication, where "n" is the sequence number used to identify the order of the attachments. For example, "AT_OUT1" identifies the first outgoing attachment, "AT_OUT2" identifies the second outgoing attachment, etc.

2D Record – Communication Text (Comments or Notes)

There may be multiple 2D records for the communication.

Field No	Field Name	Comments
1	Record Type	"2D" - indicates comments or notes about the communication.
2	Person ID	ID which identifies the person associated with the communication record. This ID must be the same as the Person ID in the associated 1A record for the person.
3	Communication ID	ID that identifies the communication. This ID must be the same as the Communication ID field in the associated 2A record.
4	2D Sequence Number	Sequence number that identifies the order of 2D records for a communication. A sequence number must be provided if fields 6/Date and 7/Time are NULL.
5	Text	Freeform text containing comments or notes about the communication.
6	Date	Date the text was added to the record. Must be in YYYYMMDD format.
7	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).

Attachment J-10

Field No	Field Name	Comments
8	User ID	User ID of the staffer who entered the text. There must be an 8A record containing this staff user ID.

2E Record – Communication Fill-in Data

When a letter is sent to a person, particularly a form letter, user-defined fill-in fields (variable text inserts) can be included in the letter. The fill-in data may be stored in the letter itself or in a 2E record associated with the outgoing communication.

There may be multiple 2E records for the communication, one for each fill-in field.

Field No	Field Name	Comments
1	Record Type	"2E" - indicates that the record contains a user-supplied fill-in data associated with the communication.
2	Person ID	ID which identifies the person associated with the communication record. This ID must be the same as the Person ID in the associated 1A record for the person.
3	Communication ID	ID that identifies the communication. This ID must be the same as the Communication ID field in the associated 2A record.
4	Fill-in Field Name	The name of the fill-in field as it appears in the document.
5	Fill-in Data	Freeform text that was inserted into the document in place of the fill-in field.

Workflow Data

Data related to an office's business processes, and not defined elsewhere in this format, will be provided as "workflow". Examples of workflow processes are casework (requests for assistance from a constituent regarding a problem/request/inquiry with a federal agency), flag requests, and tour requests.

3A Record – Workflow Data

There may be more than one 3A record for a person if there are multiple workflows for a person.

Field No	Field Name	Comments
1	Record Type	"3A"- Basic workflow record.
2	Person ID	ID which identifies the person about whom the workflow was opened. This ID must be the same as the Person ID in the associated 1A record for the person. NULL if no person is associated with the workflow.
3	Workflow ID	A unique ID that identifies the workflow.
4	Workflow Type	A code that identifies the type of workflow process in this record (e.g. casework, flag request, etc.). Use the appropriate workflow type code from the table below.
5	User ID	User ID of the individual who handled the workflow. There must be an 8A

Attachment J-10

Field No	Field Name	Comments
		record containing this staff user ID.
6	Start Date	Date workflow was initiated. Must be in YYYYMMDD format.
7	End Date	Date workflow was completed. Must be in YYYYMMDD format.
8	Reminder date	Reminder date for workflow. Must be in YYYYMMDD format.
9	Update Date	Date the workflow was last updated. Must be in YYYYMMDD format.
10	Workflow Description	Freeform description of the workflow. For example, "Veteran benefits inquiry" or "Immigration problem".
11	Status*	The status of the workflow. For example, "Open", "Pending", "Closed Favorably", "Closed Unfavorably". *All possible status values must be provided in the table below.

Workflow Type Values

Additional "workflow types" should be added as needed. All additions must be documented by the vendor.

Value	Meaning
CASE	Casework
PROJECT	Project
GRANT	Grant
FLAG	Flag Request
TOUR	Tour Request
INVITE	Invitation/Meeting Request
APPROP	Appropriation Request
ACADEMY	Academy Nominations
INTERN	Intern Application

*Workflow Status Values

All possible Workflow Status values must be documented in the table below as part of the outgoing vendor's conversion documentation.

Status Value	Closed Flag
(The status provided must be the value that is displayed to the user when viewing the record.)	("Y" if this status indicates that the office has finished/completed their work on this workflow, NULL if the status indicates that work on this workflow is not completed.)

Attachment J-10

3B Record – Workflow Codes

There may be more than one 3B record for a workflow.

Field No	Field Name	Comments
1	Record Type	"3B" - indicates that the record contains codes associated with the workflow.
2	Person ID	ID which identifies the person about whom the workflow was opened. This ID must be the same as the Person ID in the associated 1A record for the person. NULL if no person is associated with the workflow.
3	Workflow ID	ID that identifies the workflow. This ID must be the same as the Workflow ID field in the associated 3A record.
4	Workflow Code	Code to describe the workflow such as "VET", "SOCSEC", "RAILROAD RETIREMENT" or "IMMIGRATION". There must be an 8A record containing this workflow code.

3D Record – Workflow Text (Comments or Notes)/Action Histories

There may be more than one 3D record for a workflow.

Field No	Field Name	Comments
1	Record Type	"3D" - indicates that the record contains comments or notes associated with the workflow, or an "action history" associated with the workflow.
2	Person ID	ID which identifies the person about whom the workflow was opened. This ID must be the same as the Person ID in the associated 1A record for the person. NULL if no person is associated with the workflow.
3	Workflow ID	ID that identifies the workflow. This ID must be the same as the Workflow ID field in the associated 3A record.
4	3D Sequence Number	Sequence number that identifies the order of 3D records for a workflow. A sequence number must be provided if fields 6/Date and 7/Time are NULL.
5	Text	Freeform text containing comments or notes, or action history details about the workflow.
6	Date	Date the text was added to the record. Must be in YYYYMMDD format.
7	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).
8	User ID	User ID of the staffer who entered the text/action history. There must be an 8A record containing this staff user ID.

3E Record – Workflow Parties

There may be more than one 3E record for a workflow.

Field No	Field Name	Comments
1	Record Type	"3E" - indicates that the record contains information about the persons (e.g. agencies, constituents) associated with the workflow.

Attachment J-10

Field No	Field Name	Comments
2	Person ID	ID which identifies the person about whom the workflow was opened. This ID must be the same as the Person ID in the associated 1A record for the person. NULL if no person is associated with the workflow.
3	Workflow ID	ID that identifies the workflow. This ID must be the same as the Workflow ID field in the associated 3A record.
4	Party ID	Person ID of a party (to include agencies) who has an interest in the workflow. There must be a 1A record containing this Person ID.

3F Record – Workflow Attachments

There may be multiple 3F records for a workflow.

Field No	Field Name	Comments
1	Record Type	“3F” - indicates that the record contains information about documents/files attached to the workflow record.
2	Person ID	ID which identifies the person about whom the workflow was opened. This ID must be the same as the Person ID in the associated 1A record for the person. NULL if no person is associated with the workflow.
3	Workflow ID	ID which identifies the workflow. This ID field must be the same as the ID field in the associated 3A record for the workflow.
4	Document Name	Name of the document/file attached to the workflow record (for documents/files not stored in the form letter/document library). The name must include file path information to identify the location of the document/file.
5	Document ID	ID that identifies the document/file attached to the workflow record (for documents/files stored in the form letter/document library). This ID must be the same as the Document ID field in the associated 6A record.
6	User ID	User ID of the staffer who attached the document/file. There must be an 8A record containing this staff user ID.
7	Attached Date	Date when the document/file was attached to the workflow record. Must be in YYYYMMDD format
8	Text	Freeform text containing comments or notes about the attached document/file.

3L Record – Additional Workflow Data

The 3L record will be used as a continuation of the 3A record type to transmit workflow type specific field data (fields that are part of the CSS's out-of-the-box configuration) and/or custom/user-defined field data that is associated with particular workflow types. Further details are provided in the “Additional Requirements” section of this format.

There may be more than one 3L record for a workflow.

Field No	Field Name	Comments
1	Record Type	“3L” - indicates that the record contains additional data about the workflow.
2	Person ID	ID which identifies the person about whom the workflow was opened. This ID must be the same as the Person ID in the associated 1A record for the person. NULL if no person is associated with the workflow.

Attachment J-10

Field No	Field Name	Comments
3	Workflow ID	ID that identifies the workflow. This ID must be the same as the Workflow ID field in the associated 3A record.
4	Workflow Type	A code that identifies the type of workflow process in this record (e.g. casework, flag request, etc.). This Workflow Type must be the same as the Workflow Type provided in the associated 3A record for this workflow.
5	Field Name	Name of the field.
6	Field Value	Value of the field.

Household Data

5A Record – Household Name Data

Field No	Field Name	Comments
1	Record Type	“5A” - indicates that the record contains household name information.
2	Household ID	A unique ID which identifies the household.
3	Household Name	Name of the household (e.g., “The Smith Family”)
4	Household Salutation	The salutation used for the household (e.g., “Smith Family”).

5B Record – Household Member Data

There will be multiple 5B records for a household, one for each person/member of the household.

Field No	Field Name	Comments
1	Record Type	“5B” - indicates that the record contains household member information.
2	Household ID	ID which identifies the household. This ID must be the same as the ID field in the associated 5A record for the household.
3	Person ID	A Person ID that identifies a person who is a member of the household. There must be a 1A record containing this Person ID.
4	Primary Contact Flag	“Y” if this person is the head of household or primary contact.

5C Record – Household Attachments

There may be multiple 5C records for a Household.

Field No	Field Name	Comments
1	Record Type	“5C” - indicates that the record contains information about documents/files attached to a household record.
2	Household ID	ID which identifies the household. This ID must be the same as the ID field in the associated 5A record for the household.

Attachment J-10

Field No	Field Name	Comments
3	Document Name	Name of the document/file attached to the household record (for documents/files not stored in the form letter/document library). The name must include file path information to identify the location of the document/file.
4	Document ID	ID that identifies the document/file attached to the household record (for documents/files stored in the form letter/document library). This ID must be the same as the Document ID field in the associated 6A record.
5	User ID	User ID of the staffer who attached the document/file. There must be an 8A record containing this user ID.
6	Attached Date	Date when the document/file was attached to the household. Must be in YYYYMMDD format
7	Text	Freeform text containing comments or notes about the attached document/file.

5D Record – Household Text (Comments or Notes)

The may be multiple 5D records for a Household.

Field No	Field Name	Comments
1	Record Type	"5D" - indicates that the record contains comments or notes associated with the household.
2	Household ID	ID which identifies the household. This ID must be the same as the ID field in the associated 5A record for the household.
3	5D Sequence Number	Sequence number that identifies the order of 5D records for a household. A sequence number must be provided if fields 5/Date and 6/Time are NULL.
4	Text	Freeform text containing comments or notes about the household.
5	Date	Date the text was added to the record. Must be in YYYYMMDD format.
6	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).
7	User ID	User ID of the staffer who entered the text. There must be an 8A record containing this Staff/user ID.

Form Letter/Document Library Data

6A Record – Form Letter/Document Library Data

The following table will be used to define form letter library items and documents/files that are part of an office's document library. Files in the document library can be any document/file (most likely with meta-data attached) that an office wishes to retain for historical or reference purposes. As such, incoming email messages, incoming correspondence images, ad-hoc outgoing correspondence, and the like are not considered to be part of the document library.

Field No	Field Name	Comments
1	Record Type	"6A" – indicates that the record contains form letter/document data.
2	Document ID	A unique ID that identifies this version of the form letter/document.

Attachment J-10

Field No	Field Name	Comments
3	Version	Version of the form letter/document. (e.g. 1, 2, 3)
4	Document Grouping ID	ID which links multiple versions of a form letter/document.
5	Document Type	The type of document/file described in this record. "FORM" for form letter library item, or "DOC" for document library file.
6	Document Display Name	Display name of this version of the form letter/document (i.e. the name that the user sees). Must be provided for all 6A records.
7	Document Description	Freeform text describing the form letter/document.
8	Document Name	Name of this version of the form letter/document file. The name must include path/directory structure information to identify the physical location of the file. For example, "/docs/newsletters/oct99nl.doc".
9	Created By	User ID of the staffer who created this version of the form letter/document. There must be an 8A record containing this staff user ID.
10	Revised By	User ID of the staffer who last revised this version of the form letter/document. There must be an 8A record containing this staff user ID.
11	Approved By	User ID of the staffer who approved this version of the form letter/document. There must be an 8A record containing this staff user ID. NULL if approval is not required, or if approval has not yet been granted.
12	Creation Date	Creation date for this version of the form letter/document. Must be in YYYYMMDD format.
13	Revision Date	Last revision date for this version of the form letter/document. Must be in YYYYMMDD format.
14	Last Used Date	Date that this version of the form letter/document was last used/assigned. Must be in YYYYMMDD format.
15	Status	Status of this version of the form letter/document (e.g. Draft, Approved).
16	Inactive Flag	"Y" if this version of the form letter/document is inactive (for example, a form letter library item that has been used/assigned previously, but is not currently available for use because it's content is out of date)
17	Virtual Directory	Virtual directory structure/path of the form letter/document (i.e. the directory structure/path that the user sees). For example, "\FY16 Appropriation Requests\Education\".

6B Record – Form Letter/Document Library Fill-in Data

There may be multiple 6B records for a form letter/document, one for each fill-in (variable text insert) field.

Field No	Field Name	Comments
1	Record Type	"6B" – indicates that the record contains form letter/document fill-in data.
2	Document ID	ID that identifies this version of the form letter/document. This ID must be the same as the Document ID field in the associated 6A record.
3	Fill-in Field Name	The name of the fill-in field as it appears in the document/file.

Attachment J-10

6C Record – Form Letter/Document Library Code Data

This record is used to associate a form letter/document with workflow, communication or document codes. There may be multiple 6C records for a form letter/document.

Field No	Field Name	Comments
1	Record Type	"6C" – indicates that the record contains form letter/document code data.
2	Document ID	ID that identifies this version of the form letter/document. This ID must be the same as the Document ID field in the associated 6A record.
3	Code Type	Type of code entered in the following field. Enter the appropriate code type from the table below.
4	Code	Code used to describe the form letter/document. There must be an 8A record containing this code.

Code Type Values

Value	Meaning
WORK	Workflow codes
COM	Communication subject codes
DOC	Document codes

6D Record – Form Letter/Document Library Attachments

There may be multiple 6D records for a Form Letter/Document.

Field No	Field Name	Comments
1	Record Type	"6D" - indicates that the record contains information about documents/files attached to a form letter/document record.
2	Document ID	ID that identifies this version of the form letter/document. This ID must be the same as the Document ID field in the associated 6A record.
3	Document Name	Name of the document/file attached to the form letter/document. The name must include file path information to identify the location of the document/file.
4	User ID	User ID of the staffer who attached the document/file. There must be an 8A record containing this user ID.
5	Attached Date	Date when the document/file was attached to the form letter/document. Must be in YYYYMMDD format
6	Text	Freeform text containing comments or notes about the attached document/file.
7	Form Letter Attachment Flag	"Y" if this document/file is attached to a form letter and should be sent as part of the form letter response.

6E Record – Form Letter/Document Library Text (Comments or Notes)

The may be multiple 6E records for a Form Letter/Document.

Field No	Field Name	Comments
1	Record Type	"6E" - indicates that the record contains comments or notes associated

Attachment J-10

Field No	Field Name	Comments
		with the form letter/document.
2	Document ID	ID that identifies this version of the form letter/document. This ID must be the same as the Document ID field in the associated 6A record.
3	6E Sequence Number	Sequence number that identifies the order of 6E records for a form letter/document. A sequence number must be provided if fields 5/Date and 6/Time are NULL.
4	Text	Freeform text containing comments or notes about the form letter/document.
5	Date	Date the text was added to the record. Must be in YYYYMMDD format.
6	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).
7	User ID	User ID of the staffer who entered the text. There must be an 8A record containing this Staff/user ID.

6F Record – Form Letter/Document Library Owner Data

There may be multiple 6F records for a form letter/document.

Field No	Field Name	Comments
1	Record Type	"6F" – indicates that the record contains form letter/document owner data.
2	Document ID	ID that identifies this version of the form letter/document. This ID must be the same as the Document ID field in the associated 6A record.
3	Owned By	User ID of the owner of this version of the form letter/document (may also be known as the responsible staffer or the staffer that this form letter/document is assigned to). There must be an 8A record containing this staff user ID.

Schedule Data

7A Record – Schedule/Event Data

Field No	Field Name	Comments
1	Record Type	"7A" - indicates that the record contains schedule data.
2	Event ID	A unique ID which identifies the event.
3	Recurrence ID	ID which identifies the recurrence if this event is part of a recurring series. There must be a 7H record containing this recurrence ID. NULL if this event is not part of a recurring series. (Note: each event that is part of a recurring series must be provided individually in the 7A-F records)
4	Event Description	Freeform text describing the event.
5	Contact	Contact information about the person requesting/organizing the event (name, phone number, etc.)
6	County	County in which the event takes place
7	Organization	Organization hosting the event
8	Start Date	Event start date in YYYYMMDD format.

Attachment J-10

Field No	Field Name	Comments
9	Start Time	Event start time in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00). The time provided will be the time in the time zone in which the event occurs.
10	End Date	Event end date in YYYYMMDD format.
11	End Time	Event end time in HH:MM:SS format. The time provided will be the time in the time zone in which the event occurs.
12	Time Zone	Time Zone in which the event takes place (EST, CST, MST, PST, etc). The default is EST.
13	Location	The location of the event (e.g. the DC or state office).
14	Status	Status (e.g. Pending, Approved, Tentative, Declined)
15	Private Flag	"Y" if event is marked as private.
16	Scheduled Date	Date the event was entered into the schedule. Must be in YYYYMMDD format.
17	Scheduled by	User ID of staff person entering the event. There must be an 8A record containing this user ID.
18	Revision Date	Date the event was last revised. Must be in YYYYMMDD format.
19	Revised By	User ID of the staff person who last revised the event. There must be an 8A record containing this staff user ID.
20	Address line 1	First line of address at which the event takes place.
21	Address line 2	Second line of address at which the event takes place.
22	Address line 3	Third line of address at which the event takes place.
23	Address line 4	Fourth line of address at which the event takes place.
24	City	City in which the event takes place.
25	State Code	2 letter state code for the state in which the event takes place. For example, "VA", "DC" or "MD".
26	Zip Code	Zip code in which the event takes place. Format for 10 digit zip code is XXXXX-XXXX. If only the 5-digit code is known, then the format is XXXXX. If international address, enter the appropriate zip code of the country.
27	Country	Country (if international address) in which the event takes place.

7B Record – Event Code Data

There may be more than one 7B record for an event.

Field No	Field Name	Comments
1	Record Type	"7B" – indicates that the record contains schedule/event code data.
2	Event ID	ID that identifies the event. This ID must be the same as the Event ID field in the associated 7A record.
3	Event Code	A subject or interest code to describe the event. There must be an 8A record containing this event code.

Attachment J-10

7C Record – Event Participant Data

There may be more than one 7C record for an event.

Field No	Field Name	Comments
1	Record Type	"7C" – indicates that the record contains schedule event participant data.
2	Event ID	ID that identifies the event. This ID must be the same as the Event ID field in the associated 7A record.
3	Participant Type	Type of event participant entered in the following field. Enter the appropriate participant type code from the table below.
4	Participant ID	User ID of the Member or staffer who is to participate in the event. There must be an 8A record containing this user ID. OR Person ID of the person who is to participate in the event. There must be a 1A record containing this Person ID.

Participant Type Values

Value	Meaning
STAFF	Member or staff who is to participate in the event.
PERSON	Person who is to participate in the event.

7D Record – Event Attachments

There may be multiple 7D records for an event.

Field No	Field Name	Comments
1	Record Type	"7D" - indicates that the record contains information about documents/files attached to a schedule event record.
2	Event ID	ID which identifies the event. This ID field must be the same as the ID field in the associated 7A record for the event.
3	Document Name	Name of the document/file attached to the event (for documents/files not stored in the form letter/document library). The name must include file path information to identify the location of the document/file.
4	Document ID	ID that identifies the document/file attached to the event (for documents/files stored in the form letter/document library). This ID must be the same as the Document ID field in the associated 6A record.
5	User ID	User ID of the staffer who attached the document/file. There must be an 8A record containing this staff user ID.
6	Attached Date	Date when the document/file was attached to the event. Must be in YYYYMMDD format
7	Text	Freeform text containing comments or notes about the attached document/file.

Attachment J-10

7E Record – Event Text (Comments or Notes)

The may be multiple 7E records for an Event.

Field No	Field Name	Comments
1	Record Type	"7E" - indicates that the record contains comments or notes associated with the event.
2	Event ID	ID which identifies the event. This ID field must be the same as the ID field in the associated 7A record for the event.
3	7E Sequence Number	Sequence number that identifies the order of 7E records for an event. A sequence number must be provided if fields 5/Date and 6/Time are NULL.
4	Text	Freeform text containing comments or notes about the event.
5	Date	Date the text was added to the record. Must be in YYYYMMDD format.
6	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).
7	User ID	User ID of the staffer who entered the text. There must be an 8A record containing this Staff/user ID.

7F Record – Event Associated Workflows

There may be multiple 7F records for an event.

Field No	Field Name	Comments
1	Record Type	"7F" - indicates that the record contains information about workflows associated with a schedule event.
2	Event ID	ID which identifies the event. This ID field must be the same as the ID field in the associated 7A record for the event.
3	Workflow ID	ID that identifies the workflow attached to the event. This ID must be the same as the Workflow ID field in the associated 3A record.

7H Record – Recurring Series Definition Data

Field No	Field Name	Comments
1	Record Type	"7H" – indicates that the record contains recurring series definition data.
2	Recurrence ID	A unique ID that identifies the recurring series.
3	Start Series Date	Date of the first event for the series of recurring events. Must be in YYYYMMDD format.
4	End Series Date	Date of the last event for the series of recurring events. Must be in YYYYMMDD format. (NULL, if no "end series date" is specified.)
5	Recurrence Type	"DAILY", "WEEKLY", "MONTHLY" or "YEARLY"
6	Recurrence Interval	Definition of the recurrence interval. Values are per the recurrence interval schema*** below.

Attachment J-10

Recurrence Interval Schema***

Recurrence Type	Recurrence Interval Definition
DAILY	Pattern of the “daily” recurrence. Defined with one value. Defines the daily frequency interval. Valid values: “1”, “2”, ..., “weekdays”, “weekenddays”.
WEEKLY	Pattern of the “weekly” recurrence. Defined with two values separated by a dash. Part one defines the weekly frequency interval. Valid values: “1”, “2,” Part two defines the day of the week. Valid values: “sunday”, “monday”, “tuesday”, “wednesday”, “thursday”, “friday”, “saturday”
MONTHLY	Pattern of the “monthly” recurrence. Defined with three values separated by dashes. Part one defines the monthly frequency interval. Valid values: “1”, “2,” Part two defines the day descriptor. Valid values: “1”, “2”, ..., “31”, “last”. Part three defines the type of day. Valid values: “sunday”, “monday”, “tuesday”, “wednesday”, “thursday”, “friday”, “saturday”, “day”, “weekday”, “weekendday”.
YEARLY	Pattern of the “yearly” recurrence. Defined with four values separated by dashes. Part one defines the yearly frequency interval. Valid values: “1”, “2,” Part two defines the day descriptor. Valid values: “1”, “2”, ..., “31”, “last”. Part three defines the type of day. Valid values: “sunday”, “monday”, “tuesday”, “wednesday”, “thursday”, “friday”, “saturday”, “day”, “weekday”, “weekendday”. Part four defines the month. Valid values: “january”, “february”, “march”, “april”, “may”, “june”, “july”, “august”, “september”, “october”, “november”, “december”.

Sample Recurrence Interval Values

Value	Meaning
1	Event recurs every day (for “DAILY” recurrence type).
4	Event recurs every 4 th day (for “DAILY” recurrence type)
weekdays	Event recurs every weekday (for “DAILY” recurrence type).
weekenddays	Event recurs every weekend day (for “DAILY” recurrence type).
1-sunday	Event recurs every week on Sunday (for “WEEKLY” recurrence type).

Attachment J-10

2-monday	Event recurs every 2 nd week on Monday (for “WEEKLY” recurrence type).
1-1-day	Event recurs every month on the 1 st day of the month (for “MONTHLY” recurrence type).
3-15-day	Event recurs every 3 rd month on the 15 th day of the month (for “MONTHLY” recurrence type).
2-last-day	Event recurs every 2 nd month on the last day of the month (for “MONTHLY” recurrence type).
4-1-weekday	Event recurs every 4 th month on the first weekday of the month (for “MONTHLY” recurrence type).
3-1-weekendday	Event recurs every 3 rd month on the first weekend day of the month (for “MONTHLY” recurrence type).
1-1-tuesday	Event recurs every month on the 1 st Tuesday of the month (for “MONTHLY” recurrence type).
4-3-sunday	Event recurs every 4 th month on the 3 rd Sunday of the month (for “MONTHLY” recurrence type).
1-9-day-may	Event recurs every year on the 9 th day of May (for the “YEARLY” recurrence type).
1-5-weekday-june	Event recurs every year on the 5 th weekday of June (for the “YEARLY” recurrence type).
1-last-day-january	Event recurs every year on the last day of January (for the “YEARLY” recurrence type).
2-1-tuesday-november	Event recurs every 2 nd year on the 1 st Tuesday of November (for the “YEARLY” recurrence type).
1-2-weekendday-april	Event recurs every year on the 2 nd weekend day of April (for the “YEARLY” recurrence type).

The 7I – 7N records will be used as adjuncts to the 7H record (Recurring Series Definition Data) and will be used to transmit any additional data associated with a recurring series.

7I Record – Recurring Series Source Data

Field No	Field Name	Comments
1	Record Type	“7I” - indicates that the record contains recurring series source data.
2	Recurrence ID	A unique ID that identifies the recurring series. This ID must be the same as the Recurrence ID field in the associated 7H record.
3	Not used	Not used
4	Event Description	Freeform text describing the recurring series.
5	Contact	Contact information about the person requesting/organizing the recurring series (name, phone number, etc.)
6	County	County in which the recurring series takes place
7	Organization	Organization hosting the recurring series
8	Not used	Not used
9	Start Time	Recurring series start time in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00). The time provided will be the time in the time zone in which the recurring series occurs.
10	Not used	Not used.
11	End Time	Recurring series end time in HH:MM:SS format. The time provided will be the time in the time zone in which the recurring series occurs.

Attachment J-10

Field No	Field Name	Comments
12	Time Zone	Time Zone in which the recurring series takes place (EST, CST, MST, PST, etc). The default is EST.
13	Location	The location of the recurring series (e.g. the DC or state office).
14	Status	Status (e.g. Pending, Approved, Tentative, Declined)
15	Private Flag	"Y" if recurring series is marked as private.
16	Scheduled Date	Date the recurring series was entered into the schedule. Must be in YYYYMMDD format.
17	Scheduled by	User ID of staff person entering the recurring series. There must be an 8A record containing this user ID.
18	Revision Date	Date the recurring series was last revised. Must be in YYYYMMDD format.
19	Revised By	User ID of the staff person who last revised the recurring series. There must be an 8A record containing this staff user ID.
20	Address line 1	First line of address at which the recurring series takes place.
21	Address line 2	Second line of address at which the recurring series takes place.
22	Address line 3	Third line of address at which the recurring series takes place.
23	Address line 4	Fourth line of address at which the recurring series takes place.
24	City	City in which the recurring series takes place.
25	State Code	2 letter state code for the state in which the recurring series takes place. For example, "VA", "DC" or "MD".
26	Zip Code	Zip code in which the recurring series takes place. Format for 10 digit zip code is XXXXX-XXXX. If only the 5-digit code is known, then the format is XXXXX. If international address, enter the appropriate zip code of the country.
27	Country	Country (if international address) in which the recurring series takes place.

7J Record – Recurring Series Code Data

There may be more than one 7J record for a recurring series.

Field No	Field Name	Comments
1	Record Type	"7J" – indicates that the record contains recurring series code data.
2	Recurrence ID	A unique ID that identifies the recurring series. This ID must be the same as the Recurrence ID field in the associated 7H record.
3	Event Code	A subject or interest code to describe the recurring series. There must be an 8A record containing this event code.

7K Record – Recurring Series Participant Data

There may be more than one 7K record for a recurring series.

Field No	Field Name	Comments
1	Record Type	"7K" – indicates that the record contains recurring series participant data.
2	Recurrence ID	A unique ID that identifies the recurring series. This ID must be the same as the Recurrence ID field in the associated 7H record.

Attachment J-10

Field No	Field Name	Comments
3	Participant Type	Type of recurring series participant entered in the following field. Enter the appropriate participant type code from the table below.
4	Participant ID	User ID of the Member or staffer who is to participate in the recurring series. There must be an 8A record containing this user ID. OR Person ID of the person who is to participate in the recurring series. There must be a 1A record containing this Person ID.

Participant Type Values

Value	Meaning
STAFF	Member or staff who is to participate in the recurring series.
PERSON	Person who is to participate in the recurring series.

7L Record – Recurring Series Attachments

There may be multiple 7L records for a recurring series.

Field No	Field Name	Comments
1	Record Type	“7L” - indicates that the record contains information about documents/files attached to a recurring series record.
2	Recurrence ID	A unique ID that identifies the recurring series. This ID must be the same as the Recurrence ID field in the associated 7H record.
3	Document Name	Name of the document/file attached to the recurring series (for documents/files not stored in the form letter/document library). The name must include file path information to identify the location of the document/file.
4	Document ID	ID that identifies the document/file attached to the recurring series (for documents/files stored in the form letter/document library). This ID must be the same as the Document ID field in the associated 6A record.
5	User ID	User ID of the staffer who attached the document/file. There must be an 8A record containing this staff user ID.
6	Attached Date	Date when the document/file was attached to the recurring series. Must be in YYYYMMDD format
7	Text	Freeform text containing comments or notes about the attached document/file.

7M Record – Recurring Series Text (Comments or Notes)

The may be multiple 7M records for a recurring series.

Field No	Field Name	Comments
1	Record Type	“7M” - indicates that the record contains comments or notes associated with the recurring series.
2	Recurrence ID	A unique ID that identifies the recurring series. This ID must be the same as the Recurrence ID field in the associated 7H record.

Attachment J-10

Field No	Field Name	Comments
3	7M Sequence Number	Sequence number that identifies the order of 7M records for a recurring series. A sequence number must be provided if fields 5/Date and 6/Time are NULL.
4	Text	Freeform text containing comments or notes about the recurring series.
5	Date	Date the text was added to the record. Must be in YYYYMMDD format.
6	Time	Time the text was added to the record. Must be in HH:MM:SS format (e.g., 2:20 PM will be provided as 14:20:00).
7	User ID	User ID of the staffer who entered the text. There must be an 8A record containing this Staff/user ID.

7N Record – Recurring Series Associated Workflows

There may be multiple 7N records for a recurring series.

Field No	Field Name	Comments
1	Record Type	“7N” - indicates that the record contains information about workflows associated with a recurring series.
2	Recurrence ID	A unique ID that identifies the recurring series. This ID must be the same as the Recurrence ID field in the associated 7H record.
3	Workflow ID	ID that identifies the workflow attached to the recurring series. This ID must be the same as the Workflow ID field in the associated 3A record.

Code Table Data

8A Record – Code Table Data

Field No	Field Name	Comments
1	Record Type	“8A” – indicates that the record contains code table data.
2	Code Type	The type of code entered in the following field. Code types are defined in the table below.
3	Code	A standard code used throughout this format.
4	Code Description	A description or value of the code. If the code description is not present in the source data, the value of the code itself shall be repeated in this field.
5	Inactive Flag	“Y” if the code is inactive (i.e. the code has been assigned previously, but is not currently available for assignment).
6	User ID	Where applicable, the User ID of the staffer associated with this code. There must be an 8A record containing this Staff/user ID.

Code Type Values

Value	Record Location	Type Code
WORK	1C, 3B, 6C	Workflow codes
PERS	1C	Person codes

Attachment J-10

Value	Record Location	Type Code
COM	2B, 6C	Communication subject codes
EVENT	7B	Event codes
DOC	6C	Document codes
STAFF	1D, 1F, 2A, 2D, 3A, 3D, 3F, 5C, 5D, 6A, 6D, 6E, 7A, 7C, 7D, 7E	Staff user IDs

The record location indicates the types of records in which the code is located.

Additional Requirements

Documents/Attachments

All documents/files associated with the CSS will be copied and provided to the receiving vendor. All directory structures, including virtual directories, must be maintained. All documents/files must include file extensions, and the file extensions must accurately reflect the format of the file.

Word processing documents/files (responses to communications, form letter library documents, word processing documents in the document library, etc) will be provided in a format such that all formatting is maintained when the file is opened in Word.

Incoming email message files will be provided in their native format (e.g. .txt, .eml), provided that the documents/files are native to Windows-based Senate Standard Supported Software.

All other documents/files will be provided in their native format (e.g. .xls, .tif, .pdf, .), provided that the documents/files are native to Windows-based Senate Standard Supported Software.

Changes to the Format

Revisions to the format may be necessary as functionality is added to, or changed in, the CSS applications. It is the contractor's responsibility to identify necessary updates/additions to the format and to submit the proposed changes to the SAA for approval. Proposed changes to the format must be fully documented and presented to the SAA for approval as part of the "Software Maintenance" process (see section C.3.1.9).

Custom/User-defined Fields

Custom/user defined fields are fields that are unique to a particular office's CSS installation, and are not part of the standard configuration of the CSS.

Custom/user-defined fields will be added to the format, documented, and provided to the SAA for approval at least three weeks (15 business days) prior to the start of a data conversion.

If a field is provided as a custom/user-defined field from the application perspective, but the field is already present in the Senate CSS Data Interchange Format, then the data will be transmitted via the existing field in the format (e.g. if "spouse's name" is a custom/user-defined field within the

Attachment J-10

application, it will be provided in field 14 of the 1A record and will not be handled as a custom/user defined field because the field already exists in the format).

Additional Workflow Data

CSS specific field data that is associated with particular workflow types (i.e. some, but not all, workflow types/templates) will be provided in the “3L – Additional Workflow Data” record. This data generally falls into two categories:

1. Data fields associated with specific “workflow types” that are part of the out-of-the box configuration of the CSS (i.e. templates for these workflow types are standard offerings for the CSS, and are not custom/user-defined templates). These data fields will be documented, and provided to the SAA for approval one month (20 business days) after contract award.
2. Data fields associated with custom/user-defined “workflow types” (i.e. the templates for these workflow types are themselves custom/user-defined workflow templates) and/or custom/user-defined data fields associated with specific “workflow types”. These data fields will be documented, and provided to the SAA for approval at least three weeks (15 business days) prior to the start of the conversion.

Data fields that are applicable to all workflow types will be provided in the standard 3-series records (3A-3F). Additions/updates to this data will follow the procedures outlined above for “Changes to the Format” and “Custom/User-defined Fields”.

Conversion Documentation

Updates/additions to the format, where permitted, will be documented within the format (the new fields must be added to the existing format and highlighted), and provided to the SAA for approval at least three weeks (15 business days) prior to the start of the data conversion. Documentation will include:

- the field number (not applicable for 3L – Additional Workflow Data),
- the field name,
- a description of the data (the description must expand on the field name and provide enough detail to allow the receiving vendor to understand the purpose of data),
- a notation identifying custom/user-defined fields, as applicable,
- the data type (e.g. date, time, number, character encoding type or text),
- all pre-defined data values, as applicable, and
- for workflow data, the “workflow type code” that identifies the type of workflow process the field is used with.

The vendor will provide the approved conversion documentation to the receiving vendor no later than 2 weeks (10 business days) before the start of the data conversion.

Sample documentation for addition of a custom field:

1A Record – Name Data

Field No	Field Name	Comments
1	Record Type	“1A” - indicates that the record contains person name information
2	Person ID	A unique numeric ID which identifies the person.
3	Person Type	A code that identifies the type of person in this record. Use the appropriate

Attachment J-10

Field No	Field Name	Comments
		entry from the table below.
4	Prefix	Prefix of person such as "Mr.", "Mrs." or "The Honorable".
5	First Name	First name of person.
6	Middle Name	Middle name or initial of person.
7	Last Name	Last name of person.
8	Suffix	Suffix of person such as "Jr.".
9	Appellation	Appellation of person such as "MD".
10	Salutation	Preferred salutation used for the person, such as "Bob" or "Senator Jones".
11	Date of Birth	The person's date of birth in the format YYYYMMDD.
12	No Mail Flag	"Y" if the person has requested that no mail be sent to then at any of their addresses.
13	Deceased Flag	"Y" if the person is deceased.
14	Spouse's Name	Name of the person's spouse.
15	Email Flag	"Y" if the person has requested that their preferred method of communication is via email.
16	Gender	Gender of the person. Custom field. Data format=text. Valid values: "MALE" or "FEMALE".

Sample documentation for additional workflow data:

3L Record -- Additional Workflow Data – Workflow Type Code = CASE

Field Name	Description	Custom Field?	Data Type	Possible Values
SSN	The person's social security number.	Yes	Text	
.				
.				
.				

3L Record -- Additional Workflow Data – Workflow Type Code = FLAG

Field Name	Description	Custom Field?	Data Type	Possible Values
Flag Type	Describes the type of flag requested.		Text	3x5 cotton 3x5 nylon 5x8 cotton 5x8 nylon
Fly Date	The date the person has requested the flag to be flown over the Capitol.		Date	
Occasion	Describes the occasion for which the flag request was made (for example, birthday, graduation, etc).		Text	
.				
.				
.				

3L Record -- Additional Workflow Data – Workflow Type Code = TOUR

Field Name	Description	Custom Field?	Data Type	Possible Values
Group Size	The number of people in the group.		Number	
Arrival Date	The date the group arrives in DC.		Date	
Departure	The date the group departs from DC.		Date	

Attachment J-10

Field Name	Description	Custom Field?	Data Type	Possible Values
Date				
Special Needs	Free form text describing any special needs of the group.		Text	
White House Tour Flag	"Y" if a White House tour is requested.		Text	Y NULL
Capitol Tour Flag	"Y" if a Capitol tour is requested.		Text	Y NULL
.				
.				
.				

Sample documentation for "status" values:

*Communication Status Values

Status Value	Closed Flag
(The status provided must be the value that is displayed to the user when viewing the record.)	("Y" if this status indicates that the office has finished/completed their work on this communication, NULL if the status indicates that work on this communication is not completed.)
PENDING	
REQUEST APPROVAL	
CLOSED	Y
.	
.	
.	
.	

*Workflow Status Values

Status Value	Closed Flag
(The status provided must be the value that is displayed to the user when viewing the record.)	("Y" if this status indicates that the office has finished/completed their work on this workflow, NULL if the status indicates that work on this workflow is not completed.)
OPEN	
CLOSED FAVORABLY	Y
CLOSED	Y
.	
.	
.	
.	

Attachment J-10

“Date” and “Time” Fields

All “date” values will be provided in YYYYMMDD format.

All “time” values will be provided in HH:MM:SS format (e.g. 2:07pm and 23 seconds will be provided as 14:07:23).

“Type Codes/Values”

New type codes/values may be added without SAA approval only in those areas specifically noted within the format (i.e. 1B “address type values”, 1E “person phone or email type values”, 3A “workflow type values”). All such additions must be fully documented and must be consistent with the data definition of the field. For example, it is acceptable to add a new “address type value” of “SU/summer home” to the 1B “address type values”, but it is not acceptable to transmit the constituent’s gender via this field.

“Text” (Comments or Notes) Fields

“Text” (Comments or Notes) fields shall be used only as defined, i.e., to transmit freeform text containing comments or notes, and shall not be used to transmit other types of data. If data from a legacy system had previously been converted into a text field, it is acceptable for that data to remain in the text field.

8A – “Code Table Data”

For exit conversions performed to facilitate the transfer of data from one CSS to another, the vendor will provide an advance copy of the 8A/Code Table Data will be to the receiving vendor two weeks (10 business days) prior to the start of the conversion. This advance copy of the 8A data will facilitate updates to the code data that the office may wish to complete with the receiving vendor as part of the data conversion, and is not required for SCDIF archiving conversions.

The outgoing vendor will also provide **all** 8A data as part of the standard conversion data.

SCDIF Archiving Conversion Customizations

SCDIF archiving conversions will be customizable to the extent that the Member offices will have the option to include or exclude all or some of the data provided as category 3-workflow data and to include or exclude all of the category 7-schedule data.

For offices who wish to include only some of their workflow data, the SAA will work with the vendor to identify all of “workflow types” created by the office so the office can specify which should be included or excluded (for example, an office may choose to include all workflow types except for “CASE” and “INTERN” workflows).