

Block-Type Heat Substation Sizing

Complete the online questionnaire to size an ANHEL® block-type heat substation. A manager will respond within one business day.

HOW TO COMPLETE THIS FORM

Fill in the form by hand or in a PDF reader. Tick the relevant boxes (☐ → ☒). Where parameters are unknown, leave the line blank or write «to be determined». Return the completed form to sales@anelspb.com — our engineering team replies within one business day with a sizing proposal.

STEP 01

Contacts and facility

Who you are and where the heat substation will operate

Contact details

Company

Full name

Position

City

Email

Contact phone

Facility

Facility name and location

How did you hear about us?

How did you hear about us?

- ☐ Yandex / Google ads
- ☐ Yandex / Google search
- ☐ Social networks
- ☐ Recommendation from a colleague
- ☐ Already familiar, worked with us before
- ☐ Other

Please specify

STEP 02

Inlet parameters

District-heating water parameters and heat carrier

District water temperature schedule

At the substation inlet / outlet (winter)

T1 (inlet) °C
 T2 (outlet) °C

District water pressure

At the substation inlet / outlet

P1 (inlet) bar
 P2 (outlet) bar

General

Building height m

Heat carrier

Water, glycol solution (%), etc.

STEP 03

Heating

Heating-system parameters

Heating

Thermal load Gcal/h

☐ **Dependent (direct)**
 Connection scheme

☐ **Direct**
 Connection scheme

☐ **Brazed**
 Plate heat-exchanger type

☐ **Independent (indirect)**
 Connection scheme

☐ **Gasketed (demountable)**
 Plate heat-exchanger type

☐ Shell-and-tube
Plate heat-exchanger type

T1.2 inlet°C

T2.2 return°C

Heating system temperature schedule (winter)

System pressure dropm H₂O

Maximum working pressurem H₂O

System volumem³

Heat-exchanger redundancy

☐ Yes☐ No

HEX backup%

☐ 100%
Pump redundancy

☐ Spare on stock
Pump redundancy

☐ Twin pump
Pump redundancy

Pump VFD speed control

☐ Yes☐ No

STEP 04

Ventilation

Ventilation-system parameters

Ventilation

Thermal load

☐

Dependent (direct)

Connection scheme

☐

Independent (indirect)

Connection scheme

☐

Direct

Connection scheme

☐

Brazed

Plate heat-exchanger type

☐

Shell-and-tube

Plate heat-exchanger type

☐

Gasketed (demountable)

Plate heat-exchanger type

T1.2 inlet

T2.2 return

°C

°C

Ventilation system temperature schedule (winter)

System pressure drop _____ m H₂O

Maximum working pressure _____ m H₂O

System volume _____ m³

Heat-exchanger redundancy

- ☐ Yes
☐ No

HEX backup _____ % ☐ 100%
Pump redundancy

☐ Spare on stock
Pump redundancy

☐ Twin pump
Pump redundancy

Pump VFD speed control

- ☐ Yes
☐ No

STEP 05

DHW

Domestic hot water

Load and temperatures

Thermal load _____ Gcal/h

Cold water temperature _____ °C Hot water temperature _____ °C

Cold water inlet pressure at substation _____ bar Required hot water pressure _____ bar

Circulation

DHW circulation line required?

- ☐ Yes
☐ No

DHW circulation flow as % of peak demand _____ % DHW circulation head loss _____ m H₂O

DHW heat-exchanger configuration

- ☐ Single-stage ☐ Two-stage
☐ Single-skid (monoblock)

Plate heat-exchanger type

☐ Brazed

☐ Gasketed (demountable)

☐ Shell-and-tube

Redundancy

Heat-exchanger redundancy

- ☐ Yes
☐ No

HEX backup

_____ % ☐ 100%
Pump redundancy

☐ Spare on stock
Pump redundancy

☐ Twin pump
Pump redundancy

Pump VFD speed control

- ☐ Yes
☐ No

STEP 06

Additional equipment

Options, valves, communication, power

Additional equipment, functions, and parameters

Outdoor-temperature compensation

- ☐ Yes
☐ No

Automatic make-up line for heating and ventilation

- ☐ Yes
☐ No

Automatic pressure-maintenance unit for heating and ventilation

- ☐ Yes
☐ No

Thermal energy metering unit

- ☐ Yes
☐ No

Differential pressure regulator

- ☐ Yes
☐ No

Expansion tank

- ☐ Yes
☐ No

Cold-water flow meter

- ☐ Yes
☐ No

Pump-failure sensor (DP switch)

- ☐ Yes
☐ No

SCADA / dispatching

- ☐ Yes
☐ No

Provide a make-up valve

- ☐ Yes
☐ No

Provide a make-up pump

- ☐ Yes
☐ No

Pipework insulation

- ☐ Yes
☐ No

Inlet valves and fittings (steel)

- ☐ Welded ☐ Flanged
☐ Threaded

Dimensions

Substation room dimensions (L × W × H) _____ mm

Doorway size (W × H) _____ mm

Data communication to SCADA

- ☐ RS232 (485) ☐ Ethernet
☐ GSM ☐ Tel. modem

Power

Pumps powered from the substation control cabinet

- ☐ Yes
☐ No

Pumps powered from an external cabinet

- ☐ Yes
☐ No

- ☐ 1 × 230 V ☐ 3 × 380 V
Supply voltage Supply voltage

Additional information

Additional information

Attach any project drawings, water analyses or specifications as separate files when you reply.