

The logo for Oracle Academy. It features the word "ORACLE" in a bold, orange, sans-serif font. Below it, the word "Academy" is written in a smaller, dark gray, sans-serif font. The entire logo is centered on a light gray background, which is framed by dark gray horizontal bars at the top and bottom.

# ORACLE

## Academy

# Database Programming with SQL

12-3

**DEFAULT Values, MERGE, and Multi-Table Inserts**

**ORACLE**  
Academy



Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

# Objectives

- This lesson covers the following objectives:
  - Understand when to specify a DEFAULT value
  - Construct and execute a MERGE statement
  - Construct and execute DML statements using subqueries
  - Construct and execute multi-table inserts

## Purpose

- Up to now, you have been updating data using a single INSERT statement
- It has been relatively easy when adding records one at a time, but what if your company is very large and utilizes a data warehouse to store sales records, customer, payroll, accounting, and personal data?
- In this case, data is probably coming in from multiple sources and being managed by multiple people
- Managing data one record at a time could be very confusing and very time consuming

A data warehouse is a collection of data designed to support business-management decision making. Data warehouses contain a wide variety of data, such as sales data, customer data, payroll, accounting, and personnel data, which presents a coherent picture of business conditions at a single point in time.

## Purpose

- How do you determine what has been newly inserted or what has been recently changed?
- In this lesson, you will learn a more efficient method to update and insert data using a sequence of conditional INSERT and UPDATE commands in a single atomic statement
- You will also learn how to retrieve data from one single subquery and INSERT the rows returned into more than one target table
- As you extend your knowledge in SQL, you'll appreciate effective ways to accomplish your work

# DEFAULT

- Each column in a table can have a default value specified for it
- In the event that a new row is inserted and no value for the column is assigned, the default value will be assigned instead of a null value
- Using default values allows you to control where and when the default value should be applied

# DEFAULT

- The default value can be a literal value, an expression, or a SQL function such as SYSDATE and USER, but the value cannot be the name of another column
- The default value must match the data type of the column
- DEFAULT can be specified for a column when the table is created or altered

## DEFAULT Example

- The example below shows a default value being specified for the hire\_date column at the time the table is created:

```
CREATE TABLE my_employees (  
    hire_date      DATE DEFAULT SYSDATE,  
    first_name     VARCHAR2(15) ,  
    last_name      VARCHAR2(15) ) ;
```

- When rows are added to this table, SYSDATE will be assigned to any row that does not explicitly specify a hire\_date value

Creating and altering tables is discussed in more detail later in the course.



## Explicit DEFAULT with INSERT

- Explicit defaults can be used in INSERT and UPDATE statements
- The INSERT example using the my\_employees table shows the explicit use of DEFAULT:

```
INSERT INTO my_employees  
  (hire_date, first_name, last_name)  
VALUES  
  (DEFAULT, 'Angelina', 'Wright');
```

- Implicit use of DEFAULT

```
INSERT INTO my_employees  
  (first_name, last_name)  
VALUES  
  ('Angelina', 'Wright');
```

If a default value was specified for the hire\_date column when the table was created, Oracle assigns the default value to the column. However, if no default value was specified, Oracle assigns a null value.

## Explicit DEFAULT with UPDATE

- Explicit defaults can be used in INSERT and UPDATE statements
- The UPDATE example using the my\_employees table shows explicit use of DEFAULT

```
UPDATE my_employees  
SET hire_date = DEFAULT  
WHERE last_name = 'Wright';
```

- If a default value was specified for the hire\_date column, the column is assigned the default value
- However, if no default value was specified when the column was created, a null value is assigned

# MERGE

- Using the MERGE statement accomplishes two tasks at the same time. MERGE will INSERT and UPDATE simultaneously. If a value is missing, a new one is inserted
- If a value exists but needs to be changed, MERGE will update it
- To perform these kinds of changes to database tables, you need to have INSERT and UPDATE privileges on the target table and SELECT privileges on the source table
- Aliases can be used with the MERGE statement

## MERGE Syntax

- One row at a time is read from the source table and compared to rows in the destination table using the matching condition
- If a matching row exists in the destination table, the source row is used to update one or more columns in the matching destination row
- If a matching row does not exist, values from the source row are used to insert a new row into the destination table

```
MERGE INTO destination-table USING source-table
ON matching-condition
WHEN MATCHED THEN UPDATE
SET .....
WHEN NOT MATCHED THEN INSERT
VALUES (.....) ;
```

## MERGE Example

- This example uses the EMPLOYEES table (alias e) as a data source to insert and update rows in a copy of the table named COPY\_EMP (alias c)

```
MERGE INTO copy_emp c USING employees e
  ON (c.employee_id = e.employee_id)
WHEN MATCHED THEN UPDATE
  SET
    c.last_name    = e.last_name,
    c.department_id = e.department_id
WHEN NOT MATCHED THEN INSERT
  VALUES (e.employee_id, e.last_name, e.department_id);
```

**ORACLE**  
Academy

DP 12-3  
DEFAULT Values, MERGE, and Multi-Table Inserts

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

13

```
create table copy_emp as (Select * from employees where department_id > 100);

select * from copy_emp;

update copy_emp
set last_name = 'Cotton'
where employee_id = 205;

select * from copy_emp;

MERGE INTO copy_emp c USING employees e
  ON (c.employee_id = e.employee_id)
WHEN MATCHED THEN UPDATE
  SET
    c.last_name    = e.last_name,
    c.department_id = e.department_id
WHEN NOT MATCHED THEN INSERT
  VALUES (e.employee_id, e.first_name, e.last_name, e.email, e.phone_number, e.hire_date, e.job_id,
e.salary, e.commission_pct, e.manager_id, e.department_id, e.bonus);

select * from copy_emp;

drop table copy_emp;
```

## MERGE Example

- EMPLOYEES rows 100 and 103 have matching rows in COPY\_EMP, and so the matching COPY\_EMP rows were updated
- EMPLOYEE 142 had no matching row, and so was inserted into COPY\_EMP

EMPLOYEES (source table)

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	King	90
103	Hunold	60
142	Davies	50

# MERGE Example

EMPLOYEES (source table)

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	King	90
103	Hunold	60
142	Davies	50

COPY\_EMP before the MERGE is executed

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	Smith	40
103	Chang	30

COPY\_EMP after the MERGE has executed

EMPLOYEE_ID	LAST_NAME	DEPARTMENT_ID
100	King	90
103	Hunold	60
142	Davies	50

## Multi-Table Inserts

- Multi-table inserts are used when the same source data should be inserted into more than one target table
- This functionality is useful when you are working in a data warehouse environment where it is common to regularly move data from the operational systems into a data warehouse for analytical reporting and analysis
- Creating and managing data warehouses is one way of managing the sometimes very high number of rows inserted into operational systems during a normal working day



## Multi-Table Inserts

- Imagine, for instance, how many rows of data your telephone provider must create daily for all of your calls or text messages made on all of the devices that you have access to?
- Then add to that your internet surfing and downloads of ringtones, wallpapers, games, and other mobile applications
- Multiply that number by the total number of customers, and that might give you an idea of the amount of data the telecommunication companies have to manage
- These rows may have to be inserted into more than one table in the data warehouse, so if we can just `SELECT` them once and then replicate them, that will improve the performance

## Multi-Table Inserts

- Multi-table inserts can be unconditional or conditional. In an unconditional multi-table insert, Oracle will insert all rows returned by the subquery into all table insert clauses found in the statement
- In a conditional multi-table insert, you can specify either ALL or FIRST



# Multi-Table Inserts

- Specifying ALL:

- If you specify ALL, the default value, the database evaluates each WHEN clause regardless of the results of the evaluation of any other WHEN clause
- For each WHEN clause whose condition evaluates to true, the database executes the corresponding INTO clause list

- Specifying FIRST:

- If you specify FIRST, the database evaluates each WHEN clause in the order in which it appears in the statement
- For the first WHEN clause that evaluates to true, the database executes the corresponding INTO clause and skips subsequent WHEN clauses for the given row

Note: there are times when the WHEN clause is not required, see example on next slide.

# Multi-Table Inserts

- Specifying the ELSE clause:
  - For a given row, if no WHEN clause evaluates to true, the database executes the INTO clause list associated with the ELSE clause
  - If you did not specify an else clause, then the database takes no action for that row



For more detailed examples including the use of FIRST and ELSE, visit  
[http://docs.oracle.com/cd/B19306\\_01/server.102/b14200/statements\\_9014.htm#i2125362](http://docs.oracle.com/cd/B19306_01/server.102/b14200/statements_9014.htm#i2125362)

# Multi-Table Inserts Syntax

- Multi-table insert statement syntax is as follows:

```
INSERT ALL INTO clause VALUES clause SUBQUERY
```

- Multi-table insert statement example is as follows:

```
INSERT ALL
  INTO my_employees
    VALUES (hire_date, first_name, last_name)
  INTO copy_my_employees
    VALUES (hire_date, first_name, last_name)
SELECT hire_date, first_name, last_name
FROM employees;
```

This multi-table insert, will retrieve the rows from the SELECT statement, and INSERT the rows into both the my\_employees and copy\_my\_employees table.

INSERT ALL requires a SELECT statement in order to run. We can, however, use the dummy table DUAL to perform multiple INSERT statements into a single table – for example:

```
INSERT ALL
  INTO copy_employees
    (employee_id, first_name, last_name, email, phone_number, hire_date, job_id, salary)
  VALUES
    (304,'James','Parrot', 'jparrot', '912-699-4656', '15/Jul/2017', 'IT_PROG',4200)
  INTO copy_employees
    (employee_id, first_name, last_name, email, phone_number, hire_date, job_id, salary)
  VALUES
    (305,'Rebecca','Graham', 'rgraham', '480-678-4259', '15/Jun/2017', 'IT_PROG',4200)
SELECT * FROM dual;
```

# Multi-Table Inserts Conditional

```
INSERT ALL
  WHEN call_format IN ('tlk','txt','pic') THEN
  INTO all_calls
    VALUES (caller_id, call_timestamp, call_duration, call_format)
  WHEN call_format IN ('tlk','txt') THEN
  INTO police_record_calls
    VALUES (caller_id, call_timestamp, recipient_caller)
  WHEN call_duration < 50 AND call_type = 'tlk' THEN
  INTO short_calls
    VALUES (caller_id, call_timestamp, call_duration)
  WHEN call_duration >= 50 AND call_type = 'tlk' THEN
  INTO long_calls
    VALUES (caller_id, call_timestamp, call_duration)
SELECT caller_id, call_timestamp, call_duration, call_format,
       recipient_caller
FROM calls
WHERE TRUNC(call_timestamp) = TRUNC(SYSDATE);
```

This multi-table insert uses the WHEN condition. If a row from the SELECT statement matches the criteria of the WHEN condition, the row is added to the table in the INTO clause.

Note: this example is used to demonstrate a real-world use for multi-table inserts, but as tables do not exist this query will not run in APEX.

# Terminology

- Key terms used in this lesson included:
  - DEFAULT
  - MERGE
  - Multi-Table Inserts
  - ALL, FIRST, and ELSE

## Summary

- In this lesson, you should have learned how to:
  - Understand when to specify a DEFAULT value
  - Construct and execute a MERGE statement
  - Construct and execute DML statements using subqueries
  - Construct and execute multi-table inserts



The logo for Oracle Academy is centered on a light gray background. It features the word "ORACLE" in a bold, orange, sans-serif font. Below it, the word "Academy" is written in a smaller, dark gray, sans-serif font. The entire logo is framed by two horizontal dark gray bars, one at the top and one at the bottom.

# ORACLE

## Academy