
# ORACLE Academy

# Database Programming with SQL

6-2
Join Clauses

ORACLE Academy



#### **Objectives**

- This lesson covers the following objectives:
  - -Construct and execute a join with the ANSI-99 USING Clause
  - -Construct and execute a join with the ANSI-99 ON Clause
  - Construct and execute an ANSI-99 query that joins three tables



DP 6-2 Join Clauses

#### Purpose

- As you add more commands to your database vocabulary, you will be better able to design queries that return the desired result
- The purpose of a join is to bind data together, across tables, without repeating all of the data in every table
- Why ask for more data than you really need?



DP 6-2 Join Clauses

#### **USING Clause**

- In a natural join, if the tables have columns with the same names but different data types, the join causes an error
- To avoid this situation, the join clause can be modified with a USING clause
- The USING clause specifies the columns that should be used for the join



DP 6-2

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

A USING clause is often preferred to a natural join even when the columns have the same data type as well as the same name, because it clearly states exactly which join column is being used.

#### **USING Clause**

- The query shown is an example of the USING clause
- The columns referenced in the USING clause should not have a qualifier (table name or alias) anywhere in the SQL statement

SELECT first\_name, last\_name, department\_id, department\_name
FROM employees JOIN departments USING (department id);

FIRST_NAME	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
Jennifer	Whalen	10	Administration
Michael	Hartstein	20	Marketing
Pat	Fay	20	Marketing



Academy

DP 6-2

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

If the column in the USING clause has a qualifier, the following error is returned

ORA-25154: column part of USING clause cannot have qualifier.

Note: the last line in the sample output uses ... ... ... to signify that more data is returned than is displayed on the slide.

6

#### **USING Clause**

• The USING clause allows us to use WHERE to restrict rows from one or both tables:

SELECT first\_name, last\_name, department\_id, department\_name
FROM employees JOIN departments USING (department\_id)
WHERE last\_name = 'Higgins';

FIRST_NAME	LAST_NAME	DEPARTMENT_ID	DEPARTMENT_NAME
Shelley	Higgins	110	Accounting



Academy

DP 6-2 Join Clauses

#### A JAMAN A TITAL

#### **ON Clause**

- What if the columns to be joined have different names, or if the join uses non-equality comparison operators such as <, >, or BETWEEN?
- We can't use USING, so instead we use an ON clause
- This allows a greater variety of join conditions to be specified
- The ON clause also allows us to use WHERE to restrict rows from one or both tables



DP 6-2 Join Clauses

#### **ON Clause Example**

 In this example, the ON clause is used to join the employees table with the jobs table

```
SELECT last_name, job_title
FROM employees e JOIN jobs j
ON (e.job_id = j.job_id);
```

 A join ON clause is required when the common columns have different names in the two tables

#### ORACLE

Academy

DP 6-2

LAST_NAME	JOB_TITLE	
King	President	
Kochhar	Administration	
Rocillai	Vice President	
De Haan	Administration	
De Haaii	Vice President	
Whalen	Administration	
vviiaičii	Assistant	
Higgins	Accounting	
riiggiiis	Manager	
Gietz	Public	
Gletz	Accountant	
Zlotkey	Sales Manager	
Abel	Sales	
Abei	Representative	
Taylor	Sales	
layioi	Representative	

#### **ON Clause Example**

- When using an ON clause on columns with the same name in both tables, you need to add a qualifier (either the table name or alias) otherwise an error will be

  returned

  ON (e.job\_id = j.job\_id);

  LAST\_NAME JOB\_TITLE

  King President

  Vice President
- The example above uses table aliases as a qualifier e.job\_id = j.job\_id, but could also have been written using the table names (employees.job\_id = jobs.job\_id

LAST_NAME	JOB_TITLE	
King	President	
Kochhar	Administration	
Kociiiai	Vice President	
De Haan	Administration	
ре паап	Vice President	
Whalen	Administration	
vviiaieii	Assistant	
Higgins	Accounting	
riiggiiis	Manager	
Gietz	Public	
GIELZ	Accountant	
Zlotkey	Sales Manager	

Sales

Sales

Representative

Representative

SELECT last\_name, job\_title
FROM employees e JOIN jobs j

ORACLE Academy

DP 6-2 Join Clauses

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

Abel

Taylor

#### ON Clause with WHERE Clause

 Here is the same query with a WHERE clause to restrict the rows selected

```
SELECT last_name, job_title
FROM employees e JOIN jobs j
  ON (e.job_id = j.job_id)
WHERE last_name LIKE 'H%';
```

LAST_NAME	JOB_TITLE
Higgins	Accounting Manager
Hunold	Programmer
Hartstein	Marketing Manager



DP 6-2

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

11

Note: As the job\_id column in the employees and jobs tables have the same name and data type, the above query could also be written with a NATURAL JOIN, or a JOIN USING.

#### ON Clause with non-equality operator

- Sometimes you may need to retrieve data from a table that has no corresponding column in another table
- Suppose we want to know the grade\_level for each employees salary
- The job\_grades table does not have a common column with the employees table
- Using an ON clause allows us to join the two tables

job grades table

GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
А	1000	2999
В	3000	5999
С	6000	9999
D	10000	14999
Е	15000	24999
F	25000	40000

ORACLE Academy

DP 6-2

#### ON Clause with non-equality operator

```
SELECT last_name, salary, grade_level, lowest_sal,
highest_sal
FROM employees JOIN job_grades
   ON(salary BETWEEN lowest_sal AND highest_sal);
```

LAST_NAME	SALARY	GRADE_LEVEL	LOWEST_SAL	HIGHEST_SAL
Vargas	2500	А	1000	2999
Matos	2600	А	1000	2999
Davies	3100	В	3000	5999
Rajs	3500	В	3000	5999
Lorentz	4200	В	3000	5999
Whalen	4400	В	3000	5999
Mourgos	5800	В	3000	5999
Fay	6000	С	6000	9999



Academy

DP 6-2

Copyright © 2020, Oracle and/or its affiliates. All rights reserved.

13

With a JOIN ON clause, you can use operators other than "=". For example >=, <=, BETWEEN.

#### Joining Three Tables

- Both USING and ON can be used to join three or more tables
- Suppose we need a report of our employees, their department, and the city where the department is located?
- We need to join three tables: employees, departments and locations





DP 6-2 Join Clauses

#### Joining Three Tables Example

SELECT last\_name, department\_name AS "Department", city
FROM employees JOIN departments USING (department\_id)
 JOIN locations USING (location\_id);



LAST_NAME	Departemen	CITY
Hartstein	Marketing	Toronto
Fay	Marketing	Toronto
Zlotkey	Sales	Oxford
Abel	Sales	Oxford
Taylor	Sales	Oxford
Hunold	IT	Southlake
Ernst	IT	Southlake
Lorentz	IT	Southlake
Mourgos	Shipping	South San Francisco



DP 6-2

### Terminology

- Key terms used in this lesson included:
  - -ON clause
  - -USING clause



DP 6-2 Join Clauses

#### Summary

- In this lesson, you should have learned how to:
  - -Construct and execute a join with the ANSI-99 USING Clause
  - -Construct and execute a join with the ANSI-99 ON Clause
  - Construct and execute an ANSI-99 query that joins three tables



DP 6-2 Join Clauses

# ORACLE Academy