What I did is basically Ollama LLM plus furhat handcrafted gestures (they are not too good though.)

The furhat can have discussions but expects gesture. When it hears “do + gesture” where gesture is “angry” or “happy” or “sad” or “thinking” or whatever, it sends the state to a gesture state where it activates one of my gesture functions. After gesture state it is expected to return the normal Loop but it is not always smooth. From what I experience, after a successful gesture, I always have had an unsuccessful one. And the loop never ends.

The gesture state as follows, which controls for all possible gestures in the inventory:

```
GestureState: {
    always: [
     {
       guard: ({ context }) => context.extractedGesture === "angry",
       target: "AngryGesture",
     },
     {
       guard: ({ context }) => context.extractedGesture === "kidding",
       target: "KiddingGesture",
     },
     {
       guard: ({ context }) => context.extractedGesture === "serious",
       target: "SeriousGesture",
     },
     {
       guard: ({ context }) => context.extractedGesture === "thinking",
       target: "ThinkingGesture",
     },
     {
       guard: ({ context }) => context.extractedGesture === "happy",
       target: "HappyGesture",
     },
     {
       guard: ({ context }) => context.extractedGesture === "sad",
       target: "SadGesture",
```

```
    },
    {
      // Fallback if something goes wrong
      target: "Loop",
    },
  ],
},
```