

Image Deblur and Denoise

Cosmin-Eusebiu Patraşcu

Vlad-Ştefan Moreanu

Abstract—Hello world! [1]

I. STATE-OF-THE-ART

The landscape of image restoration and synthesis has advanced rapidly, moving from highly optimized Convolutional Neural Networks (CNNs) to highly efficient Vision Transformers and diffusion models. Each state-of-the-art (SOTA) model introduces distinct architectural innovations to overcome the trade-offs between computational cost and restoration accuracy

A. Convolutional Neural Networks

DnCNN (Denoising Convolutional Neural Network) introduces a residual learning strategy combined with batch normalization. Instead of predicting the clean image directly, the model learns to predict the residual noise. This speeds up training, stabilizes the network and allows a single model (DnCNN-B) to handle blind gaussian denoising. [1]

This strategy allowed DnCNN-B to outperform AR-CNN, a specialized model, by 0.3 dB in PSNR.

FFDNet brings a tunable noise level map as a direct input, allowing a single network to flexibly handle complex, non-uniform noise. Additionally, it processes the image in a down-sampled sub-image space, which vastly improves inference speed and expands the receptive field without losing modeling capacity. [2]

This model can keep a performance of 26-27 dB PSNR across a vast noise level range, while being significantly faster than DnCNN.

B. High-Efficiency and Adversarial Architectures

DeblurGAN approaches blind motion deblurring as an image-to-image translation task using Conditional Generative Adversarial Networks (cGANs). This introduces a multi-component loss function, combining WGAN-GP and perceptual loss, to generate sharp and realistic textures rather than the overly smooth results found in basic CNNs. Its efficient architecture makes it 5 times faster than other models, making it a good choice for downstream object detection tasks. On the GoPro dataset, it achieved a PSNR of 29.7 dB and an SSIM of 0.958. [3]

MIMO-UNet brings the re-engineering of the coarse-to-fine strategy into a single U-Net. It uses a Multi-Input Single Encoder (MISE) to process multi-scale blurry images simultaneously, and a Multi-Output Single Decoder (MOSD) to output multiple deblurred images, achieving SOTA accuracy while running over 4 times faster than previous complex models. [4]

The largest model (MIMO-Unet++) has a PSNR of 32.68 dB on the GoPro dataset, with a processing time of 0.004 seconds.

C. Vision Transformers

SwinIR, based on the Swin transformer, replaces traditional convolution layers with Residual Swin Transformer Blocks (RSTB). This has the advantage of local attention processing and shifted-window mechanisms for modeling long range dependencies. The model. For the super-resolution task it has achieved a PSNR of 32.7 dB, while having significantly less parameters than models with the same results. [5]

Uformer brings transformer capabilities into a classic U-shaped architecture. Its contribution is the Locally-enhanced Window (LeWin) Transformer block, which calculates self-attention only within non-overlapping windows to reduce computational complexity. It also introduces a learnable multi-scale restoration modulator to handle varied image degradations. [6]

On image denoising, Uformer achieved 39.9 dB in PSNR, outperforming heavier models. For deblurring, on the GoPro dataset, the model obtained a result of 33 dB

Restormer brings Multi-Dconv Head Transposed Attention (MDTA), which calculates self-attention across the feature (channel) dimension rather than the spatial dimension, bringing the self-attention complexity down to a linear scale, which is quadratic for normal transformers. It also introduces a Gated-Dconv Feed-Forward Network (GDFN) to act as a filter for less important features. For the task of denoising, it has achieved a PSNR of 40 dB, and 33 dB for deblurring. [7]

D. Generative Synthesis

While diffusion models are powerful, calculating them directly in pixel space is incredibly slow and expensive. Latent Diffusion Models (LDM) bring the innovation of decoupling perceptual and semantic compression. By first training an autoencoder to compress images into a lower-dimensional latent space, the diffusion process can occur much more efficiently. This allows the model to strike a near-optimal balance between complexity reduction and detail preservation. Furthermore, LDMs introduce cross-attention layers into the diffusion UNet, making them incredibly flexible for multi-modal conditioning. [8]

II. METHOD AND DATASET DESCRIPTION

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy

eget, consecetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

III. EXPERIMENTS AND RESULTS

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis.

Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

IV. CONCLUSIONS

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

REFERENCES

- [1] K. Zhang, W. Zuo, Y. Chen, D. Meng, and L. Zhang, "Beyond a gaussian denoiser: Residual learning of deep cnn for image denoising," *IEEE transactions on image processing*, vol. 26, no. 7, pp. 3142–3155, 2017.
- [2] K. Zhang, W. Zuo, and L. Zhang, "Ffdnet: Toward a fast and flexible solution for cnn-based image denoising," *IEEE Transactions on Image Processing*, vol. 27, no. 9, pp. 4608–4622, 2018.
- [3] O. Kupyn, V. Budzan, M. Mykhailych, D. Mishkin, and J. Matas, "Deblurgan: Blind motion deblurring using conditional adversarial networks," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2018, pp. 8183–8192.
- [4] S.-J. Cho, S.-W. Ji, J.-P. Hong, S.-W. Jung, and S.-J. Ko, "Rethinking coarse-to-fine approach in single image deblurring," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2021, pp. 4641–4650.
- [5] J. Liang, J. Cao, G. Sun, K. Zhang, L. Van Gool, and R. Timofte, "Swinir: Image restoration using swin transformer," in *Proceedings of the IEEE/CVF international conference on computer vision*, 2021, pp. 1833–1844.
- [6] Z. Wang, X. Cun, J. Bao, W. Zhou, J. Liu, and H. Li, "Uformer: A general u-shaped transformer for image restoration," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 17 683–17 693.
- [7] S. W. Zamir, A. Arora, S. Khan, M. Hayat, F. S. Khan, and M.-H. Yang, "Restormer: Efficient transformer for high-resolution image restoration," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 5728–5739.

- [8] R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer, “High-resolution image synthesis with latent diffusion models,” in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2022, pp. 10 684–10 695.