




## DECLARATION DE PERFORMANCE

No. 01OPR

|   |   |   |
|---|---|---|
| 1. Unique identification code of the product type<br>Type, batch or serial number or any other element allowing identification of the product | <b>Dry-pressed ceramic tiles, with water absorption Eb ≤ 0,5%</b><br><br><b>Brand Bell'Italia Tiles</b><br><b>SERIE GREYSTONE</b> |   |
| 2. Intended use(s)  | <b>For internal and external floorings</b>  |   |
| 3. Name or registered trade mark, and contact address of the manufacture  | <b>Opera Group S.r.l. - Via Martinella, 74</b><br><b>41053 Maranello (Italy)</b>  |   |
| 4. Systems(s) of assessment and verification of costancy of performance (AVCP)  | <b>Systems 4</b>  |   |
| 6. Declared performances  |   |   |
| <b>Essential characteristics</b>  | <b>Performance</b>  | <b>Harmonised technical specification</b>   |
| <b>Reaction to fire</b>   | A1fl/A1   | <br><b>EN 14411:2012</b> |
| <b>Breaking strength</b>  | Thickness ≥7,5 mm >1300 N   |   |
| <b>Release of dangerous substance, for:</b><br><b>- Cadmium</b><br><b>- Lead</b>  | NPD<br>NPD  |   |
| <b>Slipperiness</b>   | NPD   |   |
| <b>Durability for:</b><br><b>- internal use</b><br><b>- external use: freeze-thaw resistance</b>  | Pass<br>NPD   |   |
| <b>Thermal shock resistance</b>   | NPD   |   |
| <b>Tactily</b>  | NPD   |   |
| <b>Bond strength/adhesion</b>   | NPD   |   |
| <b>Slipperiness</b>   | R10   |   |
|   |   |   |

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Maranello, 27.03.018