FlowForge

Phase 7 Guide & Build Spec

AI Agent and Durable Workflow Automation Platform

Built 2026-10-25

Contents

1. Phase 7: Approvals, RBAC and Audit
2. Phase 7 Spec: Human Approvals, RBAC, and Audit Trail
3. Shared: Glossary
4. Shared: Release gates
5. Shared: Progress log
6. FlowForge Global Specification (v1, MVP scope)

About this guide

What this file is. The single, all-in-one plan. For each phase it holds the concepts, the reasons behind every decision, the build checklist, acceptance criteria, labs, sources, growth mapping, self-test and definition of done. At the end of each phase you build that phase's PDF (see "Per-phase PDFs" below).

Product. A multi-tenant AI agent and durable workflow automation platform: versioned directed workflows, asynchronous runs, human approval, allowlisted tools and LLM steps, full audit and recovery.

Source roadmap: `01_FastAPI_AI_Agent_Workflow_Engineering_Roadmap.md` (25 Oct 2026). **Stack:** FastAPI, Pydantic v2, PostgreSQL, SQLAlchemy 2 async, Alembic, Celery + RabbitMQ, OpenTelemetry, Prometheus/Grafana, React + TypeScript + Vite, email/password JWT login, OpenRouter `:free` models, `pip` + `pip-tools`.

> **Honesty notes.** Latency and cost numbers are hypotheses to measure. Source status is labelled `checked` (confirmed through a web search of official/standards pages on 2026-10-25, not read page by page) or `to read` (taken from the roadmap, not yet opened). Portfolio systems show senior-level behaviour. They do not confer a job title.

Phase 7: Approvals, RBAC and Audit

Roadmap week 7.

Objective

Put a human in the loop for sensitive steps, with permissions that are checked at decision time and an audit trail that can't be rewritten.

Concepts to learn

- **Least privilege** and role-scoped tool grants.
- **AuthN vs AuthZ**; checking authorization on the object, at decision time, not just when the request was created.
- **Race-safe decisions:** `UPDATE approval_requests SET state='APPROVED' WHERE id=:id AND state='PENDING' AND expires_at > now()`; exactly one row wins.
- **Expiry** and one-time decisions.
- **Audit design:** who, what, when, request ID, redacted metadata; append-only.
- **OAuth/OIDC principles** (for later replacement of the email/password login).
- **Irreversible-action gate** in the workflow engine.

Design patterns

Policy Enforcement Point, RBAC, Command (decision as an event), Append-only log, State pattern (approval states).

Why these decisions

Decision	Rejected	Why	Failure prevented
Conditional UPDATE for decisions	Read then write	Atomic, race-free	Two reviewers both "winning"
Recheck role at decision time	Trust the creation-time role	Roles change	Revoked users approving
Approval bound to run, step, version	Free-floating approvals	Stops reuse	Approving one thing and executing another
Append-only audit with redaction	Mutable logs	Evidence and privacy	Tampering, secret leakage

Build tasks

- [ ] `approval_requests` table; the approval step sets the run to `WAITING_APPROVAL` and schedules expiry
- [ ] `POST /v1/approvals/{id}/decisions` with role checks and `409` for already-decided
- [ ] Irreversible-tool gate requiring an approved request
- [ ] `audit_events` writer with request IDs and redaction
- [ ] Frontend: approval inbox, role-aware buttons, pending states

Acceptance

- Two simultaneous decisions → exactly one succeeds, the other gets `409`.
- A reviewer whose role was removed after the request is denied.
- An expired approval is rejected and the run follows the expiry policy.

Break-it labs

1. Approval race with two concurrent requests.
2. Cancel racing a step completion; define the monotonic result.

Sources

Source	Type	Status
OWASP API Security Top 10	Security reference	to read
FastAPI OAuth2/JWT tutorial	Official docs	to read (learning only; production uses OIDC)
Pang et al. 2019, Zanzibar	USENIX ATC	to read (concepts only, not implemented)
NIST AI Risk Management Framework	Government guidance	to read

How this makes you a better engineer

You practise authorization as a property of data and time, and learn to prove a race condition is fixed by a deterministic test.

Self-test

1. What proves a reviewer may approve now, given permissions changed?
2. Why a conditional UPDATE instead of read-then-write?
3. What goes in the audit log, and what must never?
4. How does expiry interact with cancellation?

Done when

- [ ] Race, expiry and RBAC tests deterministic and green.
- [ ] Audit events present for every decision.

Phase 7 Spec: Human Approvals, RBAC, and Audit Trail

Learning material: `flowforge.md` → Phase 7. Contracts: `spec/00-global.md` (§2 role matrix and `assigned_role` ordering; §3 tables `approval_requests`, `audit_events`; §4 state machines R4, R5, R8, R9; §5 `approval` step; §7 errors; §8 API surface). **Prerequisite:** Phase 6 done-when is green.

Scope

Migration `0006_approvals_audit` (`approval_requests`, `audit_events` + append-only DB trigger), worker execution of `approval` step (pauses run into `WAITING_APPROVAL`, creates pending approval request), race-safe approval decision endpoint (`POST /v1/approvals/{id}/decisions`) with decision-time role hierarchy verification (`reviewer < admin < owner`), sweeper expiration of stale approvals, runtime enforcement of approval before irreversible `http_request` execution, append-only `audit_events` recording and query API, and frontend Approval Inbox + Audit Log pages.

Steps

ID	Step	Done when
P7-S01	Revision `0006_approvals_audit` (`approval_requests`, `audit_events`, and `forbid_audit_mutation` trigger)	`alembic upgrade head && alembic downgrade -1 && alembic upgrade head` succeeds
P7-S02	`app/modules/audit/{models,schemas,repository,service,router}.py`: append-only `record_audit_event(...)` helper (redacts metadata, attaches `request_id`) and `GET /v1/organizations/{org_id}/audit-events`	unit + integration tests pass
P7-S03	Wire `record_audit_event` into auth (`user.signup`, `user.login`), org/member changes (`member.added`, `member.role_changed`), workflow publish (`workflow.published`), credentials (`credential.created`), and run lifecycle (`run.triggered`, `run.cancelled`, `run.retried`)	audit integration tests pass
P7-S04	`app/modules/approvals/{models,schemas,repository,service,router}.py`: list, get, and race-safe `decide_approval` (`approve` / `reject`)	integration + concurrency tests pass
P7-S05	Extend `app/workers/runner.py` for `approval` step (R4) and runtime irreversible-tool gate; extend `app/workers/sweeper.py` for expired approvals (R8) and `cancel` service for pending approvals (R9)	worker + sweeper approval tests pass
P7-S06	Export `openapi.json`, run `gen:api`, build frontend `ApprovalsPage`, `ApprovalBanner` on `RunDetailPage`, and `AuditEventsPage`	Vitest tests pass
P7-S07	Labs (concurrent approval race, cancel-vs-complete race, revoked role at decision time) + progress log	recorded in `docs/lab-notes/phase-07.md`

Files

```
alembic/versions/0006_approvals_audit.py
app/modules/audit/{__init__,models,schemas,repository,service,router}.py
app/modules/approvals/{__init__,models,schemas,repository,service,router}.py
app/workers/{runner,sweeper}.py                                  # modified
app/modules/{identity,organizations,workflows,integrations,executions}/service.py  # audit
hooks
tests/unit/test_approval_roles.py
tests/integration/{test_approvals,test_approval_races,test_audit_events}.py
frontend/src/features/{approvals/ApprovalsPage,audit/AuditEventsPage,runs/
ApprovalBanner}.tsx
docs/lab-notes/phase-07.md
```

Database & algorithm contracts

1. Audit Append-Only Trigger (`0006_approvals_audit.py`)

```
CREATE FUNCTION forbid_audit_mutation() RETURNS trigger AS $$
BEGIN
  RAISE EXCEPTION 'audit_events is append-only' USING ERRCODE = 'P0002';
END; $$ LANGUAGE plpgsql;
CREATE TRIGGER trg_audit_events_immutable BEFORE UPDATE OR DELETE ON audit_events
  FOR EACH ROW EXECUTE FUNCTION forbid_audit_mutation();
```

2. Worker `approval` Step Execution (`app/workers/runner.py`)

When `current_step_id` is an `approval` step: 1. Check if an `approval_requests` row for `(run_id, step_id)` already exists with `state = 'APPROVED'` and `version_id = run.version_id`: - If yes: record `step_attempts(SUCCEEDED)` with `output = {"decision": "approved", "decided_by": str(req.decided_by), "decided_at": req.decided_at.isoformat()}`, advance `current_step_id = step.next`, and continue the step loop. 2. Otherwise, in one transaction (fenced by `attempt_epoch`): - Render `summary` template via `template_engine` and pass through `redact()`. - `INSERT INTO approval_requests (org_id, run_id, step_id, version_id = run.version_id, assigned_role = step.config.assigned_role, state = 'PENDING', summary = redacted_summary, expires_at = now() + make_interval(secs => step.config.expires_in_seconds))`. - Transition run via R4: `sql UPDATE workflow_runs SET state = 'WAITING_APPROVAL', lease_owner = NULL, lease_expires_at = NULL, current_step_id = :step_id, updated_at = now() WHERE id = :run_id AND state = 'RUNNING' AND attempt_epoch = :epoch;` - Commit and exit worker cleanly.

3. Race-Safe Approval Decision (`POST /v1/approvals/{id}/decisions`)

1. Load `approval_requests` joined with caller's `memberships` on `org_id`. If no row → `404 NOT_FOUND`.
2. **Decision-time RBAC check:** - Caller's current role in `memberships` must have `approval.decide` (`reviewer`, `admin`, or `owner`) **and** must satisfy `ROLE_RANK[caller_role] >= ROLE_RANK[approval.assigned_role]` where `ROLE_RANK = {"viewer": 0, "operator": 1, "reviewer": 2, "admin": 3, "owner": 4}`. If not → `403 FORBIDDEN`.
3. **Atomic conditional UPDATE on `approval_requests`:** `sql UPDATE approval_requests SET state = :new_state, -- 'APPROVED' or 'REJECTED' decided_by = :user_id, decided_at =`

`now(), decision_comment = :comment WHERE id = :approval_id AND org_id = :org_id AND state = 'PENDING' AND expires_at > now() RETURNING run_id, step_id, version_id;` - If `rowcount == 0`: re-read the row. If `expires_at <= now()`, transition it to `EXPIRED` (if still `PENDING`), commit, and raise `409 INVALID_STATE_TRANSITION` (`detail="Approval request has expired"`). Otherwise (`state != 'PENDING'`), raise `409 INVALID_STATE_TRANSITION` (`detail="Approval request already decided"`).

4. **In the same transaction**, update `workflow_runs`: - If `APPROVED` (R5): `sql UPDATE workflow_runs SET state = 'QUEUED', next_attempt_at = now(), updated_at = now() WHERE id = :run_id AND version_id = :version_id AND state = 'WAITING_APPROVAL';` If `rowcount != 1` → raise `409 INVALID_STATE_TRANSITION` (rolls back the approval update too). Insert `outbox_events` (`event_type = 'RunResumeRequested'`, `payload = {"run_id": str(run_id), "org_id": str(org_id)}`). - If `REJECTED` (R8): `sql UPDATE workflow_runs SET state = 'FAILED', error_code = 'APPROVAL_REJECTED', error_detail = 'Rejected by reviewer', finished_at = now(), updated_at = now() WHERE id = :run_id AND state = 'WAITING_APPROVAL';` - Insert `audit_events` (`action = "approval.approved"` or `"approval.rejected"`, `target_type = "approval_request"`, `target_id = approval_id`, `redacted_metadata = {"run_id": str(run_id), "step_id": step_id, "comment": comment}`). - Commit.

4. Approval Expiry in Sweeper (`app/workers/sweeper.py`)

Every sweep cycle: 1. Select up to 100 rows `SELECT id, org_id, run_id FROM approval_requests WHERE state = 'PENDING' AND expires_at <= now() FOR UPDATE SKIP LOCKED`. 2. For each: update `approval_requests SET state = 'EXPIRED'`, update `workflow_runs SET state = 'FAILED', error_code = 'APPROVAL_EXPIRED', finished_at = now() WHERE id = :run_id AND state = 'WAITING_APPROVAL'`, and write an `audit_events` row (`actor_type = 'system'`, `action = 'approval.expired'`).

5. Runtime Irreversible-Tool Gate (`app/workers/runner.py`)

Before executing an `http_request` step where `effect == "write"` and the credential has `"irreversible"` in `permission_scopes`: - Query `approval_requests` for this `run_id` and `version_id` with `state = 'APPROVED'` whose `step_id` is in $\text{Dom}(\text{current_step_id})$. If none exists, fail the run immediately (`error_code = 'FORBIDDEN_TOOL_PERMISSION'`, `retryable = False`).

API contracts

Endpoint	Request	Success	Errors
`GET /v1/organizations/{org_id}/approvals`	`limit`, `cursor`, `state` (optional: `PENDING`, `APPROVED`, `REJECTED`, `EXPIRED`, `CANCELLED`)	`200` page of `ApprovalOut`	404; 400
`GET /v1/approvals/{id}`	—	`200` `ApprovalOut`	404
`POST /v1/approvals/{id}/decisions`	`{"decision": "approve"|"reject", "comment"?: str(≤1000)}`	`200` `ApprovalOut`	404; 403 (`FORBIDDEN`); 409 `INVALID_STATE_TRANSITION`; 422
`GET /v1/organizations/`	`limit`, `cursor`, `action` (optional)	`200` page of `AuditEventOut`	404; 403 (`owner`/`admin` only)

Endpoint	Request	Success	Errors
`{org_id}/audit-events`			

`ApprovalOut`:
`{"id","org_id","run_id","step_id","version_id","assigned_role","state","summary","expires_at","decided_by`
`AuditEventOut`:
`{"id","org_id","actor_user_id","actor_type","action","target_type","target_id","request_id","redacted_met`

Test cases

ID	File	Given / When / Then
P7-T01	test_approval_roles	`reviewer` can decide `assigned_role="reviewer"`, denied (`403`) on `"admin"` or `"owner"`; `operator` and `viewer` denied (`403`) on all approvals; `admin` can decide `"reviewer"` and `"admin"`, denied on `"owner"`
P7-T02	test_approvals	Support-ticket workflow pauses at `approve` step: run state is `WAITING_APPROVAL`, lease is cleared (`lease_owner IS NULL`), and `approval_requests(PENDING)` is created with redacted summary
P7-T03	test_approvals	Approving (`decision="approve"`) transitions approval to `APPROVED`, transitions run to `QUEUED`, emits `RunResumeRequested`, worker executes downstream `crm` HTTP step and finishes `SUCCEEDED`
P7-T04	test_approvals	Rejecting (`decision="reject"`) transitions approval to `REJECTED` and run to `FAILED` (`error_code="APPROVAL_REJECTED"`); downstream `crm` HTTP step is **never** called
P7-T05	test_approval_races	**Approval race:** two reviewers concurrently POST decisions (`approve` and `reject`) to the same pending approval → `asyncio.gather` returns one `200` and one `409 INVALID_STATE_TRANSITION`; DB has a single winner
P7-T06	test_approval_races	**Permission revocation before decision:** user has `reviewer` role when approval is created, is demoted to `viewer` before deciding → `POST /decisions` returns `403 FORBIDDEN`
P7-T07	test_approvals	Expired approval (`expires_at <= now()`): `POST /decisions` returns `409 INVALID_STATE_TRANSITION`; sweeper marks approval `EXPIRED` and run `FAILED` (`APPROVAL_EXPIRED`)
P7-T08	test_approval_races	**Cancel vs approval:** cancelling a `WAITING_APPROVAL` run marks both the run and the pending `approval_requests` row `CANCELLED`; subsequent `POST /decisions` returns `409`
P7-T09	test_audit_events	Every mutating action writes an `audit_events` row with `request_id` and redacted metadata; `UPDATE` or `DELETE` on `audit_events` fails in PostgreSQL with `P0002`
P7-T10	test_audit_events	`GET /v1/organizations/{org_id}/audit-events` returns `200` for `owner`/`admin`, `403` for `operator`/`reviewer`/`viewer`, `404` for non-member

Frontend

- `ApprovalsPage` (`/orgs/:orgId/approvals`): filterable by state (default `PENDING`), shows `summary`, `assigned_role`, `expires_at` countdown, and "Approve" / "Reject" buttons (disabled with explanation if user's role rank is below `assigned_role`).

- `ApprovalBanner` on `RunDetailPage`: when `run.state === "WAITING_APPROVAL"`, displays the pending approval card inline with Approve/Reject actions.
- `AuditEventsPage` (`/orgs/:orgId/audit`): visible to `owner`/`admin`, paginated table of audit events.
- Frontend tests: `P7-F01` renders pending approvals and disables Approve/Reject for insufficient role; `P7-F02` submitting decision updates status and handles 409 conflict; `P7-F03` `ApprovalBanner` appears on `WAITING_APPROVAL` run.

Labs (`docs/lab-notes/phase-07.md`)

1. **Simultaneous reviewer race:** fire 10 concurrent decision requests against one approval ID; confirm 1 succeeds (`200`) and 9 return `409`.
2. **Cancel vs step completion race:** trigger `POST /v1/runs/{id}/cancel` while a step is in flight; confirm monotonic terminal state and accurate `tool_effects` + `audit_events` records.

Verification commands

```
docker compose up -d postgres rabbitmq
alembic upgrade head
ruff check . && ruff format --check . && mypy app && pytest -q
python scripts/export_openapi.py && git diff --exit-code openapi.json
cd frontend && npm run gen:api && npm run lint && npm run typecheck && npm test && npm run
build
```

Done when

- [ ] P7-T01…T10 and P7-F01…F03 pass.
- [ ] Labs 1–2 recorded; Phase 7 PDF built.

Agent brief

Do: evaluate role permissions against the live `memberships` row inside the decision transaction. **Don't:** allow updating or deleting `audit_events` rows from application code. **Stop and report** if any mutating endpoint from Phases 2–7 is missing an `audit_events` entry.

Shared: Glossary

Term	Meaning
Organization (tenant)	Owner of workflows, credentials, runs and budgets
WorkflowVersion	Immutable published definition; edits create a new version
Run / StepAttempt	One execution of a pinned version / one try of a step
Idempotency key	Token ensuring a repeated request has one effect
Outbox	Events written in the same transaction as state, published later
Lease / heartbeat	Time-limited claim on a run, renewed while alive
At-least-once delivery	A message may arrive more than once, so consumers are idempotent
Tool effect	An external side effect recorded in a ledger
Approval	Human decision bound to run, step, version, actor and time window
Invariant	A rule that must always hold
ADR	Architecture Decision Record
SLI / SLO	Measured indicator / target for it
Problem Details	RFC 9457 standard error body
SSRF	Server-side request forgery
MVCC	Multi-version concurrency control

Shared: Release gates

Gate	Pass evidence
G1 Specification	PRD + tests define allowed and forbidden behaviour
G2 Data correctness	Tests fail on invalid transitions and races
G3 Security	Cross-tenant, unauthenticated and replay attacks denied
G4 Recovery	Kill worker/provider gives a correct outcome or a declared limit
G5 Operations	Traces, dashboards, restore and rollback documented
G6 Communication	ADRs show alternatives, assumptions, costs, evidence

Shared: Progress log

Phase	Started	Finished	Notes / surprises
1	2026-10-25	2026-10-25	Fast skeleton bootstrap; doc check rules and ReportLab PDF toolchain operational.
2	2026-10-25	2026-10-25	Asyncpg connection pool requires NullPool in per-test event loops; SELECT FOR UPDATE required for last-owner safety; Keyset pagination benchmarks 33% faster with 58% lower cost than offset.
3	2026-10-25	2026-10-25	Strict dominators prevent undefined variable races in diamond graphs; 500 Hypothesis property tests verify acyclic invariants; DB trigger enforces published immutability.
4	2026-10-25	2026-10-25	Transactional outbox with SKIP LOCKED solves dual-write race; lease + fencing tokens (attempt_epoch) prevent zombie worker commit; asyncpg interval encoding requires datetime.timedelta.
5	2026-10-25	2026-10-25	Tool-effects ledger INTENDED/COMMITTED/AMBIGUOUS stops duplicate external side effects; bounded exponential backoff with full jitter & Retry-After; recovery sweeper rescues stale leases; cancel/retry state machine (R9-R11) verified.
6			
7			
8			
9			
10			

FlowForge Global Specification (v1, MVP scope)

Binding contract for every phase. If a phase spec and this file disagree, **this file wins**; fix the phase spec. Scope is MVP/P0 only. P1/P2 items are in the backlog at the end.

Related: flowforge.md (learning plan) and the per-phase specs `spec/phase-NN.md`.

1. Conventions

Topic	Rule
IDs	UUIDv7 (time-ordered), generated in the app with the standard library `uuid.uuid7()` (present in Python 3.14, confirmed on this machine), stored as PostgreSQL `uuid`, serialized as lowercase hyphenated strings
Time	`timestamptz`, always UTC. JSON uses ISO 8601 with `Z`. Durations are integers in seconds or milliseconds, with the unit in the field name (`timeout_seconds`, `duration_ms`)
Money	Integer **micro-USD** (1 USD = 1,000,000). Column suffix `_micro_usd`. No floats
JSON	`snake_case` keys. Unknown request fields are rejected (`extra="forbid"`)
Versioning	URL prefix `/v1`. Additive changes only within v1
Request ID	Client may send `X-Request-ID` (must match `^[A-Za-z0-9._-]{8,64}$`), otherwise generated (UUIDv7). Always echoed in the response header and in error bodies
Auth header	`Authorization: Bearer <access_token>`
Idempotency	`Idempotency-Key` header, `^[A-Za-z0-9._:-]{8,128}$`, supported on `POST /v1/workflows/{id}/runs`
Pagination	Cursor based. Query: `limit` (default 25, max 100), `cursor` (opaque base64url). Response envelope: `{"items": [...], "next_cursor": "..."|null}`. Sort: `created_at DESC, id DESC` unless stated
Errors	`application/problem+json` (RFC 9457) with extra members `code` and `request_id`. Never include stack traces or SQL
Tenancy	Every tenant table has `org_id`. Foreign-tenant objects return `404 NOT_FOUND`, never `403`
Deletes	No hard deletes of business data in MVP. Workflows use `archived_at`

Problem Details body

```
{
  "type": "https://flowforge.dev/errors/VALIDATION_ERROR",
  "title": "Validation error",
  "status": 422,
  "detail": "Request body failed validation.",
  "instance": "/v1/organizations/…/workflows",
  "code": "VALIDATION_ERROR",
  "request_id": "0192…",
  "errors": [{"field": "display_name", "message": "String should have at least 1
```

```
character"}]
}
```

`errors` is present only for validation errors. `type` is `https://flowforge.dev/errors/<CODE>` (not required to resolve).

2. Roles and permission matrix

Roles: `owner`, `admin`, `operator`, `reviewer`, `viewer`. A user has one role per organization.

Action	owner	admin	operator	reviewer	viewer
`org.manage` (rename, budgets, limits)	✔	✔			
`member.manage` (add, change role)	✔	✔ (cannot grant or change `owner`)			
`credential.manage`	✔	✔			
`workflow.write` (create, version, trigger config)	✔	✔			
`workflow.publish`	✔	✔			
`workflow.read`	✔	✔	✔	✔	✔
`run.trigger`	✔	✔	✔		
`run.cancel`, `run.retry`	✔	✔	✔		
`run.read`	✔	✔	✔	✔	✔
`approval.read`	✔	✔	✔	✔	✔
`approval.decide` (and role ≥ the request's `assigned_role`)	✔	✔		✔	
`usage.read`	✔	✔	✔		✔
`audit.read`	✔	✔			

Approval role ordering for `assigned_role`: `reviewer < admin < owner`. A decider needs an allowed action **and** a role at or above `assigned_role`. Permissions are re-evaluated at decision time.

3. Data dictionary

All tables: `id uuid PRIMARY KEY` (UUIDv7, app-generated) unless noted. `created_at timestamptz NOT NULL DEFAULT now()` on every table. `updated_at timestamptz NOT NULL DEFAULT now()` where marked (set by the application on update). Phase = the phase whose migration creates the table.

users (phase 2)

Column	Type	Constraints
email	text	NOT NULL; stored lowercased; unique index on `email`
password_hash	text	NOT NULL (argon2id)
display_name	text	NOT NULL, 1–80 chars

Column	Type	Constraints
is_active	boolean	NOT NULL DEFAULT true
updated_at	timestamptz	

refresh_tokens (phase 2)

Column	Type	Constraints
user_id	uuid	FK users, NOT NULL
token_hash	text	NOT NULL UNIQUE (SHA-256 of the token)
expires_at	timestamptz	NOT NULL
revoked_at	timestamptz	NULL
replaced_by	uuid	NULL (rotation chain)

organizations (phase 2)

Column	Type	Constraints
name	text	NOT NULL, 1–80
slug	text	NOT NULL UNIQUE, `^[a-z0-9][a-z0-9-]{2,39}$`
plan	text	NOT NULL DEFAULT 'free'
budget_limit_micro_usd	bigint	NOT NULL DEFAULT 5000000, CHECK ≥ 0
max_concurrent_runs	int	NOT NULL DEFAULT 5, CHECK 1–100
updated_at	timestamptz	

memberships (phase 2)

Column	Type	Constraints
org_id	uuid	FK organizations, NOT NULL
user_id	uuid	FK users, NOT NULL
role	text	NOT NULL, CHECK in (`owner`,`admin`,`operator`,`reviewer`,`viewer`)
Unique `(org_id, user_id)`. Index `(user_id)`. An org must always have at least one `owner` (enforced in the application, tested).		

workflows (phase 2)

Column	Type	Constraints
org_id	uuid	FK, NOT NULL
display_name	text	NOT NULL, 1–120
description	text	NULL, ≤ 1000
current_version_id	uuid	

Column	Type	Constraints
		NULL, FK workflow_versions (DEFERRABLE INITIALLY DEFERRED); the latest **published** version
archived_at	timestamptz	NULL
created_by	uuid	FK users
updated_at	timestamptz	
Index `(org_id, created_at DESC, id DESC)`.		

workflow_versions (phase 2 table, phase 3 behaviour)

Column	Type	Constraints
workflow_id	uuid	FK, NOT NULL
org_id	uuid	NOT NULL (denormalised for tenant filtering)
version	int	NOT NULL, ≥ 1
status	text	NOT NULL, CHECK in (`draft`, `published`)
definition_json	jsonb	NOT NULL
schema_version	int	NOT NULL (definition format version, currently 1)
checksum	text	NULL until published; SHA-256 hex of canonical JSON
created_by	uuid	FK users
published_at	timestamptz	NULL
Unique `(workflow_id, version)`. CHECK: `status='published'` ⇒ `checksum IS NOT NULL AND published_at IS NOT NULL`. A trigger `forbid_published_version_update` raises on any UPDATE or DELETE of a row whose OLD.status is `published` (immutability enforced by the database). Only one draft per workflow at a time: partial unique index `(workflow_id) WHERE status='draft'`.		

triggers (phase 4 for manual metadata, phase 9 for webhook)

Column	Type	Constraints
org_id	uuid	FK, NOT NULL
workflow_id	uuid	FK, NOT NULL
kind	text	CHECK in (`webhook`) (manual runs have no trigger row)
credential_id	uuid	FK integration_credentials, NOT NULL (holds the HMAC secret)
enabled	boolean	NOT NULL DEFAULT true
updated_at	timestamptz	

integration_credentials (phase 5 table, phase 9 encryption)

Column	Type	Constraints
org_id	uuid	FK, NOT NULL
provider	text	NOT NULL, `^[a-z0-9_-]{2,40}$`
name	text	NOT NULL, unique `(org_id, name)`
encrypted_secret	bytea	NOT NULL (AES-256-GCM, nonce prepended)
key_id	text	NOT NULL (which master key encrypted it)
allowed_hosts	text[]	NOT NULL DEFAULT '{}' (exact hostnames)
permission_scopes	text[]	NOT NULL DEFAULT '{}'
rotated_at	timestamptz	NULL
Secrets are write-only through the API: never returned after creation.		

workflow_runs (phase 4)

Column	Type	Constraints
org_id	uuid	FK, NOT NULL
workflow_id	uuid	FK, NOT NULL
version_id	uuid	FK workflow_versions, NOT NULL (pinned)
state	text	NOT NULL, CHECK in (`QUEUED`,`RUNNING`,`WAITING_APPROVAL`,`SUCCEEDED`,`FAILED`,`CANCELLED`)
trigger_kind	text	NOT NULL, CHECK in (`manual`,`webhook`)
trigger_id	uuid	NULL, FK triggers
idempotency_key	text	NULL
request_fingerprint	text	NULL (SHA-256 of canonical request body, to detect key reuse with a different body)
inputs	jsonb	NOT NULL DEFAULT '{}'
context	jsonb	NOT NULL DEFAULT '{}' (map `step_id → output`)
outputs	jsonb	NULL (output of the last step on success)
current_step_id	text	NULL
error_code	text	NULL
error_detail	text	NULL (safe, redacted)
cancel_requested	boolean	NOT NULL DEFAULT false
lease_owner	text	NULL (worker id)
lease_expires_at	timestamptz	NULL
heartbeat_at	timestamptz	NULL
next_attempt_at	timestamptz	NULL

Column	Type	Constraints
attempt_epoch	int	NOT NULL DEFAULT 0 (incremented on each claim; a fencing token)
created_by	uuid	NULL, FK users
started_at, finished_at	timestamptz	NULL
updated_at	timestamptz	
Constraints: partial unique `(org_id, idempotency_key) WHERE idempotency_key IS NOT NULL`. Indexes: `(org_id, created_at DESC, id DESC)`; `(state, next_attempt_at)`; `(org_id, state)`; `(lease_expires_at) WHERE state='RUNNING'`.		

step_attempts (phase 4)

Column	Type	Constraints
run_id	uuid	FK, NOT NULL
org_id	uuid	NOT NULL
step_id	text	NOT NULL
step_type	text	NOT NULL
attempt_no	int	NOT NULL, ≥ 1
status	text	NOT NULL, CHECK in (`RUNNING`, `SUCCEEDED`, `FAILED`)
input	jsonb	NULL (redacted, ≤ 64 KB)
output	jsonb	NULL (redacted, ≤ 64 KB)
error_code	text	NULL
error_detail	text	NULL
retryable	boolean	NULL
epoch	int	NOT NULL (run `attempt_epoch` at start)
started_at	timestamptz	NOT NULL
ended_at	timestamptz	NULL
duration_ms	int	NULL
Unique `(run_id, step_id, attempt_no)`. Index `(run_id, started_at)`.		

approval_requests (phase 7)

Column	Type	Constraints
org_id	uuid	NOT NULL
run_id	uuid	FK, NOT NULL
step_id	text	NOT NULL
version_id	uuid	FK, NOT NULL (bound version)
assigned_role	text	NOT NULL, CHECK in (`reviewer`,`admin`,`owner`)
state	text	NOT NULL, CHECK in (`PENDING`,`APPROVED`,`REJECTED`,`EXPIRED`,`CANCELLED`)
summary	jsonb	NOT NULL (what the reviewer sees; redacted)
expires_at	timestamptz	NOT NULL
decided_by	uuid	NULL, FK users
decided_at	timestamptz	NULL
decision_comment	text	NULL, ≤ 1000
Partial unique `(run_id, step_id) WHERE state='PENDING'`. Index `(org_id, state, expires_at)`. CHECK: state in (APPROVED, REJECTED) ⇒ `decided_by` and `decided_at` NOT NULL.		

tool_effects (phase 5)

Column	Type	Constraints
org_id	uuid	NOT NULL
run_id	uuid	FK, NOT NULL
step_id	text	NOT NULL
provider	text	NOT NULL (credential provider name or host)
idempotency_key	text	NOT NULL (`{run_id}:{step_id}`)
state	text	NOT NULL, CHECK in (`INTENDED`,`COMMITTED`,`FAILED`,`AMBIGUOUS`)
request_hash	text	NOT NULL
external_ref	text	NULL
response_summary	jsonb	NULL
updated_at	timestamptz	
Unique `(provider, idempotency_key)`.		

outbox_events (phase 4)

Column	Type	Constraints
aggregate_type	text	NOT NULL (`run`)
aggregate_id	uuid	NOT NULL
event_type	text	NOT NULL, CHECK in (`RunRequested`,`RunResumeRequested`,`RunCancelRequested`)
schema_version	int	NOT NULL DEFAULT 1
payload	jsonb	NOT NULL
published_at	timestamptz	NULL
publish_attempts	int	NOT NULL DEFAULT 0
next_publish_at	timestamptz	NOT NULL DEFAULT now()
Partial index `(next_publish_at) WHERE published_at IS NULL`.		

usage_records (phase 6)

Column	Type	Constraints
org_id	uuid	NOT NULL
run_id	uuid	FK, NOT NULL
step_id	text	NOT NULL
attempt_id	uuid	FK step_attempts
provider	text	NOT NULL (`openrouter`, `fake`)
model_name	text	NOT NULL
prompt_tokens, completion_tokens, total_tokens	int	NOT NULL ≥ 0
estimated_cost_micro_usd	bigint	NOT NULL ≥ 0 (tokens × configured price; used for budgets)
billed_cost_micro_usd	bigint	NOT NULL DEFAULT 0 (free models: 0)
latency_ms	int	NOT NULL
prompt_template_id, prompt_template_version	text, int	NOT NULL
outcome	text	NOT NULL, CHECK in (`ok`,`invalid_output`,`provider_error`,`rate_limited`)
Index `(org_id, created_at DESC)`.		

budget_reservations (phase 9; the table is created in phase 9, phase 6 uses only usage_records)

Column	Type	Constraints
org_id	uuid	NOT NULL
run_id	uuid	NOT NULL
step_id	text	NOT NULL
reserved_micro_usd	bigint	NOT NULL ≥ 0
settled_micro_usd	bigint	NULL
state	text	CHECK in (`RESERVED`,`SETTLED`,`RELEASED`)
settled_at	timestamptz	NULL
Unique `(run_id, step_id)`.		

audit_events (phase 7)

Column	Type	Constraints
org_id	uuid	NULL (auth events have none)
actor_user_id	uuid	NULL
actor_type	text	NOT NULL, CHECK in (`user`,`system`,`webhook`)
action	text	NOT NULL (e.g. `approval.decided`)
target_type	text	NOT NULL
target_id	uuid	NULL
request_id	text	NULL
redacted_metadata	jsonb	NOT NULL DEFAULT '{}'
Append-only: a trigger raises on UPDATE and DELETE. Index `(org_id, created_at DESC)`.		

Migration order (Alembic revision names)

1. `0001_identity_orgs` : users, refresh_tokens, organizations, memberships
2. `0002_workflows` : workflows, workflow_versions (+ immutability trigger)
3. `0003_runs_outbox` : workflow_runs, step_attempts, outbox_events
4. `0004_tools_credentials` : integration_credentials, tool_effects
5. `0005_usage` : usage_records
6. `0006_approvals_audit` : approval_requests, audit_events (+ append-only trigger)
7. `0007_triggers_budgets` : triggers, budget_reservations

`triggers` references `workflow_runs.trigger_id`. **Rule:** migration `0003` creates `workflow_runs.trigger_id uuid NULL` with no FK; migration `0007` creates `triggers` and then adds the FK.

4. State machines

Run (`workflow_runs.state`)

#	From	Event	To	Actor	Guard	DB update (single
R1	—	create	QUEUED	API	caller has `run.trigger`; org under concurrency cap; version published	INSERT run + INSER transaction
R2	QUEUED	claim	RUNNING	worker	`next_attempt_at <= now()` or NULL	`UPDATE … SET sta lease_expires_at= attempt_epoch=att started_at=COALES id=:id AND state=`
R3	RUNNING	reclaim	RUNNING	worker	`lease_expires_at < now()`	same as R2 but `WHE AND lease_expires`
R4	RUNNING	needs approval	WAITING_APPROVAL	worker	epoch matches	`UPDATE … SET sta lease_owner=NULL, current_step_id= state='RUNNING' A`
R5	WAITING_APPROVAL	approved	QUEUED	API (decision)	approval decided APPROVED in the same transaction	`UPDATE … SET sta next_attempt_at=n state='WAITING_AP`
R6	RUNNING	all steps done	SUCCEEDED	worker	epoch matches; `cancel_requested=false`	`UPDATE … SET sta finished_at=now() AND state='RUNNIN`
R7	RUNNING	step failed finally	FAILED	worker	epoch matches	same shape, with `e`
R8	WAITING_APPROVAL	rejected / expired	FAILED	API / sweeper	approval REJECTED or EXPIRED	`UPDATE … SET sta error_code='APPRO WHERE id=:id AND`
R9	QUEUED, WAITING_APPROVAL	cancel	CANCELLED	API	`run.cancel`	`UPDATE … SET sta cancel_requested= id=:id AND state ('QUEUED','WAITIN`
R10	RUNNING	cancel requested	CANCELLED	worker (at next step boundary)	`cancel_requested=true`, epoch matches	`UPDATE … SET sta state='RUNNING' A`
R11	FAILED	retry (manual)	QUEUED	API	`run.retry`; error is not `CANCELLED`	`UPDATE … SET sta error_detail=NULL next_attempt_at=n state='FAILED'`

Terminal states: `SUCCEEDED`, `CANCELLED`. `FAILED` is terminal except for manual retry (R11). Any `UPDATE` with rowcount 0 means the guard failed → return `409 INVALID_STATE_TRANSITION` (API) or abandon the work (worker).

Cancel vs complete race. R6 and R10 and R9 all carry state guards. Whichever commits first wins; the loser sees rowcount 0. A provider effect that already committed cannot be undone; the run still ends CANCELLED and the `tool_effects` ledger shows the effect.

Step attempt (`step_attempts.status`)

`RUNNING → SUCCEEDED | FAILED`. A retry is a **new row** with `attempt_no+1`. Rows are never mutated after `ended_at` is set.

Approval (`approval_requests.state`)

From	Event	To	Guarded statement
PENDING	approve	APPROVED	`UPDATE … SET state='APPROVED', decided_by=:u, decided_at=now() WHERE id=:id AND state='PENDING' AND expires_at > now()`
PENDING	reject	REJECTED	same, with `'REJECTED'`
PENDING	expire	EXPIRED	`UPDATE … SET state='EXPIRED' WHERE id=:id AND state='PENDING' AND expires_at <= now()` (sweeper)
PENDING	run cancelled	CANCELLED	in the cancel transaction

Outbox (`published_at`)

`unpublished (published_at IS NULL) → published`. The publisher selects `WHERE published_at IS NULL AND next_publish_at <= now() ORDER BY id LIMIT 100 FOR UPDATE SKIP LOCKED`, publishes with confirm, then sets `published_at=now()`. On failure: `publish_attempts+1`, `next_publish_at = now() + backoff`.

5. Workflow definition format (schema_version 1)

```
{
  "schema_version": 1,
  "name": "Support ticket triage",
  "inputs_schema": {
    "type": "object",
    "required": ["ticket_id", "body"],
    "properties": {"ticket_id": {"type": "string"}, "body": {"type": "string", "maxLength":
4000}},
    "additionalProperties": false
  },
  "start": "classify",
  "steps": [
    {"id": "classify", "type": "llm_classify",
     "config": {"prompt_template_id": "ticket_classify", "input": "{{ inputs.body }}",
                "labels": ["billing", "bug", "other"], "max_tokens": 100},
     "next": "route"},
    {"id": "route", "type": "condition",
     "config": {"branches": [{"when": {"op": "eq", "left":
"{{ steps.classify.output.label }}", "right": "billing"}, "next": "approve"}],
                "else": "done"}},
    {"id": "approve", "type": "approval",
```

```
     "config": {"assigned_role": "reviewer", "expires_in_seconds": 86400,
                "summary": "Create CRM ticket for {{ inputs.ticket_id }}"},
     "next": "crm"},
    {"id": "crm", "type": "http_request",
     "config": {"credential_id": "…uuid…", "method": "POST", "url": "https://
crm.example.com/tickets",
                "headers": {"Content-Type": "application/json"},
                "body": {"ticket_id": "{{ inputs.ticket_id }}"}, "timeout_seconds": 10,
                "effect": "write", "max_attempts": 3},
     "next": "done"},
    {"id": "done", "type": "set_data", "config": {"values": {"status": "complete"}},
"next": null}
  ]
}
```

Rules - `id`: `^[a-z][a-z0-9_]{0,39}$`, unique. Max 50 steps. `start` must name a step. - Every step except `condition` has `next` (a step id or `null` = end of the workflow). `condition` has `config.branches` (1–5 entries, each `{when, next}`) and `config.else` (step id or null). Branches are evaluated in order; first match wins; no match uses `else`. - Graph must be a DAG, every step reachable from `start`, every referenced step must exist. At least one terminating path. Cycles → `GRAPH_CYCLE`. - **Templating**: `{{ path }}` only. Allowed roots: `inputs.<field>` and `steps.<step_id>.output.<field>`. Dotted paths and numeric indexes (`items.0.name`) only. No functions, no code. A string that is exactly one placeholder keeps the JSON type of the value; otherwise placeholders are string-interpolated. A template may reference only steps that are **ancestors** of the current step in the graph (validated at publish → `UNKNOWN_REFERENCE`). - Condition `when`: `{"op": "eq|neq|gt|gte|lt|lte|in|exists", "left": <template or literal>, "right": <template or literal>}` (`exists` has `left` only).

Step types and `config` (unknown config keys are rejected) | type | Required config | Optional config (default) | Output (`steps.<id>.output`) | |---|---|---|---| | `set_data` | `values` (object of templates) | — | the resolved `values` object | | `condition` | `branches`, `else` | — | `{"matched": <index or "else">}` | | `http_request` | `method` (GET, POST, PUT, PATCH, DELETE), `url` (https only) | `credential_id`, `headers` (`{}`; may not contain Authorization, Cookie, Proxy-Authorization, Host), `body` (null), `timeout_seconds` (10, 1–30), `effect` (`read`/`write`; default `read` for GET, else `write`), `max_attempts` (3, 1–5) | `{"status": int, "body": json|text (≤ 64 KB), "headers": {allowlisted}}` | | `llm_classify` | `prompt_template_id`, `input`, `labels` (2–20 strings) | `max_tokens` (100, 1–500) | `{"label": one of labels, "confidence": 0–1 or null}` | | `llm_transform` | `prompt_template_id`, `input`, `output_schema` (JSON Schema object, max 4 KB, depth ≤ 4) | `max_tokens` (400, 1–1500) | the validated object | | `approval` | `assigned_role` (reviewer, admin, owner), `summary` (template) | `expires_in_seconds` (86400, 60–604800) | `{"decision": "approved", "decided_by": uuid, "decided_at": iso}` (only reached if approved) |

`http_request` with `effect="write"` requires the **same run** to have passed through an `approval` step earlier in the graph, if the credential's `permission_scopes` contains `irreversible` (validated at publish → `APPROVAL_REQUIRED_FOR_IRREVERSIBLE`).

Prompt templates live in the repository as `app/ai/prompts/<id>.yaml` (`id`, `version`, `system`, `user` with `{{ input }}` and `{{ labels }}` placeholders). The workflow references them by id. Prompt text is never stored in the database or logs.

6. Execution algorithm (worker)

Defined precisely in `spec/phase-04.md` and `spec/phase-05.md`. Global parameters:

Parameter	Value
Lease duration	60 s
Heartbeat interval	15 s (extends `lease_expires_at` to `now()+60 s` only if `attempt_epoch` still matches)
Sweeper interval	30 s
Outbox publisher poll	1 s idle sleep, batch 100
Step max attempts	`config.max_attempts` (default 3)
Backoff	`delay = random(0, min(60, 2 * 2^(attempt_no-1)))` seconds (full jitter); `Retry-After` header wins if larger, capped at 120 s
Max steps executed per run	100 (guards against definition mistakes)
Max step output stored	64 KB (truncated with a marker `{"_truncated": true}`)
Default per-org concurrent runs	5; the cap counts runs in `QUEUED` or `RUNNING` (runs in `WAITING_APPROVAL` do not consume a slot)
Celery	`acks_late=True`, `reject_on_worker_lost=True`, `worker_prefetch_multiplier=1`, `task_acks_on_failure_or_timeout=False`

Resume rule. When a run is claimed, the worker rebuilds `context` from its `context` column and continues at `current_step_id` (or `start`). A step whose latest attempt is `SUCCEEDED` is not re-executed; its stored output is used.

Fencing. Every write the worker makes to `workflow_runs` or `step_attempts` includes `AND attempt_epoch = :epoch`. A worker that lost its lease gets rowcount 0 and must stop without further effects.

7. Error catalog

Code	HTTP	When
`VALIDATION_ERROR`	422	Request body, query or path failed validation
`BAD_REQUEST`	400	Malformed JSON, bad cursor, bad header format
`UNAUTHENTICATED`	401	Missing, malformed, expired or invalid access token
`INVALID_CREDENTIALS`	401	Wrong email or password (same message for both)
`FORBIDDEN`	403	Member of the org but lacks the permission
`NOT_FOUND`	404	Object missing **or** in another tenant; unknown route
`METHOD_NOT_ALLOWED`	405	Wrong HTTP method
`EMAIL_TAKEN`	409	Signup with an existing email
`CONFLICT`	409	Unique constraint conflict (slug, name, member exists)
`INVALID_STATE_TRANSITION`	409	State guard failed (cancel finished run, decide twice, …)

Code	HTTP	When
`IDEMPOTENCY_KEY_REUSED`	409	Same key, different body
`VERSION_NOT_PUBLISHED`	409	Run requested against a draft / archived workflow
`DRAFT_EXISTS`	409	Creating a draft when one exists
`LAST_OWNER`	409	Action would leave an org without an owner
`GRAPH_CYCLE`	422	Definition contains a cycle (`errors` lists the step ids)
`GRAPH_UNREACHABLE_STEP`	422	Step not reachable from `start`
`GRAPH_MISSING_STEP`	422	`next`/`start`/branch references an unknown step
`UNKNOWN_REFERENCE`	422	Template references a non-ancestor step or unknown input
`TYPE_MISMATCH`	422	Condition or mapping type clearly invalid
`INVALID_STEP_CONFIG`	422	Unknown key, out-of-range value, bad schema
`FORBIDDEN_TOOL_PERMISSION`	422	Step uses a host or credential not allowed
`APPROVAL_REQUIRED_FOR_IRREVERSIBLE`	422	See §5
`PAYLOAD_TOO_LARGE`	413	Body over `MAX_REQUEST_BYTES`
`RATE_LIMITED`	429	API rate limit hit (`Retry-After` header set)
`CONCURRENCY_LIMIT`	429	Org at `max_concurrent_runs`
`BUDGET_EXCEEDED`	402	Org budget exhausted (run request)
`INTERNAL_ERROR`	500	Unhandled error (generic message)
`SERVICE_UNAVAILABLE`	503	`/ready` fails, or the DB is unavailable
`WEBHOOK_SIGNATURE_INVALID`	401	Signature missing or wrong
`WEBHOOK_REPLAY`	401	Timestamp outside the window or signature reused

Run `error_code` values (stored on the run or attempt): `STEP_TIMEOUT`, `STEP_HTTP_ERROR`, `STEP_RETRIES_EXHAUSTED`, `TOOL_EFFECT_AMBIGUOUS`, `LLM_INVALID_OUTPUT`, `LLM_RATE_LIMITED`, `LLM_PROVIDER_ERROR`, `LLM_NON_FREE_MODEL`, `APPROVAL_REJECTED`, `APPROVAL_EXPIRED`, `MAX_STEPS_EXCEEDED`, `BUDGET_EXCEEDED`, `EGRESS_BLOCKED`, `INTERNAL_ERROR`.

8. API surface (all paths under `/v1`)

Unless stated: `Authorization` required; responses are JSON; errors per §7. `{org_id}` routes check membership first. Phase = when the endpoint is implemented. Full request/response schemas are in the phase specs.

Phase	Method and path	Permission	Success
1	`GET /health` (no `/v1`, no auth)	public	200
1	`GET /ready` (no `/v1`, no auth)	public	200 / 503
2	`POST /v1/auth/signup`	public	201
2	`POST /v1/auth/login`	public	200
2	`POST /v1/auth/refresh`	refresh token	200
2	`POST /v1/auth/logout`	refresh token	204

Phase	Method and path	Permission	Success
2	`GET /v1/me`	any user	200
2	`POST /v1/organizations`	any user	201
2	`GET /v1/organizations`	any user	200 (mine)
2	`GET /v1/organizations/{org_id}`	member	200
2	`GET /v1/organizations/{org_id}/members`	member	200
2	`POST /v1/organizations/{org_id}/members`	`member.manage`	201
2	`PATCH /v1/organizations/{org_id}/members/{user_id}`	`member.manage`	200
2	`POST /v1/organizations/{org_id}/workflows`	`workflow.write`	201
2	`GET /v1/organizations/{org_id}/workflows`	`workflow.read`	200
2	`GET /v1/workflows/{id}`	`workflow.read`	200
3	`POST /v1/workflows/{id}/versions`	`workflow.write`	201 (draft)
3	`PUT /v1/workflows/{id}/versions/{n}` (drafts only)	`workflow.write`	200
3	`GET /v1/workflows/{id}/versions` / `…/{n}`	`workflow.read`	200
3	`POST /v1/workflows/{id}/validate`	`workflow.write`	200
3	`POST /v1/workflows/{id}/publish`	`workflow.publish`	200
4	`POST /v1/workflows/{id}/runs`	`run.trigger`	**202**
4	`GET /v1/organizations/{org_id}/runs`	`run.read`	200
4	`GET /v1/runs/{id}`	`run.read`	200
4	`GET /v1/runs/{id}/steps`	`run.read`	200
5	`POST /v1/runs/{id}/cancel`	`run.cancel`	200
5	`POST /v1/runs/{id}/retry`	`run.retry`	202
5	`POST /v1/organizations/{org_id}/credentials`	`credential.manage`	201 (no secret returned)
5	`GET /v1/organizations/{org_id}/credentials`	`credential.manage`	200 (no secrets)
7	`GET /v1/organizations/{org_id}/approvals`	`approval.read`	200
7	`GET /v1/approvals/{id}`	`approval.read`	200
7	`POST /v1/approvals/{id}/decisions`	`approval.decide`	200
7	`GET /v1/organizations/{org_id}/audit-events`	`audit.read`	200
8	`GET /v1/organizations/{org_id}/usage?from=&to=`	`usage.read`	200
8	`GET /metrics` (no `/v1`; network-restricted)	internal	200
9	`POST /v1/workflows/{id}/triggers`	`workflow.write`	201
9	`POST /v1/triggers/webhooks/{trigger_id}`	HMAC signature	202

Deliberate deviation from the source roadmap: the roadmap lists `GET /v1/usage`. This spec scopes it to `/v1/organizations/{org_id}/usage` so tenancy is explicit in the URL. The source's `POST /v1/organizations/{org_id}/workflows` is kept.

9. Configuration reference (environment variables)

Read through `app/core/config.py` (pydantic-settings). Names are exact. `.env.example` is committed with placeholders only.

Variable	Type	Default	Meaning
`APP_ENV`	`dev|test|prod`	`dev`	Enables strict `prod`
`LOG_LEVEL`	str	`INFO`	
`API_CORS_ORIGINS`	comma list	`http://localhost:5173`	Exact allowli
`MAX_REQUEST_BYTES`	int	`1048576`	Body size lim
`DATABASE_URL`	str	`postgresql+asyncpg://flowforge:flowforge@localhost:5432/flowforge`	
`DB_POOL_SIZE` / `DB_MAX_OVERFLOW`	int	`10` / `10`	
`TEST_DATABASE_URL`	str	same server, db `flowforge_test`	Integration t
`JWT_SECRET`	str (≥ 32 chars)	none (required)	HS256 signi
`JWT_ISSUER` / `JWT_AUDIENCE`	str	`flowforge` / `flowforge-api`	Verified on e
`ACCESS_TOKEN_TTL_SECONDS`	int	`900`	
`REFRESH_TOKEN_TTL_SECONDS`	int	`604800`	
`PASSWORD_MIN_LENGTH`	int	`12`	
`RABBITMQ_URL`	str	`amqp://flowforge:flowforge@localhost:5672//`	
`CELERY_TASK_QUEUE`	str	`runs.execute`	
`LEASE_SECONDS` / `HEARTBEAT_SECONDS` / `SWEEPER_INTERVAL_SECONDS`	int	`60` / `15` / `30`	
`EGRESS_ALLOWED_HOSTS`	comma list	empty	Hosts usable `http_reque` credential
`EGRESS_BLOCK_PRIVATE`	bool	`true`	Block private local, metad
`LLM_PROVIDER`	`fake|openrouter`	`fake`	
`OPENROUTER_API_KEY`	secret	empty	Never logge
`OPENROUTER_BASE_URL`	str	`https://openrouter.ai/api/v1`	
`LLM_MODEL`	str	`openrouter/free`	Must end wi equal `openr`
`LLM_FALLBACK_MODELS`	comma list	empty	Each must e
`LLM_TIMEOUT_SECONDS`	int	`30`	
`LLM_FREE_RPM` / `LLM_FREE_RPD`	int	`20` / `50`	Local limiter RPD after $1
`LLM_PRICE_PER_1K_TOKENS_MICRO_USD`	int	`2000`	Used for `estimated_` (budget dem

Variable	Type	Default	Meaning
`SECRETS_MASTER_KEYS`	`key_id:base64key` list	none (phase 9)	AES-256 key active one
`WEBHOOK_TIMESTAMP_TOLERANCE_SECONDS`	int	`300`	
`OTEL_EXPORTER_OTLP_ENDPOINT`	str	empty (disabled)	Phase 8
`OTEL_SERVICE_NAME`	str	per process	`flowforge-` `-scheduler`
`METRICS_ENABLED`	bool	`true`	

10. Security rules (exact)

- **Passwords:** min 12 chars, max 128, argon2id (library defaults), compared in constant time. Same `INVALID_CREDENTIALS` response for unknown email and wrong password.
- **Access token (JWT HS256):** claims `sub` (user id), `iat`, `exp`, `iss`, `aud`, `jti`. 15 min lifetime. Verified: signature, `exp`, `iss`, `aud`. **No org or role claim**: roles are read from the database on each request.
- **Refresh token:** 256-bit random, only its SHA-256 stored, rotation on each use (old marked `revoked_at`, `replaced_by` set); reuse of a revoked token revokes the whole chain.
- **Storage in the SPA:** access token in memory only; refresh token in an `HttpOnly; Secure; SameSite=Strict` cookie scoped to `/v1/auth` (set by the API).
- **Rate limits (phase 9):** login 10/min per IP+email, signup 5/hour per IP, other API 300/min per user. Over limit → `429 RATE_LIMITED` with `Retry-After`.
- **Egress blocklist** (checked on every resolved IP, including after redirects; redirects are **not followed** in MVP): `0.0.0.0/8`, `10.0.0.0/8`, `100.64.0.0/10`, `127.0.0.0/8`, `169.254.0.0/16`, `172.16.0.0/12`, `192.0.0.0/24`, `192.168.0.0/16`, `198.18.0.0/15`, `224.0.0.0/4`, `240.0.0.0/4`, `::1/128`, `fc00::/7`, `fe80::/10`, `::ffff:0:0/96` (IPv4-mapped). Only `https` URLs, ports 443 (and 8443), hostnames from the credential's `allowed_hosts` or `EGRESS_ALLOWED_HOSTS`. Connect to the validated IP while keeping the original `Host`/SNI.
- **Webhook signature:** header `X-FlowForge-Timestamp` (unix seconds) and `X-FlowForge-Signature: v1=<hex>` where hex = HMAC-SHA256(secret, `"{timestamp}.{raw_body}"`). Reject if the timestamp is outside ±300 s, if the signature mismatches (constant-time), or if `(trigger_id, signature)` was already used inside the window.
- **Redaction:** keys matching `(?i)(password|secret|token|authorization|api[_-]?key|cookie)` are replaced with `"***"` in logs, step inputs/outputs and audit metadata. Credentials are never passed to templates, prompts or models.
- **LLM:** model output is untrusted; validated against the step's schema; tool arguments come only from the workflow definition, never from model output.

11. Infrastructure reference

Docker Compose services (`compose.yaml`; dev ports on `127.0.0.1` only):

Service	Image / build	Port	Healthcheck	Phase
`postgres`	`postgres:<pinned>`	5432	`pg_isready -U flowforge`	2
`rabbitmq`	`rabbitmq:<pinned>-management`	5672, 15672		4

Service	Image / build	Port	Healthcheck	Phase
			`rabbitmq-diagnostics -q ping`	
`api`	build `infra/docker/api.Dockerfile`	8000	`GET /ready`	1
`worker`	same image, command `celery -A app.workers.celery_app worker`	—	`celery inspect ping`	4
`scheduler`	same image, command `python -m app.workers.scheduler` (outbox publisher + sweeper + approval expiry)	—	process alive + heartbeat file	4
`frontend`	build `frontend/Dockerfile` (prod) or Vite dev server on host	5173	HTTP 200	1
`otel-collector`, `jaeger`	pinned	4317, 16686	—	8
`prometheus`, `grafana`	pinned	9090, 3000	—	8

RabbitMQ topology (declared by the publisher/worker at start-up, idempotently): exchange `flowforge.runs` (direct, durable), queue `runs.execute` (durable, quorum, `x-dead-letter-exchange=flowforge.dlx`, `x-delivery-limit=5`), binding key `run.execute`; exchange `flowforge.dlx` (fanout) → queue `runs.dead`. Message body JSON: `{"event_id": uuid, "event_type": "...", "schema_version": 1, "run_id": uuid, "org_id": uuid, "trace_context": {...}}`, `delivery_mode=2`, `message_id=event_id`.

12. Dependency set

Latest versions found on 2026-10-25 with `pip index versions` and `npm view`. **Not yet confirmed to install together on Python 3.14.4.** Phase 1 task P1-S03 runs `pip-compile` and records any version that must be lowered. Pin the result in `requirements.txt` and `frontend/package-lock.json`; this table is the starting point, not the lock.

Runtime	Version on this machine
Python	3.14.4
Node / npm	24.21.0 / 11.19.0
Docker Compose	5.6.1

Backend (`requirements.in`) `fastapi==0.162.0`, `uvicorn[standard]==0.54.0`, `pydantic==2.14.1`, `pydantic-settings==2.16.1`, `email-validator==2.3.0`, `sqlalchemy[asyncio]==2.1.6`, `asyncpg==0.32.0`, `alembic==1.20.1`, `celery==5.6.3`, `kombu==5.6.2`, `httpx==0.28.1`, `pyjwt==2.15.1`, `argon2-cffi==25.1.0`, `cryptography==50.0.2`, `orjson==3.13.0`, `structlog==26.1.0`, `prometheus-client==0.26.0`, `opentelemetry-api==1.45.1`, `opentelemetry-sdk==1.45.1`, `jsonschema` (version to be looked up in P1-S03). **Dev** (`requirements-dev.in`): `pytest==9.1.1`, `pytest-asyncio==1.4.0`, `hypothesis==6.170.9`, `testcontainers==4.15.0`, `ruff==0.17.2`, `mypy==2.4.0`, `pip-tools==7.6.2`, `pre-commit`. **Frontend** (`frontend/package.json`): `react@19.3.1`, `react-dom`, `vite@8.3.5`, `typescript@7.0.2`, `@tanstack/react-query@5.104.5`, `react-router-dom@7.18.4`, `vitest@5.0.5`, `@playwright/test@1.64.1`, `openapi-typescript@7.13.0`, `eslint@10.13.0`. **Docker images:** tags for

PostgreSQL, RabbitMQ, Prometheus, Grafana, Jaeger and the OTel collector have **not** been looked up. P2-S01 and later phases pick current stable tags with `docker pull` and record the digests.

13. Backlog (explicitly NOT in this spec)

Cron triggers, templates, version rollback, fine-grained RBAC, SSE live updates, per-org fairness, budget alerting, searchable run history, dry-run replay, LangGraph sub-agent, MCP, RAG, provider failover, sagas, Temporal prototype, data residency, audit export, chaos/soak harness, visual node canvas.