

Frame 189: 655 bytes on wire (5240 bits), 655 bytes captured (5240 bits) on interface 0

Interface id: 0 (\Device\NPF_{21B75C48-4517-49BD-8920-7CE390BC5B90})

Interface name: \Device\NPF_{21B75C48-4517-49BD-8920-7CE390BC5B90}

Interface description: Wi-Fi

Encapsulation type: Ethernet (1)

Arrival Time: Oct 19, 2019 11:40:04.333220000 Фінляндія (літо)

[Time shift for this packet: 0.000000000 seconds]

Epoch Time: 1571474404.333220000 seconds

[Time delta from previous captured frame: 0.000183000 seconds]

[Time delta from previous displayed frame: 0.000000000 seconds]

[Time since reference or first frame: 22.726782000 seconds]

Frame Number: 189

Frame Length: 655 bytes (5240 bits)

Capture Length: 655 bytes (5240 bits)

[Frame is marked: False]

[Frame is ignored: False]

[Protocols in frame: eth:ethertype:ip:tcp:http]

[Coloring Rule Name: ____conversation_color_filter____06]

[Coloring Rule String: frame]

Ethernet II, Src: HonHaiPr_e6:be:99 (bc:85:56:e6:be:99), Dst: AsustekC_67:19:61 (00:18:f3:67:19:61)

Destination: AsustekC_67:19:61 (00:18:f3:67:19:61)

Address: AsustekC_67:19:61 (00:18:f3:67:19:61)

.... ..0. = LG bit: Globally unique address (factory default)

.... ..0 = IG bit: Individual address (unicast)

Source: HonHaiPr_e6:be:99 (bc:85:56:e6:be:99)

Address: HonHaiPr_e6:be:99 (bc:85:56:e6:be:99)

.... ..0. = LG bit: Globally unique address (factory default)

....0 = IG bit: Individual address (unicast)

Type: IPv4 (0x0800)

Internet Protocol Version 4, Src: 192.168.118.21, **Dst:** 128.119.245.12

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

0000 00.. = Differentiated Services Codepoint: Default (0)

.... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)

Total Length: 641

Identification: 0x2694 (9876)

Flags: 0x4000, Don't fragment

0... = Reserved bit: Not set

.1.. = Don't fragment: Set

..0. = More fragments: Not set

...0 0000 0000 0000 = Fragment offset: 0

Time to live: 128

Protocol: TCP (6)

Header checksum: 0x25a1 [validation disabled]

[Header checksum status: Unverified]

Source: 192.168.118.21

Destination: 128.119.245.12

Transmission Control Protocol, Src Port: 49408, **Dst Port:** 80, **Seq:** 1, **Ack:** 1, **Len:** 601

Source Port: 49408

Destination Port: 80

[Stream index: 4]

[TCP Segment Len: 601]

Sequence number: 1 (relative sequence number)

[Next sequence number: 602 (relative sequence number)]

0101 = Header Length: 20 bytes (5)

Flags: 0x018 (PSH, ACK)

000. = Reserved: Not set

...0 = Nonce: Not set

.... 0... = Congestion Window Reduced (CWR): Not set

.... .0.. = ECN-Echo: Not set

.... ..0. = Urgent: Not set

.... ...1 = Acknowledgment: Set

.... 1... = Push: Set

....0.. = Reset: Not set

....0. = Syn: Not set

....0 = Fin: Not set

[TCP Flags:AP...]

Window size value: 513

[Calculated window size: 131328]

[Window size scaling factor: 256]

Checksum: 0xc0da [unverified]

[Checksum Status: Unverified]

Urgent pointer: 0

[SEQ/ACK analysis]

[iRTT: 0.221972000 seconds]

[Bytes in flight: 601]

[Bytes sent since last PSH flag: 601]

[Timestamps]

[Time since first frame in this TCP stream: 0.222425000 seconds]

[Time since previous frame in this TCP stream: 0.000453000 seconds]

TCP payload (601 bytes)

Hypertext Transfer Protocol