

DIVINE: Analysis of C++ Programs

Vladimír Štill



Masaryk University
Brno, Czech Republic

22nd September 2017



- DIVINE is an analyser for C and C++ programs
- focus on language features
- built on top of the LLVM infrastructure
- tightly integrated compiler



waiting in journal review process:

- Petr Ročkai, Vladimír Štill, Ivana Černá, Jiří Barnat:
DiVM: Model Checking with LLVM and Graph Memory



waiting in journal review process:

- Petr Ročkai, Vladimír Štill, Ivana Černá, Jiří Barnat:
DiVM: Model Checking with LLVM and Graph Memory

freshly published:

- Vladimír Štill, Petr Ročkai, Jiří Barnat:
**Using Off-the-Shelf Exception Support Components in C++
Verification**



waiting in journal review process:

- Petr Ročkai, Vladimír Štill, Ivana Černá, Jiří Barnat:
DiVM: Model Checking with LLVM and Graph Memory

freshly published:

- Vladimír Štill, Petr Ročkai, Jiří Barnat:
Using Off-the-Shelf Exception Support Components in C++ Verification
- **Model Checking of C and C++ with DIVINE 4**



waiting in journal review process:

- Petr Ročkai, Vladimír Štill, Ivana Černá, Jiří Barnat:
DiVM: Model Checking with LLVM and Graph Memory

freshly published:

- Vladimír Štill, Petr Ročkai, Jiří Barnat:
Using Off-the-Shelf Exception Support Components in C++ Verification
- **Model Checking of C and C++ with DIVINE 4**
- Katarína Kejstová, Petr Ročkai, Jiří Barnat:
From Model Checking to Runtime Verification and Back



waiting in journal review process:

- Petr Ročkal, Vladimír Štill, Ivana Černá, Jiří Barnat:
DiVM: Model Checking with LLVM and Graph Memory

freshly published:

- Vladimír Štill, Petr Ročkal, Jiří Barnat:
Using Off-the-Shelf Exception Support Components in C++ Verification
- **Model Checking of C and C++ with DIVINE 4**
- Katarína Kejstová, Petr Ročkal, Jiří Barnat:
From Model Checking to Runtime Verification and Back

reworking:

- Petr Ročkal, Jiří Barnat: **A Simulator for LLVM Bitcode**



DIVINE Operating System (DiOS)

- modularized for more flexibility and configurability
- support for processes (`fork`)



DIVINE Operating System (DiOS)

- modularized for more flexibility and configurability
- support for processes (`fork`)

Symbolic Data

- symbolization of data structures
- multiple data domains in the same program
- refactoring and cleaning



DIVINE Operating System (DiOS)

- modularized for more flexibility and configurability
- support for processes (`fork`)

Symbolic Data

- symbolization of data structures
- multiple data domains in the same program
- refactoring and cleaning

Relaxed Memory Models

- resurrected and refactored implementation
- work on efficiency



Simulator

- multiple usability improvements



Simulator

- multiple usability improvements

Algorithms

- more robust counterexample format
- `divine run` can output stream of executed instructions



Simulator

- multiple usability improvements

Algorithms

- more robust counterexample format
- `divine run` can output stream of executed instructions

Core

- improved state space reduction



- **DiOS: A Lightweight Approach to Verifying POSIX-Based Programs**



- **DiOS: A Lightweight Approach to Verifying POSIX-Based Programs**
- **A Semi-Dynamic State Space Reduction for C/C++ Programs**



- **DiOS: A Lightweight Approach to Verifying POSIX-Based Programs**
- **A Semi-Dynamic State Space Reduction for C/C++ Programs**
- **Symbolic Computation via Program Transformations**



- **DiOS: A Lightweight Approach to Verifying POSIX-Based Programs**
- **A Semi-Dynamic State Space Reduction for C/C++ Programs**
- **Symbolic Computation via Program Transformations**
- **Verification of Concurrent C++ Programs with Realistic Memory Models**



- currently we can record and replay syscall interaction



- currently we can record and replay syscall interaction
- replay can explore further runs



- currently we can record and replay syscall interaction
- replay can explore further runs
- but syscall ordering has to match



- currently we can record and replay syscall interaction
- replay can explore further runs
- but syscall ordering has to match
- in future we want to allow reordering of independent syscalls



- currently we can record and replay syscall interaction
- replay can explore further runs
- but syscall ordering has to match
- in future we want to allow reordering of independent syscalls
- also possibility to replace replies of some syscalls with symbolic/nondeterministic values



What is relaxed memory model?

- describes how memory operations propagate between processors



What is relaxed memory model?

- describes how memory operations propagate between processors
- effects of cache, out-of-order execution



What is relaxed memory model?

- describes how memory operations propagate between processors
- effects of cache, out-of-order execution
- depends on architecture



What is relaxed memory model?

- describes how memory operations propagate between processors
- effects of cache, out-of-order execution
- depends on architecture
 - Intel x86: store buffering
 - ARM/POWER: almost arbitrary reordering of loads and stores



What is relaxed memory model?

- describes how memory operations propagate between processors
- effects of cache, out-of-order execution
- depends on architecture
 - Intel x86: store buffering
 - ARM/POWER: almost arbitrary reordering of loads and stores
- significantly increases theoretical complexity of verification



- rest of my PhD work
- thesis proposal submitted



- rest of my PhD work
- thesis proposal submitted
- focus on mitigation of state space explosion



- rest of my PhD work
- thesis proposal submitted
- focus on mitigation of state space explosion
 - a lot of equivalent interleavings with conventional methods
 - opportunity for static analysis, heuristics



- rest of my PhD work
- thesis proposal submitted
- focus on mitigation of state space explosion
 - a lot of equivalent interleavings with conventional methods
 - opportunity for static analysis, heuristics
- plans to support multiple memory models



- rest of my PhD work
- thesis proposal submitted
- focus on mitigation of state space explosion
 - a lot of equivalent interleavings with conventional methods
 - opportunity for static analysis, heuristics
- plans to support multiple memory models
- completeness of analysis



- program's behaviour can depend on input values



- program's behaviour can depend on input values
- need for verification under arbitrary inputs



- program's behaviour can depend on input values
- need for verification under arbitrary inputs
- cannot be handled explicitly: too many combinations



main idea: transform the program to encode symbolic/abstracted data

- Henrich's master's thesis, later PhD



main idea: transform the program to encode symbolic/abstracted data

- Henrich's master's thesis, later PhD
- framework for using different abstractions



main idea: transform the program to encode symbolic/abstracted data

- Henrich's master's thesis, later PhD
- framework for using different abstractions
- master's thesis in December
 - finalizing the initial implementation
 - testing and benchmarking
 - support for functions, data structures
 - but no dynamic memory and aliased pointers



main idea: transform the program to encode symbolic/abstracted data

- Henrich's master's thesis, later PhD
- framework for using different abstractions
- master's thesis in December
 - finalizing the initial implementation
 - testing and benchmarking
 - support for functions, data structures
 - but no dynamic memory and aliased pointers
- planned PhD work
 - full abstraction of programs with memory
 - symbolic memory
 - ...