RESEARCH PAPER

Ferry Capacity Utilization & Operational Efficiency Analytics System

Prepared by: Vincy Mehta
Mentor: Unified Mentor | saikagne2601@gmail.com

Abstract

This research paper presents a comprehensive analysis of ferry capacity utilization and operational efficiency for the Toronto Island Ferry service over a period from 2015 to 2025. Using live data collected through the Toronto Island Ferry Intelligence Platform, this study examines key performance indicators including capacity utilization ratios, congestion pressure, idle capacity rates, peak strain durations, and operational variability scores.

The findings reveal consistent seasonal patterns in ridership, with summer months experiencing the highest congestion and winter months showing significantly lower utilization. The weekly congestion heatmap identifies specific peak hours primarily mid-morning to early afternoon on weekdays and throughout the day on weekends as critical stress points for operational planning. Overall, the ferry system maintains an acceptable utilization ratio of 0.36, though targeted improvements in scheduling and capacity management during peak periods could significantly enhance the passenger experience and reduce idle capacity waste.

1. Introduction

Urban ferry services play a critical role in the transportation infrastructure of coastal and island-connected cities. For Toronto, the ferry service connecting the mainland to Toronto Island is not just a mode of transport it is a lifeline for residents and a major attraction for millions of tourists each year. As demand grows and climate-related factors influence travel patterns, it becomes increasingly important to monitor, analyze and optimize ferry operations using data-driven methods.

This paper presents findings derived from the Toronto Island Ferry Capacity Utilization and Operational Efficiency Analytics System a live intelligence platform that tracks ferry performance metrics in real time. The system aggregates historical data going back to 2015 and provides visual dashboards, trend analyses, and alert mechanisms that help operators make informed decisions.

The goal of Unified Mentor internship project is to provide a clear, accessible overview of what the data tells us about ferry operations: when the system is overloaded, when it is underused, and how those patterns change across seasons, days of the week, and hours of the day.

2. System Overview & Methodology

The analytics system used for this study collects data from ferry boarding logs, scheduling records, and operational reports spanning January 2015 to December 2025. The data is aggregated the frequencies 15-minute, hourly, daily, monthly, and yearly for trend analysis and broken down by hour and day of the week for congestion mapping.

2.1 Key Metrics Tracked

- Capacity Utilization Ratio – The ratio of actual passengers to maximum ferry capacity
- Congestion Pressure Index – Number of time intervals where the ferry exceeded a defined congestion threshold
- Idle Capacity % – The percentage of trips where the ferry was significantly underloaded
- Peak Strain Duration – The average length of time the ferry sustained high passenger loads
- Operational Variability Score – A measure of how stable and predictable ferry operations are (100 = perfectly stable)

2.2 Filters & Configuration

The system allows users to filter data by season (Spring, Summer, Fall, Winter), adjust the congestion threshold, and choose aggregation frequencies. For this study, all four seasons are included, and data is viewed at monthly granularity to capture long-term trends.

3. Dashboard Visualization

The figure below shows the main dashboard of the Ferry Intelligence Platform, displaying all key metrics and charts used in this analysis:

Figure 1: Toronto Island Ferry Capacity Utilization & Operational Efficiency Analytics Dashboard (Live View, 2015–2025)

4. Key Findings

4.1 Summary of Key Performance Indicators

0.36	44.5	45.8%	1.3h
Capacity Utilization Ratio	Congestion Pressure Index	Idle Capacity	Peak Strain Duration
Ferry load efficiency	*Over-utilized intervals*	*Under-utilization rate*	*Avg sustained high-load*

The table above summarizes of the five core performance indicators captured by the system (the fifth, Operational Variability, is discussed in Section 4.6). An Operational Variability Score of 28.8 (out of 100) indicates that the system is moderately unpredictable, suggesting room for schedule optimization.

4.2 Capacity Utilization Ratio: 0.36

A utilization ratio of 0.36 means that, on average, the ferry operates at 36% of its maximum passenger capacity. While this seems low, it reflects the wide variation between peak and off-peak periods. During busy summer weekends, the ferry may run at or above capacity, while quiet winter mornings see very few passengers. This average masks critical stress points that require individual attention.

4.3 Congestion Pressure Index: 44.5

The Congestion Pressure Index (CPI) of 44.5 means that, on average across the study period, there were 44.5-time intervals per analysis window where passenger loads exceeded the 75% congestion threshold. This is a significant figure, indicating that congestion is a recurring and predictable challenge not a rare anomaly. Addressing these intervals through increased sailing frequency or capacity upgrades could substantially improve service quality.

4.4 Idle Capacity: 45.8%

Nearly half of all ferry trips (45.8%) are under-utilized, meaning the ferry is carrying far fewer passengers than it could. This idle capacity represents wasted resources fuel, crew time, and maintenance costs are incurred for trips that could potentially be combined or rescheduled. Better demand forecasting and dynamic scheduling could help reduce this waste.

4.5 Peak Strain Duration: 1.3 Hours

On average, the ferry sustains high passenger loads for about 1.3 hours per peak period. This means that during rush hours or popular tourist times, the system is under pressure for just over an hour at a stretch. Knowing the typical duration of peak strain allows operators to pre-position staff, prepare additional vessels, and manage crowd flow more effectively.

4.6 Operational Variability Score: 28.8

With a score of 28.8 out of 100 (where 100 is perfectly stable), the ferry system shows moderate operational unpredictability. This means that actual ridership and performance frequently deviate from planned schedules. Causes may include weather disruptions, unexpected surges in tourist demand, or mechanical issues. Reducing variability through better planning tools and real-time monitoring is a key recommendation of this study.

5. Seasonal Trends Analysis

The data reveals a strong and consistent seasonal variation in ferry utilization arguably the most operationally significant pattern in the dataset. The Density by Season chart in the dashboard highlights clear differences in ridership distribution across all four seasons:

Season	Utilization Pattern	Key Observation
Summer	Highest — broad, high spread	Peak tourist season; many trips near or above 75% threshold
Spring	Moderate-high; growing utilization	Transitional period; increasing recreational use
Fall	Moderate; declining from summer peaks	Ridership drops as temperatures cool
Winter	Lowest — narrow, low spread	Primarily local residents; minimal tourist traffic

The Historical Utilization Trend chart (2015–2025) clearly shows recurring peaks and valleys in monthly utilization data confirming that the seasonal cycle is consistent year after year. This predictability is actually an asset: it means the ferry system can be proactively scaled up for summer and wound down for winter with confidence.

6. Weekly Congestion Heatmap Analysis

The Weekly Congestion Heatmap is one of the most operationally useful visualizations in the dashboard. It maps ferry congestion across every hour of every day of the week, revealing exactly when and where bottlenecks occur.

6.1 Key Observations from the Heatmap

- Midday Peak (10 AM – 3 PM): The heatmap shows bright yellow-green colours (high congestion) during midday hours on most days, indicating this is the busiest window for ferry travel.
- Weekend Congestion is Broader: On Saturdays and Sundays, congestion stretches across a longer portion of the day compared to weekdays, reflecting leisure travel patterns.
- Early Morning and Late Night are Quiet: Hours before 7 AM and after 9 PM show dark purple tones (low utilization) across all days.
- Weekday Evenings Show a Secondary Peak: A moderate uptick in congestion around 5–7 PM on weekdays reflects the evening commute back from the island.

These patterns provide clear guidance for scheduling decisions. Increasing sailing frequency during 10 AM to 3 PM on weekends, and adding capacity during the weekday evening shoulder peak, would most directly address the highest congestion windows.

7. System Alerts & Status

The dashboard includes a real-time System Alerts section at the bottom of the interface. At the time of this analysis, the alert reads:

> *NOMINAL: Ferry utilization is within acceptable bounds for the selected dates.*

A "NOMINAL" status means the ferry system is currently operating within acceptable performance boundaries, and no emergency or critical threshold has been breached. This is a positive indicator. However, it is important to note that the alert status is dynamic — during summer peak periods or unexpected surges, the system may escalate to WARNING or CRITICAL status, triggering operational responses.

8. Recommendations

Based on the findings of this analysis, the following actions are recommended to improve Toronto Island Ferry operations, listed in order of estimated operational impact:

- Increase Sailing Frequency During Summer Midday: Given the consistent congestion pressure during summer afternoons, adding extra sailings between 10 AM and 3 PM on weekends from June through August would directly address the highest-demand window.
- Introduce Dynamic Scheduling: Rather than a fixed timetable year-round, consider a demand-responsive schedule that automatically increases frequency when utilization exceeds 60% and reduces it when below 25%.
- Reduce Idle Capacity Through Smarter Rostering: With 45.8% idle capacity, there is significant opportunity to consolidate low-demand trips or substitute smaller vessels during off-peak hours to reduce operating costs.

- Invest in Real-Time Capacity Alerts for Passengers: A public-facing display (app or website) showing current ferry load levels would help passengers plan trips and self-distribute demand across sailings.
- Use the Weekly Heatmap for Staff Planning: The congestion heatmap provides a clear weekly template for staff scheduling — aligning crew and crew breaks with low-demand windows.
- Monitor and Reduce Operational Variability: A variability score of 28.8 suggests instability. Conducting a root-cause analysis on the most variable periods can identify whether weather, mechanical issues, or demand spikes are the primary drivers.

9. Conclusion

This research paper has analysed ten years of ferry operations data for the Toronto Island Ferry service using the live Ferry Capacity Utilization and Operational Efficiency Analytics System. The data reveals a clear picture: the ferry system is generally operating within safe bounds, but it faces predictable, recurring challenges around seasonal peaks and midday congestion windows.

The key metrics — a 0.36 utilization ratio, 44.5 congestion pressure index, 45.8% idle capacity, 1.3-hour peak strain duration, and 28.8 operational variability score — together reveal a system that is underutilized on average but significantly stressed during predictable peak windows. The seasonality analysis and weekly heatmap provide actionable, precise information about when and where to focus operational improvements.

With the right scheduling adjustments, capacity investments, and passenger communication tools, the Toronto Island Ferry service can reduce congestion, lower operating costs, and deliver a significantly improved experience for both daily commuters and visitors. The intelligence platform analysed here is already a powerful foundation — acting on its insights is the logical next step.

References & Data Sources

- Toronto Island Ferry Intelligence Platform — Live Operational Dashboard (2015–2025)
- City of Toronto — Parks & Recreation Division, Toronto Island Park Management. Available at: https://www.toronto.ca/city-government/accountability-operations-customer-service/city-administration/staff-directory-divisions-and-customer-service/parks-forestry-recreation/
- Streamlit Inc. — Streamlit: The fastest way to build and share data apps (v1.x). 2024. Available at: https://streamlit.io
- McKinney, W. et al. — pandas: Powerful Python Data Analysis Library (v2.x). NumFOCUS, 2024. Available at: https://pandas.pydata.org
- Harris, C.R. et al. — Array programming with NumPy. Nature, 585, 357–362, 2020. Available at: https://numpy.org
- Plotly Technologies Inc. — Plotly Python Graphing Library / Plotly Express. Montreal, QC, 2024. Available at: https://plotly.com/python
- Python Software Foundation — Python Programming Language (v3.x). 2024. Available at: https://www.python.org