

# Image Uploade CRUD Using Model in LARAVEL

## MIGRATION Page –

Command :

php artisan make:migration create\_images\_table

php artisan migrate

php artisan migrate:refresh

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('images', function (Blueprint $table) {
            $table->integer('id');
            $table->string('fname',20);
            $table->string('lname',20);
            $table->string('email',50);
            $table->string('password',20);
            $table->string('confpassword',20);
            $table->string('class',30);
            $table->string('gender',10);
            $table->text('address');
            $table->string('phone');
            $table->string('image');
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('images');
    }
};
```

## Controller Page –

Command:

php artisan make:controller CrudController

```
<?php

namespace App\Http\Controllers;

use App\Models\Student;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\File;

class StudentController extends Controller
{
    public function addStudent(Request $req)
    {
        $req->validate([
            'name'=>'required',
            'email'=>'required|email',
            'password'=>'required|min:8',
            'class'=>'required',
            'language'=>'required',
            'gender'=>'required',
            'phone'=>'required|numeric|digits:10',
            'address'=>'required',
            'image'=>'required|mimes:png,jpg,jpeg,webp,gif',

        ]);

        if($req->has('image'))
        {
            $file = $req->file('image');
            $extension = $file->getClientOriginalExtension();
            $filename = time() . '.' . $extension;
            $path = 'uploads/images/';
            $file->move(public_path($path), $filename);
        }
        $students = Student::create(
            [

                'id'=>rand(111,999999999),
                'name'=>$req->name,
                'email'=>$req->email,
                'password'=>$req->password,
                'class'=>$req->class,
                'language'=>implode(',',$req->language),
                'gender'=>$req->gender,
                'phone'=>$req->phone,
                'address'=>$req->address,
                'image'=>$path.$filename,

            ]
        );
    }
}
```

```

        if ($students)
        {
            return redirect()->route('home')->with('success', 'Student Added
Successfully');
        }

    }

    public function ShowStudent()
    {
        $students = student::get();
        return view('index',compact('students'));
    }

    public function deleteStudent(string $id)
    {
        $students = student::findorFail($id);

        if(File::exists($students->image))
        {
            File::delete($students->image);
        }

        $students->delete();

        if ($students)
        {
            return redirect()->route('home')->with('denger', 'Student Deleted
Successfully');
        }
    }

    public function singleStudent(string $id)
    {
        $students = student::findorFail($id);
        return view('view',compact('students'));
    }

    public function updatePage(string $id)
    {
        $students = student::find($id);
        return view('update',compact('students'));
    }

    public function updateStudent(Request $req , $id)
    {
        $req->validate([
            'name'=>'required',

```

```

        'email'=>'required|email',
        'password'=>'required|min:8',
        'class'=>'required',
        'language'=>'required',
        'gender'=>'required',
        'phone'=>'required|numeric|digits:10',
        'address'=>'required',
        'image'=>'required|mimes:png,jpg,jpeg,webp,gif',

    ]);

    $students = Student::findorFail($id);

    if($req->has('image'))
    {
        $file = $req->file('image');
        $extension = $file->getClientOriginalExtension();
        $filename = time() . '.' . $extension;
        $path = 'uploads/images/';
        $file->move(public_path($path), $filename);

        if(File::exists($students->image))
        {
            File::delete($students->image);
        }
    }

    $students->update(
        [
            'name'=>$req->name,
            'email'=>$req->email,
            'password'=>$req->password,
            'class'=>$req->class,
            'language'=>implode(',',$req->language),
            'gender'=>$req->gender,
            'phone'=>$req->phone,
            'address'=>$req->address,
            'image'=>$path.$filename,
        ]
    );

    if ($students)
    {
        return redirect()->route('home')->with('success', 'Student Updated Successfully');
    }
}

```

### model Page –

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Student extends Model
{
    use HasFactory;

    protected $table = 'images';

    protected $fillable = [
        'id',
        'name',
        'email',
        'password',
        'class',
        'language',
        'gender',
        'phone',
        'address',
        'image'
    ];
}
```

### route Page –

```
<?php

use App\Http\Controllers\ImageCrudController;
use Illuminate\Support\Facades\Route;

/*
|-----
| Web Routes
|-----
|
| Here is where you can register web routes for your application. These
| routes are loaded by the RouteServiceProvider and all of them will
| be assigned to the "web" middleware group. Make something great!
|
*/
```

```

Route::get('/add', function () {
    return view('add');
})->name('add');

route::post('/addStudent',[ImageCrudController::class,'addStudent']->name('addStudent');

route::get('/singleStudent/{id}',[ImageCrudController::class,'singleStudent']->name('singleStudent');

route::get('/',[ImageCrudController::class,'ShowStudent']->name('home'));

route::get('/delete/{id}',[ImageCrudController::class,'deleteStudent']->name('deleteStudent');

route::get('/updatePage/{id}',[ImageCrudController::class,'updatePage']->name('updatePage');

route::post('/updateStudent/{id}',[ImageCrudController::class,'updateStudent']->name('updateStudent');
// route::post('/adddata',[CrudController::class,'adduser']->name('adduser');

```

[view Page –](#)

[Header.blade.php –](#)

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta http-equiv="X-UA-Compatible" content="ie=edge">
    <title>CRUD</title>
    <link rel="stylesheet" href="/css/style.css">
</head>
<body>
    <div id="wrapper">
        <div id="header">
            <h1>Crud</h1>

```

```

</div>
<div id="menu">
    <ul>
        <li>
            <a href="{{route('home')}}">Home</a>
        </li>
        <li>
            <a href="{{route('add')}}">Add</a>
        </li>
    </ul>
</div>

```

### add.blade.php –

```

@include ('header')
<div id="main-content">
    <h2>Add New Record</h2>
    <form class="post-form" action="{{route('addStudent')}}" method="POST"
enctype="multipart/form-data">
        @csrf
        <div class="form-group">
            <label>First Name</label>
            <input type="text" name="fname" value="{{old('fname')}}" />
            <span style="color:red;">@error('fname'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Last Name</label>
            <input type="text" name="lname" value="{{old('lname')}}" />
            <span style="color:red;">@error('lname'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Email</label>
            <input type="email" name="email" value="{{old('email')}}" />
            <span style="color:red;">@error('email'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Password</label>
            <input type="password" name="password" value="{{old('password')}}" />
            <span style="color:red;">@error('password'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Confirm Password</label>
            <input type="password" name="confpassword" value="{{old('confpassword')}}" />
            <span style="color:red;">@error('confpassword'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>gender</label>
            <input type="text" name="gender" value="{{old('gender')}}" />
            <span style="color:red;">@error('gender'){{$message}}@enderror</span>
        </div>
    </div>

```

```

<div class="form-group">
    <label>Address</label>
    <textarea name="address" cols="30" rows="10" >{{old('address')}}</textarea>
    <span style="color:red;">@error('address'){{$message}}@enderror</span>
</div>
<div class="form-group">
    <label>Class</label>
    <select name="class">
        <option value="" selected disabled>Select Class</option>
        <option value="BCA" {{ old('class') == 'BCA' ? 'selected' : ''
    }}>BCA</option>
        <option value="BSC" {{ old('class') == 'BSC' ? 'selected' : ''
    }}>BSC</option>
        <option value="B.TECH" {{ old('class') == 'B.TECH' ? 'selected' : ''
    }}>B.TECH</option>
    </select>
    <span style="color:red;">@error('class'){{$message}}@enderror</span>
</div>
<div class="form-group">
    <label>Phone</label>
    <input type="number" name="phone" value="{{old('phone')}}" />
    <span style="color:red;">@error('phone'){{$message}}@enderror</span>
</div>
<div class="form-group">
    <label>Image</label>
    <input type="file" name="image" value="{{old('image')}}" />
    <span style="color:red;">@error('image'){{$message}}@enderror</span>
</div>
<input class="submit" type="submit" value="Save" />
</form>
</div>
</div>
</body>
</html>

```

### index.blade.php –

```

@include ('header')
<div id="main-content">
    <h2>All Records</h2>
    @if(Session::has('success'))
        <div style="border:2px solid white;width:100%;background-color:rgb(142, 208,
142);padding:5px;border-radius:30px;">
            <p>{{Session::get('success')}}</p>
        </div>
    @endif
    @if(Session::has('denger'))
        <div style="border:2px solid white;(204, 90, 14);width:100%;background-
color:rgb(214, 107, 13);padding:5px;border-radius:30px;">
            <p>{{Session::get('denger')}}</p>
        </div>
    @endif
</div>

```



```

</div>
    @endif

<table cellpadding="7px">
    <thead>
        <th>Id</th>
        <th>First Name</th>
        <th>Last Name</th>
        <th>Password</th>
        <th>Conf Password</th>
        <th>Email</th>
        <th>Class</th>
        <th>Gender</th>
        <th>Phone</th>
        <th>Address</th>
        <th>Image</th>
        <th>View</th>
        <th>Edit</th>
        <th>Delete</th>
    </thead>
    <tbody>
        @foreach($data as $student)
            <tr>
                <td>{{ $student->id }}</td>
                <td>{{ $student->fname }}</td>
                <td>{{ $student->lname }}</td>
                <td>{{ $student->password }}</td>
                <td>{{ $student->confpassword }}</td>
                <td>{{ $student->email }}</td>
                <td>{{ $student->class }}</td>
                <td>{{ $student->gender }}</td>
                <td>{{ $student->phone }}</td>
                <td>{{ $student->address }}</td>
                <td>
                    
                </td>

                <td><a style="background-color:green;"
href={{route('singleStudent',$student->id)}}>View</a></td>
                <td><a style="background-color:blue;" href={{route('updatePage',$student-
>id)}}>Edit</a></td>
                <td><a href={{route('deleteStudent',$student->id)}}>Delete</a></td>
            </tr>
        @endforeach

    </tbody>
</table>
</div>
</div>
</body>
</html>

```

### update.blade.php –

```
@include('header')
<div id="main-content">
    <h2>Update Record</h2>
    <form class="post-form" action="{{route('updateStudent',$data->id)}}" method="post"
    enctype="multipart/form-data">
        @csrf
        <div class="form-group">
            <label>First Name</label>
            <input type="text" name="fname" value="{{ $data->fname }}" />
            <span style="color:red;">@error('fname'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Last Name</label>
            <input type="text" name="lname" value="{{ $data->lname }}" />
            <span style="color:red;">@error('lname'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Email</label>
            <input type="email" name="email" value="{{ $data->email }}" />
            <span style="color:red;">@error('email'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Password</label>
            <input type="password" name="password" value="{{ $data->password }}" />
            <span style="color:red;">@error('password'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Confirm Password</label>
            <input type="password" name="confpassword" value="{{ $data->confpassword }}" />
            <span style="color:red;">@error('confpassword'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>gender</label>
            <input type="text" name="gender" value="{{ $data->gender }}" />
            <span style="color:red;">@error('gender'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Address</label>
            <textarea name="address" cols="30" rows="10">{{ $data->address }}</textarea>
            <span style="color:red;">@error('address'){{$message}}@enderror</span>
        </div>
        <div class="form-group">
            <label>Class</label>
            <select name="class">
                <option value="" selected disabled>Select Class</option>
                <option value="BCA" @if($data->class == 'BCA')selected @endif>BCA</option>
                <option value="BSC" @if($data->class == 'BSC')selected @endif>BSC</option>
                <option value="B.TECH" @if($data->class == 'B.TECH')selected
            @endif>B.TECH</option>
            </select>
        </div>
    </form>
</div>
```

```

        <span style="color:red;">@error('class'){{$message}}@enderror</span>
    </div>
    <div class="form-group">
        <label>Phone</label>
        <input type="number" name="phone" value="{{ $data->phone }}" />
        <span style="color:red;">@error('phone'){{$message}}@enderror</span>
    </div>
    <div class="form-group">
        <label>Image</label>
        
        <input type="file" name="image" style="margin-left:30%" />
        <span style="color:red;">@error('image'){{$message}}@enderror</span>
    </div>
    <div class="form-group">
    </div>
    <input class="submit" type="submit" value="Update" />
</form>
</div>
</div>
</body>
</html>

```

## Frontend –

CRUD

HOME ADD

All Records

ID	FIRST NAME	LAST NAME	PASSWORD	CONF PASSWORD	EMAIL	CLASS	GENDER	PHONE	ADDRESS	IMAGE	VIEW	EDIT	DELETE
177736833	Vishal	maurya	vk000000	vk000000	atul123@gmail.com	BSC	Male	9511081531	Police line , ramaipatti mirzapur		<a href="#">VIEW</a>	<a href="#">EDIT</a>	<a href="#">DELETE</a>

## Add

CRUD

HOMEADD

Add New Record

First Name

Last Name

Email

Password

Confirm Password

gender

Address

Class

Phone

Image

Select Class

Choose File | No file chosen

SAVE

CRUD

HOMEADD

Update Record

First Name

Last Name

Email

Password

Confirm Password

gender

Address

Class

Phone

Image

Vishal

maurya

atul123@gmail.com

\*\*\*\*\*


\*\*\*\*\*

Male

Police line , ramaipatti mirzapur

BSC

9511081531



Choose File | No file chosen

UPDATE