


Tutorial -3

In this tutorial, we will go through the concepts of recursion, time and space complexities, and how to solve recurrence relations

* Recursion:

Question 1)

```
1  #include<stdio.h>
2
3
4
5  void func(int n){
6
7      if(n>0){
8          func(n-1);
9          printf("%d ",n);
10         func(n-1);
11     }
12
13 }
14
15 void main(){
16     func(4);
17
18
19 }
20
```



1 2 1 3 1 2 1 4 1 2 1 3 1 2 1

Explanation:

Draw recursion tree and traverse in top to bottom, left to right fashion

Question 2)

```
1  #include<stdio.h>
2  int c=0;
3
4  void func(int n){
5
6      if(n==0){
7          return;
8      }
9      c++;
10     func(n/10);
11
12 }
13
14 void main(){
15
16     func(123456789);
17     printf("Value of c is %d",c);
18
19 }
20
21
```

Output:

Value of c is 9

Explanation:

Draw a recursion tree and traverse in top to bottom fashion. Final value of $c=9$, after that we reach the base case $n=0$ and so return.

Efficiency of Algorithms:**Question 1)**

Find the Time Complexity and Space Complexity of the following snippet:

```
int a = 0, b = 0;
for (i = 0; i < N; i++) {
    a = a + rand(); //rand() returns a random number
}
for (j = 0; j < M; j++) {
    b = b + rand();
}
```

Answer:

Time Complexity = $O(m+n)$

Space Complexity = $O(1)$ (constant number of variables)

Question 2)

Find the Time Complexity of the following snippet:

```
int a = 0;
for (i = 0; i < N; i++) {
    for (j = N; j > i; j--) {
        a = a + i + j;
    }
}
```

Answer:

Question 3)

Find the Time Complexity of the following snippet:

```
int a = 0, i = N;
while (i > 0) {
    a += i;
    i /= 2;
}
```

Answer:

$O(\log n)$

Question 4)

Find the Time Complexity of the following function:

```
int fun(int n) {
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j < n; j += i) {
            // Some  $O(1)$  task
        }
    }
}
```

Answer:

$O(n \cdot \log n)$

Explanation:

For $i = 1$, the inner loop is executed n times.

For $i = 2$, the inner loop is executed approximately $n/2$ times.
 For $i = 3$, the inner loop is executed approximately $n/3$ times.
 For $i = 4$, the inner loop is executed approximately $n/4$ times.

.....

For $i = n$, the inner loop is executed approximately n/n times.

The total time complexity of the above algorithm is $(n + n/2 + n/3 + \dots + n/n) = n * (1/1 + 1/2 + 1/3 + \dots + 1/n)$
 [Recall the complexity of harmonic series]

Hence, the time complexity of fun is $O(n \log n)$

Question 5)

Find the Time Complexity of the following function:

```
void demo()
{
    int i, j;
    for (i=1; i<=n; i++)
        for (j=1; j<=log(i); j++)
            System.out.println("Hello World");
}
```

Answer:

$$\begin{aligned} & \Theta(\log 1) + \Theta(\log 2) + \Theta(\log 3) + \dots + \Theta(\log n) \\ &= \Theta(\log n!) \\ &= \Theta(n \log n) \end{aligned}$$

Solving Recurrence Relations:

Question 1)

Solve the following recurrence:

$$T(n) = 2T(n/2) + n$$

$$T(1) = 0$$

Answer:

$$T(n) = 2T(n/2) + n$$

$$= 2[2T(n/2^2) + n/2] + n = 2^2 T(n/2^2) + 2n =$$

$$2^2 [2T(n/2^3) + n/2^2] + 2n = 2^3 T(n/2^3) + 3n$$

.....

$$= 2^k T(n/2^k) + kn$$

$$\text{If } n/2^k = 1 \Rightarrow n = 2^k \Rightarrow k = \log n \text{ (with base 2)}$$

$$\text{Complexity} = O(n \log n)$$

Question 2)

Find time complexity of the recursive fibonacci method

```
public static int rFib( int n) {
    if (n == 0 || n == 1)
        return 1;
    else
        return rFib (n-1) + rFib (n-2);
}
```

Answer:

$$O(2^n)$$

Few Basic Questions:

Find the time complexity of the given expressions?

Q1) An algorithm takes 0.5 ms for input size 100. How large a problem can be solved in 1 min if the running time is Linear (assume low-order terms are negligible)

Answer: $x/100 = 60,000/0.5$

solving for x gives an input size of 12,000,000

Q2) An algorithm takes 0.5 ms for input size 100. How large a problem can be solved in 1 min if the running time is $O(n \log n)$ (assume low-order terms are negligible)

Answer: $x \log x / 100 \log 100 = 60,000/0.5$

solving for x gives an input size of 3,656,807

Homework Questions:

Q1) An algorithm takes 0.5 ms for input size 100. How large a problem can be solved in 1 min if the running time is Quadratic (assume low-order terms are negligible)

Q2) An algorithm takes 0.5 ms for input size 100. How large a problem can be solved in 1 min if the running time is Cubic (assume low-order terms are negligible)

Q3) Use the definition of Big-Oh to prove that $n^{1+0.001}$ is not $O(n)$.

Q4) When $n = 2^{2^k}$ for some $k \geq 0$, the recurrence relation

$$T(n) = \sqrt{2} T(n/2) + \sqrt{n}, T(1) = 1 \quad \text{evaluates to?}$$

Q5) $3n \log n + 2n^{1.8}$

Q6) $8 \log n + 4 \log \log n$

Q7) $3n + 2(\log n)^2 + 4 \log n$

Q8) Apply Master's Theorem

$$T(n) = 64 T(n/8) - n^2 \log n$$

Q9) Apply Master's Theorem

$$T(2^k) = 3T(2^{k-1}) + 1; T(1) = 1$$

