

Question **1**

Not yet answered

Marked out of 1.00

🚩 Flag question

The probability of symbol error for 16-QAM with $\frac{E_s}{N_0} = 20$ is given as

Select one:

- ☐ $\frac{3}{2}Q\left(\frac{1}{\sqrt{2}}\right)$
- ☐ $3Q(1)$
- ☐ $\frac{7}{2}Q\left(\sqrt{\frac{1}{3}}\right)$
- ☒ $3Q(2)$

Question **2**

Not yet answered

Marked out of 1.00

🚩 Flag question

Let the decision regions for $\mathcal{H}_1, \mathcal{H}_0$ be R_1, R_0 , respectively, and corresponding prior probabilities of the hypotheses be π_1, π_0 . The probability of error is given as

Select one:

- ☐ $\pi_1 \int_{R_1} p(\bar{\mathbf{y}}|\mathcal{H}_1) d\bar{\mathbf{y}} + \pi_0 \int_{R_0} p(\bar{\mathbf{y}}|\mathcal{H}_0) d\bar{\mathbf{y}}$
- ☐ $\pi_1 \int_{R_0} p(\bar{\mathbf{y}}|\mathcal{H}_0) d\bar{\mathbf{y}} + \pi_0 \int_{R_1} p(\bar{\mathbf{y}}|\mathcal{H}_1) d\bar{\mathbf{y}}$
- ☒ $\pi_1 \int_{R_0} p(\bar{\mathbf{y}}|\mathcal{H}_1) d\bar{\mathbf{y}} + \pi_0 \int_{R_1} p(\bar{\mathbf{y}}|\mathcal{H}_0) d\bar{\mathbf{y}}$
- ☐ $\pi_0 \int_{R_0} p(\bar{\mathbf{y}}|\mathcal{H}_1) d\bar{\mathbf{y}} + \pi_1 \int_{R_1} p(\bar{\mathbf{y}}|\mathcal{H}_0) d\bar{\mathbf{y}}$

Question **3**

Not yet answered

Marked out of 1.00

🚩 Flag question

The min P_e detector chooses \mathcal{H}_0 when

Select one:

- ☒ $\frac{p(\bar{\mathbf{y}}|\mathcal{H}_0)}{p(\bar{\mathbf{y}}|\mathcal{H}_1)} \geq \frac{\pi_1}{\pi_0}$
- ☐ $\frac{p(\bar{\mathbf{y}}|\mathcal{H}_0)}{p(\bar{\mathbf{y}}|\mathcal{H}_1)} \geq \frac{\pi_0}{\pi_1}$
- ☐ $\frac{p(\bar{\mathbf{y}}|\mathcal{H}_0)}{p(\bar{\mathbf{y}}|\mathcal{H}_1)} \leq \frac{\pi_1}{\pi_0}$
- ☐ $\frac{p(\bar{\mathbf{y}}|\mathcal{H}_0)}{p(\bar{\mathbf{y}}|\mathcal{H}_1)} \geq \frac{\pi_0}{\pi_1}$

Question **4**

Not yet answered

Marked out of 1.00

🚩 Flag question

The min P_e detector chooses \mathcal{H}_0 when

Select one:

- ☒ $\Pr(\mathcal{H}_0|\bar{\mathbf{y}}) \geq \Pr(\mathcal{H}_1|\bar{\mathbf{y}})$
- ☐ $\Pr(\mathcal{H}_1|\bar{\mathbf{y}}) \geq \Pr(\mathcal{H}_0|\bar{\mathbf{y}})$
- ☐ $\Pr(\bar{\mathbf{y}}|\mathcal{H}_0) \geq \Pr(\bar{\mathbf{y}}|\mathcal{H}_1)$
- ☐ $\Pr(\bar{\mathbf{y}}|\mathcal{H}_1) \geq \Pr(\bar{\mathbf{y}}|\mathcal{H}_0)$

Question **5**

Not yet answered

Marked out of 1.00

🚩 Flag question

The min P_e decision rule is the

Select one:

- ☐ ML rule
- ☐ LRT
- ☐ Least Squares
- ☒ MAP rule

Question **6**

Not yet answered

Marked out of 1.00

Flag question

For equiprobable hypotheses, the min P_e decision rule reduces to the

Select one:

- ☐ LRT
- ☒ ML rule
- ☐ Least Squares
- ☐ Maximum Apriori Probability rule

Question **7**

Not yet answered

Marked out of 1.00

Flag question

Consider $\bar{s} = \begin{bmatrix} 2 \\ -2 \\ 2 \\ -2 \end{bmatrix}$, $\sigma^2 = 2$ and $\pi_0 = \frac{e}{1+e}$. For the binary signal detection problem described in class, the threshold for the MAP decision rule is given as

Select one:

- ☒ 10
- ☐ 8
- ☐ 6
- ☐ 12

Question **8**

Not yet answered

Marked out of 1.00

Flag question

For the binary signal detection problem described in class, the minimum P_e achieved using the MAP rule is given as

Select one:

- ☐ $\pi_0 Q\left(\frac{\|\bar{s}\|^2 + 2\sigma^2 \ln \frac{\pi_1}{\pi_0}}{2\sigma\|\bar{s}\|}\right) + \pi_1 Q\left(\frac{\|\bar{s}\|^2 - 2\sigma^2 \ln \frac{\pi_1}{\pi_0}}{2\sigma\|\bar{s}\|}\right)$
- ☐ $\pi_0 Q\left(\frac{\|\bar{s}\| - 2\sigma \ln \frac{\pi_1}{\pi_0}}{2\sigma^2\|\bar{s}\|^2}\right) + \pi_1 Q\left(\frac{\|\bar{s}\| + 2\sigma \ln \frac{\pi_1}{\pi_0}}{2\sigma^2\|\bar{s}\|^2}\right)$
- ☒ $\pi_0 Q\left(\frac{\|\bar{s}\|^2 - 2\sigma^2 \ln \frac{\pi_1}{\pi_0}}{2\sigma\|\bar{s}\|}\right) + \pi_1 Q\left(\frac{\|\bar{s}\|^2 + 2\sigma^2 \ln \frac{\pi_1}{\pi_0}}{2\sigma\|\bar{s}\|}\right)$
- ☐ $\pi_0 Q\left(\frac{\|\bar{s}\| + 2\sigma \ln \frac{\pi_1}{\pi_0}}{2\sigma^2\|\bar{s}\|^2}\right) + \pi_1 Q\left(\frac{\|\bar{s}\| - 2\sigma \ln \frac{\pi_1}{\pi_0}}{2\sigma^2\|\bar{s}\|^2}\right)$

Question **9**

Not yet answered

Marked out of 1.00

Flag question

Consider the binary signal detection problem with $SNR = 10 \text{ dB}$ and $\pi_1 = 0.60$. The min P_e achieved using the optimal decision rule is

Select one:

- ☐ 0.00787
- ☐ 0.0569
- ☒ 0.0555
- ☐ 0.1046

Question **10**

Not yet answered

Marked out of 1.00

Flag question

Consider the binary signal detection problem with $SNR = 10 \text{ dB}$ and $\pi_1 = 0.60$. The P_e achieved using the ML decision rule is

Select one:

- ☐ 0.00787
- ☒ 0.0569
- ☐ 0.0555

○ **0.1046**

Finish attempt ...