

doc

API Documentation

May 2, 2018

Contents

Contents	1
1 Module __main__	4
1.1 Functions	4
1.2 Variables	4
2 Package model	5
2.1 Modules	5
2.2 Variables	5
3 Module model.Ciudad	6
3.1 Variables	6
3.2 Class Ciudad	6
3.2.1 Methods	6
4 Module modelCurso	7
4.1 Variables	7
4.2 Class Curso	7
4.2.1 Methods	7
5 Module model.Departamento	9
5.1 Variables	9
5.2 Class Departamento	9
5.2.1 Methods	9
6 Module model.Estudiante	10
6.1 Variables	10
6.2 Class Estudiante	10
6.2.1 Methods	10
6.2.2 Properties	11
7 Module model.Horario	12
7.1 Variables	12
7.2 Class Horario	12
7.2.1 Methods	12
8 Module model.Persona	13
8.1 Variables	13

8.2	Class Persona	13
8.2.1	Methods	14
8.2.2	Properties	15
9	Module model.Planificacion	16
9.1	Variables	16
9.2	Class Planificacion	16
9.2.1	Methods	16
10	Module model.Profesor	17
10.1	Variables	17
10.2	Class Profesor	17
10.2.1	Methods	18
10.2.2	Properties	19
11	Package view	20
11.1	Modules	20
11.2	Variables	20
12	Module view.frmCrearCurso	21
12.1	Variables	21
12.2	Class Frm_Crear_Curso	23
12.2.1	Methods	24
12.2.2	Properties	27
12.2.3	Class Variables	27
13	Module view.frmCrearEstudiante	32
13.1	Variables	32
13.2	Class Frm_Crear_Estudiante	34
13.2.1	Methods	35
13.2.2	Properties	39
13.2.3	Class Variables	40
14	Module view.frmCrearHorario	44
14.1	Variables	44
14.2	Class Frm_Crear_Horario	46
14.2.1	Methods	47
14.2.2	Properties	49
14.2.3	Class Variables	50
15	Module view.frmCrearNombramiento	55
15.1	Variables	55
15.2	Class Frm_Crear_Nombramiento	57
15.2.1	Methods	58
15.2.2	Properties	60
15.2.3	Class Variables	61
16	Module view.frmCrearProfesor	66
16.1	Variables	66
16.2	Class Frm_Crear_Profesor	68
16.2.1	Methods	69
16.2.2	Properties	74
16.2.3	Class Variables	74

17 Module view.frmListaCursos	79
17.1 Variables	79
17.2 Class Frm_Lista_Curso	81
17.2.1 Methods	82
17.2.2 Properties	84
17.2.3 Class Variables	84
18 Module view.frmListaEstudiante	89
18.1 Variables	89
18.2 Class Frm_Lista_Estudiante	91
18.2.1 Methods	92
18.2.2 Properties	94
18.2.3 Class Variables	95
19 Module view.frmListaProfesor	100
19.1 Variables	100
19.2 Class Frm_Lista_Profesor	102
19.2.1 Methods	103
19.2.2 Properties	105
19.2.3 Class Variables	105
20 Module view.frmPrincipalEstudiante	110
20.1 Variables	110
20.2 Class Frm_Principal_Estudiante	112
20.2.1 Methods	113
20.2.2 Properties	115
20.2.3 Class Variables	115
21 Module view.frmPrincipalProfesor	120
21.1 Variables	120
21.2 Class Frm_Principal_Profesor	122
21.2.1 Methods	123
21.2.2 Properties	126
21.2.3 Class Variables	127
22 Module view.frmRol	131
22.1 Variables	131
22.2 Class Frm_Rol	133
22.2.1 Methods	134
22.2.2 Properties	136
22.2.3 Class Variables	136
23 Module view.scroll	141
23.1 Variables	141
23.2 Class TreeViewFilterWindow	143
23.2.1 Methods	144
23.2.2 Properties	145
23.2.3 Class Variables	145
Index	150

1 Module `__main__`

1.1 Functions

run()
Metodo de inicializacion

1.2 Variables

Name	Description
<code>--package--</code>	Value: None

2 Package model

2.1 Modules

- **Ciudad** (*Section 3, p. 6*)
- **Curso** (*Section 4, p. 7*)
- **Departamento** (*Section 5, p. 9*)
- **Estudiante** (*Section 6, p. 10*)
- **Horario** (*Section 7, p. 12*)
- **Persona** (*Section 8, p. 13*)
- **Planificacion** (*Section 9, p. 16*)
- **Profesor** (*Section 10, p. 17*)

2.2 Variables

Name	Description
<code>--package--</code>	Value: None

3 Module model.Ciudad

3.1 Variables

Name	Description
<code>--package--</code>	Value: None

3.2 Class Ciudad

Clase Ciudad, con datos especificos del mismo

3.2.1 Methods

<code>--init--(self, nombre, descripcion, id=0)</code> Constructor de Ciudad Parameters nombre: Nombre de la Ciudad <i>(type=str)</i> descripcion: descripcion de la Ciudad <i>(type=str)</i> id: Identificacion de la Ciudad <i>(type=integer)</i>
<code>--str--(self)</code> Convierte clase a str Return Value Str convertido de la clase <i>(type=str)</i>
<code>set_id(self, id)</code> Modifica id de la ciudad Parameters id: Identificacion nueva <i>(type=integer)</i>
<code>get_nom(self)</code> Retorna Nombre de la Ciudad Return Value Nombre de la Ciudad <i>(type=str)</i>

4 Module model.Curso

4.1 Variables

Name	Description
<code>--package--</code>	Value: 'model'

4.2 Class Curso

Clase Curso

4.2.1 Methods

<code>--init--(self, nombre, aula, tiempo, dia_reunion, edificio, id=0)</code>	
Constructor de clase Curso	
Parameters	
nombre:	Nombre del Curso (<i>type=str</i>)
aula:	Aula donde se va hacer el curso (<i>type=str</i>)
id:	Identificacion del curso (<i>type=integer</i>)
tiempo:	Tiempo en horas del curso (<i>type=double</i>)
dia_reunion:	Fecha de Reunion (<i>type=datetime</i>)
edificio:	Edificio donde es el lugar de Reunion (<i>type=str</i>)
<code>--str--(self)</code>	
Conversion de Clase a str	
Return Value	
Conversion de Clase (<i>type=str</i>)	

set_profesor(*self*, *profesor*)

Pone profesor a cargo del curso

Parameters

profesor: Profesor encargado del curso
(*type=Profesor*)

5 Module model.Departamento

5.1 Variables

Name	Description
<code>--package--</code>	Value: None

5.2 Class Departamento

Clase Departamento

5.2.1 Methods

`--init--(self, nombre, ciudad, telefono, id=0)`

Constructor de clase Departamento

Parameters

nombre: Nombre del Departamento
(*type=str*)

ciudad: Ciudad donde esta el Departamento
(*type=Ciudad*)

telefono: Telefono de contacto del Departamento
(*type=integer*)

id: Identificacion de Departamento
(*type=integer*)

`--str--(self)`

Conversion de clase a str

Return Value


Conversion de clase
(*type=str*)

6 Module model.Estudiante

6.1 Variables

Name	Description
<code>--package--</code>	Value: 'model'

6.2 Class Estudiante



Clase de los estudiantes

6.2.1 Methods

__init__(self, num, nombre1, nombre2, apellido1, apellido2, edad, lug_nacimiento, lug_residencia, dir_residencia, semestre)

Constructor de estudiante, tiene datos de persona, quien es su super-clase

Parameters

num: Numero de identificacion, Unico e Irrepetible
nombre1: Primer nombre
nombre2: Segundo nombre
apellido1: Primer apellido
apellido2: Segundo apellido
edad: Edad de persona
lug_nacimiento: Lugar de nacimiento
ciu_residencia: Ciudad de Residencia
dir_residencia: Direccin de Residencia

Overrides: object.__init__

es_is_graduado(self)

Retorna en español si esta graduado o no

Return Value

Retorno de graduado en español
(type=str)

<code>__str__(self)</code>
Conversion de clase a str de Estudiante
Return Value Clase convertida a str (<i>type=</i> str)
Overrides: object.__str__

<code>set_consejero(self, consejero)</code>
Pone consejero a estudiante solo si esta graduado
Parameters consejero: Profesor consejero que esta disponible (<i>type=</i> Profesor)
Return Value retron true si se puso consejero correctamente y false de no se estudiante graduado (<i>type=</i> bool)

<code>set_horario(self, horario)</code>
Modifica y relaciona el horario dado
Parameters horario: Horario que se va a vincular a estudiante (<i>type=</i> Horario)

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

6.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

7 Module model.Horario

7.1 Variables

Name	Description
<code>--package--</code>	Value: 'model'

7.2 Class Horario

Clase horario

7.2.1 Methods

<code>--init--(self, curso, fecha_inicio, fecha_fin, semestre)</code>	
Construccion del horario del estudiante	
Parameters	
curso:	Curso Vinnclado al horario (<i>type=Curso</i>)
fecha_inicio:	Fecha de inicio de clase (<i>type=datetime</i>)
fecha_fin:	Fecha de finalizacion de clase (<i>type=datetime</i>)
semestre:	Semestre que esta ubicado el horario (<i>type=int</i>)
<code>--str--(self)</code>	
Conversion de clase a str de Horario	
Return Value	
Clase convertida a str (<i>type=str</i>)	

8 Module *model.Persona*

8.1 Variables

Name	Description
<code>--package--</code>	Value: None

8.2 Class *Persona*

object └─
 model.Persona.Persona

Known Subclasses: *model.Estudiante.Estudiante*, *model.Profesor.Profesor*

Representacion de los datos basicos de la persona

8.2.1 Methods

__init__(*self, num, nombre1, nombre2, apellido1, apellido2, edad, lug_nacimiento, ciu_residencia, dir_residencia*)

Constructor de Persona

Parameters

num:	Numero de identificacion, Unico e Irrepetible (<i>type=integer</i>)
nombre1:	Primer nombre (<i>type=str</i>)
nombre2:	Segundo nombre (<i>type=str</i>)
apellido1:	Primer apellido (<i>type=str</i>)
apellido2:	Segundo apellido (<i>type=str</i>)
edad:	Edad de persona (<i>type=int</i>)
lug_nacimiento:	Lugar de nacimiento (<i>type=Ciudad</i>)
ciu_residencia:	Ciudad de Residencia (<i>type=Ciudad</i>)
dir_residencia:	Direccin de Residencia (<i>type=str</i>)

Overrides: object.__init__

__str__(*self*)

Conversion a str de clase

Return Value

Datos de clase en str
(*type=str*)

Overrides: object.__str__

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`,
`__repr__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

8.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

9 Module model.Planificacion

9.1 Variables

Name	Description
--package--	Value: None

9.2 Class Planificacion

Clase de Planificacion de los estudiantes

9.2.1 Methods


--init-- (<i>self, semestre, id_estudiante, id_curso</i>)	
Constructor de clase de Planificacion	
Parameters	
id_estudiante:	Codigo unico del estudiante (<i>type=integer</i>)
id_curso:	Codigo unico del curso (<i>type=integer</i>)
semestre:	Semestre en el que el estudiante se inscribio (<i>type=integer</i>)
--str-- (<i>self</i>)	
Conversion de clase a str	
Return Value	
Conversion de clase (<i>type=str</i>)	
set_nota (<i>self, nota</i>)	
Poner nota al estudiante que esta inscrito en el curso	
Parameters	
nota:	Nota obtenida del curso (<i>type=double</i>)

10 Module model.Profesor

10.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'model'</code>

10.2 Class Profesor



10.2.1 Methods

```
__init__(self, num, nombre1, nombre2, apellido1, apellido2, edad,
lug_nacimiento, lug_residencia, dir_residencia, titulo, contrato,
is_visitante=False, ini_nombramiento=None, fin_nombramiento=None)
```

Constructor de clase de Profesor

Parameters

is_visitante: Obtener si un profesor es visitante o no
(*type=bool*)

titulo: Titulo obtenido
(*type=str*)

contrato: Contrato que se ha firmado ante la universidad para ejercer enseñanza
(*type=str*)

ini_nombramiento: Fecha de inicio de Nombramiento solo si es profesor visitante
(*type=datetime*)

fin_nombramiento: Fecha de fin de Nombramiento solo si es profesor visitante
(*type=datetime*)

Overrides: object.__init__

```
es_is_visitante(self)
```

Retorna en español si esta visitante o no

Return Value

Retorno de visitante en español
(*type=str*)

```
__str__(self)
```

Conversion de clase a str de Profesor

Return Value

Datos de clase en str
(*type=str*)

Overrides: object.__str__

set_departamento (<i>self</i> , <i>departamento</i>)

Pone el profesor en un departamento

Parameters

departamento: Departamento a cambiar <i>(type=Departamento)</i>

set_ini_nombramiento (<i>self</i> , <i>fecha</i>)
--

Modifica la fecha de inicio de nombramiento

Parameters

fecha: Fecha de nombramiento ini <i>(type=date)</i>

set_fin_nombramiento (<i>self</i> , <i>fecha</i>)
--

Modifica la fecha de fin de nombramiento
--

Parameters

fecha: Fecha de nombramiento_fin <i>(type=date)</i>

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(),
 __repr__(), __setattr__(), __sizeof__(), __subclasshook__()

10.2.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

11 Package view

11.1 Modules

- **frmCrearCurso** (*Section 12, p. 21*)
- **frmCrearEstudiante** (*Section 13, p. 32*)
- **frmCrearHorario** (*Section 14, p. 44*)
- **frmCrearNombramiento** (*Section 15, p. 55*)
- **frmCrearProfesor** (*Section 16, p. 66*)
- **frmListaCursos** (*Section 17, p. 79*)
- **frmListaEstudiante** (*Section 18, p. 89*)
- **frmListaProfesor** (*Section 19, p. 100*)
- **frmPrincipalEstudiante** (*Section 20, p. 110*)
- **frmPrincipalProfesor** (*Section 21, p. 120*)
- **frmRol** (*Section 22, p. 131*)
- **scroll** (*Section 23, p. 141*)

11.2 Variables


Name	Description
<code>--package--</code>	Value: None

12 Module view.frmCrearCurso

12.1 Variables

Name	Description
__package__	Value: 'view'

12.2 Class Frm_Crear_Curso



Clase en la que se va a poder crear o modificar curso

12.2.1 Methods

`__init__(self)`

Construtor de la clase Frm_Crear_Curso, enfocado a la vista

Overrides: `object.__init__`

`box1(self)`

Construccion de la caja 1, caja superior que va a dato acerca del curso

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`box2(self)`

Construccion de la caja 2, caja intermedia que va a dato acerca del curso

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`box3(self)`

Construccion de la caja 3, caja intermedia que va a dato acerca del curso

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`box4(self)`

Construccion de la caja 3, caja intermedia que va a dato acerca del curso

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box5(*self*)

Construccion de la caja 3, caja intermedia que va a dato acerca del curso

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box6(*self*)

Construccion de la caja 6, caja final, da a los botones

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

index_box(*self*)

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(*type=Gtk.Box*)

dev_frm(*self*)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_cb_edificio_changed(*self*, *widget*)

Evento para combobox cuando este cambia

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_guardar_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_borrar_clicked (<i>self, widget</i>)
--

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

on_btn_salir_clicked (<i>self, widget</i>)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

Inherited from gi.overrides.Gtk.Container

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from ??.Container

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from gi.overrides.Gtk.Widget

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from ??.Widget

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

Inherited from gi.overrides.GObject.Object

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`, `weak_ref()`

Inherited from ??Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from gi._gi.GObject

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(),
__new__(), __repr__(), __setattr__(), props()

Inherited from object

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(),
__subclasshook__()

12.2.2 Properties

Name	Description
<i>Inherited from ??Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ??Container</i> widget	
<i>Inherited from ??Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	
<i>Inherited from object</i> __class__	

12.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmCrearCurso+Frm_Crear_Curso (94499136502784)>
<i>Inherited from ??Window</i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus³⁰_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>


Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

13 Module view.frmCrearEstudiante

13.1 Variables

Name	Description
__package__	Value: 'view'

13.2 Class Frm_Crear_Estudiante



Clase en la que se va a poder crear o modificar estudiante

13.2.1 Methods

`__init__(self)`

Construtor de la clase Frm_Crear_Estudiante, enfocado a la vista

Overrides: `object.__init__`

`box1(self)`

Construccion de la caja 1, caja superior que va a dato acerca del estudiante enfocado en el codigo del estudiante

Return Value

Caja con boton dentro

(type=Gtk.Box)

`box2(self)`

Construccion de la caja 2, caja intermedia que va a dato acerca del estudiante enfocado en el nombre 1 del estudiante

Return Value

Caja con boton dentro

(type=Gtk.Box)

`box3(self)`

Construccion de la caja 3, caja intermedia que va a dato acerca del estudiante enfocado en el nombre 1 del estudiante

Return Value

Caja con boton dentro

(type=Gtk.Box)

`box4(self)`

Construccion de la caja 4, caja intermedia que va a dato acerca del estudiante enfocado en el nombre 2 del estudiante

Return Value

Caja con boton dentro

(type=Gtk.Box)

box5(self)

Construccion de la caja 5, caja intermedia que va a dato acerca del estudiante enfocado en el Apellido 1 del estudiante

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box6(self)

Construccion de la caja 6, caja intermedia que va a dato acerca del estudiante enfocado en el Apellido 2 del estudiante

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box7(self)

Construccion de la caja 7, caja intermedia que va a dato acerca del estudiante enfocado en la edad del estudiante

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box8(self)

Construccion de la caja 8, caja intermedia que va a dato acerca del estudiante enfocado en el lugar de nacimiento del estudiante

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box9(self)

Construccion de la caja 9, caja intermedia que va a dato acerca del estudiante enfocado en el lugar de residencia del estudiante

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box10(self)

Construccion de la caja 10, caja intermedia que va a dato acerca del estudiante enfocado en la direccion de residencia del estudiante

Return Value

Caja con boton dentro

(type=Gtk.Box)

box11(self)

Construccion de la caja 10, caja intermedia que va a dato acerca del estudiante enfocado en la semestre del estudiante

Return Value

Caja con boton dentro

(type=Gtk.Box)

box12(self)

Construccion de la caja 12, caja final, da a los botones

Return Value

Caja con boton dentro

(type=Gtk.Box)

index_box(self)

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(type=Gtk.Box)

dev_frm(self)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_cb_lug_nacimiento_changed(self, widget)

Evento para combobox cuando este cambia

Parameters

widget: Widget que esta relacionado al evento

(type=Gtk.Widget)

on_cb_lug_residencia_changed(*self*, *widget*)

Evento para combobox cuando este cambia

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_guardar_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_borrar_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_salir_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

Inherited from *gi.overrides.Gtk.Container*

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from *??Container*

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from *gi.overrides.Gtk.Widget*

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from *??Widget*

bind_template_callback_full(), bind_template_child_full(), find_style_property(), get_css_name(), install_style_property(), list_style_properties(), set_accessible_role(), set_accessible_type(), set_connect_func(), set_css_name(), set_template(), set_template_from_resource()

Inherited from gi.overrides.GObject.Object

__copy__(), __deepcopy__(), bind_property(), bind_property_full(), chain(), compat_control(), connect(), connect_after(), connect_data(), connect_object(), connect_object_after(), disconnect(), disconnect_by_func(), emit(), emit_stop_by_name(), force_floating(), freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from ?? .Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from gi._gi.GObject

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from object

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

13.2.2 Properties

Name	Description
<i>Inherited from ?? .Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ?? .Container</i> widget	
<i>Inherited from ?? .Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	

continued on next page

Name	Description
<i>Inherited from object</i>	
__class__	

13.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmCrearEstudiante+Frm_Crear_Estudiante (9449...
<i>Inherited from ??Window</i>	
__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	
<i>Inherited from gi.repository.Gtk.Bin</i>	
get_child	

continued on next page

Name	Description
<i>Inherited from ??Container</i>	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus42_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	

14 Module *view.frmCrearHorario*

14.1 Variables

Name	Description
<code>--package--</code>	Value: <code>'view'</code>

Clase enfocda en la construccion del horario, tiene permiso desde el formulario principal del estudiante

14.2.1 Methods

`__init__(self, estudiante, curso)`

Constructor de la clase *Frm_Crear_Horario*, enfocado en la construccion de la creacion del horario, antes de cargar este formulario habra que cargar varias cosas, como lo pueden ser la lista de estudiantes y cursos

Parameters

estudiante: id del estudiante seleccionado previamente

(type=int)

curso: codigo del curso seleccionado previamente

(type=int)

Overrides: *object.__init__*

`box1(self)`

Construccion de la caja1, caja superior que va a reunir los datos acerca del horario

Return Value

Caja con comboBox Adentro

(type=Gtk.Box)

`box2(self)`

Construccion de la caja 2, caja intermedia enfocada en la presentacion la construccion del calendario en pantalla para su posterior seleccion

`box3(self)`

Construccion de la caja 3, caja intermedia enfocada en la presentacion la construccion del calendario en pantalla para su posterior seleccion

`box4(self)`

Construccion de la caja 4, caja final, da a los botones

Return Value

Caja con boton dentro

(type=Gtk.Box)

index_box(self)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrara alguna propiedades del mismo

dev_frm(self)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_cb_semestre_changed(self, widget)

Metodo enfocado en ejecutar el evento del combobox para el cambio de semestre

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_guardar_clicked(self, widget)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_borrar_clicked(self, widget)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_salir_clicked(self, widget)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

Inherited from *gi.overrides.Gtk.Container*

`--bool--()`, `--contains--()`, `--iter--()`, `--len--()`, `--nonzero--()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from `??`.Container

find_child_property(), handle_border_width(), install_child_properties(), install_child_property(), list_child_properties()

Inherited from `gi.overrides.Gtk.Widget`

drag_dest_set_target_list(), drag_source_set_target_list(), style_get_property(), translate_coordinates()

Inherited from `??`.Widget

bind_template_callback_full(), bind_template_child_full(), find_style_property(), get_css_name(), install_style_property(), list_style_properties(), set_accessible_role(), set_accessible_type(), set_connect_func(), set_css_name(), set_template(), set_template_from_resource()

Inherited from `gi.overrides.GObject.Object`

__copy__(), __deepcopy__(), bind_property(), bind_property_full(), chain(), compat_control(), connect(), connect_after(), connect_data(), connect_object(), connect_object_after(), disconnect(), disconnect_by_func(), emit(), emit_stop_by_name(), force_floating(), freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from `??`.Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from `gi._gi.GObject`

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from `object`

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

14.2.2 Properties

Name	Description
<i>Inherited from <code>??</code>.Window</i>	
bin, priv	

continued on next page

Name	Description
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ???.Container</i> widget	
<i>Inherited from ???.Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	
<i>Inherited from object</i> __class__	

14.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmCrearHorario+Frm_Crear_Horario (9449913682...
<i>Inherited from ???.Window</i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus⁵³_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

15 Module view.frmCrearNombramiento

15.1 Variables

Name	Description
__package__	Value: 'view'

Clase en la que se va a poder crear o modificar el Nombramiento del Profesor

15.2.1 Methods

__init__(self)

Construtor de la clase Frm_Crear_Nombramiento, enfocado a la vista

Overrides: object.__init__

load(self, profesor)

Carga los datos para su posterior modificacion

Parameters

profesor: Datos referentes al profesor

(*type=Profesor*)

box1(self)

Construccion de la caja 1, caja intermedia que va a dato acerca del Nombramiento del profesor nombramiento fecha inicio

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box2(self)

Construccion de la caja 2, caja intermedia que va a dato acerca del Nombramiento del profesor nombramiento fecha fin

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box3(self)

Construccion de la caja 3, caja final, da a los botones

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

index_box(*self*)

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(*type=Gtk.Box*)

dev_frm(*self*)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_btn_guardar_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_borrar_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_salir_clicked(*self*, *widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

Inherited from gi.overrides.Gtk.Container

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from ??Container

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from gi.overrides.Gtk.Widget

drag_dest_set_target_list(), drag_source_set_target_list(), style_get_property(), translate_coordinates()

Inherited from `??`.Widget

bind_template_callback_full(), bind_template_child_full(), find_style_property(), get_css_name(), install_style_property(), list_style_properties(), set_accessible_role(), set_accessible_type(), set_connect_func(), set_css_name(), set_template(), set_template_from_resource()

Inherited from `gi.overrides.GObject.Object`

__copy__(), __deepcopy__(), bind_property(), bind_property_full(), chain(), compat_control(), connect(), connect_after(), connect_data(), connect_object(), connect_object_after(), disconnect(), disconnect_by_func(), emit(), emit_stop_by_name(), force_floating(), freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from `??`.Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from `gi._gi.GObject`

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from `object`

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

15.2.2 Properties

Name	Description
<i>Inherited from <code>??</code>.Window</i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??</code>.Container</i> widget	
<i>Inherited from <code>??</code>.Widget</i> parent_instance	

continued on next page

Name	Description
	<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count
	<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__
	<i>Inherited from object</i> __class__

15.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmCrearNombramiento+Frm_Crear_Nombramiento (...
	<i>Inherited from ?? Window</i>

continued on next page

Name	Description
	__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick
	<i>Inherited from gi.repository.Gtk.Bin</i> get_child
	<i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	

16 Module view.frmCrearProfesor

16.1 Variables

Name	Description
__package__	Value: 'view'

Clase en la que se va a poder crear o modificar Profesor

16.2.1 Methods

`__init__(self, fecha1=None, fecha2=None)`

Construtor de la clase Frm_Crear_Profesor, enfocado a la vista Este esta enfocado cuando el profesor no es de planta

Overrides: `object.__init__`

`load(self, profesor)`

Carga los datos para su posterior modificacion

Parameters

profesor: Datos referentes al profesor
(*type=Profesor*)

`box1(self)`

Construccion de la caja 1, caja superior que va a dato acerca del profesor enfocado en el codigo del profesor

Return Value

Caja con boton dentro
(*type=Gtk.Box*)

`box2(self)`

Construccion de la caja 2, caja intermedia que va a dato acerca del profesor enfocado en el nombre 1 del profesor

Return Value

Caja con boton dentro
(*type=Gtk.Box*)

`box3(self)`

Construccion de la caja 3, caja intermedia que va a dato acerca del profesor enfocado en el nombre 2 del profesor

Return Value

Caja con boton dentro
(*type=Gtk.Box*)

box4(self)

Construccion de la caja 4, caja intermedia que va a dato acerca del profesor enfocado en el Apellido 1 del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box5(self)

Construccion de la caja 5, caja intermedia que va a dato acerca del profesor enfocado en el Apellido 2 del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box6(self)

Construccion de la caja 6, caja intermedia que va a dato acerca del profesor enfocado en la edad del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box7(self)

Construccion de la caja 7, caja intermedia que va a dato acerca del profesor enfocado en el lugar de nacimiento del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box8(self)

Construccion de la caja 8, caja intermedia que va a dato acerca del profesor enfocado en el lugar de residencia del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box9(*self*)

Construccion de la caja 9, caja intermedia que va a dato acerca del profesor enfocado en la direccion de residencia del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box10(*self*)

Construccion de la caja 10, caja intermedia que va a dato acerca del profesor enfocado en el titulo del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box11(*self*)

Construccion de la caja 11, caja intermedia que va a dato acerca del profesor enfocado en el contrato del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box12(*self*)

Construccion de la caja 12, caja intermedia que va a dato acerca del profesor enfocado en la facultad del profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box13(*self*)

Construccion de la caja 13, caja final, da a los botones

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

index_box(self)

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(*type=Gtk.Box*)

dev_frm(self)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_cb_lug_nacimiento_changed(self, widget)

Evento para combobox cuando este cambia

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_cb_departamento_changed(self, widget)

Evento para combobox cuando este cambia

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_cb_lug_residencia_changed(self, widget)

Evento para combobox cuando este cambia

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_guardar_clicked(self, widget)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_borrar_clicked (<i>self, widget</i>)
--

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

Inherited from gi.overrides.Gtk.Container

__bool__(), __contains__(), __iter__(), __len__(), __nonzero__(), child_get(), child_get_property(), child_set(), get_focus_chain()

Inherited from ??Container

find_child_property(), handle_border_width(), install_child_properties(), install_child_property(), list_child_properties()

Inherited from gi.overrides.Gtk.Widget

drag_dest_set_target_list(), drag_source_set_target_list(), style_get_property(), translate_coordinates()

Inherited from ??Widget

bind_template_callback_full(), bind_template_child_full(), find_style_property(), get_css_name(), install_style_property(), list_style_properties(), set_accessible_role(), set_accessible_type(), set_connect_func(), set_css_name(), set_template(), set_template_from_resource()

Inherited from gi.overrides.GObject.Object

__copy__(), __deepcopy__(), bind_property(), bind_property_full(), chain(), compat_control(), connect(), connect_after(), connect_data(), connect_object(), connect_object_after(), disconnect(), disconnect_by_func(), emit(), emit_stop_by_name(), force_floating(), freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from ??Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from gi._gi.GObject

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from object

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`,
`__subclasshook__()`

16.2.2 Properties

Name	Description
<i>Inherited from ???.Window</i>	bin, priv
<i>Inherited from gi.repository.Gtk.Bin</i>	container
<i>Inherited from ???.Container</i>	widget
<i>Inherited from ???.Widget</i>	parent_instance
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i>	g_type_instance, qdata, ref_count
<i>Inherited from gi._gi.GObject</i>	__gpointer__, __grefcount__
<i>Inherited from object</i>	__class__

16.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmCrearProfesor+Frm_Crear_Profesor (94499137...)
<i>Inherited from ???.Window</i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>


Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

17 Module view.frmListaCursos

17.1 Variables

Name	Description
__package__	Value: 'view'

17.2 Class Frm_Lista_Curso



Clase de la lista de los cursos

17.2.1 Methods

`__init__(self, cod_profesor, formulario_siguiente)`

Construtor de la clase Frm_Lista_Curso, enfocado a la vista

Parameters

formulario_siguiente: Formulario que estara cargado despues de la seleccion
(*type=*str)

Overrides: object.__init__

`box1(self)`

Construccion de la lista de seleccion para el curso

`box2(self)`

Boton de seleccion

`index_box(self)`

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro
(*type=*Gtk.Box)

`dev_frm(self)`

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

`on_btn_modificar_clicked(self, widget)`

Evento que funciona al accionar el boton de curso

Parameters

widget: Widget que esta relacionado al evento
(*type=*Gtk.Widget)

on_btn_borrar_clicked(*self*, *widget*)

Evento que funciona al accionar el boton de curso

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_cerrar_clicked(*self*, *widget*)

Evento que funciona al accionar el boton de cerrar

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

get_seleccion(*self*)

Retorna el valor de la seleccion del formulario despues de aceptar

Return Value

Valor seleccionado en la lista, especificamente el id
(*type=int*)

Inherited from *gi.overrides.Gtk.Container*

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from *??Container*

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from *gi.overrides.Gtk.Widget*

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from *??Widget*

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

Inherited from *gi.overrides.GObject.Object*

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`,

freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from `??Object`

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from `gi._gi.GObject`

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from `object`

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

17.2.2 Properties

Name	Description
<i>Inherited from <code>??Window</code></i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??Container</code></i> widget	
<i>Inherited from <code>??Widget</code></i> parent_instance	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> g_type_instance, qdata, ref_count	
<i>Inherited from <code>gi._gi.GObject</code></i> __gpointer__, __grefcount__	
<i>Inherited from <code>object</code></i> __class__	

17.2.3 Class Variables

Name	Description
--gtype--	Value: <GType view+frmListaCursos+Frm_Lista_Curso (94499137722032)>
<i>Inherited from ??Window</i> __info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	
<i>Inherited from gi.repository.Gtk.Bin</i> get_child	
<i>Inherited from ??Container</i>	

continued on next page

Name	Description
	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>


Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

18 Module *view.frmListaEstudiante*

18.1 Variables

Name	Description
<code>--package--</code>	Value: 'view'

18.2 Class Frm_Lista_Estudiante



Clase de la lista de los estudiantes

18.2.1 Methods

`__init__(self, formulario_siguiente)`

Construtor de la clase Frm_Lista_Estudiante, enfocado a la vista

Parameters

formulario_siguiente: Formulario que estara cargado despues de la seleccion
(*type=*str)

Overrides: object.__init__

`box1(self)`

Construccion de la lista de seleccion para el Estudiante

Return Value

Caja con datos referentes a la lista de estudiantes
(*type=*Gtk.Box)

`box2(self)`

Boton de seleccion para su posterior control

Return Value

Caja con cajas dentro
(*type=*Gtk.Box)

`box3(self)`

Boton de seleccion

`index_box(self)`

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro
(*type=*Gtk.Box)

dev_frm(*self*)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_btn_semestre_siguiente_clicked(*self*, *widget*)

Evento que funciona al accionar el boton de Estudiante

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_semestre_anterior_clicked(*self*, *widget*)

Evento que funciona al accionar el boton de Estudiante

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_borrar_clicked(*self*, *widget*)

Evento que funciona al accionar el boton de Estudiante

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

get_seleccion(*self*)

Retorna el valor de la seleccion de la lista aqui mostrada y con ello tomar decisiones

Return Value

Valor de id_estudiante que se seleccionó al oprimir
(*type=int*)

Inherited from gi.overrides.Gtk.Container

`--bool--()`, `--contains--()`, `--iter--()`, `--len--()`, `--nonzero--()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from ??Container

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from gi.overrides.Gtk.Widget

drag_dest_set_target_list(), drag_source_set_target_list(), style_get_property(), translate_coordinates()

Inherited from ??.Widget

bind_template_callback_full(), bind_template_child_full(), find_style_property(), get_css_name(), install_style_property(), list_style_properties(), set_accessible_role(), set_accessible_type(), set_connect_func(), set_css_name(), set_template(), set_template_from_resource()

Inherited from gi.overrides.GObject.Object

__copy__(), __deepcopy__(), bind_property(), bind_property_full(), chain(), compat_control(), connect(), connect_after(), connect_data(), connect_object(), connect_object_after(), disconnect(), disconnect_by_func(), emit(), emit_stop_by_name(), force_floating(), freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from ??.Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from gi._gi.GObject

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from object

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

18.2.2 Properties

Name	Description
<i>Inherited from ??.Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ??.Container</i> widget	

continued on next page

Name	Description
<i>Inherited from <code>??Widget</code></i>	parent_instance
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i>	g_type_instance, qdata, ref_count
<i>Inherited from <code>gi._gi.GObject</code></i>	__gpointer__, __grefcount__
<i>Inherited from object</i>	__class__

18.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmListaEstudiante+Frm_Lista_Estudiante (9449...
<i>Inherited from <code>??Window</code></i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>


Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

19 Module view.frmListaProfesor

19.1 Variables

Name	Description
__package__	Value: 'view'

19.2 Class Frm_Lista_Profesor



Clase de la lista de los profesores

19.2.1 Methods

`__init__(self, formulario_siguiente='')`

Construtor de la clase Frm_Lista_Profesor, enfocado a la vista

Parameters

formulario_siguiente: Formulario que estara cargado despues de la seleccion
(*type=str*)

Overrides: object.__init__

`box1(self)`

Construccion de la lista de seleccion para el Profesor

`box2(self)`

Boton de seleccion para su posterior control

`box3(self)`

Boton de seleccion

`index_box(self)`

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro
(*type=Gtk.Box*)

`dev_frm(self)`

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

`on_btn_facultad_siguiente_clicked(self)`

Evento que funciona al accionar el boton de profesor

on_btn_facultad_anterior_clicked(<i>self</i>)
Evento que funciona al accionar el boton de profesor

on_btn_seleccionar_clicked(<i>self, widget</i>)
Evento que funciona al accionar el boton de profesor
Parameters
widget: Widget que esta relacionado al evento
(<i>type=Gtk.Widget</i>)

Inherited from gi.overrides.Gtk.Container

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from ??.Container

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from gi.overrides.Gtk.Widget

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from ??.Widget

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

Inherited from gi.overrides GObject.Object

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`, `weak_ref()`

Inherited from ??.Object

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

Inherited from gi._gi.GObject

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`,
`__new__()`, `__repr__()`, `__setattr__()`, `props()`

Inherited from object

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`,
`__subclasshook__()`

19.2.2 Properties

Name	Description
<i>Inherited from ?? .Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ?? .Container</i> widget	
<i>Inherited from ?? .Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	
<i>Inherited from object</i> __class__	

19.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmListaProfesor+Frm_Lista_Profesor (94499137...)
<i>Inherited from ?? .Window</i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

20 Module *view.frmPrincipalEstudiante*

20.1 Variables

Name	Description
<code>--package--</code>	Value: 'view'

Formulario principal de estudiante

20.2.1 Methods

`__init__(self)`

Construtor de la clase *Frm_Principal_Estudiante*, enfocado a la vista

Overrides: *object.__init__*

`box1(self)`

Construccion de la caja 1, caja superior que va a albergar un boton

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`box2(self)`

Construccion de la caja 2, caja superior que va a albergar un boton

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`index_box(self)`

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(*type=Gtk.Box*)

`dev_frm(self, frm)`

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

Parameters

frm: formulario anterior para su posterior cierre

(*type=Gtk.Windows*)

on_btn_crear_horario_clicked (<i>self, widget</i>)

Evento que funciona al accionar el boton de profesor
--

Parameters

widget: Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

on_btn_modificar_estudiante_clicked (<i>self, widget</i>)
--

Evento que funciona al accionar el boton de profesor
--

Parameters

widget: Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

Inherited from gi.overrides.Gtk.Container

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from ??.Container

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from gi.overrides.Gtk.Widget

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from ??.Widget

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

Inherited from gi.overrides.GObject.Object

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`, `weak_ref()`

Inherited from `??Object`

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

Inherited from `gi.gi.GObject`

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`,
`__new__()`, `__repr__()`, `__setattr__()`, `props()`

Inherited from `object`

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`,
`__subclasshook__()`

20.2.2 Properties

Name	Description
<i>Inherited from <code>??Window</code></i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??Container</code></i> widget	
<i>Inherited from <code>??Widget</code></i> parent_instance	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> g_type_instance, qdata, ref_count	
<i>Inherited from <code>gi.gi.GObject</code></i> __gpointer__, __grefcount__	
<i>Inherited from <code>object</code></i> __class__	

20.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmPrincipalEstudiante+Frm_Principal_Estudian...
<i>Inherited from <code>??Window</code></i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

21 Module view.frmPrincipalProfesor

21.1 Variables

Name	Description
__package__	Value: 'view'

Formulario principal del profesor

21.2.1 Methods

__init__(*self*)

Construtor de la clase Frm_Principal_Profesor, enfocado a la vista

Overrides: object.__init__

box1(*self*)

Construccion de la caja 1, caja superior que va a albergar un boton

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box2(*self*)

Construccion de la caja 2, caja media 1 que va a albergar dos botones referentes a estudiante

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box3(*self*)

Construccion de la caja 3, caja media 2 que va a albergar dos botones referentes a profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

box4(*self*)

Construccion de la caja 4, caja media 3 que va a albergar un boton sobre el profesor

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

index_box(*self*)

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(*type=Gtk.Box*)

dev_frm(*self*, *frm*)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

Parameters

frm: formulario anterior para su posterior cierre

(*type=Gtk.Windows*)

on_btn_lista_curso_clicked(*self*, *widget*)

Evento para btn de lista de cursos

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_crear_curso_clicked(*self*, *widget*)

Evento para btn de crear curso

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_crear_estudiante_clicked(*self*, *widget*)

Evento para btn de crear estudiante

Parameters

widget: Widget que esta relacionado al evento

(*type=Gtk.Widget*)

on_btn_borrar_estudiante_clicked(*self, widget*)

Evento para btn de borrar estudiante

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_crear_profesor_clicked(*self, widget*)

Evento para btn de crear profesor

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_borrar_profesor_clicked(*self, widget*)

Evento para btn de borrar profesor

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_modificar_profesor_clicked(*self, widget*)

Evento para btn de modificar profesor

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

Inherited from *gi.overrides.Gtk.Container*

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from *??Container*

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from *gi.overrides.Gtk.Widget*

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from *??Widget*

bind_template_callback_full(), bind_template_child_full(), find_style_property(), get_css_name(),
install_style_property(), list_style_properties(), set_accessible_role(), set_accessible_type(),
set_connect_func(), set_css_name(), set_template(), set_template_from_resource()

Inherited from gi.overrides.GObject.Object

__copy__(), __deepcopy__(), bind_property(), bind_property_full(), chain(), compat_control(),
connect(), connect_after(), connect_data(), connect_object(), connect_object_after(),
disconnect(), disconnect_by_func(), emit(), emit_stop_by_name(), force_floating(),
freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(),
handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(),
handler_unblock_by_func(), interface_find_property(), interface_install_property(),
interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), re-
place_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(),
steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(),
weak_ref()

Inherited from ??Object

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from gi._gi.GObject

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(),
__new__(), __repr__(), __setattr__(), props()

Inherited from object

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(),
__subclasshook__()

21.2.2 Properties

Name	Description
<i>Inherited from ??Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ??Container</i> widget	
<i>Inherited from ??Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	

continued on next page

Name	Description
<i>Inherited from object</i>	
__class__	

21.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmPrincipalProfesor+Frm_Principal_Profesor (...
<i>Inherited from ??Window</i> __info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	
<i>Inherited from gi.repository.Gtk.Bin</i> get_child	

continued on next page

Name	Description
<i>Inherited from ??Container</i>	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>


Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

22 Module view.frmRol

22.1 Variables

Name	Description
__package__	Value: 'view'

22.2 Class Frm_Rol



Clase en la que se va a poder seleccionar el rol

22.2.1 Methods

`__init__(self)`

Construtor de la clase Frm_Rol, enfocado a la vista

Overrides: `object.__init__`

`box1(self)`

Construccion de la caja 1, caja usuario

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`box2(self)`

Construccion de la caja 2, caja de pass

Return Value

Caja con entrada dentro

(*type=Gtk.Box*)

`box3(self)`

Construccion de la caja 3, caja inferior que va a albergar los botones

Return Value

Caja con boton dentro

(*type=Gtk.Box*)

`index_box(self)`

Construccion de la caja Principal, caja principal que se va a mostrar

Return Value

Caja con cajas dentro

(*type=Gtk.Box*)

`dev_frm(self)`

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

on_btn_guardar_clicked(*self, widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_borrar_clicked(*self, widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

on_btn_salir_clicked(*self, widget*)

Evento para button cuando este se hace clic

Parameters

widget: Widget que esta relacionado al evento
(*type=Gtk.Widget*)

Inherited from gi.overrides.Gtk.Container

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from ??.Container

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from gi.overrides.Gtk.Widget

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from ??.Widget

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

Inherited from gi.overrides.GObject.Object

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`,

freeze_notify(), get_data(), get_properties(), get_property(), get_qdata(), handler_block(), handler_block_by_func(), handler_disconnect(), handler_is_connected(), handler_unblock(), handler_unblock_by_func(), interface_find_property(), interface_install_property(), interface_list_properties(), notify_by_pspec(), ref(), ref_sink(), replace_data(), replace_qdata(), run_dispose(), set_data(), set_properties(), set_property(), steal_data(), steal_qdata(), stop_emission(), stop_emission_by_name(), unref(), watch_closure(), weak_ref()

Inherited from `??Object`

find_property(), install_properties(), install_property(), list_properties(), override_property()

Inherited from `gi._gi.GObject`

__delattr__(), __eq__(), __gdoc__(), __ge__(), __gt__(), __hash__(), __le__(), __lt__(), __ne__(), __new__(), __repr__(), __setattr__(), props()

Inherited from `object`

__format__(), __getattr__(), __reduce__(), __reduce_ex__(), __sizeof__(), __str__(), __subclasshook__()

22.2.2 Properties

Name	Description
<i>Inherited from <code>??Window</code></i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??Container</code></i> widget	
<i>Inherited from <code>??Widget</code></i> parent_instance	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> g_type_instance, qdata, ref_count	
<i>Inherited from <code>gi._gi.GObject</code></i> __gpointer__, __grefcount__	
<i>Inherited from <code>object</code></i> __class__	

22.2.3 Class Variables

Name	Description
__gtype__	Value: <GType view+frmRol+Frm_Rol (94499140896112)>

continued on next page

Name	Description
<i>Inherited from ??Window</i>	__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick
<i>Inherited from gi.repository.Gtk.Bin</i>	get_child
<i>Inherited from ??Container</i>	

continued on next page

Name	Description
	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>


Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

23 Module *view.scroll*

23.1 Variables

Name	Description
<code>software_list</code>	Value: [('Firefox', 2002, 'C++'), ('Eclipse', 2004, 'Java'), ('P...
<code>win</code>	Value: <scroll.TreeViewFilterWindow object at 0x7f9f669502d0 (vi...
<code>--package--</code>	Value: 'view'
<code>--warningregistry--</code>	Value: {'Using positional arguments with the GObject constructo...

23.2 Class `TreeViewFilterWindow`



23.2.1 Methods**`__init__(self)`**

Initializer for a GObject based classes with support for property sets through the use of explicit keyword arguments.

Overrides: `object.__init__` `exitit`(inherited documentation)

`language_filter_func(self, model, iter, data)`

Tests if the language in the row is the one in the filter

`on_selection_button_clicked(self, widget)`

Called on any of the button clicks

Inherited from `gi.overrides.Gtk.Container`

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

Inherited from `??Container`

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

Inherited from `gi.overrides.Gtk.Widget`

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

Inherited from `??Widget`

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

Inherited from `gi.overrides.GObject.Object`

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`

`weak_ref()`

Inherited from `??Object`

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

Inherited from `gi.GiObject`

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`, `__new__()`, `__repr__()`, `__setattr__()`, `props()`

Inherited from `object`

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

23.2.2 Properties

Name	Description
<i>Inherited from <code>??Window</code></i> <code>bin</code> , <code>priv</code>	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> <code>container</code>	
<i>Inherited from <code>??Container</code></i> <code>widget</code>	
<i>Inherited from <code>??Widget</code></i> <code>parent_instance</code>	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> <code>g_type_instance</code> , <code>qdata</code> , <code>ref_count</code>	
<i>Inherited from <code>gi.GiObject</code></i> <code>__gpointer__</code> , <code>__grefcount__</code>	
<i>Inherited from <code>object</code></i> <code>__class__</code>	

23.2.3 Class Variables

Name	Description
<code>__gtype__</code>	Value: <code><GType view+scroll+TreeViewFilterWindow (94499132910960)></code>
<i>Inherited from <code>??Window</code></i>	

continued on next page

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from <code>??Widget</code></i>	

continued on next page

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus⁴⁴⁸_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

Index

- `__main__` (*module*), 4
- `__main__.run` (*function*), 4
- `model` (*package*), 5
 - `model.Ciudad` (*module*), 6
 - `model.Ciudad.Ciudad` (*class*), 6
 - `model.Curso` (*module*), 7–8
 - `model.Curso.Curso` (*class*), 7–8
 - `model.Departamento` (*module*), 9
 - `model.Departamento.Departamento` (*class*), 9
 - `model.Estudiante` (*module*), 10–11
 - `model.Estudiante.Estudiante` (*class*), 10–11
 - `model.Horario` (*module*), 12
 - `model.Horario.Horario` (*class*), 12
 - `model.Persona` (*module*), 13–15
 - `model.Persona.Persona` (*class*), 13–15
 - `model.Planificacion` (*module*), 16
 - `model.Planificacion.Planificacion` (*class*), 16
 - `model.Profesor` (*module*), 17–19
 - `model.Profesor.Profesor` (*class*), 17–19
- `view` (*package*), 20
 - `view.frmCrearCurso` (*module*), 21–31
 - `view.frmCrearCurso.Frm_Crear_Curso` (*class*), 21–31
 - `view.frmCrearEstudiante` (*module*), 32–43
 - `view.frmCrearEstudiante.Frm_Crear_Estudiante` (*class*), 32–43
 - `view.frmCrearHorario` (*module*), 44–54
 - `view.frmCrearHorario.Frm_Crear_Horario` (*class*), 44–54
 - `view.frmCrearNombramiento` (*module*), 55–65
 - `view.frmCrearNombramiento.Frm_Crear_Nombramiento` (*class*), 55–65
 - `view.frmCrearProfesor` (*module*), 66–78
 - `view.frmCrearProfesor.Frm_Crear_Profesor` (*class*), 66–78
 - `view.frmListaCursos` (*module*), 79–88
 - `view.frmListaCursos.Frm_Lista_Curso` (*class*), 79–88
 - `view.frmListaEstudiante` (*module*), 89–99
 - `view.frmListaEstudiante.Frm_Lista_Estudiante` (*class*), 89–99
 - `view.frmListaProfesor` (*module*), 100–109
 - `view.frmListaProfesor.Frm_Lista_Profesor` (*class*), 100–109
 - `view.frmPrincipalEstudiante` (*module*), 110–119
 - `view.frmPrincipalEstudiante.Frm_Principal_Estudiante` (*class*), 110–119
 - `view.frmPrincipalProfesor` (*module*), 120–130
 - `view.frmPrincipalProfesor.Frm_Principal_Profesor` (*class*), 120–130
 - `view.frmRol` (*module*), 131–140
 - `view.frmRol.Frm_Rol` (*class*), 131–140
 - `view.scroll` (*module*), 141–149
 - `view.scroll.TreeViewFilterWindow` (*class*), 141–149