

doc

## API Documentation

May 9, 2018

## Contents

<b>Contents</b>	<b>1</b>
<b>1 Module __main__</b>	<b>5</b>
1.1 Functions . . . . .	5
1.2 Variables . . . . .	5
<b>2 Package model</b>	<b>6</b>
2.1 Modules . . . . .	6
2.2 Variables . . . . .	6
<b>3 Module model.Ciudad</b>	<b>7</b>
3.1 Variables . . . . .	7
3.2 Class Ciudad . . . . .	7
3.2.1 Methods . . . . .	7
<b>4 Module modelCurso</b>	<b>8</b>
4.1 Variables . . . . .	8
4.2 Class Curso . . . . .	8
4.2.1 Methods . . . . .	8
<b>5 Module model.Departamento</b>	<b>10</b>
5.1 Variables . . . . .	10
5.2 Class Departamento . . . . .	10
5.2.1 Methods . . . . .	10
<b>6 Module model.Estudiante</b>	<b>11</b>
6.1 Variables . . . . .	11
6.2 Class Estudiante . . . . .	11
6.2.1 Methods . . . . .	11
6.2.2 Properties . . . . .	12
6.2.3 Class Variables . . . . .	12
<b>7 Module model.Horario</b>	<b>13</b>
7.1 Variables . . . . .	13
7.2 Class Horario . . . . .	13
7.2.1 Methods . . . . .	13
<b>8 Module model.Persona</b>	<b>14</b>

8.1	Variables . . . . .	14
8.2	Class Persona . . . . .	14
8.2.1	Methods . . . . .	15
8.2.2	Properties . . . . .	16
<b>9</b>	<b>Module model.Planificacion</b>	<b>17</b>
9.1	Variables . . . . .	17
9.2	Class Planificacion . . . . .	17
9.2.1	Methods . . . . .	17
<b>10</b>	<b>Module model.Profesor</b>	<b>18</b>
10.1	Variables . . . . .	18
10.2	Class Profesor . . . . .	18
10.2.1	Methods . . . . .	19
10.2.2	Properties . . . . .	20
<b>11</b>	<b>Module model.conector</b>	<b>21</b>
11.1	Variables . . . . .	21
11.2	Class Conexion . . . . .	21
11.2.1	Methods . . . . .	21
11.2.2	Class Variables . . . . .	22
11.2.3	Instance Variables . . . . .	22
<b>12</b>	<b>Package view</b>	<b>23</b>
12.1	Modules . . . . .	23
12.2	Variables . . . . .	23
<b>13</b>	<b>Module view.frmCrearCurso</b>	<b>24</b>
13.1	Variables . . . . .	24
13.2	Class Frm_Crear_Curso . . . . .	26
13.2.1	Methods . . . . .	27
13.2.2	Properties . . . . .	30
13.2.3	Class Variables . . . . .	31
<b>14</b>	<b>Module view.frmCrearEstudiante</b>	<b>35</b>
14.1	Variables . . . . .	35
14.2	Class Frm_Crear_Estudiante . . . . .	37
14.2.1	Methods . . . . .	38
14.2.2	Properties . . . . .	42
14.2.3	Class Variables . . . . .	43
<b>15</b>	<b>Module view.frmCrearHorario</b>	<b>48</b>
15.1	Variables . . . . .	48
15.2	Class Frm_Crear_Horario . . . . .	50
15.2.1	Methods . . . . .	51
15.2.2	Properties . . . . .	53
15.2.3	Class Variables . . . . .	54
<b>16</b>	<b>Module view.frmCrearNombramiento</b>	<b>59</b>
16.1	Variables . . . . .	59
16.2	Class Frm_Crear_Nombramiento . . . . .	61
16.2.1	Methods . . . . .	62
16.2.2	Properties . . . . .	64

16.2.3 Class Variables . . . . .	65
<b>17 Module view.frmCrearProfesor</b>	<b>70</b>
17.1 Variables . . . . .	70
17.2 Class Frm_Crear_Profesor . . . . .	72
17.2.1 Methods . . . . .	73
17.2.2 Properties . . . . .	78
17.2.3 Class Variables . . . . .	79
<b>18 Module view.frmListaCursos</b>	<b>83</b>
18.1 Variables . . . . .	83
18.2 Class Frm_Lista_Curso . . . . .	85
18.2.1 Methods . . . . .	86
18.2.2 Properties . . . . .	89
18.2.3 Class Variables . . . . .	89
<b>19 Module view.frmListaEstudiante</b>	<b>94</b>
19.1 Variables . . . . .	94
19.2 Class Frm_Lista_Estudiante . . . . .	96
19.2.1 Methods . . . . .	97
19.2.2 Properties . . . . .	101
19.2.3 Class Variables . . . . .	101
<b>20 Module view.frmListaProfesor</b>	<b>106</b>
20.1 Variables . . . . .	106
20.2 Class Frm_Lista_Profesor . . . . .	108
20.2.1 Methods . . . . .	109
20.2.2 Properties . . . . .	112
20.2.3 Class Variables . . . . .	113
<b>21 Module view.frmPrincipalEstudiante</b>	<b>118</b>
21.1 Variables . . . . .	118
21.2 Class Frm_Principal_Estudiante . . . . .	120
21.2.1 Methods . . . . .	121
21.2.2 Properties . . . . .	123
21.2.3 Class Variables . . . . .	123
<b>22 Module view.frmPrincipalProfesor</b>	<b>128</b>
22.1 Variables . . . . .	128
22.2 Class Frm_Principal_Profesor . . . . .	130
22.2.1 Methods . . . . .	131
22.2.2 Properties . . . . .	134
22.2.3 Class Variables . . . . .	134
<b>23 Module view.frmRol</b>	<b>139</b>
23.1 Variables . . . . .	139
23.2 Class Frm_Rol . . . . .	141
23.2.1 Methods . . . . .	142
23.2.2 Properties . . . . .	144
23.2.3 Class Variables . . . . .	144
<b>24 Module view.scroll</b>	<b>149</b>
24.1 Variables . . . . .	149

---

24.2 Class TreeViewFilterWindow . . . . .	151
24.2.1 Methods . . . . .	152
24.2.2 Properties . . . . .	153
24.2.3 Class Variables . . . . .	153
<b>Index</b>	<b>158</b>

## 1 Module `__main__`

### 1.1 Functions

<b>run()</b>
Metodo de inicializacion

### 1.2 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> None

## 2 Package model

### 2.1 Modules

- **Ciudad** (*Section 3, p. 7*)
- **Curso** (*Section 4, p. 8*)
- **Departamento** (*Section 5, p. 10*)
- **Estudiante** (*Section 6, p. 11*)
- **Horario** (*Section 7, p. 13*)
- **Persona** (*Section 8, p. 14*)
- **Planificacion** (*Section 9, p. 17*)
- **Profesor** (*Section 10, p. 18*)
- **conector** (*Section 11, p. 21*)

### 2.2 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> None

### 3 Module model.Ciudad

#### 3.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> None

#### 3.2 Class Ciudad

Clase Ciudad, con datos especificos del mismo

##### 3.2.1 Methods

<b><code>--init--(self, nombre, descripcion, id=0)</code></b> Constructor de Ciudad <b>Parameters</b> <b>nombre:</b> Nombre de la Ciudad <i>(type=str)</i> <b>descripcion:</b> descripcion de la Ciudad <i>(type=str)</i> <b>id:</b> Identificacion de la Ciudad <i>(type=integer)</i>
<b><code>--str--(self)</code></b> Convierte clase a str <b>Return Value</b> Str convertido de la clase <i>(type=str)</i>
<b><code>set_id(self, id)</code></b> Modifica id de la ciudad <b>Parameters</b> <b>id:</b> Identificacion nueva <i>(type=integer)</i>
<b><code>get_nom(self)</code></b> Retorna Nombre de la Ciudad <b>Return Value</b> Nombre de la Ciudad <i>(type=str)</i>

## 4 Module model.Curso

### 4.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> 'model'

### 4.2 Class Curso

Clase Curso

#### 4.2.1 Methods

<b><code>--init--(self, nombre, aula, tiempo, dia_reunion, edificio, id=0)</code></b>	
Constructor de clase Curso	
<b>Parameters</b>	
<b>nombre:</b>	Nombre del Curso ( <i>type=str</i> )
<b>aula:</b>	Aula donde se va hacer el curso ( <i>type=str</i> )
<b>id:</b>	Identificacion del curso ( <i>type=integer</i> )
<b>tiempo:</b>	Tiempo en horas del curso ( <i>type=double</i> )
<b>dia_reunion:</b>	Fecha de Reunion ( <i>type=datetime</i> )
<b>edificio:</b>	Edificio donde es el lugar de Reunion ( <i>type=str</i> )
<b><code>--str--(self)</code></b>	
Conversion de Clase a str	
<b>Return Value</b>	
Conversion de Clase ( <i>type=str</i> )	



---

**set\_profesor**(*self*, *profesor*)

Pone profesor a cargo del curso

**Parameters**

**profesor:** Profesor encargado del curso  
(*type=Profesor*)

## 5 Module model.Departamento

### 5.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> None

### 5.2 Class Departamento

Clase Departamento

#### 5.2.1 Methods


<b><code>--init--(self, nombre, ciudad, telefono, id=0)</code></b>	
Constructor de clase Departamento	
<b>Parameters</b>	
<b>nombre:</b>	Nombre del Departamento ( <i>type=str</i> )
<b>ciudad:</b>	Ciudad donde esta el Departamento ( <i>type=Ciudad</i> )
<b>telefono:</b>	Telefono de contacto del Departamento ( <i>type=integer</i> )
<b>id:</b>	Identificacion de Departamento ( <i>type=integer</i> )
<b><code>--str--(self)</code></b>	
Conversion de clase a str	
<b>Return Value</b>	
Conversion de clase ( <i>type=str</i> )	

## 6 Module *model.Estudiante*

### 6.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> <code>'model'</code>

### 6.2 Class *Estudiante*



Clase de los estudiantes

#### 6.2.1 Methods

```
__init__(self, datos=None, num=0, nombre1='1', nombre2='1', apellido1='1',
apellido2='1', edad=1, lug_nacimiento=1, lug_residencia=1, dir_residencia='1',
semestre=1, usuario='1', contra='1')
```

Constructor de estudiante, tiene datos de persona, quien es su super-clase; Convierte una tupla y la genera en su respectiva clase, se identifica con ella para su tratamiento

**Parameters**

**datos:** datos en forma de tupla que se obtienen de una relacion de datos  
(*type=tuple*)

Overrides: `object.__init__`

```
es_is_graduado(self)
```

Retorna en español si esta graduado o no

**Return Value**

Retorno de graduado en español  
(*type=str*)

```
__str__(self)
```

Conversion de clase a str de Estudiante

**Return Value**

Clase convertida a str  
(*type=str*)

Overrides: `object.__str__`

<b>set_consejero</b> ( <i>self</i> , <i>consejero</i> )
---

Pone consejero a estudiante solo si esta graduado
---

<b>Parameters</b>
-------------------

<b>consejero:</b> Profesor consejero que esta disponible ( <i>type=Profesor</i> )
--

<b>Return Value</b>
---------------------

retrona true si se puso consejero correctamente y false de no se estudiante graduado ( <i>type=bool</i> )
--

<b>set_horario</b> ( <i>self</i> , <i>horario</i> )
---

Modifica y relaciona el horario dado
--------------------------------------

<b>Parameters</b>
-------------------

<b>horario:</b> Horario que se va a vincular a estudiante ( <i>type=Horario</i> )
--

**Inherited from object**

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__subclasshook__()`

**6.2.2 Properties**

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

**6.2.3 Class Variables**

Name	Description
<code>consejero</code>	<b>Value:</b> None

## 7 Module model.Horario

### 7.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> 'model'

### 7.2 Class Horario

Clase horario

#### 7.2.1 Methods

<b><code>--init--(self, curso, fecha_inicio, fecha_fin, semestre)</code></b>	
Construccion del horario del estudiante	
<b>Parameters</b>	
<b>curso:</b>	Curso Vinnclado al horario ( <i>type=Curso</i> )
<b>fecha_inicio:</b>	Fecha de inicio de clase ( <i>type=datetime</i> )
<b>fecha_fin:</b>	Fecha de finalizacion de clase ( <i>type=datetime</i> )
<b>semestre:</b>	Semestre que esta ubicado el horario ( <i>type=int</i> )
<b><code>--str--(self)</code></b>	
Conversion de clase a str de Horario	
<b>Return Value</b>	
Clase convertida a str ( <i>type=str</i> )	

## 8 Module *model.Persona*

### 8.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> None

### 8.2 Class *Persona*

object  **model.Persona.Persona**

**Known Subclasses:** *model.Estudiante.Estudiante*, *model.Profesor.Profesor*

Representacion de los datos basicos de la persona

### 8.2.1 Methods

```
__init__(self, num, nombre1, nombre2, apellido1, apellido2, edad,  
lug_nacimiento, ciu_residencia, dir_residencia, usuario, contra)
```

Constructor de Persona

#### Parameters

<b>num:</b>	Numero de identificacion, Unico e Irrepetible ( <i>type=integer</i> )
<b>nombre1:</b>	Primer nombre ( <i>type=str</i> )
<b>nombre2:</b>	Segundo nombre ( <i>type=str</i> )
<b>apellido1:</b>	Primer apellido ( <i>type=str</i> )
<b>apellido2:</b>	Segundo apellido ( <i>type=str</i> )
<b>edad:</b>	Edad de persona ( <i>type=int</i> )
<b>lug_nacimiento:</b>	Lugar de nacimiento ( <i>type=Ciudad</i> )
<b>ciu_residencia:</b>	Ciudad de Residencia ( <i>type=Ciudad</i> )
<b>dir_residencia:</b>	Direccin de Residencia ( <i>type=str</i> )
<b>usuario:</b>	Nombre de usuario ( <i>type=str</i> )
<b>contra:</b>	Contraseña para usuario ( <i>type=str</i> )

Overrides: object.\_\_init\_\_

<b><code>--str--(self)</code></b>
Conversion a str de clase
<b>Return Value</b>
Datos de clase en str
<i>(type=str)</i>
Overrides: <code>object.__str__</code>

***Inherited from object***

`--delattr--()`, `--format--()`, `--getattr--()`, `--hash--()`, `--new--()`, `--reduce--()`, `--reduce_ex--()`,  
`--repr--()`, `--setattr--()`, `--sizeof--()`, `--subclasshook--()`

**8.2.2 Properties**

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	



## 9 Module model.Planificacion

## 9.1 Variables

Name	Description
--package--	Value: None

## 9.2 Class Planificacion

### Clase de Planificacion de los estudiantes

### 9.2.1 Methods


<b>--init--</b> ( <i>self, semestre, id_estudiante, id_curso</i> )	
Constructor de clase de Planificacion	
<b>Parameters</b>	
<b>id_estudiante:</b>	Codigo unico del estudiante ( <i>type=integer</i> )
<b>id_curso:</b>	Codigo unico del curso ( <i>type=integer</i> )
<b>semestre:</b>	Semestre en el que el estudiante se inscribio ( <i>type=integer</i> )
<b>--str--</b> ( <i>self</i> )	
Conversion de clase a str	
<b>Return Value</b>	
Conversion de clase ( <i>type=str</i> )	
<b>set_nota</b> ( <i>self, nota</i> )	
Poner nota al estudiante que esta inscrito en el curso	
<b>Parameters</b>	
<b>nota:</b>	Nota obtenida del curso ( <i>type=double</i> )

## 10 Module model.Profesor

### 10.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> <code>'model'</code>

### 10.2 Class Profesor



## 10.2.1 Methods

```
__init__(self, datos=None, num=1, nombre1='1', nombre2='1',
apellido1='1', apellido2='1', edad=1, lug_nacimiento=1, lug_residencia=1,
dir_residencia='1', titulo='1', contrato='1', usuario='1', contra='1',
ini_nombramiento=None, fin_nombramiento=None, departamento=1)
```

Constructor de clase de Profesor; Constructor especificado para la implementacion directa de diseño de labase de datos a traves de la tupla

**Parameters**

<b>is_visitante:</b>	Obtener si un profesor es visitante o no ( <i>type=bool</i> )
<b>titulo:</b>	Titulo obtenido ( <i>type=str</i> )
<b>contrato:</b>	Contrato que se ha firmado ante la universidad para ejercer enseñanza ( <i>type=str</i> )
<b>ini_nombramiento:</b>	Fecha de inicio de Nombramiento solo si es profesor visitante ( <i>type=datetime</i> )
<b>fin_nombramiento:</b>	Fecha de fin de Nombramiento solo si es profesor visitante ( <i>type=datetime</i> )
<b>datos:</b>	Tupla con los datos del profesor listos para ser identificados en la clase ( <i>type=tuple</i> )

Overrides: object.\_\_init\_\_

```
es_is_visitante(self)
```

Retorna en español si esta visitante o no

**Return Value**

Retorno de visitante en español  
(*type=str*)

<b><code>--str--(self)</code></b>
Conversion de clase a str de Profesor
<b>Return Value</b>
Datos de clase en str
<i>(type=str)</i>
Overrides: object.--str--

<b><code>set_departamento(self, departamento)</code></b>
Pone el profesor en un departamento
<b>Parameters</b>
departamento: Departamento a cambiar
<i>(type=Departamento)</i>

<b><code>set_ini_nombramiento(self, fecha)</code></b>
Modifica la fecha de inicio de nombramiento
<b>Parameters</b>
fecha: Fecha de nombramiento_ini
<i>(type=date)</i>

<b><code>set_fin_nombramiento(self, fecha)</code></b>
Modifica la fecha de fin de nombramiento
<b>Parameters</b>
fecha: Fecha de nombramiento_fin
<i>(type=date)</i>

### *Inherited from object*

`--delattr--()`, `--format--()`, `--getattr--()`, `--hash--()`, `--new--()`, `--reduce--()`, `--reduce_ex--()`, `--repr--()`, `--setattr--()`, `--sizeof--()`, `--subclasshook--()`

### 10.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>--class--</code>	

## 11 Module model.conector

### 11.1 Variables

Name	Description
<code>__package__</code>	<b>Value:</b> 'model'

### 11.2 Class Conexion

Clase para la consolidacion con la base de datos

#### 11.2.1 Methods

<b><code>__init__(self)</code></b>
Variables características para la conexión de base de datos, variables características para el uso de la misma

<b><code>enviar_registro(self, query)</code></b>
<p>Una consulta caracterizada por el envío de información, nada de traer datos, ya que</p> <ul style="list-style-type: none"> <li>- estructura funciona de la siguiente manera: "insert into people values (%s, %s)"</li> <li>- datos funciona como los datos arrojados para ser enviados</li> </ul> <p>@param estructura: Variable característica que enfoca en enviar la consulta como un</p> <p>@type estructura: str</p> <p>@return: Valor 1 o 0 según sea el caso de ingreso</p> <p>@rtype: int</p>

**enviar\_consulta**(*self*, *query*)

Con enviar consulta, unicamente se envia la consulta ya tratada con los datos ingresados en un str y puestas para enviarse a DB

**Parameters**

**query:** consulta que se desea enviar

**query:** (*type=*str)

**Return Value**

lista de consulta de salida de datos tomado de la base de datos

(*type=<class 'list'>*)

**conector**(*self*)

variable principal que se caracteriza por tener los datos de la conexion de base de datos

### 11.2.2 Class Variables

Name	Description
conn	<b>Value:</b> None

### 11.2.3 Instance Variables

Name	Description
dispositivo	<p>Explicacion del dispositivo:</p> <ul style="list-style-type: none"> <li>- self.dispositivo = "localhost" or "127.0.0.1"</li> </ul> <p>Datos dispositivo actual</p>

## 12 Package view

### 12.1 Modules

- **frmCrearCurso** (*Section 13, p. 24*)
- **frmCrearEstudiante** (*Section 14, p. 35*)
- **frmCrearHorario** (*Section 15, p. 48*)
- **frmCrearNombramiento** (*Section 16, p. 59*)
- **frmCrearProfesor** (*Section 17, p. 70*)
- **frmListaCursos** (*Section 18, p. 83*)
- **frmListaEstudiante** (*Section 19, p. 94*)
- **frmListaProfesor** (*Section 20, p. 106*)
- **frmPrincipalEstudiante** (*Section 21, p. 118*)
- **frmPrincipalProfesor** (*Section 22, p. 128*)
- **frmRol** (*Section 23, p. 139*)
- **scroll** (*Section 24, p. 149*)

### 12.2 Variables

Name	Description
__package__	<b>Value:</b> None

## 13 Module view.frmCrearCurso


### 13.1 Variables

Name	Description
__package__	Value: 'view'





## 13.2 Class Frm\_Crear\_Curso



Clase en la que se va a poder crear o modificar curso

### 13.2.1 Methods

**`__init__(self, profesor=0, datos=None)`**

Construtor de la clase Frm\_Crear\_Curso, enfocado a la vista

**Parameters**

**profesor:** Dato importante del profesor encargado  
(*type=int*)

Overrides: object.\_\_init\_\_

**`box1(self)`**

Construccion de la caja 1, caja superior que va a dato acerca del curso

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**`box2(self)`**

Construccion de la caja 2, caja intermedia que va a dato acerca del curso

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**`box3(self)`**

Construccion de la caja 3, caja intermedia que va a dato acerca del curso

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**`box4(self)`**

Construccion de la caja 3, caja intermedia que va a dato acerca del curso

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**box5(*self*)**

Construccion de la caja 3, caja intermedia que va a dato acerca del curso

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box6(*self*)**

Construccion de la caja 6, caja final, da a los botones

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**cargar\_datos(*self*)**

Datos especificamente obtenidos de la base de datos puestos en el departamento

**solo\_nombre(*self*, *tupla*)**

Proceso funcional para que solo se tome el atributo de la posicion 1

**Parameters**

*tupla*: Tupla

(*type=tuple*)

**Return Value**

datos str con el nombre

(*type=str*)

**index\_box(*self*)**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(*type=Gtk.Box*)

**dev\_frm(*self*)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

<b>on_btn_guardar_clicked</b> ( <i>self</i> , <i>widget</i> )
---

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget</b> : Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
---

<b>modificar</b> ( <i>self</i> )
----------------------------------

Especializacion de Modificar
------------------------------

<b>eliminar</b> ( <i>self</i> )
---------------------------------

Especializacion de eliminar
-----------------------------

<b>on_btn_borrar_clicked</b> ( <i>self</i> , <i>widget</i> )
--

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget</b> : Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
---

<b>on_btn_salir_clicked</b> ( <i>self</i> , <i>widget</i> )
---

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget</b> : Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
---

***Inherited from gi.overrides.Gtk.Container***

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

***Inherited from ??.Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

***Inherited from gi.overrides.Gtk.Widget***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

***Inherited from ??.Widget***

bind\_template\_callback\_full(), bind\_template\_child\_full(), find\_style\_property(), get\_css\_name(), install\_style\_property(), list\_style\_properties(), set\_accessible\_role(), set\_accessible\_type(), set\_connect\_func(), set\_css\_name(), set\_template(), set\_template\_from\_resource()

### ***Inherited from gi.overrides.GObject.Object***

\_\_copy\_\_(), \_\_deepcopy\_\_(), bind\_property(), bind\_property\_full(), chain(), compat\_control(), connect(), connect\_after(), connect\_data(), connect\_object(), connect\_object\_after(), disconnect(), disconnect\_by\_func(), emit(), emit\_stop\_by\_name(), force\_floating(), freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(), handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(), handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(), interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), replace\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(), steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(), weak\_ref()

### ***Inherited from ?? .Object***

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

### ***Inherited from gi.\_gi.GObject***

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(), \_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

### ***Inherited from object***

\_\_format\_\_(), \_\_getattr\_\_(), \_\_reduce\_\_(), \_\_reduce\_ex\_\_(), \_\_sizeof\_\_(), \_\_str\_\_(), \_\_subclasshook\_\_()

## **13.2.2 Properties**

Name	Description
<i>Inherited from ?? .Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ?? .Container</i> widget	
<i>Inherited from ?? .Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	

*continued on next page*

Name	Description
<i>Inherited from object</i>	
__class__	

### 13.2.3 Class Variables

Name	Description
__gtype__	<b>Value:</b> <GType view+frmCrearCurso+Frm_Crear_Curso (94027599166416)>
<i>Inherited from ??Window</i> __info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	
<i>Inherited from gi.repository.Gtk.Bin</i> get_child	

*continued on next page*

Name	Description
<i>Inherited from ??Container</i>	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

*continued on next page*



Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus3_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	


## 14 Module view.frmCrearEstudiante

### 14.1 Variables

Name	Description
__package__	Value: 'view'



## 14.2 Class Frm\_Crear\_Estudiante



Clase en la que se va a poder crear o modificar estudiante

#### 14.2.1 Methods

**`__init__(self, profesor=None)`**

Construtor de la clase Frm\_Crear\_Estudiante, enfocado a la vista

Overrides: `object.__init__`

**`box1(self)`**

Construccion de la caja 1, caja superior que va a dato acerca del estudiante enfocado en el codigo del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**`box2(self)`**

Construccion de la caja 2, caja intermedia que va a dato acerca del estudiante enfocado en el nombre 1 del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**`box3(self)`**

Construccion de la caja 3, caja intermedia que va a dato acerca del estudiante enfocado en el nombre 2 del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**`box4(self)`**

Construccion de la caja 4, caja intermedia que va a dato acerca del estudiante enfocado en el Apellido 1 del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box5(*self*)**

Construccion de la caja 5, caja intermedia que va a dato acerca del estudiante enfocado en el Apellido 2 del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box6(*self*)**

Construccion de la caja 6, caja intermedia que va a dato acerca del estudiante enfocado en la edad del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box7(*self*)**

Construccion de la caja 7, caja intermedia que va a dato acerca del estudiante enfocado en el lugar de nacimiento del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box8(*self*)**

Construccion de la caja 8, caja intermedia que va a dato acerca del estudiante enfocado en el lugar de residencia del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box9(*self*)**

Construccion de la caja 9, caja intermedia que va a dato acerca del estudiante enfocado en la direccion de residencia del estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box10(self)**

Construccion de la caja 10, caja intermedia que va a dato acerca del estudiante enfocado en la semestre del estudiante

**Return Value**

Caja con boton dentro

(type=Gtk.Box)

**box11(self)**

Construccion de la caja 11, caja intermedia que va a dato acerca del estudiante enfocado en el usuario del estudiante

**Return Value**

Caja con boton dentro

(type=Gtk.Box)

**box12(self)**

Construccion de la caja 12, caja intermedia que va a dato acerca del estudiante enfocado en la contraseña del estudiante

**Return Value**

Caja con boton dentro

(type=Gtk.Box)

**box13(self)**

Construccion de la caja 13, caja final, da a los botones

**Return Value**

Caja con boton dentro

(type=Gtk.Box)

**index\_box(self)**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(type=Gtk.Box)



**dev\_frm(*self*)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**cargar\_datos(*self*)**

Datos especificamente obtenidos de la base de datos puestos en la ciudad

**solo\_nombre\_ciudad(*self*, *ciudad*)**

Proceso funcional para que solo se tome el nombre de la ciudad en una entrada tupla

**Parameters**

**ciudad:** Tupla con datos de una sola ciudad  
(*type=tuple*)

**Return Value**

datos str con el nombre de la ciudad  
(*type=str*)

**on\_btn\_guardar\_clicked(*self*, *widget*)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_borrar\_clicked(*self*, *widget*)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_salir\_clicked(*self*, *widget*)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

*Inherited from gi.overrides.Gtk.Container*

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`,  
`child_set()`, `get_focus_chain()`

### ***Inherited from `??`.Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`,  
`list_child_properties()`

### ***Inherited from `gi.overrides.Gtk.Widget`***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

### ***Inherited from `??`.Widget***

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`,  
`install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`,  
`set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

### ***Inherited from `gi.overrides.GObject.Object`***

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`,  
`connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`,  
`disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`,  
`freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`,  
`handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`,  
`handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`,  
`interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`,  
`run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`,  
`steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`,  
`weak_ref()`

### ***Inherited from `??`.Object***

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

### ***Inherited from `gi._gi.GObject`***

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`,  
`__new__()`, `__repr__()`, `__setattr__()`, `props()`

### ***Inherited from `object`***

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`,  
`__subclasshook__()`

## **14.2.2 Properties**

Name	Description
<i>Inherited from ??.</i> Window	
bin, priv	
<i>Inherited from gi.repository.Gtk.</i> Bin	
container	
<i>Inherited from ??.</i> Container	
widget	
<i>Inherited from ??.</i> Widget	
parent_instance	
<i>Inherited from gi.repository.GObject.</i> InitiallyUnowned	
g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.</i> GObject	
__gpointer__, __grefcount__	
<i>Inherited from object</i>	
__class__	

#### 14.2.3 Class Variables

Name	Description
--gtype--	<b>Value:</b> <GType view+frmCrearEstudiante+Frm_Crear_Estudiente (9402...
<i>Inherited from ??.</i> Window	

*continued on next page*

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

## 15 Module *view.frmCrearHorario*

### 15.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> 'view'







Clase enfocda en la construccion del horario, tiene permiso desde el formulario principal del estudiante

### 15.2.1 Methods

**\_\_init\_\_**(*self*, *estudiante*, *curso*)

Constructor de la clase Frm\_Crear\_Horario, enfocado en la construccion de la creacion del horario, antes de cargar este formulario habra que cargar varias cosas, como lo pueden ser la lista de estudiantes y cursos

**Parameters**

**estudiante:** id del estudiante seleccionado previamente

(*type=int*)

**curso:** codigo del curso seleccionado previamente

(*type=int*)

Overrides: object.\_\_init\_\_

**box1**(*self*)

Construccion de la caja1, caja superior que va a reunir los datos acerca del horario

**Return Value**

Caja con comboBox Adentro

(*type=Gtk.Box*)

**box2**(*self*)

Construccion de la caja 2, caja intermedia enfocada en la presentacion la construccion del calendario en pantalla para su posterior seleccion

**box3**(*self*)

Construccion de la caja 3, caja intermedia enfocada en la presentacion la construccion del calendario en pantalla para su posterior seleccion

**box4**(*self*)

Construccion de la caja 4, caja final, da a los botones

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**index\_box(*self*)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrara alguna propiedades del mismo

**dev\_frm(*self*)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**on\_cb\_semestre\_changed(*self*, *widget*)**

Metodo enfocado en ejecutar el evento del combobox para el cambio de semestre

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_guardar\_clicked(*self*, *widget*)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_borrar\_clicked(*self*, *widget*)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_salir\_clicked(*self*, *widget*)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**Inherited from *gi.overrides.Gtk.Container***

`--bool--()`, `--contains--()`, `--iter--()`, `--len--()`, `--nonzero--()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

***Inherited from `??`.Container***

find\_child\_property(), handle\_border\_width(), install\_child\_properties(), install\_child\_property(), list\_child\_properties()

***Inherited from `gi.overrides.Gtk.Widget`***

drag\_dest\_set\_target\_list(), drag\_source\_set\_target\_list(), style\_get\_property(), translate\_coordinates()

***Inherited from `??`.Widget***

bind\_template\_callback\_full(), bind\_template\_child\_full(), find\_style\_property(), get\_css\_name(), install\_style\_property(), list\_style\_properties(), set\_accessible\_role(), set\_accessible\_type(), set\_connect\_func(), set\_css\_name(), set\_template(), set\_template\_from\_resource()

***Inherited from `gi.overrides.GObject.Object`***

\_\_copy\_\_(), \_\_deepcopy\_\_(), bind\_property(), bind\_property\_full(), chain(), compat\_control(), connect(), connect\_after(), connect\_data(), connect\_object(), connect\_object\_after(), disconnect(), disconnect\_by\_func(), emit(), emit\_stop\_by\_name(), force\_floating(), freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(), handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(), handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(), interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), replace\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(), steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(), weak\_ref()

***Inherited from `??`.Object***

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

***Inherited from `gi._gi.GObject`***

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(), \_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

***Inherited from `object`***

\_\_format\_\_(), \_\_getattr\_\_(), \_\_reduce\_\_(), \_\_reduce\_ex\_\_(), \_\_sizeof\_\_(), \_\_str\_\_(), \_\_subclasshook\_\_()

**15.2.2 Properties**

Name	Description
<i>Inherited from <code>??</code>.Window</i> bin, priv	

*continued on next page*

Name	Description
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ???.Container</i> widget	
<i>Inherited from ???.Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	
<i>Inherited from object</i> __class__	

### 15.2.3 Class Variables

Name	Description
--gtype--	<b>Value:</b> <GType view+frmCrearHorario+Frm_Crear_Horario (9402759841...
<i>Inherited from ???.Window</i>	

*continued on next page*

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*



Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>


## 16 Module view.frmCrearNombramiento

### 16.1 Variables

Name	Description
__package__	Value: 'view'



## 16.2 Class Frm\_Crear\_Nombramiento



Clase en la que se va a poder crear o modificar el Nombramiento del Profesor

### 16.2.1 Methods

**\_\_init\_\_(self)**

Construtor de la clase Frm\_Crear\_Nombramiento, enfocado a la vista

Overrides: object.\_\_init\_\_

**load(self, profesor)**

Carga los datos para su posterior modificacion

**Parameters**

**profesor:** Datos referentes al profesor

(*type=Profesor*)

**box1(self)**

Construccion de la caja 1, caja intermedia que va a dato acerca del Nombramiento del profesor nombramiento fecha inicio

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box2(self)**

Construccion de la caja 2, caja intermedia que va a dato acerca del Nombramiento del profesor nombramiento fecha fin

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box3(self)**

Construccion de la caja 3, caja final, da a los botones

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**index\_box(self)**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(type=Gtk.Box)

**dev\_frm(self)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**on\_btn\_guardar\_clicked(self, widget)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento

(type=Gtk.Widget)

**on\_btn\_borrar\_clicked(self, widget)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento

(type=Gtk.Widget)

**on\_btn\_salir\_clicked(self, widget)**

Evento para button cuando este se hace clic

**Parameters**

**widget:** Widget que esta relacionado al evento

(type=Gtk.Widget)

**Inherited from gi.overrides.Gtk.Container**

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

**Inherited from ??Container**

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

**Inherited from gi.overrides.Gtk.Widget**

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

### ***Inherited from `??`.Widget***

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

### ***Inherited from `gi.overrides.GObject.Object`***

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`, `weak_ref()`

### ***Inherited from `??`.Object***

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

### ***Inherited from `gi._gi.GObject`***

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`, `__new__()`, `__repr__()`, `__setattr__()`, `props()`

### ***Inherited from `object`***

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

## **16.2.2 Properties**

Name	Description
<i>Inherited from <code>??</code>.Window</i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??</code>.Container</i> widget	
<i>Inherited from <code>??</code>.Widget</i> parent_instance	

*continued on next page*



Name	Description
	<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count
	<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__
	<i>Inherited from object</i> __class__

### 16.2.3 Class Variables

Name	Description
__gtype__	<b>Value:</b> <GType view+frmCrearNombramiento+Frm_Crear_Nombramiento (...
	<i>Inherited from ?? Window</i>

*continued on next page*

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	


## 17 Module view.frmCrearProfesor

### 17.1 Variables

Name	Description
__package__	Value: 'view'



## 17.2 Class Frm\_Crear\_Profesor





Clase en la que se va a poder crear o modificar Profesor

### 17.2.1 Methods

**`__init__(self, fecha1=None, fecha2=None)`**

Construtor de la clase Frm\_Crear\_Profesor, enfocado a la vista Este esta enfocado cuando el profesor no es de planta

Overrides: `object.__init__`

**`load(self, profesor)`**

Carga los datos para su posterior modificacion

**Parameters**

**profesor:** Datos referentes al profesor  
(*type=Profesor*)

**`box1(self)`**

Construccion de la caja 1, caja superior que va a dato acerca del profesor enfocado en el codigo del profesor

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**`box2(self)`**

Construccion de la caja 2, caja intermedia que va a dato acerca del profesor enfocado en el nombre 1 del profesor

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**`box3(self)`**

Construccion de la caja 3, caja intermedia que va a dato acerca del profesor enfocado en el nombre 2 del profesor

**Return Value**

Caja con boton dentro  
(*type=Gtk.Box*)

**box4(self)**

Construccion de la caja 4, caja intermedia que va a dato acerca del profesor enfocado en el Apellido 1 del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box5(self)**

Construccion de la caja 5, caja intermedia que va a dato acerca del profesor enfocado en el Apellido 2 del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box6(self)**

Construccion de la caja 6, caja intermedia que va a dato acerca del profesor enfocado en la edad del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box7(self)**

Construccion de la caja 7, caja intermedia que va a dato acerca del profesor enfocado en el lugar de nacimiento del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box8(self)**

Construccion de la caja 8, caja intermedia que va a dato acerca del profesor enfocado en el lugar de residencia del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box9(*self*)**

Construccion de la caja 9, caja intermedia que va a dato acerca del profesor enfocado en la direccion de residencia del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box10(*self*)**

Construccion de la caja 10, caja intermedia que va a dato acerca del profesor enfocado en el titulo del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box11(*self*)**

Construccion de la caja 11, caja intermedia que va a dato acerca del profesor enfocado en el contrato del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box12(*self*)**

Construccion de la caja 12, caja intermedia que va a dato acerca del profesor enfocado en el nombre de usuario del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box13(*self*)**

Construccion de la caja 13, caja intermedia que va a dato acerca del profesor enfocado en la contraseña del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box14(self)**

Construccion de la caja 14, caja intermedia que va a dato acerca del profesor enfocado en la facultad del profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box15(self)**

Construccion de la caja 15, caja final, da a los botones

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**index\_box(self)**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(*type=Gtk.Box*)

**dev\_frm(self)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**cargar\_datos(self)**

Metodo para el uso de la carga de los datos dentro del formulario

**solo\_nombre(self, tupla)**

Proceso funcional para que solo se tome el atributo de la posicion 1

**Parameters**

tupla: Tupla

(*type=tuple*)

**Return Value**

datos str con el nombre

(*type=str*)

<b>on_btn_guardar_clicked</b> ( <i>self</i> , <i>widget</i> )
---

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget:</b> Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

<b>guardar_profesor</b> ( <i>self</i> )
---

Metodo para el guardado del profesor
--------------------------------------

<b>modificar_profesor</b> ( <i>self</i> )
---

Metodo para el modificado del profesor
--

<b>on_btn_borrar_clicked</b> ( <i>self</i> , <i>widget</i> )
--

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget:</b> Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

<b>on_cerrar_clicked</b> ( <i>self</i> , <i>widget</i> )
--

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget:</b> Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

***Inherited from gi.overrides.Gtk.Container***

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

***Inherited from ??.Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

***Inherited from gi.overrides.Gtk.Widget***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

***Inherited from ??.Widget***

bind\_template\_callback\_full(), bind\_template\_child\_full(), find\_style\_property(), get\_css\_name(),  
install\_style\_property(), list\_style\_properties(), set\_accessible\_role(), set\_accessible\_type(),  
set\_connect\_func(), set\_css\_name(), set\_template(), set\_template\_from\_resource()

### ***Inherited from gi.overrides.GObject.Object***

\_\_copy\_\_(), \_\_deepcopy\_\_(), bind\_property(), bind\_property\_full(), chain(), compat\_control(),  
connect(), connect\_after(), connect\_data(), connect\_object(), connect\_object\_after(),  
disconnect(), disconnect\_by\_func(), emit(), emit\_stop\_by\_name(), force\_floating(),  
freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(),  
handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(),  
handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(),  
interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), re-  
place\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(),  
steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(),  
weak\_ref()

### ***Inherited from ??Object***

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

### ***Inherited from gi.\_gi.GObject***

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(),  
\_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

### ***Inherited from object***

\_\_format\_\_(), \_\_getattr\_\_(), \_\_reduce\_\_(), \_\_reduce\_ex\_\_(), \_\_sizeof\_\_(), \_\_str\_\_(),  
\_\_subclasshook\_\_()

## **17.2.2 Properties**

Name	Description
<i>Inherited from ??Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ??Container</i> widget	
<i>Inherited from ??Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	

*continued on next page*

Name	Description
<i>Inherited from object</i>	
__class__	

### 17.2.3 Class Variables

Name	Description
fecha1	<b>Value:</b> None
fecha2	<b>Value:</b> None
__gtype__	<b>Value:</b> <GType view+frmCrearProfesor+Frm_Crear_Profesor (94027599...
<i>Inherited from ??Window</i> __info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshown_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	

*continued on next page*

Name	Description
<i>Inherited from gi.repository.Gtk.Bin</i> get_child	
<i>Inherited from Gtk.Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain	
<i>Inherited from Gtk.Widget</i>	

*continued on next page*



Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>


## 18 Module view.frmListaCursos

### 18.1 Variables

Name	Description
__package__	Value: 'view'



## 18.2 Class Frm\_Lista\_Curso



Clase de la lista de los cursos

### 18.2.1 Methods

**\_\_init\_\_**(*self*, *cod\_profesor*=0, *formulario\_siguiente*='lista\_curso', *especificacion*=None)

Construtor de la clase Frm\_Lista\_Curso, enfocado a la vista

**Parameters**

**formulario\_siguiente:** Formulario que estara cargado despues de la seleccion  
(*type*=str)

Overrides: object.\_\_init\_\_

**box1**(*self*)

Construccion de la lista de seleccion para el curso

**box2**(*self*)

Boton de seleccion

**index\_box**(*self*)

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro  
(*type*=Gtk.Box)

**dev\_frm**(*self*)

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**cargar\_datos**(*self*)

Construccion de los datos dentro de la pantalla

**matriz\_to\_liststore**(*self*, *matriz*)

Convierte una matriz comun y corriente en una listStore

**Parameters**

**matriz:** Matriz que se va a convertir en listStore  
(*type=<class= 'list'>*)

**Return Value**

listStore correspondiente de la matriz  
(*type=Gtk.listStore*)

**filtro\_parametro**(*self*, *vector*)

Filtrar los parametros del vector deseado para ser puesto

**Parameters**

**vector:** Vector que se va a reducir  
(*type=tuple*)

**Return Value**

Vector reducido  
(*type=tuple*)

**filtro\_parametros**(*self*, *matriz*)

Filtra los parametros necesarios, no mas no menos

**Parameters**

**matriz:** Matriz que se va a reducir  
(*type=<class= 'list'>*)

**Return Value**

Matriz reducida con los parametros necesarios  
(*type=<class= 'list'>*)

**on\_btn\_modificar\_clicked**(*self*, *widget*)

Evento que funciona al accionar el boton de curso

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_borrar\_clicked**(*self*, *widget*)

Evento que funciona al accionar el boton de curso

**Parameters**

**widget**: Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_cerrar\_clicked**(*self*, *widget*)

Evento que funciona al accionar el boton de cerrar

**Parameters**

**widget**: Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**get\_seleccion**(*self*)

Retorna el valor de la seleccion del formulario despues de aceptar

**Return Value**

Valor seleccionado en la lista, especificamente el id  
(*type=int*)

**Inherited from *gi.overrides.Gtk.Container***

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

**Inherited from *??Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

**Inherited from *gi.overrides.Gtk.Widget***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

**Inherited from *??Widget***

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

**Inherited from *gi.overrides.GObject.Object***

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`,



freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(), handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(), handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(), interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), replace\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(), steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(), weak\_ref()

### ***Inherited from `??Object`***

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

### ***Inherited from `gi._gi.GObject`***

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(), \_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

### ***Inherited from `object`***

\_\_format\_\_(), \_\_getattr\_\_(), \_\_reduce\_\_(), \_\_reduce\_ex\_\_(), \_\_sizeof\_\_(), \_\_str\_\_(), \_\_subclasshook\_\_()

## **18.2.2 Properties**

Name	Description
<i>Inherited from <code>??Window</code></i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??Container</code></i> widget	
<i>Inherited from <code>??Widget</code></i> parent_instance	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> g_type_instance, qdata, ref_count	
<i>Inherited from <code>gi._gi.GObject</code></i> __gpointer__, __grefcount__	
<i>Inherited from <code>object</code></i> __class__	

## **18.2.3 Class Variables**

Name	Description
--gtype--	<b>Value:</b> <GType view+frmListaCursos+Frm_Lista_Curso (94027599300944)>
<i>Inherited from ??Window</i> __info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	
<i>Inherited from gi.repository.Gtk.Bin</i> get_child	
<i>Inherited from ??Container</i>	

continued on next page

Name	Description
	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	

## 19 Module *view.frmListaEstudiante*

### 19.1 Variables

Name	Description
<code>--package--</code>	<b>Value:</b> 'view'







Clase de la lista de los estudiantes

### 19.2.1 Methods

**`__init__(self, formulario_siguiente='')`**

Construtor de la clase Frm\_Lista\_Estudiante, enfocado a la vista

**Parameters**

**formulario\_siguiente:** Formulario que estara cargado despues de la seleccion  
(*type=*str)

Overrides: object.\_\_init\_\_

**`box1(self)`**

Construccion de la lista de seleccion para el Estudiante

**Return Value**

Caja con datos referentes a la lista de estudiantes  
(*type=*Gtk.Box)

**`box2(self)`**

Boton de seleccion para su posterior control

**Return Value**

Caja con cajas dentro  
(*type=*Gtk.Box)

**`box3(self)`**

Boton de seleccion

**`index_box(self)`**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro  
(*type=*Gtk.Box)

**dev\_frm(*self*)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**cargar\_datos(*self*)**

Cargara los datos de la base de datos para su posterior muestreo

**matriz.to\_liststore(*self*, *matriz*)**

Convierte una matriz comun y corriente en una listStore

**Parameters**

**matriz:** Matriz que se va a convertir en listStore  
(*type=<class= 'list'>*)

**Return Value**

listStore correspondiente de la matriz  
(*type=Gtk.listStore*)

**filtro\_parametro(*self*, *vector*)**

Fitrla los parametros del vector deseado para ser puesto

**Parameters**

**vector:** Vector que se va a reducir  
(*type=tuple*)

**Return Value**

Vector reducido  
(*type=tuple*)

**filtro\_parametros(*self*, *matriz*)**

Filtra los parametros necesarios, no mas no menos

**Parameters**

**matriz:** Matriz que se va a reducir  
(*type=<class= 'list'>*)

**Return Value**

Matriz reducida con los parametros necesarios  
(*type=<class= 'list'>*)

**seleccionar\_semestre**(*self, model, ite, data*)

Relacion con el metodo de filtro para el treeview

**Parameters****model:** Modelo**ite:** iterador**data:** datos relacionados**on\_btn\_semestre\_siguiente\_clicked**(*self, widget*)

Evento que funciona al accionar el boton de Estudiante

**Parameters****widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)**on\_btn\_semestre\_anterior\_clicked**(*self, widget*)

Evento que funciona al accionar el boton de Estudiante

**Parameters****widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)**on\_btn\_seleccionar\_clicked**(*self, widget*)

Evento que funciona al accionar el boton de Estudiante

**Parameters****widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)**on\_btn\_borrar\_clicked**(*self, widget*)

Evento que funciona al accionar el boton de estudiante

**Parameters****widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

```
get_seleccion(self)
```

Retorna el valor de la seleccion de la lista aqui mostrada y con ello tomar decisiones

**Return Value**

Valor de id\_estudiante que se seleccionó al oprimir

(type=int)

**Inherited from gi.overrides.Gtk.Container**

\_\_bool\_\_(), \_\_contains\_\_(), \_\_iter\_\_(), \_\_len\_\_(), \_\_nonzero\_\_(), child\_get(), child\_get\_property(), child\_set(), get\_focus\_chain()

**Inherited from ??Container**

find\_child\_property(), handle\_border\_width(), install\_child\_properties(), install\_child\_property(), list\_child\_properties()

**Inherited from gi.overrides.Gtk.Widget**

drag\_dest\_set\_target\_list(), drag\_source\_set\_target\_list(), style\_get\_property(), translate\_coordinates()

**Inherited from ??Widget**

bind\_template\_callback\_full(), bind\_template\_child\_full(), find\_style\_property(), get\_css\_name(), install\_style\_property(), list\_style\_properties(), set\_accessible\_role(), set\_accessible\_type(), set\_connect\_func(), set\_css\_name(), set\_template(), set\_template\_from\_resource()

**Inherited from gi.overrides.GObject.Object**

\_\_copy\_\_(), \_\_deepcopy\_\_(), bind\_property(), bind\_property\_full(), chain(), compat\_control(), connect(), connect\_after(), connect\_data(), connect\_object(), connect\_object\_after(), disconnect(), disconnect\_by\_func(), emit(), emit\_stop\_by\_name(), force\_floating(), freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(), handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(), handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(), interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), replace\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(), steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(), weak\_ref()

**Inherited from ??Object**

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

**Inherited from gi.\_gi.GObject**

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(),

`__new__()`, `__repr__()`, `__setattr__()`, `props()`

### ***Inherited from object***

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`,  
`__subclasshook__()`

### **19.2.2 Properties**

Name	Description
<i>Inherited from <code>??</code>.Window</i>	<code>bin</code> , <code>priv</code>
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i>	<code>container</code>
<i>Inherited from <code>??</code>.Container</i>	<code>widget</code>
<i>Inherited from <code>??</code>.Widget</i>	<code>parent</code> instance
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i>	<code>g_type_instance</code> , <code>qdata</code> , <code>ref_count</code>
<i>Inherited from <code>gi._gi.GObject</code></i>	<code>__gpointer__</code> , <code>__grefcount__</code>
<i>Inherited from <code>object</code></i>	<code>__class__</code>

### **19.2.3 Class Variables**

Name	Description
<code>__gtype__</code>	<b>Value:</b> <code>&lt;GType</code> <code>view+frmListaEstudiante+Frm_Lista_Estudiante</code> <code>(9402...</code>
<i>Inherited from <code>??</code>.Window</i>	

*continued on next page*

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>



Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

## 20 Module view.frmListaProfesor

### 20.1 Variables

Name	Description
__package__	Value: 'view'





Clase de la lista de los profesores

### 20.2.1 Methods

**`__init__(self, formulario_siguiente='', datos_profesor=None)`**

Construtor de la clase *Frm\_Lista\_Profesor*, enfocado a la vista

**Parameters**

**`formulario_siguiente`:** Formulario que estara cargado despues de la seleccion  
(*type=**str*)

Overrides: *object.\_\_init\_\_*

**`box1(self)`**

Construccion de la lista de seleccion para el Profesor

**`box2(self)`**

Boton de seleccion para su posterior control

**`box3(self)`**

Boton de seleccion

**`index_box(self)`**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro  
(*type=Gtk.Box*)

**`dev_frm(self)`**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**matriz\_to\_liststore**(*self*, *matriz*)

Convierte una matriz comun y corriente en una listStore

**Parameters**

**matriz:** Matriz que se va a convertir en listStore  
(*type=<class= 'list'>*)

**Return Value**

listStore correspondiente de la matriz  
(*type=Gtk.listStore*)

**filtro\_parametro**(*self*, *vector*)

Filtrar los parametros del vector deseado para ser puesto

**Parameters**

**vector:** Vector que se va a reducir  
(*type=tuple*)

**Return Value**

Vector reducido  
(*type=tuple*)

**filtro\_parametros**(*self*, *matriz*)

Filtrar los parametros necesarios, no mas no menos

**Parameters**

**matriz:** Matriz que se va a reducir  
(*type=<class= 'list'>*)

**Return Value**

Matriz reducida con los parametros necesarios  
(*type=<class= 'list'>*)

**seleccionar\_facultad**(*self*, *model*, *ite*, *data*)

Relacion con el metodo de filtro para el treeview

**Parameters**

**model:** Modelo  
**ite:** iterador  
**data:** datos relacionados

**cargar\_datos(*self*)**

Evento de ejecucion para cargar datos de la base de datos

**on\_btn\_facultad\_siguiente\_clicked(*self*, *widget*)**

Evento que funciona al accionar el boton de profesor

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_facultad\_anterior\_clicked(*self*, *widget*)**

Evento que funciona al accionar el boton de profesor

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_seleccionar\_clicked(*self*, *widget*)**

Evento que funciona al accionar el boton de profesor

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**fs\_modificar\_profesor(*self*)**

Evento de caracterizacion y limpieza de codigo

**on\_btn\_borrar\_clicked(*self*, *widget*)**

Evento que funciona al accionar el boton de curso

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

**on\_btn\_cerrar\_clicked(*self*, *widget*)**

Evento que funciona al accionar el boton de cerrar

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

***Inherited from gi.overrides.Gtk.Container***

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

***Inherited from ??Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

***Inherited from gi.overrides.Gtk.Widget***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

***Inherited from ??Widget***

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

***Inherited from gi.overrides.GObject.Object***

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`, `weak_ref()`

***Inherited from ??Object***

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

***Inherited from gi.\_gi.GObject***

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`, `__new__()`, `__repr__()`, `__setattr__()`, `props()`

***Inherited from object***

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

**20.2.2 Properties**



Name	Description
<i>Inherited from ??.</i> Window	
bin, priv	
<i>Inherited from gi.repository.Gtk.</i> Bin	
container	
<i>Inherited from ??.</i> Container	
widget	
<i>Inherited from ??.</i> Widget	
parent_instance	
<i>Inherited from gi.repository.GObject.</i> InitiallyUnowned	
g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.</i> GObject	
__gpointer__, __grefcount__	
<i>Inherited from object</i>	
__class__	

### 20.2.3 Class Variables

Name	Description
__gtype__	<b>Value:</b> <GType view+frmListaProfesor+Frm_Lista_Profesor (94027599...
<i>Inherited from ??.</i> Window	

*continued on next page*

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshown_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	


## 21 Module view.frmPrincipalEstudiante

### 21.1 Variables

Name	Description
__package__	Value: 'view'



## 21.2 Class Frm\_Principal\_Estudiante





Formulario principal de estudiante

### 21.2.1 Methods

**`__init__(self, sesion)`**

Construtor de la clase *Frm\_Principal\_Estudiante*, enfocado a la vista

Overrides: `object.__init__`

**`box1(self)`**

Construccion de la caja 1, caja superior que va a albergar un boton

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**`box2(self)`**

Construccion de la caja 2, caja superior que va a albergar un boton

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**`index_box(self)`**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(*type=Gtk.Box*)

**`dev_frm(self)`**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**`on_btn_crear_horario_clicked(self, widget)`**

Evento que funciona al accionar el boton de profesor

**Parameters**

**widget:** Widget que esta relacionado al evento

(*type=Gtk.Widget*)

<b>on_btn_modificar_estudiante_clicked</b> ( <i>self</i> , <i>widget</i> )
--

Evento que funciona al accionar el boton de profesor
--

<b>Parameters</b>
-------------------

<b>widget:</b> Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

**Inherited from gi.overrides.Gtk.Container**

\_\_bool\_\_(), \_\_contains\_\_(), \_\_iter\_\_(), \_\_len\_\_(), \_\_nonzero\_\_(), child\_get(), child\_get\_property(), child\_set(), get\_focus\_chain()

**Inherited from ??Container**

find\_child\_property(), handle\_border\_width(), install\_child\_properties(), install\_child\_property(), list\_child\_properties()

**Inherited from gi.overrides.Gtk.Widget**

drag\_dest\_set\_target\_list(), drag\_source\_set\_target\_list(), style\_get\_property(), translate\_coordinates()

**Inherited from ??Widget**

bind\_template\_callback\_full(), bind\_template\_child\_full(), find\_style\_property(), get\_css\_name(), install\_style\_property(), list\_style\_properties(), set\_accessible\_role(), set\_accessible\_type(), set\_connect\_func(), set\_css\_name(), set\_template(), set\_template\_from\_resource()

**Inherited from gi.overrides.GObject.Object**

\_\_copy\_\_(), \_\_deepcopy\_\_(), bind\_property(), bind\_property\_full(), chain(), compat\_control(), connect(), connect\_after(), connect\_data(), connect\_object(), connect\_object\_after(), disconnect(), disconnect\_by\_func(), emit(), emit\_stop\_by\_name(), force\_floating(), freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(), handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(), handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(), interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), replace\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(), steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(), weak\_ref()

**Inherited from ??Object**

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

**Inherited from gi.\_gi.GObject**

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(), \_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

***Inherited from object***

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`,  
`__subclasshook__()`

**21.2.2 Properties**

Name	Description
<i>Inherited from <code>??</code>.Window</i>	<code>bin</code> , <code>priv</code>
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i>	<code>container</code>
<i>Inherited from <code>??</code>.Container</i>	<code>widget</code>
<i>Inherited from <code>??</code>.Widget</i>	<code>parent_instance</code>
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i>	<code>g_type_instance</code> , <code>qdata</code> , <code>ref_count</code>
<i>Inherited from <code>gi._gi.GObject</code></i>	<code>__gpointer__</code> , <code>__grefcount__</code>
<i>Inherited from object</i>	<code>__class__</code>

**21.2.3 Class Variables**

Name	Description
<code>__gtype__</code>	<b>Value:</b> <code>&lt;GType</code> <code>view+frmPrincipalEstudiante+Frm_Principal_Estudian...</code>
<i>Inherited from <code>??</code>.Window</i>	

*continued on next page*

Name	Description
	__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick
	<i>Inherited from gi.repository.Gtk.Bin</i> get_child
	<i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus<sup>126</sup>_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	

## 22 Module view.frmPrincipalProfesor

### 22.1 Variables

Name	Description
__package__	Value: 'view'







Formulario principal del profesor

### 22.2.1 Methods

**\_\_init\_\_**(*self*, *sesion*)

Construtor de la clase Frm\_Principal\_Profesor, enfocado a la vista

Overrides: object.\_\_init\_\_

**box1**(*self*)

Construccion de la caja 1, caja superior que va a albergar un boton

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box2**(*self*)

Construccion de la caja 2, caja media 1 que va a albergar dos botones referentes a estudiante

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box3**(*self*)

Construccion de la caja 3, caja media 2 que va a albergar dos botones referentes a profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box4**(*self*)

Construccion de la caja 4, caja media 3 que va a albergar un boton sobre el profesor

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**index\_box(*self*)**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(*type=Gtk.Box*)

**dev\_frm(*self*)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

**on\_btn\_lista\_curso\_clicked(*self*, *widget*)**

Evento para btn de lista de cursos

**Parameters**

**widget:** Widget que esta relacionado al evento

(*type=Gtk.Widget*)

**on\_btn\_crear\_curso\_clicked(*self*, *widget*)**

Evento para btn de crear curso

**Parameters**

**widget:** Widget que esta relacionado al evento

(*type=Gtk.Widget*)

**on\_btn\_crear\_estudiante\_clicked(*self*, *widget*)**

Evento para btn de crear estudiante

**Parameters**

**widget:** Widget que esta relacionado al evento

(*type=Gtk.Widget*)

**on\_btn\_borrar\_estudiante\_clicked(*self*, *widget*)**

Evento para btn de borrar estudiante

**Parameters**

**widget:** Widget que esta relacionado al evento

(*type=Gtk.Widget*)

---

**on\_btn\_crear\_profesor\_clicked**(*self, widget*)

---

Evento para btn de crear profesor

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

---

**on\_btn\_borrar\_profesor\_clicked**(*self, widget*)

---

Evento para btn de borrar profesor

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

---

**on\_btn\_modificar\_profesor\_clicked**(*self, widget*)

---

Evento para btn de eleccion de cursos del profesor

**Parameters**

**widget:** Widget que esta relacionado al evento  
(*type=Gtk.Widget*)

***Inherited from gi.overrides.Gtk.Container***

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

***Inherited from ??.Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

***Inherited from gi.overrides.Gtk.Widget***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

***Inherited from ??.Widget***

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

***Inherited from gi.overrides.GObject.Object***

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`,

freeze\_notify(), get\_data(), get\_properties(), get\_property(), get\_qdata(), handler\_block(), handler\_block\_by\_func(), handler\_disconnect(), handler\_is\_connected(), handler\_unblock(), handler\_unblock\_by\_func(), interface\_find\_property(), interface\_install\_property(), interface\_list\_properties(), notify\_by\_pspec(), ref(), ref\_sink(), replace\_data(), replace\_qdata(), run\_dispose(), set\_data(), set\_properties(), set\_property(), steal\_data(), steal\_qdata(), stop\_emission(), stop\_emission\_by\_name(), unref(), watch\_closure(), weak\_ref()

### ***Inherited from `??Object`***

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

### ***Inherited from `gi._gi.GObject`***

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(), \_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

### ***Inherited from `object`***

\_\_format\_\_(), \_\_getattr\_\_(), \_\_reduce\_\_(), \_\_reduce\_ex\_\_(), \_\_sizeof\_\_(), \_\_str\_\_(), \_\_subclasshook\_\_()

## **22.2.2 Properties**

Name	Description
<i>Inherited from <code>??Window</code></i> bin, priv	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> container	
<i>Inherited from <code>??Container</code></i> widget	
<i>Inherited from <code>??Widget</code></i> parent_instance	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> g_type_instance, qdata, ref_count	
<i>Inherited from <code>gi._gi.GObject</code></i> __gpointer__, __grefcount__	
<i>Inherited from <code>object</code></i> __class__	

## **22.2.3 Class Variables**

Name	Description
--gtype--	<b>Value:</b> <GType view+frmPrincipalProfesor+Frm_Principal_Profesor (...
<i>Inherited from ??Window</i> __info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick	
<i>Inherited from gi.repository.Gtk.Bin</i> get_child	
<i>Inherited from ??Container</i>	

continued on next page

Name	Description
	add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain
<i>Inherited from ??Widget</i>	

*continued on next page*



Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus<sup>137</sup>_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>


## 23 Module view.frmRol

### 23.1 Variables

Name	Description
__package__	Value: 'view'



## 23.2 Class Frm\_Rol



Clase en la que se va a poder seleccionar el rol

### 23.2.1 Methods

**\_\_init\_\_(self)**

Construtor de la clase Frm\_Rol, enfocado a la vista

Overrides: object.\_\_init\_\_

**box1(self)**

Construccion de la caja 1, caja usuario

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**box2(self)**

Construccion de la caja 2, caja de pass

**Return Value**

Caja con entrada dentro

(*type=Gtk.Box*)

**box3(self)**

Construccion de la caja 3, caja inferior que va a albergar los botones

**Return Value**

Caja con boton dentro

(*type=Gtk.Box*)

**index\_box(self)**

Construccion de la caja Principal, caja principal que se va a mostrar

**Return Value**

Caja con cajas dentro

(*type=Gtk.Box*)

**dev\_frm(self)**

Enfocado en la construccion de cada una de las partes del formulario este funcionara cargando la caja principal y mostrando algunas propiedades del mismo

<b>on_btn_guardar_clicked</b> ( <i>self, widget</i> )
---

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget:</b> Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

<b>on_btn_borrar_clicked</b> ( <i>self, widget</i> )
--

Evento para button cuando este se hace clic
---

<b>Parameters</b>
-------------------

<b>widget:</b> Widget que esta relacionado al evento <i>(type=Gtk.Widget)</i>
--

***Inherited from gi.overrides.Gtk.Container***

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

***Inherited from ??.Container***

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

***Inherited from gi.overrides.Gtk.Widget***

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

***Inherited from ??.Widget***

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

***Inherited from gi.overrides.GObject.Object***

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`, `weak_ref()`

***Inherited from ??Object***

find\_property(), install\_properties(), install\_property(), list\_properties(), override\_property()

***Inherited from gi.\_gi.GObject***

\_\_delattr\_\_(), \_\_eq\_\_(), \_\_gdoc\_\_(), \_\_ge\_\_(), \_\_gt\_\_(), \_\_hash\_\_(), \_\_le\_\_(), \_\_lt\_\_(), \_\_ne\_\_(),  
\_\_new\_\_(), \_\_repr\_\_(), \_\_setattr\_\_(), props()

***Inherited from object***

\_\_format\_\_(), \_\_getattr\_\_(), \_\_reduce\_\_(), \_\_reduce\_ex\_\_(), \_\_sizeof\_\_(), \_\_str\_\_(),  
\_\_subclasshook\_\_()

**23.2.2 Properties**

Name	Description
<i>Inherited from ??Window</i> bin, priv	
<i>Inherited from gi.repository.Gtk.Bin</i> container	
<i>Inherited from ??Container</i> widget	
<i>Inherited from ??Widget</i> parent_instance	
<i>Inherited from gi.repository.GObject.InitiallyUnowned</i> g_type_instance, qdata, ref_count	
<i>Inherited from gi._gi.GObject</i> __gpointer__, __grefcount__	
<i>Inherited from object</i> __class__	

**23.2.3 Class Variables**

Name	Description
__gtype__	<b>Value:</b> <GType view+frmRol+Frm_Rol (94027599240656)>
<i>Inherited from ??Window</i>	

*continued on next page*



Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshow_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

continued on next page

Name	Description
<i>Inherited from ??Widget</i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus<sup>447</sup>_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	
<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>	
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	
<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>	


## 24 Module *view.scroll*

### 24.1 Variables

Name	Description
<code>software_list</code>	<b>Value:</b> [('Firefox', 2002, 'C++'), ('Eclipse', 2004, 'Java'), ('P...
<code>win</code>	<b>Value:</b> <scroll.TreeViewFilterWindow object at 0x7f1ca6a11960 (vi...
<code>--package--</code>	<b>Value:</b> 'view'
<code>--warningregistry--</code>	<b>Value:</b> {'Using positional arguments with the GObject constructo...



## 24.2 Class `TreeViewFilterWindow`



### 24.2.1 Methods

**`__init__(self)`**

Initializer for a GObject based classes with support for property sets through the use of explicit keyword arguments.

Overrides: `object.__init__` `exitit`(inherited documentation)

**`language_filter_func(self, model, iter, data)`**

Tests if the language in the row is the one in the filter

**`on_selection_button_clicked(self, widget)`**

Called on any of the button clicks

#### *Inherited from `gi.overrides.Gtk.Container`*

`__bool__()`, `__contains__()`, `__iter__()`, `__len__()`, `__nonzero__()`, `child_get()`, `child_get_property()`, `child_set()`, `get_focus_chain()`

#### *Inherited from `??Container`*

`find_child_property()`, `handle_border_width()`, `install_child_properties()`, `install_child_property()`, `list_child_properties()`

#### *Inherited from `gi.overrides.Gtk.Widget`*

`drag_dest_set_target_list()`, `drag_source_set_target_list()`, `style_get_property()`, `translate_coordinates()`

#### *Inherited from `??Widget`*

`bind_template_callback_full()`, `bind_template_child_full()`, `find_style_property()`, `get_css_name()`, `install_style_property()`, `list_style_properties()`, `set_accessible_role()`, `set_accessible_type()`, `set_connect_func()`, `set_css_name()`, `set_template()`, `set_template_from_resource()`

#### *Inherited from `gi.overrides.GObject.Object`*

`__copy__()`, `__deepcopy__()`, `bind_property()`, `bind_property_full()`, `chain()`, `compat_control()`, `connect()`, `connect_after()`, `connect_data()`, `connect_object()`, `connect_object_after()`, `disconnect()`, `disconnect_by_func()`, `emit()`, `emit_stop_by_name()`, `force_floating()`, `freeze_notify()`, `get_data()`, `get_properties()`, `get_property()`, `get_qdata()`, `handler_block()`, `handler_block_by_func()`, `handler_disconnect()`, `handler_is_connected()`, `handler_unblock()`, `handler_unblock_by_func()`, `interface_find_property()`, `interface_install_property()`, `interface_list_properties()`, `notify_by_pspec()`, `ref()`, `ref_sink()`, `replace_data()`, `replace_qdata()`, `run_dispose()`, `set_data()`, `set_properties()`, `set_property()`, `steal_data()`, `steal_qdata()`, `stop_emission()`, `stop_emission_by_name()`, `unref()`, `watch_closure()`



`weak_ref()`

### *Inherited from `??Object`*

`find_property()`, `install_properties()`, `install_property()`, `list_properties()`, `override_property()`

### *Inherited from `gi.gi.GObject`*

`__delattr__()`, `__eq__()`, `__gdoc__()`, `__ge__()`, `__gt__()`, `__hash__()`, `__le__()`, `__lt__()`, `__ne__()`, `__new__()`, `__repr__()`, `__setattr__()`, `props()`

### *Inherited from `object`*

`__format__()`, `__getattr__()`, `__reduce__()`, `__reduce_ex__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

## 24.2.2 Properties

Name	Description
<i>Inherited from <code>??Window</code></i> <code>bin</code> , <code>priv</code>	
<i>Inherited from <code>gi.repository.Gtk.Bin</code></i> <code>container</code>	
<i>Inherited from <code>??Container</code></i> <code>widget</code>	
<i>Inherited from <code>??Widget</code></i> <code>parent_instance</code>	
<i>Inherited from <code>gi.repository.GObject.InitiallyUnowned</code></i> <code>g_type_instance</code> , <code>qdata</code> , <code>ref_count</code>	
<i>Inherited from <code>gi.gi.GObject</code></i> <code>__gpointer__</code> , <code>__grefcount__</code>	
<i>Inherited from <code>object</code></i> <code>__class__</code>	

## 24.2.3 Class Variables

Name	Description
<code>__gtype__</code>	<b>Value:</b> <code>&lt;GType view+scroll+TreeViewFilterWindow (94027598936608)&gt;</code>
<i>Inherited from <code>??Window</code></i>	

*continued on next page*

Name	Description
	<p>__info__, activate_default, activate_focus, activate_key, add_accel_group, add_mnemonic, begin_move_drag, begin_resize_drag, close, deiconify, do_activate_default, do_activate_focus, do_enable_debugging, do_keys_changed, do_set_focus, fullscreen, fullscreen_on_monitor, get_accept_focus, get_application, get_attached_to, get_decorated, get_default_icon_list, get_default_icon_name, get_default_size, get_default_widget, get_deletable, get_destroy_with_parent, get_focus, get_focus_on_map, get_focus_visible, get_gravity, get_group, get_has_resize_grip, get_hide_titlebar_when_maximized, get_icon, get_icon_list, get_icon_name, get_mnemonic_modifier, get_mnemonics_visible, get_modal, get_opacity, get_position, get_resizable, get_resize_grip_area, get_role, get_screen, get_size, get_skip_pager_hint, get_skip_taskbar_hint, get_title, get_titlebar, get_transient_for, get_type_hint, get_urgency_hint, get_window_type, has_group, has_toplevel_focus, iconify, is_active, is_maximized, list_toplevels, maximize, mnemonic_activate, move, new, parse_geometry, present, present_with_time, propagate_key_event, remove_accel_group, remove_mnemonic, reshown_with_initial_size, resize, resize_grip_is_visible, resize_to_geometry, set_accept_focus, set_application, set_attached_to, set_auto_startup_notification, set_decorated, set_default, set_default_geometry, set_default_icon, set_default_icon_from_file, set_default_icon_list, set_default_icon_name, set_default_size, set_deletable, set_destroy_with_parent, set_focus, set_focus_on_map, set_focus_visible, set_geometry_hints, set_gravity, set_has_resize_grip, set_has_user_ref_count, set_hide_titlebar_when_maximized, set_icon, set_icon_from_file, set_icon_list, set_icon_name, set_interactive_debugging, set_keep_above, set_keep_below, set_mnemonic_modifier, set_mnemonics_visible, set_modal, set_opacity, set_position, set_resizable, set_role, set_screen, set_skip_pager_hint, set_skip_taskbar_hint, set_startup_id, set_title, set_titlebar, set_transient_for, set_type_hint, set_urgency_hint, set_wmclass, stick, unfullscreen, unmaximize, unstick</p>
	<p><i>Inherited from gi.repository.Gtk.Bin</i> get_child</p>
	<p><i>Inherited from ??Container</i> add, check_resize, child_notify, child_notify_by_pspec, child_set_property, child_type, do_add, do_check_resize, do_child_type, do_composite_name, do_forall, do_get_child_property, do_get_path_for_child, do_remove, do_set_child_property, do_set_focus_child, forall, foreach, get_border_width, get_children, get_focus_child, get_focus_hadjustment, get_focus_vadjustment, get_path_for_child, get_resize_mode, propagate_draw, remove, resize_children, set_border_width, set_focus_chain, set_focus_child, set_focus_hadjustment, set_focus_vadjustment, set_reallocate_redraws, set_resize_mode, unset_focus_chain</p>

*continued on next page*

Name	Description
<i>Inherited from <code>??Widget</code></i>	

*continued on next page*

Name	Description
	<p>activate, add_accelerator, add_device_events, add_events, add_mnemonic_label, add_tick_callback, can_activate_accel, child_focus, class_path, compute_expand, create_pango_context, create_pango_layout, destroy, destroyed, device_is_shadowed, do_adjust_baseline_allocation, do_adjust_baseline_request, do_adjust_size_allocation, do_adjust_size_request, do_button_press_event, do_button_release_event, do_can_activate_accel, do_child_notify, do_composited_changed, do_compute_expand, do_configure_event, do_damage_event, do_delete_event, do_destroy, do_destroy_event, do_direction_changed, do_dispatch_child_properties_changed, do_drag_begin, do_drag_data_delete, do_drag_data_get, do_drag_data_received, do_drag_drop, do_drag_end, do_drag_failed, do_drag_leave, do_drag_motion, do_draw, do_enter_notify_event, do_event, do_focus, do_focus_in_event, do_focus_out_event, do_get_accessible, do_get_preferred_height, do_get_preferred_height_and_baseline_for_width, do_get_preferred_height_for_width, do_get_preferred_width, do_get_preferred_width_for_height, do_get_request_mode, do_grab_broken_event, do_grab_focus, do_grab_notify, do_hide, do_hierarchy_changed, do_key_press_event, do_key_release_event, do_keynav_failed, do_leave_notify_event, do_map, do_map_event, do_mnemonic_activate, do_motion_notify_event, do_move_focus, do_parent_set, do_popup_menu, do_property_notify_event, do_proximity_in_event, do_proximity_out_event, do_query_tooltip, do_queue_draw_region, do_realize, do_screen_changed, do_scroll_event, do_selection_clear_event, do_selection_get, do_selection_notify_event, do_selection_received, do_selection_request_event, do_show, do_show_all, do_show_help, do_size_allocate, do_state_changed, do_state_flags_changed, do_style_set, do_style_updated, do_touch_event, do_unmap, do_unmap_event, do_unrealize, do_visibility_notify_event, do_window_state_event, drag_begin, drag_begin_with_coordinates, drag_check_threshold, drag_dest_add_image_targets, drag_dest_add_text_targets, drag_dest_add_uri_targets, drag_dest_find_target, drag_dest_get_target_list, drag_dest_get_track_motion, drag_dest_set, drag_dest_set_proxy, drag_dest_set_track_motion, drag_dest_unset, drag_get_data, drag_highlight, drag_source_add_image_targets, drag_source_add_text_targets, drag_source_add_uri_targets, drag_source_get_target_list, drag_source_set, drag_source_set_icon_gicon, drag_source_set_icon_name, drag_source_set_icon_pixbuf, drag_source_set_icon_stock, drag_source_unset, drag_unhighlight, draw, ensure_style, error_bell, event, freeze_child_notify, get_accessible, get_action_group, get_allocated_baseline, get_allocated_height, get_allocated_size, get_allocated_width, get_allocation, get_ancestor, get_app_paintable, get_can_default, get_can_focus, get_child_requisition, get_child_visible, get_clip, get_clipboard, get_composite_name, get_default_direction, get_default_style, get_device_enabled, get_device_events, get_direction, get_display, get_double_buffered, get_events, get_focus<sup>156</sup>_on_click, get_font_map, get_font_options, get_frame_clock, get_halign, get_has_tooltip, get_has_window, get_hexpand, get_hexpand_set, get_mapped, get_margin_bottom, get_margin_end, get_margin_left, get_margin_right, get_margin_start, get_margin_top, get_modifier_mask, get_modifier_style,</p>

Name	Description
<i>Inherited from <code>??Object</code></i>	<code>--gsignals--</code> , <code>getv</code> , <code>is_floating</code> , <code>newv</code> , <code>notify</code> , <code>thaw_notify</code>
<i>Inherited from <code>gi.repository.Gtk.Buildable</code></i>	<code>add_child</code> , <code>construct_child</code> , <code>custom_finished</code> , <code>custom_tag_end</code> , <code>custom_tag_start</code> , <code>get_internal_child</code> , <code>parser_finished</code> , <code>set_buildable_property</code>

## Index

- `__main__` (*module*), 5
  - `__main__.run` (*function*), 5
- `model` (*package*), 6
  - `model.Ciudad` (*module*), 7
    - `model.Ciudad.Ciudad` (*class*), 7
  - `model.conector` (*module*), 21–22
    - `model.conector.Conexion` (*class*), 21–22
  - `model.Curso` (*module*), 8–9
    - `model.Curso.Curso` (*class*), 8–9
  - `model.Departamento` (*module*), 10
    - `model.Departamento.Departamento` (*class*), 10
  - `model.Estudiante` (*module*), 11–12
    - `model.Estudiante.Estudiante` (*class*), 11–12
  - `model.Horario` (*module*), 13
    - `model.Horario.Horario` (*class*), 13
  - `model.Persona` (*module*), 14–16
    - `model.Persona.Persona` (*class*), 14–16
  - `model.Planificacion` (*module*), 17
    - `model.Planificacion.Planificacion` (*class*), 17
  - `model.Profesor` (*module*), 18–20
    - `model.Profesor.Profesor` (*class*), 18–20
- `view` (*package*), 23
  - `view.frmCrearCurso` (*module*), 24–34
    - `view.frmCrearCurso.Frm_Crear_Curso` (*class*), 24–34
  - `view.frmCrearEstudiante` (*module*), 35–47
    - `view.frmCrearEstudiante.Frm_Crear_Estudiante` (*class*), 35–47
  - `view.frmCrearHorario` (*module*), 48–58
    - `view.frmCrearHorario.Frm_Crear_Horario` (*class*), 48–58
  - `view.frmCrearNombramiento` (*module*), 59–69
    - `view.frmCrearNombramiento.Frm_Crear_Nombramiento` (*class*), 59–69
  - `view.frmCrearProfesor` (*module*), 70–82
    - `view.frmCrearProfesor.Frm_Crear_Profesor` (*class*), 70–82
  - `view.frmListaCursos` (*module*), 83–93
    - `view.frmListaCursos.Frm_Lista_Curso` (*class*), 83–93
  - `view.frmListaEstudiante` (*module*), 94–105
    - `view.frmListaEstudiante.Frm_Lista_Estudiante` (*class*), 94–105
  - `view.frmListaProfesor` (*module*), 106–117
    - `view.frmListaProfesor.Frm_Lista_Profesor` (*class*), 106–117
  - `view.frmPrincipalEstudiante` (*module*), 118–127
    - `view.frmPrincipalEstudiante.Frm_Principal_Estudiante` (*class*), 118–127
  - `view.frmPrincipalProfesor` (*module*), 128–138
    - `view.frmPrincipalProfesor.Frm_Principal_Profesor` (*class*), 128–138
  - `view.frmRol` (*module*), 139–148
    - `view.frmRol.Frm_Rol` (*class*), 139–148
  - `view.scroll` (*module*), 149–157
    - `view.scroll.TreeViewFilterWindow` (*class*), 149–157