Parallel Programming

CUDA Streams

Phạm Trọng Nghĩa
ptnghia@fit.hcmus.edu.vn

Host device data transfer

Memory Allocation Types

- Device memory (cannot be paged)
- (Host) Pageable memory
- (Host) Pinned memory
- (Both) Mapped memory
- (Both) Unified memory

What we learn

Pageable Data Transfer



Pinned Data Transfer



Virtual Memory Management

- Modern computers use virtual memory management
  - Many virtual memory spaces mapped into a single physical memory
  - Virtual addresses (pointer values) are translated into physical addresses
- Not all variables and data structures are always in the physical memory
  - Each virtual address space is divided into pages that are mapped into and out of the physical memory
  - Virtual memory pages can be mapped out of the physical memory (page-out) to make room
  - Whether or not a variable is in the physical memory is checked at address translation time

Memory Allocation Types

- Pagable memory is transferred using the host CPU (memory Map I/O)
- Pinned memory is transferred using the DMA engines
  - Frees the CPU for asynchronous execution
  - Achieves a higher percent of peak bandwidth
- ***cudaMemcpy()*** use **DMA (Direct Memory Access) hardware**
  - Hardware unit specialized to transfer a number of bytes requested by OS
  - Between physical memory address space regions
  - Uses system interconnect, typically PCIe in today's systems



DMA cần biết địa chỉ vật lý

Data Transfer and Virtual Memory

- DMA uses physical addresses
  - When cudaMemcpy() copies an array, it is implemented as one or more DMA transfers
  - Address is translated and page presence checked for the entire source and destination regions at the beginning of each DMA transfer
  - No address translation for the rest of the same DMA transfer so that high efficiency can be achieved
- The *OS could accidentally page-out the data that is being read or written by a DMA* and page-in another virtual page into the same physical location

Pinned Memory & DMA Data Transfer

- Pinned memory are virtual memory pages that are specially marked so that they ***cannot be paged out***
- Allocated with a special system API function call
- a.k.a. Page Locked Memory, Locked Pages, etc.
- CPU memory that serve as the source or destination of a DMA transfer ***must be allocated as pinned memory***

Pageable memory

- The memory allocated in host is by ***default pageable memory*** (malloc)
- To transfer this data to the device, the CUDA run time ***copies this memory to a temporary pinned memory*** and then transfers to the device memory.
- There are two memory transfers ➔ **Slow**



Pageable memory - Usage

```
int* h_in = (int*)malloc(nBytes);
// Init data for h_in ...

int* d_in;
cudaMalloc(&d_in, nBytes);

// Copy data to device memories
cudaMemcpy(d_in, in, nBytes, cudaMemcpyHostToDevice));

cudaFree(d_in);
free(in);
```

Pageable memory - Usage



Pageable

Pinned memory

- The data can be initialized directly in the **host pinned memory**.

Không tốn thêm 1 lần copy, nhưng chỉ nên pin đúng lúc

- ***Avoid two data transfers*** as in pageable memory.
- Make the process faster but at the cost of host performance.
  - When data is initialized in the *pinned memory*, the memory availability for host processing is reduced



Pinned memory

- cudaHostAlloc(), three parameters:
  - Address of pointer to the allocated memory
  - Size of the allocated memory in bytes
  - Option (Ex: cudaHostAllocDefault)
- cudaFreeHost(), one parameter
  - Pointer to the memory to be freed

Pinned memory - Usage

```
int* h_in;
int* d_in
cudaMallocHost(&h_in, nBytes);
// Init data for h_in ...

cudaMalloc(&d_in, nBytes);

// Copy data to device memories
cudaMemcpy(d_in1, in1, nBytes, cudaMemcpyHostToDevice);
//...
cudaFree(d_in);
cudaFreeHost(h_in);
```

Pinned memory - Usage



Mapped memory

Copy trực tiếp CPU <=> GPU mà không cần vùng nhớ đệm

- Mapped memory (zero-copy memory): pinned memory that is mapped into the device address space.
- ***Both host and device have direct access*** to this memory.
- **Pros**:
  - Can leverage host memory when there is insufficient device memory.
  - Can avoid explicit data transfers between host and device.
  - Improves PCIe transfer rates

CUDA driver tự động truyền dữ liệu cho mình

- **Cons**:
  - Transfer will happen during execution which will increase the processing time considerably

Mapped memory - Usage

- Host allocation:

```
int* h_a2, * h_b2, * h_c2;
cudaHostAlloc((int**)&h_a2, nBytes, cudaHostAllocMapped);
cudaHostAlloc((int**)&h_b2, nBytes, cudaHostAllocMapped);
cudaHostAlloc((int**)&h_c2, nBytes, cudaHostAllocMapped);
```

- Device allocation:

```
int* d_a2, * d_b2, * d_c2;
cudaHostGetDevicePointer(&d_a2, h_a2, 0);
cudaHostGetDevicePointer(&d_b2, h_b2, 0);
cudaHostGetDevicePointer(&d_c2, h_c2, 0);
```

  - ***cudaHostGetDevicePointer***: Passes back the device pointer corresponding to the mapped, pinned host buffer allocated by cudaHostAlloc()

Unified memory

Vùng nhớ hợp nhất
=> Hiện giờ đang được recommend

- More general than Mapped memory



Unified memory

- Is a single memory address space ***accessible both from the host and from the device***.
- The hardware/software handles ***automatically*** the data migration between the host and the device maintaining consistency between them.
- **Pros**:
  - No explicit allocation and recovery of memory for device needed. This ***reduces programming complexity***.
  - Enabling ***larger arrays*** than the device memory size.
- **Cons**:

Cần thêm các câu lệnh chạy ngầm định bên dưới

  - Adds additional instructions under the hood for memory management

Unified memory - Usage

- Only need 1 initialization

Host và Device đều có thể dùng a,b,c

```
int *a, *b, *c;
cudaMallocManaged((int **)&a, nBytes);
cudaMallocManaged((int **)&b, nBytes);
cudaMallocManaged((int **)&c, nBytes);
```

- cudaMallocManaged()
  - Allocates an object in the Unified Memory address space.
  - Address of a pointer to the allocated object
  - Size of the allocated object in terms of bytes
- cudaFree()
  - Frees object from unified memory.
- cudaMemcpy()
  - Copy data between different arrays, regardless of position
  - Direction: cudaMemcpyDefault

Comparision

- Runing Matrix addition with #rows = 4096, #cols = 8192
- Run on Tesla T4 (C.C 7.5)

Memory	Total run time
Pageable	152.19 ms
Pinned	38.22 ms
Mapped	22.00 ms
Unified	122.11 ms

Note: *these numbers will change depend on hardware*

CUDA STREAM

Introduction

- Optimization: try to make full use of hardware resources, don’t let any of them idle
- So far, we have discussed about optimization limited to the scope of a kernel

  Phải có đủ block để che Latency

  - Need enough blocks to utilize SMs
  - In each SM, need enough independent instructions (coming from one warp or from different warps) to utilize execution pipelines, hide latency
  - Minimize warp divergence
- Today, we will discuss about optimization in a bigger scope: outside a kernel

Simple processing Flow



1. Copy input data from CPU memory to GPU memory
2. Launch a GPU Kernel
3. Copy results from GPU memory to CPU memory
4. Repeat Many Times

Source: Justin Luitjens, CUDA Streams, GTC2014

Simple processing Flow

- So far, the way we use cudaMemcpy serializes data transfer and GPU computation for MatAddKernel()



idle = rảnh, không làm việc

Concurrency Through Pipelining

- Serial

- Concurrent– overlap kernel and D2H copy



Source: Justin Luitjens, CUDA Streams, GTC2014

Concurrency Through Pipelining

- Serial (1x)

- 2-way concurrency (up to 2x)



- 3-way concurrency (up to 3x)

- **4-way concurrency** (3x+)



- **4+ way concurrency**



Source: Justin Luitjens, CUDA Streams, GTC2014

Overlap tasks

- With most current devices, in the extreme, we can overlap:

  many host computations (if utilize CPU cores)

  and many device computations (kernels)

  and one H2D

  and one D2H

- Basic conditions to overlap tasks:
  - These tasks are independent of each other
  - There are enough hardware resources for these tasks

In CUDA, how to overlap tasks?

When host calls a CUDA command, there are 2 possible situations:

host gọi và đợi

- **Synchronous:** host sends this command to a device queue and waits until it finishes

  E.g, `cudaMemcpy`

host gọi và có thể làm việc khác

- **Asynchronous:** host sends this command to a device queue and continues to do other works without waiting this command to finish

  E.g., host calls a kernel



By default, we can overlap a host computation and a device computation

How to overlap other tasks (e.g., a kernel with another kernel)?

Image source: Justin Luitjens, CUDA Streams, GTC2014

In CUDA, how to overlap tasks?

- A CUDA stream is a task queue of device

  Host sends device tasks to this queue
- Tasks in the same stream will be executed by device sequentially in FIFO order
- Tasks in different streams will have no order with each other and can overlap with each other
- Driver ensures that commands in a queue are processed in sequence





Stream CUDA commands

- **Create stream**

```
cudaStream_t stream;
cudaStreamCreate(&stream);
```
Tạo stream bình thường

- **Destroy stream**

```
cudaStreamDestroy(stream);
```

- **Send tasks to stream**
  - ```
    kernel<<<gridSize, blockSize,
                      0, // Share memory
             stream>>>(…);
    ```
    Kernel chạy ở stream nào
  - ```
    cudaMemcpyAsync(dst, src, size, dir,
                    stream);
    ```
    Mem-copy ở stream nào

Default stream (stream 0 / NULL stream)

- By default, tasks will be sent to stream 0
- Note: stream 0 synchronizes with other streams

  E.g., host sends tasks (T) to streams (S) in order T0-S0, T-S1, T-S2, T1-S0, then in device:

  - First, execute T0-S0
  - After finishing T0-S0, execute T-S1, T-S2 (T-S1 and T-S2 can overlap)
  - After finishing T-S1 and T-S2, execute T1-S0
- To overlap
  - Option 1: replace stream 0 by stream non-0
  - Option 2: create stream non-0 as follows

```
cudaStreamCreateWithFlags(&stream,
                          cudaStreamNonBlocking)
```

Tạo stream được phép // với stream 0

Example: overlap kernels

- Assume a kernel `foo` only utilizes 50% of device resource
- **Use stream 0**

```
foo<<<blocks, threads>>>();
foo<<<blocks, threads>>>();
```

- **Use stream 0 and stream non-0**

```
cudaStream_t stream1;
cudaStreamCreate(&stream1);
foo<<<blocks, threads>>>();
foo<<<blocks, threads,
          0, stream1>>>();
cudaStreamDestroy(stream1);
```

Image source: Justin Luitjens, CUDA Streams, GTC2014

Example: overlap kernels

- Assume a kernel `foo` only utilizes 50% of device resource
- **Use stream 0**

```
foo<<<blocks, threads>>>();
foo<<<blocks, threads>>>();
```

- **Use stream 0 and stream non-0**

```
cudaStream_t stream1;
cudaStreamCreateWithFlags(
   &stream1, cudaStreamNonBlocking);
foo<<<blocks, threads>>>();
foo<<<blocks, threads,
      0, stream1>>>();
cudaStreamDestroy(stream1);
```



Image source: Justin Luitjens, CUDA Streams, GTC2014

Example: overlap kernels

- Assume a kernel foo only utilizes 50% of device resource
- **Use stream non-0**

Thường dùng cách này nhiều nhất
Dùng các stream khác 0

```
cudaStream_t stream1, stream2;
cudaStreamCreate(&stream1);
cudaStreamCreate(&stream2);
foo<<<blocks, threads,
         0, stream1>>>();
foo<<<blocks, threads,
         0, stream2>>>();
cudaStreamDestroy(stream1);
cudaStreamDestroy(stream2);
```



Image source: Justin Luitjens, CUDA Streams, GTC2014

Example: overlap data transfer with other tasks

- **Example 1**

```
cudaMemcpy(...);
foo<<<...>>>();
```

Đây là hàm đồng bộ => CPU phải chờ

- **Example 2** Trong lúc copy CPU chạy tiếp

```
cudaMemcpyAsync(..., stream1);
foo<<<..., stream1>>>();
```

Need to **pin** 📌 host memory: replace `malloc` by `cudaMallocHost` (and `free` by `cudaFreeHost`)
Why? In order for host to continue to do other works and device hardware to transfer data, the physical memory storing data in host must be kept intact – must be pinned; otherwise, data stored in the physical memory of host can be changed by OS while device is transferring data (because of virtual memory mechanism in host) ☹

Image source: Justin Luitjens, CUDA Streams, GTC2014

Example: overlap data transfer with other tasks

- **Example 1**

```
cudaMemcpy(...);
foo<<<...>>>();
```

- **Example 2**

```
cudaMemcpyAsync(..., stream1);
foo<<<..., stream1>>>();
```

- **Example 3**

```
cudaMemcpyAsync(..., stream1);
foo<<<..., stream2>>>();
```



Image source: Justin Luitjens, CUDA Streams, GTC2014

Device Overlap

- Some CUDA devices support device overlap
- Simultaneously execute a kernel while copying data between device and host memory

```
cudaDeviceProp devProv;
cudaGetDeviceProperties(&devProv, 0);
printf("Number of copy engines: %d\n",
       devProv.asyncEngineCount);
```

- RTX 3050 Laptop GPU: **1**
  - Can only transfer 1 direction at one time.
- **Tesla T4 (Colab)**: **3**
  - H2D, D2H, NVLink (With 1 other GPU)
- Volta V100-32GB GPU: **6**
  - H2D, D2H, 4 NVLink (With 4 other GPU) 1 bộ gồm 5 card

Conceptual View of Streams



Host chủ động phân phối công việc cho các stream khác nhau

Concurrent memory copies

- cudaMemcpy(...)
  - Places transfer into default stream
  - Synchronous: Must complete prior to returning
- cudaMemcpyAsync(..., &stream)
  - Places transfer into stream and returns immediately
- To achieve concurrency 4 điều kiện để song song
  - Transfers must be in a ***non-default stream***
  - Must use ***async*** copies
  - ***1 transfer per direction*** at a time
  - Memory on the host must be ***pinned***

Synchronization

When we let tasks run asynchronously, we will need to synchronize at some point

- Synchronize everything
  - cudaDeviceSynchronize() synchronize mạnh nhất
  - Blocks host until all issued CUDA calls are complete
- Synchronize host w.r.t. a specific stream
  - cudaStreamSynchronize(stream)
  - Blocks host until all issued CUDA calls in stream are complete host chờ 1 stream
- Synchronize host or devices using events

More Synchronization



Less Synchronization

Synchronization

Synchronize host with device

```
cudaDeviceSynchronize();
```

Synchronize host with a stream

- `cudaStreamSynchronize(stream);`
- `cudaStreamQuery(stream);` Xem stream hoạt động xong chưa
  - Host doesn't have to wait
  - Return: `cudaSuccess` if all tasks in `stream` are finished; `cudaErrorNotReady` otherwise

CUDA EVENTS

- Provide a mechanism to signal when operations have occurred in a stream
  - Useful for profiling and synchronization
- Events have a boolean state:
  - Occurred
  - Not Occurred
  - **Important: Default state = occurred**

Synchronization

Synchronize host with a point in a stream: use event

- Create event

```
cudaEvent_t event;
cudaEventCreate(&event);
```

- Send event to stream

```
cudaEventRecord(event, stream);
- Set the event state to not occurred
- Event state is set to occurred when it reaches the front
of the stream
```

- Synchronize host with event
  - `cudaEventSynchronize(event);` Host dừng đến khi event xảy ra
  - `cudaEventQuery(event);//Similar to cudaStreamQuery`
- Destroy event

```
cudaEventDestroy(event);
```

Synchronization

Synchronize streams with each other

`cudaStreamWaitEvent(stream, event)`

- `stream` waits `event` (of another stream) to happen, only then it continues to do tasks enqueued to `stream` after this command
- Host doesn't have to wait

THE END

Reference

- [1] Wen-Mei, W. Hwu, David B. Kirk, and Izzat El Hajj. *Programming Massively Parallel Processors: A Hands-on Approach*. Morgan Kaufmann, 2022
- [2] Cheng John, Max Grossman, and Ty McKercher. *Professional Cuda C Programming*. John Wiley & Sons, 2014
- [3] *Illinois-NVIDIA GPU Teaching Kit*
- [4] Cuda Streamsbest Practices And Common Pitfalls, Justin Luitjens -NVIDIA