

## mongoose Scan Report

Project Name	mongoose
Scan Start	Friday, June 21, 2024 10:59:58 PM
Preset	Checkmarx Default
Scan Time	00h:04m:35s
Lines Of Code Scanned	18588
Files Scanned	8
Report Creation Time	Friday, June 21, 2024 11:05:23 PM
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053</a>
Team	CxServer
Checkmarx Version	8.7.0
Scan Type	Full
Source Origin	LocalPath
Density	1/100 (Vulnerabilities/LOC)
Visibility	Public

## Filter Settings

### **Severity**

Included: High, Medium, Low, Information

Excluded: None

### **Result State**

Included: Confirmed, Not Exploitable, To Verify, Urgent, Proposed Not Exploitable

Excluded: None

### **Assigned to**

Included: All

### **Categories**

Included:

Uncategorized	All
Custom	All
PCI DSS v3.2	All
OWASP Top 10 2013	All
FISMA 2014	All
NIST SP 800-53	All
OWASP Top 10 2017	All
OWASP Mobile Top 10 2016	All

Excluded:

Uncategorized	None
Custom	None
PCI DSS v3.2	None
OWASP Top 10 2013	None
FISMA 2014	None

NIST SP 800-53	None
OWASP Top 10 2017	None
OWASP Mobile Top 10 2016	None

**Results Limit**


Results limit per query was set to 50

**Selected Queries**


Selected queries are listed in [Result Summary](#)

---


## Result Summary



## Most Vulnerable Files



## Top 5 Vulnerabilities



## Scan Summary - OWASP Top 10 2017

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2017](#)

Category	Threat Agent	Exploitability	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	App. Specific	EASY	COMMON	EASY	SEVERE	App. Specific	30	17
A2-Broken Authentication	App. Specific	EASY	COMMON	AVERAGE	SEVERE	App. Specific	1	1
A3-Sensitive Data Exposure	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	App. Specific	6	3
A4-XML External Entities (XXE)	App. Specific	AVERAGE	COMMON	EASY	SEVERE	App. Specific	0	0
A5-Broken Access Control*	App. Specific	AVERAGE	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A6-Security Misconfiguration	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A7-Cross-Site Scripting (XSS)	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A8-Insecure Deserialization	App. Specific	DIFFICULT	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A9-Using Components with Known Vulnerabilities*	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	MODERATE	App. Specific	85	85
A10-Insufficient Logging & Monitoring	App. Specific	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	App. Specific	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - OWASP Top 10 2013

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2013](#)

Category	Threat Agent	Attack Vectors	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	AVERAGE	SEVERE	ALL DATA	0	0
A2-Broken Authentication and Session Management	EXTERNAL, INTERNAL USERS	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	AFFECTED DATA AND FUNCTIONS	0	0
A3-Cross-Site Scripting (XSS)	EXTERNAL, INTERNAL, ADMIN USERS	AVERAGE	VERY WIDESPREAD	EASY	MODERATE	AFFECTED DATA AND SYSTEM	0	0
A4-Insecure Direct Object References	SYSTEM USERS	EASY	COMMON	EASY	MODERATE	EXPOSED DATA	0	0
A5-Security Misconfiguration	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	EASY	MODERATE	ALL DATA AND SYSTEM	0	0
A6-Sensitive Data Exposure	EXTERNAL, INTERNAL, ADMIN USERS, USERS BROWSERS	DIFFICULT	UNCOMMON	AVERAGE	SEVERE	EXPOSED DATA	0	0
A7-Missing Function Level Access Control*	EXTERNAL, INTERNAL USERS	EASY	COMMON	AVERAGE	MODERATE	EXPOSED DATA AND FUNCTIONS	0	0
A8-Cross-Site Request Forgery (CSRF)	USERS BROWSERS	AVERAGE	COMMON	EASY	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0
A9-Using Components with Known Vulnerabilities*	EXTERNAL USERS, AUTOMATED TOOLS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	85	85
A10-Unvalidated Redirects and Forwards	USERS BROWSERS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - PCI DSS v3.2

Category	Issues Found	Best Fix Locations
PCI DSS (3.2) - 6.5.1 - Injection flaws - particularly SQL injection	0	0
PCI DSS (3.2) - 6.5.2 - Buffer overflows	21	13
PCI DSS (3.2) - 6.5.3 - Insecure cryptographic storage	0	0
PCI DSS (3.2) - 6.5.4 - Insecure communications	0	0
PCI DSS (3.2) - 6.5.5 - Improper error handling*	0	0
PCI DSS (3.2) - 6.5.7 - Cross-site scripting (XSS)	0	0
PCI DSS (3.2) - 6.5.8 - Improper access control	0	0
PCI DSS (3.2) - 6.5.9 - Cross-site request forgery	0	0
PCI DSS (3.2) - 6.5.10 - Broken authentication and session management	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - FISMA 2014

Category	Description	Issues Found	Best Fix Locations
Access Control	Organizations must limit information system access to authorized users, processes acting on behalf of authorized users, or devices (including other information systems) and to the types of transactions and functions that authorized users are permitted to exercise.	0	0
Audit And Accountability*	Organizations must: (i) create, protect, and retain information system audit records to the extent needed to enable the monitoring, analysis, investigation, and reporting of unlawful, unauthorized, or inappropriate information system activity; and (ii) ensure that the actions of individual information system users can be uniquely traced to those users so they can be held accountable for their actions.	0	0
Configuration Management	Organizations must: (i) establish and maintain baseline configurations and inventories of organizational information systems (including hardware, software, firmware, and documentation) throughout the respective system development life cycles; and (ii) establish and enforce security configuration settings for information technology products employed in organizational information systems.	6	3
Identification And Authentication*	Organizations must identify information system users, processes acting on behalf of users, or devices and authenticate (or verify) the identities of those users, processes, or devices, as a prerequisite to allowing access to organizational information systems.	1	1
Media Protection	Organizations must: (i) protect information system media, both paper and digital; (ii) limit access to information on information system media to authorized users; and (iii) sanitize or destroy information system media before disposal or release for reuse.	0	0
System And Communications Protection	Organizations must: (i) monitor, control, and protect organizational communications (i.e., information transmitted or received by organizational information systems) at the external boundaries and key internal boundaries of the information systems; and (ii) employ architectural designs, software development techniques, and systems engineering principles that promote effective information security within organizational information systems.	0	0
System And Information Integrity	Organizations must: (i) identify, report, and correct information and information system flaws in a timely manner; (ii) provide protection from malicious code at appropriate locations within organizational information systems; and (iii) monitor information system security alerts and advisories and take appropriate actions in response.	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - NIST SP 800-53

Category	Issues Found	Best Fix Locations
AC-12 Session Termination (P2)	0	0
AC-3 Access Enforcement (P1)	1	1
AC-4 Information Flow Enforcement (P1)	0	0
AC-6 Least Privilege (P1)	0	0
AU-9 Protection of Audit Information (P1)	0	0
CM-6 Configuration Settings (P2)	0	0
IA-5 Authenticator Management (P1)	0	0
IA-6 Authenticator Feedback (P2)	0	0
IA-8 Identification and Authentication (Non-Organizational Users) (P1)	0	0
SC-12 Cryptographic Key Establishment and Management (P1)	0	0
SC-13 Cryptographic Protection (P1)	6	3
SC-17 Public Key Infrastructure Certificates (P1)	0	0
SC-18 Mobile Code (P2)	0	0
SC-23 Session Authenticity (P1)*	0	0
SC-28 Protection of Information at Rest (P1)	0	0
SC-4 Information in Shared Resources (P1)	0	0
SC-5 Denial of Service Protection (P1)*	14	9
SC-8 Transmission Confidentiality and Integrity (P1)	0	0
SI-10 Information Input Validation (P1)*	11	3
SI-11 Error Handling (P2)*	57	57
SI-15 Information Output Filtering (P0)	0	0
SI-16 Memory Protection (P1)	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.



## Scan Summary - OWASP Mobile Top 10 2016

Category	Description	Issues Found	Best Fix Locations
M1-Improper Platform Usage	This category covers misuse of a platform feature or failure to use platform security controls. It might include Android intents, platform permissions, misuse of TouchID, the Keychain, or some other security control that is part of the mobile operating system. There are several ways that mobile apps can experience this risk.	0	0
M2-Insecure Data Storage	This category covers insecure data storage and unintended data leakage.	0	0
M3-Insecure Communication	This category covers poor handshaking, incorrect SSL versions, weak negotiation, cleartext communication of sensitive assets, etc.	0	0
M4-Insecure Authentication	This category captures notions of authenticating the end user or bad session management. This can include: -Failing to identify the user at all when that should be required -Failure to maintain the user's identity when it is required -Weaknesses in session management	0	0
M5-Insufficient Cryptography	The code applies cryptography to a sensitive information asset. However, the cryptography is insufficient in some way. Note that anything and everything related to TLS or SSL goes in M3. Also, if the app fails to use cryptography at all when it should, that probably belongs in M2. This category is for issues where cryptography was attempted, but it wasn't done correctly.	0	0
M6-Insecure Authorization	This is a category to capture any failures in authorization (e.g., authorization decisions in the client side, forced browsing, etc.). It is distinct from authentication issues (e.g., device enrolment, user identification, etc.). If the app does not authenticate users at all in a situation where it should (e.g., granting anonymous access to some resource or service when authenticated and authorized access is required), then that is an authentication failure not an authorization failure.	0	0
M7-Client Code Quality	This category is the catch-all for code-level implementation problems in the mobile client. That's distinct from server-side coding mistakes. This would capture things like buffer overflows, format string vulnerabilities, and various other code-level mistakes where the solution is to rewrite some code that's running on the mobile device.	0	0
M8-Code Tampering	This category covers binary patching, local resource modification, method hooking, method swizzling, and dynamic memory modification. Once the application is delivered to the mobile device, the code and data resources are resident there. An attacker can either directly modify the code, change the contents of memory dynamically, change or replace the system APIs that the application uses, or	0	0

	modify the application's data and resources. This can provide the attacker a direct method of subverting the intended use of the software for personal or monetary gain.		
M9-Reverse Engineering	This category includes analysis of the final core binary to determine its source code, libraries, algorithms, and other assets. Software such as IDA Pro, Hopper, otool, and other binary inspection tools give the attacker insight into the inner workings of the application. This may be used to exploit other nascent vulnerabilities in the application, as well as revealing information about back end servers, cryptographic constants and ciphers, and intellectual property.	0	0
M10-Extraneous Functionality	Often, developers include hidden backdoor functionality or other internal development security controls that are not intended to be released into a production environment. For example, a developer may accidentally include a password as a comment in a hybrid app. Another example includes disabling of 2-factor authentication during testing.	0	0

## Scan Summary - Custom


Category	Issues Found	Best Fix Locations
Must audit	0	0
Check	0	0
Optional	0	0

## Results Distribution By Status

First scan of the project

	High	Medium	Low	Information	Total
New Issues	10	120	69	0	199
Recurrent Issues	0	0	0	0	0
Total	10	120	69	0	199

Fixed Issues	0	0	0	0	0
--------------	---	---	---	---	---



## Results Distribution By State

	High	Medium	Low	Information	Total
Confirmed	0	0	0	0	0
Not Exploitable	0	0	0	0	0
To Verify	10	120	69	0	199
Urgent	0	0	0	0	0
Proposed Not Exploitable	0	0	0	0	0
Total	10	120	69	0	199

## Result Summary

Vulnerability Type	Occurrences	Severity
<a href="#">Buffer Overflow OutOfBound</a>	10	High
<a href="#">Dangerous Functions</a>	85	Medium
<a href="#">MemoryFree on StackVariable</a>	14	Medium
<a href="#">Buffer Overflow boundcpy WrongSizeParam</a>	9	Medium
<a href="#">Inadequate Encryption Strength</a>	6	Medium

<a href="#">Use of Zero Initialized Pointer</a>	3	Medium
<a href="#">Buffer Overflow AddressOfLocalVarReturned</a>	2	Medium
<a href="#">Wrong Size t Allocation</a>	1	Medium
<a href="#">Unchecked Return Value</a>	57	Low
<a href="#">NULL Pointer Dereference</a>	9	Low
<a href="#">Improper Resource Access Authorization</a>	1	Low
<a href="#">TOCTOU</a>	1	Low
<a href="#">Unchecked Array Index</a>	1	Low

## 10 Most Vulnerable Files

### High and Medium Vulnerabilities

File Name	Issues Found
mongoose/unit_test.c	92
mongoose/eap.c	17
mongoose/driver_stm32.c	13
mongoose/queue.c	5
mongoose/heap_4.c	2
mongoose/net.c	1

# Scan Results Details

## Buffer Overflow OutOfBound

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow OutOfBound Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
NIST SP 800-53: SI-10 Information Input Validation (P1)  
OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow OutOfBound\Path 1:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=1">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=1</a>
Status	New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that descriptors passes to s\_rxdesc, at line 39 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	39	127
Object	s_rxdesc	s_rxdesc

### Code Snippet

File Name mongoose/driver\_stm32.c  
Method static uint32\_t s\_rxdesc[ETH\_DESC\_CNT][ETH\_DS]; // RX descriptors

```
....
39. static uint32_t s_rxdesc[ETH_DESC_CNT][ETH_DS]; // RX
descriptors
```

File Name mongoose/driver\_stm32.c  
Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
127. s_rxdesc[i][1] = sizeof(s_rxbuf[i]) | BIT(14); // 2nd
address chained
```

#### Buffer Overflow OutOfBound\Path 2:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=1">http://WIN-</a>

[BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=2](http://BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=2)

Status New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that descriptors passes to s\_rxdesc, at line 39 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	39	126
Object	s_rxdesc	s_rxdesc

#### Code Snippet

File Name mongoose/driver\_stm32.c

Method static uint32\_t s\_rxdesc[ETH\_DESC\_CNT][ETH\_DS]; // RX descriptors

```
....
39. static uint32_t s_rxdesc[ETH_DESC_CNT][ETH_DS]; // RX
descriptors
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
126. s_rxdesc[i][0] = BIT(31); // Own
```

#### Buffer Overflow OutOfBound\Path 3:

Severity High

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=3>

Status New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that descriptors passes to s\_rxdesc, at line 39 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	39	128
Object	s_rxdesc	s_rxdesc

#### Code Snippet

File Name mongoose/driver\_stm32.c

Method static uint32\_t s\_rxdesc[ETH\_DESC\_CNT][ETH\_DS]; // RX descriptors

```
....
39. static uint32_t s_rxdesc[ETH_DESC_CNT][ETH_DS]; // RX
descriptors
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
128. s_rxdesc[i][2] = (uint32_t) (uintptr_t) s_rxbuf[i]; // Point
to data buffer
```

#### Buffer Overflow OutOfBound\Path 4:

Severity High

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=4>

Status New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that descriptors passes to s\_rxdesc, at line 39 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	39	129
Object	s_rxdesc	s_rxdesc

#### Code Snippet

File Name mongoose/driver\_stm32.c

Method static uint32\_t s\_rxdesc[ETH\_DESC\_CNT][ETH\_DS]; // RX descriptors

```
....
39. static uint32_t s_rxdesc[ETH_DESC_CNT][ETH_DS]; // RX
descriptors
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
129. s_rxdesc[i][3] =
```

#### Buffer Overflow OutOfBound\Path 5:

Severity High

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=4>



	<a href="http://BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=5">BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=5</a>
Status	New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that buffers passes to s\_rxbuf, at line 41 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	41	127
Object	s_rxbuf	s_rxdesc

#### Code Snippet

File Name mongoose/driver\_stm32.c  
Method static uint8\_t s\_rxbuf[ETH\_DESC\_CNT][ETH\_PKT\_SIZE]; // RX ethernet buffers

```
....
41. static uint8_t s_rxbuf[ETH_DESC_CNT][ETH_PKT_SIZE]; // RX ethernet
    buffers
```

File Name mongoose/driver\_stm32.c  
Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
127. s_rxdesc[i][1] = sizeof(s_rxbuf[i]) | BIT(14); // 2nd
    address chained
```

#### Buffer Overflow OutOfBound\Path 6:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=6">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=6</a>
Status	New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that buffers passes to s\_rxbuf, at line 41 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	41	126
Object	s_rxbuf	s_rxdesc

#### Code Snippet

File Name mongoose/driver\_stm32.c  
Method static uint8\_t s\_rxbuf[ETH\_DESC\_CNT][ETH\_PKT\_SIZE]; // RX ethernet buffers

```
....
41. static uint8_t s_rxbuf[ETH_DESC_CNT][ETH_PKT_SIZE]; // RX ethernet
    buffers
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
126. s_rxdesc[i][0] = BIT(31); // Own
```

### Buffer Overflow OutOfBound\Path 7:

Severity High

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=7>

Status New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in i, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that buffers passes to s\_rxbuf, at line 41 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	41	127
Object	s_rxbuf	i

### Code Snippet

File Name mongoose/driver\_stm32.c

Method static uint8\_t s\_rxbuf[ETH\_DESC\_CNT][ETH\_PKT\_SIZE]; // RX ethernet buffers

```
....
41. static uint8_t s_rxbuf[ETH_DESC_CNT][ETH_PKT_SIZE]; // RX ethernet
    buffers
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
127. s_rxdesc[i][1] = sizeof(s_rxbuf[i]) | BIT(14); // 2nd
    address chained
```

### Buffer Overflow OutOfBound\Path 8:

Severity High

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=7>

Status	<a href="#">53&amp;pathid=8</a> New
--------	--

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that buffers passes to s\_rxbuf, at line 41 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	41	128
Object	s_rxbuf	s_rxdesc

#### Code Snippet

File Name mongoose/driver\_stm32.c  
Method static uint8\_t s\_rxbuf[ETH\_DESC\_CNT][ETH\_PKT\_SIZE]; // RX ethernet buffers

```
....
41. static uint8_t s_rxbuf[ETH_DESC_CNT][ETH_PKT_SIZE]; // RX ethernet
    buffers
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
128. s_rxdesc[i][2] = (uint32_t) (uintptr_t) s_rxbuf[i]; // Point
    to data buffer
```

#### Buffer Overflow OutOfBound\Path 9:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=9">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=9</a>
Status	New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in i, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that buffers passes to s\_rxbuf, at line 41 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	41	128
Object	s_rxbuf	i

#### Code Snippet

File Name mongoose/driver\_stm32.c  
Method static uint8\_t s\_rxbuf[ETH\_DESC\_CNT][ETH\_PKT\_SIZE]; // RX ethernet buffers

```
....
41. static uint8_t s_rxbuf[ETH_DESC_CNT][ETH_PKT_SIZE]; // RX ethernet
    buffers
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
128. s_rxdesc[i][2] = (uint32_t) (uintptr_t) s_rxbuf[i]; // Point
    to data buffer
```

### Buffer Overflow OutOfBound\Path 10:

Severity High

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=10>

Status New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_init in s\_rxdesc, at line 119 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that buffers passes to s\_rxbuf, at line 41 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	41	129
Object	s_rxbuf	s_rxdesc

### Code Snippet

File Name mongoose/driver\_stm32.c

Method static uint8\_t s\_rxbuf[ETH\_DESC\_CNT][ETH\_PKT\_SIZE]; // RX ethernet buffers

```
....
41. static uint8_t s_rxbuf[ETH_DESC_CNT][ETH_PKT_SIZE]; // RX ethernet
    buffers
```

File Name mongoose/driver\_stm32.c

Method static bool mg\_tcpip\_driver\_stm32\_init(struct mg\_tcpip\_if \*ifp) {

```
....
129. s_rxdesc[i][3] =
```

## Dangerous Functions

Query Path:

CPP\Cx\CPP Medium Threat\Dangerous Functions Version:1

### Categories

OWASP Top 10 2013: A9-Using Components with Known Vulnerabilities

OWASP Top 10 2017: A9-Using Components with Known Vulnerabilities

### Description

#### **Dangerous Functions\Path 1:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=104">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=104</a>
Status	New

The dangerous function, memcpy, was found in use at line 169 in mongoose/driver\_stm32.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	180	180
Object	memcpy	memcpy

#### Code Snippet

File Name mongoose/driver\_stm32.c  
Method static size\_t mg\_tcpip\_driver\_stm32\_tx(const void \*buf, size\_t len,

```
....  
180.      memcpy(s_txbuf[s_txno], buf, len);      // Copy data
```

#### **Dangerous Functions\Path 2:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=105">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=105</a>
Status	New

The dangerous function, memcpy, was found in use at line 2070 in mongoose/queue.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2098	2098
Object	memcpy	memcpy

#### Code Snippet

File Name mongoose/queue.c  
Method static BaseType\_t prvCopyDataToQueue( Queue\_t \* const pxQueue, const void \*pvItemToQueue, const BaseType\_t xPosition )

```

.....
2098.          ( void ) memcpy( ( void * ) pxQueue->pcWriteTo,
pvItemToQueue, ( size_t ) pxQueue->uxItemSize ); /*lint !e961 !e418
!e9087 MISRA exception as the casts are only redundant for some ports,
plus previous logic ensures a null pointer can only be passed to
memcpy() if the copy size is 0. Cast to void required by function
signature and safe as no alignment requirement and copy length specified
in bytes. */

```

### Dangerous Functions\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=106">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=106</a>
Status	New

The dangerous function, memcpy, was found in use at line 2070 in mongoose/queue.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2111	2111
Object	memcpy	memcpy

### Code Snippet

File Name mongoose/queue.c  
Method static BaseType\_t prvCopyDataToQueue( Queue\_t \* const pxQueue, const void \*pvItemToQueue, const BaseType\_t xPosition )

```

.....
2111.          ( void ) memcpy( ( void * ) pxQueue-
>u.xQueue.pcReadFrom, pvItemToQueue, ( size_t ) pxQueue->uxItemSize );
/*lint !e961 !e9087 !e418 MISRA exception as the casts are only
redundant for some ports. Cast to void required by function signature
and safe as no alignment requirement and copy length specified in bytes.
Assert checks null pointer only used when length is 0. */

```

### Dangerous Functions\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=107">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=107</a>
Status	New

The dangerous function, memcpy, was found in use at line 2149 in mongoose/queue.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c

Line	2162	2162
Object	memcpy	memcpy

**Code Snippet**

File Name mongoose/queue.c

Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2162.             ( void ) memcpy( ( void * ) pvBuffer, ( void * )
pxQueue->u.xQueue.pcReadFrom, ( size_t ) pxQueue->uxItemSize ); /*lint
!e961 !e418 !e9087 MISRA exception as the casts are only redundant for
some ports. Also previous logic ensures a null pointer can only be
passed to memcpy() when the count is 0. Cast to void required by
function signature and safe as no alignment requirement and copy length
specified in bytes. */
```

**Dangerous Functions\Path 5:**

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=108>

Status New

The dangerous function, memcpy, was found in use at line 2446 in mongoose/queue.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2496	2496
Object	memcpy	memcpy

**Code Snippet**

File Name mongoose/queue.c

Method BaseType\_t xQueueCRRReceive( QueueHandle\_t xQueue, void \*pvBuffer, TickType\_t xTicksToWait )

```
....
2496.             ( void ) memcpy( ( void * ) pvBuffer, (
void * ) pxQueue->u.xQueue.pcReadFrom, ( unsigned ) pxQueue->uxItemSize
);
```

**Dangerous Functions\Path 6:**

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=109>

Status New

The dangerous function, memcpy, was found in use at line 2584 in mongoose/queue.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2604	2604
Object	memcpy	memcpy

#### Code Snippet

File Name mongoose/queue.c

Method BaseType\_t xQueueCRReceiveFromISR( QueueHandle\_t xQueue, void \*pvBuffer, BaseType\_t \*pxCoRoutineWoken )

```
....
2604.                ( void ) memcpy( ( void * ) pvBuffer, ( void * )
pxQueue->u.xQueue.pcReadFrom, ( unsigned ) pxQueue->uxItemSize );
```

#### Dangerous Functions\Path 7:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=110>

Status New

The dangerous function, memcpy, was found in use at line 1664 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1897	1897
Object	memcpy	memcpy

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_str(void) {

```
....
1897.        memcpy(a.ip, &addr, sizeof(uint32_t));
```

#### Dangerous Functions\Path 8:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=111>

Status New



The dangerous function, memcpy, was found in use at line 1993 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2010	2010
Object	memcpy	memcpy

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_util(void) {

```
....  
2010.    memcpy(&ipv4, a.ip, sizeof(ipv4));
```

#### Dangerous Functions\Path 9:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=112">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=112</a>
Status	New

The dangerous function, memcpy, was found in use at line 2940 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2949	2949
Object	memcpy	memcpy

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void producer(void \*param) {

```
....  
2949.    memcpy(buf, &tmp[ofs], len);
```

#### Dangerous Functions\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=113">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=113</a>
Status	New

The dangerous function, strcat, was found in use at line 1250 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1255	1255
Object	strcat	strcat

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void f4(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {

```
....  
1255.         strcat((char *) fn_data, "m");
```

#### Dangerous Functions\Path 11:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=114>

Status New

The dangerous function, strcat, was found in use at line 1250 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1258	1258
Object	strcat	strcat

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void f4(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {

```
....  
1258.         strcat((char *) fn_data, "f");
```

#### Dangerous Functions\Path 12:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=115>

Status New

The dangerous function, strcat, was found in use at line 1250 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c

Line	1260	1260
Object	strcat	strcat

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void f4(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {

```
....  
1260.      strcat((char *) fn_data, "c");
```

#### Dangerous Functions\Path 13:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=116>

Status New

The dangerous function, strcat, was found in use at line 1264 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1270	1270
Object	strcat	strcat

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void f4c(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {

```
....  
1270.      strcat((char *) fn_data, "m");
```

#### Dangerous Functions\Path 14:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=117>

Status New

The dangerous function, strcat, was found in use at line 1264 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1274	1274
Object	strcat	strcat

**Code Snippet**

File Name mongoose/unit\_test.c

Method static void f4c(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {

```
....  
1274.      strcat((char *) fn_data, "f");
```

**Dangerous Functions\Path 15:**

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=118>

Status New

The dangerous function, strcat, was found in use at line 1264 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1276	1276
Object	strcat	strcat

**Code Snippet**

File Name mongoose/unit\_test.c

Method static void f4c(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {

```
....  
1276.      strcat((char *) fn_data, "c");
```

**Dangerous Functions\Path 16:**

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=119>

Status New

The dangerous function, strcpy, was found in use at line 1311 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1365	1365
Object	strcpy	strcpy

**Code Snippet**

File Name mongoose/eap.c

```
Method      static void eap_request(ppp_pcb *pcb, u_char *inp, int id, int len) {  
  
    ....  
    1365.          strcpy(rhostname, SRP_PSEUDO_ID);
```

#### Dangerous Functions\Path 17:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=120">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=120</a>
Status	New

The dangerous function, strlen, was found in use at line 225 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	232	232
Object	strlen	strlen

#### Code Snippet

```
File Name    mongoose/eap.c  
Method       void eap_authwithpeer(ppp_pcb *pcb, const char *localname) {  
  
    ....  
    232.          pcb->eap.es_client.ea_namelen = strlen(localname);
```

#### Dangerous Functions\Path 18:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=121">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=121</a>
Status	New

The dangerous function, strlen, was found in use at line 315 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	328	328
Object	strlen	strlen

#### Code Snippet

```
File Name    mongoose/eap.c  
Method       pncrypt_setkey(int timeoffs)
```

```
....
328.          SHA1Update(&ctxt, pn_secret, strlen(pn_secret));
```

### Dangerous Functions\Path 19:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=122">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=122</a>
Status	New

The dangerous function, strlen, was found in use at line 315 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	330	330
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method pncrypt\_setkey(int timeoffs)

```
....
330.          SHA1Update(&ctxt, tbuf, strlen(tbuf));
```

### Dangerous Functions\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=123">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=123</a>
Status	New

The dangerous function, strlen, was found in use at line 638 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	664	664
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method static void eap\_send\_request(ppp\_pcb \*pcb) {

```
.....
664.                                int len = (int)strlen(pcb->remote_name);
```

### Dangerous Functions\Path 21:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=124">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=124</a>
Status	New

The dangerous function, strlen, was found in use at line 638 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	707	707
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method static void eap\_send\_request(ppp\_pcb \*pcb) {

```
.....
707.                                len = strlen(str);
```

### Dangerous Functions\Path 22:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=125">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=125</a>
Status	New

The dangerous function, strlen, was found in use at line 876 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	880	880
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method void eap\_authpeer(ppp\_pcb \*pcb, const char \*localname) {

```
.....  
880.          pcb->eap.es_server.ea_namelen = strlen(localname);
```

### Dangerous Functions\Path 23:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=126">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=126</a>
Status	New

The dangerous function, strlen, was found in use at line 1197 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1210	1210
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method name\_of\_pn\_file()

```
.....  
1210.          pl = strlen(user) + strlen(file) + 2;
```

### Dangerous Functions\Path 24:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=127">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=127</a>
Status	New

The dangerous function, strlen, was found in use at line 1197 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1210	1210
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method name\_of\_pn\_file()



```
.....
1210.          pl = strlen(user) + strlen(file) + 2;
```

### Dangerous Functions\Path 25:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=128">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=128</a>
Status	New

The dangerous function, strlen, was found in use at line 1311 in mongoose/eap.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1515	1515
Object	strlen	strlen

#### Code Snippet

File Name mongoose/eap.c  
Method static void eap\_request(ppp\_pcb \*pcb, u\_char \*inp, int id, int len) {

```
.....
1515.          rhostnamelen = (int)strlen(rhostname);
```

### Dangerous Functions\Path 26:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=129">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=129</a>
Status	New

The dangerous function, strlen, was found in use at line 356 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	397	397
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {

```
.....
397.                prop.val.len == strlen("test_content_val_2"));
```

### Dangerous Functions\Path 27:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=130">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=130</a>
Status	New

The dangerous function, strlen, was found in use at line 356 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	402	402
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {

```
.....
402.                prop.key.len == strlen("test_key_1"));
```

### Dangerous Functions\Path 28:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=131">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=131</a>
Status	New

The dangerous function, strlen, was found in use at line 356 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	404	404
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {

```
.....  
404.                prop.val.len == strlen("test_value_1"));
```

### Dangerous Functions\Path 29:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=132">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=132</a>
Status	New

The dangerous function, strlen, was found in use at line 356 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	409	409
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {

```
.....  
409.                prop.key.len == strlen("test_key_2"));
```

### Dangerous Functions\Path 30:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=133">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=133</a>
Status	New

The dangerous function, strlen, was found in use at line 356 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	411	411
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {

```
....  
411.                prop.val.len == strlen("test_value_2"));
```

### Dangerous Functions\Path 31:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=134">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=134</a>
Status	New

The dangerous function, strlen, was found in use at line 459 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	461	461
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void check\_mqtt\_message(struct mg\_mqtt\_opts \*opts,

```
....  
461.    if (opts->topic.len != strlen(data->topic) ||
```

### Dangerous Functions\Path 32:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=135">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=135</a>
Status	New

The dangerous function, strlen, was found in use at line 459 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	466	466
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void check\_mqtt\_message(struct mg\_mqtt\_opts \*opts,

```
.....
466.      if (*data->msg != 'X' || opts->message.len != (strlen(&data-
>msg[1])) ||
```

### Dangerous Functions\Path 33:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=136">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=136</a>
Status	New

The dangerous function, strlen, was found in use at line 735 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	738	738
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static struct mg\_http\_message gethm(const char \*buf) {

```
.....
738.      mg_http_parse(buf, strlen(buf), &hm);
```

### Dangerous Functions\Path 34:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=137">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=137</a>
Status	New

The dangerous function, strlen, was found in use at line 742 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	745	745
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static int cmpbody(const char \*buf, const char \*str) {

```
....  
745.    size_t len = strlen(buf);
```

### Dangerous Functions\Path 35:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=138">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=138</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	883	883
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
883.    mg_hexdump(buf, strlen(buf));
```

### Dangerous Functions\Path 36:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=139">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=139</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	913	913
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
913.      ASSERT (mg_http_parse(buf, strlen(buf), &hm) > 0);
```

### Dangerous Functions\Path 37:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=140">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=140</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	924	924
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
924.      mg_http_parse(buf, strlen(buf), &hm);
```

### Dangerous Functions\Path 38:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=141">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=141</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	952	952
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
952.      mg_http_parse(buf, strlen(buf), &hm);
```

### Dangerous Functions\Path 39:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=142">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=142</a>
Status	New

The dangerous function, `strlen`, was found in use at line 835 in `mongoose/unit_test.c` file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	<code>mongoose/unit_test.c</code>	<code>mongoose/unit_test.c</code>
Line	973	973
Object	<code>strlen</code>	<code>strlen</code>

#### Code Snippet

File Name `mongoose/unit_test.c`  
Method `static void test_http_server(void) {`

```
....  
973.      mg_http_parse(buf, strlen(buf), &hm);
```

### Dangerous Functions\Path 40:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=143">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=143</a>
Status	New

The dangerous function, `strlen`, was found in use at line 835 in `mongoose/unit_test.c` file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	<code>mongoose/unit_test.c</code>	<code>mongoose/unit_test.c</code>
Line	1000	1000
Object	<code>strlen</code>	<code>strlen</code>

#### Code Snippet

File Name `mongoose/unit_test.c`  
Method `static void test_http_server(void) {`



```
....  
1000.      mg_http_parse(buf, strlen(buf), &hm);
```

#### Dangerous Functions\Path 41:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=144">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=144</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1006	1006
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
1006.      mg_http_parse(buf, strlen(buf), &hm);
```

#### Dangerous Functions\Path 42:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=145">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=145</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1012	1012
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
1012.      mg_http_parse(buf, strlen(buf), &hm);
```

### Dangerous Functions\Path 43:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=146">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=146</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1018	1018
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
1018.      mg_http_parse(buf, strlen(buf), &hm);
```

### Dangerous Functions\Path 44:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=147">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=147</a>
Status	New

The dangerous function, strlen, was found in use at line 835 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1070	1070
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
1070.      mg_http_parse(buf, strlen(buf), &hm);
```

#### Dangerous Functions\Path 45:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=148">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=148</a>
Status	New

The dangerous function, strlen, was found in use at line 1320 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1328	1328
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_parse(void) {

```
....  
1328.      ASSERT(mg_http_parse(s, strlen(s) - 1, &req) == 0);
```

#### Dangerous Functions\Path 46:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=149">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=149</a>
Status	New

The dangerous function, strlen, was found in use at line 1320 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1329	1329
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_parse(void) {

```
....  
1329.      ASSERT(mg_http_parse(s, strlen(s), &req) == (int) strlen(s));
```

#### Dangerous Functions\Path 47:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=150">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=150</a>
Status	New

The dangerous function, strlen, was found in use at line 1320 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1329	1329
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_parse(void) {

```
....  
1329.      ASSERT(mg_http_parse(s, strlen(s), &req) == (int) strlen(s));
```

#### Dangerous Functions\Path 48:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=151">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=151</a>
Status	New

The dangerous function, strlen, was found in use at line 1320 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1330	1330
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_parse(void) {

```
....  
1330.      ASSERT(req.message.len == strlen(s));
```

### Dangerous Functions\Path 49:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=152">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=152</a>
Status	New

The dangerous function, strlen, was found in use at line 1320 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1336	1336
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_parse(void) {

```
....  
1336.      size_t idx, len = strlen(s);
```

### Dangerous Functions\Path 50:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=153">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=153</a>
Status	New

The dangerous function, strlen, was found in use at line 1320 in mongoose/unit\_test.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1337	1337
Object	strlen	strlen

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_parse(void) {

```
....  
1337.      ASSERT(mg_http_parse(s, strlen(s), &req) == (int) len);
```

## MemoryFree on StackVariable

Query Path:

CPP\Cx\CPP Medium Threat\MemoryFree on StackVariable Version:0

[Description](#)

### MemoryFree on StackVariable\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=79">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=79</a>
Status	New

Calling free() (line 835) on a variable that was not dynamically allocated (line 835) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	966	966
Object	data	data

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
....  
966.      free(data);
```

### MemoryFree on StackVariable\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=80">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=80</a>
Status	New

Calling free() (line 835) on a variable that was not dynamically allocated (line 835) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1041	1041
Object	p	p

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_http\_server(void) {

```
....  
1041.      free(p);
```

### MemoryFree on StackVariable\Path 3:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=81>

Status New

Calling free() (line 835) on a variable that was not dynamically allocated (line 835) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1056	1056
Object	p	p

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_http\_server(void) {

```
....  
1056.      free(p);
```

### MemoryFree on StackVariable\Path 4:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=82>

Status New

Calling free() (line 1664) on a variable that was not dynamically allocated (line 1664) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1781	1781
Object	p	p

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_str(void) {

```
....  
1781.      free(p);
```

**MemoryFree on StackVariable\Path 5:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=83">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=83</a>
Status	New

Calling free() (line 1664) on a variable that was not dynamically allocated (line 1664) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1785	1785
Object	p	p

**Code Snippet**

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
....  
1785.      free(p);
```

**MemoryFree on StackVariable\Path 6:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=84">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=84</a>
Status	New

Calling free() (line 1924) on a variable that was not dynamically allocated (line 1924) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1939	1939
Object	buf	buf

**Code Snippet**

File Name mongoose/unit\_test.c  
Method static void test\_dns\_error(const char \*dns\_server\_url, const char \*errstr) {



```
....  
1939.      free(buf);
```

#### MemoryFree on StackVariable\Path 7:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=85">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=85</a>
Status	New

Calling free() (line 1993) on a variable that was not dynamically allocated (line 1993) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2002	2002
Object	p	p

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_util(void) {

```
....  
2002.      free(p);
```

#### MemoryFree on StackVariable\Path 8:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=86">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=86</a>
Status	New

Calling free() (line 1993) on a variable that was not dynamically allocated (line 1993) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2081	2081
Object	s	s

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_util(void) {

```
.....
2081.      free(s);
```

#### MemoryFree on StackVariable\Path 9:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=87">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=87</a>
Status	New

Calling free() (line 2447) on a variable that was not dynamically allocated (line 2447) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2460	2460
Object	data	data

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_packed(void) {

```
.....
2460.      free(data);
```

#### MemoryFree on StackVariable\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=88">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=88</a>
Status	New

Calling free() (line 2447) on a variable that was not dynamically allocated (line 2447) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2466	2466
Object	data	data

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_packed(void) {

```
.....  
2466.      free(data);
```

#### MemoryFree on StackVariable\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=89">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=89</a>
Status	New

Calling free() (line 2669) on a variable that was not dynamically allocated (line 2669) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2758	2758
Object	str	str

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_json(void) {

```
.....  
2758.      free(str);
```

#### MemoryFree on StackVariable\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=90">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=90</a>
Status	New

Calling free() (line 2669) on a variable that was not dynamically allocated (line 2669) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2765	2765
Object	str	str

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_json(void) {

```
.....  
2765.         free(str);
```

#### MemoryFree on StackVariable\Path 13:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=91">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=91</a>
Status	New

Calling free() (line 2669) on a variable that was not dynamically allocated (line 2669) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2784	2784
Object	str	str

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_json(void) {

```
.....  
2784.         free(str);
```

#### MemoryFree on StackVariable\Path 14:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=92">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=92</a>
Status	New

Calling free() (line 2669) on a variable that was not dynamically allocated (line 2669) in file mongoose/unit\_test.c may result with a crash.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2787	2787
Object	str	str

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_json(void) {

```
....
2787.      free(str);
```

## Buffer Overflow boundcpy WrongSizeParam

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow boundcpy WrongSizeParam Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow boundcpy WrongSizeParam\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=70">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=70</a>
Status	New

The size of the buffer used by test\_str in uint32\_t, at line 1664 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_str passes to uint32\_t, at line 1664 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1897	1897
Object	uint32_t	uint32_t

### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
....
1897.      memcpy(a.ip, &addr, sizeof(uint32_t));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=71">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=71</a>
Status	New

The size of the buffer used by test\_str in Namespace253051155, at line 1664 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_str passes to Namespace253051155, at line 1664 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c

Line	1907	1907
Object	Namespace253051155	Namespace253051155

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_str(void) {

```
....  
1907.      memset(a.ip, 0, sizeof(a.ip));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 3:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=72>

Status New

The size of the buffer used by test\_util in Namespace253051155, at line 1993 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_util passes to Namespace253051155, at line 1993 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2020	2020
Object	Namespace253051155	Namespace253051155

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_util(void) {

```
....  
2020.      memset(a.ip, 0xaa, sizeof(a.ip));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 4:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=73>

Status New

The size of the buffer used by test\_util in Namespace253051155, at line 1993 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_util passes to Namespace253051155, at line 1993 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c

Line	2028	2028
Object	Namespace253051155	Namespace253051155

**Code Snippet**

File Name mongoose/unit\_test.c

Method static void test\_util(void) {

```
....  
2028.    memset(a.ip, 0xaa, sizeof(a.ip));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 5:**

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=74>

Status New

The size of the buffer used by test\_util in Namespace253051155, at line 1993 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_util passes to Namespace253051155, at line 1993 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2036	2036
Object	Namespace253051155	Namespace253051155

**Code Snippet**

File Name mongoose/unit\_test.c

Method static void test\_util(void) {

```
....  
2036.    memset(a.ip, 0xaa, sizeof(a.ip));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 6:**

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=75>

Status New

The size of the buffer used by test\_util in Namespace253051155, at line 1993 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_util passes to Namespace253051155, at line 1993 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c

Line	2044	2044
Object	Namespace253051155	Namespace253051155

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_util(void) {

```
....
2044.    memset(a.ip, 0xaa, sizeof(a.ip));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 7:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=76>

Status New

The size of the buffer used by test\_util in Namespace253051155, at line 1993 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that test\_util passes to Namespace253051155, at line 1993 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2052	2052
Object	Namespace253051155	Namespace253051155

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void test\_util(void) {

```
....
2052.    memset(a.ip, 0xaa, sizeof(a.ip));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 8:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=77>

Status New

The size of the buffer used by mg\_tcpip\_driver\_stm32\_tx in len, at line 169 of mongoose/driver\_stm32.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that mg\_tcpip\_driver\_stm32\_tx passes to len, at line 169 of mongoose/driver\_stm32.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c



Line	180	180
Object	len	len

#### Code Snippet

File Name mongoose/driver\_stm32.c

Method static size\_t mg\_tcpip\_driver\_stm32\_tx(const void \*buf, size\_t len,

```
....
180.      memcpy(s_txbuf[s_txno], buf, len);      // Copy data
```

### Buffer Overflow boundcpy WrongSizeParam\Path 9:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=78>

Status New

The size of the buffer used by producer in len, at line 2940 of mongoose/unit\_test.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that producer passes to len, at line 2940 of mongoose/unit\_test.c, to overwrite the target buffer.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2949	2949
Object	len	len

#### Code Snippet

File Name mongoose/unit\_test.c

Method static void producer(void \*param) {

```
....
2949.      memcpy(buf, &tmp[ofs], len);
```

## Inadequate Encryption Strength

Query Path:

CPP\Cx\CPP Medium Threat\Inadequate Encryption Strength Version:1

### Categories

FISMA 2014: Configuration Management

NIST SP 800-53: SC-13 Cryptographic Protection (P1)

OWASP Top 10 2017: A3-Sensitive Data Exposure

### Description

### Inadequate Encryption Strength\Path 1:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=192>

Status New

The application uses a weak cryptographic algorithm, `lwip_md5_update` at line 1311 of `mongoose/eap.c`, to protect sensitive personal information `secret_len`, from `mongoose/eap.c` at line 1311.

	Source	Destination
File	<code>mongoose/eap.c</code>	<code>mongoose/eap.c</code>
Line	1450	1450
Object	<code>secret_len</code>	<code>lwip_md5_update</code>

#### Code Snippet

File Name `mongoose/eap.c`

Method `static void eap_request(ppp_pcb *pcb, u_char *inp, int id, int len) {`

```
....  
1450.          lwip_md5_update(&mdContext, (u_char *)secret,  
secret_len);
```

#### Inadequate Encryption Strength\Path 2:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=193>

Status New

The application uses a weak cryptographic algorithm, `lwip_md5_update` at line 1311 of `mongoose/eap.c`, to protect sensitive personal information `secret`, from `mongoose/eap.c` at line 1311.

	Source	Destination
File	<code>mongoose/eap.c</code>	<code>mongoose/eap.c</code>
Line	1450	1450
Object	<code>secret</code>	<code>lwip_md5_update</code>

#### Code Snippet

File Name `mongoose/eap.c`

Method `static void eap_request(ppp_pcb *pcb, u_char *inp, int id, int len) {`

```
....  
1450.          lwip_md5_update(&mdContext, (u_char *)secret,  
secret_len);
```

#### Inadequate Encryption Strength\Path 3:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=194>

Status New

The application uses a weak cryptographic algorithm, `lwip_md5_update` at line 1725 of `mongoose/eap.c`, to protect sensitive personal information `secret_len`, from `mongoose/eap.c` at line 1725.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1877	1877
Object	secret_len	lwip_md5_update

#### Code Snippet

File Name mongoose/eap.c

Method static void eap\_response(ppp\_pcb \*pcb, u\_char \*inp, int id, int len) {

```
.....  
1877.          lwip_md5_update(&mdContext, (u_char *)secret,  
secret_len);
```

### Inadequate Encryption Strength\Path 4:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=195>

Status New

The application uses a weak cryptographic algorithm, lwip\_md5\_update at line 1725 of mongoose/eap.c, to protect sensitive personal information secret, from mongoose/eap.c at line 1725.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1877	1877
Object	secret	lwip_md5_update

#### Code Snippet

File Name mongoose/eap.c

Method static void eap\_response(ppp\_pcb \*pcb, u\_char \*inp, int id, int len) {

```
.....  
1877.          lwip_md5_update(&mdContext, (u_char *)secret,  
secret_len);
```

### Inadequate Encryption Strength\Path 5:

Severity Medium

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=196>

Status New

The application uses a weak cryptographic algorithm, SHA1Update at line 315 of mongoose/eap.c, to protect sensitive personal information pn\_secret, from mongoose/eap.c at line 315.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c

Line	328	328
Object	pn_secret	SHA1Update

#### Code Snippet

File Name mongoose/eap.c  
Method pncrypt\_setkey(int timeoffs)

```
....
328.          SHA1Update(&ctxt, pn_secret, strlen(pn_secret));
```

### Inadequate Encryption Strength\Path 6:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=197">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=197</a>
Status	New

The application uses a weak cryptographic algorithm, SHA1Update at line 315 of mongoose/eap.c, to protect sensitive personal information pn\_secret, from mongoose/eap.c at line 315.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	328	328
Object	pn_secret	SHA1Update

#### Code Snippet

File Name mongoose/eap.c  
Method pncrypt\_setkey(int timeoffs)

```
....
328.          SHA1Update(&ctxt, pn_secret, strlen(pn_secret));
```

## Use of Zero Initialized Pointer

Query Path:

CPP\Cx\CPP Medium Threat\Use of Zero Initialized Pointer Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

### Description

#### Use of Zero Initialized Pointer\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=189">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=189</a>
Status	New

The variable declared in pvReturn at mongoose/heap\_4.c in line 113 is not initialized when it is used by pvReturn at mongoose/heap\_4.c in line 113.

	Source	Destination
File	mongoose/heap_4.c	mongoose/heap_4.c
Line	116	258
Object	pvReturn	pvReturn

#### Code Snippet

File Name mongoose/heap\_4.c  
Method void \*pvPortMalloc( size\_t xWantedSize )

```
....
116. void *pvReturn = NULL;
....
258.         configASSERT( ( ( ( size_t ) pvReturn ) & ( size_t )
portBYTE_ALIGNMENT_MASK ) == 0 );
```

### Use of Zero Initialized Pointer\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=190">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=190</a>
Status	New

The variable declared in pxNextFreeBlock at mongoose/heap\_4.c in line 329 is not initialized when it is used by pxNextFreeBlock at mongoose/heap\_4.c in line 329.

	Source	Destination
File	mongoose/heap_4.c	mongoose/heap_4.c
Line	360	366
Object	pxNextFreeBlock	pxNextFreeBlock

#### Code Snippet

File Name mongoose/heap\_4.c  
Method static void prvHeapInit( void )

```
....
360.         pxEnd->pxNextFreeBlock = NULL;
....
366.         pxFirstFreeBlock->pxNextFreeBlock = pxEnd;
```

### Use of Zero Initialized Pointer\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=191">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=191</a>
Status	New

The variable declared in head at mongoose/unit\_test.c in line 2845 is not initialized when it is used by head at mongoose/unit\_test.c in line 2845.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2846	2886
Object	head	head

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_rpc(void) {

```
....  
2846.     struct mg_rpc *head = NULL;  
....  
2886.     req.head = &head;
```

## Buffer Overflow AddressOfLocalVarReturned

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow AddressOfLocalVarReturned Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
NIST SP 800-53: SC-5 Denial of Service Protection (P1)  
OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow AddressOfLocalVarReturned\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=68">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=68</a>
Status	New

The pointer result at mongoose/net.c in line 96 is being used after it has been freed.

	Source	Destination
File	mongoose/net.c	mongoose/net.c
Line	120	120
Object	result	result

#### Code Snippet

File Name mongoose/net.c  
Method static struct user \*authenticate(struct mg\_http\_message \*hm) {

```
....  
120.     return result;
```

#### Buffer Overflow AddressOfLocalVarReturned\Path 2:

Severity	Medium
Result State	To Verify

Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=69">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=69</a>
Status	New

The pointer ahbptab at mongoose/driver\_stm32.c in line 65 is being used after it has been freed.

	Source	Destination
File	mongoose/driver_stm32.c	mongoose/driver_stm32.c
Line	88	88
Object	ahbptab	ahbptab

#### Code Snippet

File Name mongoose/driver\_stm32.c

Method static uint32\_t get\_hclk(void) {

```
....
88.     return ((uint32_t) clk) >> ahbptab[hpre - 8];
```

## Wrong Size t Allocation

Query Path:

CPP\Cx\CPP Integer Overflow\Wrong Size t Allocation Version:0

[Description](#)

### Wrong Size t Allocation\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=93">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=93</a>
Status	New

The function pl in mongoose/eap.c at line 1197 assigns an incorrectly calculated size to a buffer, resulting in a mismatch between the value being written and the size of the buffer it is being written into.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1211	1211
Object	pl	pl

#### Code Snippet

File Name mongoose/eap.c

Method name\_of\_pn\_file()

```
....
1211.     path = malloc(pl);
```

## Unchecked Return Value

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Return Value Version:1

## Categories

### NIST SP 800-53: SI-11 Error Handling (P2)

#### Description

##### Unchecked Return Value\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=11">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=11</a>
Status	New

The mqtt\_cb method calls the snprintf function, at line 356 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	379	379
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
 Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {

```

    ....
    379.     snprintf(test_data->topic, test_data->topicsize, "%.5s",

```

##### Unchecked Return Value\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=12">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=12</a>
Status	New

The mqtt\_cb method calls the snprintf function, at line 356 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	381	381
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
 Method static void mqtt\_cb(struct mg\_connection \*c, int ev, void \*evd, void \*fnd) {



```
.....
381.      snprintf(buf + 1, test_data->msgsize - 2, "%.s", (int) mm-
>data.len,
```

### Unchecked Return Value\Path 3:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=13">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=13</a>
Status	New

The fcb method calls the snprintf function, at line 687 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	691	691
Object	snprintf	snprintf

#### Code Snippet

```
File Name    mongoose/unit_test.c
Method       static void fcb(struct mg_connection *c, int ev, void *ev_data, void *fn_data) {

.....
691.      snprintf(fd->buf, FETCH_BUF_SIZE, "%.s", (int) hm-
>message.len,
```

### Unchecked Return Value\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=14">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=14</a>
Status	New

The test\_http\_server method calls the remove function, at line 835 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1025	1025
Object	remove	remove

#### Code Snippet

```
File Name    mongoose/unit_test.c
Method       static void test_http_server(void) {
```

```
.....
1025.         remove ("uploaded.txt");
```

### Unchecked Return Value\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=15">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=15</a>
Status	New

The test\_http\_server method calls the remove function, at line 835 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1042	1042
Object	remove	remove

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
.....
1042.         remove ("uploaded.txt");
```

### Unchecked Return Value\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=16">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=16</a>
Status	New

The test\_http\_server method calls the remove function, at line 835 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1048	1048
Object	remove	remove

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
.....  
1048.         remove ("uploaded.txt");
```

### Unchecked Return Value\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=17">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=17</a>
Status	New

The test\_http\_server method calls the remove function, at line 835 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1057	1057
Object	remove	remove

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_http\_server(void) {

```
.....  
1057.         remove ("uploaded.txt");
```

### Unchecked Return Value\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=18">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=18</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1813	1813
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
....  
1813.          TESTDOUBLE ("%g", 0.0, "0");
```

#### Unchecked Return Value\Path 9:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=19">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=19</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1814	1814
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
....  
1814.          TESTDOUBLE ("%g", 0.123, "0.123");
```

#### Unchecked Return Value\Path 10:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=20">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=20</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1815	1815
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1815.          TESTDOUBLE ("%g", 0.00123, "0.00123");
```

#### Unchecked Return Value\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=21">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=21</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1816	1816
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1816.          TESTDOUBLE ("%g", 0.123456333, "0.123456");
```

#### Unchecked Return Value\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=22">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=22</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1817	1817
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1817.          TESTDOUBLE ("%g", 123.0, "123");
```

### Unchecked Return Value\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=23">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=23</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1818	1818
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1818.          TESTDOUBLE ("%g", 11.5454, "11.5454");
```

### Unchecked Return Value\Path 14:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=24">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=24</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1819	1819
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1819.      TESTDOUBLE ("%g", 11.0001, "11.0001");
```

#### Unchecked Return Value\Path 15:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=25">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=25</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1820	1820
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1820.      TESTDOUBLE ("%g", 0.999, "0.999");
```

#### Unchecked Return Value\Path 16:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=26">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=26</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1821	1821
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1821.          TESTDOUBLE ("%g", 0.999999, "0.999999");
```

#### Unchecked Return Value\Path 17:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=27">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=27</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1822	1822
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1822.          TESTDOUBLE ("%g", 0.9999999, "1");
```

#### Unchecked Return Value\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=28">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=28</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1823	1823
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {



```
.....
1823.          TESTDOUBLE ("%g", 10.9, "10.9");
```

#### Unchecked Return Value\Path 19:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=29">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=29</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1824	1824
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1824.          TESTDOUBLE ("%g", 10.01, "10.01");
```

#### Unchecked Return Value\Path 20:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=30">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=30</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1825	1825
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1825.          TESTDOUBLE ("%g", 1.0, "1");
```

#### Unchecked Return Value\Path 21:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=31">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=31</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1826	1826
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1826.          TESTDOUBLE ("%g", 10.0, "10");
```

#### Unchecked Return Value\Path 22:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=32">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=32</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1827	1827
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1827.          TESTDOUBLE ("%g", 100.0, "100");
```

### Unchecked Return Value\Path 23:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=33">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=33</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1828	1828
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1828.          TESTDOUBLE ("%g", 1000.0, "1000");
```

### Unchecked Return Value\Path 24:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=34">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=34</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1829	1829
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1829.          TESTDOUBLE ("%g", 10000.0, "10000");
```

#### Unchecked Return Value\Path 25:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=35">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=35</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1830	1830
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1830.          TESTDOUBLE ("%g", 100000.0, "100000");
```

#### Unchecked Return Value\Path 26:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=36">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=36</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1831	1831
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1831.          TESTDOUBLE ("%g", 1000000.0, "1e+06");
```

#### Unchecked Return Value\Path 27:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=37">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=37</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1832	1832
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1832.          TESTDOUBLE ("%g", 10000000.0, "1e+07");
```

#### Unchecked Return Value\Path 28:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=38">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=38</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1833	1833
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1833.          TESTDOUBLE ("%g", 100000001.0, "1e+08");
```

### Unchecked Return Value\Path 29:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=39">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=39</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1834	1834
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1834.          TESTDOUBLE ("%g", 10.5454, "10.5454");
```

### Unchecked Return Value\Path 30:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=40">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=40</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1835	1835
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1835.          TESTDOUBLE ("%g", 999999.0, "999999");
```

### Unchecked Return Value\Path 31:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=41">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=41</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1836	1836
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1836.          TESTDOUBLE ("%g", 9999999.0, "1e+07");
```

### Unchecked Return Value\Path 32:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=42">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=42</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1837	1837
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1837.          TESTDOUBLE ("%g", 44556677.0, "4.45567e+07");
```

### Unchecked Return Value\Path 33:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=43">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=43</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1838	1838
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1838.          TESTDOUBLE ("%g", 1234567.2, "1.23457e+06");
```

### Unchecked Return Value\Path 34:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=44">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=44</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1839	1839
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {



```
.....
1839.          TESTDOUBLE ("%g", -987.65432, "-987.654");
```

### Unchecked Return Value\Path 35:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=45">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=45</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1840	1840
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1840.          TESTDOUBLE ("%g", 0.00000000001, "1e-10");
```

### Unchecked Return Value\Path 36:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=46">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=46</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1841	1841
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1841.          TESTDOUBLE ("%g", 2.34567e-57, "2.34567e-57");
```

### Unchecked Return Value\Path 37:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=47">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=47</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1842	1842
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1842.          TESTDOUBLE ("%.*g", DBLWIDTH(7, 9999999.0), "9999999");
```

### Unchecked Return Value\Path 38:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=48">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=48</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1843	1843
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1843.          TESTDOUBLE ("%.*g", DBLWIDTH(10, 0.123456333), "0.123456333");
```

### Unchecked Return Value\Path 39:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=49">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=49</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1844	1844
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1844.          TESTDOUBLE ("%g", 123.456222, "123.456");
```

### Unchecked Return Value\Path 40:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=50">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=50</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1845	1845
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1845.          TESTDOUBLE ("%.*g", DBLWIDTH(10, 123.456222), "123.456222");
```

#### Unchecked Return Value\Path 41:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=51">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=51</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1846	1846
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....  
1846.          TESTDOUBLE ("%g", 600.1234, "600.123");
```

#### Unchecked Return Value\Path 42:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=52">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=52</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1847	1847
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1847.          TESTDOUBLE ("%g", -600.1234, "-600.123");
```

### Unchecked Return Value\Path 43:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=53">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=53</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1848	1848
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1848.          TESTDOUBLE ("%g", 599.1234, "599.123");
```

### Unchecked Return Value\Path 44:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=54">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=54</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1849	1849
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1849.      TESTDOUBLE ("%g", -599.1234, "-599.123");
```

#### Unchecked Return Value\Path 45:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=55">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=55</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1850	1850
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1850.      TESTDOUBLE ("%g", 0.14, "0.14");
```

#### Unchecked Return Value\Path 46:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=56">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=56</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1851	1851
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1851.          TESTDOUBLE ("%f", 0.14, "0.140000");
```

#### Unchecked Return Value\Path 47:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=57">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=57</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1852	1852
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1852.          TESTDOUBLE ("%.*f", DBLWIDTH(4, 0.14), "0.1400");
```

#### Unchecked Return Value\Path 48:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=58">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=58</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1853	1853
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1853.          TESTDOUBLE ("%.*f", DBLWIDTH (3, 0.14), "0.140");
```

#### Unchecked Return Value\Path 49:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=59">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=59</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1854	1854
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {

```
.....
1854.          TESTDOUBLE ("%.*f", DBLWIDTH (2, 0.14), "0.14");
```

#### Unchecked Return Value\Path 50:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=60">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=60</a>
Status	New

The test\_str method calls the snprintf function, at line 1664 of mongoose/unit\_test.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	1855	1855
Object	snprintf	snprintf

#### Code Snippet

File Name mongoose/unit\_test.c  
Method static void test\_str(void) {



```
....
1855.          TESTDOUBLE ("%.*f", DBLWIDTH(1, 0.14), "0.1");
```

## NULL Pointer Dereference

Query Path:

CPP\Cx\CPP Low Visibility\NULL Pointer Dereference Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

OWASP Top 10 2017: A1-Injection

### Description

#### NULL Pointer Dereference\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=94">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=94</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2852 is not initialized when it is used by u at mongoose/queue.c in line 2149.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2854	2162
Object	null	u

### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSet( QueueSetHandle\_t xQueueSet, TickType\_t const xTicksToWait )

```
....
2854.          QueueSetMemberHandle_t xReturn = NULL;
```

File Name mongoose/queue.c  
Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2162.          ( void ) memcpy( ( void * ) pvBuffer, ( void * )
pxQueue->u.xQueue.pcReadFrom, ( size_t ) pxQueue->uxItemSize ); /*lint
!e961 !e418 !e9087 MISRA exception as the casts are only redundant for
some ports. Also previous logic ensures a null pointer can only be
passed to memcpy() when the count is 0. Cast to void required by
function signature and safe as no alignment requirement and copy length
specified in bytes. */
```

## NULL Pointer Dereference\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=95">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=95</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2865 is not initialized when it is used by u at mongoose/queue.c in line 2149.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2867	2162
Object	null	u

### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSetFromISR( QueueSetHandle\_t xQueueSet )

```
....
2867.         QueueSetMemberHandle_t xReturn = NULL;
```



File Name mongoose/queue.c  
Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2162.         ( void ) memcpy( ( void * ) pvBuffer, ( void * )
pxQueue->u.xQueue.pcReadFrom, ( size_t ) pxQueue->uxItemSize ); /*lint
!e961 !e418 !e9087 MISRA exception as the casts are only redundant for
some ports. Also previous logic ensures a null pointer can only be
passed to memcpy() when the count is 0. Cast to void required by
function signature and safe as no alignment requirement and copy length
specified in bytes. */
```

## NULL Pointer Dereference\Path 3:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=96">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=96</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2852 is not initialized when it is used by u at mongoose/queue.c in line 2149.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c

Line	2854	2154
Object	null	u

#### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSet( QueueSetHandle\_t xQueueSet, TickType\_t const xTicksToWait )

```
....
2854.         QueueSetMemberHandle_t xReturn = NULL;
```



File Name mongoose/queue.c  
Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2154.         if( pxQueue->u.xQueue.pcReadFrom >= pxQueue->u.xQueue.pcTail ) /*lint !e946 MISRA exception justified as use of the relational operator is the cleanest solutions. */
```

#### NULL Pointer Dereference\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=97">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=97</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2865 is not initialized when it is used by u at mongoose/queue.c in line 2149.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2867	2154
Object	null	u

#### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSetFromISR( QueueSetHandle\_t xQueueSet )

```
....
2867.         QueueSetMemberHandle_t xReturn = NULL;
```



File Name mongoose/queue.c  
Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2154.                if( pxQueue->u.xQueue.pcReadFrom >= pxQueue-
>u.xQueue.pcTail ) /*lint !e946 MISRA exception justified as use of the
relational operator is the cleanest solutions. */
```

### NULL Pointer Dereference\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=98">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=98</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2852 is not initialized when it is used by u at mongoose/queue.c in line 2149.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2854	2154
Object	null	u

#### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSet( QueueSetHandle\_t xQueueSet, TickType\_t const xTicksToWait )

```
....
2854.        QueueSetMemberHandle_t xReturn = NULL;
```



File Name mongoose/queue.c  
Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2154.                if( pxQueue->u.xQueue.pcReadFrom >= pxQueue-
>u.xQueue.pcTail ) /*lint !e946 MISRA exception justified as use of the
relational operator is the cleanest solutions. */
```

### NULL Pointer Dereference\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=99">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=99</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2865 is not initialized when it is used by u at mongoose/queue.c in line 2149.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2867	2154
Object	null	u

#### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSetFromISR( QueueSetHandle\_t xQueueSet )

```
....
2867.         QueueSetMemberHandle_t xReturn = NULL;
```

File Name mongoose/queue.c  
Method static void prvCopyDataFromQueue( Queue\_t \* const pxQueue, void \* const pvBuffer )

```
....
2154.         if( pxQueue->u.xQueue.pcReadFrom >= pxQueue->
>u.xQueue.pcTail ) /*lint !e946 MISRA exception justified as use of the
relational operator is the cleanest solutions. */
```

#### NULL Pointer Dereference\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=100">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=100</a>
Status	New

The variable declared in null at mongoose/queue.c in line 2852 is not initialized when it is used by pxQueue at mongoose/queue.c in line 2287.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	2854	2293
Object	null	pxQueue

#### Code Snippet

File Name mongoose/queue.c  
Method QueueSetMemberHandle\_t xQueueSelectFromSet( QueueSetHandle\_t xQueueSet, TickType\_t const xTicksToWait )

```
....
2854.         QueueSetMemberHandle_t xReturn = NULL;
```

File Name mongoose/queue.c

Method static BaseType\_t prvIsQueueEmpty( const Queue\_t \*pxQueue )

```
....  
2293.             if( pxQueue->uxMessagesWaiting == ( UBaseType_t ) 0 )
```

#### NULL Pointer Dereference\Path 8:

Severity Low

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=101>

Status New

The variable declared in 0 at mongoose/heap\_4.c in line 329 is not initialized when it is used by xStart at mongoose/heap\_4.c in line 329.

	Source	Destination
File	mongoose/heap_4.c	mongoose/heap_4.c
Line	351	351
Object	0	xStart

#### Code Snippet

File Name mongoose/heap\_4.c

Method static void prvHeapInit( void )

```
....  
351.             xStart.xBlockSize = ( size_t ) 0;
```

#### NULL Pointer Dereference\Path 9:

Severity Low

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=102>

Status New

The variable declared in 0 at mongoose/queue.c in line 255 is not initialized when it is used by pxQueue at mongoose/queue.c in line 255.

	Source	Destination
File	mongoose/queue.c	mongoose/queue.c
Line	264	264
Object	0	pxQueue

#### Code Snippet

File Name mongoose/queue.c

Method BaseType\_t xQueueGenericReset( QueueHandle\_t xQueue, BaseType\_t xNewQueue )

```
....  
264.                pxQueue->uxMessagesWaiting = ( UBaseType_t ) 0U;
```

## Unchecked Array Index

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Array Index Version:1

### Categories

NIST SP 800-53: SI-10 Information Input Validation (P1)

### Description

#### Unchecked Array Index\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=103">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=103</a>
Status	New

	Source	Destination
File	mongoose/unit_test.c	mongoose/unit_test.c
Line	2586	2586
Object	ofs	ofs

### Code Snippet

File Name mongoose/unit\_test.c  
Method static void w2(struct mg\_connection \*c, int ev, void \*ev\_data, void \*fn\_data) {  
  
....  
2586. if (n < msg.len - 1) c->send.buf[ofs] = op; // Clear FIN  
flag

## Improper Resource Access Authorization

Query Path:

CPP\Cx\CPP Low Visibility\Improper Resource Access Authorization Version:1

### Categories

FISMA 2014: Identification And Authentication

NIST SP 800-53: AC-3 Access Enforcement (P1)

OWASP Top 10 2017: A2-Broken Authentication

### Description

#### Improper Resource Access Authorization\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=198">http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&amp;projectid=50053&amp;pathid=198</a>
Status	New

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1366	1366
Object	BinaryExpr	BinaryExpr

#### Code Snippet

File Name mongoose/eap.c

Method static void eap\_request(ppp\_pcb \*pcb, u\_char \*inp, int id, int len) {

```
....  
1366. len = read(fd, rhostname + SRP_PSEUDO_LEN,
```

## TOCTOU

Query Path:

CPP\Cx\CPP Low Visibility\TOCTOU Version:1

[Description](#)

### TOCTOU\Path 1:

Severity Low

Result State To Verify

Online Results <http://WIN-BA8RD5TJ8IG/CxWebClient/ViewerMain.aspx?scanid=1050063&projectid=50053&pathid=199>

Status New

The open\_pn\_file method in mongoose/eap.c file utilizes open that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	mongoose/eap.c	mongoose/eap.c
Line	1231	1231
Object	open	open

#### Code Snippet

File Name mongoose/eap.c

Method open\_pn\_file(modebits)

```
....  
1231. fd = open(path, modebits, S_IRUSR | S_IWUSR);
```

## Buffer Overflow OutOfBound

### Risk

#### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.



## Cause

### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

---

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
- Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strncpy` over `strcpy`, and so on.
- Consistently apply tests for the size of buffers.
- Do not return variable addresses outside the scope of their variables.

---

## Source Code Examples

### CPP

#### Overflowing Buffers

```
const int BUFFER_SIZE = 10;
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    strcpy(buffer, inputString);
}
```

#### Checked Buffers

```
const int BUFFER_SIZE = 10;
const int MAX_INPUT_SIZE = 256;
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    if (strlen(inputString, MAX_INPUT_SIZE) < sizeof(buffer))
    {
        strncpy(buffer, inputString, sizeof(buffer));
    }
}
```

# Buffer Overflow AddressOfLocalVarReturned

## Risk

### What might happen

A use after free error will cause code to use an area of memory previously assigned with a specific value, which has since been freed and may have been overwritten by another value. This error will likely cause unexpected behavior, memory corruption and crash errors. In some cases where the freed and used section of memory is used to determine execution flow, and the error can be induced by an attacker, this may result in execution of malicious code.

---

## Cause

### How does it happen

Pointers to variables allow code to have an address with a set size to a dynamically allocated variable. Eventually, the pointer's destination may become free - either explicitly in code, such as when programmatically freeing this variable, or implicitly, such as when a local variable is returned - once it is returned, the variable's scope is released. Once freed, this memory will be re-used by the application, overwritten with new data. At this point, dereferencing this pointer will potentially resolve newly written and unexpected data.

---

## General Recommendations

### How to avoid it

- Do not return local variables or pointers
  - Review code to ensure no flow allows use of a pointer after it has been explicitly freed
- 

## Source Code Examples

### CPP

#### Use of Variable after It was Freed

```
free(input);  
printf("%s", input);
```

#### Use of Pointer to Local Variable That Was Freed On Return

```
int* func1()  
{  
    int i;  
    i = 1;  
    return &i;  
}  
  
void func2()
```

```
{  
    int j;  
    j = 5;  
}  
  
//..  
int * i = func1();  
printf("%d\r\n", *i); // Output could be 1 or Segmentation Fault  
func2();  
printf("%d\r\n", *i); // Output is 5, which is j's value, as func2() overwrote data in  
the stack  
//..
```

# Buffer Overflow boundcpy WrongSizeParam

## Risk

### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.

---

## Cause

### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

---

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
  - Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strncpy` over `strcpy`, and so on.
  - Consistently apply tests for the size of buffers.
  - Do not return variable addresses outside the scope of their variables.
- 

## Source Code Examples

# MemoryFree on StackVariable

## Risk

### What might happen

Undefined Behavior may result with a crash. Crashes may give an attacker valuable information about the system and the program internals. Furthermore, it may leave unprotected files (e.g. memory) that may be exploited.

---

## Cause

### How does it happen

Calling `free()` on a variable that was not dynamically allocated (e.g. `malloc`) will result with an Undefined Behavior.

---

## General Recommendations

### How to avoid it

Use `free()` only on dynamically allocated variables in order to prevent unexpected behavior from the compiler.

---

## Source Code Examples

### CPP

#### Bad - Calling `free()` on a static variable

```
void clean_up() {  
    char temp[256];  
    do_something();  
    free(tmp);  
    return;  
}
```

#### Good - Calling `free()` only on variables that were dynamically allocated

```
void clean_up() {  
    char *buff;  
    buff = (char*) malloc(1024);  
    free(buff);  
    return;  
}
```

# Wrong Size t Allocation

## Risk

### What might happen

Incorrect allocation of memory may result in unexpected behavior by either overwriting sections of memory with unexpected values. Under certain conditions where both an incorrect allocation of memory and the values being written can be controlled by an attacker, such an issue may result in execution of malicious code.

---

## Cause

### How does it happen

Some memory allocation functions require a size value to be provided as a parameter. The allocated size should be derived from the provided value, by providing the length value of the intended source, multiplied by the size of that length. Failure to perform the correct arithmetic to obtain the exact size of the value will likely result in the source overflowing its destination.

---

## General Recommendations

### How to avoid it

- Always perform the correct arithmetic to determine size.
  - Specifically for memory allocation, calculate the allocation size from the allocation source:
    - Derive the size value from the length of intended source to determine the amount of units to be processed.
    - Always programmatically consider the size of the each unit and their conversion to memory units - for example, by using `sizeof()` on the unit's type.
    - Memory allocation should be a multiplication of the amount of units being written, times the size of each unit.
- 

## Source Code Examples

### CPP

#### Allocating and Assigning Memory without Sizeof Arithmetic

```
int *ptr;
ptr = (int*)malloc(5);
for (int i = 0; i < 5; i++)
{
    ptr[i] = i * 2 + 1;
}
```

#### Allocating and Assigning Memory with Sizeof Arithmetic

```
int *ptr;
ptr = (int*)malloc(5 * sizeof(int));
```

```
for (int i = 0; i < 5; i++)
{
    ptr[i] = i * 2 + 1;
}
```

### Incorrect Arithmetic of Multi-Byte String Allocation

```
wchar_t * dest;
dest = (wchar_t *)malloc(wcslen(source) + 1); // Would not crash for a short "source"
wcscpy((wchar_t *)dest, source);
wprintf(L"Dest: %s\r\n", dest);
```

### Correct Arithmetic of Multi-Byte String Allocation

```
wchar_t * dest;
dest = (wchar_t *)malloc((wcslen(source) + 1) * sizeof(wchar_t));
wcscpy((wchar_t *)dest, source);
wprintf(L"Dest: %s\r\n", dest);
```

# Dangerous Functions

## Risk

### What might happen

Use of dangerous functions may expose varying risks associated with each particular function, with potential impact of improper usage of these functions varying significantly. The presence of such functions indicates a flaw in code maintenance policies and adherence to secure coding practices, in a way that has allowed introducing known dangerous code into the application.

---

## Cause

### How does it happen

A dangerous function has been identified within the code. Functions are often deemed dangerous to use for numerous reasons, as there are different sets of vulnerabilities associated with usage of such functions. For example, some string copy and concatenation functions are vulnerable to Buffer Overflow, Memory Disclosure, Denial of Service and more. Use of these functions is not recommended.

---

## General Recommendations

### How to avoid it

- Deploy a secure and recommended alternative to any functions that were identified as dangerous.
    - If no secure alternative is found, conduct further researching and testing to identify whether current usage successfully sanitizes and verifies values, and thus successfully avoids the use-cases for whom the function is indeed dangerous
  - Conduct a periodical review of methods that are in use, to ensure that all external libraries and built-in functions are up-to-date and whose use has not been excluded from best secure coding practices.
- 

## Source Code Examples

### CPP

#### Buffer Overflow in gets()

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    gets(buf); // veryveryverylongname
    if (buf == ACCEPTED_NAME)
    {
        // Do something
    }
    return 0;
}
```



## Safe reading from user

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    fgets(buf, sizeof(buf), stdin); //setting the amount of bytes to read
    if (buf == ACCEPTED_NAME)
    {
        //Do something
    }
    return 0;
}
```

## Unsafe function for string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strcpy(buf, argv[1]); // overflow occurs when len(argv[1]) > 10 bytes

    return 0;
}
```

## Safe string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strncpy(buf, argv[1], sizeof(buf));
    buf[9] = '\0'; //strncpy doesn't NULL terminates

    return 0;
}
```

## Unsafe format string

```
int main(int argc, char* argv[])
{
    printf(argv[1]); // If argv[1] contains a format token, such as %s,%x or %d, will cause an access violation
    return 0;
}
```

## Safe format string

```
int main(int argc, char* argv[])
{
    printf("%s", argv[1]); // Second parameter is not a formattable string
    return 0;
}
```

# Use of Zero Initialized Pointer

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

### CPP

#### Explicit NULL Dereference

```
char * input = NULL;
printf("%s", input);
```

#### Implicit NULL Dereference

```
char * input;
printf("%s", input);
```

### Java

#### Explicit Null Dereference

```
Object o = null;  
out.println(o.getClass());
```

# Inadequate Encryption Strength

## Risk

### What might happen

Using weak or outdated cryptography does not provide sufficient protection for sensitive data. An attacker that gains access to the encrypted data would likely be able to break the encryption, using either cryptanalysis or brute force attacks. Thus, the attacker would be able to steal user passwords and other personal data. This could lead to user impersonation or identity theft.

---

## Cause

### How does it happen

The application uses a weak algorithm, that is considered obsolete since it is relatively easy to break. These obsolete algorithms are vulnerable to several different kinds of attacks, including brute force.

---

## General Recommendations

### How to avoid it

Generic Guidance:

- Always use strong, modern algorithms for encryption, hashing, and so on.
- Do not use weak, outdated, or obsolete algorithms.
- Ensure you select the correct cryptographic mechanism according to the specific requirements.
- Passwords should be protected with a dedicated password protection scheme, such as bcrypt, scrypt, PBKDF2, or Argon2.

Specific Recommendations:

- Do not use SHA-1, MD5, or any other weak hash algorithm to protect passwords or personal data. Instead, use a stronger hash such as SHA-256 when a secure hash is required.
  - Do not use DES, Triple-DES, RC2, or any other weak encryption algorithm to protect passwords or personal data. Instead, use a stronger encryption algorithm such as AES to protect personal data.
  - Do not use weak encryption modes such as ECB, or rely on insecure defaults. Explicitly specify a stronger encryption mode, such as GCM.
  - For symmetric encryption, use a key length of at least 256 bits.
- 

## Source Code Examples

### Java

#### Weakly Hashed PII

```
string protectSSN(HttpServletRequest req) {  
    string socialSecurityNum = req.getParameter("SocialSecurityNo");  
  
    return DigestUtils.md5Hex(socialSecurityNum);  
}
```

### Stronger Hash for PII

```
string protectSSN(HttpServletRequest req) {  
    string socialSecurityNum = req.getParameter("SocialSecurityNo");  
  
    return DigestUtils.sha256Hex(socialSecurityNum);  
}
```

# Unchecked Return Value

## Risk

### What might happen

A program that does not check function return values could cause the application to enter an undefined state. This could lead to unexpected behavior and unintended consequences, including inconsistent data, system crashes or other error-based exploits.

---

## Cause

### How does it happen

The application calls a system function, but does not receive or check the result of this function. These functions often return error codes in the result, or share other status codes with its caller. The application simply ignores this result value, losing this vital information.

---

## General Recommendations

### How to avoid it

- Always check the result of any called function that returns a value, and verify the result is an expected value.
  - Ensure the calling function responds to all possible return values.
  - Expect runtime errors and handle them gracefully. Explicitly define a mechanism for handling unexpected errors.
- 

## Source Code Examples

### CPP

#### Unchecked Memory Allocation

```
buff = (char*) malloc(size);  
strncpy(buff, source, size);
```

#### Safer Memory Allocation

```
buff = (char*) malloc(size+1);  
if (buff==NULL) exit(1);  
  
strncpy(buff, source, size);  
buff[size] = '\0';
```

# NULL Pointer Dereference

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples



## Improper Validation of Array Index

**Weakness ID:** 129 (*Weakness Base*)

**Status:** Draft

### Description

### Description Summary

The product uses untrusted input when calculating or using an array index, but the product does not validate or incorrectly validates the index to ensure the index references a valid position within the array.

### Alternate Terms

out-of-bounds array index

index-out-of-range

array index underflow

### Time of Introduction

### Implementation

### Applicable Platforms

### Languages

C: (*Often*)

C++: (*Often*)

### Language-independent

### Common Consequences

Scope	Effect
Integrity Availability	Unchecked array indexing will very likely result in the corruption of relevant memory and perhaps instructions, leading to a crash, if the values are outside of the valid memory area.
Integrity	If the memory corrupted is data, rather than instructions, the system will continue to function with improper values.
Confidentiality Integrity	Unchecked array indexing can also trigger out-of-bounds read or write operations, or operations on the wrong objects; i.e., "buffer overflows" are not always the result. This may result in the exposure or modification of sensitive data.
Integrity	If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code, as with a standard buffer overflow and possibly without the use of large inputs if a precise index can be controlled.
Integrity Availability Confidentiality	A single fault could allow either an overflow (CWE-788) or underflow (CWE-786) of the array index. What happens next will depend on the type of operation being performed out of bounds, but can expose sensitive information, cause a system crash, or possibly lead to arbitrary code execution.

### Likelihood of Exploit

High

### Detection Methods

#### Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report array index errors that originate from command line arguments in a program that is not expected to run with setuid or other special privileges.

**Effectiveness: High**

This is not a perfect solution, since 100% accuracy and coverage are not feasible.

---

### Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

---

### Black Box

Black box methods might not get the needed code coverage within limited time constraints, and a dynamic test might not produce any noticeable side effects even if it is successful.

---

## Demonstrative Examples

### Example 1

The following C/C++ example retrieves the sizes of messages for a pop3 mail server. The message sizes are retrieved from a socket that returns in a buffer the message number and the message size, the message number (num) and size (size) are extracted from the buffer and the message size is placed into an array using the message number for the array index.

*(Bad Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
...
char buf[BUFFER_SIZE];
int ok;
int num, size;

// read values from socket and added to sizes array
while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
{

// continue read from socket until buf only contains '.'
if (DOTLINE(buf))
break;
else if (sscanf(buf, "%d %d", &num, &size) == 2)
sizes[num - 1] = size;
}
...
}
```

In this example the message number retrieved from the buffer could be a value that is outside the allowable range of indices for the array and could possibly be a negative number. Without proper validation of the value to be used for the array index an array overflow could occur and could potentially lead to unauthorized access to memory addresses and system crashes. The value of the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
...
char buf[BUFFER_SIZE];
int ok;
int num, size;

// read values from socket and added to sizes array
while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
{

// continue read from socket until buf only contains '.'
if (DOTLINE(buf))
```

```
break;
else if (sscanf(buf, "%d %d", &num, &size) == 2) {
if (num > 0 && num <= (unsigned)count)
sizes[num - 1] = size;
else
/* warn about possible attempt to induce buffer overflow */
report(stderr, "Warning: ignoring bogus data for message sizes returned by server.\n");
}
}
...
}
```

## Example 2

In the code snippet below, an unchecked integer value is used to reference an object in an array.

*(Bad Code)*

**Example Language: Java**

```
public String getValue(int index) {
return array[index];
}
```

If index is outside of the range of the array, this may result in an `ArrayIndexOutOfBoundsException` Exception being raised.

## Example 3

In the following Java example the method `displayProductSummary` is called from a Web service servlet to retrieve product summary information for display to the user. The servlet obtains the integer value of the product number from the user and passes it to the `displayProductSummary` method. The `displayProductSummary` method passes the integer value of the product number to the `getProductSummary` method which obtains the product summary from the array object containing the project summaries using the integer value of the product number as the array index.

*(Bad Code)*

**Example Language: Java**

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");

try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
return products[index];
}
```

In this example the integer value used as the array index that is provided by the user may be outside the allowable range of indices for the array which may provide unexpected results or may cause the application to fail. The integer value used for the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

**Example Language: Java**

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");
```

```
try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
String productSummary = "";

if ((index >= 0) && (index < MAX_PRODUCTS)) {
productSummary = products[index];
}
else {
System.err.println("index is out of bounds");
throw new IndexOutOfBoundsException();
}

return productSummary;
}
```

An alternative in Java would be to use one of the collection objects such as ArrayList that will automatically generate an exception if an attempt is made to access an array index that is out of bounds.

*(Good Code)*

#### Example Language: Java

```
ArrayList productArray = new ArrayList(MAX_PRODUCTS);
...
try {
productSummary = (String) productArray.get(index);
} catch (IndexOutOfBoundsException ex) {...}
```

### Observed Examples

Reference	Description
<a href="#">CVE-2005-0369</a>	large ID in packet used as array index
<a href="#">CVE-2001-1009</a>	negative array index as argument to POP LIST command
<a href="#">CVE-2003-0721</a>	Integer signedness error leads to negative array index
<a href="#">CVE-2004-1189</a>	product does not properly track a count and a maximum number, which can lead to resultant array index overflow.
<a href="#">CVE-2007-5756</a>	chain: device driver for packet-capturing software allows access to an unintended IOCTL with resultant array index error.

### Potential Mitigations

#### Phase: Architecture and Design

### Strategies: Input Validation; Libraries or Frameworks

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

---

#### Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

---

#### Phase: Requirements

### Strategy: Language Selection

Use a language with features that can automatically mitigate or eliminate out-of-bounds indexing errors.

---

For example, Ada allows the programmer to constrain the values of a variable and languages such as Java and Ruby will allow the programmer to handle exceptions when an out-of-bounds index is accessed.

#### Phase: Implementation

### Strategy: Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy (i.e., use a whitelist). Reject any input that does not strictly conform to specifications, or transform it into something that does. Use a blacklist to reject any unexpected inputs and detect potential attacks.

When accessing a user-controlled array index, use a stringent range of values that are within the target array. Make sure that you do not allow negative values to be used. That is, verify the minimum as well as the maximum of the range of acceptable values.

#### Phase: Implementation

Be especially careful to validate your input when you invoke code that crosses language boundaries, such as from an interpreted language to native code. This could create an unexpected interaction between the language boundaries. Ensure that you are not violating any of the expectations of the language with which you are interfacing. For example, even though Java may not be susceptible to buffer overflows, providing a large argument in a call to native code might trigger an overflow.

### Weakness Ordinalities

Ordinality	Description
Resultant	The most common condition situation leading to unchecked array indexing is the use of loop index variables as buffer indexes. If the end condition for the loop is subject to a flaw, the index can grow or shrink unbounded, therefore causing a buffer overflow or underflow. Another common situation leading to this condition is the use of a function's return value, or the resulting value of a calculation directly as an index in to a buffer.

### Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	20	<a href="#">Improper Input Validation</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	189	<a href="#">Numeric Errors</a>	Development Concepts699
ChildOf	Category	633	<a href="#">Weaknesses that Affect Memory</a>	<b>Resource-specific Weaknesses (primary)631</b>
ChildOf	Category	738	<a href="#">CERT C Secure Coding Section 04 - Integers (INT)</a>	<b>Weaknesses Addressed by the CERT C Secure Coding Standard (primary)734</b>
ChildOf	Category	740	<a href="#">CERT C Secure Coding Section 06 - Arrays (ARR)</a>	Weaknesses Addressed by the CERT C Secure Coding Standard734
ChildOf	Category	802	<a href="#">2010 Top 25 - Risky Resource Management</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
CanPrecede	Weakness Class	119	<a href="#">Failure to Constrain Operations within the Bounds of a Memory Buffer</a>	Research Concepts1000
CanPrecede	Weakness Variant	789	<a href="#">Uncontrolled Memory Allocation</a>	Research Concepts1000
PeerOf	Weakness Base	124	<a href="#">Buffer Underwrite ('Buffer Underflow')</a>	Research Concepts1000

### Theoretical Notes

An improperly validated array index might lead directly to the always-incorrect behavior of "access of array using out-of-bounds index."

### Affected Resources

## Memory

### f Causal Nature

### Explicit

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unchecked array indexing
PLOVER			INDEX - Array index overflow
CERT C Secure Coding	ARR00-C		Understand how arrays work
CERT C Secure Coding	ARR30-C		Guarantee that array indices are within the valid range
CERT C Secure Coding	ARR38-C		Do not add or subtract an integer to a pointer if the resulting value does not refer to a valid array element
CERT C Secure Coding	INT32-C		Ensure that operations on signed integers do not result in overflow

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">100</a>	Overflow Buffers	

### References

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 5, "Array Indexing Errors" Page 144. 2nd Edition. Microsoft. 2002.

### Content History

Submissions			
Submission Date	Submitter	Organization	Source
	CLASP		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Sean Eidemiller	Cigital	External
	added/updated demonstrative examples		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Applicable Platforms, Common Consequences, Relationships, Other Notes, Taxonomy Mappings, Weakness Ordinalities		
2008-11-24	CWE Content Team	MITRE	Internal
	updated Relationships, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Description, Name, Relationships		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Observed Examples, Other Notes, Potential Mitigations, Theoretical Notes, Weakness Ordinalities		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Demonstrative Examples, Detection Factors, Likelihood of Exploit, Potential Mitigations, References, Related Attack Patterns, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Related Attack Patterns		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-10-29	Unchecked Array Indexing		

[BACK TO TOP](#)

**Improper Access Control (Authorization)****Weakness ID:** 285 (*Weakness Class*)**Status:** Draft**Description****Description Summary**

The software does not perform or incorrectly performs access control checks across all potential execution paths.

**Extended Description**

When access control checks are not applied consistently - or not at all - users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information leaks, denial of service, and arbitrary code execution.

**Alternate Terms****AuthZ:**

"AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

**Time of Introduction**

- Architecture and Design
- Implementation
- Operation

**Applicable Platforms****Languages**

Language-independent

**Technology Classes**

Web-Server: (*Often*)

Database-Server: (*Often*)

**Modes of Introduction**

A developer may introduce authorization weaknesses because of a lack of understanding about the underlying technologies. For example, a developer may assume that attackers cannot modify certain inputs such as headers or cookies.

Authorization weaknesses may arise when a single-user application is ported to a multi-user environment.

**Common Consequences**

Scope	Effect
Confidentiality	An attacker could read sensitive data, either by reading the data directly from a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.
Integrity	An attacker could modify sensitive data, either by writing the data directly to a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to write the data.
Integrity	An attacker could gain privileges by modifying or reading critical data directly, or by accessing insufficiently-protected, privileged functionality.

**Likelihood of Exploit**

High

**Detection Methods**

### Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries.

Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

### **Effectiveness: Limited**

---

### Automated Dynamic Analysis

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic

---

### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

### **Effectiveness: Moderate**

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

---

## Demonstrative Examples

### Example 1

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

*(Bad Code)*

#### Example Language: Perl

```
sub DisplayPrivateMessage {
my($id) = @_ ;
my $Message = LookupMessageObject($id);
print "From: " . encodeHTML($Message->{from}) . "<br>\n";
print "Subject: " . encodeHTML($Message->{subject}) . "\n";
print "<hr>\n";
print "Body: " . encodeHTML($Message->{body}) . "\n";
}

my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (! AuthenticateUser($q->param('username'), $q->param('password'))) {
ExitError("invalid username or password");
}

my $id = $q->param('id');
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users. One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

## Observed Examples

Reference	Description
<a href="#">CVE-2009-3168</a>	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords.



<a href="#">CVE-2009-2960</a>	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users.
<a href="#">CVE-2009-3597</a>	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request.
<a href="#">CVE-2009-2282</a>	Terminal server does not check authorization for guest access.
<a href="#">CVE-2009-3230</a>	Database server does not use appropriate privileges for certain sensitive operations.
<a href="#">CVE-2009-2213</a>	Gateway uses default "Allow" configuration for its authorization settings.
<a href="#">CVE-2009-0034</a>	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges.
<a href="#">CVE-2008-6123</a>	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect.
<a href="#">CVE-2008-5027</a>	System monitoring software allows users to bypass authorization by creating custom forms.
<a href="#">CVE-2008-7109</a>	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client.
<a href="#">CVE-2008-3424</a>	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access.
<a href="#">CVE-2009-3781</a>	Content management system does not check access permissions for private files, allowing others to view those files.
<a href="#">CVE-2008-4577</a>	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions.
<a href="#">CVE-2008-6548</a>	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files.
<a href="#">CVE-2007-2925</a>	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries.
<a href="#">CVE-2006-6679</a>	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header.
<a href="#">CVE-2005-3623</a>	OS kernel does not check for a certain privilege before setting ACLs for files.
<a href="#">CVE-2005-2801</a>	Chain: file-system code performs an incorrect comparison (CWE-697), preventing defaults ACLs from being properly applied.
<a href="#">CVE-2001-1155</a>	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions.

## Potential Mitigations

### Phase: Architecture and Design

Divide your application into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) to enforce the roles at the appropriate boundaries.

Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

### Phase: Architecture and Design

Ensure that you perform access control checks related to your business logic. These checks may be different than the access control checks that you apply to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor.

### Phase: Architecture and Design

## Strategy: Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness

easier to avoid.

For example, consider using authorization frameworks such as the JAAS Authorization Framework and the OWASP ESAPI Access Control feature.

### Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page.

One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

### Phases: System Configuration; Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	254	<a href="#">Security Features</a>	<b>Seven Pernicious Kingdoms (primary)700</b>
ChildOf	Weakness Class	284	<a href="#">Access Control (Authorization) Issues</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	721	<a href="#">OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access</a>	<b>Weaknesses in OWASP Top Ten (2007) (primary)629</b>
ChildOf	Category	723	<a href="#">OWASP Top Ten 2004 Category A2 - Broken Access Control</a>	<b>Weaknesses in OWASP Top Ten (2004) (primary)711</b>
ChildOf	Category	753	<a href="#">2009 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)750</b>
ChildOf	Category	803	<a href="#">2010 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
ParentOf	Weakness Variant	219	<a href="#">Sensitive Data Under Web Root</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Base	551	<a href="#">Incorrect Behavior Order: Authorization Before Parsing and Canonicalization</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts1000</b>
ParentOf	Weakness Class	638	<a href="#">Failure to Use Complete Mediation</a>	<b>Research Concepts1000</b>
ParentOf	Weakness Base	804	<a href="#">Guessable CAPTCHA</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing Access Control
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">1</a>	Accessing Functionality Not Properly Constrained by ACLs	
<a href="#">13</a>	Subverting Environment Variable Values	

<a href="#">17</a>	Accessing, Modifying or Executing Executable Files
<a href="#">87</a>	Forceful Browsing
<a href="#">39</a>	Manipulating Opaque Client-based Data Tokens
<a href="#">45</a>	Buffer Overflow via Symbolic Links
<a href="#">51</a>	Poison Web Service Registry
<a href="#">59</a>	Session Credential Falsification through Prediction
<a href="#">60</a>	Reusing Session IDs (aka Session Replay)
<a href="#">77</a>	Manipulating User-Controlled Variables
<a href="#">76</a>	Manipulating Input to File System Calls
<a href="#">104</a>	Cross Zone Scripting

## References

NIST. "Role Based Access Control and Role Based Security". <<http://csrc.nist.gov/groups/SNS/rbac/>>.

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 4, "Authorization" Page 114; Chapter 6, "Determining Appropriate Access Control" Page 171. 2nd Edition. Microsoft. 2002.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	7 Pernicious Kingdoms		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Time of Introduction		
2008-08-15		Veracode	External
	Suggested OWASP Top Ten 2004 mapping		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Relationships, Other Notes, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences, Description, Likelihood of Exploit, Name, Other Notes, Potential Mitigations, References, Relationships		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
2009-05-27	CWE Content Team	MITRE	Internal
	updated Description, Related Attack Patterns		
2009-07-27	CWE Content Team	MITRE	Internal
	updated Relationships		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Type		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Demonstrative Examples, Detection Factors, Modes of Introduction, Observed Examples, Relationships		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Detection Factors, Potential Mitigations, References, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-01-12	Missing or Inconsistent Access Control		

[BACK TO TOP](#)

# TOCTOU

## Risk

### What might happen

At best, a Race Condition may cause errors in accuracy, overridden values or unexpected behavior that may result in denial-of-service. At worst, it may allow attackers to retrieve data or bypass security processes by replaying a controllable Race Condition until it plays out in their favor.

---

## Cause

### How does it happen

Race Conditions occur when a public, single instance of a resource is used by multiple concurrent logical processes. If these logical processes attempt to retrieve and update the resource without a timely management system, such as a lock, a Race Condition will occur.

An example for when a Race Condition occurs is a resource that may return a certain value to a process for further editing, and then updated by a second process, resulting in the original process' data no longer being valid. Once the original process edits and updates the incorrect value back into the resource, the second process' update has been overwritten and lost.

---

## General Recommendations

### How to avoid it

When sharing resources between concurrent processes across the application ensure that these resources are either thread-safe, or implement a locking mechanism to ensure expected concurrent activity.

---

## Source Code Examples

### Java Different Threads Increment and Decrement The Same Counter Repeatedly, Resulting in a Race Condition

```
public static int counter = 0;
public static void start() throws InterruptedException {
    incrementCounter ic;
    decrementCounter dc;
    while(counter == 0) {
        counter = 0;
        ic = new incrementCounter();
        dc = new decrementCounter();
        ic.start();
        dc.start();
        ic.join();
        dc.join();
    }
    System.out.println(counter); //Will stop and return either -1 or 1 due to race
    condition over counter
}

public static class incrementCounter extends Thread {
    public void run() {
        counter++;
    }
}
```

```
}

public static class decrementCounter extends Thread {
    public void run() {
        counter--;
    }
}
```

### Different Threads Increment and Decrement The Same Thread-Safe Counter Repeatedly, Never Resulting in a Race Condition

```
public static int counter = 0;
public static Object lock = new Object();

public static void start() throws InterruptedException {
    incrementCounter ic;
    decrementCounter dc;
    while(counter == 0) { // because of proper locking, this condition is never false
        counter = 0;
        ic = new incrementCounter();
        dc = new decrementCounter();
        ic.start();
        dc.start();
        ic.join();
        dc.join();
    }
    System.out.println(counter); // Never reached
}

public static class incrementCounter extends Thread {
    public void run() {
        synchronized (lock) {
            counter++;
        }
    }
}

public static class decrementCounter extends Thread {
    public void run() {
        synchronized (lock) {
            counter--;
        }
    }
}
```

## Scanned Languages

Language	Hash Number	Change Date
CPP	4541647240435660	6/19/2024
Common	0105849645654507	6/19/2024