
algosdk

Oct 04, 2021

Contents

1	Installation	3
2	SDK Development	5
3	Quick start	7
4	Node setup	9
5	Running examples/example.py	11
6	Documentation	13
7	License	15
8	Modules	17
8.1	algosdk	17
8.1.1	account	17
8.1.2	algod	17
8.1.3	auction	20
8.1.4	constants	22
8.1.5	encoding	25
8.1.6	error	26
8.1.7	future	28
8.1.7.1	future.template	28
8.1.7.2	future.transaction	31
8.1.8	kmd	57
8.1.9	logic	61
8.1.10	mnemonic	63
8.1.11	template	63
8.1.12	transaction	67
8.1.13	util	80
8.1.14	v2client	81
8.1.14.1	v2client.algod	81
8.1.14.2	v2client.indexer	84
8.1.15	wallet	90
8.1.16	wordlist	93
	Python Module Index	95

A python library for interacting with the Algorand network.

CHAPTER 1

Installation

Run `$ pip3 install py-algorand-sdk` to install the package.

Alternatively, choose a [distribution file](#), and run `$ pip3 install [file name]`.

CHAPTER 2

SDK Development

Run tests with `make docker-test`

CHAPTER 3

Quick start

Here's a simple example you can run without a node.

```
from algosdk import account, encoding

# generate an account
private_key, address = account.generate_account()
print("Private key:", private_key)
print("Address:", address)

# check if the address is valid
if encoding.is_valid_address(address):
    print("The address is valid!")
else:
    print("The address is invalid.")
```


CHAPTER 4

Node setup

Follow the instructions in Algorand's [developer resources](#) to install a node on your computer.

CHAPTER 5

Running examples/example.py

Before running [example.py](#), start kmd on a private network or testnet node:

```
$ ./goal kmd start -d [data directory]
```

Next, create a wallet and an account:

```
$ ./goal wallet new [wallet name] -d [data directory]
```

```
$ ./goal account new -d [data directory] -w [wallet name]
```

Visit the [Algorand dispenser](#) and enter the account address to fund your account.

Next, in [tokens.py](#), either update the tokens and addresses, or provide a path to the data directory.

You're now ready to run [example.py](#)!

CHAPTER 6

Documentation

Documentation for the Python SDK is available at py-algorand-sdk.readthedocs.io.

CHAPTER 7

License

py-algorand-sdk is licensed under a MIT license. See the [LICENSE](#) file for details.

8.1 algosdk

8.1.1 account

generate_account ()

Generate an account.

Returns private key, account address

Return type (str, str)

address_from_private_key (*private_key*)

Return the address for the private key.

Parameters **private_key** (*str*) – private key of the account in base64

Returns address of the account

Return type str

8.1.2 algod

class AlgodClient (*algod_token, algod_address, headers=None*)

Bases: object

Client class for kmd. Handles all algod requests.

Parameters

- **algod_token** (*str*) – algod API token
- **algod_address** (*str*) – algod address
- **headers** (*dict, optional*) – extra header name/value for all requests

algod_token

Type str

algod_address

Type str

headers

Type dict

algod_request (*method, requrl, params=None, data=None, headers=None, raw_response=False*)

Execute a given request.

Parameters

- **method** (*str*) – request method
- **requrl** (*str*) – url for the request
- **params** (*dict, optional*) – parameters for the request
- **data** (*dict, optional*) – data in the body of the request
- **headers** (*dict, optional*) – additional header for request
- **raw_response** (*bool, default False*) – return the HttpResponse object

Returns loaded from json response body

Return type dict

status (***kwargs*)

Return node status.

health (***kwargs*)

Return null if the node is running.

status_after_block (*block_num=None, round_num=None, **kwargs*)

Return node status immediately after blockNum.

Parameters

- **block_num** (*int, optional*) – block number
- **round_num** (*int, optional*) – alias for block_num; specify one of these

pending_transactions (*max_txns=0, **kwargs*)

Return pending transactions.

Parameters **max_txns** (*int*) – maximum number of transactions to return; if max_txns is 0, return all pending transactions

versions (***kwargs*)

Return algod versions.

ledger_supply (***kwargs*)

Return supply details for node's ledger.

transactions_by_address (*address, first=None, last=None, limit=None, from_date=None, to_date=None, **kwargs*)

Return transactions for an address. If indexer is not enabled, you can search by date and you do not have to specify first and last rounds.

Parameters

- **address** (*str*) – account public key
- **first** (*int, optional*) – no transactions before this block will be returned

- **last** (*int*, *optional*) – no transactions after this block will be returned; defaults to last round
- **limit** (*int*, *optional*) – maximum number of transactions to return; default is 100
- **from_date** (*str*, *optional*) – no transactions before this date will be returned; format YYYY-MM-DD
- **to_date** (*str*, *optional*) – no transactions after this date will be returned; format YYYY-MM-DD

account_info (*address*, ***kwargs*)

Return account information.

Parameters **address** (*str*) – account public key

asset_info (*index*, ***kwargs*)

Return asset information.

Parameters **index** (*int*) – asset index

list_assets (*max_index=None*, *max_assets=None*, ***kwargs*)

Return a list of up to *max_assets* assets, where the maximum asset index is *max_index*.

Parameters

- **max_index** (*int*, *optional*) – maximum asset index; defaults to 0, which lists most recent assets
- **max_assets** (*int*, *optional*) – maximum number of assets (0 to 100); defaults to 100

transaction_info (*address*, *transaction_id*, ***kwargs*)

Return transaction information.

Parameters

- **address** (*str*) – account public key
- **transaction_id** (*str*) – transaction ID

pending_transaction_info (*transaction_id*, ***kwargs*)

Return transaction information for a pending transaction.

Parameters **transaction_id** (*str*) – transaction ID

transaction_by_id (*transaction_id*, ***kwargs*)

Return transaction information; only works if indexer is enabled.

Parameters **transaction_id** (*str*) – transaction ID

suggested_fee (***kwargs*)

Return suggested transaction fee.

suggested_params (***kwargs*)

Return suggested transaction parameters.

suggested_params_as_object (***kwargs*)

Return suggested transaction parameters.

send_raw_transaction (*txn*, *headers=None*, ***kwargs*)

Broadcast a signed transaction to the network. Sets the default Content-Type header, if not previously set.

Parameters

- **txn** (*str*) – transaction to send, encoded in base64

- **request_header** (*dict*, *optional*) – additional header for request

Returns transaction ID

Return type str

send_transaction (*txn*, ***kwargs*)

Broadcast a signed transaction object to the network.

Parameters

- **txn** (*SignedTransaction* or *MultisigTransaction*) – transaction to send
- **request_header** (*dict*, *optional*) – additional header for request

Returns transaction ID

Return type str

send_transactions (*txns*, ***kwargs*)

Broadcast list of a signed transaction objects to the network.

Parameters

- **txns** (*SignedTransaction[]* or *MultisigTransaction[]*) – transactions to send
- **request_header** (*dict*, *optional*) – additional header for request

Returns first transaction ID

Return type str

block_info (*round=None*, *round_num=None*, ***kwargs*)

Return block information.

Parameters

- **round** (*int*, *optional*) – block number; deprecated, please use round_num
- **round_num** (*int*, *optional*) – alias for round; specify only one of these

block_raw (*round=None*, *round_num=None*, ***kwargs*)

Return decoded raw block as the network sees it.

Parameters

- **round** (*int*, *optional*) – block number; deprecated, please use round_num
- **round_num** (*int*, *optional*) – alias for round; specify only one of these

8.1.3 auction

class Bid (*bidder*, *bid_currency*, *max_price*, *bid_id*, *auction_key*, *auction_id*)

Bases: object

Represents a bid in an auction.

Parameters

- **bidder** (*str*) – address of the bidder
- **bid_currency** (*int*) – how much external currency is being spent
- **max_price** (*int*) – the maximum price the bidder is willing to pay
- **bid_id** (*int*) – bid ID

- **auction_key** (*str*) – address of the auction
- **auction_id** (*int*) – auction ID

bidder

Type *str*

bid_currency

Type *int*

max_price

Type *int*

bid_id

Type *int*

auction_key

Type *str*

auction_id

Type *int*

dictify ()

sign (*private_key*)

Sign a bid.

Parameters **private_key** (*str*) – private_key of the bidder

Returns signed bid with the signature

Return type *SignedBid*

static undictify (*d*)

class SignedBid (*bid, signature*)

Bases: *object*

Represents a signed bid in an auction.

Parameters

- **bid** (*Bid*) – bid that was signed
- **signature** (*str*) – the signature of the bidder

bid

Type *Bid*

signature

Type *str*

dictify ()

static undictify (*d*)

class NoteField (*signed_bid, note_field_type*)

Bases: *object*

Can be encoded and added to a transaction.

Parameters

- **signed_bid** (*SignedBid*) – bid with signature of bidder
- **note_field_type** (*str*) – the type of note; see constants for possible types

signed_bid

Type *SignedBid*

note_field_type

Type *str*

dictify ()

static undictify (*d*)

8.1.4 constants

Contains useful constants.

KMD_AUTH_HEADER = 'X-KMD-API-Token'

header key for kmd requests

Type *str*

ALGOD_AUTH_HEADER = 'X-Algo-API-Token'

header key for algod requests

Type *str*

INDEXER_AUTH_HEADER = 'X-Indexer-API-Token'

header key for indexer requests

Type *str*

UNVERSIONED_PATHS = ['/health', '/versions', '/metrics', '/genesis']

paths that don't use the version path prefix

Type *str[]*

NO_AUTH = []

requests that don't require authentication

Type *str[]*

PAYMENT_TXN = 'pay'

indicates a payment transaction

Type *str*

KEYREG_TXN = 'keyreg'

indicates a key registration transaction

Type *str*

ASSETCONFIG_TXN = 'acfg'

indicates an asset configuration transaction

Type *str*

ASSETFREEZE_TXN = 'afrz'

indicates an asset freeze transaction

Type *str*

ASSETTRANSFER_TXN = 'axfer'

indicates an asset transfer transaction

Type str

APPCALL_TXN = 'appl'

indicates an app call transaction, allows creating, deleting, and interacting with an application

Type str

NOTE_FIELD_TYPE_DEPOSIT = 'd'

indicates a signed deposit in NoteField

Type str

NOTE_FIELD_TYPE_BID = 'b'

indicates a signed bid in NoteField

Type str

NOTE_FIELD_TYPE_SETTLEMENT = 's'

indicates a signed settlement in NoteField

Type str

NOTE_FIELD_TYPE_PARAMS = 'p'

indicates signed params in NoteField

Type str

TXID_PREFIX = b'TX'

transaction prefix when signing

Type bytes

TGID_PREFIX = b'TG'

transaction group prefix when computing the group ID

Type bytes

BID_PREFIX = b'aB'

bid prefix when signing

Type bytes

BYTES_PREFIX = b'MX'

bytes prefix when signing

Type bytes

MSIG_ADDR_PREFIX = 'MultisigAddr'

prefix for multisig addresses

Type str

LOGIC_PREFIX = b'Program'

program (logic) prefix when signing

Type bytes

LOGIC_DATA_PREFIX = b'ProgData'

program (logic) data prefix when signing

Type bytes

APPID_PREFIX = b'appID'

application ID prefix when signing

Type bytes

HASH_LEN = 32

how long various hash-like fields should be

Type int

CHECK_SUM_LEN_BYTES = 4

how long checksums should be

Type int

KEN_LEN_BYTES = 32

how long addresses are in bytes

Type int

ADDRESS_LEN = 58

how long addresses are in base32, including the checksum

Type int

MNEMONIC_LEN = 25

how long mnemonic phrases are

Type int

MIN_TXN_FEE = 1000

minimum transaction fee

Type int

MICROALGOS_TO_ALGOS_RATIO = 1000000

how many microalgos per algo

Type int

METADATA_LENGTH = 32

length of asset metadata

Type int

NOTE_MAX_LENGTH = 1024

maximum length of note field

Type int

LEASE_LENGTH = 32

byte length of leases

Type int

MULTISIG_ACCOUNT_LIMIT = 255

maximum number of addresses in a multisig account

Type int

TX_GROUP_LIMIT = 16

maximum number of transaction in a transaction group

Type int

MAX_ASSET_DECIMALS = 19

maximum value for decimals in assets

Type int

LOGIC_SIG_MAX_COST = 20000

max execution cost of a teal program

Type int

LOGIC_SIG_MAX_SIZE = 1000

max size of a teal program and its arguments in bytes

Type int

8.1.5 encoding

msgpack_encode (*obj*)

Encode the object using canonical msgpack.

Parameters **obj** (*Transaction*, *SignedTransaction*, *MultisigTransaction*, *Multisig*, *Bid*, or *SignedBid*) – object to be encoded

Returns msgpack encoded object

Return type str

Note: Canonical Msgpack: maps must contain keys in lexicographic order; maps must omit key-value pairs where the value is a zero-value; positive integer values must be encoded as “unsigned” in msgpack, regardless of whether the value space is semantically signed or unsigned; integer values must be represented in the shortest possible encoding; binary arrays must be represented using the “bin” format family (that is, use the most recent version of msgpack rather than the older msgpack version that had no “bin” family).

future_msgpack_decode (*enc*)

Decode a msgpack encoded object from a string.

Parameters **enc** (*str*) – string to be decoded

Returns decoded object

Return type *Transaction*, *SignedTransaction*, *Multisig*, *Bid*, or *SignedBid*

msgpack_decode (*enc*)

Decode a msgpack encoded object from a string.

Parameters **enc** (*str*) – string to be decoded

Returns decoded object

Return type *Transaction*, *SignedTransaction*, *Multisig*, *Bid*, or *SignedBid*

is_valid_address (*addr*)

Check if the string address is a valid Algorand address.

Parameters **addr** (*str*) – base32 address

Returns whether or not the address is valid

Return type bool

decode_address (*addr*)

Decode a string address into its address bytes and checksum.

Parameters **addr** (*str*) – base32 address

Returns address decoded into bytes

Return type bytes

encode_address (*addr_bytes*)

Encode a byte address into a string composed of the encoded bytes and the checksum.

Parameters **addr_bytes** (*bytes*) – address in bytes

Returns base32 encoded address

Return type str

checksum (*data*)

Compute the checksum of arbitrary binary input.

Parameters **data** (*bytes*) – data as bytes

Returns checksum of the data

Return type bytes

8.1.6 error

exception BadTxnSenderError

Bases: Exception

exception InvalidThresholdError

Bases: Exception

exception InvalidSecretKeyError

Bases: Exception

exception MergeKeysMismatchError

Bases: Exception

exception MergeAuthAddrMismatchError

Bases: Exception

exception DuplicateSigMismatchError

Bases: Exception

exception LogicSigOverspecifiedSignature

Bases: Exception

exception LogicSigSigningKeyMissing

Bases: Exception

exception WrongAmountType

Bases: Exception

exception WrongChecksumError

Bases: Exception

exception WrongKeyLengthError

Bases: Exception

exception WrongMnemonicLengthError

Bases: Exception

exception WrongHashLengthError

Bases: Exception

General error that is normally changed to be more specific

exception WrongKeyBytesLengthError

Bases: Exception

```
exception UnknownMsigVersionError  
    Bases: Exception  
  
exception WrongMetadataLengthError  
    Bases: Exception  
  
exception WrongLeaseLengthError  
    Bases: Exception  
  
exception WrongNoteType  
    Bases: Exception  
  
exception WrongNoteLength  
    Bases: Exception  
  
exception InvalidProgram (message='invalid program for logic sig')  
    Bases: Exception  
  
exception TransactionGroupSizeError  
    Bases: Exception  
  
exception MultisigAccountSizeError  
    Bases: Exception  
  
exception OutOfRangeDecimalsError  
    Bases: Exception  
  
exception EmptyAddressError  
    Bases: Exception  
  
exception WrongContractError (contract_type)  
    Bases: Exception  
  
exception OverspecifiedRoundError (contract_type)  
    Bases: Exception  
  
exception UnderspecifiedRoundError (contract_type)  
    Bases: Exception  
  
exception ZeroAddressError  
    Bases: Exception  
  
exception KeyregOnlineTxnInitError (attr)  
    Bases: Exception  
  
exception TemplateInputError  
    Bases: Exception  
  
exception TemplateError  
    Bases: Exception  
  
exception KMDHTTPError  
    Bases: Exception  
  
exception AlgodHTTPError (msg, code=None)  
    Bases: Exception  
  
exception AlgodResponseError (msg)  
    Bases: Exception  
  
exception IndexerHTTPError  
    Bases: Exception
```

exception ConfirmationTimeoutErrorBases: `Exception`

8.1.7 future

8.1.7.1 future.template

class TemplateBases: `object`**get_address()**

Return the address of the contract.

get_program()**class Split** (*owner: str, receiver_1: str, receiver_2: str, rat_1: int, rat_2: int, expiry_round: int, min_pay: int, max_fee: int*)Bases: `algosdk.future.template.Template`

Split allows locking algos in an account which allows transferring to two predefined addresses in a specified ratio such that for the given `ratn` and `ratd` parameters we have:

$$\text{first_recipient_amount} * \text{rat_2} == \text{second_recipient_amount} * \text{rat_1}$$

Split also has an expiry round, after which the owner can transfer back the funds.

Parameters

- **owner** (*str*) – an address that can receive the funds after the expiry round
- **receiver_1** (*str*) – first address to receive funds
- **receiver_2** (*str*) – second address to receive funds
- **rat_1** (*int*) – how much receiver_1 receives (proportionally)
- **rat_2** (*int*) – how much receiver_2 receives (proportionally)
- **expiry_round** (*int*) – the round on which the funds can be transferred back to owner
- **min_pay** (*int*) – the minimum number of microalgos that can be transferred from the account to receiver_1
- **max_fee** (*int*) – half the maximum fee that can be paid to the network by the account

get_program()

Return a byte array to be used in LogicSig.

static get_split_funds_transaction (*contract, amount: int, sp*)

Return a group transactions array which transfers funds according to the contract's ratio.

Parameters

- **amount** (*int*) – total amount to be transferred
- **sp** (`SuggestedParams`) – suggested params from algod

Returns `Transaction[]`**class HTLC** (*owner: str, receiver: str, hash_function: str, hash_image: str, expiry_round: int, max_fee: int*)Bases: `algosdk.future.template.Template`

Hash Time Locked Contract allows a user to receive the Algo prior to a deadline (in terms of a round) by proving knowledge of a special value or to forfeit the ability to claim, returning it to the payer. This contract is usually used to perform cross-chained atomic swaps.

More formally, algos can be transferred under only two circumstances:

1. To receiver if `hash_function(arg_0) = hash_value`
2. To owner if `txn.FirstValid > expiry_round`

Parameters

- **owner** (*str*) – an address that can receive the asset after the expiry round
- **receiver** (*str*) – address to receive Algos
- **hash_function** (*str*) – the hash function to be used (must be either sha256 or keccak256)
- **hash_image** (*str*) – the hash image in base64
- **expiry_round** (*int*) – the round on which the assets can be transferred back to owner
- **max_fee** (*int*) – the maximum fee that can be paid to the network by the account

get_program()

Return a byte array to be used in LogicSig.

static get_transaction (*contract, preimage, sp*)

Return a transaction which will release funds if a matching preimage is used.

Parameters

- **contract** (*bytes*) – the contract containing information, should be received from payer
- **preimage** (*str*) – the preimage of the hash in base64
- **sp** (*SuggestedParams*) – suggested params from algod

Returns

transaction to claim algos from contract account

Return type *LogicSigTransaction*

class DynamicFee (*receiver: str, amount: int, sp, close_remainder_address: str = None*)

Bases: *algosdk.future.template.Template*

DynamicFee contract allows you to create a transaction without specifying the fee. The fee will be determined at the moment of transfer.

Parameters

- **receiver** (*str*) – address to receive the assets
- **amount** (*int*) – amount of assets to transfer
- **sp** (*SuggestedParams*) – suggested params from algod
- **close_remainder_address** (*str, optional*) – the address that receives the remainder

get_program()

Return a byte array to be used in LogicSig.

static get_transactions (*txn, lsig, private_key, fee*)

Create and sign the secondary dynamic fee transaction, update transaction fields, and sign as the fee payer; return both transactions.

Parameters

- **txn** (*Transaction*) – main transaction from payer
- **lsig** (*LogicSig*) – signed logic received from payer
- **private_key** (*str*) – the secret key of the account that pays the fee in base64
- **fee** (*int*) – fee per byte, for both transactions

sign_dynamic_fee (*private_key*)

Return the main transaction and signed logic needed to complete the transfer. These should be sent to the fee payer, who can use `get_transactions()` to update fields and create the auxiliary transaction.

Parameters **private_key** (*bytes*) – the secret key to sign the contract in base64

class PeriodicPayment (*receiver: str, amount: int, withdrawing_window: int, period: int, max_fee: int, timeout: int*)

Bases: *algosdk.future.template.Template*

PeriodicPayment contract enables creating an account which allows the withdrawal of a fixed amount of assets every fixed number of rounds to a specific Algorand Address. In addition, the contract allows to add timeout, after which the address can withdraw the rest of the assets.

Parameters

- **receiver** (*str*) – address to receive the assets
- **amount** (*int*) – amount of assets to transfer at every cycle
- **withdrawing_window** (*int*) – the number of blocks in which the user can withdraw the asset once the period start (must be < 1000)
- **period** (*int*) – how often the address can withdraw assets (in rounds)
- **fee** (*int*) – maximum fee per transaction
- **timeout** (*int*) – a round in which the receiver can withdraw the rest of the funds after

get_program ()

Return a byte array to be used in LogicSig.

static get_withdrawal_transaction (*contract, sp*)

Return the withdrawal transaction to be sent to the network.

Parameters

- **contract** (*bytes*) – contract containing information, should be received from payer
- **sp** (*SuggestedParams*) – suggested params from algod; the value of `sp.last` will not be used. Instead, the last valid round will be calculated from first valid round and withdrawing window

class LimitOrder (*owner: str, asset_id: int, ratn: int, ratd: int, expiry_round: int, max_fee: int, min_trade: int*)

Bases: *algosdk.future.template.Template*

Limit Order allows to trade Algos for other assets given a specific ratio; for N Algos, swap for Rate * N Assets.

...

Parameters

- **owner** (*str*) – an address that can receive the asset after the expiry round

- **asset_id** (*int*) – asset to be transferred
- **ratn** (*int*) – the numerator of the exchange rate
- **ratd** (*int*) – the denominator of the exchange rate
- **expiry_round** (*int*) – the round on which the assets can be transferred back to owner
- **max_fee** (*int*) – the maximum fee that can be paid to the network by the account
- **min_trade** (*int*) – the minimum amount (of Algos) to be traded away

get_program ()

Return a byte array to be used in LogicSig.

static get_swap_assets_transactions (*contract: bytes, asset_amount: int, microalgo_amount: int, private_key: str, sp*)

Return a group transactions array which transfer funds according to the contract's ratio.

Parameters

- **contract** (*bytes*) – the contract containing information, should be received from payer
- **asset_amount** (*int*) – the amount of assets to be sent
- **microalgo_amount** (*int*) – the amount of microalgos to be received
- **private_key** (*str*) – the secret key to sign the contract
- **sp** (*SuggestedParams*) – suggested params from algod

put_uvarint (*buf, x*)

inject (*orig, offsets, values, values_types*)

8.1.7.2 future.transaction

class SuggestedParams (*fee, first, last, gh, gen=None, flat_fee=False, consensus_version=None, min_fee=None*)

Bases: object

Contains various fields common to all transaction types.

Parameters

- **fee** (*int*) – transaction fee (per byte if flat_fee is false). When flat_fee is true, fee may fall to zero but a group of N atomic transactions must still have a fee of at least N*min_txn_fee.
- **first** (*int*) – first round for which the transaction is valid
- **last** (*int*) – last round for which the transaction is valid
- **gh** (*str*) – genesis hash
- **gen** (*str, optional*) – genesis id
- **flat_fee** (*bool, optional*) – whether the specified fee is a flat fee
- **consensus_version** (*str, optional*) – the consensus protocol version as of 'first'
- **min_fee** (*int, optional*) – the minimum transaction fee (flat)

fee

Type int

first

```

        Type int
last
        Type int
gen
        Type str
gh
        Type str
flat_fee
        Type bool
consensus_version
        Type str
min_fee
        Type int
class Transaction(sender, sp, note, lease, txn_type, rekey_to)
    Bases: object
    Superclass for various transaction types.
    static as_hash(hash)
        Confirm that a value is 32 bytes. If all zeros, or a falsy value, return None
    static as_note(note)
    classmethod as_lease(lease)
    get_txid()
        Get the transaction's ID.
        Returns transaction ID
        Return type str
    sign(private_key)
        Sign the transaction with a private key.
        Parameters private_key(str) – the private key of the signing account
        Returns signed transaction with the signature
        Return type SignedTransaction
    raw_sign(private_key)
        Sign the transaction.
        Parameters private_key(str) – the private key of the signing account
        Returns signature
        Return type bytes
    estimate_size()
    dictify()
    static undictify(d)
    static required(arg)

```

static creatable_index (*index*, *required=False*)

Coerce an index for apps or assets to an integer.

By using this in all constructors, we allow callers to use strings as indexes, check our convenience Txn types to ensure index is set, and ensure that 0 is always used internally for an unset id, not None, so `__eq__` works properly.

class PaymentTxn (*sender*, *sp*, *receiver*, *amt*, *close_remainder_to=None*, *note=None*, *lease=None*, *rekey_to=None*)

Bases: `algosdk.future.transaction.Transaction`

Represents a payment transaction.

Parameters

- **sender** (*str*) – address of the sender
- **sp** (`SuggestedParams`) – suggested params from algod
- **receiver** (*str*) – address of the receiver
- **amt** (*int*) – amount in microAlgos to be sent
- **close_remainder_to** (*str*, *optional*) – if nonempty, account will be closed and remaining algos will be sent to this address
- **note** (*bytes*, *optional*) – arbitrary optional bytes
- **lease** (*byte[32]*, *optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str*, *optional*) – additionally rekey the sender to this address

sender

Type `str`

fee

Type `int`

first_valid_round

Type `int`

last_valid_round

Type `int`

note

Type `bytes`

genesis_id

Type `str`

genesis_hash

Type `str`

group

Type `bytes`

receiver

Type `str`

amt

```
    Type int
close_remainder_to
    Type str
type
    Type str
lease
    Type byte[32]
rekey_to
    Type str
dictify()
class KeyregTxn(sender, sp, votekey, selkey, votefst, votelst, votekd, note=None, lease=None,
               rekey_to=None, nonpart=None)
    Bases: algosdk.future.transaction.Transaction
    Represents a key registration transaction.

    Parameters
    • sender (str) – address of sender
    • sp (SuggestedParams) – suggested params from algod
    • votekey (str) – participation public key in base64
    • selkey (str) – VRF public key in base64
    • votefst (int) – first round to vote
    • votelst (int) – last round to vote
    • votekd (int) – vote key dilution
    • note (bytes, optional) – arbitrary optional bytes
    • lease (byte[32], optional) – specifies a lease, and no other transaction with the
      same sender and lease can be confirmed in this transaction’s valid rounds
    • rekey_to (str, optional) – additionally rekey the sender to this address
    • nonpart (bool, optional) – mark the account non-participating if true

sender
    Type str
fee
    Type int
first_valid_round
    Type int
last_valid_round
    Type int
note
    Type bytes
```

```

genesis_id
    Type str
genesis_hash
    Type str
group
    Type bytes
votepk
    Type str
selkey
    Type str
votefst
    Type int
votelst
    Type int
votekd
    Type int
type
    Type str
lease
    Type byte[32]
rekey_to
    Type str
nonpart
    Type bool
dictify()
class KeyregOnlineTxn(sender, sp, votekey, selkey, votefst, votelst, votekd, note=None, lease=None,
                      rekey_to=None)
Bases: algosdk.future.transaction.KeyregTxn

```

Represents an online key registration transaction. nonpart is implicitly False for this transaction.

Parameters

- **sender** (*str*) – address of sender
- **sp** (*SuggestedParams*) – suggested params from algod
- **votekey** (*str*) – participation public key in base64
- **selkey** (*str*) – VRF public key in base64
- **votefst** (*int*) – first round to vote
- **votelst** (*int*) – last round to vote
- **votekd** (*int*) – vote key dilution

- **note** (*bytes, optional*) – arbitrary optional bytes
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str, optional*) – additionally rekey the sender to this address

sender

Type str

fee

Type int

first_valid_round

Type int

last_valid_round

Type int

note

Type bytes

genesis_id

Type str

genesis_hash

Type str

group

Type bytes

votepk

Type str

selkey

Type str

votefst

Type int

votelst

Type int

votekd

Type int

type

Type str

lease

Type byte[32]

rekey_to

Type str


```
class KeyregOfflineTxn (sender, sp, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.KeyregTxn`

Represents an offline key registration transaction. `nonpart` is implicitly `False` for this transaction.

Parameters

- **sender** (*str*) – address of sender
- **sp** (`SuggestedParams`) – suggested params from algod
- **note** (*bytes, optional*) – arbitrary optional bytes
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str, optional*) – additionally rekey the sender to this address

sender

Type `str`

fee

Type `int`

first_valid_round

Type `int`

last_valid_round

Type `int`

note

Type `bytes`

genesis_id

Type `str`

genesis_hash

Type `str`

group

Type `bytes`

type

Type `str`

lease

Type `byte[32]`

rekey_to

Type `str`

```
class KeyregNonparticipatingTxn (sender, sp, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.KeyregTxn`

Represents a nonparticipating key registration transaction. `nonpart` is implicitly `True` for this transaction.

Parameters

- **sender** (*str*) – address of sender

- **sp** (*SuggestedParams*) – suggested params from algod
- **note** (*bytes, optional*) – arbitrary optional bytes
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str, optional*) – additionally rekey the sender to this address

sender

Type str

fee

Type int

first_valid_round

Type int

last_valid_round

Type int

note

Type bytes

genesis_id

Type str

genesis_hash

Type str

group

Type bytes

type

Type str

lease

Type byte[32]

rekey_to

Type str

class AssetConfigTxn (*sender, sp, index=None, total=None, default_frozen=None, unit_name=None, asset_name=None, manager=None, reserve=None, freeze=None, clawback=None, url=None, metadata_hash=None, note=None, lease=None, strict_empty_address_check=True, decimals=0, rekey_to=None*)

Bases: *algosdk.future.transaction.Transaction*

Represents a transaction for asset creation, reconfiguration, or destruction.

To create an asset, include the following: total, default_frozen, unit_name, asset_name, manager, reserve, freeze, clawback, url, metadata, decimals

To destroy an asset, include the following: index, strict_empty_address_check (set to False)

To update asset configuration, include the following: index, manager, reserve, freeze, clawback, strict_empty_address_check (optional)

Parameters

- **sender** (*str*) – address of the sender
- **sp** (*SuggestedParams*) – suggested params from algod
- **index** (*int*, *optional*) – index of the asset
- **total** (*int*, *optional*) – total number of base units of this asset created
- **default_frozen** (*bool*, *optional*) – whether slots for this asset in user accounts are frozen by default
- **unit_name** (*str*, *optional*) – hint for the name of a unit of this asset
- **asset_name** (*str*, *optional*) – hint for the name of the asset
- **manager** (*str*, *optional*) – address allowed to change nonzero addresses for this asset
- **reserve** (*str*, *optional*) – account whose holdings of this asset should be reported as “not minted”
- **freeze** (*str*, *optional*) – account allowed to change frozen state of holdings of this asset
- **clawback** (*str*, *optional*) – account allowed take units of this asset from any account
- **url** (*str*, *optional*) – a URL where more information about the asset can be retrieved
- **metadata_hash** (*byte[32]*, *optional*) – a commitment to some unspecified asset metadata (32 byte hash)
- **note** (*bytes*, *optional*) – arbitrary optional bytes
- **lease** (*byte[32]*, *optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **strict_empty_address_check** (*bool*, *optional*) – set this to False if you want to specify empty addresses. Otherwise, if this is left as True (the default), having empty addresses will raise an error, which will prevent accidentally removing admin access to assets or deleting the asset.
- **decimals** (*int*, *optional*) – number of digits to use for display after decimal. If set to 0, the asset is not divisible. If set to 1, the base unit of the asset is in tenths. Must be between 0 and 19, inclusive. Defaults to 0.
- **rekey_to** (*str*, *optional*) – additionally rekey the sender to this address

sender

Type *str*

fee

Type *int*

first_valid_round

Type *int*

last_valid_round

Type *int*

genesis_hash

```

        Type str
    index
        Type int
    total
        Type int
    default_frozen
        Type bool
    unit_name
        Type str
    asset_name
        Type str
    manager
        Type str
    reserve
        Type str
    freeze
        Type str
    clawback
        Type str
    url
        Type str
    metadata_hash
        Type byte[32]
    note
        Type bytes
    genesis_id
        Type str
    type
        Type str
    lease
        Type byte[32]
    decimals
        Type int
    rekey
        Type str
    dictify()

```

```
classmethod as_metadata(md)
```

```
class AssetCreateTxn(sender, sp, total, decimals, default_frozen, *, manager=None, reserve=None,
                    freeze=None, clawback=None, unit_name="", asset_name="", url="", meta-
                    data_hash=None, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.AssetConfigTxn`

Represents a transaction for asset creation.

Keyword arguments are required, starting with the special addresses, to prevent errors, as type checks can't prevent simple confusion of similar typed arguments. Since the special addresses are required, `strict_empty_address_check` is turned off.

Parameters

- **sender** (*str*) – address of the sender
- **sp** (`SuggestedParams`) – suggested params from algod
- **total** (*int*) – total number of base units of this asset created
- **decimals** (*int, optional*) – number of digits to use for display after decimal. If set to 0, the asset is not divisible. If set to 1, the base unit of the asset is in tenths. Must be between 0 and 19, inclusive. Defaults to 0.
- **default_frozen** (*bool*) – whether slots for this asset in user accounts are frozen by default
- **manager** (*str*) – address allowed to change nonzero addresses for this asset
- **reserve** (*str*) – account whose holdings of this asset should be reported as “not minted”
- **freeze** (*str*) – account allowed to change frozen state of holdings of this asset
- **clawback** (*str*) – account allowed take units of this asset from any account
- **unit_name** (*str*) – hint for the name of a unit of this asset
- **asset_name** (*str*) – hint for the name of the asset
- **url** (*str*) – a URL where more information about the asset can be retrieved
- **metadata_hash** (*byte[32], optional*) – a commitment to some unspecified asset metadata (32 byte hash)
- **note** (*bytes, optional*) – arbitrary optional bytes
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction's valid rounds
- **rekey_to** (*str, optional*) – additionally rekey the sender to this address

```
class AssetDestroyTxn(sender, sp, index, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.AssetConfigTxn`

Represents a transaction for asset destruction.

An asset destruction transaction can only be sent by the manager address, and only when the manager possesses all units of the asset.

```
class AssetUpdateTxn(sender, sp, index, *, manager, reserve, freeze, clawback, note=None,
                    lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.AssetConfigTxn`

Represents a transaction for asset modification.

To update asset configuration, include the following: `index`, `manager`, `reserve`, `freeze`, `clawback`.

Keyword arguments are required, starting with the special addresses, to prevent argument reordering errors. Since the special addresses are required, `strict_empty_address_check` is turned off.

Parameters

- **sender** (*str*) – address of the sender
- **sp** (*SuggestedParams*) – suggested params from algod
- **index** (*int*) – index of the asset to reconfigure
- **manager** (*str*) – address allowed to change nonzero addresses for this asset
- **reserve** (*str*) – account whose holdings of this asset should be reported as “not minted”
- **freeze** (*str*) – account allowed to change frozen state of holdings of this asset
- **clawback** (*str*) – account allowed take units of this asset from any account
- **note** (*bytes*, *optional*) – arbitrary optional bytes
- **lease** (*byte[32]*, *optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str*, *optional*) – additionally rekey the sender to this address

```
class AssetFreezeTxn(sender, sp, index, target, new_freeze_state, note=None, lease=None,
                    rekey_to=None)
```

Bases: `algosdk.future.transaction.Transaction`

Represents a transaction for freezing or unfreezing an account’s asset holdings. Must be issued by the asset’s freeze manager.

Parameters

- **sender** (*str*) – address of the sender, who must be the asset’s freeze manager
- **sp** (*SuggestedParams*) – suggested params from algod
- **index** (*int*) – index of the asset
- **target** (*str*) – address having its assets frozen or unfrozen
- **new_freeze_state** (*bool*) – true if the assets should be frozen, false if they should be transferrable
- **note** (*bytes*, *optional*) – arbitrary optional bytes
- **lease** (*byte[32]*, *optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str*, *optional*) – additionally rekey the sender to this address

sender

Type *str*

fee

Type *int*

first_valid_round

Type *int*

last_valid_round

Type *int*

genesis_hash

```

        Type str
    index
        Type int
    target
        Type str
    new_freeze_state
        Type bool
    note
        Type bytes
    genesis_id
        Type str
    type
        Type str
    lease
        Type byte[32]
    rekey_to
        Type str
    dictify()

class AssetTransferTxn(sender, sp, receiver, amt, index, close_assets_to=None, revoca-
                        tion_target=None, note=None, lease=None, rekey_to=None)
    Bases: algosdk.future.transaction.Transaction

```

Represents a transaction for asset transfer.

To begin accepting an asset, supply the same address as both sender and receiver, and set amount to 0 (or use `AssetOptInTxn`)

To revoke an asset, set `revocation_target`, and issue the transaction from the asset's revocation manager account.

Parameters

- **sender** (*str*) – address of the sender
- **sp** (*SuggestedParams*) – suggested params from algod
- **receiver** (*str*) – address of the receiver
- **amt** (*int*) – amount of asset base units to send
- **index** (*int*) – index of the asset
- **close_assets_to** (*string, optional*) – send all of sender's remaining assets, after paying *amt* to receiver, to this address
- **revocation_target** (*string, optional*) – send assets from this address, rather than the sender's address (can only be used by an asset's revocation manager, also known as clawback)
- **note** (*bytes, optional*) – arbitrary optional bytes
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction's valid rounds

- **rekey_to**(*str*, *optional*) – additionally rekey the sender to this address

sender

Type *str*

fee

Type *int*

first_valid_round

Type *int*

last_valid_round

Type *int*

genesis_hash

Type *str*

index

Type *int*

amount

Type *int*

receiver

Type *string*

close_assets_to

Type *string*

revocation_target

Type *string*

note

Type *bytes*

genesis_id

Type *str*

type

Type *str*

lease

Type *byte[32]*

rekey_to

Type *str*

dictify()

class AssetOptInTxn (*sender, sp, index, note=None, lease=None, rekey_to=None*)

Bases: *algosdk.future.transaction.AssetTransferTxn*

Make a transaction that will opt in to an ASA

Parameters

- **sender** (*str*) – address of sender
- **sp** (*SuggestedParams*) – contains information such as fee and genesis hash
- **index** (*int*) – the ASA to opt into
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `AssetTransferTxn`

class `AssetCloseOutTxn` (*sender*, *sp*, *receiver*, *index*, *note=None*, *lease=None*, *rekey_to=None*)

Bases: `algosdk.future.transaction.AssetTransferTxn`

Make a transaction that will send all of an ASA away, and opt out of it.

Parameters

- **sender** (*str*) – address of sender
- **sp** (*SuggestedParams*) – contains information such as fee and genesis hash
- **receiver** (*str*) – address of the receiver
- **index** (*int*) – the ASA to opt into
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `AssetTransferTxn`

class `StateSchema` (*num_uints=None*, *num_byte_slices=None*)

Bases: `object`

Restricts state for an application call.

Parameters

- **num_uints** (*int*, *optional*) – number of uints to store
- **num_byte_slices** (*int*, *optional*) – number of byte slices to store

num_uints

Type `int`

num_byte_slices

Type `int`

dictify ()

static undictify (*d*)

class `OnComplete`

Bases: `enum.IntEnum`

An enumeration.

NoOpOC = 0

OptInOC = 1

CloseOutOC = 2

`ClearStateOC = 3`

`UpdateApplicationOC = 4`

`DeleteApplicationOC = 5`

```
class ApplicationCallTxn(sender, sp, index, on_complete, local_schema=None,
                        global_schema=None, approval_program=None, clear_program=None,
                        app_args=None, accounts=None, foreign_apps=None, foreign_assets=None,
                        note=None, lease=None, rekey_to=None, extra_pages=0)
```

Bases: `algosdk.future.transaction.Transaction`

Represents a transaction that interacts with the application system.

Parameters

- **sender** (*str*) – address of the sender
- **sp** (*SuggestedParams*) – suggested params from algod
- **index** (*int*) – index of the application to call; 0 if creating a new application
- **on_complete** (*OnComplete*) – intEnum representing what app should do on completion
- **local_schema** (*StateSchema, optional*) – restricts what can be stored by created application; must be omitted if not creating an application
- **global_schema** (*StateSchema, optional*) – restricts what can be stored by created application; must be omitted if not creating an application
- **approval_program** (*bytes, optional*) – the program to run on transaction approval; must be omitted if not creating or updating an application
- **clear_program** (*bytes, optional*) – the program to run when state is being cleared; must be omitted if not creating or updating an application
- **app_args** (*list[bytes], optional*) – list of arguments to the application, each argument itself a buf
- **accounts** (*list[string], optional*) – list of additional accounts involved in call
- **foreign_apps** (*list[int], optional*) – list of other applications (identified by index) involved in call
- **foreign_assets** (*list[int], optional*) – list of assets involved in call
- **extra_pages** (*int, optional*) – additional program space for supporting larger programs. A page is 1024 bytes.

sender

Type *str*

fee

Type *int*

first_valid_round

Type *int*

last_valid_round

Type *int*

genesis_hash

```

        Type str
index
        Type int
on_complete
        Type int
local_schema
        Type StateSchema
global_schema
        Type StateSchema
approval_program
        Type bytes
clear_program
        Type bytes
app_args
        Type list[bytes]
accounts
        Type list[str]
foreign_apps
        Type list[int]
foreign_assets
        Type list[int]
extra_pages
        Type int
static state_schema (schema)
    Confirm the argument is a StateSchema, or false which is coerced to None
static teal_bytes (teal)
    Confirm the argument is bytes-like, or false which is coerced to None
static bytes_list (lst)
    Confirm or coerce list elements to bytes. Return None for empty/false lst.
static int_list (lst)
    Confirm or coerce list elements to int. Return None for empty/false lst.
dictify ()
class ApplicationCreateTxn (sender, sp, on_complete, approval_program, clear_program,
                           global_schema, local_schema, app_args=None, accounts=None,
                           foreign_apps=None, foreign_assets=None, note=None, lease=None,
                           rekey_to=None, extra_pages=0)
    Bases: algosdk.future.transaction.ApplicationCallTxn
    Make a transaction that will create an application.

    Parameters

```

- **sender** (*str*) – address of sender
- **sp** (*SuggestedParams*) – contains information such as fee and genesis hash
- **on_complete** (*OnComplete*) – what application should do once the program is done being run
- **approval_program** (*bytes*) – the compiled TEAL that approves a transaction
- **clear_program** (*bytes*) – the compiled TEAL that runs when clearing state
- **global_schema** (*StateSchema*) – restricts the number of ints and byte slices in the global state
- **local_schema** (*StateSchema*) – restricts the number of ints and byte slices in the per-user local state
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction
- **extra_pages** (*int*, *optional*) – provides extra program size

See `ApplicationCallTxn`

```
class ApplicationUpdateTxn (sender, sp, index, approval_program, clear_program, app_args=None,
                           accounts=None, foreign_apps=None, foreign_assets=None,
                           note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.ApplicationCallTxn`

Make a transaction that will change an application's approval and clear programs.

Parameters

- **sender** (*str*) – address of sender
- **sp** (*SuggestedParams*) – contains information such as fee and genesis hash
- **index** (*int*) – the application to update
- **approval_program** (*bytes*) – the new compiled TEAL that approves a transaction
- **clear_program** (*bytes*) – the new compiled TEAL that runs when clearing state
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field

- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `ApplicationCallTxn`

```
class ApplicationDeleteTxn(sender, sp, index, app_args=None, accounts=None, foreign_apps=None, foreign_assets=None, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.ApplicationCallTxn`

Make a transaction that will delete an application

Parameters

- **sender** (*str*) – address of sender
- **sp** (`SuggestedParams`) – contains information such as fee and genesis hash
- **index** (*int*) – the application to update
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `ApplicationCallTxn`

```
class ApplicationOptInTxn(sender, sp, index, app_args=None, accounts=None, foreign_apps=None, foreign_assets=None, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.ApplicationCallTxn`

Make a transaction that will opt in to an application

Parameters

- **sender** (*str*) – address of sender
- **sp** (`SuggestedParams`) – contains information such as fee and genesis hash
- **index** (*int*) – the application to update
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `ApplicationCallTxn`

```
class ApplicationCloseOutTxn(sender, sp, index, app_args=None, accounts=None, foreign_apps=None, foreign_assets=None, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.ApplicationCallTxn`

Make a transaction that will close out a user's state in an application

Parameters

- **sender** (*str*) – address of sender
- **sp** (`SuggestedParams`) – contains information such as fee and genesis hash
- **index** (*int*) – the application to update
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `ApplicationCallTxn`

```
class ApplicationClearStateTxn(sender, sp, index, app_args=None, accounts=None, foreign_apps=None, foreign_assets=None, note=None, lease=None, rekey_to=None)
```

Bases: `algosdk.future.transaction.ApplicationCallTxn`

Make a transaction that will clear a user's state for an application

Parameters

- **sender** (*str*) – address of sender
- **sp** (`SuggestedParams`) – contains information such as fee and genesis hash
- **index** (*int*) – the application to update
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See `ApplicationCallTxn`

```
class ApplicationNoOpTxn (sender, sp, index, app_args=None, accounts=None, foreign_apps=None,
                          foreign_assets=None, note=None, lease=None, rekey_to=None)
Bases: algosdk.future.transaction.ApplicationCallTxn
```

Make a transaction that will do nothing on application completion In other words, just call the application

Parameters

- **sender** (*str*) – address of sender
- **sp** (*SuggestedParams*) – contains information such as fee and genesis hash
- **index** (*int*) – the application to update
- **app_args** (*list[bytes]*, *optional*) – any additional arguments to the application
- **accounts** (*list[str]*, *optional*) – any additional accounts to supply to the application
- **foreign_apps** (*list[int]*, *optional*) – any other apps used by the application, identified by app index
- **foreign_assets** (*list[int]*, *optional*) – list of assets involved in call
- **note** (*bytes*, *optional*) – transaction note field
- **lease** (*bytes*, *optional*) – transaction lease field
- **rekey_to** (*str*, *optional*) – rekey-to field, see Transaction

See *ApplicationCallTxn*

```
class SignedTransaction (transaction, signature, authorizing_address=None)
Bases: object
```

Represents a signed transaction.

Parameters

- **transaction** (*Transaction*) – transaction that was signed
- **signature** (*str*) – signature of a single address
- **authorizing_address** (*str*, *optional*) – the address authorizing the signed transaction, if different from sender

transaction

Type *Transaction*

signature

Type *str*

authorizing_address

Type *str*

get_txid()

Get the transaction's ID.

Returns transaction ID

Return type *str*

dictify()

static undictify(d)

class MultisigTransaction (*transaction: algosdk.future.transaction.Transaction, multisig: algosdk.future.transaction.Multisig*)

Bases: object

Represents a signed transaction.

Parameters

- **transaction** (*Transaction*) – transaction that was signed
- **multisig** (*Multisig*) – multisig account and signatures

transaction

Type *Transaction*

multisig

Type *Multisig*

auth_addr

Type str, optional

sign (*private_key*)

Sign the multisig transaction.

Parameters **private_key** (*str*) – private key of signing account

Note: A new signature will replace the old if there is already a signature for the address. To sign another transaction, you can either overwrite the signatures in the current Multisig, or you can use Multisig.get_multisig_account() to get a new multisig object with the same addresses.

get_txid ()

Get the transaction's ID.

Returns transaction ID

Return type str

dictify ()

static undictify (*d*)

static merge (*part_stxs: List[MultisigTransaction]*) → algosdk.future.transaction.MultisigTransaction

Merge partially signed multisig transactions.

Parameters **part_stxs** (*MultisigTransaction[]*) – list of partially signed multisig transactions

Returns multisig transaction containing signatures

Return type *MultisigTransaction*

Note: Only use this if you are given two partially signed multisig transactions. To append a signature to a multisig transaction, just use MultisigTransaction.sign()

class Multisig (*version, threshold, addresses*)

Bases: object

Represents a multisig account and signatures.

Parameters

- **version** (*int*) – currently, the version is 1
- **threshold** (*int*) – how many signatures are necessary
- **addresses** (*str[]*) – addresses in the multisig account

version

Type *int*

threshold

Type *int*

subsigs

Type *MultisigSubsig[]*

validate ()

Check if the multisig account is valid.

address ()

Return the multisig account address.

verify (*message*)

Verify that the multisig is valid for the message.

dictify ()

json_dictify ()

static undictify (*d*)

get_multisig_account ()

Return a Multisig object without signatures.

get_public_keys ()

Return the base32 encoded addresses for the multisig account.

class MultisigSubsig (*public_key, signature=None*)

Bases: *object*

public_key

Type *bytes*

signature

Type *bytes*

dictify ()

json_dictify ()

static undictify (*d*)

class LogicSig (*program, args=None*)

Bases: *object*

Represents a logic signature

NOTE: This type is deprecated. Use LogicSigAccount instead.

Parameters

- **logic** (*bytes*) – compiled program
- **args** (*list[bytes]*) – args are not signed, but are checked by logic

```

logic
    Type bytes

sig
    Type bytes

msig
    Type Multisig

args
    Type list[bytes]

dictify()

static undictify(d)

verify(public_key)
    Verifies LogicSig against the transaction's sender address

    Parameters public_key (bytes) – sender address

    Returns true if the signature is valid (the sender address matches the logic hash or the signature
        is valid against the sender address), false otherwise

    Return type bool

address()
    Compute hash of the logic sig program (that is the same as escrow account address) as string address

    Returns program address

    Return type str

static sign_program(program, private_key)

static single_sig_multisig(program, private_key, multisig)

sign(private_key, multisig=None)
    Creates signature (if no pk provided) or multi signature

    Parameters
        • private_key (str) – private key of signing account
        • multisig (Multisig) – optional multisig account without signatures to sign with

    Raises
        • InvalidSecretKeyError – if no matching private key in multisig object
        • LogicSigOverspecifiedSignature – if the opposite signature type has already
            been provided

append_to_multisig(private_key)
    Appends a signature to multi signature

    Parameters private_key (str) – private key of signing account

    Raises InvalidSecretKeyError – if no matching private key in multisig object

class LogicSigAccount (program: bytes, args: List[bytes] = None)
    Bases: object

    Represents an account that can sign with a LogicSig program.
    
```

dictify()

static undictify(d)

is_delegated() → bool

Check if this LogicSigAccount has been delegated to another account with a signature.

Returns True if and only if this is a delegated LogicSigAccount.

Return type bool

verify() → bool

Verifies the LogicSig's program and signatures.

Returns

True if and only if the LogicSig program and signatures are valid.

Return type bool

address() → str

Get the address of this LogicSigAccount.

If the LogicSig is delegated to another account, this will return the address of that account.

If the LogicSig is not delegated to another account, this will return an escrow address that is the hash of the LogicSig's program code.

sign_multisig(multisig: algosdk.future.transaction.Multisig, private_key: str) → None

Turns this LogicSigAccount into a delegated LogicSig.

This type of LogicSig has the authority to sign transactions on behalf of another account, called the delegating account. Use this function if the delegating account is a multisig account.

Parameters

- **multisig** (Multisig) – The multisig delegating account
- **private_key** (str) – The private key of one of the members of the delegating multisig account. Use *append_to_multisig* to add additional signatures from other members.

Raises

- InvalidSecretKeyError – if no matching private key in multisig object
- LogicSigOverspecifiedSignature – if this LogicSigAccount has already been signed with a single private key.

append_to_multisig(private_key: str) → None

Adds an additional signature from a member of the delegating multisig account.

Parameters **private_key** (str) – The private key of one of the members of the delegating multisig account.

Raises InvalidSecretKeyError – if no matching private key in multisig object

sign(private_key: str) → None

Turns this LogicSigAccount into a delegated LogicSig.

This type of LogicSig has the authority to sign transactions on behalf of another account, called the delegating account. If the delegating account is a multisig account, use *sign_multisig* instead.

Parameters **private_key** (str) – The private key of the delegating account.

Raises LogicSigOverspecifiedSignature – if this LogicSigAccount has already been signed by a multisig account.

```
class LogicSigTransaction (transaction: algosdk.future.transaction.Transaction,
                             lsig: Union[algosdk.future.transaction.LogicSig,
                                           algosdk.future.transaction.LogicSigAccount])
```

Bases: object

Represents a logic signed transaction

Parameters

- **transaction** (*Transaction*) –
- **lsig** (*LogicSig* or *LogicSigAccount*) –

transaction

Type *Transaction*

lsig

Type *LogicSig*

auth_addr

Type str, optional

verify () → bool

Verify the LogicSig used to sign the transaction

Returns true if the signature is valid, false otherwise

Return type bool

get_txid ()

Get the transaction's ID.

Returns transaction ID

Return type str

dictify ()

static undictify (d)

write_to_file (txns, path, overwrite=True)

Write signed or unsigned transactions to a file.

Parameters

- **txns** (*Transaction*[], *SignedTransaction*[], or *MultisigTransaction*[]) – can be a mix of the three
- **path** (str) – file to write to
- **overwrite** (bool) – whether or not to overwrite what's already in the file; if False, transactions will be appended to the file

Returns true if the transactions have been written to the file

Return type bool

retrieve_from_file (path)

Retrieve signed or unsigned transactions from a file.

Parameters **path** (str) – file to read from

Returns can be a mix of the three

Return type *Transaction*[], *SignedTransaction*[], or *MultisigTransaction*[]

```
class TxGroup (txns)
    Bases: object

    dictify ()

    static undictify (d)

calculate_group_id (txns)
    Calculate group id for a given list of unsigned transactions

    Parameters txns (list) – list of unsigned transactions

    Returns checksum value representing the group id

    Return type bytes

assign_group_id (txns, address=None)
    Assign group id to a given list of unsigned transactions

    Parameters

    • txns (list) – list of unsigned transactions

    • address (str) – optional sender address specifying which transaction return

    Returns list of unsigned transactions with group property set

    Return type txns (list)

wait_for_confirmation (algod_client, txid, wait_rounds=0, **kwargs)
    Block until a pending transaction is confirmed by the network.

    Parameters

    • algod_client (algod.AlgodClient) – Instance of the algod client

    • txid (str) – transaction ID

    • wait_rounds (int, optional) – The number of rounds to block for before exiting
      with an Exception. If not supplied, there is no timeout.
```

8.1.8 kmd

```
class KMDClient (kmd_token, kmd_address)
    Bases: object

    Client class for kmd. Handles all kmd requests.

    Parameters

    • kmd_token (str) – kmd API token

    • kmd_address (str) – kmd address

kmd_token
    Type str

kmd_address
    Type str

kmd_request (method, requrl, params=None, data=None)
    Execute a given request.

    Parameters
```

- **method** (*str*) – request method
- **requrl** (*str*) – url for the request
- **params** (*dict*, *optional*) – parameters for the request
- **data** (*dict*, *optional*) – data in the body of the request

Returns loaded from json response body

Return type dict

versions ()

Get kmd versions.

Returns list of versions

Return type str[]

list_wallets ()

List all wallets hosted on node.

Returns list of dictionaries containing wallet information

Return type dict[]

create_wallet (*name*, *pswd*, *driver_name*=*'sqlite'*, *master_deriv_key*=*None*)

Create a new wallet.

Parameters

- **name** (*str*) – wallet name
- **pswd** (*str*) – wallet password
- **driver_name** (*str*, *optional*) – name of the driver
- **master_deriv_key** (*str*, *optional*) – if recovering a wallet, include

Returns dictionary containing wallet information

Return type dict

get_wallet (*handle*)

Get wallet information.

Parameters **handle** (*str*) – wallet handle token

Returns dictionary containing wallet handle and wallet information

Return type dict

init_wallet_handle (*id*, *password*)

Initialize a handle for the wallet.

Parameters

- **id** (*str*) – wallet ID
- **password** (*str*) – wallet password

Returns wallet handle token

Return type str

release_wallet_handle (*handle*)

Deactivate the handle for the wallet.

Args: handle (str): wallet handle token

Returns True if the handle has been deactivated

Return type bool

renew_wallet_handle (*handle*)

Renew the wallet handle.

Parameters **handle** (*str*) – wallet handle token

Returns dictionary containing wallet handle and wallet information

Return type dict

rename_wallet (*id*, *password*, *new_name*)

Rename the wallet.

Parameters

- **id** (*str*) – wallet ID
- **password** (*str*) – wallet password
- **new_name** (*str*) – new name for the wallet

Returns dictionary containing wallet information

Return type dict

export_master_derivation_key (*handle*, *password*)

Get the wallet's master derivation key.

Parameters

- **handle** (*str*) – wallet handle token
- **password** (*str*) – wallet password

Returns master derivation key

Return type str

import_key (*handle*, *private_key*)

Import an account into the wallet.

Parameters

- **handle** (*str*) – wallet handle token
- **private_key** (*str*) – private key of account to be imported

Returns base32 address of the account

Return type str

export_key (*handle*, *password*, *address*)

Return an account private key.

Parameters

- **handle** (*str*) – wallet handle token
- **password** (*str*) – wallet password
- **address** (*str*) – base32 address of the account

Returns private key

Return type str

generate_key (*handle*, *display_mnemonic=True*)

Generate a key in the wallet.

Parameters

- **handle** (*str*) – wallet handle token
- **display_mnemonic** (*bool*, *optional*) – whether or not the mnemonic should be displayed

Returns base32 address of the generated account

Return type *str*

delete_key (*handle*, *password*, *address*)

Delete a key in the wallet.

Parameters

- **handle** (*str*) – wallet handle token
- **password** (*str*) – wallet password
- **address** (*str*) – base32 address of account to be deleted

Returns True if the account has been deleted

Return type *bool*

list_keys (*handle*)

List all keys in the wallet.

Parameters **handle** (*str*) – wallet handle token

Returns list of base32 addresses in the wallet

Return type *str[]*

sign_transaction (*handle*, *password*, *txn*, *signing_address=None*)

Sign a transaction.

Parameters

- **handle** (*str*) – wallet handle token
- **password** (*str*) – wallet password
- **txn** (*Transaction*) – transaction to be signed
- **signing_address** (*str*, *optional*) – sign the transaction with SK corresponding to base32 *signing_address*, if provided, rather than SK corresponding to sender

Returns signed transaction with signature of sender

Return type *SignedTransaction*

list_multisig (*handle*)

List all multisig accounts in the wallet.

Parameters **handle** (*str*) – wallet handle token

Returns list of base32 multisig account addresses

Return type *str[]*

import_multisig (*handle*, *multisig*)

Import a multisig account into the wallet.

Parameters

- **handle** (*str*) – wallet handle token
- **multisig** (*Multisig*) – multisig account to be imported

Returns base32 address of the imported multisig account

Return type *str*

export_multisig (*handle, address*)

Export a multisig account.

Parameters

- **handle** (*str*) – wallet token handle
- **address** (*str*) – base32 address of the multisig account

Returns multisig object corresponding to the address

Return type *Multisig*

delete_multisig (*handle, password, address*)

Delete a multisig account.

Parameters

- **handle** (*str*) – wallet handle token
- **password** (*str*) – wallet password
- **address** (*str*) – base32 address of the multisig account to delete

Returns True if the multisig account has been deleted

Return type *bool*

sign_multisig_transaction (*handle, password, public_key, mtx*)

Sign a multisig transaction for the given public key.

Parameters

- **handle** (*str*) – wallet handle token
- **password** (*str*) – wallet password
- **public_key** (*str*) – base32 address that is signing the transaction
- **mtx** (*MultisigTransaction*) – multisig transaction containing unsigned or partially signed multisig

Returns multisig transaction with added signature

Return type *MultisigTransaction*

8.1.9 logic

check_program (*program, args=None*)

Performs program checking for max length and cost

Parameters

- **program** (*bytes*) – compiled program
- **args** (*list[bytes]*) – args are not signed, but are checked by logic

Returns True on success

Return type *bool*

Raises `InvalidProgram` – on error

```
read_program (program, args=None)
check_int_const_block (program, pc)
read_int_const_block (program, pc)
check_byte_const_block (program, pc)
read_byte_const_block (program, pc)
check_push_int_block (program, pc)
read_push_int_block (program, pc)
check_push_byte_block (program, pc)
read_push_byte_block (program, pc)
parse_uvarint (buf)
```

address (*program*)

Return the address of the program.

Parameters **program** (*bytes*) – compiled program

Returns program address

Return type `str`

teal_sign (*private_key*, *data*, *contract_addr*)

Return the signature suitable for ed25519verify TEAL opcode

Parameters

- **private_key** (*str*) – private key to sign with
- **data** (*bytes*) – data to sign
- **contract_addr** (*str*) – program hash (contract address) to sign for

Returns signature

Return type `bytes`

teal_sign_from_program (*private_key*, *data*, *program*)

Return the signature suitable for ed25519verify TEAL opcode

Parameters

- **private_key** (*str*) – private key to sign with
- **data** (*bytes*) – data to sign
- **program** (*bytes*) – program to sign for

Returns signature

Return type `bytes`

get_application_address (*appID: int*) → `str`

Return the escrow address of an application.

Parameters **appID** (*int*) – The ID of the application.

Returns The address corresponding to that application’s escrow account.

Return type `str`

8.1.10 mnemonic

from_master_derivation_key (*key*)

Return the mnemonic for the master derivation key.

Parameters **key** (*str*) – master derivation key in base64

Returns mnemonic

Return type str

to_master_derivation_key (*mnemonic*)

Return the master derivation key for the mnemonic.

Parameters **mnemonic** (*str*) – mnemonic of the master derivation key

Returns master derivation key in base64

Return type str

from_private_key (*key*)

Return the mnemonic for the private key.

Parameters **key** (*str*) – private key in base64

Returns mnemonic

Return type str

to_private_key (*mnemonic*)

Return the private key for the mnemonic.

Parameters **mnemonic** (*str*) – mnemonic of the private key

Returns private key in base64

Return type str

to_public_key (*mnemonic*)

Return the public key for the mnemonic. This method returns the Algorand address and will be deprecated, use `account.address_from_private_key` instead.

Parameters **mnemonic** (*str*) – mnemonic of the private key

Returns public key in base32

Return type str

8.1.11 template

class Template

Bases: object

get_address ()

Return the address of the contract.

get_program ()

class Split (*owner: str, receiver_1: str, receiver_2: str, rat_1: int, rat_2: int, expiry_round: int, min_pay: int, max_fee: int*)

Bases: `algosdk.template.Template`

Split allows locking algos in an account which allows transferring to two predefined addresses in a specified ratio such that for the given `ratn` and `ratd` parameters we have:

`first_recipient_amount * rat_2 == second_recipient_amount * rat_1`

Split also has an expiry round, after which the owner can transfer back the funds.

Parameters

- **owner** (*str*) – an address that can receive the funds after the expiry round
- **receiver_1** (*str*) – first address to receive funds
- **receiver_2** (*str*) – second address to receive funds
- **rat_1** (*int*) – how much receiver_1 receives (proportionally)
- **rat_2** (*int*) – how much receiver_2 receives (proportionally)
- **expiry_round** (*int*) – the round on which the funds can be transferred back to owner
- **min_pay** (*int*) – the minimum number of microalgos that can be transferred from the account to receiver_1
- **max_fee** (*int*) – half the maximum fee that can be paid to the network by the account

get_program()

Return a byte array to be used in LogicSig.

static get_split_funds_transaction (*contract*, *amount: int*, *fee: int*, *first_valid*, *last_valid*, *gh*)

Return a group transactions array which transfers funds according to the contract's ratio. :param amount: total amount to be transferred :type amount: int :param fee: fee per byte :type fee: int :param first_valid: first round where the transactions are valid :type first_valid: int :param gh: genesis hash in base64 :type gh: str

Returns Transaction[]

class HTLC (*owner: str*, *receiver: str*, *hash_function: str*, *hash_image: str*, *expiry_round: int*, *max_fee: int*)

Bases: `algosdk.template.Template`

Hash Time Locked Contract allows a user to receive the Algo prior to a deadline (in terms of a round) by proving knowledge of a special value or to forfeit the ability to claim, returning it to the payer.

This contract is usually used to perform cross-chained atomic swaps.

More formally, algos can be transferred under only two circumstances:

1. To receiver if `hash_function(arg_0) = hash_value`
2. To owner if `txn.FirstValid > expiry_round`

Parameters

- **owner** (*str*) – an address that can receive the asset after the expiry round
- **receiver** (*str*) – address to receive Algos
- **hash_function** (*str*) – the hash function to be used (must be either sha256 or keccak256)
- **hash_image** (*str*) – the hash image in base64
- **expiry_round** (*int*) – the round on which the assets can be transferred back to owner
- **max_fee** (*int*) – the maximum fee that can be paid to the network by the account

get_program()

Return a byte array to be used in LogicSig.

static get_transaction (*contract*, *preimage*, *first_valid*, *last_valid*, *gh*, *fee*)

Return a transaction which will release funds if a matching preimage is used.

Parameters

- **contract** (*bytes*) – the contract containing information, should be received from payer
- **preimage** (*str*) – the preimage of the hash in base64
- **first_valid** (*int*) – first valid round for the transactions
- **last_valid** (*int*) – last valid round for the transactions
- **gh** (*str*) – genesis hash in base64
- **fee** (*int*) – fee per byte

Returns

transaction to claim algos from contract account

Return type *LogicSigTransaction*

class DynamicFee (*receiver: str*, *amount: int*, *first_valid: int*, *last_valid: int = None*,
close_remainder_address: str = None)

Bases: *algosdk.template.Template*

DynamicFee contract allows you to create a transaction without specifying the fee. The fee will be determined at the moment of transfer.

Parameters

- **receiver** (*str*) – address to receive the assets
- **amount** (*int*) – amount of assets to transfer
- **first_valid** (*int*) – first valid round for the transaction
- **last_valid** (*int*, *optional*) – last valid round for the transaction (defaults to first_valid + 1000)
- **close_remainder_address** (*str*, *optional*) – the address that receives the remainder

get_program ()

Return a byte array to be used in LogicSig.

static get_transactions (*txn*, *lsig*, *private_key*, *fee*)

Create and sign the secondary dynamic fee transaction, update transaction fields, and sign as the fee payer; return both transactions.

Parameters

- **txn** (*Transaction*) – main transaction from payer
- **lsig** (*LogicSig*) – signed logic received from payer
- **private_key** (*str*) – the secret key of the account that pays the fee in base64
- **fee** (*int*) – fee per byte, for both transactions

sign_dynamic_fee (*private_key*, *gh*)

Return the main transaction and signed logic needed to complete the transfer. These should be sent to the fee payer, who can use get_transactions() to update fields and create the auxiliary transaction.

Parameters

- **private_key** (*bytes*) – the secret key to sign the contract in base64

- **gh** (*str*) – genesis hash, in base64

class PeriodicPayment (*receiver: str, amount: int, withdrawing_window: int, period: int, max_fee: int, timeout: int*)

Bases: *algosdk.template.Template*

PeriodicPayment contract enables creating an account which allows the withdrawal of a fixed amount of assets every fixed number of rounds to a specific Algorand Address. In addition, the contract allows to add timeout, after which the address can withdraw the rest of the assets.

Parameters

- **receiver** (*str*) – address to receive the assets
- **amount** (*int*) – amount of assets to transfer at every cycle
- **withdrawing_window** (*int*) – the number of blocks in which the user can withdraw the asset once the period start (must be < 1000)
- **period** (*int*) – how often the address can withdraw assets (in rounds)
- **fee** (*int*) – maximum fee per transaction
- **timeout** (*int*) – a round in which the receiver can withdraw the rest of the funds after

get_program ()

Return a byte array to be used in LogicSig.

static get_withdrawal_transaction (*contract, first_valid, gh, fee*)

Return the withdrawal transaction to be sent to the network.

Parameters

- **contract** (*bytes*) – contract containing information, should be received from payer
- **first_valid** (*int*) – first round the transaction should be valid; this must be a multiple of self.period
- **gh** (*str*) – genesis hash in base64
- **fee** (*int*) – fee per byte

class LimitOrder (*owner: str, asset_id: int, ratn: int, ratd: int, expiry_round: int, max_fee: int, min_trade: int*)

Bases: *algosdk.template.Template*

Limit Order allows to trade Algos for other assets given a specific ratio; for N Algos, swap for Rate * N Assets.

Parameters

- **owner** (*str*) – an address that can receive the asset after the expiry round
- **asset_id** (*int*) – asset to be transferred
- **ratn** (*int*) – the numerator of the exchange rate
- **ratd** (*int*) – the denominator of the exchange rate
- **expiry_round** (*int*) – the round on which the assets can be transferred back to owner
- **max_fee** (*int*) – the maximum fee that can be paid to the network by the account
- **min_trade** (*int*) – the minimum amount (of Algos) to be traded away

get_program ()

Return a byte array to be used in LogicSig.

```
static get_swap_assets_transactions (contract: bytes, asset_amount: int, microalgo_amount: int, private_key: str, first_valid, last_valid, gh, fee)
```

Return a group transactions array which transfer funds according to the contract's ratio.

Parameters

- **contract** (*bytes*) – the contract containing information, should be received from payer
- **asset_amount** (*int*) – the amount of assets to be sent
- **microalgo_amount** (*int*) – the amount of microalgos to be received
- **private_key** (*str*) – the secret key to sign the contract
- **first_valid** (*int*) – first valid round for the transactions
- **last_valid** (*int*) – last valid round for the transactions
- **gh** (*str*) – genesis hash in base64
- **fee** (*int*) – fee per byte

```
put_uvarint (buf, x)
```

```
inject (orig, offsets, values, values_types)
```

8.1.12 transaction

```
class Transaction (sender, fee, first, last, note, gen, gh, lease, txn_type, rekey_to)
```

Bases: object

Superclass for various transaction types.

```
get_txid()
```

Get the transaction's ID.

Returns transaction ID

Return type str

```
sign (private_key)
```

Sign the transaction with a private key.

Parameters **private_key** (*str*) – the private key of the signing account

Returns signed transaction with the signature

Return type *SignedTransaction*

```
raw_sign (private_key)
```

Sign the transaction.

Parameters **private_key** (*str*) – the private key of the signing account

Returns signature

Return type bytes

```
estimate_size()
```

```
dictify()
```

```
static undictify (d)
```

```
class PaymentTxn(sender, fee, first, last, gh, receiver, amt, close_remainder_to=None, note=None,  
                 gen=None, flat_fee=False, lease=None, rekey_to=None)  
    Bases: algosdk.transaction.Transaction
```

Represents a payment transaction.

Parameters

- **sender** (*str*) – address of the sender
- **fee** (*int*) – transaction fee (per byte if *flat_fee* is false). When *flat_fee* is true, fee may fall to zero but a group of *N* atomic transactions must still have a fee of at least *N***min_txn_fee*.
- **first** (*int*) – first round for which the transaction is valid
- **last** (*int*) – last round for which the transaction is valid
- **gh** (*str*) – *genesis_hash*
- **receiver** (*str*) – address of the receiver
- **amt** (*int*) – amount in microAlgos to be sent
- **close_remainder_to** (*str, optional*) – if nonempty, account will be closed and remaining algos will be sent to this address
- **note** (*bytes, optional*) – arbitrary optional bytes
- **gen** (*str, optional*) – *genesis_id*
- **flat_fee** (*bool, optional*) – whether the specified fee is a flat fee
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str, optional*) – additionally rekey the sender to this address

sender

Type *str*

fee

Type *int*

first_valid_round

Type *int*

last_valid_round

Type *int*

note

Type *bytes*

genesis_id

Type *str*

genesis_hash

Type *str*

group

Type *bytes*

receiver


```

        Type str
    amt
        Type int
    close_remainder_to
        Type str
    type
        Type str
    lease
        Type byte[32]
    rekey_to
        Type str
    dictify()
class KeyregTxn(sender, fee, first, last, gh, votekey, selkey, votefst, votelst, votekd, note=None,
                gen=None, flat_fee=False, lease=None, rekey_to=None)
Bases: algosdk.transaction.Transaction

```

Represents a key registration transaction.

Parameters

- **sender** (*str*) – address of sender
- **fee** (*int*) – transaction fee (per byte if *flat_fee* is false). When *flat_fee* is true, fee may fall to zero but a group of *N* atomic transactions must still have a fee of at least $N * \text{min_txn_fee}$.
- **first** (*int*) – first round for which the transaction is valid
- **last** (*int*) – last round for which the transaction is valid
- **gh** (*str*) – genesis_hash
- **votekey** (*str*) – participation public key
- **selkey** (*str*) – VRF public key
- **votefst** (*int*) – first round to vote
- **votelst** (*int*) – last round to vote
- **votekd** (*int*) – vote key dilution
- **note** (*bytes*, *optional*) – arbitrary optional bytes
- **gen** (*str*, *optional*) – genesis_id
- **flat_fee** (*bool*, *optional*) – whether the specified fee is a flat fee
- **lease** (*byte[32]*, *optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction's valid rounds
- **rekey_to** (*str*, *optional*) – additionally rekey the sender to this address

sender

Type *str*

fee

Type *int*

first_valid_round

Type int

last_valid_round

Type int

note

Type bytes

genesis_id

Type str

genesis_hash

Type str

group

Type bytes

votepk

Type str

selkey

Type str

votefst

Type int

votelst

Type int

votekd

Type int

type

Type str

lease

Type byte[32]

rekey_to

Type str

dictify()

```
class AssetConfigTxn(sender, fee, first, last, gh, index=None, total=None, default_frozen=None,
                    unit_name=None, asset_name=None, manager=None, reserve=None,
                    freeze=None, clawback=None, url=None, metadata_hash=None, note=None,
                    gen=None, flat_fee=False, lease=None, strict_empty_address_check=True,
                    decimals=0, rekey_to=None)
```

Bases: *algosdk.transaction.Transaction*

Represents a transaction for asset creation, reconfiguration, or destruction.

To create an asset, include the following: total, default_frozen, unit_name, asset_name, manager, reserve, freeze, clawback, url, metadata, decimals

To destroy an asset, include the following: `index`, `strict_empty_address_check` (set to `False`)

To update asset configuration, include the following: `index`, `manager`, `reserve`, `freeze`, `clawback`, `strict_empty_address_check` (optional)

Parameters

- **`sender`** (*str*) – address of the sender
- **`fee`** (*int*) – transaction fee (per byte if `flat_fee` is `false`). When `flat_fee` is `true`, fee may fall to zero but a group of `N` atomic transactions must still have a fee of at least `N*min_txn_fee`.
- **`first`** (*int*) – first round for which the transaction is valid
- **`last`** (*int*) – last round for which the transaction is valid
- **`gh`** (*str*) – `genesis_hash`
- **`index`** (*int*, *optional*) – index of the asset
- **`total`** (*int*, *optional*) – total number of base units of this asset created
- **`default_frozen`** (*bool*, *optional*) – whether slots for this asset in user accounts are frozen by default
- **`unit_name`** (*str*, *optional*) – hint for the name of a unit of this asset
- **`asset_name`** (*str*, *optional*) – hint for the name of the asset
- **`manager`** (*str*, *optional*) – address allowed to change nonzero addresses for this asset
- **`reserve`** (*str*, *optional*) – account whose holdings of this asset should be reported as “not minted”
- **`freeze`** (*str*, *optional*) – account allowed to change frozen state of holdings of this asset
- **`clawback`** (*str*, *optional*) – account allowed take units of this asset from any account
- **`url`** (*str*, *optional*) – a URL where more information about the asset can be retrieved
- **`metadata_hash`** (*byte[32]*, *optional*) – a commitment to some unspecified asset metadata (32 byte hash)
- **`note`** (*bytes*, *optional*) – arbitrary optional bytes
- **`gen`** (*str*, *optional*) – `genesis_id`
- **`flat_fee`** (*bool*, *optional*) – whether the specified fee is a flat fee
- **`lease`** (*byte[32]*, *optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **`strict_empty_address_check`** (*bool*, *optional*) – set this to `False` if you want to specify empty addresses. Otherwise, if this is left as `True` (the default), having empty addresses will raise an error, which will prevent accidentally removing admin access to assets or deleting the asset.
- **`decimals`** (*int*, *optional*) – number of digits to use for display after decimal. If set to 0, the asset is not divisible. If set to 1, the base unit of the asset is in tenths. Must be between 0 and 19, inclusive. Defaults to 0.
- **`rekey_to`** (*str*, *optional*) – additionally rekey the sender to this address

```
sender
    Type str
fee
    Type int
first_valid_round
    Type int
last_valid_round
    Type int
genesis_hash
    Type str
index
    Type int
total
    Type int
default_frozen
    Type bool
unit_name
    Type str
asset_name
    Type str
manager
    Type str
reserve
    Type str
freeze
    Type str
clawback
    Type str
url
    Type str
metadata_hash
    Type byte[32]
note
    Type bytes
genesis_id
    Type str
```

```

type
    Type str

lease
    Type byte[32]

decimals
    Type int

rekey_to
    Type str

dictify()

class AssetFreezeTxn(sender, fee, first, last, gh, index, target, new_freeze_state, note=None,
                       gen=None, flat_fee=False, lease=None, rekey_to=None)
    Bases: algosdk.transaction.Transaction

    Represents a transaction for freezing or unfreezing an account's asset holdings. Must be issued by the asset's
    freeze manager.

    Parameters

    • sender (str) – address of the sender, who must be the asset's freeze manager

    • fee (int) – transaction fee (per byte if flat_fee is false). When flat_fee is true, fee may fall
      to zero but a group of N atomic transactions must still have a fee of at least N*min_txn_fee.

    • first (int) – first round for which the transaction is valid

    • last (int) – last round for which the transaction is valid

    • gh (str) – genesis_hash

    • index (int) – index of the asset

    • target (str) – address having its assets frozen or unfrozen

    • new_freeze_state (bool) – true if the assets should be frozen, false if they should be
      transferrable

    • note (bytes, optional) – arbitrary optional bytes

    • gen (str, optional) – genesis_id

    • flat_fee (bool, optional) – whether the specified fee is a flat fee

    • lease (byte[32], optional) – specifies a lease, and no other transaction with the
      same sender and lease can be confirmed in this transaction's valid rounds

    • rekey_to (str, optional) – additionally rekey the sender to this address

sender
    Type str

fee
    Type int

first_valid_round
    Type int

last_valid_round

```

```
        Type int
genesis_hash
        Type str
index
        Type int
target
        Type str
new_freeze_state
        Type bool
note
        Type bytes
genesis_id
        Type str
type
        Type str
lease
        Type byte[32]
rekey_to
        Type str
dictify()
class AssetTransferTxn(sender, fee, first, last, gh, receiver, amt, index, close_assets_to=None, re-
    vocation_target=None, note=None, gen=None, flat_fee=False, lease=None,
    rekey_to=None)
```

Bases: *algosdk.transaction.Transaction*

Represents a transaction for asset transfer. To begin accepting an asset, supply the same address as both sender and receiver, and set amount to 0. To revoke an asset, set `revocation_target`, and issue the transaction from the asset's revocation manager account.

Parameters

- **sender** (*str*) – address of the sender
- **fee** (*int*) – transaction fee (per byte if `flat_fee` is false). When `flat_fee` is true, fee may fall to zero but a group of `N` atomic transactions must still have a fee of at least `N*min_txn_fee`.
- **first** (*int*) – first round for which the transaction is valid
- **last** (*int*) – last round for which the transaction is valid
- **gh** (*str*) – `genesis_hash`
- **receiver** (*str*) – address of the receiver
- **amt** (*int*) – amount of asset base units to send
- **index** (*int*) – index of the asset
- **close_assets_to** (*string, optional*) – send all of sender's remaining assets, after paying *amt* to receiver, to this address

- **revocation_target** (*string, optional*) – send assets from this address, rather than the sender’s address (can only be used by an asset’s revocation manager, also known as clawback)
- **note** (*bytes, optional*) – arbitrary optional bytes
- **gen** (*str, optional*) – genesis_id
- **flat_fee** (*bool, optional*) – whether the specified fee is a flat fee
- **lease** (*byte[32], optional*) – specifies a lease, and no other transaction with the same sender and lease can be confirmed in this transaction’s valid rounds
- **rekey_to** (*str, optional*) – additionally rekey the sender to this address

sender

Type str

fee

Type int

first_valid_round

Type int

last_valid_round

Type int

genesis_hash

Type str

index

Type int

amount

Type int

receiver

Type string

close_assets_to

Type string

revocation_target

Type string

note

Type bytes

genesis_id

Type str

type

Type str

lease

Type byte[32]

rekey_to

Type str

dictify()

class SignedTransaction (*transaction, signature, authorizing_address=None*)

Bases: object

Represents a signed transaction.

Parameters

- **transaction** (*Transaction*) – transaction that was signed
- **signature** (*str*) – signature of a single address
- **authorizing_address** (*str, optional*) – the address authorizing the signed transaction, if different from sender

transaction

Type *Transaction*

signature

Type str

authorizing_address

Type str

dictify()

static undictify (*d*)

class MultisigTransaction (*transaction, multisig*)

Bases: object

Represents a signed transaction.

Parameters

- **transaction** (*Transaction*) – transaction that was signed
- **multisig** (*Multisig*) – multisig account and signatures

transaction

Type *Transaction*

multisig

Type *Multisig*

sign (*private_key*)

Sign the multisig transaction.

Parameters **private_key** (*str*) – private key of signing account

Note: A new signature will replace the old if there is already a signature for the address. To sign another transaction, you can either overwrite the signatures in the current Multisig, or you can use Multisig.get_multisig_account() to get a new multisig object with the same addresses.

dictify()

static undictify (*d*)

static merge (*part_stxs*)

Merge partially signed multisig transactions.

Parameters **part_stxs** (*MultisigTransaction*[]) – list of partially signed multisig transactions

Returns multisig transaction containing signatures

Return type *MultisigTransaction*

Note: Only use this if you are given two partially signed multisig transactions. To append a signature to a multisig transaction, just use *MultisigTransaction.sign()*

class Multisig (*version, threshold, addresses*)

Bases: *object*

Represents a multisig account and signatures.

Parameters

- **version** (*int*) – currently, the version is 1
- **threshold** (*int*) – how many signatures are necessary
- **addresses** (*str*[]) – addresses in the multisig account

version

Type *int*

threshold

Type *int*

subsigs

Type *MultisigSubsig*[]

validate ()

Check if the multisig account is valid.

address ()

Return the multisig account address.

verify (*message*)

Verify that the multisig is valid for the message.

dictify ()

json_dictify ()

static undictify (*d*)

get_multisig_account ()

Return a Multisig object without signatures.

get_public_keys ()

Return the base32 encoded addresses for the multisig account.

class MultisigSubsig (*public_key, signature=None*)

Bases: *object*

public_key

Type *bytes*

signature

Type bytes

dictify()

json_dictify()

static undictify(d)

class LogicSig(*program, args=None*)

Bases: object

Represents a logic signature.

Parameters

- **logic** (*bytes*) – compiled program
- **args** (*list[bytes]*) – args are not signed, but are checked by logic

logic

Type bytes

sig

Type bytes

msig

Type *Multisig*

args

Type list[bytes]

dictify()

static undictify(d)

verify(*public_key*)

Verifies LogicSig against the transaction's sender address

Parameters **public_key** (*bytes*) – sender address

Returns true if the signature is valid (the sender address matches the logic hash or the signature is valid against the sender address), false otherwise

Return type bool

address()

Compute hash of the logic sig program (that is the same as escrow account address) as string address

Returns program address

Return type str

static sign_program(*program, private_key*)

static single_sig_multisig(*program, private_key, multisig*)

sign(*private_key, multisig=None*)

Creates signature (if no pk provided) or multi signature

Parameters

- **private_key** (*str*) – private key of signing account
- **multisig** (*Multisig*) – optional multisig account without signatures to sign with

Raises `InvalidSecretKeyError` – if no matching private key in multisig object

append_to_multisig (*private_key*)
 Appends a signature to multi signature

Parameters *private_key* (*str*) – private key of signing account

Raises `InvalidSecretKeyError` – if no matching private key in multisig object

class `LogicSigTransaction` (*transaction*, *lsig*)
 Bases: `object`
 Represents a logic signed transaction.

Parameters

- **transaction** (`Transaction`) –
- **lsig** (`LogicSig`) –

transaction
 Type `Transaction`

lsig
 Type `LogicSig`

verify ()
 Verify LogicSig against the transaction

Returns `true` if the signature is valid (the sender address matches the logic hash or the signature is valid against the sender address), `false` otherwise

Return type `bool`

dictify ()

static undictify (*d*)

write_to_file (*objs*, *path*, *overwrite=True*)
 Write signed or unsigned transactions to a file.

Parameters

- **txns** (`Transaction[]`, `SignedTransaction[]`, or `MultisigTransaction[]`) – can be a mix of the three
- **path** (*str*) – file to write to
- **overwrite** (*bool*) – whether or not to overwrite what’s already in the file; if `False`, transactions will be appended to the file

Returns `true` if the transactions have been written to the file

Return type `bool`

retrieve_from_file (*path*)
 Retrieve encoded objects from a file.

Parameters *path* (*str*) – file to read from

Returns list of objects

Return type `Object[]`

class `TxGroup` (*txns*)
 Bases: `object`

dictify()

static undictify(d)

calculate_group_id(txns)

Calculate group id for a given list of unsigned transactions

Parameters **txns** (*list*) – list of unsigned transactions

Returns checksum value representing the group id

Return type bytes

assign_group_id(txns, address=None)

Assign group id to a given list of unsigned transactions.

Parameters

- **txns** (*list*) – list of unsigned transactions
- **address** (*str*) – optional sender address specifying which transaction to return

Returns list of unsigned transactions with group property set

Return type txns (list)

8.1.13 util

microalgos_to_algos(microalgos)

Convert microalgos to algos.

Parameters **microalgos** (*int*) – how many microalgos

Returns how many algos

Return type int or decimal

algos_to_microalgos(algos)

Convert algos to microalgos.

Parameters **algos** (*int or decimal*) – how many algos

Returns how many microalgos

Return type int

sign_bytes(to_sign, private_key)

Sign arbitrary bytes after prepending with “MX” for domain separation.

Parameters **to_sign** (*bytes*) – bytes to sign

Returns base64 signature

Return type str

verify_bytes(message, signature, public_key)

Verify the signature of a message that was prepended with “MX” for domain separation.

Parameters

- **message** (*bytes*) – message that was signed, without prefix
- **signature** (*str*) – base64 signature
- **public_key** (*str*) – base32 address

Returns whether or not the signature is valid

Return type bool

build_headers_from (*kwarg_headers: Dict[str, Any], additional_headers: Dict[str, Any]*)

Build correct headers for *AlgodClient.algod_request*.

Parameters

- **kwarg_headers** (*Dict[str, Any]*) – headers passed through kwargs.
- **additional_headers** (*Dict[str, Any]*) – additional headers to pass to *AlgodClient.algod_request*

Returns final version of headers dictionary to be used for *AlgodClient.algod_request*

Return type Dict[str, any]

8.1.14 v2client

8.1.14.1 v2client.algod

class AlgodClient (*algod_token, algod_address, headers=None*)

Bases: object

Client class for algod. Handles all algod requests.

Parameters

- **algod_token** (*str*) – algod API token
- **algod_address** (*str*) – algod address
- **headers** (*dict, optional*) – extra header name/value for all requests

algod_token

Type str

algod_address

Type str

headers

Type dict

algod_request (*method, requrl, params=None, data=None, headers=None, response_format='json'*)

Execute a given request.

Parameters

- **method** (*str*) – request method
- **requrl** (*str*) – url for the request
- **params** (*dict, optional*) – parameters for the request
- **data** (*dict, optional*) – data in the body of the request
- **headers** (*dict, optional*) – additional header for request

Returns loaded from json response body

Return type dict

account_info (*address, **kwargs*)

Return account information.

Parameters **address** (*str*) – account public key

asset_info (*asset_id*, ***kwargs*)

Return information about a specific asset.

Parameters **asset_id** (*int*) – The ID of the asset to look up.

application_info (*application_id*, ***kwargs*)

Return information about a specific application.

Parameters **application_id** (*int*) – The ID of the application to look up.

pending_transactions_by_address (*address*, *limit=0*, *response_format='json'*, ***kwargs*)

Get the list of pending transactions by address, sorted by priority, in decreasing order, truncated at the end at MAX. If MAX = 0, returns all pending transactions.

Parameters

- **address** (*str*) – account public key
- **limit** (*int*, *optional*) – maximum number of transactions to return
- **response_format** (*str*) – the format in which the response is returned: either “json” or “msgpack”

block_info (*block=None*, *response_format='json'*, *round_num=None*, ***kwargs*)

Get the block for the given round.

Parameters

- **block** (*int*) – block number
- **response_format** (*str*) – the format in which the response is returned: either “json” or “msgpack”
- **round_num** (*int*, *optional*) – alias for block; specify one of these

ledger_supply (***kwargs*)

Return supply details for node’s ledger.

status (***kwargs*)

Return node status.

status_after_block (*block_num=None*, *round_num=None*, ***kwargs*)

Return node status immediately after blockNum.

Parameters

- **block_num** – block number
- **round_num** (*int*, *optional*) – alias for block_num; specify one of these

send_transaction (*txn*, ***kwargs*)

Broadcast a signed transaction object to the network.

Parameters

- **txn** (*SignedTransaction* or *MultisigTransaction*) – transaction to send
- **request_header** (*dict*, *optional*) – additional header for request

Returns transaction ID

Return type *str*

send_raw_transaction (*txn*, ***kwargs*)

Broadcast a signed transaction to the network.

Parameters

- **txn** (*str*) – transaction to send, encoded in base64
- **request_header** (*dict*, *optional*) – additional header for request

Returns transaction ID

Return type *str*

pending_transactions (*max_txns=0*, *response_format='json'*, ***kwargs*)

Return pending transactions.

Parameters

- **max_txns** (*int*) – maximum number of transactions to return; if max_txns is 0, return all pending transactions
- **response_format** (*str*) – the format in which the response is returned: either “json” or “msgpack”

pending_transaction_info (*transaction_id*, *response_format='json'*, ***kwargs*)

Return transaction information for a pending transaction.

Parameters

- **transaction_id** (*str*) – transaction ID
- **response_format** (*str*) – the format in which the response is returned: either “json” or “msgpack”

health (***kwargs*)

Return null if the node is running.

versions (***kwargs*)

Return algod versions.

send_transactions (*txns*, ***kwargs*)

Broadcast list of a signed transaction objects to the network.

Parameters

- **txns** (*SignedTransaction[]* or *MultisigTransaction[]*) – transactions to send
- **request_header** (*dict*, *optional*) – additional header for request

Returns first transaction ID

Return type *str*

suggested_params (***kwargs*)

Return suggested transaction parameters.

compile (*source*, ***kwargs*)

Compile TEAL source with remote algod.

Parameters

- **source** (*str*) – source to be compiled
- **request_header** (*dict*, *optional*) – additional header for request

Returns loaded from json response body. “result” property contains compiled bytes, “hash” - program hash (escrow address)

Return type *dict*

dryrun (*drr, **kwargs*)

Dryrun with remote algod.

Parameters

- **drr** (*obj*) – dryrun request object
- **request_header** (*dict, optional*) – additional header for request

Returns loaded from json response body

Return type dict

genesis (***kwargs*)

Returns the entire genesis file.

proof (*round_num, txid, **kwargs*)

Get the proof for a given transaction in a round.

Parameters

- **round_num** (*int*) – The round in which the transaction appears.
- **txid** (*str*) – The transaction ID for which to generate a proof.

8.1.14.2 v2client.indexer

class IndexerClient (*indexer_token, indexer_address, headers=None*)

Bases: object

Client class for indexer. Handles all indexer requests.

Parameters

- **indexer_token** (*str*) – indexer API token
- **indexer_address** (*str*) – indexer address
- **headers** (*dict, optional*) – extra header name/value for all requests

indexer_token

Type str

indexer_address

Type str

headers

Type dict

indexer_request (*method, requrl, params=None, data=None, headers=None*)

Execute a given request.

Parameters

- **method** (*str*) – request method
- **requrl** (*str*) – url for the request
- **params** (*dict, optional*) – parameters for the request
- **data** (*dict, optional*) – data in the body of the request
- **headers** (*dict, optional*) – additional header for request

Returns loaded from json response body

Return type dict

health (***kwargs*)

Return 200 and a simple status message if the node is running.

accounts (*asset_id=None, limit=None, next_page=None, min_balance=None, max_balance=None, block=None, auth_addr=None, application_id=None, round_num=None, include_all=False, **kwargs*)

Return accounts that match the search; microalgos are the default currency unless *asset_id* is specified, in which case the asset will be used.

Parameters

- **asset_id** (*int, optional*) – include accounts holding this asset
- **limit** (*int, optional*) – maximum number of results to return
- **next_page** (*str, optional*) – the next page of results; use the next token provided by the previous results
- **min_balance** (*int, optional*) – results should have an amount greater than this value (results with an amount equal to this value are excluded)
- **max_balance** (*int, optional*) – results should have an amount less than this value (results with an amount equal to this value are excluded)
- **block** (*int, optional*) – include results for the specified round; for performance reasons, this parameter may be disabled on some configurations
- **auth_addr** (*str, optional*) – Include accounts configured to use this spending key.
- **application_id** (*int, optional*) – results should filter on this application
- **round_num** (*int, optional*) – alias for block; only specify one of these
- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

asset_balances (*asset_id, limit=None, next_page=None, min_balance=None, max_balance=None, block=None, round_num=None, include_all=False, **kwargs*)

Return accounts that hold the asset; microalgos are the default currency unless *asset_id* is specified, in which case the asset will be used.

Parameters

- **asset_id** (*int*) – include accounts holding this asset
- **limit** (*int, optional*) – maximum number of results to return
- **next_page** (*str, optional*) – the next page of results; use the next token provided by the previous results
- **min_balance** (*int, optional*) – results should have an amount greater than this value (results with an amount equal to this value are excluded)
- **max_balance** (*int, optional*) – results should have an amount less than this value (results with an amount equal to this value are excluded)
- **block** (*int, optional*) – include results for the specified round; for performance reasons, this parameter may be disabled on some configurations
- **round_num** (*int, optional*) – alias for block; only specify one of these

- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

block_info (*block=None, round_num=None, **kwargs*)

Get the block for the given round.

Parameters

- **block** (*int, optional*) – block number
- **round_num** (*int, optional*) – alias for block; specify one of these

account_info (*address, block=None, round_num=None, include_all=False, **kwargs*)

Return account information.

Parameters

- **address** (*str*) – account public key
- **block** (*int, optional*) – use results from the specified round
- **round_num** (*int, optional*) – alias for block; only specify one of these
- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

transaction (*txid, **kwargs*)

Returns information about the given transaction.

Parameters txid (*str*) – The ID of the transaction to look up.

search_transactions (*limit=None, next_page=None, note_prefix=None, txn_type=None, sig_type=None, txid=None, block=None, min_round=None, max_round=None, asset_id=None, start_time=None, end_time=None, min_amount=None, max_amount=None, address=None, address_role=None, exclude_close_to=False, application_id=None, rekey_to=False, round_num=None, **kwargs*)

Return a list of transactions satisfying the conditions.

Parameters

- **limit** (*int, optional*) – maximum number of results to return
- **next_page** (*str, optional*) – the next page of results; use the next token provided by the previous results
- **note_prefix** (*bytes, optional*) – specifies a prefix which must be contained in the note field
- **txn_type** (*str, optional*) – type of transaction; one of “pay”, “keyreg”, “acfg”, “axfer”, “afrz”
- **sig_type** (*str, optional*) – type of signature; one of “sig”, “msig”, “lsig”
- **txid** (*str, optional*) – lookup a specific transaction by ID
- **block** (*int, optional*) – include results for the specified round
- **min_round** (*int, optional*) – include results at or after the specified round
- **max_round** (*int, optional*) – include results at or before the specified round
- **asset_id** (*int, optional*) – include transactions for the specified asset

- **end_time**(*str, optional*) – include results before the given time; must be an RFC 3339 formatted string
- **start_time**(*str, optional*) – include results after the given time; must be an RFC 3339 formatted string
- **min_amount**(*int, optional*) – results should have an amount greater than this value; microalgos are the default currency unless an asset-id is provided, in which case the asset will be used
- **max_amount**(*int, optional*) – results should have an amount less than this value, microalgos are the default currency unless an asset-id is provided, in which case the asset will be used
- **address**(*str, optional*) – only include transactions with this address in one of the transaction fields
- **address_role**(*str, optional*) – one of “sender” or “receiver”; combine with the address parameter to define what type of address to search for
- **exclude_close_to**(*bool, optional*) – combine with address and address_role parameters to define what type of address to search for; the close to fields are normally treated as a receiver, if you would like to exclude them set this parameter to true
- **application_id**(*int, optional*) – filter for transactions pertaining to an application
- **rekey_to**(*bool, optional*) – include results which include the rekey-to field
- **round_num**(*int, optional*) – alias for block; only specify one of these

search_transactions_by_address(*address, limit=None, next_page=None, note_prefix=None, txn_type=None, sig_type=None, txid=None, block=None, min_round=None, max_round=None, asset_id=None, start_time=None, end_time=None, min_amount=None, max_amount=None, rekey_to=False, round_num=None, **kwargs*)

Return a list of transactions satisfying the conditions for the address.

Parameters

- **address**(*str*) – only include transactions with this address in one of the transaction fields
- **limit**(*int, optional*) – maximum number of results to return
- **next_page**(*str, optional*) – the next page of results; use the next token provided by the previous results
- **note_prefix**(*bytes, optional*) – specifies a prefix which must be contained in the note field
- **txn_type**(*str, optional*) – type of transaction; one of “pay”, “keyreg”, “acfg”, “axfer”, “afrz”
- **sig_type**(*str, optional*) – type of signature; one of “sig”, “msig”, “lsig”
- **txid**(*str, optional*) – lookup a specific transaction by ID
- **block**(*int, optional*) – include results for the specified round
- **min_round**(*int, optional*) – include results at or after the specified round
- **max_round**(*int, optional*) – include results at or before the specified round

- **asset_id**(*int, optional*) – include transactions for the specified asset
- **end_time**(*str, optional*) – include results before the given time; must be an RFC 3339 formatted string
- **start_time**(*str, optional*) – include results after the given time; must be an RFC 3339 formatted string
- **min_amount**(*int, optional*) – results should have an amount greater than this value; microalgos are the default currency unless an asset-id is provided, in which case the asset will be used
- **max_amount**(*int, optional*) – results should have an amount less than this value, microalgos are the default currency unless an asset-id is provided, in which case the asset will be used
- **rekey_to**(*bool, optional*) – include results which include the rekey-to field
- **round_num**(*int, optional*) – alias for block; only specify one of these

```
search_asset_transactions(asset_id, limit=None, next_page=None, note_prefix=None,
                           txn_type=None, sig_type=None, txid=None, block=None,
                           min_round=None, max_round=None, address=None,
                           start_time=None, end_time=None, min_amount=None,
                           max_amount=None, address_role=None, ex-
                           clude_close_to=False, rekey_to=False, round_num=None,
                           **kwargs)
```

Return a list of transactions satisfying the conditions for the address.

Parameters

- **asset_id**(*int*) – include transactions for the specified asset
- **limit**(*int, optional*) – maximum number of results to return
- **next_page**(*str, optional*) – the next page of results; use the next token provided by the previous results
- **note_prefix**(*bytes, optional*) – specifies a prefix which must be contained in the note field
- **txn_type**(*str, optional*) – type of transaction; one of “pay”, “keyreg”, “acfg”, “axfer”, “afrz”
- **sig_type**(*str, optional*) – type of signature; one of “sig”, “msig”, “lsig”
- **txid**(*str, optional*) – lookup a specific transaction by ID
- **block**(*int, optional*) – include results for the specified round
- **min_round**(*int, optional*) – include results at or after the specified round
- **max_round**(*int, optional*) – include results at or before the specified round
- **address**(*str, optional*) – only include transactions with this address in one of the transaction fields
- **end_time**(*str, optional*) – include results before the given time; must be an RFC 3339 formatted string
- **start_time**(*str, optional*) – include results after the given time; must be an RFC 3339 formatted string

- **min_amount** (*int, optional*) – results should have an amount greater than this value; microalgos are the default currency unless an asset-id is provided, in which case the asset will be used
- **max_amount** (*int, optional*) – results should have an amount less than this value, microalgos are the default currency unless an asset-id is provided, in which case the asset will be used
- **address_role** (*str, optional*) – one of “sender” or “receiver”; combine with the address parameter to define what type of address to search for
- **exclude_close_to** (*bool, optional*) – combine with address and address_role parameters to define what type of address to search for; the close to fields are normally treated as a receiver, if you would like to exclude them set this parameter to true
- **rekey_to** (*bool, optional*) – include results which include the rekey-to field
- **round_num** (*int, optional*) – alias for block; only specify one of these

search_assets (*limit=None, next_page=None, creator=None, name=None, unit=None, asset_id=None, include_all=False, **kwargs*)

Return assets that satisfy the conditions.

Parameters

- **limit** (*int, optional*) – maximum number of results to return
- **next_page** (*str, optional*) – the next page of results; use the next token provided by the previous results
- **creator** (*str, optional*) – filter just assets with the given creator address
- **name** (*str, optional*) – filter just assets with the given name
- **unit** (*str, optional*) – filter just assets with the given unit
- **asset_id** (*int, optional*) – return only the asset with this ID
- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

asset_info (*asset_id, include_all=False, **kwargs*)

Return asset information.

Parameters

- **asset_id** (*int*) – asset index
- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

applications (*application_id, round=None, round_num=None, include_all=False, **kwargs*)

Return applications that satisfy the conditions.

Parameters

- **application_id** (*int*) – application index
- **round** (*int, optional*) – not supported, DO NOT USE!
- **round_num** (*int, optional*) – not supported, DO NOT USE!

- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

search_applications (*application_id=None, round=None, limit=None, next_page=None, round_num=None, include_all=False, **kwargs*)

Return applications that satisfy the conditions.

Parameters

- **application_id** (*int, optional*) – restrict search to application index
- **round** (*int, optional*) – not supported, DO NOT USE!
- **limit** (*int, optional*) – restrict number of results to limit
- **next_page** (*string, optional*) – used for pagination
- **round_num** (*int, optional*) – not supported, DO NOT USE!
- **include_all** (*bool, optional*) – include all items including closed accounts, deleted applications, destroyed assets, opted-out asset holdings, and closed-out application localstates. Defaults to false.

application_logs (*application_id, limit=None, min_round=None, max_round=None, next_page=None, sender_addr=None, txid=None, **kwargs*)

Return log messages generated by the passed in application.

Parameters

- **application_id** (*int*) – application index
- **limit** (*int, optional*) – limit maximum number of results to return
- **min_round** (*int, optional*) – only include results at or after the specified round
- **max_round** (*int, optional*) – only include results at or before the specified round
- **next_page** (*string, optional*) – used for pagination
- **sender_addr** (*string, optional*) – only include transactions with this sender address
- **txid** (*string, optional*) – only include results with this transaction ID

8.1.15 wallet

class Wallet (*wallet_name, wallet_pswd, kmd_client, driver_name='sqlite', mdk=None*)

Bases: object

Represents a wallet.

Parameters

- **wallet_name** (*str*) – wallet name
- **wallet_pswd** (*str*) – wallet password
- **kmd_client** (*KMDClient*) – a KMDClient to handle wallet requests
- **mdk** (*str, optional*) – master derivation key if recovering wallet

Note: When initializing, if the wallet doesn't already exist, it will be created.

name
Type str

pswd
Type str

kcl
Type *KMDClient*

id
Type str

handle
Type str

info()
 Get wallet information.
Returns dictionary containing wallet handle and wallet information
Return type dict

list_keys()
 List all keys in the wallet.
Returns list of base32 addresses in the wallet
Return type str[]

rename(new_name)
 Rename the wallet.
Parameters **new_name** (*str*) – new name for the wallet
Returns dictionary containing wallet information
Return type dict

get_mnemonic()
 Get recovery phrase mnemonic for the wallet.
Returns mnemonic converted from the wallet’s master derivation key
Return type str

export_master_derivation_key()
 Get the wallet’s master derivation key.
Returns master derivation key
Return type str

import_key(private_key)
 Import an account into a wallet.
Parameters **private_key** (*str*) – private key of account to be imported
Returns base32 address of the account
Return type str

export_key(address)
 Return an account private key.

Parameters **address** (*str*) – base32 address of the account

Returns private key

Return type *str*

generate_key (*display_mnemonic=True*)

Generate a key in the wallet.

Parameters **display_mnemonic** (*bool, optional*) – whether or not the mnemonic should be displayed

Returns base32 address of the generated account

Return type *str*

delete_key (*address*)

Delete a key in the wallet.

Parameters **address** (*str*) – base32 address of account to be deleted

Returns True if the account has been deleted

Return type *bool*

sign_transaction (*txn*)

Sign a transaction.

Parameters **txn** (*Transaction*) – transaction to be signed

Returns signed transaction with signature of sender

Return type *SignedTransaction*

list_multisig ()

List all multisig accounts in the wallet.

Returns list of base32 multisig account addresses

Return type *str[]*

import_multisig (*multisig*)

Import a multisig account into the wallet.

Parameters **multisig** (*Multisig*) – multisig account to be imported

Returns base32 address of the imported multisig account

Return type *str*

export_multisig (*address*)

Export a multisig account.

Parameters **address** (*str*) – base32 address of the multisig account

Returns multisig object corresponding to the address

Return type *Multisig*

delete_multisig (*address*)

Delete a multisig account.

Parameters **address** (*str*) – base32 address of the multisig account to delete

Returns True if the multisig account has been deleted

Return type *bool*

sign_multisig_transaction (*public_key*, *mtx*)

Sign a multisig transaction for the given public key.

Parameters

- **public_key** (*str*) – base32 address that is signing the transaction
- **mtx** (*MultisigTransaction*) – object containing unsigned or partially signed multisig

Returns multisig transaction with added signature

Return type *MultisigTransaction*

automate_handle ()

Get a new handle or renews the current one.

Returns True if a handle is active

Return type bool

init_handle ()

Get a new handle.

Returns True if a handle is active

Return type bool

renew_handle ()

Renew the current handle.

Returns dictionary containing wallet handle and wallet information

Return type dict

release_handle ()

Deactivate the current handle.

Returns True if the handle has been deactivated

Return type bool

8.1.16 wordlist

word_list_raw ()

Return the wordlist used for mnemonics.

a

- `algosdk.account`, 17
- `algosdk.algod`, 17
- `algosdk.auction`, 20
- `algosdk.constants`, 22
- `algosdk.encoding`, 25
- `algosdk.error`, 26
- `algosdk.future.template`, 28
- `algosdk.future.transaction`, 31
- `algosdk.kmd`, 57
- `algosdk.logic`, 61
- `algosdk.mnemonic`, 63
- `algosdk.template`, 63
- `algosdk.transaction`, 67
- `algosdk.util`, 80
- `algosdk.v2client.algod`, 81
- `algosdk.v2client.indexer`, 84
- `algosdk.wallet`, 90
- `algosdk.wordlist`, 93

A

- `account_info()` (*AlgodClient* method), 19, 81
- `account_info()` (*IndexerClient* method), 86
- `accounts` (*ApplicationCallTxn* attribute), 47
- `accounts()` (*IndexerClient* method), 85
- `address()` (*in module algosdk.logic*), 62
- `address()` (*LogicSig* method), 54, 78
- `address()` (*LogicSigAccount* method), 55
- `address()` (*Multisig* method), 53, 77
- `address_from_private_key()` (*in module algosdk.account*), 17
- `ADDRESS_LEN` (*in module algosdk.constants*), 24
- `algod_address` (*AlgodClient* attribute), 18, 81
- `ALGOD_AUTH_HEADER` (*in module algosdk.constants*), 22
- `algod_request()` (*AlgodClient* method), 18, 81
- `algod_token` (*AlgodClient* attribute), 17, 81
- `AlgodClient` (*class in algosdk.algod*), 17
- `AlgodClient` (*class in algosdk.v2client.algod*), 81
- `AlgodHTTPError`, 27
- `AlgodResponseError`, 27
- `algos_to_microalgos()` (*in module algosdk.util*), 80
- `algosdk.account` (*module*), 17
- `algosdk.algod` (*module*), 17
- `algosdk.auction` (*module*), 20
- `algosdk.constants` (*module*), 22
- `algosdk.encoding` (*module*), 25
- `algosdk.error` (*module*), 26
- `algosdk.future.template` (*module*), 28
- `algosdk.future.transaction` (*module*), 31
- `algosdk.kmd` (*module*), 57
- `algosdk.logic` (*module*), 61
- `algosdk.mnemonic` (*module*), 63
- `algosdk.template` (*module*), 63
- `algosdk.transaction` (*module*), 67
- `algosdk.util` (*module*), 80
- `algosdk.v2client.algod` (*module*), 81
- `algosdk.v2client.indexer` (*module*), 84
- `algosdk.wallet` (*module*), 90
- `algosdk.wordlist` (*module*), 93
- `amount` (*AssetTransferTxn* attribute), 44, 75
- `amt` (*PaymentTxn* attribute), 33, 69
- `app_args` (*ApplicationCallTxn* attribute), 47
- `APPCALL_TXN` (*in module algosdk.constants*), 23
- `append_to_multisig()` (*LogicSig* method), 54, 79
- `append_to_multisig()` (*LogicSigAccount* method), 55
- `APPID_PREFIX` (*in module algosdk.constants*), 23
- `application_info()` (*AlgodClient* method), 82
- `application_logs()` (*IndexerClient* method), 90
- `ApplicationCallTxn` (*class in algosdk.future.transaction*), 46
- `ApplicationClearStateTxn` (*class in algosdk.future.transaction*), 50
- `ApplicationCloseOutTxn` (*class in algosdk.future.transaction*), 49
- `ApplicationCreateTxn` (*class in algosdk.future.transaction*), 47
- `ApplicationDeleteTxn` (*class in algosdk.future.transaction*), 49
- `ApplicationNoOpTxn` (*class in algosdk.future.transaction*), 50
- `ApplicationOptInTxn` (*class in algosdk.future.transaction*), 49
- `applications()` (*IndexerClient* method), 89
- `ApplicationUpdateTxn` (*class in algosdk.future.transaction*), 48
- `approval_program` (*ApplicationCallTxn* attribute), 47
- `args` (*LogicSig* attribute), 54, 78
- `as_hash()` (*Transaction* static method), 32
- `as_lease()` (*algosdk.future.transaction.Transaction* class method), 32
- `as_metadata()` (*algosdk.future.transaction.AssetConfigTxn* class method), 40
- `as_note()` (*Transaction* static method), 32
- `asset_balances()` (*IndexerClient* method), 85

asset_info() (*AlgodClient* method), 19, 82
asset_info() (*IndexerClient* method), 89
asset_name (*AssetConfigTxn* attribute), 40, 72
AssetCloseOutTxn (class in *algorithms.future.transaction*), 45
ASSETCONFIG_TXN (in module *algorithms.constants*), 22
AssetConfigTxn (class in *algorithms.future.transaction*), 38
AssetConfigTxn (class in *algorithms.transaction*), 70
AssetCreateTxn (class in *algorithms.future.transaction*), 41
AssetDestroyTxn (class in *algorithms.future.transaction*), 41
ASSETFREEZE_TXN (in module *algorithms.constants*), 22
AssetFreezeTxn (class in *algorithms.future.transaction*), 42
AssetFreezeTxn (class in *algorithms.transaction*), 73
AssetOptInTxn (class in *algorithms.future.transaction*), 44
ASSETTRANSFER_TXN (in module *algorithms.constants*), 22
AssetTransferTxn (class in *algorithms.future.transaction*), 43
AssetTransferTxn (class in *algorithms.transaction*), 74
AssetUpdateTxn (class in *algorithms.future.transaction*), 41
assign_group_id() (in module *algorithms.future.transaction*), 57
assign_group_id() (in module *algorithms.transaction*), 80
auction_id (*Bid* attribute), 21
auction_key (*Bid* attribute), 21
auth_addr (*LogicSigTransaction* attribute), 56
auth_addr (*MultisigTransaction* attribute), 52
authorizing_address (*SignedTransaction* attribute), 51, 76
automate_handle() (*Wallet* method), 93

B

BadTxnSenderError, 26
Bid (class in *algorithms.auction*), 20
bid (*SignedBid* attribute), 21
bid_currency (*Bid* attribute), 21
bid_id (*Bid* attribute), 21
BID_PREFIX (in module *algorithms.constants*), 23
bidder (*Bid* attribute), 21
block_info() (*AlgodClient* method), 20, 82
block_info() (*IndexerClient* method), 86
block_raw() (*AlgodClient* method), 20
build_headers_from() (in module *algorithms.util*), 81
bytes_list() (*ApplicationCallTxn* static method), 47
BYTES_PREFIX (in module *algorithms.constants*), 23

C

calculate_group_id() (in module *algorithms.future.transaction*), 57
calculate_group_id() (in module *algorithms.transaction*), 80
check_byte_const_block() (in module *algorithms.logic*), 62
check_int_const_block() (in module *algorithms.logic*), 62
check_program() (in module *algorithms.logic*), 61
check_push_byte_block() (in module *algorithms.logic*), 62
check_push_int_block() (in module *algorithms.logic*), 62
CHECK_SUM_LEN_BYTES (in module *algorithms.constants*), 24
checksum() (in module *algorithms.encoding*), 26
clawback (*AssetConfigTxn* attribute), 40, 72
clear_program (*ApplicationCallTxn* attribute), 47
ClearStateOC (*OnComplete* attribute), 45
close_assets_to (*AssetTransferTxn* attribute), 44, 75
close_remainder_to (*PaymentTxn* attribute), 34, 69
CloseOutOC (*OnComplete* attribute), 45
compile() (*AlgodClient* method), 83
ConfirmationTimeoutError, 27
consensus_version (*SuggestedParams* attribute), 32
creatable_index() (*Transaction* static method), 32
create_wallet() (*KMDClient* method), 58

D

decimals (*AssetConfigTxn* attribute), 40, 73
decode_address() (in module *algorithms.encoding*), 25
default_frozen (*AssetConfigTxn* attribute), 40, 72
delete_key() (*KMDClient* method), 60
delete_key() (*Wallet* method), 92
delete_multisig() (*KMDClient* method), 61
delete_multisig() (*Wallet* method), 92
DeleteApplicationOC (*OnComplete* attribute), 46
dictify() (*ApplicationCallTxn* method), 47
dictify() (*AssetConfigTxn* method), 40, 73
dictify() (*AssetFreezeTxn* method), 43, 74
dictify() (*AssetTransferTxn* method), 44, 76
dictify() (*Bid* method), 21
dictify() (*KeyregTxn* method), 35, 70
dictify() (*LogicSig* method), 54, 78
dictify() (*LogicSigAccount* method), 54
dictify() (*LogicSigTransaction* method), 56, 79
dictify() (*Multisig* method), 53, 77
dictify() (*MultisigSubsig* method), 53, 78
dictify() (*MultisigTransaction* method), 52, 76

dictify() (*NoteField* method), 22
dictify() (*PaymentTxn* method), 34, 69
dictify() (*SignedBid* method), 21
dictify() (*SignedTransaction* method), 51, 76
dictify() (*StateSchema* method), 45
dictify() (*Transaction* method), 32, 67
dictify() (*TxGroup* method), 57, 79
dryrun() (*AlgodClient* method), 83
DuplicateSigMismatchError, 26
DynamicFee (class in *algorithms.future.template*), 29
DynamicFee (class in *algorithms.template*), 65

E

EmptyAddressError, 27
encode_address() (in module *algorithms.encoding*), 26
estimate_size() (*Transaction* method), 32, 67
export_key() (*KMDClient* method), 59
export_key() (*Wallet* method), 91
export_master_derivation_key() (*KMD-Client* method), 59
export_master_derivation_key() (*Wallet* method), 91
export_multisig() (*KMDClient* method), 61
export_multisig() (*Wallet* method), 92
extra_pages (*ApplicationCallTxn* attribute), 47

F

fee (*ApplicationCallTxn* attribute), 46
fee (*AssetConfigTxn* attribute), 39, 72
fee (*AssetFreezeTxn* attribute), 42, 73
fee (*AssetTransferTxn* attribute), 44, 75
fee (*KeyregNonparticipatingTxn* attribute), 38
fee (*KeyregOfflineTxn* attribute), 37
fee (*KeyregOnlineTxn* attribute), 36
fee (*KeyregTxn* attribute), 34, 69
fee (*PaymentTxn* attribute), 33, 68
fee (*SuggestedParams* attribute), 31
first (*SuggestedParams* attribute), 31
first_valid_round (*ApplicationCallTxn* attribute), 46
first_valid_round (*AssetConfigTxn* attribute), 39, 72
first_valid_round (*AssetFreezeTxn* attribute), 42, 73
first_valid_round (*AssetTransferTxn* attribute), 44, 75
first_valid_round (*KeyregNonparticipatingTxn* attribute), 38
first_valid_round (*KeyregOfflineTxn* attribute), 37
first_valid_round (*KeyregOnlineTxn* attribute), 36
first_valid_round (*KeyregTxn* attribute), 34, 70

first_valid_round (*PaymentTxn* attribute), 33, 68
flat_fee (*SuggestedParams* attribute), 32
foreign_apps (*ApplicationCallTxn* attribute), 47
foreign_assets (*ApplicationCallTxn* attribute), 47
freeze (*AssetConfigTxn* attribute), 40, 72
from_master_derivation_key() (in module *algorithms.mnemonic*), 63
from_private_key() (in module *algorithms.mnemonic*), 63
future_msgpack_decode() (in module *algorithms.encoding*), 25

G

gen (*SuggestedParams* attribute), 32
generate_account() (in module *algorithms.account*), 17
generate_key() (*KMDClient* method), 59
generate_key() (*Wallet* method), 92
genesis() (*AlgodClient* method), 84
genesis_hash (*ApplicationCallTxn* attribute), 46
genesis_hash (*AssetConfigTxn* attribute), 39, 72
genesis_hash (*AssetFreezeTxn* attribute), 42, 74
genesis_hash (*AssetTransferTxn* attribute), 44, 75
genesis_hash (*KeyregNonparticipatingTxn* attribute), 38
genesis_hash (*KeyregOfflineTxn* attribute), 37
genesis_hash (*KeyregOnlineTxn* attribute), 36
genesis_hash (*KeyregTxn* attribute), 35, 70
genesis_hash (*PaymentTxn* attribute), 33, 68
genesis_id (*AssetConfigTxn* attribute), 40, 72
genesis_id (*AssetFreezeTxn* attribute), 43, 74
genesis_id (*AssetTransferTxn* attribute), 44, 75
genesis_id (*KeyregNonparticipatingTxn* attribute), 38
genesis_id (*KeyregOfflineTxn* attribute), 37
genesis_id (*KeyregOnlineTxn* attribute), 36
genesis_id (*KeyregTxn* attribute), 34, 70
genesis_id (*PaymentTxn* attribute), 33, 68
get_address() (*Template* method), 28, 63
get_application_address() (in module *algorithms.logic*), 62
get_mnemonic() (*Wallet* method), 91
get_multisig_account() (*Multisig* method), 53, 77
get_program() (*DynamicFee* method), 29, 65
get_program() (*HTLC* method), 29, 64
get_program() (*LimitOrder* method), 31, 66
get_program() (*PeriodicPayment* method), 30, 66
get_program() (*Split* method), 28, 64
get_program() (*Template* method), 28, 63
get_public_keys() (*Multisig* method), 53, 77
get_split_funds_transaction() (*Split* static method), 28, 64

get_swap_assets_transactions() (*LimitOrder static method*), 31, 66
 get_transaction() (*HTLC static method*), 29, 64
 get_transactions() (*DynamicFee static method*), 29, 65
 get_txid() (*LogicSigTransaction method*), 56
 get_txid() (*MultisigTransaction method*), 52
 get_txid() (*SignedTransaction method*), 51
 get_txid() (*Transaction method*), 32, 67
 get_wallet() (*KMDClient method*), 58
 get_withdrawal_transaction() (*PeriodicPayment static method*), 30, 66
 gh (*SuggestedParams attribute*), 32
 global_schema (*ApplicationCallTxn attribute*), 47
 group (*KeyregNonparticipatingTxn attribute*), 38
 group (*KeyregOfflineTxn attribute*), 37
 group (*KeyregOnlineTxn attribute*), 36
 group (*KeyregTxn attribute*), 35, 70
 group (*PaymentTxn attribute*), 33, 68

H

handle (*Wallet attribute*), 91
 HASH_LEN (*in module algosdk.constants*), 24
 headers (*AlgodClient attribute*), 18, 81
 headers (*IndexerClient attribute*), 84
 health() (*AlgodClient method*), 18, 83
 health() (*IndexerClient method*), 85
 HTLC (*class in algosdk.future.template*), 28
 HTLC (*class in algosdk.template*), 64

I

id (*Wallet attribute*), 91
 import_key() (*KMDClient method*), 59
 import_key() (*Wallet method*), 91
 import_multisig() (*KMDClient method*), 60
 import_multisig() (*Wallet method*), 92
 index (*ApplicationCallTxn attribute*), 47
 index (*AssetConfigTxn attribute*), 40, 72
 index (*AssetFreezeTxn attribute*), 43, 74
 index (*AssetTransferTxn attribute*), 44, 75
 indexer_address (*IndexerClient attribute*), 84
 INDEXER_AUTH_HEADER (*in module algosdk.constants*), 22
 indexer_request() (*IndexerClient method*), 84
 indexer_token (*IndexerClient attribute*), 84
 IndexerClient (*class in algosdk.v2client.indexer*), 84
 IndexerHTTPError, 27
 info() (*Wallet method*), 91
 init_handle() (*Wallet method*), 93
 init_wallet_handle() (*KMDClient method*), 58
 inject() (*in module algosdk.future.template*), 31
 inject() (*in module algosdk.template*), 67
 int_list() (*ApplicationCallTxn static method*), 47

InvalidProgram, 27
 InvalidSecretKeyError, 26
 InvalidThresholdError, 26
 is_delegated() (*LogicSigAccount method*), 55
 is_valid_address() (*in module algosdk.encoding*), 25

J

json_dictify() (*Multisig method*), 53, 77
 json_dictify() (*MultisigSubsig method*), 53, 78

K

kcl (*Wallet attribute*), 91
 KEN_LEN_BYTES (*in module algosdk.constants*), 24
 KEYREG_TXN (*in module algosdk.constants*), 22
 KeyregNonparticipatingTxn (*class in algosdk.future.transaction*), 37
 KeyregOfflineTxn (*class in algosdk.future.transaction*), 36
 KeyregOnlineTxn (*class in algosdk.future.transaction*), 35
 KeyregOnlineTxnInitError, 27
 KeyregTxn (*class in algosdk.future.transaction*), 34
 KeyregTxn (*class in algosdk.transaction*), 69
 kmd_address (*KMDClient attribute*), 57
 KMD_AUTH_HEADER (*in module algosdk.constants*), 22
 kmd_request() (*KMDClient method*), 57
 kmd_token (*KMDClient attribute*), 57
 KMDClient (*class in algosdk.kmd*), 57
 KMDHTTPError, 27

L

last (*SuggestedParams attribute*), 32
 last_valid_round (*ApplicationCallTxn attribute*), 46
 last_valid_round (*AssetConfigTxn attribute*), 39, 72
 last_valid_round (*AssetFreezeTxn attribute*), 42, 73
 last_valid_round (*AssetTransferTxn attribute*), 44, 75
 last_valid_round (*KeyregNonparticipatingTxn attribute*), 38
 last_valid_round (*KeyregOfflineTxn attribute*), 37
 last_valid_round (*KeyregOnlineTxn attribute*), 36
 last_valid_round (*KeyregTxn attribute*), 34, 70
 last_valid_round (*PaymentTxn attribute*), 33, 68
 lease (*AssetConfigTxn attribute*), 40, 73
 lease (*AssetFreezeTxn attribute*), 43, 74
 lease (*AssetTransferTxn attribute*), 44, 75
 lease (*KeyregNonparticipatingTxn attribute*), 38
 lease (*KeyregOfflineTxn attribute*), 37
 lease (*KeyregOnlineTxn attribute*), 36
 lease (*KeyregTxn attribute*), 35, 70

[lease](#) (*PaymentTxn* attribute), 34, 69
[LEASE_LENGTH](#) (in module *algosdk.constants*), 24
[ledger_supply\(\)](#) (*AlgodClient* method), 18, 82
[LimitOrder](#) (class in *algosdk.future.template*), 30
[LimitOrder](#) (class in *algosdk.template*), 66
[list_assets\(\)](#) (*AlgodClient* method), 19
[list_keys\(\)](#) (*KMDClient* method), 60
[list_keys\(\)](#) (*Wallet* method), 91
[list_multisig\(\)](#) (*KMDClient* method), 60
[list_multisig\(\)](#) (*Wallet* method), 92
[list_wallets\(\)](#) (*KMDClient* method), 58
[local_schema](#) (*ApplicationCallTxn* attribute), 47
[logic](#) (*LogicSig* attribute), 53, 78
[LOGIC_DATA_PREFIX](#) (in module *algosdk.constants*), 23
[LOGIC_PREFIX](#) (in module *algosdk.constants*), 23
[LOGIC_SIG_MAX_COST](#) (in module *algosdk.constants*), 24
[LOGIC_SIG_MAX_SIZE](#) (in module *algosdk.constants*), 25
[LogicSig](#) (class in *algosdk.future.transaction*), 53
[LogicSig](#) (class in *algosdk.transaction*), 78
[LogicSigAccount](#) (class in *algosdk.future.transaction*), 54
[LogicSigOverspecifiedSignature](#), 26
[LogicSigSigningKeyMissing](#), 26
[LogicSigTransaction](#) (class in *algosdk.future.transaction*), 55
[LogicSigTransaction](#) (class in *algosdk.transaction*), 79
[lsig](#) (*LogicSigTransaction* attribute), 56, 79

M

[manager](#) (*AssetConfigTxn* attribute), 40, 72
[MAX_ASSET_DECIMALS](#) (in module *algosdk.constants*), 24
[max_price](#) (*Bid* attribute), 21
[merge\(\)](#) (*MultisigTransaction* static method), 52, 76
[MergeAuthAddrMismatchError](#), 26
[MergeKeysMismatchError](#), 26
[metadata_hash](#) (*AssetConfigTxn* attribute), 40, 72
[METADATA_LENGTH](#) (in module *algosdk.constants*), 24
[microalgos_to_algos\(\)](#) (in module *algosdk.util*), 80
[MICROALGOS_TO_ALGOS_RATIO](#) (in module *algosdk.constants*), 24
[min_fee](#) (*SuggestedParams* attribute), 32
[MIN_TXN_FEE](#) (in module *algosdk.constants*), 24
[MNEMONIC_LEN](#) (in module *algosdk.constants*), 24
[msgpack_decode\(\)](#) (in module *algosdk.encoding*), 25
[msgpack_encode\(\)](#) (in module *algosdk.encoding*), 25
[msig](#) (*LogicSig* attribute), 54, 78

[MSIG_ADDR_PREFIX](#) (in module *algosdk.constants*), 23
[Multisig](#) (class in *algosdk.future.transaction*), 52
[Multisig](#) (class in *algosdk.transaction*), 77
[multisig](#) (*MultisigTransaction* attribute), 52, 76
[MULTISIG_ACCOUNT_LIMIT](#) (in module *algosdk.constants*), 24
[MultisigAccountSizeError](#), 27
[MultisigSubsig](#) (class in *algosdk.future.transaction*), 53
[MultisigSubsig](#) (class in *algosdk.transaction*), 77
[MultisigTransaction](#) (class in *algosdk.future.transaction*), 51
[MultisigTransaction](#) (class in *algosdk.transaction*), 76

N

[name](#) (*Wallet* attribute), 90
[new_freeze_state](#) (*AssetFreezeTxn* attribute), 43, 74
[NO_AUTH](#) (in module *algosdk.constants*), 22
[nonpart](#) (*KeyregTxn* attribute), 35
[NoOpOC](#) (*OnComplete* attribute), 45
[note](#) (*AssetConfigTxn* attribute), 40, 72
[note](#) (*AssetFreezeTxn* attribute), 43, 74
[note](#) (*AssetTransferTxn* attribute), 44, 75
[note](#) (*KeyregNonparticipatingTxn* attribute), 38
[note](#) (*KeyregOfflineTxn* attribute), 37
[note](#) (*KeyregOnlineTxn* attribute), 36
[note](#) (*KeyregTxn* attribute), 34, 70
[note](#) (*PaymentTxn* attribute), 33, 68
[note_field_type](#) (*NoteField* attribute), 22
[NOTE_FIELD_TYPE_BID](#) (in module *algosdk.constants*), 23
[NOTE_FIELD_TYPE_DEPOSIT](#) (in module *algosdk.constants*), 23
[NOTE_FIELD_TYPE_PARAMS](#) (in module *algosdk.constants*), 23
[NOTE_FIELD_TYPE_SETTLEMENT](#) (in module *algosdk.constants*), 23
[NOTE_MAX_LENGTH](#) (in module *algosdk.constants*), 24
[NoteField](#) (class in *algosdk.auction*), 21
[num_byte_slices](#) (*StateSchema* attribute), 45
[num_uints](#) (*StateSchema* attribute), 45

O

[on_complete](#) (*ApplicationCallTxn* attribute), 47
[OnComplete](#) (class in *algosdk.future.transaction*), 45
[OptInOC](#) (*OnComplete* attribute), 45
[OutOfRangeDecimalsError](#), 27
[OverspecifiedRoundError](#), 27

P

[parse_uvarint\(\)](#) (in module *algosdk.logic*), 62

PAYMENT_TXN (in module *algosdk.constants*), 22
 PaymentTxn (class in *algosdk.future.transaction*), 33
 PaymentTxn (class in *algosdk.transaction*), 67
 pending_transaction_info() (*AlgodClient* method), 19, 83
 pending_transactions() (*AlgodClient* method), 18, 83
 pending_transactions_by_address() (*AlgodClient* method), 82
 PeriodicPayment (class in *algosdk.future.template*), 30
 PeriodicPayment (class in *algosdk.template*), 66
 proof() (*AlgodClient* method), 84
 pswd (Wallet attribute), 91
 public_key (MultisigSubsig attribute), 53, 77
 put_uvarint() (in module *algosdk.future.template*), 31
 put_uvarint() (in module *algosdk.template*), 67

R

raw_sign() (Transaction method), 32, 67
 read_byte_const_block() (in module *algosdk.logic*), 62
 read_int_const_block() (in module *algosdk.logic*), 62
 read_program() (in module *algosdk.logic*), 62
 read_push_byte_block() (in module *algosdk.logic*), 62
 read_push_int_block() (in module *algosdk.logic*), 62
 receiver (AssetTransferTxn attribute), 44, 75
 receiver (PaymentTxn attribute), 33, 68
 rekey (AssetConfigTxn attribute), 40
 rekey_to (AssetConfigTxn attribute), 73
 rekey_to (AssetFreezeTxn attribute), 43, 74
 rekey_to (AssetTransferTxn attribute), 44, 75
 rekey_to (KeyregNonparticipatingTxn attribute), 38
 rekey_to (KeyregOfflineTxn attribute), 37
 rekey_to (KeyregOnlineTxn attribute), 36
 rekey_to (KeyregTxn attribute), 35, 70
 rekey_to (PaymentTxn attribute), 34, 69
 release_handle() (Wallet method), 93
 release_wallet_handle() (*KMDClient* method), 58
 rename() (Wallet method), 91
 rename_wallet() (*KMDClient* method), 59
 renew_handle() (Wallet method), 93
 renew_wallet_handle() (*KMDClient* method), 59
 required() (Transaction static method), 32
 reserve (AssetConfigTxn attribute), 40, 72
 retrieve_from_file() (in module *algosdk.future.transaction*), 56
 retrieve_from_file() (in module *algosdk.transaction*), 79

revocation_target (AssetTransferTxn attribute), 44, 75

S

search_applications() (*IndexerClient* method), 90
 search_asset_transactions() (*IndexerClient* method), 88
 search_assets() (*IndexerClient* method), 89
 search_transactions() (*IndexerClient* method), 86
 search_transactions_by_address() (*IndexerClient* method), 87
 selkey (KeyregOnlineTxn attribute), 36
 selkey (KeyregTxn attribute), 35, 70
 send_raw_transaction() (*AlgodClient* method), 19, 82
 send_transaction() (*AlgodClient* method), 20, 82
 send_transactions() (*AlgodClient* method), 20, 83
 sender (ApplicationCallTxn attribute), 46
 sender (AssetConfigTxn attribute), 39, 71
 sender (AssetFreezeTxn attribute), 42, 73
 sender (AssetTransferTxn attribute), 44, 75
 sender (KeyregNonparticipatingTxn attribute), 38
 sender (KeyregOfflineTxn attribute), 37
 sender (KeyregOnlineTxn attribute), 36
 sender (KeyregTxn attribute), 34, 69
 sender (PaymentTxn attribute), 33, 68
 sig (LogicSig attribute), 54, 78
 sign() (Bid method), 21
 sign() (LogicSig method), 54, 78
 sign() (LogicSigAccount method), 55
 sign() (MultisigTransaction method), 52, 76
 sign() (Transaction method), 32, 67
 sign_bytes() (in module *algosdk.util*), 80
 sign_dynamic_fee() (DynamicFee method), 30, 65
 sign_multisig() (LogicSigAccount method), 55
 sign_multisig_transaction() (*KMDClient* method), 61
 sign_multisig_transaction() (Wallet method), 92
 sign_program() (LogicSig static method), 54, 78
 sign_transaction() (*KMDClient* method), 60
 sign_transaction() (Wallet method), 92
 signature (MultisigSubsig attribute), 53, 77
 signature (SignedBid attribute), 21
 signature (SignedTransaction attribute), 51, 76
 signed_bid (NoteField attribute), 22
 SignedBid (class in *algosdk.auction*), 21
 SignedTransaction (class in *algosdk.future.transaction*), 51
 SignedTransaction (class in *algosdk.transaction*), 76

single_sig_multisig() (*LogicSig* static method), 54, 78
 Split (class in *algosdk.future.template*), 28
 Split (class in *algosdk.template*), 63
 state_schema() (*ApplicationCallTxn* static method), 47
 StateSchema (class in *algosdk.future.transaction*), 45
 status() (*AlgodClient* method), 18, 82
 status_after_block() (*AlgodClient* method), 18, 82
 subsigs (*Multisig* attribute), 53, 77
 suggested_fee() (*AlgodClient* method), 19
 suggested_params() (*AlgodClient* method), 19, 83
 suggested_params_as_object() (*AlgodClient* method), 19
 SuggestedParams (class in *algosdk.future.transaction*), 31

T

target (*AssetFreezeTxn* attribute), 43, 74
 teal_bytes() (*ApplicationCallTxn* static method), 47
 teal_sign() (in module *algosdk.logic*), 62
 teal_sign_from_program() (in module *algosdk.logic*), 62
 Template (class in *algosdk.future.template*), 28
 Template (class in *algosdk.template*), 63
 TemplateError, 27
 TemplateInputError, 27
 TGID_PREFIX (in module *algosdk.constants*), 23
 threshold (*Multisig* attribute), 53, 77
 to_master_derivation_key() (in module *algosdk.mnemonic*), 63
 to_private_key() (in module *algosdk.mnemonic*), 63
 to_public_key() (in module *algosdk.mnemonic*), 63
 total (*AssetConfigTxn* attribute), 40, 72
 Transaction (class in *algosdk.future.transaction*), 32
 Transaction (class in *algosdk.transaction*), 67
 transaction (*LogicSigTransaction* attribute), 56, 79
 transaction (*MultisigTransaction* attribute), 52, 76
 transaction (*SignedTransaction* attribute), 51, 76
 transaction() (*IndexerClient* method), 86
 transaction_by_id() (*AlgodClient* method), 19
 transaction_info() (*AlgodClient* method), 19
 TransactionGroupSizeError, 27
 transactions_by_address() (*AlgodClient* method), 18
 TX_GROUP_LIMIT (in module *algosdk.constants*), 24
 TxGroup (class in *algosdk.future.transaction*), 56
 TxGroup (class in *algosdk.transaction*), 79
 TXID_PREFIX (in module *algosdk.constants*), 23
 type (*AssetConfigTxn* attribute), 40, 72
 type (*AssetFreezeTxn* attribute), 43, 74
 type (*AssetTransferTxn* attribute), 44, 75

type (*KeyregNonparticipatingTxn* attribute), 38
 type (*KeyregOfflineTxn* attribute), 37
 type (*KeyregOnlineTxn* attribute), 36
 type (*KeyregTxn* attribute), 35, 70
 type (*PaymentTxn* attribute), 34, 69

U

UnderspecifiedRoundError, 27
 undictify() (*Bid* static method), 21
 undictify() (*LogicSig* static method), 54, 78
 undictify() (*LogicSigAccount* static method), 55
 undictify() (*LogicSigTransaction* static method), 56, 79
 undictify() (*Multisig* static method), 53, 77
 undictify() (*MultisigSubsig* static method), 53, 78
 undictify() (*MultisigTransaction* static method), 52, 76
 undictify() (*NoteField* static method), 22
 undictify() (*SignedBid* static method), 21
 undictify() (*SignedTransaction* static method), 51, 76
 undictify() (*StateSchema* static method), 45
 undictify() (*Transaction* static method), 32, 67
 undictify() (*TxGroup* static method), 57, 80
 unit_name (*AssetConfigTxn* attribute), 40, 72
 UnknownMsigVersionError, 26
 UNVERSIONED_PATHS (in module *algosdk.constants*), 22
 UpdateApplicationOC (*OnComplete* attribute), 46
 url (*AssetConfigTxn* attribute), 40, 72

V

validate() (*Multisig* method), 53, 77
 verify() (*LogicSig* method), 54, 78
 verify() (*LogicSigAccount* method), 55
 verify() (*LogicSigTransaction* method), 56, 79
 verify() (*Multisig* method), 53, 77
 verify_bytes() (in module *algosdk.util*), 80
 version (*Multisig* attribute), 53, 77
 versions() (*AlgodClient* method), 18, 83
 versions() (*KMDClient* method), 58
 votefst (*KeyregOnlineTxn* attribute), 36
 votefst (*KeyregTxn* attribute), 35, 70
 votekd (*KeyregOnlineTxn* attribute), 36
 votekd (*KeyregTxn* attribute), 35, 70
 votelst (*KeyregOnlineTxn* attribute), 36
 votelst (*KeyregTxn* attribute), 35, 70
 voteapk (*KeyregOnlineTxn* attribute), 36
 voteapk (*KeyregTxn* attribute), 35, 70

W

wait_for_confirmation() (in module *algosdk.future.transaction*), 57
 Wallet (class in *algosdk.wallet*), 90

`word_list_raw()` (in module *algosdk.wordlist*), [93](#)
`write_to_file()` (in module *algosdk.future.transaction*), [56](#)
`write_to_file()` (in module *algosdk.transaction*), [79](#)
`WrongAmountType`, [26](#)
`WrongChecksumError`, [26](#)
`WrongContractError`, [27](#)
`WrongHashLengthError`, [26](#)
`WrongKeyBytesLengthError`, [26](#)
`WrongKeyLengthError`, [26](#)
`WrongLeaseLengthError`, [27](#)
`WrongMetadataLengthError`, [27](#)
`WrongMnemonicLengthError`, [26](#)
`WrongNoteLength`, [27](#)
`WrongNoteType`, [27](#)

Z

`ZeroAddressError`, [27](#)