∨ Vincenzo's workspace ⇕

⬡ inventory-db ⌄

🔍 Search    K

＋ New    ⬆ Upgrade    ⚲    ∨

← Dashboard

⬡ inventory-db

▦ Info

MONITOR

🗐 Logs

⬘ Metrics

MANAGE

🗗 Apps

🗄 Recovery

🗐 Changelog                                            ⌄

◁ Invite a friend

🗗 Contact support

∨ Render Status

# ⬡ POSTGRESQL

# inventory-db

View docs ↗    Connect ⌄

Free    Upgrade your instance →    ≡ Blueprint managed

Service ID: dpg-d4pcq7adbo4c73edodog-a 🗐

## Info

ⓘ Your database will expire on January 4, 2026. The database will be deleted unless you
upgrade to a paid instance type.

## General

### Name

A unique name for your database.

inventory-db

✎ Edit

### Created

5 days ago

### Status

⌄ Available

### PostgreSQL Version

18

### Region

Oregon (US West)

### Read Replicas

Add Read Replica

**Storage**

**6.58% used out of 1 GB**

**Storage Autoscaling**

Disabled

**Datadog API Key**

+ Add Datadog API Key

## Postgres Instance

**Instance Type**

**Free**
**256 MB** RAM
**0.1** CPU
**1 GB** Storage

Update

ⓘ A credit card is required to change instance types.

Add payment information

## High Availability

Run a standby instance of your database and automatically fail over to it if the primary encounters an issue.

Disabled ⚪

ⓘ Only available for **Pro** instances and higher.

See upgrade options

## Connections

**Hostname**
An internal hostname used by your Render services.

```
dpg-d4pcq7adbo4c73edodog-a
```

**Port**

5432

**Database**

inventario_db_sj2w

**Username**

inventory_user

**Password**

4Eo5lLFf6F2snM9bKcbrjEOlUrZVZiCo

**Internal Database URL**

postgresql://inventory_user:4Eo5lLFf6F2snM9bKcbrjEOlUrZVZiCo@dpg-d4pcq7adbo4c73ed…

**External Database URL**

postgresql://inventory_user:4Eo5lLFf6F2snM9bKcbrjEOlUrZVZiCo@dpg-d4pcq7adbo4c73ed…

**PSQL Command**

PGPASSWORD=4Eo5lLFf6F2snM9bKcbrjEOlUrZVZiCo psql -h dpg-d4pcq7adbo4c73edodog-a.or…

## Credentials

Create new default credentials and delete the old
ones when ready.

| USERNAME 1 | PASSWORD | CREATED ↓ |
|---|---|---|
| inventory_user  Default | ●●●●●●●●●●●●●‹ | 5d |

+ New default credential

## Networking

**Inbound IP Restrictions**
Limit incoming traffic to your services from specific IP ranges. Sources are specified in CIDR block notation.

1 **IP range** is allowed from outside of your private network.

Validate IP address

```
0.0.0.0
```

PostgreSQL Inbound IP Rules

| SOURCE | DESCRIPTION | |
|--------|-------------|---|
| 0.0.0.0/0 | everywhere | 🗑 |

+ Add source                                              Cancel    Save

Delete Database     ↻ Restart Database     ⏸ Suspend Database