

HPC 4MA 2021/2022

Members

PHAM Tuan Kiet

VO Van Nghia

Date

12 Dec, 2021

Contents

Contents *i*

1 OpenMP *1*

1.1 Optimization techniques *1*

1.1.1 Naive dot *1*

1.1.2 Spatial locality *1*

1.1.3 OpenMP parallelization *3*

Chapter 1

OpenMP

1.1 Optimization techniques

1.1.1 Naive dot

We first mention here the original `naive_dot` function. This function serves as an anchor (or base case) for performance comparison as well as for making sure we have the right result when using other techniques.

```
for (i = 0; i < M; i++)
  for (j = 0; j < N; j++)
    for (k = 0; k < K; k++) C[i + ldc * j] += A[i + lda * k] * B[k + ldb * j];
```

Below is the output of `naive_dot` for $M = 1$, $K = 2$ and $N = 2$:

```
## ( 1.00  1.50 )
##
## ( 1.00  1.50 )
## ( 1.50  2.00 )
##
## Frobenius Norm   = 5.550901
## Total time naive = 0.000001
## Gflops           = 0.013333
##
## ( 3.25  4.50 )
```

As

$$\begin{pmatrix} 1 & 1,5 \end{pmatrix} \begin{pmatrix} 1 & 1,5 \\ 1,5 & 2 \end{pmatrix} = \begin{pmatrix} 3,25 & 4,5 \end{pmatrix}$$

The result of this function is correct. We move on to the next technique.

1.1.2 Spatial locality

Spatial locality refers to the following scenario: if a particular storage location is referenced at a particular time, then it is likely that nearby memory locations will be referenced in the near future. In order to take advantages of this property, we notice that:

- In memory, A, B, C are stored in contiguous memory block.
- When using the index order i, j, k, we access B consecutively (as we access B by $B[k + \text{ldb} * j]$), but not A and C.
- Data from A, B, C are loaded in a memory block consisting of several consecutive elements to cache. Thus, we could make use of spatial locality when reading data continuously.

From 3 points above, we decide to switch the index order to k, j, i. Now we see that both reading and writing operations on C are in cache, this brings us a critical gain in performance. In addition, reading operations on A are in cache too but those on B are not.

```
for (k = 0; k < K; k++)
  for (j = 0; j < N; j++)
    for (i = 0; i < M; i++) C[i + ldc * j] += A[i + lda * k] * B[k + ldb * j];
```

For comparison, we have a table below with $M = 4$, $K = 8$ and $N = 4$.

Table 1.1: naive vs saxpy when M, N, K is small

algo	time	norm	gflops
naive	0.000002	3.461352	0.111304
saxpy	0.000001	3.461352	0.182857

We have the frobenius norm of both techniques are 3,461352 which indicate we have the right computation result. In addition, calculating time is already significantly small (≈ 0 second in both methods) and the difference between these two can therefore be omitted.

However, if we set $M = 2048$, $K = 2048$ and $N = 2048$, there will be a huge performance gain as in the table shown below. In addition, from now, for an easier comparison between results, we will consider the default value of M, K and N is $M = 2048$, $K = 2048$ and $N = 2048$ if not explicitly mentioned.

Table 1.2: naive vs saxpy when M, N, K is big

algo	time	norm	gflops
naive	149.30573	2.323362	0.115065
saxpy	62.04563	2.323362	0.276891

Here, the `naive_dot` function is approximately 2,41 times slower than the `saxpy_dot` function.

1.1.3 OpenMP parallelization

In this section, we will analyse the main technique of this chapter: OpenMP. First, we show how we enable it on each function. We add a directive above each loop we want to parallelize whose general form is as below:

- Variables inside `private` are tied to one specific thread (each thread has their own copies of those variables).
- `SCHEDULE_HPC` is replaced by the `schedule`¹ we want.
- `NUM_THREADS_HPC` is corresponding to the number of threads to use for `parallel` regions.

```
#pragma omp parallel for schedule(SCHEDULE_HPC) default(shared) private(i, j) \
    num_threads(NUM_THREADS_HPC)
```

In addition, inside `norm` function, we add a reduction clause `reduction(+ : norm)` as we want to sum up every `norm` from each thread to one final `norm` and taking square of that final sum. Finally, we have to add `#pragma omp atomic` above each line that updating the result matrix (`c`). It is because that matrix is shared among threads, `atomic` makes sure that there is only one `+=` operation (which is essentially reading and writing) on one specific pair of indices at a given time. Note that `norm` does not need atomicity thank to `reduction`.

Here, we show a comparison between with and without OpenMP. Default OpenMP options will be `SCHEDULE_HPC = static` and `NUM_THREADS_HPC = 4`.

Table 1.3: naive vs saxpy with OpenMP

algo	time	norm	gflops	omp
naive	45.08355	2.323362	0.381067	x
naive	149.30573	2.323362	0.115065	
saxpy	15.29221	2.323362	1.123440	x
saxpy	62.04563	2.323362	0.276891	

Thank to OpenMP, naive approach is faster than 0,3 times while the `saxpy_dot` took less 0,25 times than before. Both approaches performance are significantly improved.

1. <https://www.openmp.org/spec-html/5.0/openmpse49.html#x288-20520006.1>