

Data Structures Algorithms Interview Preparation Topic-wise Practice C++ Java Python

Simplified Data Encryption Standard Key Generation

Last Updated: 27 Sep, 2021

Simplified Data Encryption Standard (S-DES) is a simple version of the <u>DES Algorithm</u>. It is similar to the <u>DES</u> algorithm but is a smaller algorithm and has fewer parameters than DES. It was made for educational purposes so that understanding DES would become simpler. It is a block cipher that takes a block of plain text and converts it into ciphertext. It takes a block of 8 bit.


It is a symmetric key cipher i.e. they use the same key for both encryption and decryption. In this article, we are going to demonstrate key generation for s-des encryption and decryption algorithm. We take a random 10-bit key and produce two 8-bit keys which will be used for encryption and decryption.

Key Generation Concept: In the key generation algorithm, we accept the 10-bit key and convert it into two 8 bit keys. This key is shared between both sender and receiver.




Login

Register



In the key generation, we use three functions:

1. Permutation P10




2. Permutation P8




Login

Register



3. Left Shift



Step 1: We accepted a 10-bit key and permuted the bits by putting them in the P10 table.

Key = 1 0 1 0 0 0 0 1 0
(k1, k2, k3, k4, k5, k6, k7, k8, k9, k10) = (1, 0, 1, 0, 0, 0, 0, 0, 1, 0)

P10 Permutation is: P10(k1, k2, k3, k4, k5, k6, k7, k8, k9, k10) = (k3, k5, After P10, we get 1 0 0 0 0 1 1 0 0

Step 2: We divide the key into 2 halves of 5-bit each.

Login

Register

$$1 = 0 0 0 0 1, r = 1 1 0 0 0$$

Step 4: Combine both keys after step 3 and permute the bits by putting them in the P8 table. The output of the given table is the first key K1.

```
After LS-1 combined, we get 0 0 0 0 1 1 1 0 0 0 P8 permutation is: P8(k1, k2, k3, k4, k5, k6, k7, k8, k9, k10) = (k6, k3, k4) After P8, we get Key-1 : 1 0 1 0 0 1 0 0
```

Step 5: The output obtained from step 3 i.e. 2 halves after one bit left shift should again undergo the process of two-bit left shift.

```
Step 3 output - l = 0 0 0 0 1, r = 1 1 0 0 0
After two bit shift - l = 0 0 1 0 0, r = 0 0 0 1 1
```

Step 6: Combine the 2 halves obtained from step 5 and permute them by putting them in the P8 table. The output of the given table is the second key K2.

```
After LS-2 combined = 0 0 1 0 0 0 0 0 1 1 P8 permutation is: P8(k1, k2, k3, k4, k5, k6, k7, k8, k9, k10) = (k6, k3, k After P8, we get Key-2 : 0 1 0 0 0 0 1 1
```

Final Output:

Key-1 is: 1 0 1 0 0 1 0 0 Key-2 is: 0 1 0 0 0 0 1 1



Login

Register

Page: 1 2 3

Know more

Like 4

Previous

RECOMMENDED ARTICLES

Simplified Data Encryption

O5 Strength of Data encryption standard (DES)

31, Jan 20

O2 Simplified International Data Encryption Algorithm (IDEA)

Standard | Set 2

17, Jan 20

01, Mar 21

O6 Advanced Encryption Standard (AES)

15, Oct 21

Difference between Software Encryption and Hardware Encryption

05, Feb 21

Public Key Encryption

28, May 19

Data encryption standard (DES) | Set 1

17, Aug 18

Difference Between Symmetric and Asymmetric Key Encryption

29, Jan 20

Login

Register

Article Contributed By:



Vote for difficulty

Easy

Normal

Medium

Hard

Expert

Improved By: guptaaman9981

Article Tags: cryptography, Computer Networks

Practice Tags: cryptography, Computer Networks

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments





5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Login

Register

--...p-a...,

About Us

Careers

Privacy Policy

Contact Us

Copyright Policy

Algorithms

Data Structures

Languages

CS Subjects

Video Tutorials

Web Development

Web Tutorials

HTML

CSS

JavaScript

Bootstrap

Contribute

Write an Article

Write Interview Experience

Internships

Videos

@geeksforgeeks, Some rights reserved

