

# Implementation of Diffie-Hellman Algorithm

Difficulty Level : Medium • Last Updated : 24 Oct, 2021

## Background

**Elliptic Curve Cryptography (ECC)** is an approach to public-key cryptography, based on the algebraic structure of elliptic curves over finite fields. ECC requires a smaller key as compared to non-ECC cryptography to provide equivalent security (a 256-bit ECC security has equivalent security attained by 3072-bit RSA cryptography).

For a better understanding of Elliptic Curve Cryptography, it is very important to understand the basics of the Elliptic Curve. An elliptic curve is a planar algebraic curve defined by an equation of the form

$$y^2 = x^3 + ax + b$$


Where 'a' is the co-efficient of x and 'b' is the constant of the equation

The curve is non-singular; that is, its graph has no cusps or self-intersections (when the characteristic of the Co-efficient field is equal to 2 or 3).

In general, an elliptic curve looks like as shown below. Elliptic curves can intersect almost 3 points when a straight line is drawn intersecting the curve. As we can see, the elliptic curve is symmetric about the x-axis. This property plays a key role in the algorithm.



# Start Your Coding Journey Now!

[Login](#)
[Register](#)


## Diffie-Hellman algorithm

The Diffie-Hellman algorithm is being used to establish a shared secret that can be used for secret communications while exchanging data over a public network using the elliptic curve to generate points and get the secret key using the parameters.

- For the sake of simplicity and practical implementation of the algorithm, we will consider only 4 variables, one prime  $P$  and  $G$  (a primitive root of  $P$ ) and two private



[Data Structures](#) [Algorithms](#) [Interview Preparation](#) [Topic-wise Practice](#) [C++](#) [Java](#) [Python](#)

secret key to encrypt.

## Step by Step Explanation

Alice

Bob

Public Keys available =  $P, G$

Public Keys available =  $P, G$

Private Key Selected =  $a$

Private Key Selected =  $b$

# Start Your Coding Journey Now!

[Login](#)
[Register](#)

$$x = G^{mod P}$$

$$y = G^{mod P}$$

Exchange of generated keys takes place

Key received = y

key received = x

Generated Secret Key =

Generated Secret Key =

$$k_a = y^a \text{ mod } P$$

$$k_b = x^b \text{ mod } P$$

Algebraically, it can be shown that

$$k_a = k_b$$

Users now have a symmetric secret key to encrypt

## Example:

Step 1: Alice and Bob get public numbers  $P = 23$ ,  $G = 9$

Step 2: Alice selected a private key  $a = 4$  and  
Bob selected a private key  $b = 3$

Step 3: Alice and Bob compute public values

Alice:  $x = (9^4 \text{ mod } 23) = (6561 \text{ mod } 23) = 6$

Bob:  $y = (9^3 \text{ mod } 23) = (729 \text{ mod } 23) = 16$

Step 4: Alice and Bob exchange public numbers

Step 5: Alice receives public key  $y = 16$  and  
Bob receives public key  $x =$

## Start Your Coding Journey Now!

[Login](#)[Register](#)

Step 7: 9 is the shared secret.

### Implementation:

#### C

```
/* This program calculates the Key for two persons
using the Diffie-Hellman Key exchange algorithm */
#include<stdio.h>
#include<math.h>

// Power function to return value of a ^ b mod P
long long int power(long long int a, long long int b,
                    long long int P)
{
    if (b == 1)
        return a;

    else
        return (((long long int)pow(a, b)) % P);
}

//Driver program
int main()
{
    long long int P, G, x, a, y, b, ka, kb;

    // Both the persons will be agreed upon the
    // public keys G and P
    P = 23; // A prime number P is taken
    printf("The value of P : %lld\n", P);

    G = 9; // A primitive root for P, G is taken
    printf("The value of G : %lld\n\n", G);

    // Alice will choose the private key a
    a = 4; // a is the chosen private key
    printf("The private key a for Alice : %lld\n", a);
    x = power(G, a, P); // gets the generated key

    // Bob will choose the private key
```

# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
ka = power(y, a, P); // Secret key for Alice
kb = power(x, b, P); // Secret key for Bob

printf("Secret key for the Alice is : %lld\n", ka);
printf("Secret Key for the Bob is : %lld\n", kb);

return 0;
}
```

## Java

```
// This program calculates the Key for two persons
// using the Diffie-Hellman Key exchange algorithm
class GFG{

// Power function to return value of a ^ b mod P
private static long power(long a, long b, long p)
{
    if (b == 1)
        return a;
    else
        return (((long)Math.pow(a, b)) % p);
}

// Driver code
public static void main(String[] args)
{
    long P, G, x, a, y, b, ka, kb;

    // Both the persons will be agreed upon the
    // public keys G and P

    // A prime number P is taken
    P = 23;
    System.out.println("The value of P:" + P);

    // A primitive root for P, G is taken
    G = 9;
    System.out.println("The value of G:" + G);

    // Alice will choose the private key
```

# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Bob will choose the private key b
// b is the chosen private key
b = 3;
System.out.println("The private key b for Bob:" + b);

// Gets the generated key
y = power(G, b, P);

// Generating the secret key after the exchange
// of keys
ka = power(y, a, P); // Secret key for Alice
kb = power(x, b, P); // Secret key for Bob

System.out.println("Secret key for the Alice is:" + ka);
System.out.println("Secret key for the Bob is:" + kb);
}
}

// This code is contributed by raghav14
```

## Python3

```
from random import randint

if __name__ == '__main__':

    # Both the persons will be agreed upon the
    # public keys G and P
    # A prime number P is taken
    P = 23

    # A primitive root for P, G is taken
    G = 9

    print('The Value of P is :%d'%(P))
    print('The Value of G is :%d'%(G))

    # Alice will choose the private key a
    a = 4
```

# Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

b = 3
print('The Private Key b for Bob is :%d'%(b))

# gets the generated key
y = int(pow(G,b,P))

# Secret key for Alice
ka = int(pow(y,a,P))

# Secret key for Bob
kb = int(pow(x,b,P))

print('Secret key for the Alice is : %d'%(ka))
print('Secret Key for the Bob is : %d'%(kb))

```

## Javascript

```

<script>

// This program calculates the Key for two persons
// using the Diffie-Hellman Key exchange algorithm

// Power function to return value of a ^ b mod P
function power(a, b, p)
{
    if (b == 1)
        return a;
    else
        return((Math.pow(a, b)) % p);
}

// Driver code
var P, G, x, a, y, b, ka, kb;

// Both the persons will be agreed upon the
// public keys G and P
// A prime number P is taken
P = 23;
document.write("The value of P:" + P + ">");

```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// a is the chosen private key
a = 4;
document.write("The private key a for Alice:" +
               a + "<br>");

// Gets the generated key
x = power(G, a, P);

// Bob will choose the private key b
// b is the chosen private key
b = 3;
document.write("The private key b for Bob:" +
               b + "<br>");

// Gets the generated key
y = power(G, b, P);

// Generating the secret key after the exchange
// of keys
ka = power(y, a, P); // Secret key for Alice
kb = power(x, b, P); // Secret key for Bob

document.write("Secret key for the Alice is:" +
               ka + "<br>");
document.write("Secret key for the Bob is:" +
               kb + "<br>");

// This code is contributed by Ankita saini

</script>
```

### Output:

The value of P : 23

The value of G : 9

The private key a for Alice : 4

The private key b for Bob : 3





## Start Your Coding Journey Now!

[Login](#)[Register](#)

contribute, you can also write an article using [contribute.geeksforgeeks.org](https://contribute.geeksforgeeks.org/) or mail your article to [contribute@GeeksforGeeks.org](mailto:contribute@GeeksforGeeks.org). See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

### GATE – CS

#### Preparation Test Series

■ All you need to complete your GATE preparation.

[Enrol Now](#)

Like 25

[Previous](#)[Next](#)

## RECOMMENDED ARTICLES

Page : [1](#) [2](#) [3](#)

01

**Implementation of a Back-off  
Algorithm for CSMA/CD**

17, Apr 20

05

**Approaches to Information Security  
Implementation**

26, Feb 20

# Start Your Coding Journey Now!

[Login](#)[Register](#)

03

## Hellman Algorithm between Client and Server

18, Oct 18

07

## UDP Server-Client implementation in C

22, Mar 18

04

## Hamming code Implementation in Java

02, Aug 19

08

## TCP Server-Client implementation in C

12, Sep 18

### Article Contributed By :

**GeeksforGeeks**

### Vote for difficulty

Current difficulty : [Medium](#)[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)**Improved By :** [nalasivam](#), [ShJos](#), [raghav14](#), [ankita\\_saini](#), [sooda367](#)**Article Tags :** [Computer Networks](#)**Practice Tags :** [Computer Networks](#)[Improve Article](#)[Report Issue](#)

# Start Your Coding Journey Now!

[Login](#)[Register](#)[Load Comments](#)

5th Floor, A-118,  
Sector-136, Noida, Uttar Pradesh - 201305

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

## Company

- [About Us](#)
- [Careers](#)
- [Privacy Policy](#)
- [Contact Us](#)
- [Copyright Policy](#)

## Learn

- [Algorithms](#)
- [Data Structures](#)
- [Languages](#)
- [CS Subjects](#)
- [Video Tutorials](#)

## Web Development

- [Web Tutorials](#)
- [HTML](#)
- [CSS](#)
- [JavaScript](#)
- [Bootstrap](#)

## Contribute

- [Write an Article](#)
- [Write Interview Experience](#)
- [Internships](#)
- [Videos](#)



@geeksforgeeks , Some rights reserved

