

Introduction to Web Science 101

Assignment 1

Victor Nwala

Department of Computer Science
Old Dominion University
09/08/2014


CS 495/595 ASSIGNMENT № 1

Victor Nwala, Old Dominion University

09/08/2014

QUESTION ONE SOLUTION

To answer this question I designed a simple html form on my localhost that looks somewhat like what we see below.



First name: Victor


Last name: Nwala

OK

The form is submitted, to the page below.

```
1 <html>
2 <head>
3 </head>
4 <body>
5
6
7 <?php
8
9 echo 'Your Name is'." ".$_POST['firstname']." ".$_POST['lastname'];
10
11 ?>
12
13
14
15
16 </body>
17 </html>
```


And the output is seen below also.



I also did the same using a curl command, I used curl -d to send parameters to my final page, I used -i to include the html response and -o to output the result into a new file (newFile.html). The command looks like this:

```
1 curl -d "firstname=VICTOR&lastname=NWALA&press=OK"-i
2 www.cs.odu.edu/~vnwala/post_2.php -o "newFile.html"
```

I opened the saved file in my browser and the result is seen below:



The image above display the output and includes the html response.

QUESTION TWO SOLUTION

Python program that receives three arguments, school name, time and url and gives the current scores.

The requirements of the program are to: a)Receive three arguments b)Run continuously until interrupted by hitting ctrl c on the keyboard.

To explain what I did I will highlight some import steps in my python code below.

Line 8, 9 and 31 ensures the function runs infinitely.

Line 11, with the help of BeautifulSoup and urllib2 library, the url is opened and stored as a huge string.

Line 12, the table rows of class game link which contains the scores are located and stored. Subsequently, the table data of classes home and away are stored also.

Line 26 and 28 ensure that scores will only be printed if the school name entered is located.

Line 30 ensures that the program sleeps for the number of seconds received in the argument.

Line 33 and 34 call the parent function only if the arguments are entered properly.

```
1 import time
2 import sys
3 import urllib2
4 from bs4 import BeautifulSoup
5
```

```

6
7 def extractScores(school, seconds,url):
8     count = 1
9     while ( count > 0):
10        seconds = float (seconds)
11        soup = BeautifulSoup(urllib2.urlopen(url).read())
12        for row in soup('table')[1].findAll('tr', {'class':'game link'}):
13            away = row.find('td', {'class':'away'})
14            away = away.em.text
15
16            awayScore = row.find('td', {'class':'score'}).findAll('span')
17            awayScore = awayScore[0].text
18
19            home = row.find('td', {'class':'home'})
20            home = home.em.text
21
22
23            homeScore = row.find('td', {'class':'score'}).findAll('span')
24            homeScore = homeScore[1].text
25
26            if (away.lower() == school.lower() or home.lower() == ↵
                school.lower()):
27
28                print away + " " + awayScore + "," + home+ " " + homeScore
29
30                time.sleep(seconds)
31            count = count + 1
32
33 if len(sys.argv) == 4:
34     extractScores(sys.argv[1],sys.argv[2],sys.argv[3])
35 else:
36     print "Error, wrong argument count, do this instead: ", sys.argv[0] + ↵
        " schoolName, url and time"

```

I entered the school name Texas A&M, and a given url and asked to program to sleep for 10 seconds before running again, as shown below.

```

1 vnwala@template:~$ python scoreBoard.py "Texas A&M" "http://sports.yahoo.↵
    com/college-football/scoreboard/?week=1&conf=all" 10

```


```

Terminal - vnwala@template: ~
File Edit View Terminal Tabs Help
vnwala@template:~$ python scoreBoard.py "Texas A&M" 10 "http://sports.yahoo.com/college-football/scoreboard/?week=1&conf=all"
Texas A&M 52, South Carolina 28
Texas A&M 52, South Carolina 28
Texas A&M 52, South Carolina 28
Texas A&M 52, South Carolina 28
Texas A&M 52, South Carolina 28
Texas A&M 52, South Carolina 28

```

I should state at this point that a fellow classmate, Alexander Nwala, help me with the logic of my Python Program.

QUESTION THREE SOLUTION



DEFINITIONS:

1. IN: Pages with no in-links or in-links from IN pages and out-links to pages in IN, SCC, Tendrils, or Tubes.
2. SCC: Pages with in-links from IN or SCC and out-links to OUT or SCC. There exists some path of links from every page in SCC to every other page in SCC.
3. OUT: Pages with no out-links or out-links to other pages in OUT, and all in-links come from OUT, SCC, Tendrils, or Tubes.
4. Tendrils: Pages that can only be reached from IN or have only out-links to OUT.
5. Tubes: Pages that have in-links from IN or other pages in Tubes and out-links to pages in Tubes or OUT.
6. Disconnected: Pages that have no in-links from any other components and no out-links to other components. These pages may be linked to each other.

SOURCE:

<http://www.harding.edu/fmccown/classes/comp475-s13/web-structure-homework.pdf>

From the graph above, the pages (links), A, B, C, G can reach every other member of this group. Hence they consist of the SCC component of the Bow-Tie web Structure.

The page M has no in-links and out-links to pages in SCC, hence it can be called the IN component of the Bow-Tie web Structure.

The pages D and H have no out-links and its in-links come from SCC, hence its consists of the OUT component of the Bow-Tie web Structure.

The pages, L, I, J have only out-links to OUT, hence the are categorized as Tendrils, K is also categorized as a Tendril because it is connected to I.

The page N, has an in-link from IN (M) and out-links to an OUT page (D), hence N is categorized as a TUBE.

The pages E and F have no in-links from any other components and no out-links to other components, hence they are called the DISCONNECTED component of the Bow-Tie Web Structure.

SCC: A,B,C,G

IN: M

OUT: D,H

TENDRILS: L,I,J,K

TUBE: N

DISCONNECTED: E,F