

ISIO

A type safe implementation of *sprintf* and more.

Introduction.

Many C++ programmers who where previously C programmers miss the convenience and conciseness of the printf family of functions.

The new generation of c++ programmers don't know what they are missing.

Take this trivial example:

```
std::cout << std::setw(10) << std::dec << 99 << '\n';
```

With printf this would be:

```
printf("%10d\n", 99);
```

Even for this trivial example, the printf code is smaller and arguably more readable.

A more realistic example would be:

```
std::cout << std::setw(10) << std::setprecision(3) << std::fixed << std::showpos << 123.45 << '\n';
```

versus:

```
printf("%+10.3f\n", 123.45);
```

Then why not just use the functions from the *std::printf* family?

Because they are fragile and error prone. When the argument does not correspond exactly with what the format expects, the behavior is undefined and often results in wrong output or core dumps.

Also, when the number of arguments is less than what the format expects, all kinds of havoc can be caused.

The TSIO packages provides a type safe version of *printf*, *sprintf* and *fprintf* that write into output streams or *std::string*. It also offers many useful extensions.

Lastly, the TSIO package allows to write the above example as:

```
std::cout << fmt("%+10.3f") << 123.45 << '\n';
```

For more information on the standard printf family of functions, you can for example go to <http://en.cppreference.com/w/cpp/io/c/fprintf>.

Printf compatible functions.

The TSIO namespace contains the following printf compatible functions.

- `template <typename... Arguments>`
`int sprintf(std::string& dest, const char* format, const`
`Arguments&... arguments)`

sprintf formats the *arguments* according to the *format* and outputs the result into the string *dest*, replacing the current contents of *dest*.

- `template <typename... Arguments>`
`int addsprintf(std::string& dest, const char* format, const`
`Arguments&... arguments)`

addsprintf formats the *arguments* according to the *format* and outputs the result into the string *dest*, appending to the current contents of *dest*.

- `template <typename... Arguments>`
`int fprintf(std::ostream& dest, const char* format, const`
`Arguments&... arguments)`

fprintf formats the *arguments* according to the *format* and outputs the result into the output stream *dest*.

- `template <typename... Arguments>`
`int oprintf(const char* format, const Arguments&... arguments)`

fprintf formats the *arguments* according to the *format* and outputs the result into the output stream *std::cout*.

- `template <typename... Arguments>`
`int eprintf(const char* format, const Arguments&... arguments)`

fprintf formats the *arguments* according to the *format* and outputs the result into the output stream *std::cerr*.

- `template <typename... Arguments>`
`std::string fstring(const char* format, const Arguments&...`
`arguments)`

fstring formats the *arguments* according to the *format* and returns the result as a *std::string*.

All the *printf* compatible functions use a format string as defined for *std::printf*.

All the conversion specifiers, flags and other parameters are faithfully implemented except wide characters.

Length modifiers are ignored, because they are not required. This means that the for example format *"%d"* can be used with all integral types (*char*, *short*, *int*, *long*, *long long* and the corresponding unsigned variants).

Many useful extensions are provided as described in the next chapter.

Extensions.

The C and S format specifiers.

The C and S format specifiers will output a string, just like c or s commands, but will replace unprintable characters by either a dot (.) or, in the alternative form (#C and #S), by an escape sequence.

Example:

```
fstring("' %C %C'", '\x12', 'a')
```

produces

```
' . a '
```

and

```
fstring("' %#C %#C %#C'", '\a', 'a', '\x5')
```

produces

```
' \a a \005 '
```

Likewise

```
fstring("' %S'", "12\a\b\f34")
```

produces

```
'12...34'
```

and

```
fstring("%#S", "12\a\b\f34")
```

produces

```
'12\\a\\b\\f34'
```

The s format on different value types.

The `s` format specifier can be used for many data types, not just `const char*`. It will choose an appropriate format as follows:

- For boolean arguments it will output the string literal `true` or `false`.
- For other integral arguments it will format like the `i` specifier for signed values and like `u` for unsigned values.
- For floating point arguments it will format like the `g` specifier.
- For pointer arguments (except `const char*` of course) the `s` specifier is not implemented.
- The `s` format specifier accepts `std::string` as argument.

Example:

```
std::string str("This is a std::string");  
fstring("%s %s %s %s %s", 123, 234.567, true, false, str)
```

produces

```
'123 234.567 true false This is a std::string'
```

and

```
fstring("%06s %5.2s %10.3s", 123, 234.567, 98.765)
```

produces

```
'000123 2.3e+02          98.8'
```

Fill characters.

The *TSIO* package supports two types of fill characters: numeric and alphabetic fill characters.

Numeric fill characters are used in formatting numeric values. They are inserted between the sign or the radix indicator and the value.

The numeric fill character is specified by adding 'x to the format flags. The zeorofill flag (0) sets the numeric fill character to '0'.

Example:

```
fstring("%'*7d', %#'*7x", -23, 0xab)
```

produces:

```
- ****23', 0x***ab
```

The alphabetic fill characters are used in formatting both numeric and alphabetic data. They are inserted outside the value (including sign and radix indicator).

The alphabetic fill character is specified by adding "x to the format flags. Don't forget to escape the quote character in the format string.

Example:

```
fstring("%\"*7d', %#\"*7x", -23, 0xab)
```

produces:

```
****-23', ***0xab
```

and

```
fstring("%\"*20s", "abc")
```

produces:

```
*****abc
```


Centering text.

Text can be centered by adding the ^ flag to the format. The alphabetic fill character will be used to fill the areas left and right of the text.

The centering works on all values, numeric and alphabetic.

Example:

```
fstring("'%^20s'", "1234")
```

Produces:

```
'          1234          '
```

Containers as arguments.

When a `std::vector`, `std::array`, `std::set`, `std::unordered_set`, `std::multiset`, `std::unordered_multiset`, `std::deque`, `std::list` or `std::forward` is passed as a parameter, all elements of the container will be printed with the same format.

Example:

```
std::vector<int> v = {10, 200, 3000 };
fstring("vector { %10d }", v)
```

produces:

```
vector {          10          200         3000 }
```

The container format allows to format the elements of any class that has implementations for *begin* and *end*. The container format allows to add a prefix and postfix to every element being formatted.

The container format is specified with the `%[` format specifier. The syntax of this specifier is `%[xxxxx%fffyyy%]` where *xxxxx* is the prefix, *yyy* is the postfix and *fff* is the format to be used for each element.

An example will make this clear:

```
std::vector<int> v = { 9, 8, 7, 6 };
fstring("%[v=%d, %]", v)
//          ^^ prefix
//          ^^ format to be executed for each element
//          ^^ postfix
```

produces:

```
v=9, v=8, v=7, v=6,
```

The extra comma at the end of the output is of course annoying, but this can be cured with the `#` flag. This flag suppresses the postfix on the last element.

Example:

```
fstring("{ %[v=%d, %] }", v)
```

produces:

```
{ v=9, v=8, v=7, v=6 }
```

Since *begin* and *end* are declared for arrays, the following also works.

Example:

```
double fa[] = { 1.2, 2.3, 3.4, 4.55555 };  
fstring("{ %#[v=%.2f, %] }", fa)
```

produces:

```
{ v=1.20, v=2.30, v=3.40, v=4.56 }
```

Repeating formats.

The *tsio* package provides repeating formats. A repeating format is a format that is executed "abcbcabcbcabcb" for multiple consecutive arguments.

A repeating format starts with `%n{` where `n` is an integer value that specifies the repeat count and ends with `%}`. All the text and format specifications between these markers are repeated. Enough parameters must be passed to satisfy all these format specifiers.

Example:

```
fstring("%10{ -=%} ")
```

produces:

```
-=-=-=-=-=-=
```

and

```
fstring("repeat: %3{%4d%}", 1, 22, 333)
```

produces:

```
repeat:    1  22 333
```

Repeating format can be nested without any practical limit.

It is possible to specify the repeat count at execution time using the `*` notation.

Example:

```
fstring("%*{abc%}", 5)
```

produces:

```
abcbcabcbcabcb
```

The *fmt* io manipulator.

The *tsio::fmt* io manipulator allows to set *std::ostream* flags according to a printf like format.

Although the format uses the same syntax as *tsio::sprintf*, it does not implement all its features. Only the features are implemented that have an equivalent in the *ostream* flags.

For example, the *space if positive* flag from printf has no equivalence in *ostream*'

Some formats, like the *g* format reproduce different results.

An example will make its usage clear:

```
std::string str;
short s = 123;
int i = 42;
float f = float(234.567);
double d = 345.678;
const char* ch = "Don't panic";

std::cout << fmt("%-15s") << ch << ', ' << fmt("%12i") << s
    << ', ' << fmt("d") << i << ', ' << fmt("12.2f") << f
    << ', ' << fmt("%7.1E") << d << ', ' << fmt("a") << d
    << fmt() << '\n';
```

produces:

```
"Don't panic      ,          123,42,
    234.57,3.5E+02,0x1.59ad916872b02p+8"
```

The *fmt* io manipulator clears all *ostream* flags when it starts. It then sets the flag as required by the format. After the next value is printed, the flags keep the newly set values except *width* that is reset to default.

The call to *fmt()* without any format resets all flags to their default value.