cells (32-byte big-endian elements of the BLS12-381 scalar field), in order:

header $n_{up} + 2^{64} \cdot n_{id}$	n_{id} vote IDs, then n_{up} slots, 4 per cell: $\lceil (n_{id}+n_{up})/4 \rceil$ cells	ballot of slot 1: $2 \cdot n_f$ point cells	ballot of slot 2: $2 \cdot n_f$ point cells

…	ballot of slot n_{up}: $2 \cdot n_f$ point cells	zero cells up to 4096 · nBlobs

split into blobs of 4096 cells: $T = 1 + \lceil (n_{id}+n_{up})/4 \rceil + 2 \cdot n_f \cdot n_{up}$ cells in total, $nBlobs = \lceil T / 4096 \rceil \le 32$

packed cell $= a \cdot 2^{189} + b \cdot 2^{126} + c \cdot 2^{63} + d$

0	a (63 bits)	b (63 bits)	c (63 bits)	d (63 bits)

vote IDs enter without their top bit (they lie in $[2^{63}, 2^{64})$); slots are already below 2^{63}

point cell: $(x, y) \to y + 2^{254} \cdot (x \bmod 2)$

0	x mod 2	y (254 bits, BN254 field element)

the identity $(0, 1)$ encodes as 1; $p_{BN254} + 2^{254} < q_{BLS}$, so every cell is a field element

binding to the commitments

for each blob b with commitment com_b:

$z_b = H(\text{processID} \,||\, \text{stateRoot}^{old} \,||\, com_b) \bmod q_{BLS}$

$y_b = p_b(z_b)$, computed in the program

$\text{blobsDigest} = H(com_1 \,||\, y_1 \,||\, \ldots)$

the registry opens each (com_b, z_b, y_b) with the point-evaluation precompile against the blob's versioned hash

Slots are listed once, in increasing order, whether they hold a new vote, an overwrite, or a silent refresh ($n_{id} = n$, $n_{up} = n + |R|$). The results accumulator is not published; observers recompute it from the old and new ballots of the listed slots.