

Assignment 2: Dynamic Programming project

Francis Vo, Soo-Hyun Yoo

November 5, 2012

1 Problem 1: mmmm ... pork

1.1 Mathematical

1.1.1 Objective function

$$\begin{array}{rclclcl} & 8 * ham_f & + & 12 * ham_r & + & 11 * ham_o & + \\ \max & 4 * bellies_f & + & 12 * bellies_r & + & 7 * bellies_o & + \\ & 4 * picnics_f & + & 13 * picnics_r & + & 9 * picnics_o \end{array}$$

1.1.2 Constraints

$$\begin{array}{rcl} ham_f + ham_r + ham_o & \leq & 480 \\ bellies_f + bellies_r + bellies_o & \leq & 400 \\ picnics_f + picnics_r + picnics_o & \leq & 230 \\ ham_r + bellies_r + picnics_r & \leq & 420 \\ ham_o + bellies_o + picnics_o & \leq & 250 \end{array}$$

1.2 Standard

1.2.1 Objective function

$$\begin{array}{rclclcl} & 8 * ham_f & + & 12 * ham_r & + & 11 * ham_o & + \\ \max & 4 * bellies_f & + & 12 * bellies_r & + & 7 * bellies_o & + \\ & 4 * picnics_f & + & 13 * picnics_r & + & 9 * picnics_o \end{array}$$

1.2.2 Constraints

$$\begin{array}{rcl} ham_f + ham_r + ham_o + ham_remain & = & 480 \\ bellies_f + bellies_r + bellies_o + bellies_remain & = & 400 \\ picnics_f + picnics_r + picnics_o + picnics_remain & = & 230 \\ ham_r + bellies_r + picnics_r + smoke_reg & = & 420 \\ ham_o + bellies_o + picnics_o + smoke_over & = & 250 \\ ham_remain, bellies_remain, picnics_remain, smoke_reg, smoke_over & \geq & 0 \end{array}$$

1.3 Matrix

$$\text{Max}(f' * x)$$

$$f' = (8 \quad 14 \quad 11 \quad 4 \quad 12 \quad 7 \quad 4 \quad 13 \quad 9)$$

$$a = \begin{pmatrix} 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 1 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 1 \\ 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 \end{pmatrix}$$

$$b = \begin{pmatrix} 480 \\ 400 \\ 230 \\ 420 \\ 250 \end{pmatrix}$$

$$x = \begin{pmatrix} ham_f \\ ham_r \\ ham_o \\ bellies_f \\ bellies_r \\ bellies_o \\ picnics_f \\ picnics_r \\ picnics_o \end{pmatrix}$$

1.4 Code

```

1  /* Decision variables */
2
3  var ham_f >=0;      /* ham */
4  var ham_r >=0;      /* ham */
5  var ham_o >=0;      /* ham */
6
7  var bellies_f >=0;  /* bellies */
8  var bellies_r >=0;  /* bellies */
9  var bellies_o >=0;  /* bellies */
10
11 var picnics_f >=0;   /* picnics */
12 var picnics_r >=0;   /* picnics */
13 var picnics_o >=0;   /* picnics */
14
15
16 /* Objective function */
17 maximize z: 8 * ham_f + 12 * ham_r + 11 * ham_o + 4 * bellies_f + 12 * bellies_r + 7 *
18             bellies_o + 4 * picnics_f + 13 * picnics_r + 9 * picnics_o;
19
20 /* Constraints */
21
22 s.t. Ham           : ham_f + ham_r + ham_o <= 480;
23 s.t. Bellies       : bellies_f + bellies_r + bellies_o <= 400;
24 s.t. Picnics       : picnics_f + picnics_r + picnics_o <= 230;
25 s.t. Smoke-Regular : ham_r + bellies_r + picnics_r <= 420;
26 s.t. Smoke-Overtime : ham_o + bellies_o + picnics_o <= 250;
27
28 end;

```

pork.mod

1.5 Solution

Total net profit: \$10,910

| | fresh | smoked on regular time | smoked on overtime |
|---------|-------|------------------------|--------------------|
| hams | 440 | 0 | 40 |
| bellies | 0 | 400 | 0 |
| picnics | 0 | 20 | 210 |

1.6 GNU Linear Programming Kit

We used a glpsol inputing a model file, pork.mod, and then it outputs a solution file, pork.sol. The command we used is “glpsol -m pork.mod -o pork.sol”

2 Problem 2: least squares isnt good enough for me

2.1 Mathematical

2.1.1 Objective function

min t

2.1.2 Constraints

for each point

$$\begin{aligned} |point.x - b| &\leq t \\ |a * (point.x) + b * (point.y) - c| &\leq t \end{aligned}$$

2.2 Standard

2.2.1 Objective function

min t

2.2.2 Constraints

for each point

$$\begin{aligned} point.x - b + point.v &= t \\ point.x - b &\geq -t \\ a * (point.x) + b * (point.y) - c + point.z &= t \\ a * (point.x) + b * (point.y) - c &\geq -t \\ point.v, point.z &\geq 0 \end{aligned}$$

2.3 Code

```
1 /* Decision variables */
2
```

```

3 var a;
4 var b;
5 var c;
6 var t;
7
8 /* Objective function */
9 minimize z: t;
10
11
12 /* Constraints */
13
14 s.t. point_x_high_1 : 1 - b <= t;
15 s.t. point_x_low_1 : 1 - b >= -t;
16
17 s.t. point_x_high_2 : 2 - b <= t;
18 s.t. point_x_low_2 : 2 - b >= -t;
19
20 s.t. point_x_high_3 : 3 - b <= t;
21 s.t. point_x_low_3 : 3 - b >= -t;
22
23 s.t. point_x_high_4 : 5 - b <= t;
24 s.t. point_x_low_4 : 5 - b >= -t;
25
26 s.t. point_x_high_5 : 7 - b <= t;
27 s.t. point_x_low_5 : 7 - b >= -t;
28
29 s.t. point_x_high_6 : 8 - b <= t;
30 s.t. point_x_low_6 : 8 - b >= -t;
31
32 s.t. point_x_high_7 : 10 - b <= t;
33 s.t. point_x_low_7 : 10 - b >= -t;
34
35 s.t. point_high_1 : a*(1)+b*(3)-c <= t;
36 s.t. point_low_1 : a*(1)+b*(3)-c >= -t;
37
38 s.t. point_high_2 : a*(2)+b*(5)-c <= t;
39 s.t. point_low_2 : a*(2)+b*(5)-c >= -t;
40
41 s.t. point_high_3 : a*(3)+b*(7)-c <= t;
42 s.t. point_low_3 : a*(3)+b*(7)-c >= -t;
43
44 s.t. point_high_4 : a*(5)+b*(11)-c <= t;
45 s.t. point_low_4 : a*(5)+b*(11)-c >= -t;
46
47 s.t. point_high_5 : a*(7)+b*(14)-c <= t;
48 s.t. point_low_5 : a*(7)+b*(14)-c >= -t;
49
50 s.t. point_high_6 : a*(8)+b*(15)-c <= t;
51 s.t. point_low_6 : a*(8)+b*(15)-c >= -t;
52
53 s.t. point_high_7 : a*(10)+b*(19)-c <= t;
54 s.t. point_low_7 : a*(10)+b*(19)-c >= -t;
55
56 end;

```

bestFit2.mod

2.4 Solution

$$a = -8.8$$

$$b = 5.5$$

$$c = 12$$

2.5 Plot




Figure 1: points and best fit line