

# Object Oriented Programming

Shaobai Kan

*chapter 6*

# Outline

- Dynamic allocation and de-allocation of memory spaces

- 
- 
- 

# *Dynamic allocation and de-allocation of memory spaces*

# Memory areas

**Fact.** Generally, programmers deal with five areas of memory

- Global name space
- The heap
- Registers
- Code space
- The stack

## Memory areas (continue...)

- **Global name space.** Global variables are in global name space.

## Memory areas (continue...)

- **Global name space.** Global variables are in global name space.
- **The stack.** Local variables are on the stack.

## Memory areas (continue...)

- **Global name space.** Global variables are in global name space.
- **The stack.** Local variables are on the stack.
- **Code space.** Code is in code space.

## Memory areas (continue...)

- **Global name space.** Global variables are in global name space.
- **The stack.** Local variables are on the stack.
- **Code space.** Code is in code space.
- **Registers.** are used for internal housekeeping functions, such as keeping track of the top of the stack and instruction pointer.




## Memory areas (continue...)

- **Global name space.** Global variables are in global name space.
- **The stack.** Local variables are on the stack.
- **Code space.** Code is in code space.
- **Registers.** are used for internal housekeeping functions, such as keeping track of the top of the stack and instruction pointer.
- **The heap.** About all remaining memory is given over to the heap; it is sometimes referred to as the free store.

# Visual representation: memory areas

**Five areas of memory**



# The heap

**Q.** Why should we bother to declare variables on the heap?

# The heap

**Q.** Why should we bother to declare variables on the heap?

- **Local variable.** The problem with local variables is that they don't persist; when the function returns, the local variables are thrown away.
- **Global variable.** Global variables solve that problem at the cost of unrestricted access throughout the program, which leads to the creation of code that is difficult to understand and maintain.

# The heap

**Q.** Why should we bother to declare variables on the heap?

- **Local variable.** The problem with local variables is that they don't persist; when the function returns, the local variables are thrown away.
- **Global variable.** Global variables solve that problem at the cost of unrestricted access throughout the program, which leads to the creation of code that is difficult to understand and maintain.

**A:** Putting data in the heap solves both of these problems.

# The heap (Continue...)

## Fact.

- The advantage to the **heap** is that the memory you reserve remains available until you explicitly free it; if you reserve memory on the heap while in a function, the memory is still available when the function returns.

# The heap (Continue...)

## Fact.

- The advantage to the **heap** is that the memory you reserve remains available until you explicitly free it; if you reserve memory on the heap while in a function, the memory is still available when the function returns.
- The advantage of accessing memory in this way, rather than using global variable, is that only functions with access to the pointer have access to data; it eliminates the problem of one function changing that data in unexpected and unanticipated ways.

# The heap (Continue...)

## Fact.

- The **stack** is cleaned automatically when a function returns; all local variables are removed from the stack.



# The heap (Continue...)

## Fact.

- The **stack** is cleaned automatically when a function returns; all local variables are removed from the stack.
- The heap is not cleaned until your program ends. It is your responsibility to free any memory that you've reserved when you are done with it; Otherwise, it will cause a **memory leak**.

# Using the new operator

**Fact.** In C++, the memory on the heap can be allocated by using the new operator; new is followed by the type of the object that you want to allocate.

# Using the new operator

**Fact.** In C++, the memory on the heap can be allocated by using the new operator; new is followed by the type of the object that you want to allocate.

Example 1.

```
unsigned short int * pPtr;  
pPtr = new unsigned short int;
```

# Using the new operator

**Fact.** In C++, the memory on the heap can be allocated by using the new operator; new is followed by the type of the object that you want to allocate.

Example 1.

```
unsigned short int * pPtr;  
pPtr = new unsigned short int;
```

Example 2.

```
unsigned short int * pPtr = new unsigned short int;
```

# Using the delete operator

**Fact.** When you are finished with your area of memory, you must call delete on the pointer; delete returns the memory to the heap.

# Using the delete operator

**Fact.** When you are finished with your area of memory, you must call delete on the pointer; delete returns the memory to the heap.

Example 1.

```
unsigned short int * pPtr = new unsigned short int;  
  
.....  
delete pPtr;
```

# Using the delete operator

**Fact.** When you are finished with your area of memory, you must call delete on the pointer; delete returns the memory to the heap.

Example 1.

```
unsigned short int * pPtr = new unsigned short int;  
  
.....  
delete pPtr;
```

**Fact.** When you delete the pointer, what you are really doing is freeing up the memory whose address is stored in the pointer.

# Operators: new and delete

## Example 1

```
// Allocating and deleting a pointer
# include <iostream>
using namespace std;

int main ( )
{
    int localVariable = 5;
    int * localPtr = & localVariable;
    int * heapPtr = new int (7);

    cout << "localVariable: " << localVariable << '\n';
    cout << "*localPtr: " << *localPtr << '\n';
    cout << "*heapPtr: " << *heapPtr << '\n';

    delete heapPtr;
    heapPtr = new int;
    *heapPtr = 9;
    cout << "*heapPtr: " << *heapPtr << '\n';
    delete heapPtr;
    return 0;
}
```



# Operators: new and delete (Continue...)

## Example 2

```
# include <iostream>
using namespace std;

struct Date
{
    int month;
    int day;
    int year;
};

int main ( )
{
    Date * datePtr = new Date;

    datePtr -> month = 2;
    datePtr -> day = 24;
    datePtr -> year = 2010;

    cout << "Date: " << datePtr -> month << '/' << datePtr -> day
          << '/' << datePtr -> year << endl;
    delete datePtr;
    return 0;
}
```