SOFTWARE ARCHITECTURE MODELING LANGUAGE

swa.ml 2.2

Complete language specification

Standard 2.2 / Parser 2.2 / Reference profile swaml-reference/2.2

PACKAGE
A closed context of top-level occurrences and connections

COMPONENT
Children, private data, typed ports and operations

USE CASE AND TEST
Subject operations and associated actor ports

Typed interfaces at every software boundary.

Embedded realtime systems, services and event-driven architectures.

10 November 2026 / Standard 2.2 / Reference implementation 3.1.0 / swa.ml contributors

Independent language design on a proposed KerML semantic foundation.

github.com/voidaliot/swaml

About this edition

STANDARD 2.2 / RELEASE EDITION, 10 NOVEMBER 2026

This book contains the complete swa.ml 2.2 language specification, every keyword in alphabetical order, formal execution rules, flat notation examples, an ontology and view guide, a reference simulation binding, the complete grammar, runnable model examples and the release notes for the syntax-preserving additions to 2.1. Source files are headerless and begin with packages; hosts select and pin parser 2.2 and the reference profile swaml-reference/2.2. A package is a closed context: its top-level occurrences, package connections, executable use cases and tests, and requirement links live side by side.

Normative chapters define syntax, validity, interface isolation, operation/state behavior, case scripts and mapping obligations. Tutorials and figures illustrate these rules. This independently authored language is not an OMG UML release or an AUTOSAR implementation. KerML export remains a proposed semantic mapping contract.

The standard uses MAJOR.MINOR versions: this is standard 2.2. The reference parser, validator, deterministic logical-time simulator and case runner of the reference implementation package 3.1.0 provide executable evidence; the package version follows its own SemVer lifecycle. A passing case is bounded evidence of one deterministic run, not proof. Production timing, runtime and platform mappings require the target binding and evidence defined in the normative chapters.

Navigation	How to use this PDF
Contents and bookmarks	Select a contents entry or use the PDF outline to open a chapter or section.
Cross-references	Links to included documents jump inside this book. Other repository links target the v2.2 release tag.
Code and tables	Code is selectable, numbered and wrapped without omitting source text. Tables repeat their headers across pages.
Source record	The build manifest lists every included source and its SHA-256 digest. Original source files are embedded as PDF attachments. The release includes a PDF checksum.

Original text and code: MIT license, copyright 2026 Catalin Ilie. Referenced standards retain their own terms; no standards PDFs are redistributed. Full license text appears at the end.

Contents

About this edition 2

swa.ml 2.2 keyword reference 10

Keyword: after . . . 10
Keyword: and . . . 10
Keyword: assert . . . 10
Keyword: associate . . . 10
Keyword: attribute . . . 10
Keyword: bool . . . 11
Keyword: by . . . 11
Keyword: byte . . . 11
Keyword: call . . . 11
Keyword: case . . . 11
Keyword: component . . . 11
Keyword: concurrent . . . 11
Keyword: connect . . . 12
Keyword: const . . . 12
Keyword: datatype . . . 12
Keyword: deadline . . . 12
Keyword: def . . . 12
Keyword: deploy . . . 12
Keyword: deployment . . . 12
Keyword: else . . . 12
Keyword: entry . . . 13
Keyword: enum . . . 13
Keyword: event . . . 13
Keyword: every . . . 13
Keyword: exit . . . 13
Keyword: fail . . . 13
Keyword: false . . . 13
Keyword: final . . . 13
Keyword: for . . . 14
Keyword: idempotent . . . 14
Keyword: if . . . 14
Keyword: import . . . 14
Keyword: in . . . 14
Keyword: include . . . 14
Keyword: initial . . . 14
Keyword: int . . . 14
Keyword: interruptible . . . 15
Keyword: kind . . . 15
Keyword: ms . . . 15
Keyword: name . . . 15

Keyword: not . . . 15
Keyword: ns . . . 15
Keyword: of . . . 15
Keyword: on . . . 16
Keyword: operation . . . 16
Keyword: optional . . . 16
Keyword: or . . . 16
Keyword: out . . . 16
Keyword: package . . . 16
Keyword: path . . . 16
Keyword: port . . . 17
Keyword: provides . . . 17
Keyword: publish . . . 17
Keyword: qos . . . 17
Keyword: real . . . 17
Keyword: receive . . . 17
Keyword: record . . . 17
Keyword: recursive . . . 17
Keyword: redefines . . . 18
Keyword: requirement . . . 18
Keyword: requires . . . 18
Keyword: return . . . 18
Keyword: returns . . . 18
Keyword: reversed . . . 18
Keyword: s . . . 18
Keyword: satisfy . . . 19
Keyword: schedule . . . 19
Keyword: send . . . 19
Keyword: specializes . . . 19
Keyword: start . . . 19
Keyword: state . . . 19
Keyword: string . . . 19
Keyword: test . . . 20
Keyword: times . . . 20
Keyword: to . . . 20
Keyword: true . . . 20
Keyword: try . . . 20
Keyword: uint . . . 20
Keyword: until . . . 20
Keyword: us . . . 20
Keyword: use . . . 21
Keyword: var . . . 21
Keyword: verify . . . 21
Keyword: view . . . 21
Keyword: void . . . 21
Keyword: wait . . . 21

Keyword: when . . . 21
Keyword: where . . . 21
Keyword: while . . . 22
Symbols and precedence . . . 22

swa.ml 2.2 language specification **23**

1. Normative set . . . 23
2. Precedence and scope . . . 23
3. Invariants . . . 23
4. Inventory . . . 24

1. Structure, names and types **25**

1.1 Names and documentation . . . 25
1.2 Components and occurrences . . . 25
1.3 State and lexical values . . . 26
1.4 Value domains . . . 26
1.5 Reuse and library boundaries . . . 26

2. Ports and communication **27**

2.1 Directed port members . . . 27
2.2 Structural compatibility . . . 27
2.3 Connectors and closure . . . 27
2.4 Versioned policies and queues . . . 28
2.5 Requests, replies and failure . . . 28

3. Operations, schedules and states **29**

3.1 Operations and effects . . . 29
3.2 Failure . . . 29
3.3 Statements and scopes . . . 29
3.4 Suspension and locks . . . 30
3.5 Schedule . . . 30
3.6 States . . . 31
3.7 Case scripts . . . 31

4. Deployment, cases, views and conformance **33**

4.1 Deployment . . . 33
4.2 Requirements, cases and package links . . . 33
4.3 Views . . . 34
4.4 Validation groups . . . 34
4.5 Evidence boundaries . . . 35

5. Proposed KerML semantic mapping **36**

5.1 Representation . . . 36
5.2 Required semantic library . . . 36
5.3 Traceability and claims . . . 36

6. Reference execution contract **37**

6.1 Lifecycle and time . . . 37
6.2 Lock and snapshot . . . 37
6.3 Values, flow and failure . . . 37
6.4 Communication . . . 38
6.5 Input ownership and interruption . . . 38
6.6 Evidence and resources . . . 38
6.7 Case runs . . . 39

7. Normalized model contract **40**

7.1 Identity and provenance . . . 40
7.2 Families . . . 40
7.3 Routes and queues . . . 41
7.4 Executable lowering . . . 41
7.5 Presentation and equivalence . . . 41

8. Conformance obligations and evidence **42**

8.1 Static obligations . . . 42
8.2 Runtime obligations . . . 43
8.3 Analysis, kernel and graphical claims . . . 43

9. Formal semantics **44**

9.1 Domains . . . 44
9.2 Typing schemas . . . 44
9.3 Transition schemas . . . 45
9.4 Projection and adequacy . . . 46

swa.ml 2.2 graphical notation **47**

swa.ml 2.2 canonical graphical catalog **48**

Packages and imports . . . 48
Typed copied values . . . 49
Component definitions and usages . . . 49
Indexed occurrence identity . . . 50
Attributes and lexical locals . . . 50
Mixed directed port members . . . 51
Policy-bearing connection . . . 51
Queue-free boundary forwarding . . . 52
Operations and nested ownership . . . 52
Expression calls and copied out values . . . 53
Runtime failure and lazy fallback . . . 53
Statements and decisions . . . 54
Loops and copied iteration . . . 54
Schedule entry and successful chaining . . . 55
Suspending wait and receive . . . 55
Armed interrupt and cancellation . . . 56
Ordered state transitions . . . 56
Platform Nodes and placement . . . 57

Requirements and package intent links . . . 57
Use cases, tests and associations . . . 58
Executable case scripts . . . 58
Seven library view definitions . . . 59
Declared and observed timing . . . 59
Owned documentation and lexical notes . . . 60
Typed expressions and operators . . . 60
Lexical and path spelling . . . 61

A. Complete concrete grammar 62

B. Grammar-to-semantics inventory 65

C. Model and library sources 72

01 hello . . . 72
02 realtime controller . . . 72
03 service pubsub . . . 73
04 stateful function . . . 74
05 values and flow . . . 75
06 mixed gateway . . . 75
07 client server . . . 76
08 service field . . . 77
09 component roots . . . 77
10 reusable qos . . . 78
11 autosar classic . . . 79
12 autosar adaptive . . . 80
13 web application . . . 80
14 cloud service . . . 81
15 component specialization . . . 82
16 requirements and views . . . 82
17 function timing . . . 83
18 control loops . . . 84
19 interruptible function . . . 84
20 classes and operations . . . 85
21 receive and try . . . 85
22 platform deployment . . . 86
23 multiplicity . . . 86
24 operation usage . . . 87
25 function completion . . . 87
26 boundary forwarding . . . 88
27 mixed port . . . 88
28 use cases . . . 89
29 executable cases . . . 90
30 associated integration . . . 93
31 case subject calls . . . 94
swaml 2.0 . . . 94

swa.ml 2.2 release **96**

Primary-subject operation calls . . . 96
Referencing associated test components . . . 96
Publication and compatibility . . . 96

Quick start: swa.ml 2.2 **97**

swa.ml 2.2 usage guide **98**

A first model . . . 98
Reuse structure without sharing state . . . 98
Choose the value's lifetime . . . 99
Compute with operations . . . 99
Connect components . . . 99
Serve and request a value . . . 100
Schedule and suspend deliberately . . . 100
Receive, interrupt and model state . . . 100
Describe deployment, intent and views . . . 100
Validate and repair . . . 101
Test explicitly associated components . . . 102

AI authoring with swa.ml 2.2 **103**

Build a model from intent . . . 103
Validate-fix loop . . . 103
Common diagnostics . . . 104

Architecture patterns **105**

Ontology and views **106**

swa.ml 2.2 reference simulation **107**

Statement sources . . . 108
Use cases and tests . . . 108

Requirements, documentation and intent **110**

swa.ml 2.2 worked diagrams **111**

Directed ports and explicit connections . . . 111
Forwarding preserves boundary direction . . . 111
Schedule and success chaining . . . 112
Operation-owned ordered states . . . 112
Indexed placement on platform Nodes . . . 113
Declared contracts and observed intervals . . . 113

swa.ml 2.2 implementation status **114**

Reference implementation . . . 114
Deliberate implementation limits . . . 115

Tool integration 117

Standard and implementation version policy 118

Standard versions . . . 118
Implementation packages . . . 119
Preparing an edition . . . 119
Existing publication history . . . 119

ADR 0016: swa.ml 2.0 restart 120

ADR 0017: Readable names and structured use cases 121

Context . . . 121
Decision . . . 121
Consequences . . . 121

ADR 0019: Package context, executable cases and package links 122

Context . . . 122
Decision . . . 122
Implementation choices . . . 124
Consequences . . . 125

ADR 0020: Associated software components in tests 126

Context . . . 126
Decision . . . 126
Consequences . . . 126

ADR 0021: Normal subject calls from use cases and tests 127

Decision . . . 127
Access boundary . . . 127
Sequential actor replies . . . 127
Validation evidence . . . 127

D. License 128

USER REFERENCE / CONCERN AND KEYWORD NAVIGATION

swa.ml 2.2 keyword reference

Generated from spec/keywords.json and the normative grammar. Examples here are grammar fragments; complete runnable models are in the usage guide and examples. 15 contextual words remain legal names outside their positions. call appears in the on call schedule trigger and in on call branches of case scripts.

after · and · assert · associate · attribute · bool · by · byte · call · case · component · concurrent · connect · const · datatype · deadline · def · deploy · deployment · else · entry · enum · event · every · exit · fail · false · final · for · idempotent · if · import · in · include · initial · int · interruptible · kind · ms · name · not · ns · of · on · operation · optional · or · out · package · path · port · provides · publish · qos · real · receive · record · recursive · redefines · requirement · requires · return · returns · reversed · s · satisfy · schedule · send · specializes · start · state · string · test · times · to · true · try · uint · until · us · use · var · verify · view · void · wait · when · where · while

Keyword: after

Introduces a state timer, receive timeout or success schedule dependency.

Context: Ordered state transitions. **Grammar:** ScheduleEntry, Receive, Transition. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: and

Used in typed expressions and operators; see its grammar contexts and normative constraints.

Context: Typed expressions and operators. **Grammar:** FilterAnd, AndExpression. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: assert

Used in runtime failure and lazy fallback; see its grammar contexts and normative constraints.

Context: Runtime failure and lazy fallback. **Grammar:** Assert. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: associate

Records that a top-level occurrence of the package takes part in a use case or test other than as its subject.

Context: Use cases, tests and associations. **Grammar:** Association, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: attribute

Declares typed occurrence state or an immutable requirement value.

Context: Attributes and lexical locals. **Grammar:** Attribute, PortMember. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: bool

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: by

Names the design that a satisfy claim refers to, or the test that a verify claim refers to.

Context: Requirements and package intent links. **Grammar:** Satisfaction, Verification, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: byte

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: call

Serves a provided operation as an on call schedule trigger, or answers a request at an actor port as an on call branch of a case script.

Context: Schedule entry and successful chaining. **Grammar:** ScheduleEntry, ReceiveBranch. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: case

Completes the use case keyword pair use case.

Context: Use cases, tests and associations. **Grammar:** CaseKind, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: component

Declares a reusable definition or a distinct owned occurrence.

Context: Component definitions and usages. **Grammar:** ComponentDef, ComponentUsage. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: concurrent

Permits overlapping non-writing snapshot activations.

Context: Schedule entry and successful chaining. **Grammar:** ScheduleEntry. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: connect

Joins compatible ports; boundary-to-child derives forwarding.

Context: Policy-bearing connection. **Grammar:** Connect. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: const

Makes an attribute immutable for its occurrence.

Context: Attributes and lexical locals. **Grammar:** Attribute. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: datatype

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** DataType. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: deadline

Used in schedule entry and successful chaining; see its grammar contexts and normative constraints.

Context: Schedule entry and successful chaining. **Grammar:** ScheduleEntry. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: def

Used in component definitions and usages; see its grammar contexts and normative constraints.

Context: Component definitions and usages. **Grammar:** ComponentDef, PortDef, QosPolicy, Operation, ViewDef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: deploy

Used in platform nodes and placement; see its grammar contexts and normative constraints.

Context: Platform Nodes and placement. **Grammar:** Placement. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: deployment

Places software root occurrences on platform Node occurrences.

Context: Platform Nodes and placement. **Grammar:** Deployment. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: else

Used in statements and decisions; see its grammar contexts and normative constraints.

Context: Statements and decisions. **Grammar:** If. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: entry

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** StateAction. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: enum

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** EnumType. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: event

Used in directed port members; see its grammar contexts and normative constraints.

Context: Directed port members. **Grammar:** PortMember. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: every

Used in schedule entry and successful chaining; see its grammar contexts and normative constraints.

Context: Schedule entry and successful chaining. **Grammar:** ScheduleEntry. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: exit

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** StateAction. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: fail

Used in runtime failure and lazy fallback; see its grammar contexts and normative constraints.

Context: Runtime failure and lazy fallback. **Grammar:** Fail. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: false

Used in typed expressions and operators; see its grammar contexts and normative constraints.

Context: Typed expressions and operators. **Grammar:** Literal. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: final

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** State. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: for

Used in loops and copied iteration; see its grammar contexts and normative constraints.

Context: Loops and copied iteration. **Grammar:** For, ForEach. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: idempotent

Used in directed port members; see its grammar contexts and normative constraints.

Context: Directed port members. **Grammar:** PortMember. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: if

Used in statements and decisions; see its grammar contexts and normative constraints.

Context: Statements and decisions. **Grammar:** If. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: import

Used in packages and imports; see its grammar contexts and normative constraints.

Context: Packages and imports. **Grammar:** Import. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: in

Used in attributes and lexical locals; see its grammar contexts and normative constraints.

Context: Attributes and lexical locals. **Grammar:** Argument, ForEach. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: include

Adds a subject selection to a view.

Context: Seven library view definitions. **Grammar:** ViewSelection. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: initial

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** OperationBody. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: int

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: interruptible

Used in armed interrupt and cancellation; see its grammar contexts and normative constraints.

Context: Armed interrupt and cancellation. **Grammar:** Interruptible. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: kind

Used in seven library view definitions; see its grammar contexts and normative constraints.

Context: Seven library view definitions. **Grammar:** FilterComparison, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: ms

Used in lexical and path spelling; see its grammar contexts and normative constraints.

Context: Lexical and path spelling. **Grammar:** Duration, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: name

Used in seven library view definitions; see its grammar contexts and normative constraints.

Context: Seven library view definitions. **Grammar:** FilterComparison, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: not

Used in typed expressions and operators; see its grammar contexts and normative constraints.

Context: Typed expressions and operators. **Grammar:** FilterPrimary, UnaryExpression. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: ns

Used in lexical and path spelling; see its grammar contexts and normative constraints.

Context: Lexical and path spelling. **Grammar:** Duration, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: of

Used in use cases, tests and associations; see its grammar contexts and normative constraints.

Context: Use cases, tests and associations. **Grammar:** Deployment, Scenario, View. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: on

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** ScheduleEntry, Receive, Interruptible, StateAction, Transition, Deployment, Placement. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: operation

Declares executable behavior; def supplies a reusable signature/body.

Context: Operations and nested ownership. **Grammar:** PortMember, Operation, OperationUsage. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: optional

Used in directed port members; see its grammar contexts and normative constraints.

Context: Directed port members. **Grammar:** PortUsage. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: or

Used in suspending wait and receive; see its grammar contexts and normative constraints.

Context: Suspending wait and receive. **Grammar:** Receive, FilterOr, OrExpression. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: out

Used in attributes and lexical locals; see its grammar contexts and normative constraints.

Context: Attributes and lexical locals. **Grammar:** Argument. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: package

Used in packages and imports; see its grammar contexts and normative constraints.

Context: Packages and imports. **Grammar:** Package. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: path

Used in seven library view definitions; see its grammar contexts and normative constraints.

Context: Seven library view definitions. **Grammar:** FilterComparison, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: port

Used in directed port members; see its grammar contexts and normative constraints.

Context: Directed port members. **Grammar:** PortDef, PortUsage. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: provides

Offers an attribute/event or implements an operation member.

Context: Directed port members. **Grammar:** PortMember. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: publish

Used in directed port members; see its grammar contexts and normative constraints.

Context: Directed port members. **Grammar:** Send. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: qos

Used in policy-bearing connection; see its grammar contexts and normative constraints.

Context: Policy-bearing connection. **Grammar:** QosPolicy. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: real

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: receive

Used in suspending wait and receive; see its grammar contexts and normative constraints.

Context: Suspending wait and receive. **Grammar:** ScheduleEntry, ReceiveBranch, Interruptible, Transition. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: record

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** RecordLiteral. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: recursive

Used in seven library view definitions; see its grammar contexts and normative constraints.

Context: Seven library view definitions. **Grammar:** ViewSelection. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: redefines

Used in component definitions and usages; see its grammar contexts and normative constraints.

Context: Component definitions and usages. **Grammar:** ComponentUsage, Attribute, PortUsage, Connect, Operation, OperationUsage. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: requirement

Used in requirements and package intent links; see its grammar contexts and normative constraints.

Context: Requirements and package intent links. **Grammar:** Requirement. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: requires

Receives an attribute/event or requests an operation member.

Context: Directed port members. **Grammar:** PortMember. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: return

Used in expression calls and copied out values; see its grammar contexts and normative constraints.

Context: Expression calls and copied out values. **Grammar:** Return. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: returns

Declares the result type; omitted result is void.

Context: Operations and nested ownership. **Grammar:** PortMember, Operation. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: reversed

Flips each direction of a port usage.

Context: Directed port members. **Grammar:** PortUsage, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: s

Used in lexical and path spelling; see its grammar contexts and normative constraints.

Context: Lexical and path spelling. **Grammar:** Duration, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: satisfy

Records the intent that a component definition or occurrence path declared in the package satisfies a requirement.

Context: Requirements and package intent links. **Grammar:** Satisfaction. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: schedule

Owns trigger-to-operation bindings.

Context: Schedule entry and successful chaining. **Grammar:** Schedule. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: send

Used in directed port members; see its grammar contexts and normative constraints.

Context: Directed port members. **Grammar:** Send. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: specializes

Used in component definitions and usages; see its grammar contexts and normative constraints.

Context: Component definitions and usages. **Grammar:** ComponentDef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: start

Used in schedule entry and successful chaining; see its grammar contexts and normative constraints.

Context: Schedule entry and successful chaining. **Grammar:** ScheduleEntry. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: state

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** State. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: string

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: test

Declares a test: a package member that may name a top-level subject occurrence with of and is the target of verify links.

Context: Use cases, tests and associations. **Grammar:** CaseKind, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: times

Introduces a once-evaluated uint loop limit.

Context: Loops and copied iteration. **Grammar:** While, Until, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: to

Introduces a state transition target or the case of an associate link.

Context: Ordered state transitions. **Grammar:** Transition, Association, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: true

Used in typed expressions and operators; see its grammar contexts and normative constraints.

Context: Typed expressions and operators. **Grammar:** Literal. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: try

Catches runtime expression failures with a lazy compatible fallback.

Context: Runtime failure and lazy fallback. **Grammar:** TryExpression. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: uint

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: until

Runs body then tests the stopping condition.

Context: Loops and copied iteration. **Grammar:** Until. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: us

Used in lexical and path spelling; see its grammar contexts and normative constraints.

Context: Lexical and path spelling. **Grammar:** Duration, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: use

Starts the use case keyword pair use case: a package member that names a top-level occurrence of its package as subject with of.

Context: Use cases, tests and associations. **Grammar:** CaseKind, Name. **Name use:** contextual.

Normative rule · Graphical catalog.

Keyword: var

Used in attributes and lexical locals; see its grammar contexts and normative constraints.

Context: Attributes and lexical locals. **Grammar:** LocalVariable. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: verify

Records the intent that a test of the package verifies a requirement; many-to-many.

Context: Requirements and package intent links. **Grammar:** Verification. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: view

Used in seven library view definitions; see its grammar contexts and normative constraints.

Context: Seven library view definitions. **Grammar:** ViewDef, View. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: void

Used in typed copied values; see its grammar contexts and normative constraints.

Context: Typed copied values. **Grammar:** TypeRef. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: wait

Suspends for a duration and releases the serial lock.

Context: Suspending wait and receive. **Grammar:** Wait. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: when

Used in ordered state transitions; see its grammar contexts and normative constraints.

Context: Ordered state transitions. **Grammar:** Transition. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: where

Used in seven library view definitions; see its grammar contexts and normative constraints.

Context: Seven library view definitions. **Grammar:** ViewSelection. **Name use:** reserved.

Normative rule · Graphical catalog.

Keyword: while

Used in loops and copied iteration; see its grammar contexts and normative constraints.

Context: Loops and copied iteration. **Grammar:** While. **Name use:** reserved.

Normative rule · Graphical catalog.

Symbols and precedence

Colon means typed by; returns names results. Dot is containment/member access; :: qualifies packages. Brackets express fixed extents, multiplicity or indexing. Parentheses group conditions/arguments and connector endpoints. There are no source arrows. Operators in ascending precedence are or, and, equality, numeric comparison, addition/subtraction, multiplication/division/remainder and unary not/minus. Only and/or short-circuit. Formal docs use /** */; ordinary comments remain lexical.

NORMATIVE / LANGUAGE CONTRACT

swa.ml 2.2 language specification

Edition: 2.2 · **Parser:** 2.2 · **Reference profile:** swaml-reference/2.2 · **Status:** release edition, 10 November 2026. The published 2.1 edition and its artifacts are unchanged. 2.2 release notes describe syntax-preserving associated-component test access and normal primary-subject calls from both case kinds. Release notes describe the changes and the migration from 2.0; the published 2.0 edition remains under its legacy v2.0.0 tag.

swa.ml is the Software Architecture Modeling Language: a textual language for explicit software structure, communication and executable behavior. ADR 0016 accepts the clean restart; ADR 0019 adds the package context and executable cases of 2.1. The language has one component concept and one operation concept. It does not accept 1.x source. Published books and PDFs retain their original bytes.

1. Normative set

The concrete grammar defines tokens and parse structure. These chapters define validity and meaning:

1. Structure and types
2. Ports and communication
3. Operations, schedules and states
4. Deployment, cases, views and conformance
5. Proposed KerML mapping
6. Execution contract
7. Normalized model
8. Conformance obligations
9. Formal semantics

Graphical notation, its catalog and the mapping inventory complete the contract. Usage, quick start, AI authoring and examples are informative. Implementation status distinguishes implemented checks from contracts and future evidence.

2. Precedence and scope

MUST and MUST NOT state requirements; SHOULD requires a documented reason for deviation; MAY grants permission. Grammar acceptance is insufficient when prose constraints fail. Unknown syntax and unsupported editions MUST be rejected. The host selects parser 2.2 and pins its package revision; files are headerless. Formatting never changes validity.

The language is closed. No generic UML/SysML constructs, host code, dynamic topology, generics, overloading, multiple inheritance, recursion or global mutable values are implicit. Platform Nodes model placement identities rather than hardware execution. A simulator run does not prove schedulability, absence of races, universal verification, KerML conformance or graphical editability.

3. Invariants

- **I1 Boundary:** every exchange between different component occurrences crosses owned typed port members and an explicit connection/forwarding route.
- **I2 Ownership:** components own private attributes, children and operations. Operations own nested operations and flow or states. Nested operations never capture enclosing locals/parameters.

- **I3 Provenance:** every provided event/attribute has an emitting operation; every required event/attribute and provided operation has exactly one input owner. Forwarded boundaries have no local handler/emitter.
- **I4 Values:** payloads, arguments, results, out values and array iterations are copied. Definition identity never merges occurrence stores. Records/enums retain nominal identity.
- **I5 Policy:** each connection occurrence has a complete effective pinned policy and independent queues. Forwarding has neither. Attributes keep latest values regardless of event/request capacity.
- **I6 Presentation:** views select existing semantic identities; drawings do not create behavior or routes. Layout stays separate; declared timing and observed evidence remain distinguishable.

Local calls, startup, periodic releases, waits, state timers and same-owner after dependencies are local lifecycle/computation. Operator and test inputs use ordinary source components, emitting operations, ports and routes; no destination injection or simulator function-release API exists.

4. Inventory

Family	Ownership and meaning
Package, import	Flat multi-segment namespace and explicit visibility
datatype, enum, arrays	Finite nominal records/enums and copied fixed arrays
Component definition/usage	Reusable structure or distinct occurrence; usage body is anonymous specialization
Attribute/local/parameter	Occurrence state, lexical local, copied in or success-only out
Port definition/usage/member	Directed typed boundary; optional and reversed prefixes
Connection/forwarding	Policy-bearing opposite directions or queue-free boundary alias
Operation definition/declaration/usage	Reusable signature/body or owned executable, nested without captures
Schedule/entry	Trigger binding, dispatch arguments, deadline and concurrency
State/transition	Ordered nested receive/timer reactions; final completion
Deployment/placement	Software occurrences placed on platform Node occurrences
Requirement/case/view	Immutable intent; package-owned use cases and tests with an optional top-level subject occurrence, package associate/satisfy/verify links; stable selection union

Definitions have qualified declaration identity. Occurrences have root plus indexed child paths. Activations add unique run identity. All transformations preserve these distinctions and source provenance.

NORMATIVE / LANGUAGE CONTRACT

1. Structure, names and types

Normative chapter of swa.ml 2.2.

1.1 Names and documentation

Files contain packages without a version header. Package names may contain several :: segments; packages do not nest. import P; exposes P's top-level declarations and requires that package in the loaded workspace. Qualified references are unambiguous; ambiguous short imports are errors independent of load order. Names are unique in their scope; a package's elements and named package connections share one namespace. No overloads or implicit imports exist. The contextual words associate, by, case, kind, name, path, reversed, test, times, to and use and the duration units ns, us, ms and s remain legal names outside their syntactic positions. Other literal words in the grammar are reserved.

A package is a closed context. It owns definitions, top-level component occurrences, package connections between those occurrences, use cases, tests and the associate, satisfy and verify links that record intent about them. Definitions, requirements and other declarations may be imported; occurrences are never connected, made a case subject or associated across packages.

A name is written as a basic name, an ASCII letter or underscore followed by ASCII letters, digits or underscores, or as a quoted name between single quotes, such as 'Withdraw cash', 'Bestellübersicht' or 'state'. Inside quotes, `\'` writes a quote and `\\` a backslash; other escapes, line breaks and control characters are invalid. The name is the quoted content: 'Pump' and Pump are the same name, and a quoted reserved word is an ordinary name. A quoted name is not empty, contains no '.', ':', '[' or ']', which delimit paths, and separates words by single spaces without leading or trailing space (SW2001). Tools write a basic name whenever one is legal and quote otherwise. Qualified names and paths combine spellings, as in Shop::'Order Service'.port; a string literal holding a path, such as a view filter value, contains the unquoted names.

Strings use double quotes and the portable escapes for quote, backslash, newline, carriage return and tab. Ordinary `//` and `/* */` comments are lexical annotations. Each declaration owns at most one formal `/** */` doc, first inside its body or immediately before the semicolon of a leaf. Documentation and comments do not execute.

1.2 Components and occurrences

component def declares a reusable type. component name: Type; creates a usage; a package-owned usage is a top-level occurrence and an execution root. An untyped package usage may own inline topology. Child usages require definitions. Closure is checked per package over all top-level occurrences and package connections (section 2.3). Definitions may be reusable open libraries; an unused definition is not an execution root.

A component whose effective members, including specialization, have ports but no operations, schedule entries or parts is interface-only. It needs no implementation: the emission and input-owner rules of section 2.1 do not apply to it. In a run it does nothing on its own; only a case script acts through its ports. Actors (external systems) and test stubs are written as interface-only components.

A usage body is an anonymous specialization with explicit whole-member replacement and added members, including typed roots. Single specializes inheritance is acyclic. An inherited member with the same name requires redefines; a nonexistent inherited target is an error. Replacement preserves category, types, operation signature and body category. Child component definitions may specialize the replaced type. Port replacement preserves directed compatibility and optionality. Attributes preserve constness and type. No partial operation-body merge, super dispatch or implicit shadowing exists.

A literal positive multiplicity [n] on a child creates n separate occurrences. Paths index every array usage with a literal in range, as in wheels[2].svc. Connector loops and port arrays do not exist. Composition is finite and acyclic. Definition identity does not identify an occurrence or a store.

1.3 State and lexical values

attribute declares component-owned mutable state; const attribute fixes its value per occurrence. Both are explicitly typed and may be redefined with a different compatible initializer in a usage. Initializers are pure and cannot read mutable state. Requirements own immutable typed attributes regardless of the const spelling.

var declares an activation/block local. in is the default parameter direction and is immutable; out parameters are mutable with success-only copy-back. Live names cannot shadow another live local, parameter or attribute. A nested operation sees its own parameters, its nested operations and the owning component's attributes, never enclosing parameters or locals. Local data access never traverses child components or ports.

1.4 Value domains

bool, byte (0-255), uint (0-9007199254740991), int (-9007199254740991 through 9007199254740991), finite real and string are primitive domains. void has no values and is only an operation result. Records and enums are nominal by qualified declaration identity. A datatype declares every field explicitly; a record construction supplies each once, with no extra fields. Enum literals use Type.literal; a live value named Type takes precedence, so a qualified enum reference avoids ambiguity.

Fixed arrays have positive safe extents, copied elements and invariant element type/extent. Array literals are checked elementwise against their destination type. Index expressions are integral; literal out-of-range indexes fail statically and dynamic bounds fail at runtime. In-place field/index assignment and reference values are absent.

Scalar widening is byte to uint to int to real. Known integral literals may initialize smaller integral domains if in range. General computed integral assignments are range-checked by the backend where permitted by the type rule; real never implicitly narrows. Integral arithmetic yields int; slash or a real operand yields real. Integer operations are exact within the safe domain and overflow fails. Division/remainder by zero and non-finite reals fail. Equality is recursive and type-compatible; ordering is numeric. Only and/or short-circuit. The grammar defines precedence.

1.5 Reuse and library boundaries

Package operation definitions use only parameters and nested operations. Their usages inherit the signature; an optional body replaces the whole body. Calls in an inherited component body resolve by name in the concrete occurrence's effective members, with signature preservation checked on redefinition. Call graphs are acyclic. No other component's operation or calculation is a fallback name resolution target.

The versioned source libraries are Swaml::Math, Swaml::Calls, Swaml::Qos, Swaml::Views and Swaml::Platform. They are always loaded but imported explicitly. Math provides abs, min, max, checked floor/round/trunc conversion to int, Unicode scalar length and concat. floor/round/trunc/length are explicitly identified host intrinsics in the reference library; round ties toward positive infinity. Their backend semantics and range failures remain required.

NORMATIVE / LANGUAGE CONTRACT

2. Ports and communication

Normative chapter of swa.ml 2.2.

2.1 Directed port members

A port def owns named provides/requires attribute, event and operation members. An attribute carries one typed value, an event has copied in parameters, and an operation has in/out parameters and an optional returns result. Only operation members may be idempotent. Interfaces, interface kinds, versions, roles and separate signals do not exist.

A component uses port p: Definition; or an inline port body. reversed flips every member direction. optional is a prefix that waives that port's closure requirement; it does not waive required ports elsewhere on a forwarding chain. A provided attribute/event is emitted by this side; a provided operation is implemented by this side. Requires means the opposite.

Every provided attribute/event MUST have syntactic operation emission provenance. Every required attribute/event and provided operation MUST have exactly one owner: a schedule entry, one stateful operation's transition set, one receive statement or one interrupt region. Multiple alternative transitions in that one stateful operation are one owner. A forwarded boundary is never also locally handled or emitted. An interface-only component (section 1.2) is exempt from these provenance and owner rules.

All input stimuli, including operator/test drivers, are ordinary typed emissions from validated source operations or case scripts through routes; a case script emits only at the ports of its associated interface-only occurrences. Hidden harness releases and destination injection are forbidden. An unconnected optional request fails unavailable. An optional unconnected event/attribute emission has no recipient and remains observable.

2.2 Structural compatibility

Connection compares names independently of declaration order or port-definition identity. Every requires member on either side has a provides member of the same name and kind on the peer. Extra provides are permitted. For attribute/event delivery the provided payload is assignable to the required payload. For operation in parameters the required type is assignable to the provided type; out parameters reverse this variance. The provided result is assignable to the required result. Directions and parameter arity agree. Records and enums are nominal; numeric widening is permitted. Every missing/mismatched member produces an individual diagnostic.

Forwarding compares a boundary and immediate child's port in the same direction. The child supplies every boundary member with preserved direction and compatible payload/signature. Child requirements cannot be lost at the boundary. This aliases identities rather than generating messages.

2.3 Connectors and closure

connect (a, b); joins owned ports or ports of immediate children. A child with multiplicity requires a literal index. Name and policy are optional: connect link: Reliable (a, b);. Endpoints are unordered.

A connect may also be a package member. Each end of a package connection is occurrence.port, where occurrence is a top-level component occurrence declared in the same package; a nested path, a definition or an imported occurrence is an error (SW2004). A package connection is always a connection, never forwarding, and follows the same compatibility, duplicate, policy and idempotence rules. It cannot redefine.

Boundary-to-child endpoints derive forwarding when same-direction compatibility holds. Forwarding has no queue or policy; a policy is an error. Each boundary and child port is forwarded at most once. Other endpoints derive a connection using opposite-direction compatibility. Invalid endpoints report the applicable

compatibility failures. Self connections and duplicate endpoint pairs, including duplicates after forwarding resolution, are errors.

Closure is checked per package. Every nonoptional port of every occurrence of the package's top-level occurrences MUST resolve through any forwarding aliases to a connection: inside its component as before or, for a port of a top-level occurrence, through package connections. Closure inside a component is unchanged. A required attribute or operation has exactly one peer after forwarding. Event-only required ports permit multiple peers. A connector owns its queue identities per expanded occurrence, direction and member; sharing a named policy never shares queues. Distinct connections remain independent under fanout. Partial fanout effects committed before a failed offer remain committed.

2.4 Versioned policies and queues

A named qos def is typed by Swaml::Qos::Policy and supplies complete valid delivery, ordering, capacity, overflow and requestTimeout fields, plus optional maxLatency/maxAge. Values use the typed Delivery, Ordering and Overflow enums. Inline policies and per-use overrides do not exist. Each effective use is checked, including inherited connections and idempotency obligations.

Default is atMostOnce, fifo, capacity 16, reject, requestTimeout 1s, without latency/age bounds. Latest is atMostOnce/fifo/1/dropOldest/1s. Reliable is atLeastOnce/fifo/16/reject/1s. BestEffort is bestEffort/unordered/16/dropNewest/1s. These are pinned library values, always inspectable. atLeastOnce requests require an idempotent provided operation declaration; the declaration alone does not prove actual idempotence.

Policy buffering applies to events and requests. Attribute members keep only the latest pending value independently of capacity and overflow. fifo preserves order within its queue. Unordered allows other orders, although the deterministic reference interpreter chooses insertion order. Overflow rejects the offer with a runtime failure or discards the selected oldest/newest message observably. Age discards are observable; latency assumptions are contract obligations. A backend identifies delivery and failure assumptions explicitly.

2.5 Requests, replies and failure

A required operation is called as p.member(args). Its timeout comes from the route policy. Each request has a unique correlation and its response returns on the same member/route in reverse. Successful result and out values are copied back together; failure copies neither. Timeout, unavailable, rejected, transport and remoteFailure are failure reasons recorded as Swaml::Calls::CallFailure values or local runtime kinds in evidence. The model cannot inspect the reason.

A request suspends and releases the caller's serial lock. Timeout and reply at the same timestamp resolve as timeout; terminal correlations never reopen. Late replies are suppressed observably. Interruption cancels the local request continuation and correlation; the server continues and its committed effects remain. The interrupted terminal is not a catchable failure. try catches expression failures and supplies a compatible lazy fallback; bare calls propagate failure to the activation.

NORMATIVE / LANGUAGE CONTRACT

3. Operations, schedules and states

Normative chapter of swa.ml 2.2.

3.1 Operations and effects

An operation declaration always has parentheses and an optional returns T result; omission means void. operation def is package-owned reusable behavior. An operation usage has a type after a colon, no parentheses/result, and optionally replaces the whole inherited body. Names are unique and call graphs acyclic. Nested operations precede executable statements/states and never capture enclosing locals/parameters. A body owns flow or states directly; the body grouping has no executable identity.

Calls are expressions. A void call is a statement; a non-void result cannot be silently discarded. Calls with out arguments are statements; each out argument is a mutable compatible local, out parameter or component attribute. In/out values are copied and out copy-back occurs only after successful whole return. An operation of a component cannot invoke a different component by a structural path; it must use its own required port operation. Case scripts have the explicitly limited subject/helper access of section 3.7. Stateful operations are activated by their schedule rather than called locally.

Effects are inferred transitively through the acyclic call graph: pure, reads state, writes state, communicates, suspends. The implementation MUST also retain a writes flag when a higher effect dominates, so communicating/suspending callees cannot conceal a write. Passing an attribute as out is a write. Attribute initializers are pure. State guards may only be pure or read state. Concurrent schedule entries cannot write state through any reachable callee or out argument.

Suspending calls may be the whole var initializer, assignment right side or expression statement, optionally wrapped in try; these must be ordinary statement values, not for-header initializers or updates. Evaluate the call before the loop when its result is needed there. Suspending calls cannot be embedded in arithmetic, call arguments, return values or predicates. Other expressions can have nonsuspending effects. Arguments evaluate left to right; only and/or short-circuit. Declarations and source order do not select overloads or change resolution.

3.2 Failure

Runtime failures unwind the current expression/frame/activation without rolling back committed effects. try(e, fallback) catches all runtime expression failures from valid source, including arithmetic, ranges, indexes, assert/fail in called operations and remote failures. Fallback is assignable to the expression type and evaluated only on failure. Nested try is valid. Void try(e) explicitly ignores failure; a void fallback can run recovery behavior.

Static errors are never caught. Interrupts and deadline/activation/resource violations bypass try. The failure reason is recorded in evidence and unavailable as an implicit binding. Void has no value; completion is not a sentinel value. Non-void flow must structurally return or fail on every path; a positive-extent copied for-in body or an until body with a proven positive/no limit can establish this, while a dynamic possibly-zero limit cannot; bounded/unbounded loops that can execute zero times are insufficient to establish a return.

3.3 Statements and scopes

var declares a typed local; assignment replaces a copied mutable cell. if requires bool. while tests first; until executes at least once unless its explicit limit is zero, and stops when its bool condition becomes true. Optional n times takes a uint-compatible expression evaluated once at entry; reaching the limit exits normally. for uses an initializer-local scope, bool condition, body and assignment update. for (x: T in values) iterates one copied fixed-array snapshot with a fresh element/body scope each time. Locals do not leak from blocks. There is no break, continue, do, bound or forEach syntax.

wait D suspends for a positive duration. on receive p.m(bindings) { ... } or receive ... or after D { ... } waits for one input or optional timeout. Each payload is explicitly bound, each member has that statement as exclusive owner, and input received before the statement waits stays in the connector queue. Without timeout the wait is unbounded, subject to an entry deadline and host limits. Selecting a branch consumes one message once.

interruptible { body } on receive p.m(bindings) { handler } arms an unnamed region only while the protected body, including its called frames, is running or suspended. Input while inactive is discarded and traced; the validator warns. Input while armed transfers within the same activation, cancels protected continuation/local request, preserves outer locals/deadline and committed effects, and then executes the handler. Protected block locals do not escape. Nested regions unwind to the selected owning region. A server handling a cancelled request is not cancelled. Regions are prohibited in stateful operations; concurrent regions are permitted only when transitively non-writing and consume input once in activation order in the reference backend.

send p.attribute(v) updates a provided attribute; publish p.event(args) emits a provided event. Return completes a frame, fail fails it, assert requires a bool and fails when false. Private state writes, emissions and successful local call effects remain committed when a later statement fails.

3.4 Suspension and locks

Every component occurrence has one serial lock. Serial dispatch evaluates/copies schedule arguments under this lock. wait, requests, receive and idle state-machine waits release it. Resumption reacquires it and reads live attributes. Other activations may run and modify state while a serial activation is suspended. Activation locals remain its own copies. Concurrent entries overlap and read the dispatch snapshot throughout, including after resumption, and never write state.

A stale-read warning identifies a pre-suspension state read that may affect a later write. Recheck live state after resuming. This warning is conservative and is not a race-freedom proof. A successful static check does not establish scheduling, termination or deadlock freedom.

3.5 Schedule

A component owns at most one schedule block. Effective entries inherit and are replaced by repeating their (trigger, operation) identity. Duplicate identities in one authored block are errors. Trigger identity includes a receive/call member, an every period, or an after predecessor. One operation can have several entries.

Trigger	Release and signature
on start	Once after the initialization barrier
on every D	At root epoch + kD, k at least 1; deadline defaults to D
on receive p.m(bindings)	One activation per received required event/attribute
on call p.m(bindings)	Serve a provided operation; typed result/out values form the reply
after predecessor	Fresh activation after successful whole same-owner predecessor completion and unlock

Entry arguments evaluate and copy at dispatch. Non-call entries bind void flow with no out parameters; after targets are parameterless void flow. Predecessors are scheduled same-owner operation names, never paths/qualified names/port members; the effective after graph is acyclic. Failure releases nothing. A fresh activation has its own release/deadline/locals/snapshot/backlog accounting; results and parameters are not forwarded. Stateful success means reaching final, not becoming idle after a reaction.

An explicit deadline is positive. An every entry's deadline cannot exceed its period. Deadline omission elsewhere is permitted; a host may impose additional documented validation requirements. concurrent is

entry-local and requires a non-writing, non-stateful operation. Source WCET, timing blocks and root profiles do not exist; target bindings own execution-cost evidence.

3.6 States

A stateful operation is parameterless void and has exactly one on start entry. initial names one owned state. States own at most one on entry and one on exit block plus ordered receive/timer transitions. A receive transition binds payload, optionally tests a pure/read-state bool guard, and names its target with to. after D is relative to the state update, before entry actions begin. Entry actions finish before a transition can run; if entry suspends past a timer expiry, the earliest elapsed timer is selected on resumption before queued input. Timers with equal expiry use declaration order. Evaluate competing enabled transitions in declaration order and take the first. There are no transition names, priorities or completion transitions.

A reaction runs exit, transition effect, state update and entry in that order. Timers are invalidated by state exit and stale firings are observable discards. Unhandled input does not reset the current state timer. Every state is graph-reachable from initial; a final state has no outgoing transitions or exit action. Reaching final runs entry and completes the whole operation once. Hierarchical/orthogonal states and physical preemption are outside the language.

3.7 Case scripts

A use case or test whose body holds statements after its optional documentation is a case script (ADR 0019). Its statements are the statement language of section 3.3: var, assignment to its own locals, send, publish, calls, on receive … or receive … or after D, wait, if, while, until, for, for in, assert, fail and return. A case owns no nested operations, states, schedule entries or interrupt regions. A case with statements needs of; a case without statements records intent only.

A script is the environment of its subject. Its endpoints are occurrence.port.member, where occurrence is a top-level component occurrence of the case's package that is not the subject, is associated with the case by associate occurrence to Case; and is interface-only. send and publish emit a provided attribute or event of that actor port; on receive waits for a required attribute or event of it; a call such as customer.panel.withdraw(200) requests a required operation and suspends like any request. on call occurrence.port.op(bindings) { … } is a further branch of on … or …, allowed only in case scripts, that answers a request for a provided operation of the actor port. Inside it return v; is the reply exactly like the result of a served operation: out bindings are mutable and their values return with the reply, a non-void branch returns or fails on every path, and a failure inside the branch replies with a remote failure and fails the case. Any other return ends the case and has no value. Operations keep port.member endpoints and serve requests through schedule on call entries.

Both case kinds may call operations of their exact primary subject, such as atm.withdraw(20), using its normal serial context (ADR 0021). The operation may communicate through its own ports, receive and wait; the case resumes on return. Stateful operations remain on-start only, and suspending calls obey the whole-expression rule. The call is local within the case activation, not a fresh schedule release or an implicit port request.

A use case cannot inspect private attributes or directly call subject parts or associated components. A test may additionally read attributes of its subject, explicitly associated software component occurrences and the single parts inside those roots, including record fields, such as atm.dispensedToday or atm.dispenser.count. Helper calls on those extra owners remain restricted to operations that neither communicate nor suspend. A referenced root must be an executed, non-multiple software occurrence of the same package; platform roots have no runtime store. Association grants no ownership and does not select execution roots. Dotted value reads retain lexical local precedence; dotted operation calls retain their occurrence-call namespace. A case never assigns component attributes directly; assignment targets only the script's own locals and out bindings. Reads observe the live store under the target's serial lock. Calls borrow the occurrence's actual execution context; suspension releases its lock and resumption reads live state. Results and output values copy back only on successful return, after restoring the caller context.

SW2010 reports a script without of, an actor that is not associated or not interface-only, the subject used as an actor, private reads or non-subject direct calls from a use case, and test inspection outside the subject and explicitly associated software roots. SW2004 reports emission and call endpoints of the wrong shape, kind or direction and SW2005 input endpoints; SW2006 reports on call outside case scripts, communicating or suspending test-helper calls outside the primary subject, on call branches without a reply on every path and interrupt regions in cases; SW2002 reports values, bindings and results.

NORMATIVE / LANGUAGE CONTRACT

4. Deployment, cases, views and conformance

Normative chapter of swa.ml 2.2.

4.1 Deployment

Swaml::Platform supplies Node, Platform, Partition and Process component definitions. Node specialization owns only const attributes and child Nodes, with no operations, ports, connectors or schedule. Optional ref: string retains an external model identity for the host; it is not required for swa.ml validity and is never silently resolved as a software path. Buses, hardware timing, core/task allocation and operating-system scheduling are target-translation concerns.

A package deployment Name of Root on PlatformRoot owns placements. deploy on nodePath places the software root; deploy childPath on nodePath places that occurrence and descendants. A more specific path overrides an ancestor; an indexed path overrides a multiplicity family path. Exact paths are unique within one deployment. Every software path and literal index resolves in that root; every target resolves to a Node occurrence of that platform root. Only components are deployed. A top-level occurrence has at most one deployment in the workspace (SW2009 on each later one, at its root reference), and a package or component run applies it to that occurrence's tree; absence remains unallocated.

4.2 Requirements, cases and package links

A requirement owns immutable typed attributes and at most one doc. Requirements may be imported. Every relation that records intent about requirements and cases is a package member, never a component member, and none of them proves fulfillment.

A case is written use case Name of subject { … } or test Name of subject { … }. Cases are package members only; components never own cases. The of clause is optional and names a top-level component occurrence declared in the same package: the subject, the system under consideration. A case of a part is written in a package where that component is a top-level occurrence. A case without of, or without statements, records intent only. The case body owns optional documentation followed by optional statements; an executable subject must be a non-multiple software occurrence; platform roots do not execute. A case with statements is a script that may call its primary subject's operations and act through the ports of associated interface-only components (section 3.7), and runs in a fresh run of its package (section 6.7).

associate Occurrence to Case; records that a top-level component occurrence of the same package takes part in a use case or test of the same package. The occurrence is not the case's subject and each pair is associated at most once. In a use case, associated occurrences are its actors. In a test, an associated software occurrence also establishes an explicit white-box participant reference; it may have its own behavior, and its single parts may be read or called under section 3.7. Neither kind of case owns those components. Interface-only participants act as actor port proxies; they communicate with the subject only through ports and package connections, and a case script acts through the ports of the interface-only ones.

satisfy Requirement by design; claims that a component satisfies a requirement. design is a component definition or a top-level component occurrence declared in this package, optionally followed by nested parts such as Workbench.editor or cells[1]; a literal index is within the multiplicity. The claim is written in the package that declares the head of the design path; the requirement may be imported. Each requirement and design pair is claimed at most once.

verify Requirement by Test; claims that a test of this package verifies a requirement. A use case never verifies. The relation is many-to-many; each requirement and test pair is written at most once; the requirement may be imported.

The 2.0 and ADR 0018 case forms are removed rather than deprecated: verification case, cases inside components, actor roles, include and extend between cases, verify inside cases, declarative steps with from, to, via and after, satisfy inside components and satisfy ... of. They are ordinary syntax errors.

4.3 Views

Swaml::Views provides General, Interconnect, Case, Sequence, Grid, Flow and Timing. A view is typed by a definition, uses compact of subject or one or more include clauses, and owns optional documentation. Include may expand recursive descendants and apply a restricted Boolean where filter over name, kind and path, string comparisons, and/or/not. Filters never call operations or execute behavior. Selection is a union of occurrence identities in first-selection order; duplicates are removed stably.

General and Grid select named semantic elements except views. Interconnect selects components. Case selects packages, cases and components; Sequence selects operations, cases, components and packages. A selected package contributes its cases. Case draws each selected case inside the boundary of its subject occurrence, its associated occurrences outside it, and the satisfy and verify intent links of the package. Flow and Timing select operations, use cases and tests. Paths preserve definition/occurrence identity and explicit multiplicity indexes. Browser is navigation rather than an eighth view kind. General Box in box and Tree layouts retain exactly the same selected identities and topology; layout/collapse/geometry stay in presentation sidecars.

Flow covers statements, nested operation calls, loops, receive, interruption and function-owned states. Timing has declared and observed modes. Declared shows schedule release grid, causes, deadlines, static wait intervals and permitted concurrent overlap. Observed adds an identified trace, serial lock gaps, message latency, activation phases, terminal markers and open intervals; WCET/budget bars identify their target-binding/evidence source. A missing trace never produces fabricated observation. Views introduce no execution semantics.

4.4 Validation groups

Code	Static group
SW2000	Syntax and recovery diagnostics in machine-readable CLI output
SW2001	Names, quoted-name spelling, imports, uniqueness and forbidden live-name shadowing
SW2002	Value types, nominal shapes, domains, arguments/results and indexes
SW2003	Definition/usage, specialization, containment and whole-member redefinition
SW2004	Port shape, structural compatibility, endpoints, package connection ends, aliases, per-package closure/cardinality
SW2005	Single input owner and emission provenance; interface-only components are exempt
SW2006	Calls, nested scope, effects, returns, out arguments and suspension placement
SW2007	Schedule identity, signatures, deadlines and after graph
SW2008	Stateful signatures, scheduling, ordered states and reachability/finality
SW2009	Node content, deployment paths, indexes and specificity
SW2010	Requirement/case/view references, case subjects, associate, satisfy and verify links, the environment role and white-box access of case scripts
SW2011	Conservative stale-read warning
SW2012	Inactive interrupt-input discard warning

Code	Static group
SW2013	Complete typed policies and representable positive durations
SW2014	Canonical formatting differs, only in explicit formatting-check mode
SW2015	Retired in 2.1 together with the 2.0 case spellings; not reported

Every diagnostic includes a source range and stable code. Machine-readable diagnostics retain declaration identity and occurrence context when resolved. A suggested edit is supplied only for a safe unambiguous correction; tools must revalidate the resulting complete workspace before applying it. Parser recovery may suspend semantic checks on invalid syntax, but the document remains invalid and must not crash the service.

4.5 Evidence boundaries

S is syntax, V is static validity, E is reference execution behavior, A is an explicitly scoped analysis, K is validated kernel export and G is validated graphical source editing. Implementations report supported groups and evidence rather than promoting one level to another. Chapter 8 defines the obligations and status reports actual support. The reference simulator uses logical zero-cost execution and bounded resources; target deployment timing requires separate evidence.

NORMATIVE / LANGUAGE CONTRACT

5. Proposed KerML semantic mapping

Normative mapping contract of swa.ml 2.2, conditional on a backend claiming K conformance. No exporter or validated KerML semantic library is supplied by the current reference implementation. Langium AST generation and exhaustive inventory coverage do not establish KerML conformance.

5.1 Representation

Packages map to Package/namespace membership and imports. Datatypes/enums preserve nominal identity; arrays preserve copied shape. Components map to software Structure definitions and owned typed features. A usage creates an occurrence, including each multiplicity index; no shared private state is introduced. Specialization/redefinition retains the effective member set and base/replacement provenance.

A result-bearing operation maps to a Function; a void operation maps to a Behavior. This mapping does not make a result-bearing swa.ml operation pure. Effects remain explicit swa.ml constraints. Operation usages retain their shared signature and effective body. Nested operations are owned executables without lexical captures; states contribute to their owning operation rather than becoming an independent executable.

Ports map to owned typed features with per-member directional projections. Reversal flips each projection. Structural compatibility is retained as per-member typing constraints, not replaced by nominal port identity. Connections map to Connector instances with source occurrence/member route and independent policy queues. Forwarding maps to queue-free boundary aliases with preserved chains, not an extra message hop. Messages, transfer values, correlation and terminal failures require swa.ml semantics over suitable KerML Step/transfer structures.

5.2 Required semantic library

A K-conforming backend MUST implement a pinned swa.ml semantic library specializing the selected KerML 1.0 library. It defines Component, Operation, Port, Connector, Message, Queue, Activation, Schedule, state-machine reactions, copied values, failure and interruption. It MUST preserve suspension/unlock/relock, snapshots, deadlines, queue identity, success-only out copy-back, after success releases, state transition ordering and cancellation/late-reply behavior. Merely attaching uninterpreted metadata is preservation rather than proof that a kernel tool understands the execution semantics.

No arbitrary metaclass name is invented as a kernel class. Abstract bases require concrete backend choices validated by that kernel. Unsupported meaning yields an explicit partial-export result. The inventory covers every grammar production/type as element, grouping, reference, value, lowering or lexical, with its normative home. Groupings/lexical nodes contribute to owners and must not create duplicate semantic elements.

5.3 Traceability and claims

Every lowered node/constraint retains source declaration identity, URI/range, occurrence context and a generation role. Inherited declarations and replacements retain both provenances. Requirements, satisfaction, verification, deployment, cases with their subject occurrence, associations, package connections and views retain typed metadata/references, without proof claims. Names keep their decoded spelling; quoted swa.ml names map to KerML unrestricted names. Timing observations reference their run and binding; layout stays separate.

A conforming backend identifies the exact source/package/library revisions, selected KerML implementation, checked constraints and evidence. Round trips preserve the normalized model and cannot erase effects, merge occurrences/queues, reorder state transitions, invent routes, weaken contracts or convert copied values into references.

NORMATIVE / LANGUAGE CONTRACT

6. Reference execution contract

Normative contract of swa.ml 2.2, profile **swaml-reference/2.2**. A run records parser/package identity, source bytes, run target, applied deployments, options, limits, fault assumptions and an ordinal logical trace. Host adapters load files and hash sources; the language core performs neither filesystem access nor hashing.

6.1 Lifecycle and time

A run target is a package or one top-level component occurrence of a package. A package run executes every top-level occurrence of the package except platform roots (occurrences that specialize Swaml::Platform::Node), with their internal connections and the package connections between their ports. A component run executes that one top-level occurrence: its package connections are absent and its top-level ports are open, so an emission through an open port has no route and a request through it fails as unavailable. A top-level occurrence has at most one deployment, and a run applies it to that occurrence's tree.

Expand the finite occurrence tree of every executed top-level occurrence and initialize separate private stores before releasing startup work. An uncaught initializer runtime failure ends initialization, records the occurrence, attribute, source range and reason, retains partial stores and source evidence, and releases no startup work. A caught initializer failure may recover and remains observable. Distinct targets are independent execution choices; the occurrences of one package run share its initialization barrier, clock and trace. The reference epoch is 0ns. Every D releases at kD for k at least 1. Schedule arguments evaluate and copy at dispatch, under the serial lock or the concurrent dispatch snapshot. Entry deadline is measured from release, including backlog, request transport, wait and receive. Periodic deadline defaults to period.

Time uses nonnegative safe integer nanoseconds. Durations are positive and must remain representable after conversion/addition. Reference CPU steps cost zero physical time; a step budget prevents runaway computation. Ordering is deterministic by timestamp, phase and insertion ordinal. Deadline/request timeout wins a tie with reply or ordinary work. Receive timeout wins a tie with delivery in the reference selection. A run explicitly records its horizon; live/waiting activations and future events yield horizon status with open intervals rather than invented completion.

6.2 Lock and snapshot

One serial activation runs at a time per component occurrence. Nonsuspending local calls borrow its context and lock. wait, requests, receive and idle state waits release the lock. On readiness, serial work reacquires it before continuing and uses live attributes; locals remain copied cells. Concurrent entries may overlap, read one dispatch snapshot throughout and cannot write state even through callees or out arguments. Target backends must state how they realize the same snapshot semantics.

After a successful whole operation completes and unlocks, each effective after entry releases one fresh activation. No release occurs on failure, idle state reaction or intermediate local return. Each dependent has fresh deadline, locals and snapshot/backlog accounting. Correlated service reply transport and local completion dependencies are distinct observations. Duplicate dependencies are statically invalid and the graph is acyclic.

6.3 Values, flow and failure

Evaluation is left to right with and/or short-circuit. Payloads, records, arrays, parameters/results and out copy-back are copied, with nominal identities and domain checks. for in uses one copied collection. A loop limit evaluates once, is checked in the uint domain, and exits normally at the count; termination beyond declared limits is not statically proved. Integer overflow, non-finite reals, zero division, invalid indexes and failed assert/fail are runtime failures.

A local failure unwinds frames to the nearest try or fails the activation. Try fallback is lazy and type-compatible; prior state writes/emissions remain committed. Out values copy back only on successful return. Interrupt transfers and deadline/resource/activation violations are outside try. Resource failure is explicit evidence; no silently dropped activation is reported as successful execution.

6.4 Communication

Resolve boundary aliases before routing; forwarding adds neither queue nor latency. Each connection occurrence/direction/member owns a queue. Bare connections use the pinned Default. Check outgoing arguments against the emitting/requesting port member before routing, even when the peer accepts a wider domain. Request out cells initialize in the provider domain; successful replies convert at caller copy-back. Attribute queues replace the pending value; event/request queues obey capacity, delivery, ordering, overflow and optional age/latency assumptions. A reference run chooses insertion order for unordered queues. Fanout proceeds in route order and may partially commit before rejection.

A required request creates a unique pending correlation and suspends the caller. Result/out values and failure return through the same route in reverse. Timeout uses requestTimeout. First terminal transition is immutable; timeout wins equal-time delivery; late replies are traced and suppressed. AtLeastOnce may redeliver and requires an idempotent declaration. The reference fault model records offer-indexed drop, duplicate, transport and additional latency; retries/redelivery assumptions must be inspectable. Each duplicate copy independently obeys queue capacity and overflow; attribute copies preserve the single latest pending value. Accepted input comes only from validated source emissions; no destination injection exists.

6.5 Input ownership and interruption

An event is consumed by its one owner. Input for a receive statement remains queued before that statement waits. Inputs for inactive interrupt regions are discarded and observed. An armed region includes suspended local callees; matching input cancels protected frames/continuation and any pending local request, but not a remote server. Transfer stays in the same activation/deadline, preserves outer locals and committed effects, and runs the handler. Terminal interrupted correlations suppress late replies. No physical scheduling/preemption guarantee is implied.

A state machine waits without the component lock. Each reaction selects the first enabled nested transition for the input/timer, runs exit/effect/state-update/entry, and releases the lock again when idle. The timer epoch is the state update before entry actions, including time spent suspended in entry. Entry completes before timer selection; elapsed timers precede queued input, with earliest expiry first and equal-expiry transitions in source order. Deadline ties still win. State entry owns timer generations; stale timers cannot fire after exit. Unhandled input does not restart a timer. Final entry completes the whole operation once; it can release after dependents.

6.6 Evidence and resources

Trace ordinals distinguish equal-time observations. Record initialize, release, dispatch, ready, unlock, wait/requestWait/receiveWait, messages/offers/delivery, writes, states, interruption, completion/failure, caught failures, timeout, overflow/discards, late replies and violations. Retain activation/correlation/route identities where applicable. Each observation caused by a statement or schedule entry records its statement identity as source: writes, emissions, asserts, failures and suspensions name the executing statement, a state wait or reaction its state or transition, releases and dispatches the schedule entry, and every message lifecycle observation (offer, delivery, replacement, overflow, drop, retry, age or input discard, interruption, request, reply, timeout, cancellation, late reply) the statement that emitted or requested the message. Messages and correlations keep the identity of the emitting or requesting statement. Final stores are occurrence-indexed and timing projections leave live intervals open. No-failure-observed means only that finite run under its recorded assumptions. Step, backlog and concurrent limits are finite, explicit options. Production timing, real transport guarantees and universal verification remain separate claims.

6.7 Case runs

Each case with statements runs in its own fresh run of its package target. The script is a serial activation of its own, released at 0 ns after every on start entry, so it starts after the initialization barrier. It may call operations of its exact primary subject and act at the ports of its associated interface-only occurrences, which do nothing else. Input that reaches an actor port before the script waits for it stays in that connection's queue under the connection's policy (capacity, overflow, ordering and age), and an attribute keeps only its latest value, so a later on receive consumes the oldest queued event or the latest attribute value. A request addressed to an actor port waits in its queue until an on call branch takes it or the caller's requestTimeout expires.

A primary-subject call waits for its serial lock, switches the actual running frame into the subject's operation context and restores the case context on return or failure. The operation uses its own ports and live store, and may suspend; suspension releases its lock and resumption reacquires it. This local call creates no new schedule activation, implicit port, route, QoS timeout or `after` release. The script waits for completion, with ordinary `try` and success-only result/output-copy semantics and the case's existing horizon and resource bounds. It cannot execute a later actor-reply branch while blocked in the call; use an independently behaving actor or an earlier actor event when that response must proceed concurrently.

Tests additionally inspect their subject and explicitly associated software roots and their single parts under the target's serial lock. Helper calls on owners other than the exact primary subject may mutate through their operation but may neither communicate nor suspend. Use cases gain no private reads or part/peer calls. Associations preserve occurrence identity without cloning stores or changing package initialization, connections or execution roots.

Execution stores remain occurrence-local, but the trace records only the observations it emits. Local and white-box calls reuse their caller's activation, and individual reads and call invocations have no separate observation. A borrowed-call failure may be labelled with the case instead of its target. Consumers must retain available declaring-source, subject, activation and correlation context; a shared statement identity alone cannot attribute facts to every instance or invocation. Legal slash names can also produce ambiguous statement identities. Leave such attribution unknown, and never infer that a short-circuited expression or an unobserved return executed merely because its containing statement was reached.

The run stops with status stopped when the script completes or fails, otherwise at the horizon or step limit, or with status quiescent when no event remains while the script waits. The case result is pass when the script completed and the run observed neither an uncaught activation failure nor a contract violation; fail when a failure occurred, decided by the first in trace order with its statement identity, message and time: the script's own (a failed assert, fail or a runtime failure), an uncaught failure of another activation or a contract violation; inconclusive when the run ended before the script completed without a failure, at the horizon, at the step limit or stalled because the script waits while no further event can occur; and no checks for a case without statements, which does not run. A caught expression failure remains trace evidence and does not fail a case, so a passing case may record the failure-observed outcome. Observations of the script name the case identity as subject and carry its statement identities as source. A use case runs the same way as a test. A pass is bounded evidence of one deterministic run under its recorded assumptions, not proof.

NORMATIVE / LANGUAGE CONTRACT

7. Normalized model contract

Normative information-preservation contract of swa.ml 2.2. It defines what any exporter/target adapter must retain; it does not claim a kernel exporter exists.

7.1 Identity and provenance

A declaration identity is package plus owned-name path. An occurrence identity is the top-level occurrence plus indexed containment path; an operation occurrence additionally identifies its effective declaration. Activations/correlations/messages add unique run identities. Anonymous syntax/lowering nodes use an owner plus structural slot/generation role, not an invented user declaration. A statement identity is the identity of its owning operation or case, a slash and the statement path from that executable's body: statement indexes in each statement list and slot names with list indexes for nested blocks, branches, states, actions and transitions, as in Banking::ATM.serve/2/then/0. States and transitions are identified by the same path, as in Banking::ATM.run/states/0/transitions/1. A schedule entry is identified by its component and its index, as in Banking::ATM/schedule/0. Statement identities follow source structure and are trace provenance, not persistent editor identities. Source ranges are provenance rather than persistent identities. Every semantic node except a root has one owner; reference edges never imply containment.

Each normalized node/constraint retains source declaration URI/range and any inherited/replacement provenance. A persistent editor identity map is separate, preserving renames/moves atomically with source references and sidecars. Same-type multiplicity occurrences never share stores, queues or activation identity.

7.2 Families

Family	Required content
Workspace/package	Edition, package revision, sources, imports, unique declaration namespaces
Record/enum/type use	Nominal identity, fields/literals, primitive domain, fixed array shape
Component definition/usage	Base, effective members, explicit replacements, anonymous usage specialization, multiplicity
Attribute/local/parameter	Owner/scope, explicit type, const/in/out, initializer, copied-cell lifetime
Operation	Signature, effective whole body, nested ownership without captures, inferred effect flags/class
Port/member	Definition or inline members, direction, reversal, optionality, payload/signature, idempotency
Connection/forwarding	Endpoint occurrence references, alias provenance, structural member checks, effective policy
Policy	Pinned complete values and declaration/use provenance; no shared runtime queue
Schedule/entry	Trigger identity, effective target, dispatch arguments/bindings, period/deadline, concurrent
State/transition	Initial/final, entry/exit/effects, receive bindings/guard or timer, ordered selection
Deployment	Software/platform roots, Node paths, family/index placements, effective specificity
Requirement/case/view	Immutable attributes/docs, package intent links (associate, satisfy, verify), case kind, subject occurrence and ordered script statements with resolved actor ports, exact normal primary-subject call targets, explicitly associated test access roots and exact inspection/helper targets, ordered selection union

Expansion creates every literal multiplicity occurrence independently and keeps the definition reference. Inheritance produces an ordered effective set; replacement points to its inherited declaration. Late-bound local calls use that occurrence's effective operation name with the preserved signature. An operation usage retains the definition signature and either inherited or replacement body; no partial merge is inferred.

7.3 Routes and queues

Each port occurrence has per-member projections with effective provides/requires direction. Resolve forwarding to leaf port identities, retaining the full boundary chain without queue/storage/hop. Every resolved input projection references its unique owner and every provided attribute/event its emission sites. Outgoing operation projection is a request rather than an emission declaration.

A normalized connection records the two leaf ports, per-member directed routes and complete policy. Queue identity is connection occurrence, source/destination direction and member; requests/replies retain correlation separately. Attribute pending values use latest replacement, not event overflow rules. Extra provides remain contract members without fabricated peer requirements. Structural checks preserve each failed/matched member and nominal payload identity.

7.4 Executable lowering

Statements retain ordered operands, scopes, effects and success/failure continuations. Calls are expression nodes with a resolved local/port target, copied in/out/result types and effect flags. Try is a failure-catching node with a lazy fallback, never a rollback boundary. Wait/request/receive creates a suspended continuation plus unlock/readiness/relock; concurrent reads keep the captured dispatch snapshot. Loop limits evaluate once; for in owns one copied collection. Interrupt regions retain armed extent, input ownership, same-activation unwind, request cancellation and inactive/late-input observations.

A schedule entry lowers to a release mechanism and dispatch-time argument evaluation. After edges retain same-owner predecessor operation and completed activation identities, success-only release after unlock, fresh deadline/context and no implicit data forwarding/join. Stateful reactions retain source-order transitions, guards, timer generations and exit/effect/update/entry phases. State bodies do not gain separate executable identities. Final entry completes the operation once.

7.5 Presentation and equivalence

Views normalize to library definition plus ordered selected occurrences, retaining original include/filter clauses. General layouts preserve the same graph. Timing observations retain exact source/run/root/activation/correlation identities and open intervals; declared contracts remain independently identifiable. Geometry, collapse, routing bends and camera stay in sidecars.

Equivalence requires an identity-respecting correspondence preserving ownership, types/shapes, effective members, routes/policies, evaluation/effect order, schedule releases, suspension, failures, cancellation, states, deployment, intent links and selected occurrence order. Whitespace/ordinary comments are outside execution equivalence but remain required for authoring round trips. Exporters cannot drop unsupported semantics silently or claim that carrying metadata supplies execution/kernel evidence.

NORMATIVE / LANGUAGE CONTRACT

8. Conformance obligations and evidence

Normative chapter of swa.ml 2.2. Acceptance levels are separate; implementations report the tested subset and limitations in their support matrix.

8.1 Static obligations

ID	Required validation	Diagnostic group
V01	Headerless pinned edition, portable tokens, malformed recovery and literal domains	syntax, SW2000/2002
V02	Legal basic/quoted name spelling, unique names, explicit imports, unambiguous qualified/short references, no live-name shadowing	SW2001
V03	Finite nominal records/enums/fixed arrays, complete typed values, no void data, index ranges	SW2002
V04	Component-only definitions/usages, finite containment, acyclic single base, explicit compatible whole replacement, typed root additions, positive multiplicity	SW2003
V05	Directed port shape, reversal, nominal payloads and structural variance with per-member diagnostics	SW2004
V06	Immediate-child indexed routes, derived forwarding/connection, policy-free unique aliases, no duplicate resolved routes, package connections between top-level occurrences of one package, per-package closure/cardinality	SW2004
V07	Every required event/attribute and provided operation has one input owner; provided event/attribute emission provenance; interface-only components are exempt	SW2005
V08	Operation signatures, no nested captures, typed calls/out/result, acyclic graph, return paths, pure initializers	SW2002/2006
V09	Transitive effect inference, read-only guards, non-writing concurrent entries, suspension only in allowed whole expressions	SW2006
V10	One schedule, unique effective identities, matching trigger/binding signatures, same-owner acyclic after, fresh void targets and period/deadline rules	SW2007
V11	Stateful parameterless void signature, exactly one start entry, reachable states, ordered transitions and final restrictions	SW2008
V12	Typed complete policies, effective-use idempotency, positive safe time/capacity domains	SW2013
V13	Node-only target content, root/occurrence/index placement resolution, unique exact paths and at most one deployment per top-level occurrence	SW2009
V14	Immutable requirements, case subjects in the same package, legal associate/satisfy/verify links, case script environment role and white-box access, seven library view kinds/subjects and stable selection union	SW2010
V15	Stale-read and inactive interrupt-input warnings without a race-freedom claim	SW2011/2012

Validation MUST rebuild semantic string paths as well as indexed references after workspace changes/additions/deletions. Negative lookups matter: a newly loaded declaration may make a previously

resolved short name ambiguous. Malformed source remains editable and invalid; recovery cannot silently accept a different program. Definite-return analysis may be conservative rather than solving arbitrary conditions. Dynamic numeric/index/termination failures remain runtime obligations.

8.2 Runtime obligations

ID	Required observable evidence
E01	Distinct occurrence/multiplicity stores, copied values, activation-local scopes and successful out copy-back
E02	Initialization barrier, dispatch arguments, serial lock release/reacquisition and concurrent dispatch snapshots
E03	Separate occurrence/direction/member queues, Default policy, latest attributes, overflow/order/age/delivery behavior
E04	Unique routed correlations, result/out reply, failure propagation, timeout tie and terminal late-reply suppression
E05	Ordered expression/flow execution, loop limits, copied iteration, checked arithmetic/indexes, lazy try without rollback
E06	Ordered state reactions, live guards, timer generations, inactive input and final whole completion
E07	Entry release/deadline accounting, finite step/backlog/concurrent resources and explicit violations outside try
E08	Armed interrupt extent across callees/suspensions, same-activation unwind, terminal cancellation and no server rollback
E09	One fresh after activation per successful whole completion after unlock, failure suppression and new context/deadline
E10	Run/source/target/profile/option provenance, package and isolated component targets, trace ordinals with statement sources, occurrence stores and open observed timing intervals
E11	Fresh package run per case script, release after startup entries, retained early actor input, on call replies, normal primary-subject calls with actual context/lock suspension and restoration, test inspection/helper access under its serial lock, stop on script completion or failure and pass/fail/inconclusive/no checks results with statement identities

A deterministic reference run may choose one permitted order/delivery outcome. Its tests do not establish all possible traces or real transport reliability. A target implementation identifies additional scheduling/transport assumptions and evidence. Idempotency annotations are checked declarations, not proofs of side-effect behavior.

8.3 Analysis, kernel and graphical claims

Case realization needs a witness execution with payloads/assumptions; a passing case script is one such deterministic witness under its recorded assumptions, not a proof for every execution. Requirement fulfillment needs identified test/analysis/review evidence beyond satisfy/verify links. Schedulability needs target scheduler, cost and transport assumptions plus measurement/proof. Race/deadlock freedom requires analysis of suspension/interleaving and requests. A finite search without failure is not universal proof.

K requires the complete normalized model, a pinned semantic library/exporter, kernel validation and round trips. Inventory coverage is not K. G requires Browser plus seven source views, occurrence-aware identity, notation, source-validated edits, sidecar layout and atomic native undo/redo. LSP syntax/formatting alone is not G. Semantic paths need path-aware rename/reference/navigation; generic name references are insufficient.

Conformance reports identify edition, exact implementation revision, groups checked, unsupported capabilities, run limits and evidence links. Implementation status is the reference report; it must change when behavior or evidence changes.

NORMATIVE / LANGUAGE CONTRACT

9. Formal semantics

Normative schemas of swa.ml 2.2. These constrain implementations without claiming a mechanically proved metatheory.

9.1 Domains

Let D be the resolved declaration/effective-member graph, O the finite indexed occurrence tree, Γ a typed lexical environment, σ occurrence stores, ρ activation locals, Q per-connection/direction/member buffers, A activations, M state/timer generations, R correlations, L serial locks, B pending releases and t integer nanoseconds.

```text
C = (D, O, σ, Q, A, M, R, L, B, t)
D ⊢ O valid
D; Γ ⊢ e : T ! ε
D; Γ ⊢ s ⇒ Γ'
C  - observation→ C'
```

Values are bounded primitive scalars, nominal enums/records and fixed copied arrays; void has no inhabitant. Effect ε retains read/write/communication/suspension flags, with pure as empty. Transitive union over an acyclic call graph computes effects. The maximum class is a presentation of these flags rather than permission to erase a write beneath suspension.

9.2 Typing schemas

Construct	Premises and result
x / x.field / x[i]	x in Γ; nominal record field or integral array index; result declared type; dynamic index must be in extent
Enum.literal	No live first-segment value shadows the enum; unambiguous accessible nominal enum and literal
operation(args)	Resolved same-owner/nested or imported pure definition; copied typed in arguments; mutable compatible out targets; result declared type; effect is union of arguments and callee
p.member(args)	p is owned, member requires operation; arguments satisfy signature; effect communicates and suspends
case subject call	Exact primary software subject; copied typed arguments/results, actual serial operation context and normal effects; suspension releases/reacquires its lock, caller context restores on return/failure; local activation semantics, no implicit route or schedule release
test occurrence access	Resolved own-package executed software root is the subject or an explicit association, followed by single effective parts; reads use its live store under its lock, helper calls outside the exact primary subject neither communicate nor suspend; no ownership transfer or direct attribute assignment
try(e, f)	e:T and f:U assignable to T; lazy f; effect union; no fallback only when T is void
var x:T=e	Compatible value, fresh live name; Γ extends with mutable x; suspension allowed only when e is whole call/try
x=e	Mutable local/out/attribute, compatible type; attribute write adds write effect; same whole-expression suspension rule

Construct	Premises and result
return e	e assignable to owning operation result; expression does not suspend; success copy-back
if/while/until/assert	bool condition; optional loop limit uint-compatible and evaluated once
for	Fresh initializer scope; bool condition; mutable typed update; fresh body scope each iteration
for in	Collection T[n], explicit compatible element type; copied collection; fresh element/body scope
wait/receive	Suspended continuation; owned input with explicit payload binding for receive; no implicit failure/payload name
interruptible	Non-stateful operation, exclusive required input; protected and handler scopes share only outer locals
state guard	bool, effects pure or reads state; transitions selected in authored order
concurrent entry	Callee transitive effect has no write and body is not stateful
attribute initializer	Explicit destination type; empty state environment; pure effect

Scalar type assignability uses widening, with checked integral value conversion in assignments/parameter initialization. Port compatibility is structural by member name with contravariant operation inputs and covariant output/result payloads. Nominal records/enums do not become structurally equivalent. Array values preserve invariant element type/extent; literals are checked elementwise.

9.3 Transition schemas

Rule	Configuration change and observation
initialize	Expand O, create separate σ[o], initialize all before startup release
release	Add fresh activation to B with release time/cause/deadline; bounded admission or explicit violation
dispatch	Acquire L[o] for serial work; copy entry arguments under lock; concurrent work captures σ[o] snapshot
local step	Evaluate in ρ plus live serial σ or captured concurrent snapshot; update copied cells and emit source-provenanced observations
suspend	Save continuation/ρ; remove serial lock; register wait timer, receive alternatives or pending request
ready	Mark continuation ready; serial continuation must reacquire lock before reading current σ
offer	Resolve alias chain, select connection/member queue, copy payload, apply latest attribute replacement or policy overflow/delivery
request	Create unique pending R[r] with expiry t + requestTimeout; offer request; suspend caller
reply	Before expiry and while pending, set immutable succeeded/failed terminal, copy success result/out, ready caller
timeout	At expiry, pending becomes failed; ready failure continuation; tie beats reply
try success/failure	Return e value on success; on RuntimeFault evaluate fallback lazily with existing σ/Q effects retained
interrupt	Match active region; disarm/unwind protected continuation, cancel pending correlation as interrupted, retain activation/deadline/outer ρ and committed effects

Rule	Configuration change and observation
state reaction	Select first enabled transition, exit/effect/update/entry, invalidate old timer generation; idle releases lock
complete	Finish activation and unlock; correlated reply is offered separately; successful whole completion releases after targets fresh
violation	Deadline, activation overflow, step/concurrent resource or clock failure stops the reference run and bypasses try
case script	A fresh package configuration adds one serial script activation after startup releases; direct primary-subject calls borrow its actual serial context, script emissions/requests/receives use actor ports, on call replies to the pending correlation, and script completion or failure stops the run

At terminal correlation, later replies cannot change R. Inactive interrupt input is discarded observably. Receive statements preserve queued early input. A state's unhandled input leaves its entry time/timer generation intact. Set entry time at the state update, before entry actions. Select an already elapsed timer after entry completes before queued input; earliest expiry then declaration order determines competing timers. Deadline/timeout measurements include suspension and backlog; zero-cost interpreter steps do not supply physical cost evidence.

9.4 Projection and adequacy

A conforming reference trace records enough identity and order to reconstruct observable writes, messages, state changes, waits and terminals under its chosen assumptions, including the statement identity that caused each one. The initial configuration of a package target expands every top-level software occurrence and adds the package connection queues; a component target expands one top-level occurrence and adds none. A view is a pure identity selection function over D/O; Timing additionally projects a separately identified trace. No view transition changes C. A bounded run ending at a horizon retains live/open intervals. Source hashing belongs to hosts. Kernel/target refinement must preserve these observations or explicitly report unsupported semantics; syntax acceptance alone is insufficient.

NORMATIVE / LANGUAGE CONTRACT

swa.ml 2.2 graphical notation

Original monochrome swa.ml notation uses thin rules, explicit labels and owned compartments. It does not claim OMG notation conformance. The canonical catalog pairs every concept with context, source subject, drawing and constraints. Worked diagrams retain source-backed model subjects. spec/notation.json covers every grammar/type family and every keyword, including a text-only rationale for lexical spelling.

Components show definition versus occurrence identity and indexed multiplicity. Private attributes stay in their component; operations show parameters/returns and nested ownership without closure captures. Schedule compartments show triggers, deadlines and concurrency separately from signatures. Do not draw performers or action allocations.

Port boundary squares expose direction per member: provides/requires attribute, event or operation. The square is a neutral container that may mix all three member kinds. Attribute/event arrows point outward for provides and inward for requires; a compact double arrow summarizes both directions only when both exist. A ball marks each provided operation and an open socket each required operation. Expanded labels preserve member names, kinds and signatures; these glyphs never assign a single kind or role to the whole port. Reversal flips every member arrow and swaps each operation ball/socket. Connection lines join opposite-compatible members and identify their effective policy; forwarding connects boundary to immediate child with the same member directions and is visibly labeled as a queue-free alias. Do not restore interface kinds, versions or whole-port roles.

Flow shows expressions/calls, decisions, loop forms, lazy try fallback, receive/wait suspension and armed interrupt transfer. States are inside an operation; transitions are nested/ordered and labeled by input/guard or after timer and target. State bodies have no separate executable identity. Final completion is distinguishable from idle reactions.

Platform Nodes own const attributes and child Nodes. Deployment edges refer to the separate placement declaration and preserve indexed occurrence identity. Requirement links are labeled «satisfy» and «verify» and show intent rather than proof. A Case view draws each case as an ellipse inside the boundary of its subject occurrence, labeled with the occurrence and its type, and each associated occurrence outside the boundary, labeled name: Type and joined to its cases by solid association lines. Use-case associations and interface-only test proxies use actor notation; active test collaborators retain component notation. A case without a subject has no boundary; a test is labeled «test». Sequence shows the subject, its parts and the associated occurrences as lifelines on real routes. Actor-port statements start on the interface-only actor whose port they use: send and publish are asynchronous arrows, calls are call arrows with dashed returns, on call answers with a dashed return, on … or after D is a timeout fragment and assert a check marker. Direct subject calls start on the source-backed case behavior context, named for the actual use case or test and marked accordingly; test-private reads and helper calls use that same test context. This context is not a component or the host runner. Local-like calls do not imply scheduled after successors. Flow shows a case script as a frame of its statements.

Browser remains navigation. General, Interconnect, Case, Sequence, Grid, Flow and Timing are imported view definitions. General Box in box/Tree preserve the same selected identities/topology. Timing declared mode shows schedules/deadlines/static waits; observed mode adds an identified run, lock gaps, message latency, terminals and open intervals. Missing evidence never becomes measured WCET. Geometry, collapse and routes stay in sidecars.

Regenerate with python scripts/build-notation.py and python scripts/build-graphical-examples.py, then run both with --check. SVG, PNG and scene JSON share the same original geometry. Current artifacts keep their established docs/notation/2.0 and docs/figures/2.0 paths so that existing links work; the directory names are not edition labels, and each drawing carries the current standard version. Historical publication assets remain untouched.


NORMATIVE / LANGUAGE CONTRACT

swa.ml 2.2 canonical graphical catalog

Generated from spec/notation.json. Original monochrome notation; no OMG notation-conformance claim. Every drawing preserves source ownership and identity.

Packages and imports

swa.ml 2.2; Hello::Demo.




Packages and imports

Source: Hello::Demo. **Grammar:** Model, Package, Import, QualifiedName.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Typed copied values

swa.ml 2.2; Values::Demo.




Typed copied values

Source: Values::Demo. **Grammar:** DataType, Field, EnumType, TypeRef, ValueType, RecordLiteral, FieldValue, ArrayLiteral.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Component definitions and usages

swa.ml 2.2; Reuse::Demo.




Component definitions and usages

Source: Reuse::Demo. **Grammar:** ComponentDef, ComponentUsage, ComponentMember, Element.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Indexed occurrence identity

swa.ml 2.2; Multiplicity::Demo.




Indexed occurrence identity

Source: Multiplicity::Demo.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Attributes and lexical locals

swa.ml 2.2; Values::Demo.




Attributes and lexical locals

Source: Values::Demo. **Grammar:** Attribute, LocalVariable, Argument.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Mixed directed port members

swa.ml 2.2; Mixed::Boundary.




Mixed directed port members

Source: Mixed::Boundary. **Grammar:** PortDef, PortUsage, PortMember, MemberPath, Send.

One square boundary can contain attribute, event and operation members together. Arrowheads show data/event direction; an outward arrow means provides and inward means requires. A ball marks a provided operation; an open socket marks a required operation. These are member glyphs, not port types. A compact double arrow summarizes opposite data/event directions only; expanded labels retain each member name and type. Reversed flips every direction, arrow and operation glyph; geometry never adds members or routes. A canonical source-backed projection; geometry is separate from semantics.

Policy-bearing connection

swa.ml 2.2; Policies::Demo.




Policy-bearing connection

Source: Policies::Demo. **Grammar:** Connect, QosPolicy, PolicySetting.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Queue-free boundary forwarding

swa.ml 2.2; Boundary::Demo.




Queue-free boundary forwarding

Source: Boundary::Demo.

Preserve owned source and distinct definition/occurrence identities. Boundary alias adds no queue, policy or message. A canonical source-backed projection; geometry is separate from semantics.

Operations and nested ownership

swa.ml 2.2; OperationUsage::Demo.




Operations and nested ownership

Source: OperationUsage::Demo. **Grammar:** Operation, OperationUsage, Executable, OperationBody.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Expression calls and copied out values

swa.ml 2.2; ClientServer::Client.




Expression calls and copied out values

Source: ClientServer::Client. **Grammar:** CallExpression, ExpressionStatement, Return.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Runtime failure and lazy fallback

swa.ml 2.2; ClientServer::Client.




Runtime failure and lazy fallback

Source: ClientServer::Client. **Grammar:** TryExpression, Fail, Assert.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Statements and decisions

swa.ml 2.2; Values::Demo.




Statements and decisions

Source: Values::Demo. **Grammar:** Block, Statement, Assign, If.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Loops and copied iteration

swa.ml 2.2; Loops::Demo.




Loops and copied iteration

Source: Loops::Demo. **Grammar:** While, Until, For, ForUpdate, ForEach.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Schedule entry and successful chaining

swa.ml 2.2; Chaining::Demo.




Schedule entry and successful chaining

Source: Chaining::Demo. **Grammar:** Schedule, ScheduleEntry.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Suspending wait and receive

swa.ml 2.2; Receiving::Receiver.




Suspending wait and receive

Source: Receiving::Receiver. **Grammar:** Wait, Receive, ReceiveBranch.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Armed interrupt and cancellation

swa.ml 2.2; Interrupts::Receiver.




Armed interrupt and cancellation

Source: Interrupts::Receiver. **Grammar:** Interruptible.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Ordered state transitions

swa.ml 2.2; States::Demo.lamp.




Ordered state transitions

Source: States::Demo.lamp. **Grammar:** State, StateAction, Transition.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Platform Nodes and placement

swa.ml 2.2; Placement::Demo.




Platform Nodes and placement

Source: Placement::Demo. **Grammar:** Deployment, Placement.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Requirements and package intent links

swa.ml 2.2; Traceability::Delivery.




Requirements and package intent links

Source: Traceability::Delivery. **Grammar:** Requirement, Satisfaction, Verification.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Use cases, tests and associations

swa.ml 2.2; Cash Machine::Withdraw cash.




Use cases, tests and associations

Source: Cash Machine::Withdraw cash. **Grammar:** Scenario, CaseKind, Association.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Executable case scripts

swa.ml 2.2; AtmTests::Bank refusal.




Executable case scripts

Source: AtmTests::Bank refusal. **Grammar:** EndpointPath.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Seven library view definitions

swa.ml 2.2; Traceability::Demo.




Seven library view definitions

Source: Traceability::Demo. **Grammar:** ViewDef, View, ViewSelection, FilterExpression, FilterOr, FilterAnd, FilterPrimary, FilterBinary, FilterNot, FilterComparison.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Declared and observed timing

swa.ml 2.2; Timing::Demo.sample.




Declared and observed timing

Source: Timing::Demo.sample.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Owned documentation and lexical notes

swa.ml 2.2; Traceability::Delivery.




Owned documentation and lexical notes

Source: Traceability::Delivery. **Grammar:** Documentation, DOC_COMMENT.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Typed expressions and operators

swa.ml 2.2; Values::Demo.




Typed expressions and operators

Source: Values::Demo. **Grammar:** Expression, OrExpression, AndExpression, EqualityExpression, RelationalExpression, AdditiveExpression, MultiplicativeExpression, UnaryExpression, PrimaryExpression, BinaryExpression, ReferenceExpression, ValuePath, Literal, Numeric.

Preserve owned source and distinct definition/occurrence identities. Drawing is a projection; it does not add execution semantics. A canonical source-backed projection; geometry is separate from semantics.

Lexical and path spelling

swa.ml 2.2; Hello::Demo.



Lexical and path spelling

Source: Hello::Demo. **Grammar:** Duration, Name, Path, WS, ID, UNRESTRICTED_NAME, NUMBER, INT, STRING, ML_COMMENT, SL_COMMENT.

Text-only spelling; show as a source caption without invented semantic nodes. Drawing is a projection; it does not add execution semantics. Lexical spelling has no independent graphical identity.

NORMATIVE APPENDIX

A. Complete concrete grammar

Authoritative Langium grammar, reproduced in full. Line wraps are typographic continuations; only numbered rows begin original source lines.

LANGIUM GRAMMAR

```
1  grammar Swaml
2
3  entry Model: packages+=Package*;
4  Package: 'package' name=QualifiedName '{' documentation=Documentation? (imports+=Import |
   elements+=Element | connections+=Connect | associations+=Association | satisfactions+=Satisfaction |
   verifications+=Verification)* '}';
5  Import: 'import' namespace=QualifiedName ';';
6  Element: DataType | EnumType | ComponentDef | ComponentUsage | PortDef | Operation | QosPolicy | ViewDef
    | Requirement | Scenario | View | Deployment;
7  DataType: 'datatype' name=Name '{' documentation=Documentation? fields+=Field* '}';
8  Field: name=Name ':' type=TypeRef documentation=Documentation? ';';
9  EnumType: 'enum' name=Name '{' documentation=Documentation? literals+=Name (',' literals+=Name)* '}';
10 TypeRef: (primitive=('bool'|'byte'|'uint'|'int'|'real'|'string'|'void') |
   type=[ValueType:QualifiedName]) ('[' size=INT ']')?;
11 type ValueType = DataType | EnumType;
12 Argument: (direction=('in'|'out'))? name=Name ':' type=TypeRef;
13 ComponentDef: 'component' 'def' name=Name ('specializes' specializes=[ComponentDef:QualifiedName])? '{'
   documentation=Documentation? members+=ComponentMember* '}';
14 ComponentUsage: (redefines?='redefines')? 'component' name=Name (':'
   definition=[ComponentDef:QualifiedName] ('[' size=INT ']')?)? (';' | '{' documentation=Documentation?
   members+=ComponentMember* '}');
15 ComponentMember: ComponentUsage | PortUsage | Attribute | Operation | OperationUsage | Connect |
   Schedule;
16 Attribute: (redefines?='redefines')? (constant?='const')? 'attribute' name=Name ':' type=TypeRef '='
   value=Expression documentation=Documentation? ';';
17 PortDef: 'port' 'def' name=Name '{' documentation=Documentation? members+=PortMember* '}';
18 PortUsage: (redefines?='redefines')? (optional?='optional')? (reversed?='reversed')? 'port' name=Name
   (':' definition=[PortDef:QualifiedName] documentation=Documentation? ';' | '{'
   documentation=Documentation? members+=PortMember* '}');
19 PortMember: direction=('provides'|'requires') (idempotent?='idempotent')?
   kind=('attribute'|'event'|'operation') name=Name (':' type=TypeRef | '(' (parameters+=Argument (','
   parameters+=Argument)*)? ')' ('returns' result=TypeRef)?) documentation=Documentation? ';';
20 Connect: (redefines?='redefines')? 'connect' (name=Name)? (':' policy=[QosPolicy:QualifiedName])? '('
   source=Path ',' target=Path ')' documentation=Documentation? ';';
21 QosPolicy: 'qos' 'def' name=Name (':' base=QualifiedName)? '{' documentation=Documentation?
   settings+=PolicySetting* '}';
22 PolicySetting: name=Name '=' (value=Expression | duration=Duration) ';';
23 Operation: (redefines?='redefines')? 'operation' (definition?='def')? name=Name '('
   (parameters+=Argument (',' parameters+=Argument)*)? ')' ('returns' result=TypeRef)? body=OperationBody;
24 OperationUsage: (redefines?='redefines')? 'operation' name=Name ':' definition=[Operation:QualifiedName]
    (documentation=Documentation? ';' | body=OperationBody);
25 Executable: Operation | OperationUsage;
26 OperationBody: '{' documentation=Documentation? operations+=Executable* ('initial' initial=Name ';'
   states+=State+ | statements+=Statement*) '}';
27 Schedule: 'schedule' '{' entries+=ScheduleEntry* '}';
28 ScheduleEntry: ('on' (kind='start' | kind='every' period=Duration | kind=('receive'|'call')
   endpoint=MemberPath '(' (bindings+=Name (',' bindings+=Name)*)? ')') | kind='after' predecessor=Name)
   operation=Name '(' (args+=Expression (',' args+=Expression)*)? ')' ('deadline' deadline=Duration)?
   (concurrent?='concurrent')? ';';
29 Block: '{' statements+=Statement* '}';
30 Statement: LocalVariable | Assign | Send | ExpressionStatement | Return | If | While | Until | For |
   ForEach | Wait | Receive | Interruptible | Fail | Assert;
31 LocalVariable: 'var' name=Name ':' type=TypeRef '=' value=Expression ';';
32 Assign: target=Name '=' value=Expression ';';
33 ExpressionStatement: expression=Expression ';';
34 Send: kind=('send'|'publish') endpoint=EndpointPath '(' (args+=Expression (',' args+=Expression)*)? ')'
   ';';
35 Return: 'return' value=Expression? ';';
```

LANGIUM GRAMMAR / CONTINUED

```
If: 'if' '(' condition=Expression ')' then=Block ('else' otherwise=Block)?;
While: 'while' '(' condition=Expression (',' limit=Expression 'times')? ')' body=Block;
Until: 'until' '(' condition=Expression (',' limit=Expression 'times')? ')' body=Block;
For: 'for' '(' initializer=LocalVariable condition=Expression ';' update=ForUpdate ')' body=Block;
ForUpdate infers Assign: target=Name '=' value=Expression;
ForEach: 'for' '(' variable=Argument 'in' collection=Expression ')' body=Block;
Wait: 'wait' duration=Duration ';';
Receive: 'on' branches+=ReceiveBranch ('or' branches+=ReceiveBranch)* ('or' 'after' timeout=Duration
timeoutBody=Block)?;
ReceiveBranch: kind=('receive'|'call') endpoint=EndpointPath '(' (bindings+=Name (',' bindings+=Name)*)?
 ')' body=Block;
Interruptible: 'interruptible' body=Block 'on' 'receive' endpoint=MemberPath '(' (bindings+=Name (','
bindings+=Name)*)? ')' handler=Block;
Fail: 'fail' reason=STRING ';';
Assert: 'assert' condition=Expression ';';
State: (final?='final')? 'state' name=Name '{' documentation=Documentation? (actions+=StateAction |
transitions+=Transition)* '}';
StateAction: 'on' kind=('entry'|'exit') body=Block;
Transition: ('on' 'receive' endpoint=MemberPath '(' (bindings+=Name (',' bindings+=Name)*)? ')' ('when'
'(' guard=Expression ')')? | 'after' delay=Duration) 'to' target=Name effect=Block;
Deployment: 'deployment' name=Name 'of' root=[ComponentUsage:QualifiedName] 'on'
platform=[ComponentUsage:QualifiedName] '{' documentation=Documentation? placements+=Placement* '}';
Placement: 'deploy' target=Path? 'on' node=Path ';';
Requirement: 'requirement' name=Name '{' documentation=Documentation? attributes+=Attribute* '}';
Documentation: text=DOC_COMMENT;
Satisfaction: 'satisfy' requirement=[Requirement:QualifiedName] 'by' design=Path ';';
Verification: 'verify' requirement=[Requirement:QualifiedName] 'by' test=[Scenario:Name] ';';
Association: 'associate' occurrence=[ComponentUsage:Name] 'to' target=[Scenario:Name] ';';
Scenario: kind=CaseKind name=Name ('of' subject=[ComponentUsage:Name])? '{' documentation=Documentation?
 statements+=Statement* '}';
CaseKind returns string: 'use' 'case' | 'test';
ViewDef: 'view' 'def' name=Name documentation=Documentation? ';';
View: 'view' name=Name ':' definition=[ViewDef:QualifiedName] ('of' subject=Path
documentation=Documentation? ';' | '{' documentation=Documentation? selections+=ViewSelection+ '}');
ViewSelection: 'include' subject=Path (recursive?='recursive')? ('where' filter=FilterExpression)? ';';
type FilterExpression = FilterBinary | FilterNot | FilterComparison;
FilterExpression returns FilterExpression: FilterOr;
FilterOr returns FilterExpression: FilterAnd ({infer FilterBinary.left=current} operator='or'
right=FilterAnd)*;
FilterAnd returns FilterExpression: FilterPrimary ({infer FilterBinary.left=current} operator='and'
right=FilterPrimary)*;
FilterPrimary returns FilterExpression: {infer FilterNot} 'not' operand=FilterPrimary | FilterComparison
 | '(' FilterExpression ')';
FilterComparison: field=('name'|'kind'|'path') operator=('=='|'!=') value=STRING;
Duration: value=INT unit=('ns'|'us'|'ms'|'s');
Name returns string: ID | UNRESTRICTED_NAME | 'reversed' | 'to' | 'times' | 'name' | 'kind' | 'path' |
'use' | 'case' | 'test' | 'associate' | 'by' | 'ns' | 'us' | 'ms' | 's';
MemberPath returns string: Name '.' Name;
EndpointPath returns string: Name '.' Name ('.' Name)?;
Path returns string: QualifiedName ('[' INT ']')? ('.' Name ('[' INT ']')?)*;
QualifiedName returns string: Name ('::' Name)*;
ValuePath returns string: QualifiedName ('.' Name)*;
type Expression = BinaryExpression | UnaryExpression | Literal | CallExpression | TryExpression |
ReferenceExpression | RecordLiteral | ArrayLiteral;
Expression returns Expression: OrExpression;
OrExpression returns Expression: AndExpression ({infer BinaryExpression.left=current} operator='or'
right=AndExpression)*;
AndExpression returns Expression: EqualityExpression ({infer BinaryExpression.left=current}
operator='and' right=EqualityExpression)*;
EqualityExpression returns Expression: RelationalExpression ({infer BinaryExpression.left=current}
operator=('=='|'!=') right=RelationalExpression)*;
RelationalExpression returns Expression: AdditiveExpression ({infer BinaryExpression.left=current}
operator=('<'|'<='|'>'|'>=') right=AdditiveExpression)*;
AdditiveExpression returns Expression: MultiplicativeExpression ({infer BinaryExpression.left=current}
operator=('+'|'-') right=MultiplicativeExpression)*;
MultiplicativeExpression returns Expression: UnaryExpression ({infer BinaryExpression.left=current}
operator=('*'|'/'|'%') right=UnaryExpression)*;
```

LANGIUM GRAMMAR / CONTINUED

```
84  UnaryExpression returns Expression: {infer UnaryExpression} operator=('not'|'-') operand=UnaryExpression
     | PrimaryExpression;
85  PrimaryExpression returns Expression: Literal | TryExpression | CallExpression | ReferenceExpression |
    RecordLiteral | ArrayLiteral | '(' Expression ')';
86  TryExpression: 'try' '(' expression=Expression (',' fallback=Expression)? ')';
87  CallExpression: target=ValuePath '(' (args+=Expression (',' args+=Expression)*)? ')';
88  ReferenceExpression: path=ValuePath ('[' index=Expression ']')?;
89  Literal: {infer Literal} (number=Numeric | text=STRING | boolean=('true'|'false'));
90  RecordLiteral: 'record' type=[DataType:QualifiedName] '{' fields+=FieldValue* '}';
91  FieldValue: name=Name '=' value=Expression ';';
92  ArrayLiteral: '[' (values+=Expression (',' values+=Expression)*)? ']';
93  Numeric returns number: NUMBER | INT;
94  hidden terminal WS: /\s+/;
95  terminal DOC_COMMENT: /\/\*\*(?:\/|[\s\S]*?\*\/)/;
96  terminal ID: /[_a-zA-Z][\w]*/;
97  terminal UNRESTRICTED_NAME: /'([^'\\\x00-\x1F\x7F]|\\['\\])*'/;
98  terminal NUMBER returns number: /[0-9]+\.[0-9]+/;
99  terminal INT returns number: /[0-9]+/;
100 terminal STRING: /"([^"\\\x00-\x1F]|\\["\\nrt])*"/;
101 hidden terminal ML_COMMENT: /\/\*(?!\*)[\s\S]*?\*\//;
102 hidden terminal SL_COMMENT: /\/\/[^\n\r]*/;
```

NORMATIVE DESIGN INVENTORY

B. Grammar-to-semantics inventory

Every grammar rule/type name is represented. Proposed kernel bases identify the design target; they do not constitute an implemented or validated exporter. Empty bases indicate syntax normalized through its owner.

Rule / kind	Proposed kernel base	Meaning to preserve
Model element	Package	Model: preserve packages and imports, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Package element	Package	Package: preserve packages and imports, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Import element	Package	Import: preserve packages and imports, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Element grouping	Owner representation	Element: preserve component definitions and usages, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
DataType element	DataType	DataType: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Field element	DataType	Field: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
EnumType element	DataType	EnumType: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
TypeRef reference	DataType	TypeRef: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ValueType element	DataType	ValueType: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Argument element	Feature	Argument: preserve attributes and lexical locals, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ComponentDef element	Structure	ComponentDef: preserve component definitions and usages, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ComponentUsage element	Structure	ComponentUsage: preserve component definitions and usages, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ComponentMember grouping	Owner representation	ComponentMember: preserve component definitions and usages, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

Rule / kind	Proposed kernel base	Meaning to preserve
Attribute element	Feature	Attribute: preserve attributes and lexical locals, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
PortDef element	Feature	PortDef: preserve directed port members, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
PortUsage element	Feature	PortUsage: preserve directed port members, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
PortMember grouping	Owner representation	PortMember: preserve directed port members, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Connect element	Connector	Connect: preserve policy-bearing connection, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
QosPolicy element	Connector	QosPolicy: preserve policy-bearing connection, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
PolicySetting element	Connector	PolicySetting: preserve policy-bearing connection, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Operation element	Behavior	Operation: preserve operations and nested ownership, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
OperationUsage element	Behavior	OperationUsage: preserve operations and nested ownership, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Executable element	Behavior	Executable: preserve operations and nested ownership, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
OperationBody grouping	Owner representation	OperationBody: preserve operations and nested ownership, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Schedule lowering	Feature	Schedule: preserve schedule entry and successful chaining, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ScheduleEntry lowering	Feature	ScheduleEntry: preserve schedule entry and successful chaining, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Block grouping	Owner representation	Block: preserve statements and decisions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Statement grouping	Owner representation	Statement: preserve statements and decisions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

Rule / kind	Proposed kernel base	Meaning to preserve
LocalVariable element	Feature	LocalVariable: preserve attributes and lexical locals, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Assign element	Feature	Assign: preserve statements and decisions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ExpressionStatement value	Expression	ExpressionStatement: preserve expression calls and copied out values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Send element	Feature	Send: preserve directed port members, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Return lowering	Feature	Return: preserve expression calls and copied out values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
If element	Feature	If: preserve statements and decisions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
While lowering	Feature	While: preserve loops and copied iteration, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Until lowering	Feature	Until: preserve loops and copied iteration, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
For lowering	Feature	For: preserve loops and copied iteration, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ForUpdate lowering	Feature	ForUpdate: preserve loops and copied iteration, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ForEach lowering	Feature	ForEach: preserve loops and copied iteration, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Wait lowering	Feature	Wait: preserve suspending wait and receive, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Receive lowering	Feature	Receive: preserve suspending wait and receive, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ReceiveBranch lowering	Feature	ReceiveBranch: preserve suspending wait and receive, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Interruptible lowering	Feature	Interruptible: preserve armed interrupt and cancellation, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

Rule / kind	Proposed kernel base	Meaning to preserve
Fail lowering	Feature	Fail: preserve runtime failure and lazy fallback, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Assert lowering	Feature	Assert: preserve runtime failure and lazy fallback, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
State lowering	Feature	State: preserve ordered state transitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
StateAction lowering	Feature	StateAction: preserve ordered state transitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Transition lowering	Feature	Transition: preserve ordered state transitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Deployment element	Feature	Deployment: preserve platform nodes and placement, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Placement element	Feature	Placement: preserve platform nodes and placement, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Requirement element	Feature	Requirement: preserve requirements and package intent links, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Documentation element	Feature	Documentation: preserve owned documentation and lexical notes, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Satisfaction element	Feature	Satisfaction: preserve requirements and package intent links, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Verification element	Feature	Verification: preserve requirements and package intent links, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Association element	Feature	Association: preserve use cases, tests and associations, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Scenario element	Feature	Scenario: preserve use cases, tests and associations, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
CaseKind element	Feature	CaseKind: preserve use cases, tests and associations, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ViewDef element	Feature	ViewDef: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

Rule / kind	Proposed kernel base	Meaning to preserve
View element	Feature	View: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ViewSelection element	Feature	ViewSelection: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
FilterExpression value	Expression	FilterExpression: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
FilterOr element	Feature	FilterOr: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
FilterAnd element	Feature	FilterAnd: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
FilterPrimary element	Feature	FilterPrimary: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
FilterComparison element	Feature	FilterComparison: preserve seven library view definitions, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Duration lexical	Owner representation	Duration: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Name lexical	Owner representation	Name: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
MemberPath reference	Feature	MemberPath: preserve directed port members, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
EndpointPath reference	Feature	EndpointPath: preserve executable case scripts, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Path lexical	Owner representation	Path: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
QualifiedName reference	Package	QualifiedName: preserve packages and imports, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ValuePath reference	Feature	ValuePath: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Expression value	Expression	Expression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

Rule / kind	Proposed kernel base	Meaning to preserve
OrExpression value	Expression	OrExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
AndExpression value	Expression	AndExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
EqualityExpression value	Expression	EqualityExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
RelationalExpression value	Expression	RelationalExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
AdditiveExpression value	Expression	AdditiveExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
MultiplicativeExpression value	Expression	MultiplicativeExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
UnaryExpression value	Expression	UnaryExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
PrimaryExpression value	Expression	PrimaryExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
TryExpression value	Expression	TryExpression: preserve runtime failure and lazy fallback, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
CallExpression value	Expression	CallExpression: preserve expression calls and copied out values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ReferenceExpression value	Expression	ReferenceExpression: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
Literal value	Expression	Literal: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
RecordLiteral value	DataType	RecordLiteral: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
FieldValue element	DataType	FieldValue: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ArrayLiteral value	DataType	ArrayLiteral: preserve typed copied values, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

Rule / kind	Proposed kernel base	Meaning to preserve
Numeric value	Expression	Numeric: preserve typed expressions and operators, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
WS lexical	Owner representation	WS: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
DOC_COMMENT lexical	Owner representation	DOC_COMMENT: preserve owned documentation and lexical notes, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ID lexical	Owner representation	ID: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
UNRESTRICTED_NAME lexical	Owner representation	UNRESTRICTED_NAME: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
NUMBER lexical	Owner representation	NUMBER: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
INT lexical	Owner representation	INT: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
STRING lexical	Owner representation	STRING: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
ML_COMMENT lexical	Owner representation	ML_COMMENT: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.
SL_COMMENT lexical	Owner representation	SL_COMMENT: preserve lexical and path spelling, ownership, types, order, occurrence identity and source provenance as defined in its normative chapter.

INFORMATIVE / COMPLETE MODELS

C. Model and library sources

01 hello

SWA.ML / 01-hello.swaml

```
package Hello {
  port def Messages {
    provides event message(value: string);
  }
  component def Sender {
    port output: Messages;
    operation emit() {
      publish output.message("Hello, SWAML");
    }
    schedule {
      on start emit();
    }
  }
  component def Receiver {
    reversed port input: Messages;
    attribute last: string = "";
    operation accept(value: string) {
      last = value;
    }
    schedule {
      on receive input.message(value) accept(value);
    }
  }
  component Demo {
    component sender: Sender;
    component receiver: Receiver;
    connect (sender.output, receiver.input);
  }
}
```

02 realtime controller

SWA.ML / 02-realtime-controller.swaml

```
package Control {
  import Swaml::Views;
  port def Temperature {
    provides attribute temperature: real;
  }
  port def Commands {
    provides event set(value: real);
  }
  component def Sensor {
    port reading: Temperature;
    operation sample() {
      wait 1ms;
      send reading.temperature(18.5);
    }
    schedule {
      on every 10ms sample();
    }
  }
  component def Controller {
    reversed port reading: Temperature;
    port command: Commands;
    attribute target: real = 21.0;
```

SWA.ML / 02-realtime-controller.swaml / CONTINUED

```
    operation regulate(measured: real) {
      var power: real = (target - measured) * 0.1;
      publish command.set(power);
    }
    schedule {
      on receive reading.temperature(t) regulate(t) deadline 5ms;
    }
  }
  component def Heater {
    reversed port command: Commands;
    attribute power: real = 0.0;
    operation apply(value: real) {
      power = value;
    }
    schedule {
      on receive command.set(value) apply(value);
    }
  }
  component Demo {
    component sensor: Sensor;
    component controller: Controller;
    component heater: Heater;
    connect samples (sensor.reading, controller.reading);
    connect commands (controller.command, heater.command);
  }
  requirement Responsive {
    attribute limitMs: uint = 5;
  }
  test ControlLoop of Demo {
    /** A sample reaches the controller, which commands the heater within its deadline. */
    wait 12ms;
    assert Demo.heater.power > 0.2 and Demo.heater.power < 0.3;
  }
  satisfy Responsive by Demo.controller;
  verify Responsive by ControlLoop;
  view overview: General of Demo;
  view intent: Case of ControlLoop;
  view sequence: Sequence of ControlLoop;
  view inventory: Grid of Demo;
  view architecture: Interconnect of Demo;
  view logic: Flow of Demo.controller.regulate;
  view timing: Timing of Demo.sensor.sample;
}
```

03 service pubsub

SWA.ML / 03-service-pubsub.swaml

```
package Commerce {
  import Swaml::Qos;
  port def Catalog {
    provides idempotent operation get(key: int) returns real;
    provides event changed(key: int);
  }
  component def Store {
    port api: Catalog;
    attribute value: real = 4.5;
    operation get(key: int) returns real {
      wait 1ms;
      return value;
    }
    operation announce() {
      publish api.changed(1);
    }
    schedule {
```

SWA.ML / 03-service-pubsub.swaml / CONTINUED

```
      on call api.get(k) get(k);
      on start announce();
    }
  }
  component def Client {
    reversed port api: Catalog;
    attribute last: real = 0.0;
    attribute changedKey: int = 0;
    operation read() {
      last = try(api.get(1), - 1.0);
    }
    operation changed(key: int) {
      changedKey = key;
    }
    schedule {
      on start read();
      on receive api.changed(k) changed(k);
    }
  }
  component Demo {
    component store: Store;
    component client: Client;
    connect catalog: Reliable (store.api, client.api);
  }
}
```

04 stateful function

SWA.ML / 04-stateful-function.swaml

```
package States {
  import Swaml::Views;
  component Demo {
    attribute lit: bool = false;
    operation lamp() {
      initial Off;
      state Off {
        after 2ms to On {
        }
      }
      state On {
        on entry {
          lit = true;
        } on exit {
          lit = false;
        }
        after 3ms to Done {
        }
      }
      final state Done {
      }
    }
    schedule {
      on start lamp();
    }
  }
  view states: Flow of Demo.lamp;
}
```

05 values and flow

SWA.ML / 05-values-and-flow.swaml

```
package Values {
  import Swaml::Math;
  datatype Reading {
    value: real;
    unit: string;
  }
  enum Mode {
    idle, active
  }
  component Demo {
    attribute sum: int = 0;
    attribute mode: Mode = Mode.idle;
    attribute reading: Reading = record Reading {
      value = 4.5;
      unit = "C";
    };
    operation add(a: int, b: int) returns int {
      return a + b;
    }
    operation boot() {
      var values: int[3] =[1, 2, 3];
      for (value: int in values) {
        sum = add(sum, value);
      }
      mode = Mode.active;
    }
    schedule {
      on start boot();
    }
  }
}
```

06 mixed gateway

SWA.ML / 06-mixed-gateway.swaml

```
package Gateway {
  port def Messages {
    provides event message(value: int);
  }
  component def Sender {
    port output: Messages;
    operation emit() {
      publish output.message(9);
    }
    schedule {
      on start emit();
    }
  }
  component def Receiver {
    reversed port input: Messages;
    attribute last: int = 0;
    operation accept(value: int) {
      last = value;
    }
    schedule {
      on receive input.message(value) accept(value);
    }
  }
  component Demo {
```

SWA.ML / 06-mixed-gateway.swaml / CONTINUED

```
    component sender: Sender;
    component receiver: Receiver;
    connect (sender.output, receiver.input);
  }
}
```

07 client server

SWA.ML / 07-client-server.swaml

```
package ClientServer {
  import Swaml::Qos;
  port def Catalog {
    provides idempotent operation get(key: int) returns real;
    provides event changed(key: int);
  }
  component def Store {
    port api: Catalog;
    attribute value: real = 4.5;
    operation get(key: int) returns real {
      wait 1ms;
      return value;
    }
    operation announce() {
      publish api.changed(1);
    }
    schedule {
      on call api.get(k) get(k);
      on start announce();
    }
  }
  component def Client {
    reversed port api: Catalog;
    attribute last: real = 0.0;
    attribute changedKey: int = 0;
    operation read() {
      last = try(api.get(1), - 1.0);
    }
    operation changed(key: int) {
      changedKey = key;
    }
    schedule {
      on start read();
      on receive api.changed(k) changed(k);
    }
  }
  component Demo {
    component store: Store;
    component client: Client;
    connect catalog: Reliable (store.api, client.api);
  }
}
```

08 service field

SWA.ML / 08-service-field.swaml

```
package Settings {
  import Swaml::Qos;
  port def Catalog {
    provides idempotent operation get(key: int) returns real;
    provides event changed(key: int);
  }
  component def Store {
    port api: Catalog;
    attribute value: real = 4.5;
    operation get(key: int) returns real {
      wait 1ms;
      return value;
    }
    operation announce() {
      publish api.changed(1);
    }
    schedule {
      on call api.get(k) get(k);
      on start announce();
    }
  }
  component def Client {
    reversed port api: Catalog;
    attribute last: real = 0.0;
    attribute changedKey: int = 0;
    operation read() {
      last = try(api.get(1), - 1.0);
    }
    operation changed(key: int) {
      changedKey = key;
    }
    schedule {
      on start read();
      on receive api.changed(k) changed(k);
    }
  }
  component Demo {
    component store: Store;
    component client: Client;
    connect catalog: Reliable (store.api, client.api);
  }
}
```

09 component roots

SWA.ML / 09-component-roots.swaml

```
package Roots {
  component def Counter {
    attribute count: int = 0;
    operation increment() {
      count = count + 1;
    }
    operation boot() {
      increment();
    }
    schedule {
      on start boot();
    }
  }
  component def Fast specializes Counter {
    redefines operation increment() {
```

SWA.ML / 09-component-roots.swaml / CONTINUED

```
      count = count + 2;
    }
  }
  component Demo {
    component left: Counter {
      redefines attribute count: int = 10;
    }
    component right: Fast;
  }
}
```

10 reusable qos

SWA.ML / 10-reusable-qos.swaml

```
package Policies {
  import Swaml::Qos;
  qos def Small: Policy {
    delivery = Delivery.atMostOnce;
    ordering = Ordering.fifo;
    capacity = 2;
    overflow = Overflow.reject;
    requestTimeout = 50ms;
  }
  port def Messages {
    provides event message(value: int);
  }
  component def Sender {
    port output: Messages;
    operation emit() {
      publish output.message(7);
    }
    schedule {
      on start emit();
    }
  }
  component def Receiver {
    reversed port input: Messages;
    attribute last: int = 0;
    operation accept(value: int) {
      last = value;
    }
    schedule {
      on receive input.message(value) accept(value);
    }
  }
  component Demo {
    component sender: Sender;
    component receiver: Receiver;
    connect delivery: Small (sender.output, receiver.input);
  }
}
```

11 autosar classic

SWA.ML / 11-autosar-classic.swaml

```
package Classic {
  import Swaml::Views;
  port def Temperature {
    provides attribute temperature: real;
  }
  port def Commands {
    provides event set(value: real);
  }
  component def Sensor {
    port reading: Temperature;
    operation sample() {
      send reading.temperature(18.5);
    }
    schedule {
      on every 10ms sample();
    }
  }
  component def Controller {
    reversed port reading: Temperature;
    port command: Commands;
    attribute target: real = 21.0;
    operation regulate(measured: real) {
      var power: real = (target - measured) * 0.1;
      publish command.set(power);
    }
    schedule {
      on receive reading.temperature(t) regulate(t) deadline 5ms;
    }
  }
  component def Heater {
    reversed port command: Commands;
    attribute power: real = 0.0;
    operation apply(value: real) {
      power = value;
    }
    schedule {
      on receive command.set(value) apply(value);
    }
  }
  component Demo {
    component sensor: Sensor;
    component controller: Controller;
    component heater: Heater;
    connect samples (sensor.reading, controller.reading);
    connect commands (controller.command, heater.command);
  }
  view architecture: Interconnect of Demo;
  view logic: Flow of Demo.controller.regulate;
  view timing: Timing of Demo.sensor.sample;
}
```

12 autosar adaptive

SWA.ML / 12-autosar-adaptive.swaml

```
package Adaptive {
  import Swaml::Qos;
  port def Catalog {
    provides idempotent operation get(key: int) returns real;
    provides event changed(key: int);
  }
  component def Store {
    port api: Catalog;
    attribute value: real = 4.5;
    operation get(key: int) returns real {
      wait 1ms;
      return value;
    }
    operation announce() {
      publish api.changed(1);
    }
    schedule {
      on call api.get(k) get(k);
      on start announce();
    }
  }
  component def Client {
    reversed port api: Catalog;
    attribute last: real = 0.0;
    attribute changedKey: int = 0;
    operation read() {
      last = try(api.get(1), - 1.0);
    }
    operation changed(key: int) {
      changedKey = key;
    }
    schedule {
      on start read();
      on receive api.changed(k) changed(k);
    }
  }
  component Demo {
    component store: Store;
    component client: Client;
    connect catalog: Reliable (store.api, client.api);
  }
}
```

13 web application

SWA.ML / 13-web-application.swaml

```
package Web {
  import Swaml::Qos;
  port def Catalog {
    provides idempotent operation get(key: int) returns real;
    provides event changed(key: int);
  }
  component def Store {
    port api: Catalog;
    attribute value: real = 4.5;
    operation get(key: int) returns real {
      wait 1ms;
      return value;
    }
    operation announce() {
      publish api.changed(1);
```

SWA.ML / 13-web-application.swaml / CONTINUED

```
    }
    schedule {
      on call api.get(k) get(k);
      on start announce();
    }
  }
  component def Client {
    reversed port api: Catalog;
    attribute last: real = 0.0;
    attribute changedKey: int = 0;
    operation read() {
      last = try(api.get(1), - 1.0);
    }
    operation changed(key: int) {
      changedKey = key;
    }
    schedule {
      on start read();
      on receive api.changed(k) changed(k);
    }
  }
  component Demo {
    component store: Store;
    component client: Client;
    connect catalog: Reliable (store.api, client.api);
  }
}
```

14 cloud service

SWA.ML / 14-cloud-service.swaml

```
package Cloud {
  import Swaml::Qos;
  port def Catalog {
    provides idempotent operation get(key: int) returns real;
    provides event changed(key: int);
  }
  component def Store {
    port api: Catalog;
    attribute value: real = 4.5;
    operation get(key: int) returns real {
      wait 1ms;
      return value;
    }
    operation announce() {
      publish api.changed(1);
    }
    schedule {
      on call api.get(k) get(k);
      on start announce();
    }
  }
  component def Client {
    reversed port api: Catalog;
    attribute last: real = 0.0;
    attribute changedKey: int = 0;
    operation read() {
      last = try(api.get(1), - 1.0);
    }
    operation changed(key: int) {
      changedKey = key;
    }
    schedule {
      on start read();
```

SWA.ML / 14-cloud-service.swaml / CONTINUED

```
      on receive api.changed(k) changed(k);
    }
  }
  component Demo {
    component store: Store;
    component client: Client;
    connect catalog: Reliable (store.api, client.api);
  }
}
```

15 component specialization

SWA.ML / 15-component-specialization.swaml

```
package Reuse {
  component def Counter {
    attribute count: int = 0;
    operation increment() {
      count = count + 1;
    }
    operation boot() {
      increment();
    }
    schedule {
      on start boot();
    }
  }
  component def Fast specializes Counter {
    redefines operation increment() {
      count = count + 2;
    }
  }
  component Demo {
    component left: Counter {
      redefines attribute count: int = 10;
    }
    component right: Fast;
  }
}
```

16 requirements and views

SWA.ML / 16-requirements-and-views.swaml

```
package Traceability {
  import Swaml::Views;
  port def Messages {
    provides event message(value: string);
  }
  component def Sender {
    port output: Messages;
    operation emit() {
      publish output.message("Hello, SWAML");
    }
    schedule {
      on start emit();
    }
  }
  component def Receiver {
    reversed port input: Messages;
    attribute last: string = "";
    operation accept(value: string) {
```

SWA.ML / 16-requirements-and-views.swaml / CONTINUED

```
      last = value;
    }
    schedule {
      on receive input.message(value) accept(value);
    }
  }
  requirement Delivery {
    /** One named routed message reaches the receiver. */
    attribute description: string = "Deliver startup message";
  }
  component Demo {
    component sender: Sender;
    component receiver: Receiver;
    connect (sender.output, receiver.input);
  }
  test Startup of Demo {
    /** The startup greeting reaches the receiver. */
    wait 1ms;
    assert Demo.receiver.last == "Hello, SWAML";
  }
  satisfy Delivery by Demo.receiver;
  verify Delivery by Startup;
  view overview: General of Demo;
  view delivery: Sequence of Startup;
}
```

17 function timing

SWA.ML / 17-function-timing.swaml

```
package Timing {
  import Swaml::Views;
  component Demo {
    attribute count: int = 0;
    operation sample() {
      wait 1ms;
      count = count + 1;
    }
    schedule {
      on every 5ms sample() deadline 3ms;
    }
  }
  view observed: Timing of Demo.sample;
}
```

18 control loops

SWA.ML / 18-control-loops.swaml

```
package Loops {
  component Demo {
    attribute count: int = 0;
    operation boot() {
      while (count < 2, 3 times) {
        count = count + 1;
      }
      until (count == 4, 5 times) {
        count = count + 1;
      }
      for (var i: int = 0; i < 2; i = i + 1) {
        count = count + i;
      }
      for (x: int in[1, 2]) {
        count = count + x;
      }
    }
    schedule {
      on start boot();
    }
  }
}
```

19 interruptible function

SWA.ML / 19-interruptible-function.swaml

```
package Interrupts {
  port def Messages {
    provides event message(value: int);
  }
  component def Sender {
    port output: Messages;
    operation emit() {
      wait 2ms;
      publish output.message(5);
    }
    schedule {
      on start emit();
    }
  }
  component def Receiver {
    reversed port input: Messages;
    attribute last: int = 0;
    operation work() {
      interruptible {
        wait 8ms;
        last = 99;
      } on receive input.message(value) {
        last = value;
      }
    }
    schedule {
      on start work();
    }
  }
  component Demo {
    component sender: Sender;
    component receiver: Receiver;
    connect (sender.output, receiver.input);
  }
}
```

20 classes and operations

SWA.ML / 20-classes-and-operations.swaml

```
package Operations {
  operation def Clamp(v: real, lo: real, hi: real) returns real {
    if (v < lo) {
      return lo;
    }
    if (v > hi) {
      return hi;
    }
    return v;
  }
  component Demo {
    attribute result: real = 0.0;
    operation clamp: Clamp;
    operation low: Clamp {
      return lo;
    }
    operation boot() {
      operation double(v: real) returns real {
        return v * 2.0;
      }
      result = clamp(double(4.0), 0.0, 5.0);
    }
    schedule {
      on start boot();
    }
  }
}
```

21 receive and try

SWA.ML / 21-receive-and-try.swaml

```
package Receiving {
  port def Messages {
    provides event message(value: int);
  }
  component def Sender {
    port output: Messages;
    operation emit() {
      publish output.message(8);
    }
    schedule {
      on start emit();
    }
  }
  component def Receiver {
    reversed port input: Messages;
    attribute last: int = 0;
    operation work() {
      wait 2ms;
      on receive input.message(value) {
        last = value;
      } or after 1ms {
        last = - 1;
      }
    }
    schedule {
      on start work();
    }
  }
  component Demo {
```

SWA.ML / 21-receive-and-try.swaml / CONTINUED

```
    component sender: Sender;
    component receiver: Receiver;
    connect (sender.output, receiver.input);
  }
}
```

22 platform deployment

SWA.ML / 22-platform-deployment.swaml

```
package Placement {
  import Swaml::Platform;
  component def Worker {
    attribute count: int = 0;
    operation boot() {
      count = count + 1;
    }
    schedule {
      on start boot();
    }
  }
  component Demo {
    component workers: Worker[3];
  }
  component def Ecu specializes Node {
    const attribute cores: uint = 2;
    const attribute ref: string = "sysml:Vehicle::ecu";
    component os: Partition;
  }
  component Vehicle: Platform {
    component front: Ecu;
    component rear: Ecu[2];
  }
  deployment OnVehicle of Demo on Vehicle {
    deploy on front;
    deploy workers on rear[0];
    deploy workers[2] on rear[1];
  }
}
```

23 multiplicity

SWA.ML / 23-multiplicity.swaml

```
package Multiplicity {
  component def Counter {
    attribute count: int = 0;
    operation increment() {
      count = count + 1;
    }
    operation boot() {
      increment();
    }
    schedule {
      on start boot();
    }
  }
  component def Fast specializes Counter {
    redefines operation increment() {
      count = count + 2;
    }
```

SWA.ML / 23-multiplicity.swaml / CONTINUED

```
  }
  component Demo {
    component counters: Counter[3];
  }
}
```

24 operation usage

SWA.ML / 24-operation-usage.swaml

```
package OperationUsage {
  operation def Clamp(v: real, lo: real, hi: real) returns real {
    if (v < lo) {
      return lo;
    }
    if (v > hi) {
      return hi;
    }
    return v;
  }
  component Demo {
    attribute result: real = 0.0;
    operation clamp: Clamp;
    operation low: Clamp {
      return lo;
    }
    operation boot() {
      operation double(v: real) returns real {
        return v * 2.0;
      }
      result = clamp(double(4.0), 0.0, 5.0);
    }
    schedule {
      on start boot();
    }
  }
}
```

25 function completion

SWA.ML / 25-function-completion.swaml

```
package Chaining {
  component Demo {
    attribute count: int = 0;
    operation load() {
      wait 1ms;
      count = 1;
    }
    operation report() {
      count = count + 1;
    }
    schedule {
      on start load();
      after load report();
    }
  }
}
```

26 boundary forwarding

SWA.ML / 26-boundary-forwarding.swaml

```
package Boundary {
  port def Temperature {
    provides attribute temperature: real;
  }
  component def Sensor {
    port reading: Temperature;
    operation sample() {
      send reading.temperature(18.5);
    }
    schedule {
      on start sample();
    }
  }
  component def Composite {
    port boundary: Temperature;
    component child: Sensor;
    connect (boundary, child.reading);
  }
  component def Display {
    reversed port reading: Temperature;
    attribute last: real = 0.0;
    operation display(value: real) {
      last = value;
    }
    schedule {
      on receive reading.temperature(value) display(value);
    }
  }
  component Demo {
    component source: Composite;
    component display: Display;
    connect (source.boundary, display.reading);
  }
}
```

27 mixed port

SWA.ML / 27-mixed-port.swaml

```
package Mixed {
  /** One boundary may combine data, event and operation members. */
  port def Boundary {
    provides attribute value: real;
    requires event reset();
    provides operation read() returns real;
    requires operation acknowledge();
  }
}
```

28 use cases

SWA.ML / 28-use-cases.swaml

```
package 'Cash Machine' {
  import Swaml::Views;
  port def Panel {
    provides event cardInserted(cardId: string);
    provides event cashRequested(amount: uint);
    requires event cashDispensed(amount: uint);
  }
  port def Authorization {
    requires operation authorize(cardId: string, amount: uint) returns bool;
  }
  component def Customer {
    /** Actor: a bank customer at the machine. Interface-only: the use cases act through its panel. */
    port panel: Panel;
  }
  component def 'ATM Controller' {
    /** The system under consideration: the subject of the machine's use cases. */
    reversed port panel: Panel;
    port bank: Authorization;
    attribute card: string = "";
    operation remember(cardId: string) {
      card = cardId;
    }
    operation withdraw(amount: uint) {
      var approved: bool = bank.authorize(card, amount);
      if (approved) {
        publish panel.cashDispensed(amount);
      }
    }
    schedule {
      on receive panel.cardInserted(cardId) remember(cardId);
      on receive panel.cashRequested(amount) withdraw(amount);
    }
  }
  component def Bank {
    /** Actor: the card issuer's authorization service. */
    reversed port link: Authorization;
    operation authorize(cardId: string, amount: uint) returns bool {
      return amount <= 500;
    }
    schedule {
      on call link.authorize(cardId, amount) authorize(cardId, amount);
    }
  }
  requirement 'Cash limit' {
    /** A single withdrawal never exceeds the limit. */
    attribute limit: uint = 500;
  }
  component customer: Customer;
  component atm: 'ATM Controller';
  component bank: Bank;
  connect (customer.panel, atm.panel);
  connect (atm.bank, bank.link);
  use case 'Withdraw cash' of atm {
    /** The customer inserts a card, asks for cash and receives it. */
    publish customer.panel.cardInserted("4711");
    publish customer.panel.cashRequested(100);
    on receive customer.panel.cashDispensed(amount) {
      assert amount == 100;
    } or after 2s {
      fail "no cash dispensed";
    }
  }
  use case Authenticate of atm {
    /** The machine reads the card before any transaction. */
    publish customer.panel.cardInserted("4711");
```

SWA.ML / 28-use-cases.swaml / CONTINUED

```
  }
  use case 'Print receipt' of atm {
    /** A receipt may follow a withdrawal. */
  }
  test 'Limit honoured' of atm {
    /** A request above the limit is refused by the bank: no cash, and the card stays known. */
    publish customer.panel.cardInserted("4711");
    publish customer.panel.cashRequested(600);
    on receive customer.panel.cashDispensed(amount) {
      fail "cash above the limit";
    } or after 1s {
    }
    assert atm.card == "4711";
  }
  use case 'Open a branch' {
    /** A use case without of states intent before its subject is chosen. */
  }
  associate customer to 'Withdraw cash';
  associate bank to 'Withdraw cash';
  associate customer to Authenticate;
  associate customer to 'Print receipt';
  associate customer to 'Limit honoured';
  associate bank to 'Limit honoured';
  satisfy 'Cash limit' by Bank;
  verify 'Cash limit' by 'Limit honoured';
  view 'use cases': Case of 'Cash Machine';
  view withdrawal: Sequence of 'Withdraw cash';
}
```

29 executable cases

SWA.ML / 29-executable-cases.swaml

```
package Banking {
  import Swaml::Views;
  port def Panel {
    provides attribute amount: uint;
    provides event cashRequested();
    requires event cashOut(paid: uint);
    requires event refused();
  }
  port def BankLink {
    requires operation authorize(amount: uint) returns bool;
  }
  port def Cash {
    provides event pay(amount: uint);
  }
  requirement 'Cash limit' {
    /** Withdrawals above the limit are refused. */
    attribute limit: uint = 500;
  }
  component def Customer {
    /** Actor: a customer at the machine. Interface-only: a case script acts through its panel. */
    port panel: Panel;
  }
  component def Controller {
    reversed port panel: Panel;
    port link: BankLink;
    port cash: Cash;
    attribute amount: uint = 0;
    operation remember(value: uint) {
      amount = value;
    }
    operation withdraw() {
      var requested: uint = amount;
```

SWA.ML / 29-executable-cases.swaml / CONTINUED

```
      var approved: bool = link.authorize(requested);
      if (approved) {
        publish cash.pay(requested);
        publish panel.cashOut(requested);
      } else {
        publish panel.refused();
      }
    }
    schedule {
      on receive panel.amount(value) remember(value);
      on receive panel.cashRequested() withdraw();
    }
  }
  component def Dispenser {
    reversed port cash: Cash;
    attribute count: uint = 0;
    attribute dispensedToday: uint = 0;
    operation pay(amount: uint) {
      count = count + 1;
      dispensedToday = dispensedToday + amount;
    }
    schedule {
      on receive cash.pay(amount) pay(amount);
    }
  }
  component def ATM {
    /** The machine: a controller and a cash dispenser behind one panel and one bank link. */
    reversed port panel: Panel;
    port link: BankLink;
    component controller: Controller;
    component dispenser: Dispenser;
    connect (panel, controller.panel);
    connect (link, controller.link);
    connect (controller.cash, dispenser.cash);
    operation fee(amount: real, percent: real) returns real {
      return amount * percent / 100.0;
    }
  }
  component def BankHost {
    reversed port link: BankLink;
    operation authorize(amount: uint) returns bool {
      return amount <= 500;
    }
    schedule {
      on call link.authorize(amount) authorize(amount);
    }
  }
  component atm: ATM;
  component customer: Customer;
  component bank: BankHost;
  connect (customer.panel, atm.panel);
  connect (atm.link, bank.link);
  use case Withdraw of atm {
    /** A customer withdraws 200 within the limit. */
    send customer.panel.amount(200);
    publish customer.panel.cashRequested();
    on receive customer.panel.cashOut(paid) {
      assert paid == 200;
    } or after 2s {
      fail "no cash";
    }
  }
  associate customer to Withdraw;
  associate bank to Withdraw;
  satisfy 'Cash limit' by atm;
  view withdrawal: Sequence of Withdraw;
}
```

SWA.ML / 29-executable-cases.swaml / CONTINUED

```
package AtmTests {
  /** An isolation package: the machine under test with an interface-only bank stub. */
  import Swaml::Views;
  import Banking;
  component def BankPeer {
    /** Stub: the test answers authorization requests itself. */
    reversed port link: BankLink;
  }
  component atm: ATM;
  component customer: Customer;
  component bank: BankPeer;
  connect (customer.panel, atm.panel);
  connect (atm.link, bank.link);
  test 'Fee rounding' of atm {
    assert atm.fee(20, 10) == 2;
  }
  test 'Bank refusal' of atm {
    /** The bank refuses: the machine refuses the customer and pays nothing. */
    send customer.panel.amount(100);
    publish customer.panel.cashRequested();
    on call bank.link.authorize(amount) {
      assert amount == 100;
      return false;
    } or after 1s {
      fail "no authorization request";
    }
    on receive customer.panel.refused() {
    } or after 1s {
      fail "not refused";
    }
    assert atm.dispenser.count == 0;
  }
  test 'Approved withdrawal' of atm {
    /** An approved request pays once and counts the amount. */
    send customer.panel.amount(300);
    publish customer.panel.cashRequested();
    on call bank.link.authorize(amount) {
      return amount <= 500;
    } or after 1s {
      fail "no authorization request";
    }
    on receive customer.panel.cashOut(paid) {
      assert paid == 300;
    } or after 1s {
      fail "no cash";
    }
    wait 1ms;
    assert atm.dispenser.count == 1 and atm.dispenser.dispensedToday == 300;
  }
  associate customer to 'Bank refusal';
  associate bank to 'Bank refusal';
  associate customer to 'Approved withdrawal';
  associate bank to 'Approved withdrawal';
  verify 'Cash limit' by 'Bank refusal';
  view refusal: Sequence of 'Bank refusal';
  view checks: Case of AtmTests;
}
```

30 associated integration

SWA.ML / 30-associated-integration.swaml

```
package AssociatedIntegration {
  import Swaml::Views;
  port def Values { provides event value(n: int); }
  component def Source {
    port output: Values;
    attribute sent: bool = false;
    operation emit() { sent = true; publish output.value(0); }
    schedule { on start emit(); }
  }
  component def Cell {
    reversed port input: Values;
    optional port output: Values;
    attribute last: int = -1;
    operation accept(n: int) { last = n + 1; publish output.value(last); }
    schedule { on receive input.value(n) accept(n); }
  }
  component source: Source;
  component c2: Cell;
  component c3: Cell;
  component c4: Cell;
  component c5: Cell;
  component c6: Cell;
  component c7: Cell;
  component c8: Cell;
  component c9: Cell;
  component c10: Cell;
  connect (source.output, c2.input);
  connect (c2.output, c3.input);
  connect (c3.output, c4.input);
  connect (c4.output, c5.input);
  connect (c5.output, c6.input);
  connect (c6.output, c7.input);
  connect (c7.output, c8.input);
  connect (c8.output, c9.input);
  connect (c9.output, c10.input);
  test Delivery of source {
    /** Nine real routed deliveries exercise ten existing components. */
    wait 1ns;
    assert source.sent;
    assert c2.last == 1 and c5.last == 4 and c10.last == 9;
  }
  associate c2 to Delivery;
  associate c3 to Delivery;
  associate c4 to Delivery;
  associate c5 to Delivery;
  associate c6 to Delivery;
  associate c7 to Delivery;
  associate c8 to Delivery;
  associate c9 to Delivery;
  associate c10 to Delivery;
  view integration: Sequence of Delivery;
}
```

31 case subject calls

SWA.ML / 31-case-subject-calls.swaml

```
package SubjectCalls {
  import Swaml::Views;
  port def Status { provides event changed(value: int); }
  component def Counter {
    port status: Status;
    attribute count: int = 0;
    operation advance() returns int {
      count = count + 1;
      wait 1ns;
      publish status.changed(count);
      return count;
    }
  }
  component subject: Counter;
  component observer { reversed port status: Status; }
  connect (subject.status, observer.status);
  use case Advance of subject {
    /** Invoke the subject, then consume the actor message retained during the call. */
    var result: int = subject.advance();
    on receive observer.status.changed(value) {
      assert result == 1 and value == result;
    }
  }
  associate observer to Advance;
  test AdvanceAndInspect of subject {
    var result: int = subject.advance();
    on receive observer.status.changed(value) {
      assert result == 1 and value == subject.count;
    }
  }
  associate observer to AdvanceAndInspect;
  view behavior: Sequence of Advance;
}
```

swaml 2.0

SWA.ML / swaml-2.0.swaml

```
package Swaml::Qos {
  enum Delivery { bestEffort, atMostOnce, atLeastOnce }
  enum Ordering { fifo, unordered }
  enum Overflow { dropOldest, dropNewest, reject }
  qos def Policy { }
  qos def Default: Policy { delivery = Delivery.atMostOnce; ordering = Ordering.fifo; capacity = 16; overflow = Overflow.reject; requestTimeout = 1s; }
  qos def Latest: Policy { delivery = Delivery.atMostOnce; ordering = Ordering.fifo; capacity = 1; overflow = Overflow.dropOldest; requestTimeout = 1s; }
  qos def Reliable: Policy { delivery = Delivery.atLeastOnce; ordering = Ordering.fifo; capacity = 16; overflow = Overflow.reject; requestTimeout = 1s; }
  qos def BestEffort: Policy { delivery = Delivery.bestEffort; ordering = Ordering.unordered; capacity = 16; overflow = Overflow.dropNewest; requestTimeout = 1s; }
}
package Swaml::Views {
  view def General; view def Interconnect; view def Case; view def Sequence;
  view def Grid; view def Flow; view def Timing;
}
package Swaml::Platform {
  component def Node { }
  component def Platform specializes Node { }
  component def Partition specializes Node { }
  component def Process specializes Node { }
}
```

SWA.ML / swaml-2.0.swaml / CONTINUED

```
package Swaml::Calls { enum CallFailure { timeout, unavailable, rejected, transport, remoteFailure,
interrupted } }
package Swaml::Math {
  operation def abs(v: real) returns real { if (v < 0.0) { return -v; } return v; }
  operation def min(a: real, b: real) returns real { if (a < b) { return a; } return b; }
  operation def max(a: real, b: real) returns real { if (a > b) { return a; } return b; }
  operation def floor(v: real) returns int { /** Host intrinsic: checked floor conversion. */ }
  operation def round(v: real) returns int { /** Host intrinsic: ties toward positive infinity. */ }
  operation def trunc(v: real) returns int { /** Host intrinsic: truncate toward zero. */ }
  operation def length(v: string) returns uint { /** Host intrinsic: Unicode scalar count. */ }
  operation def concat(a: string, b: string) returns string { return a + b; }
}
```

INFORMATIVE / GUIDANCE AND PROJECT STATUS

swa.ml 2.2 release

10 November 2026. Standard 2.2, parser/host semantics 2.2, reference profile `swaml-reference/2.2`, reference implementation package 3.1.0. The concrete grammar is unchanged from 2.1. Hosts select the new semantics and pin an exact implementation revision; source models need no new syntax.

Primary-subject operation calls

Both use cases and tests may also call operations of their exact primary subject, including operations that communicate through their own ports, receive or wait. The call uses the subject's actual serial context, releases its lock during suspension and returns to the case on completion. It retains local-call semantics without a new schedule activation, route, transport timeout or `after` release. Caller context restores on return or failure; failing statements retain their actual source and outputs copy back only after success. Stateful operations remain on-start-only. See ADR 0021 and example 31.

A case is sequential: a later actor reply branch cannot execute while that same case is blocked in a subject call. Use independently behaving actors or stimulate the subject asynchronously before serving its reply. Waiting calls occupy ordinary whole-value statements, declarations or assignments, with optional `try`; evaluate a call before a loop if its result is needed in the header.

Referencing associated test components

Tests may inspect their subject, explicitly associated software component occurrences and those roots' single parts. Existing `associate` links and dotted paths express the references. Use cases gain no private reads or direct calls on parts or associated peers. Tests' helper calls outside the primary subject may change the target through its operation but must neither communicate nor suspend. Direct attribute assignment remains forbidden. See ADR 0020 and the ten-component integration.

Neither case kind owns components. Associations reference existing same-package software occurrences; they do not select execution roots, choose a fixture topology or suppress unrelated startup work. Every case still runs a fresh package configuration. Indexed component paths remain outside the grammar. Actor-port association, interface-only, direction and route rules are unchanged.

Publication and compatibility

The release includes the complete reference, PDF, source manifest and SHA-256 checksum. The publication gate checks exact current sources, embedded attachments, navigation, readable bounds and every rendered page. A tagged release and uploaded artifacts establish publication; a source merge alone does not.

All published 2.1 reference, 2.1 PDF, manifests, checksums, figures, release notes and tags retain their bytes, as do earlier editions. The 2.2 assets use their own paths. This edition extends the supported 2.1 behavior without a compatibility parser or source migration. Passing tests and example cases remain bounded evidence, not universal verification or production scheduling certification.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

Quick start: swa.ml 2.2

Read a model in this order: components, attributes, ports, operations, schedule, connections. A def defines a reusable type/body; a usage creates a distinct occurrence. Every value has an explicit type. Every cross-component message has an owned port and explicit route.

SWAML

```
package HelloGuide {
  port def Greeting { provides event message(text: string); }
  component def Speaker {
    port output: Greeting;
    operation greet() { publish output.message("Hello, swa.ml"); }
    schedule { on start greet(); }
  }
  component def Listener {
    reversed port input: Greeting;
    attribute last: string = "";
    operation accept(text: string) { last = text; }
    schedule { on receive input.message(text) accept(text); }
  }
  component Demo {
    component speaker: Speaker;
    component listener: Listener;
    connect (speaker.output, listener.input);
  }
}
```

Install dependencies with npm ci, build with npm run build, then validate the saved file using node out/src/cli/main.js --json hello.swaml. To execute, create options.json with {"untilNs": 1000000} and run node out/src/cli/simulate.js HelloGuide::Demo options.json hello.swaml. Listener.last becomes Hello, swa.ml through a real routed event. Bare connect uses the pinned Default policy.

Continue with the usage guide, complete examples, AI guide and support matrix. The 2.2 edition uses the same concrete grammar as 2.1; hosts must select its added test semantics deliberately. See the 2.2 release notes. Published references, including 2.1, remain unchanged; the 2.1 release notes describe the migration from 2.0.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

swa.ml 2.2 usage guide

Start with a component, give each persistent value a typed attribute, and write named operations for behavior. Add a schedule to say when those operations run. Add directed ports and explicit connections when behavior crosses component boundaries.

This guide targets the 2.2 host semantics and the unchanged 2.1 concrete grammar. For repository validation use Node.js 26.12.0 from .node-version and npm 10.2.3+, then run npm ci and npm run build. Validate with node out/src/cli/main.js --language-version 2.2 model.swaml. Files are headerless; the host and exact package revision select the edition. The published 2.1 reference remains frozen.

A first model

SWAML

```
package Counter {
  component Demo {
    /** A small autonomous counter. */
    attribute count: int = 0;
    operation increment() {
      count = count + 1;
    }
    schedule {
      on every 10ms increment();
    }
  }
}
```

Demo is the execution root. count belongs to its occurrence for the run; a var inside increment would belong to that activation/block. The schedule releases at 10ms, 20ms and so on, with a default 10ms deadline. Operations without a schedule entry are local helpers. Unscheduled behavior is not automatically executed.

Create options.json containing {"untilNs": 25000000}, then run:

SH

```
node out/src/cli/simulate.js Counter::Demo options.json model.swaml
```

The final Demo.count is 2. The JSON records sources, logical trace, limits and final stores. It is bounded reference evidence with zero physical CPU cost. It does not prove production timing.

Reuse structure without sharing state

SWAML

```
package ReuseGuide {
  component def Counter {
    attribute count: int = 0;
    operation increment() { count = count + 1; }
    schedule { on start increment(); }
  }
  component Demo {
    component left: Counter {
      redefines attribute count: int = 10;
    }
    component right: Counter;
    component bank: Counter[3];
  }
}
```

left starts with its own count at 10, then reaches 11. right and every bank index reach 1 independently. A usage body adds members or explicitly redefines an inherited whole member. Single specializes inheritance follows the same rule. Definition identity is shared; occurrence state is separate. Use bank[0] in connector/deployment/view paths. Port arrays and connector loops are absent.

Choose the value's lifetime

Use const attribute for a fixed per-occurrence configuration value, attribute for mutable component state, var for lexical activation data and typed parameters/results for copied calls. Requirements own immutable attributes. Never read another component's private state by a dotted path.

Primitive types are bool, byte, uint, int, real and string; arrays have fixed extents. Define nominal records with datatype and enums with enum. Construct records with every field, as in record Reading { value = 2.5; unit = "C"; }. Access an enum with Mode.active, or a qualified package name if a local value shadows Mode. Check the values example for a complete model. Numeric overflow, division by zero and dynamic invalid indexes fail at runtime; narrowing real to int uses the checked Math conversions.

Compute with operations

SWAML

```
package OperationGuide {
  operation def Clamp(v: real, lo: real, hi: real) returns real {
    if (v < lo) { return lo; }
    if (v > hi) { return hi; }
    return v;
  }
  component Demo {
    attribute result: real = 0.0;
    operation clamp: Clamp;
    operation calculate() {
      operation double(v: real) returns real { return v * 2.0; }
      result = clamp(double(4.0), 0.0, 5.0);
    }
    schedule { on start calculate(); }
  }
}
```

A declaration has parentheses and optional returns; a usage has a type and inherits its signature. Its optional body replaces the whole definition body. Nested operations come first and never capture the outer operation's parameters/locals. Pass values explicitly. Component operations may read/write their own attributes. Package definitions can use only parameters/nested operations. Calls are expressions; void calls are statements; a value result cannot be discarded. Out arguments name mutable compatible cells and copy back only after success. Recursion and overloading are absent.

Import Swaml::Math explicitly for abs/min/max/floor/round/trunc/length/concat. View, QoS, CallFailure and Platform libraries are also loaded and explicitly imported when using their short names. Do not invent host built-ins or assume an arbitrary library exists.

Connect components

The hello model is the smallest complete routed example. A port definition declares provides event message(value: string). Sender owns a port of that type and emits with publish. Receiver uses reversed port, making that member requires, and binds it once in on receive. The root connects the two child ports.

Use provides/requires on each member, rather than assigning a role to the whole port. send updates a provided attribute; publish emits a provided event; p.operation(args) calls a required operation. Port definitions may differ if their members match structurally by name and compatible type. Records/enums remain nominal. A boundary-to-child same-direction connection forwards the boundary without queue/latency; it cannot have a policy or local handler.

A bare connect uses Swaml::Qos::Default: atMostOnce, fifo, capacity 16, reject, request timeout 1s. Select a named complete policy with connect link: Reliable (a.p, b.p). Reliable requests need an idempotent provided operation. Attributes retain the latest pending value regardless of event/request buffering. Nonoptional ports of every concrete root must resolve to a connection. optional only waives that port's closure requirement.

Serve and request a value

See the service example. The provider binds its provided operation through on call api.get(k) get(k). The consumer calls its own required member and usually chooses an explicit fallback:

```text
last = try(api.get(1), -1.0);
```

Timeout comes from the route policy. A bare failing call fails the activation; try catches runtime expression failures and evaluates fallback lazily. Static errors, interruption, deadlines and resource violations cannot be caught. Committed effects remain committed. The reason is trace evidence and is not an implicit model variable. A suspending call must be the whole initializer, assignment value or statement, optionally wrapped in try; avoid api.get(1) + 2.

Schedule and suspend deliberately

on start runs once; on every D runs periodically; on receive binds an incoming event/attribute; on call serves a provided operation; after op runs after successful whole same-owner completion. One operation may have several entries, but the same trigger/operation pair cannot appear twice in one block. After dependencies are acyclic and release fresh parameterless void activations, with no forwarded arguments or result. The chaining example shows this distinction.

wait, requests and receive statements release the component's serial lock. Another activation can change attributes before resumption. Recheck conditions after resuming before writing state. A concurrent entry cannot write state, even through a helper or out argument, and always reads its dispatch snapshot. Entry deadlines include suspension/backlog; an every entry defaults to its period. WCET belongs to target binding/evidence.

while tests first; until tests after its body. An optional n times limit evaluates once and exits normally. Counted for and copied-array for in have lexical loop scopes. The loop model covers every form. Unbounded loops are permitted but a finite run has a step budget/deadline.

Receive, interrupt and model state

Receive statements wait for one of several explicitly bound inputs or a timeout, keeping early input queued. An interruptible region is armed only during its body/callees and transfers within the same activation, preserving committed effects. Inactive region input is discarded observably; heed SW2012.

For a state machine, write initial and state directly in an operation. Put transitions inside each source state, in the order they should be tested. Use on entry/on exit, on receive with optional when, after D to Target, and final state. A stateful operation has no parameters/result and exactly one on start schedule entry. The state example completes at its final state; idle reactions do not release after dependents.

Describe deployment, intent and views

Use a separate deployment declaration over software and platform roots. Targets are component occurrences specializing Swaml::Platform::Node. Const attributes may retain external ref identities; task/core scheduling stays in target adapters. The deployment example shows family placement with an indexed override.

Requirements, satisfy and test/verify record intent. The traceability example includes a test of its root, satisfy and verify links and views. A case does not inject events at a destination; a case script acts through actor ports and its pass is evidence of one run, not proof.

A package is a closed context. Declare the system and its surroundings as top-level component occurrences and join their ports with package connections, connect (customer.panel, atm.panel);. Write use case Name of subject { … } or test Name of subject { … } in the package; the subject is its focal top-level occurrence. A case without statements records intent only and may omit of; a script requires of. Script-driven actors and stubs are interface-only components, component def Customer { port panel: Panel; }, which need no implementation; associate customer to 'Withdraw cash'; records participation. satisfy Requirement by design; claims a component definition or occurrence path of the package, and verify Requirement by Test; links a test. The use case example shows these package links and quoted names.

A case body may continue after its documentation with statements acting through its associated interface-only actors: publish customer.panel.cashRequested(100); and on receive customer.panel.cashDispensed(amount) { assert amount == 100; } or after 2s { fail "no cash"; }. A script can answer a stub request with on call bank.link.authorize(amount) { return false; }. Both use cases and tests may call operations of their primary subject, such as var amount: int = atm.withdraw(20);. The operation runs in the subject's own context and may communicate, receive and wait; the case resumes when it returns. A test may additionally inspect private attributes and call eligible helpers on explicitly associated same-package roots and single parts. Use cases cannot inspect private state or directly call those extra owners. Association does not create components or permit impersonating an active collaborator's ports.

Subject calls are sequential. An event emitted by the subject can stay queued for a later actor receive, as in the subject-call example. If the subject instead waits for a reply from an actor, a later reply branch in the same blocked case cannot run. Give that actor independent behavior, or start the subject with an actor event before handling its reply. Stateful operations retain their on-start-only lifecycle. Suspended calls use a whole initializer, assignment or statement; immediate calls may still appear in expressions.

swaml test runs every case in its own fresh whole-package run and reports pass, fail, inconclusive or no checks; the executable cases example adds an isolation package with a bank stub, and the associated-component example checks several implemented peers. Names containing spaces, letters outside ASCII or reserved words are written in single quotes, for example use case 'Withdraw cash' or attribute 'state': int = 0;.

Import Swaml::Views and type views by General, Interconnect, Case, Sequence, Grid, Flow or Timing. Compact of selects a subject; include/recursive/where builds a stable union. Filter kinds are component and operation for the structural/executable families. Browser navigates ownership; Flow combines statements/states; Timing separates declared schedule/deadline information from identified observed traces. Presentation layout belongs in sidecars, not language source.

Validate and repair

SH

```sh
node out/src/cli/main.js --json model.swaml
node out/src/cli/main.js --format model.swaml
node out/src/cli/main.js --check-format model.swaml
npm run check
```

Load every application dependency together. Fix syntax/names first, then ownership/routes, types/effects and schedules. JSON diagnostics expose stable codes/ranges and identity metadata. Always revalidate after a repair; formatting is not a semantic repair. Read AI authoring, the keyword reference and the support matrix for precise boundaries.

Test explicitly associated components

In the 2.2 semantics, a test may inspect its primary subject and the software components explicitly referenced by its `associate` links, including their single parts. The components remain owned by the structural model. For example:

SWAML

```
package AssociatedTests {
  component def Counter { attribute count: int = 0; operation bump() { count = count + 1; } }
  component def Assembly { component worker: Counter; }
  component primary: Counter;
  component companion: Assembly;
  test Integration of primary {
    companion.worker.bump();
    assert primary.count == 0 and companion.worker.count == 1;
  }
  associate companion to Integration;
}
```

Without the association, access to `companion` is rejected. A use case gains no private state or direct peer/part access from that association. Normal calls on the exact primary subject work in both case kinds; helper calls on the extra test owners must neither communicate nor suspend, although they may change the target through its own operation. Direct attribute assignment stays forbidden. Communicate through the subject's own operation or associated interface-only actor ports and real connections; association does not let a script take over an active component's ports.

Every case still initializes and runs its whole package, and each run gets fresh stores. Associations do not select a subset, disable unrelated startup work, create an atomic snapshot or own components. Only executed, non-multiple software roots are accessible; nested singleton parts work, while intermediate component indexes remain unsupported. See the ten-component routed integration and 2.2 release notes.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

AI authoring with swa.ml 2.2

Treat swa.ml as typed source that must be validated, rather than prose to approximate. Start with the usage guide, inspect a relevant complete example, and read the affected normative chapter. Pin parser 2.2 and the exact package revision. Use the portable repository skills swaml-author and swaml-validate; they are versioned with the language and may be installed in the user's agent skill directory. They do not authorize publication or external messages.

Build a model from intent

Identify execution roots and reusable component definitions. Assign each persistent value to one component attribute, configuration to const attribute and scratch data to var. Identify every exchange before writing behavior: give its two sides owned port members with provides/requires, then an explicit connect route. Decide which inputs are queued events and which are latest attributes. Bind each input exactly once.

Write operations with explicit parameter/result types. Use return for values, expressions for calls and statements for void calls. Nested operations take explicit inputs; they do not capture enclosing locals. A package operation def is parameter-only reusable behavior. Use a usage to reuse its signature/body. No class/function/calc/interface, role suffixes, call/as syntax, profile or old transition syntax is accepted.

Put activation in one schedule. Use on start/every/receive/call or after same-owner operation. Select complete policy definitions where Default is unsuitable. Keep remote calls as whole initializer/assignment/statement forms, optionally in try. Recheck live attributes after suspension; use concurrent only when the transitive operation graph cannot write. Copy-back of out parameters occurs only on success.

Multiplicity is literal and paths are indexed explicitly. Deployment targets are platform Node occurrences. Requirements express intent. A case without statements records intent; a case with statements drives its primary subject through normal operation calls or associated interface-only actor ports and runs with swaml test, as bounded evidence rather than proof. A package is a closed context: declare top-level component occurrences, join their ports with package connections, connect (customer.panel, atm.panel);, and write use case Name of subject { … } or test Name of subject { … } as package members, where the subject is a top-level occurrence of the same package. Write script-driven external systems and stubs as interface-only components (ports only) and associate them with associate customer to Name;. Script endpoints use occurrence.port.member, and on call bank.link.authorize(amount) { return true; } answers a stub request. Private reads and direct helper calls on parts/peers remain test-only; a normal primary-subject call works in either case kind. Claims are package links: satisfy Requirement by design; and verify Requirement by Test;. Quote names that contain spaces, letters outside ASCII or reserved words, such as 'Withdraw cash'. View definitions select existing identities, with geometry separate.

Validate-fix loop

SH

```sh
npm run build
node out/src/cli/main.js --json model.swaml dependency.swaml
node out/src/cli/main.js --format model.swaml
node out/src/cli/main.js --json model.swaml dependency.swaml
```

Inspect errorCount and diagnostic code/range/message/data. Resolve parser/name errors before reasoning from a recovered AST. Fix the smallest relevant declaration, keeping private scopes and explicit routes intact. A suggested edit is advice to revalidate, never permission to apply a stale edit. Validate the complete source workspace after changes, including negative lookups made ambiguous by newly loaded files. Never invent a library, untyped value, implicit port, hidden event or direct destination injection to silence diagnostics.

Run a bounded simulation only after validation. Choose the run target: a package runs its top-level occurrences with their package connections, Package::component runs one top-level occurrence with its ports open. Record source bytes/hashes, target, profile, options, deployments and trace; trace sources name the statements that caused each observation. Inspect final occurrence stores and relevant failure/timeout/discard/interrupt observations. A caught failure is still evidence of that runtime failure; no-failure-observed is a finite-run statement. Show declared timing separately from observed intervals and never label zero-cost logical steps as measured WCET.

Common diagnostics

Group	Repair direction
SW2001	Load/import the correct package, disambiguate a name, remove shadowing
SW2002	Correct explicit types, record shape, fallback/result or array bounds
SW2003	Add explicit redefines only for a real compatible inherited member; break cycles
SW2004/2005	Repair member direction/type/route/closure, emission provenance or exclusive input owner
SW2006	Correct nested scope, return/out use, effects or whole-expression suspension
SW2007/2008	Repair schedule identity/signature/after graph or ordered state ownership
SW2009/2010	Resolve occurrence/Node paths, case subjects, associate/satisfy/verify targets in the same package, view subject, or a script actor that must be associated and interface-only
SW2011/2012	Recheck live state after resumption; account for inactive interrupt input
SW2013	Supply complete typed policy values and safe positive durations

Keep diagnostics/evidence honest. Consult implementation status before claiming full V/E/G/K support. Publishing a page or release is a separate user-authorized action; this project requires a design preview before publication.

For 2.2 tests, resolve each inspection root to the subject or an explicit same-package `associate` occurrence. Follow only existing single parts; preserve effective inherited members and exact occurrence identity. Both case kinds may call operations of the exact primary subject normally, including its own port communication and waits; use cases gain no private reads, part calls or peer calls. Calls on extra test owners remain immediate noncommunicating helpers. Unassociated peers, same-prefix names, platform roots and multiplicity families do not gain access. Association never owns an occurrence or narrows the whole-package run. Actor interaction keeps its associated interface-only port rules. See ADR 0020 and ADR 0021.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

Architecture patterns

swa.ml 2.2.

Start each pattern from owned component state and explicit typed boundary members. Components may be leaves or composites and both may own operations. A composite forwards a port to an immediate child with same-direction connect; peer connections use opposite-compatible directions and own queues.

A pipeline sends latest attributes when freshness matters and publishes events when every occurrence matters. The controller model samples temperature, computes power and publishes an actuator command. Each receiver owns its input once; no private data is read through a sibling path.

A service uses required/provided operation members, on call schedule bindings and a policy request timeout. try supplies a lazy fallback. Suspension unlocks the caller; recheck live state before committing a decision. Service model.

Publish/subscribe fanout uses event-only required ports and several explicit connections. Each connection occurrence has an independent policy queue; partial fanout may commit before a failed offer. Adding an attribute or operation requirement changes cardinality to exactly one peer.

Reusable components use single specializes inheritance and explicit compatible whole-member redefines. Usage bodies configure per-occurrence const/attribute values without sharing stores. Reuse and multiplicity.

Classic, Adaptive, web and cloud example filenames illustrate these software patterns. They do not claim generated RTE/task, middleware, broker, infrastructure or production timing bindings. Deployment places software on platform Node occurrences; target translation is separate.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

Ontology and views

swa.ml 2.2.

The semantic families are package, nominal values/types, component definition/usage, attribute/local/parameter, port/member, operation definition/declaration/usage, schedule/entry, connection/forwarding, state/transition, deployment, requirement, case and view. A nested operation has no closure capture; an operation body has no independent executable identity. An indexed occurrence is distinct from its shared definition.

Browser navigates ownership. Seven imported library definitions provide source views: General, Interconnect, Case, Sequence, Grid, Flow and Timing. General and Grid can select named model identities; Interconnect selects components; Case selects packages, cases and components; Sequence also selects operations; Flow/Timing select operations, use cases and tests. General Box in box and Tree retain the same selected graph. Flow contains statements, loops, receive/interrupt regions and states.

Compact of selects one subject. Include/recursive/where selects a stable union with Boolean name/kind/path predicates. Structural/executable kinds are component and operation. Filters do not call behavior. Timing declared mode shows schedules/deadlines/static waits; observed mode requires a run identity and preserves open intervals. Geometry/routing/camera live in sidecars. See normative view rules and traceability example.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

swa.ml 2.2 reference simulation

The portable interpreter selects **swaml-reference/2.2** and requires linked, validated source. All activation comes from ordinary source schedules/ports/routes, including authored test drivers. Execution semantics is normative; this guide covers the reference host.

SH

```sh
npm ci
npm run build
node out/src/cli/main.js --json examples/01-hello.swaml
node out/src/cli/main.js simulate --until-ns 10000000 examples/28-use-cases.swaml
node out/src/cli/main.js simulate --target Hello::Demo --options examples/simulation/01-hello.json examples/01-hello.swaml
node out/src/cli/simulate.js Hello::Demo examples/simulation/01-hello.json examples/01-hello.swaml
node out/src/cli/main.js test examples/29-executable-cases.swaml
node out/src/cli/main.js test --json --case 'AtmTests::Bank refusal' examples/29-executable-cases.swaml
node scripts/check-simulations.mjs
```

A run target is a package or one top-level component occurrence (ADR 0019). A package target such as 'Cash Machine' runs every top-level software occurrence of the package with its internal connections, the package connections between top-level ports and each occurrence's deployment. Platform roots, top-level occurrences that specialize Swaml::Platform::Node, only describe deployment targets and do not run. A component target such as Hello::Demo runs that top-level occurrence alone: its package connections are absent and its top-level ports are open, so emissions find no route and requests fail as unavailable. swaml simulate takes --target Package or --target Package::component and defaults to the package when the supplied sources declare exactly one; it needs either --options file.json or --until-ns N. The positional swaml-simulate host takes the same targets. The core exports runTargets and runTarget for hosts that list or resolve targets.

Options include required untilNs and optional maxSteps (100000), maxPending (1024), maxConcurrent (64), latencyNs (0) and explicit offer-indexed faults. Unknown options are rejected. A top-level occurrence has at most one deployment (SW2009), and every run applies it to that occurrence's tree; there is no deployment selection option. faults contains an offer number, kind drop/duplicate/transport and optional delayNs. Faults operate on real routed source emissions/requests, never destination injection. The deterministic backend chooses insertion order for unordered queues and records its delivery assumptions.

Serial wait/request/receive suspensions release the component lock; resumption reads live state. Concurrent activations retain a dispatch snapshot and cannot write. Default connection policy is atMostOnce/fifo/16/reject/requestTimeout 1s. Attribute queues keep latest values independently. try catches runtime expression failures with lazy fallback and retained effects; deadlines/resources/interrupts bypass it. Requests retain route correlation, timeout wins ties and late replies are suppressed. After edges release fresh work after successful whole completion/unlock.

The JSON result records profile, target (kind package or component and its identity), options, logical trace ordinals/identities, sources, final occurrence stores, state machines and placements. Store and deployment keys are occurrence paths that begin with the top-level occurrence name, such as atm or Demo.receiver. Route identities are occurrence-relative: Demo.@connect0 inside a component, and the connection name or @packageN for the Nth package connection. CLI adds SHA-256 source digests. Status is quiescent, horizon, violation, limit, or stopped for a case run that ended with its script; a case run whose script still waits with no event left is quiescent. Failure observations remain evidence even when a caller catches them. Horizon retains live/open intervals. An event left pending without possible progress may be quiescent; that is not proof of useful behavior.

Statement sources

Trace events carry source, the statementIdentity of the statement or schedule entry that caused them: write, publish, send, assert, failure, caught, arm, wait, receiveWait and requestWait name the executing statement; release and dispatch name the schedule entry; state names the entered state. Message lifecycle events name the statement that emitted or requested the message: offer, deliver, replaceAttribute, overflow, drop, retry, discardAge, discardInput and interrupt (which also records the armed interruptible statement as region) name the emitting send or publish or the requesting call; request, reply, timeout, lateReply and cancelRequest name the requesting call. A loop condition belongs to its loop statement on every iteration. In a state machine, the wait for a transition belongs to the state, and a guard and its failure to the transition. Offers record the leaf ports as sourcePort and targetPort, deliveries as targetPort. An assert event records passed; a failed assert also produces a failure.

A statement identity is the identity of its executable, a slash and a statement path, for example Hello::Sender.emit/0 or Banking::ATM.serve/2/then/0. The executable identity is the declaring operation, or a case, with decoded names; an operation usage that inherits its body names the definition. The path walks the abstract syntax from the executable's body: a statement contributes its index in the enclosing statement list and every other step its slot name, followed by an index for list slots: then, otherwise, body, branches/N, timeoutBody, handler, initializer, update, states/N, actions/N, transitions/N and effect. A state is itself identified as Executable/states/N and a transition, with its guard, as Executable/states/N/transitions/M. A schedule entry is the component identity followed by /schedule/N. resolveStatement maps an identity back to its node, trying the longest declared owner first because a quoted name may contain a slash. Legal names can therefore make it ambiguous: an operation 'run/0/then' with statement 0 and an operation run with statement path 0/then/0 both yield Pkg::Def.run/0/then/0, and resolveStatement selects the longer owner. Avoid such names when trace sources must be unambiguous. Identities follow source structure, so reordering statements changes them. Preserve available subject and activation fields; these often distinguish occurrences but cannot distinguish every borrowed-call failure or repeated invocation. Do not copy a shared declaration's facts to every instance, or claim that an individual read, short-circuited subexpression or return was observed when the trace provides no such observation.

The examples' expected final stores and placements are checked independently, every use case and test of the examples runs with its expected result (examples/simulation/cases.json), and deterministic reruns check reproducibility. The current 2.2 hello trace uses the selected 2.2 profile; the published 2.1 trace stays frozen. Tests cover package and isolated component runs, adversarial requests, interruptions, failure effects and resource limits. Physical CPU/WCET, production transport/retry protocols, target scheduling and universal analysis remain outside this logical interpreter. Exporting a trace does not establish those claims.

Outcome failure-observed includes caught expression failures as well as failed activations; status separately records whether execution reached quiescence, a horizon or a resource/contract stop. The CLI returns 1 when a failure was observed, including a successfully handled fallback, so automation must inspect the trace and final stores when exercising expected failure scenarios.

Use cases and tests

A use case or test with statements is a script (behavior, case runs). swaml test runs the cases of the supplied sources:

```text
swaml test [--language-version 2.2] [--package P] [--case Package::Case|Case] [--json] [--options
options.json | --until-ns N] file.swaml [more files...]
```

Each case with statements runs in its own fresh run of its package. The default horizon is 10 s of logical time (untilNs 10000000000); the run stops earlier when the script completes or fails. The script is one serial activation released at 0 ns after every on start entry. Both case kinds may call operations of the exact primary subject, including its own port communication, receive and wait behavior; the actual frame uses the subject's context, releases its lock while suspended and restores the caller context on return or failure. This remains a local call, with no new schedule release or implicit transport timeout. The script also acts at the

ports of its associated interface-only occurrences. Input that reaches an actor port before the script waits for it is retained under the connection's policy and attributes keep their latest value. A request to an actor port waits until an on call branch answers it or the caller's request times out; a later branch in the same case cannot run while blocked in a synchronous subject call. A test additionally reads private attributes and calls eligible helpers of explicitly associated same-package roots and single parts. Those extra helper calls cannot communicate or suspend. Associations do not create occurrences or alter the whole-package run.

Results are pass, fail, inconclusive and no checks. The first failure in trace order decides a failed case, with its statement identity and time: the script's own (a failed assert reports Assertion and the assert source, fail reports its message, a runtime failure its code), an uncaught failure of another activation (run-failure, with the failing activation as observed), or a contract violation (violation). An earlier run failure, such as a request timeout of the subject at 1 s, therefore wins over a later fail of the script. A case is inconclusive when the run ends before the script completes without a failure: at the horizon (horizon), at the step limit (limit), or because the script waits but no further event can occur (stalled); a stalled case run has status quiescent, since nothing remains that could reach the script, while ordinary runs keep horizon for waiting activations so that their intervals stay open. A case without statements has no checks. Caught failures stay evidence without failing a case: a passing case can carry run.outcome failure-observed, with caught events in its trace, when a try fallback handled a failure, so consumers read result rather than outcome. The summary prints one line per case and a count; --json prints languageVersion, profile, options, summary and cases with case, kind, subject, result, reason, message, source, timeNs and the run (target, status, trace and stores, without source text), plus implementation identity and source digests. The exit code is 1 when a case fails or the sources are invalid, 2 for usage errors and 0 otherwise.

The core exports runCase(models, 'Package::Case', options), runTests(models, options, { package, case }) and workspaceCases(models), returning CaseResult values, and caseTarget from semantic, which resolves a script path to an actor port member, a white-box operation or an attribute. Script trace events name the case identity as subject, for example AtmTests::Bank refusal, and carry case statement identities such as AtmTests::Bank refusal/2/branches/0/body/0 as source; failure events also record the message of fail and of a failed case assert. A package run, without a case, leaves interface-only occurrences idle.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

Requirements, documentation and intent

swa.ml 2.2.

A requirement owns immutable typed attributes and at most one formal doc. Use `/** ... */` first in a body or immediately before the semicolon of a leaf declaration. Ordinary `//` and `/* ... */` comments remain separate lexical annotations. Formal documentation is owned source, not an executable statement or proof.

satisfy Requirement by design; links intent from a component definition or occurrence path declared in the same package. verify Requirement by Test; links a test of the package; a use case never verifies. Use cases describe an intended interaction without asserting verification. A use case or test is a package member; of names its subject, a top-level occurrence of the same package, and associate Occurrence to Case; names the other occurrences that take part. A case without of or without statements records intent only; a case with statements is a script that swaml test runs.

Subjects, associations and design paths must resolve in the package. Cases do not create channels or inject events at a destination; a case script emits only through the ports of its associated interface-only actors. A passing script is an identified witness execution of one deterministic run; it does not prove realization in every execution. A requirement needs associated test/analysis/review evidence before fulfillment can be claimed.


The complete traceability model contains a documented requirement, satisfaction, a test with its verify link and selected views. General/Grid can inspect intent relations; Case/Sequence present cases. All preserve occurrence identity and retain unproven status where evidence is absent.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

swa.ml 2.2 worked diagrams

Generated from original scene geometry; source subjects remain authoritative.


Directed ports and explicit connections



Directed ports and explicit connections

Source: Control::Demo.


Forwarding preserves boundary direction



Forwarding preserves boundary direction

Source: Boundary::Demo.


Schedule and success chaining



Schedule and success chaining

Source: Chaining::Demo.


Operation-owned ordered states



Operation-owned ordered states

Source: States::Demo.lamp.


Indexed placement on platform Nodes



Indexed placement on platform Nodes

Source: Placement::Demo.

Declared contracts and observed intervals



Declared contracts and observed intervals

Source: Timing::Demo.sample.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

swa.ml 2.2 implementation status

Standard: 2.2 · **Implementation package:** 3.1.0 · **Selected host semantics:** 2.2 · **Reference profile:** swaml-reference/2.2. The concrete grammar is unchanged. The 2.2 reference and PDF record the release sources. The published 2.1 reference book and complete PDF, manifest and checksum remain frozen. The strict current-source publication gate checks the new edition independently of historical publications.

The 2.0 core replaced the 1.x grammar, AST, resolver, validator and interpreter; 2.1 adds the package context, executable use cases and tests, package links, run targets and statement identities of ADR 0019. It does not accept 1.x or 2.0 source; the release notes describe the migration. Published 1.x and 2.0.0 books, PDFs, manifests/checksums and historical figure files remain unchanged. ADR 0016 defines the restart; conformance obligations separate syntax, validation, execution, analysis, kernel and graphical claims.

Reference implementation

The 2.2 edition adds explicit test access to the subject and associated software occurrence roots and their single parts, using the existing grammar. Both case kinds may call their exact primary subject's operations normally, including its own port communication and waits, with actual context/lock restoration and local activation semantics. Use cases gain no private reads or direct part/peer calls; extra test-owner calls remain restricted helpers. Actor port and whole-package run rules remain unchanged. ADR 0020 and ADR 0021 specify the boundaries. The ten-component integration exercises real routes and checks explicitly associated occurrences.

Capability	Implemented evidence and boundary
Syntax and recovery	Normative Langium grammar, generated AST/TextMate, quoted names with naming hints for spaces, reserved words, double quotes, non-ASCII letters and misplaced docs, malformed input and retired-syntax rejection tests
Components and values	Single specialization, whole redefinition, usage bodies, typed roots, indexed multiplicity, private copied stores, nominal records/enums/arrays and checked domains
Operations	Definitions/usages, explicit returns, nested no-capture scope, expression calls, in/out, success-only copy-back, definite out assignment and acyclic calls
Effects and failures	Transitive write/read/communication/suspension flags, pure initializers, read-only guards, non-writing concurrency, lazy try and allowed suspension placement
Ports and routes	Per-member direction/reversal, structural compatibility with variance and individual diagnostics, connection/forwarding, package connections between top-level occurrences, per-package closure, resolved cardinality and ownership/emission provenance with the interface-only exemption
Policies	Versioned complete typed QoS definitions, Default/Latest/Reliable/BestEffort, per-use idempotency; occurrence/direction/member queues and latest attributes
Schedule and runtime	Start/every/receive/call/after entries, inherited entry replacement, dispatch copying, deadlines, lock release/reacquisition, live serial reads and concurrent snapshots
Flow and state	Loops and copied iteration, wait/receive, interruption across callees, ordered nested transitions, final completion and queued startup input
Correlation and adverse behavior	Routed results/out values, failures, timeout ties, terminal cancellation, late-reply suppression, policy overflow, age at eligibility and explicit resource limits
Deployment	Separate software/platform roots, Node-only contents/targets, indexed/family placements and most-specific selection

Capability	Implemented evidence and boundary
Requirements/cases/views	Immutable intent; package-owned use case/test with an optional subject that is a top-level occurrence of the same package; case scripts with the environment role of associated interface-only actors, on call replies, normal primary-subject operation calls in both case kinds and tests' private reads/helper calls (SW2010/SW2004/SW2005/SW2006); intent-only cases without statements; package associate, satisfy ... by and verify ... by links with SW2010 rules; seven library definitions, package/member subjects and stable occurrence unions
AI authoring	Usage and AI guides, portable author/validate skills, --json diagnostics with code/range/URI/declaration/occurrence metadata and selected safe repair edits
Authoring services	Canonical token-preserving full-document formatting; semantic index, definition/references and versioned multi-file rename over indexed paths, port members, nested operations, schedules, states, placements, package connection ends, case subjects, associate, satisfy and verify links and view subjects/eligible filters; rename writes quoted names where required and unquoted names inside string paths; portable name spelling helpers for hosts
Case runs	A fresh package run per case script released after startup entries, retained early actor input, on call replies, white-box access under the serial lock, stop on completion or failure, pass/fail/inconclusive/no checks with statement identities; swaml test with summary, JSON and exit codes; every example case runs with its expected result
Host behavior	CLI exit/JSON/edition checks and LSP negotiation pinned to 2.2 with the swaml-reference/2.2 profile and package identity, complete dependency enforcement, standard-library validation and workspace negative-lookup invalidation
Diagrams and page	Exhaustive notation/mapping inventories; original SVG/PNG/scenes labeled with the standard version and source-subject checks; generated source/trace site data, seven interactive views, light/dark/system themes and responsive preview

The unit suite exercises observable positive/negative language behavior, malformed recovery, final stores/traces and validated authoring edits. The example gate validates every current model, checks explicit expected stores and deterministic reruns. These are reference implementation tests, not an independent formal certification of all possible executions.

Deliberate implementation limits

The reference validator expands at most 10000 component occurrences per top-level occurrence and reports SW2013 above that host limit; closure is not checked for a top-level occurrence that exceeds it. This is a reference resource boundary, not a new mathematical language multiplicity restriction. The reference simulator runs a package target (all top-level software occurrences with their package connections and deployments) or one top-level component alone with its ports open, and records statement identities as trace sources. A case script runs in one deterministic order; a pass is evidence of that run only. Script endpoints reach only top-level actors without multiplicity, white-box paths follow single parts (no indexed parts) and helper calls outside the exact primary subject cannot communicate or suspend. Normal primary-subject calls in both case kinds may use the subject's own ports and wait. An unassigned out binding of on call replies with its zero value. Stale-read analysis is conservative and may warn after a safe recheck. Definite-return/out assignment is conservative. Formatter range/on-type operations are not implemented. A rename that introduces an error, changes any indexed reference binding, or cannot preserve selected view identities is refused; persistent editor sidecar identity/native undo belongs to the editor integration.

Math abs/min/max/concat are ordinary source; floor/round/trunc/length are explicitly documented host intrinsics with checked semantics. The interpreter uses zero physical CPU cost and one deterministic permitted order, with finite resources and recorded fault assumptions. It does not implement a production scheduler, real network reliability protocol or universal analysis.

No validated KerML exporter or executable KerML semantic library exists; chapter 5 and the mapping inventory remain a proposed contract. No XMI adapter, generic UML/SysML importer or graphical

conformance certification is claimed. The adjacent editor has its own pin, source-edit, desktop/browser and package gates; its completion must be reported separately from a passing core suite.

The 2.1 edition is published with the production website and a separately versioned PDF, SWAML-2.1-Specification.pdf with its manifest and checksum, under the publication gate; see the 2.1 release notes. The 2.0 standard remains published under the legacy v2.0.0 tag with its review resolution and release notes. Draft mockups are excluded; archived editions are never rebuilt from current sources.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

Tool integration

swa.ml 2.2.

The language core is portable TypeScript over Langium 4.4.0 and the normative grammar. Node CLI/server adapters own file access and source hashing. Build with npm run build; validate with node out/src/cli/main.js --json and explicitly load all application dependencies. The host selects parser 2.2; unsupported edition flags are errors.

JSON diagnostics expose stable SW2xxx codes, range, URI and identity metadata. --format applies canonical token-preserving whitespace; --check-format checks it without writing. The LSP exposes full-document formatting. Source repairs must be validated against the complete workspace before application.

The simulator requires validated models and records swaml-reference/2.2, sources, options, trace, final stores and deployment. Source digests are added by the CLI. Its finite logical run does not supply production timing or universal verification.

The adjacent editor repository has separate acceptance, diagram, refactoring and packaging gates. Paths with multiplicity, port members, schedules, nested operations, deployments, cases and views need semantic path-aware navigation/rename; generic Langium references alone are insufficient. Preserve occurrence identity and validated source transactions, with geometry in sidecars. See implementation status for the current evidence boundary.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

Standard and implementation version policy

The swa.ml standard uses **MAJOR.MINOR only**. The maintained source prepares the authorized **2.2 release edition**, dated **10 November 2026**. Publication is established by the immutable `v2.2` tag and its verified reference/PDF/manifest/checksum, not by a local build or merge. The reference implementation, consuming tools and websites have separate release lifecycles. Read this before changing versions, changelog entries, published references or release workflows.

On 10 November 2026, the owner selected explicitly associated component access for tests using unchanged syntax. This is a normative addition, so it allocates draft standard 2.2, implementation 3.1.0 and selected host/profile 2.2 / `swaml-reference/2.2`. Remote tags/releases contained no 2.2 or 3.1.0 allocation. The complete 2.1 reference, PDF, manifests, checksums, release notes, tag and figure paths remain unchanged. New draft references and figures use 2.2 paths; no new PDF, release tag or publication is authorized by this work.

The owner subsequently selected primary-subject operation calls from both use cases and tests, including the subject's own messages and waits, without extending use-case private access. This continues the same unpublished 2.2 / 3.1.0 candidate under ADR 0021; it does not allocate a version per commit or alter any published artifact. Consumers pin the exact reviewed implementation commit, since execution observations can change within this draft profile.

The owner then explicitly authorized a fresh adversarial release review, correction of findings, release-preparation PRs and publication of swa.ml 2.2 and the consuming extension. This supersedes the earlier implementation-only hold. The standard remains 2.2 and implementation 3.1.0; no upstream npm package is published from this private workspace root. Every published artifact remains immutable.

Standard versions

spec/standard.json owns the standard version. Use two nonnegative integers with no leading zeroes, patch component or prerelease suffix: 2.0, 2.1, 2.2, 3.0. Draft status belongs in prose or separate status metadata, never in a version such as 2.2.0 or 2.2-beta.

Increment the major number for incompatible syntax or semantic changes and reset minor to zero. Increment minor for compatible normative additions or corrections that require a new standard edition. Editorial corrections, website changes and fixes that bring an implementation into conformance do not create a standard version. Record them under Unreleased with the exact implementation commit as needed. Never silently change a published edition's normative meaning.

Generated keyword/notation inventories, maintained reference headings and draft website edition metadata use the standard version. The selected parser/host semantics and execution profile are currently 2.2 and swaml-reference/2.2, despite the unchanged 2.1 concrete grammar. Review these deliberately when standard semantics change; do not bump them for an implementation patch.

Future standard release titles, tags, changelog headings and new publication filenames use X.Y: for example, swa.ml 2.1, v2.1 and SWAML-2.1-Specification.pdf. Inspect existing tags, GitHub releases and manifests before allocating a version. Never move a release tag or reuse a published version for different bytes.

Implementation packages

The root package.json owns the reference implementation's npm version. npm tooling uses three-part SemVer, currently 3.1.0 for standard 2.2; this is not the displayed standard version. Keep both root version entries in package-lock.json synchronized. Implementation packages may receive patch versions while continuing to implement the same standard edition. A consuming tool has its independent version. Do not choose version numbers merely to match other products.

When deliberately changing the implementation package version, use `npm version <X.Y.Z> --no-git-tag-version`, inspect both manifests, and run `npm run check`. Never run npm version merely to rename the standard. An exact source commit remains necessary for a host pin; unchanged package versions across documentation commits do not identify identical sources.

Do not bulk-bump consumers or vendored language packages. Follow each consumer's own version policy and update its source pin, checksums and bundled references only during an intentional integration.

Preparing an edition

1. Record work under `## Unreleased` in CHANGELOG.md. Allocate a new standard version only for a reviewed normative change.
2. Update spec/standard.json and review grammar, validator, runtime, parser/profile identifiers, examples and affected normative chapters. Regenerate inventories with `node scripts/build-inventories.mjs`, the maintained reference with `npm run docs:build`, and site data with `node scripts/build-showcase-data.mjs`. Update remaining versioned source paths deliberately.
3. Run `npm run check` and the Publication and compatibility workflow. The standard-version gate rejects patch versions, mismatched generated metadata and unsynchronized implementation lockfiles.
4. Prepare new publication files under X.Y names. Pass strict current-source PDF checks and inspect every rendered page as required by PDF_PUBLICATION.md.
5. Move the selected standard notes to `## X.Y - YYYY-MM-DD` using the intended publication date. Keep implementation-only changes identified separately. Prepare everything in a reviewable PR without creating a tag.
6. Publish only when authorized, then confirm the actual tag, assets, checksums and date. A local build, merge or website deployment does not publish a standard.

Several commits may belong to one unreleased version. Do not allocate a version per commit or label draft work as released.

Existing publication history

Standard 2.0 was already published on 22 October 2026 under the legacy tag v2.0.0. This is the original publication of standard 2.0, not a separate patch-level standard. Preserve that tag, its release notes and all existing 1.x/2.0.0 artifacts and filenames. Do not create a duplicate v2.0 release or rename/rebuild its bytes merely to adopt the new numbering policy.

The frozen 2.0 reference remains under history/2.0.0/docs. Its PDF, embedded sources, manifest and checksum remain intact. The published docs/SWAML-2.1-Reference.md is frozen too. The current 2.2 reference is generated as docs/SWAML-2.2-Reference.md; its new figures and simulation trace use edition-specific 2.2 paths. Published figure paths and examples/simulation/hello-trace.json retain their bytes. The former maintained path docs/SWAML-2.0.0-Reference.md remains a historical pointer. Archive validation checks frozen inputs; it cannot replace the strict current-source gate for a new edition.

Keep published changelog sections and their original terminology. Record later corrections under Unreleased. Maintained documentation identifies **swa.ml 2.2** and distinguishes it from historical 2.1 artifacts; local website builds use the selected 2.2 edition metadata. A local build does not deploy a website or publish an edition. Link to actual existing publications; older pages and artifacts keep their original names. Preserve .swaml filenames and technical IDs.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

ADR 0016: swa.ml 2.0 restart

Status: accepted for implementation, 2026-10-21.

The accepted design is the 2.0 proposal, sections 1-11 and 13-15. This is a clean restart: no compatibility parser, aliases, conversion tool or new migration guide. Published 1.x books, PDFs and their provenance remain immutable.

swa.ml has one structural kind, component, and one executable kind, operation. Attributes belong to occurrences; locals belong to activations. Nested operations never capture enclosing locals. Operation definitions supply reusable signatures and bodies. Usage bodies replace whole operations or explicitly redefine component members. Inherited calls resolve against effective occurrence members.

Ports own directed attribute, event and operation members. Compatibility is structural by name, with nominal records/enums. Reversal flips every direction. Connect derives connection or forwarding from boundary ownership and direction. Only connections own queues and policies; omission selects the pinned Default. Attributes retain the latest value independently of buffering.

One effective schedule binds triggers to operations. Suspension releases the serial lock. Serial resumptions read live attributes; concurrent activations retain their dispatch snapshot and cannot write state through any callee. After dependencies create new activations only after successful whole completion and unlock. Out parameters copy back only on success. Try catches expression failures, preserving committed effects; it cannot catch interruption or contract/resource violations.

State transitions are nested, ordered and unnamed. Stateful operations have exactly one on start entry. Receive statements exclusively own their members. Interrupt regions are armed only during their protected body, including suspended callees; inactive input is discarded with trace evidence. Concurrent operations may receive/interrupt if their transitive effects do not write state. Each input is consumed once, in activation order in the reference interpreter.

Deployment is separate and targets platform Node occurrences. Multiplicity expands separate stores. Views use General, Interconnect, Case, Sequence, Grid, Flow and Timing library definitions. Browser remains the editor navigation surface. Timing separates declared contracts from identified observations. Geometry stays in sidecars.

Libraries are versioned source. Any Math host intrinsics must be explicitly identified and implemented by a backend. KerML remains a proposed mapping until an exporter, semantic library and kernel validation exist.

Stable diagnostics: SW2001 names/imports; SW2002 types/values; SW2003 structure/redefinition; SW2004 ports/routes; SW2005 ownership/provenance; SW2006 operations/effects; SW2007 schedules; SW2008 states; SW2009 deployment; SW2010 cases/views; SW2011 stale reads; SW2012 inactive interrupt input; SW2013 policies/durations. Diagnostics retain ranges and identity; attach edits only when unambiguous.

Supersedes ADRs 0007, 0008, 0011, 0014 and 0015 for 2.0. Amends ADR 0010 with from/to and returns; ADR 0012 with library views and declared/observed timing; ADR 0013 with source operations and schedules. Their published-edition decisions remain historical evidence. ADRs 0001, 0002, 0006 and 0009 retain the boundary, evidence, queue, requirement and identity constraints.

Acceptance requires positive/negative language tests, malformed recovery, runtime traces/stores, synchronized inventories/diagrams, executable guides and an honest support matrix. Preview the site before publication. A release additionally requires the PDF and visual publication gate.

The proposal’s deployment illustration spelling component def Ecu: Node is resolved consistently with its unchanged single-inheritance rule: definitions use specializes Node; colon types usages. No alias is accepted. The reference host reports an explicit 10000-expanded-occurrence validation resource limit, without changing the language’s finite multiplicity domain.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

ADR 0017: Readable names and structured use cases

Status: accepted for implementation, 2026-10-25. Normative additions for the next minor standard edition, included in the 2.1 edition. The case root, subject and actor clauses and the deprecated 2.0 case spellings were superseded by ADR 0018; all case clauses are superseded by ADR 0019. Quoted names remain in force.

Context

A usability review of the language and its editor found three problems. Names were limited to ASCII identifiers, so a use case could not be called "Withdraw cash", common words such as name, kind, state or event could not name fields, and letters outside ASCII were rejected with raw parser messages. Cases were message scenarios only: a case root contained every participant, so a Case view could not separate the system under consideration from its actors and had no include or extend relations. The owner asked for cases to be written use case and verification case.

Decision

Names are basic ASCII names or quoted names in single quotes, following the KerML unrestricted-name form. The quoted content is the name, so 'Pump' and Pump are equal and a quoted reserved word is an ordinary name. Quoted names exclude '.', ':', '[' and ']', which delimit swa.ml paths, control characters and untidy spaces. This keeps every semantic path, occurrence identity and sidecar key an unambiguous string. Tools write the basic spelling whenever it is legal. name, kind and path become contextual words because they are only syntax inside view filters.

Cases are written use case and verification case. The 2.0 spellings useCase and verificationCase remain valid and report the SW2015 warning with a safe replacement, so every 2.0 model keeps its meaning. The new words use, case, verification, subject, actor and extend are contextual, so no existing name becomes reserved.

A case may name a subject occurrence inside its root and actor occurrences outside the subject. Actors remain ordinary components: exchanges with them still use ports and routes, so invariant I1 is unchanged and no hidden actor is introduced. When a subject is declared, steps stay within the subject and its actors. Use cases of one root may include or extend each other in an acyclic graph. Subject, actor, include and extend are intent, like satisfy and verify; they merge no steps and execute nothing.

The parser explains spaces in names, double-quoted names, reserved words used as names, letters outside ASCII and misplaced documentation comments. Identical diagnostics produced for a definition and the usages that inherit it are reported once.

Consequences

The grammar, normative chapters 1, 4, 5, 7 and 8, inventories, canonical notation and guides change together. The Case notation draws use case ellipses inside a subject boundary, stick-figure actors outside it with association lines, and labeled «include», «extend», «satisfy» and «verify» arrows. Rename writes quoted names where needed and unquoted names inside string paths. Hosts can reuse the portable name helpers exported as names.

The parser, profile and edition identifiers remain 2.0 until the edition is prepared under the version policy. A model using the new syntax needs this implementation or a later one. Leading /** */ documentation before a declaration remains invalid; only its diagnostic improves.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

ADR 0019: Package context, executable cases and package links

Status: accepted for implementation, 2026-11-01. Normative change for the 2.1 standard edition, prepared on 2026-11-01 with the 2.1 notes in CHANGELOG.md and the release notes. Supersedes ADR 0018 and the case clauses of ADR 0016 and ADR 0017; quoted names from ADR 0017 stay.

Implementation is incremental. The package context, interface-only components, package-owned intent-only cases and the package links are implemented with this decision. Run targets and trace identity are implemented by the run targets change. Executable use cases and tests are implemented by the executable cases change. The parts implemented by follow-up changes are marked below.

Context

ADR 0018 placed cases inside the component they describe and modeled actors as typed roles. Actors therefore were not occurrences of the model, a concrete root had to bind each role through connections, and a case could not be executed: its declarative steps described exchanges that no occurrence performed. Requirements, cases and their links were spread over components and packages. The owner asked for a model in which the system, its surroundings and the scenarios that exercise them live side by side and can be run.

Decision

swa.ml has no external adopters, so 2.1 may break 2.0 and ADR 0018 syntax. No deprecations, aliases or compatibility parsing are added. Removed forms are ordinary parse or validation errors.

Package context

A package is a closed context. connect is allowed as a package member between ports of the package's own top-level component occurrences, with the existing forms connect (a.p, b.q);, connect name (a.p, b.q); and connect name: Policy (a.p, b.q);. Definitions may be imported; occurrences may not be connected across packages. Each end of a package connection is occurrence.port, where occurrence is a top-level component occurrence declared in the same package (SW2004). A package connection is always a connection, never forwarding, and follows the existing compatibility, duplicate, policy and idempotence rules. Named package connections share the package namespace with its elements.

Closure moves from per root to per package for top-level ports: every required (non-optional) port of a top-level occurrence needs a peer through package connections, and the existing rules (exactly one peer for required attributes and operations, duplicates after forwarding, compatibility and variance) apply across the whole package. Closure inside a component stays as before. Diagnostics name the package: Unconnected required port atm.link in package Banking.

A run target is a whole package, with all its top-level occurrences and package connections, or one top-level component alone, with its package connections absent and its ports open. A package run applies at most one deployment per top-level occurrence. *Implemented by the run targets change:* a top-level occurrence has at most one deployment (SW2009) and every run applies it to that occurrence's tree. Platform roots, top-level occurrences that specialize Swaml::Platform::Node, describe deployment targets and are not executed or offered as targets. Results record target with kind package or component and its identity, the package name or Package::component. Trace events carry source, the identity of the statement or schedule entry that caused them: Executable/statement path, such as Banking::ATM.serve/2/then/0, or Component/schedule/N; the format is specified in the reference simulation guide and the normalized model chapter.

Interface-only components

A component, as its effective definition including specialization or as a bodied usage, that has ports but no operations, no schedule entries and no parts is interface-only. It needs no implementation: the emitter and input-owner rules (SW2005) do not apply to it. In a run it does nothing on its own; only a case script can act through its ports. Actors (external systems) and test stubs are written as interface-only components. A component without ports is not interface-only; it has no port members to check either way.

Use cases and tests

use case X of y { … } and test X of y { … } are package members only; components no longer own cases. test replaces verification case. y names a top-level component occurrence of the same package: the subject. of is optional. A case without of, or without statements, records intent only. A use case of a sub-component is written in a package where that component is a top-level occurrence. The case body owns optional documentation. Case kinds are useCase and test in the abstract syntax.

Implemented by the executable cases change: after the documentation, a case body owns the existing statement language: var, assignment to locals, send p.m(v);, publish p.e(args);, calls through ports, on receive … { } or receive … { } or after D { }, on call actor.port.op(a) { return v; }, wait D;, if, while, for, for … in, assert, fail "reason"; and return. Cases own no nested operations, states or schedules. Statements require of. Endpoints in case scripts are occurrence.port.member. Statements act as associated interface-only components, through their ports. A use case may act only through ports of associated interface-only components (black box). A test may do the same and may additionally call operations of the subject and of parts inside it and read their attributes, such as atm.fee(20, 10), atm.dispensedToday or atm.dispenser.count; it cannot assign them. on call answers a request addressed to an actor port, a provided operation of the actor's port; inside it return v; is the reply, exactly like a served operation. A top-level return ends the case. Each case with statements runs in its own fresh deterministic run of its package; the script starts after the initialization barrier and the run stops when the script completes or fails, or at the horizon or limit. Results are pass (script completed, no failed assert or fail, no failure observed in the run), fail (with location and trace), inconclusive (horizon or limit first) and no checks (intent-only case). swaml test runs them. A use case runs the same way as an executable example.

Links live in the package

associate Z to X; names a top-level component occurrence Z of the same package that is not the subject of X, and a use case or test X of the same package; duplicates are errors. satisfy R by X; names a component definition or a component occurrence path declared in this package, top-level or nested such as Workbench.editor or cells[1]; the claim is written in the package that declares the head of the path, the path resolves through effective members and a literal index stays within the multiplicity; R may be imported. verify R by T; names a test T of this package, never a use case; the relation is many-to-many and R may be imported. Duplicate satisfy or verify pairs are errors. All link diagnostics use SW2010 with the range of the offending reference.

Removed

Declarative steps (publish a from … to … via … after …, with send, request and reply), actor roles, include and extend between cases, verify inside cases, cases inside components, satisfy R; inside components, satisfy R of path and the verification case keyword.

Names and keywords

The new words test, associate and by are contextual and remain usable as names, like use and case. The duration units ns, us, ms and s become contextual too: a duration is always an integer immediately followed by its unit, and no other production accepts an integer followed by a name, so the grammar stays unambiguous. Words that no production uses any more stop being keywords: verification, actor, extend, request, reply, via and from. include stays for views, to for transitions and associations, after for timers, timeouts and schedule dependencies, and of for deployments, views and case subjects.

Views

Case subjects include packages, cases and components; Sequence subjects include cases, components and packages; a selected package contributes its cases. *Implemented by the executable cases change:* Flow and Timing subjects include use cases and tests, and Sequence subjects include operations.

Versions

The edition is standard 2.1 in spec/standard.json, parser family 2.1 and execution profile swaml-reference/2.1, with implementation npm package 3.0.0 because the exported API changes incompatibly. *Prepared by the edition change on 2026-11-01:* spec/standard.json is 2.1, hosts select parser 2.1 and record swaml-reference/2.1, and the implementation package is 3.0.0.

Implementation choices

Until run targets existed the simulator could run only one root, so the S1 change temporarily removed example 28's reference run, and Customer kept its behavior (an emitting start operation and a receiving operation) because no case script can act through an interface-only actor yet; Customer becomes an interface-only actor with the executable cases change. The run targets change restores the run as a package run of 'Cash Machine' with its expected stores.

The run targets change resolves Package or Package::component through runTarget, with runTargets listing every package with software roots followed by each software root alone; a name that selects both a package and a component is ambiguous. The deployment selection option is removed rather than kept for one deployment per root, since there is nothing left to choose. Package connection route identities are the connection name or @packageN. The pre-existing offer and deliver fields source and target that held port paths become sourcePort and targetPort, because source now means the statement identity on every event. Asserts are observed as assert events with their outcome so that case results can cite them. Replies, timeouts and late replies name the requesting call rather than the serving return, which keeps one source for a correlation. Statement identities follow source structure, so reordering statements changes them; a quoted name may contain a slash, so resolveStatement tries the longest declared owner first. A top-level port that is open or over-connected is reported on its top-level occurrence, at the occurrence name, with the port declaration as related information.

The abstract syntax keeps Scenario for cases, with subject as a reference to a component usage. Package owns connections, associations, satisfactions and verifications beside its elements. The references of of, associate and verify resolve in the owning package first and fall back to imports only so that validation can explain a cross-package reference instead of reporting an unresolved name. semantic exports packageOccurrences, packageEndpoint, interfaceOnly, designComponent and caseSubject; connectionRoutes accepts a whole package and resolves package connections through forwarding aliases. Projections add subject, associate, satisfy and verify edges and package connection edges.

Executable cases (implementation choices)

The executable cases change implements the case scripts with these choices, each the closest option consistent with the existing semantics:

- Grammar. Scenario owns statements after its documentation. Send and ReceiveBranch take an EndpointPath of two or three names, and ReceiveBranch gains kind receive or call; the validator decides by context: occurrence.port.member only in case scripts, port.member in operations, and on call branches only in case scripts. Interrupt regions, schedule entries, states and nested operations stay outside cases; interruptible is rejected in a case (SW2006) because its endpoint form belongs to operations.
- Environment role. An endpoint occurrence is a top-level occurrence of the case's package, not the subject, associated with the case and interface-only (SW2010); its kind and direction follow the actor port (SW2004 for emissions and calls, SW2005 for inputs). Calls through actor ports use the existing call expression, and a white-box call is an ordinary expression call.

- White-box access. A test reads attributes, with record fields and indexes, and calls operations of its subject and of single (unindexed) parts inside it. Calls are restricted to operations that neither communicate nor suspend, so they can occur inside expressions such as assert atm.fee(20, 10) == 2;; they borrow the occurrence's context and serial lock like a local call, and reads observe the live store; both wait while another activation holds that lock. Assignment syntax names locals only, so a test cannot assign its subject.
- Early input. Input reaching an actor port before the script waits stays in the connection queue under its policy, attributes keep the latest value, and requests wait for an on call branch or the caller's timeout. This needs no new mechanism: an interface-only occurrence has no input owner, so the existing rule that receive input stays queued applies.
- Start and stop. The script is one serial activation, released at 0 ns after every on start entry, with the case identity as trace subject and case statement identities as sources. The run stops after the event that completes or fails the script, with the new status stopped; a case run whose script waits with no event left is quiescent.
- Results. A failure observed in the run means an uncaught activation failure or a contract violation; a caught expression failure is handled behavior and does not fail a case, so a test can check a fallback such as a refusal after a bank timeout. The first failure in trace order decides a failed case, so an earlier run failure wins over a later script failure. A script that waits while no further event can occur is inconclusive with reason stalled, like a script that reaches the horizon: the run ended before the script completed without a failed check, and the result must not depend on unrelated activity that merely moves the end of the run to the horizon. A passing case may carry the failure-observed run outcome when a try fallback handled a failure. A failure inside on call replies with a remote failure and fails the case; an out binding that the branch does not assign replies with its zero value.
- API and host. The core exports runCase, runTests and workspaceCases with CaseResult values (case, kind, subject, result, reason, message, source, observed, timeNs, run) and caseTarget, associatedOccurrences and executableCase from semantic. swaml test shares loading and option parsing with swaml simulate, defaults to a 10 s horizon, prints a summary or JSON without repeating source text, and exits 1 when a case fails.
- Examples. Customer in example 28 is an interface-only actor driven by its use cases; its reference run is now the run of the use case 'Withdraw cash' with the ATM's expected store, and every example case runs with its expected result in the simulation gate. Example 29 is the reference example of the design with a composite ATM, so that white-box reads reach parts such as atm.dispenser.count; its fee operation uses real values because division yields real.

Consequences

This is an incompatible change, approved by the owner for the 2.1 edition because swa.ml has no external adopters. Published 2.0.0 artifacts and their frozen sources remain unchanged. A 2.0 or ADR 0018 model declares its system and surroundings as top-level occurrences joined by package connections, moves its cases into the package with of naming the subject, replaces actor roles by associated interface-only occurrences, drops include, extend and steps, and rewrites satisfy and verify as package links.

Case views draw the subject occurrence as the boundary and associated occurrences outside it. Sequence views show the subject, its parts and the associated occurrences as lifelines. A case without statements remains intent: it executes nothing and proves nothing. A passing case script is bounded evidence of one deterministic run, not proof.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

ADR 0020: Associated software components in tests

Status: accepted for standard 2.2, 10 November 2026. Amends the white-box access clauses of ADR 0019. Published 2.1 artifacts remain unchanged.

ADR 0021 subsequently allows normal calls on the exact primary subject from both case kinds. It supersedes the primary-subject call/effect restrictions below; the additional test inspection/helper boundary remains unchanged.

Context

The 2.1 test script can inspect only its primary subject and that subject's single parts. An integration spanning existing peer components therefore cannot inspect all of its explicitly associated participants. The owner selected existing associations as the access boundary, with neither new reference syntax nor case-owned components.

Decision

A test may read attributes and directly call operations of its subject and explicitly associated software component occurrences of its own package, following single effective child occurrences. A root must actually execute in the package run and have a non-multiple identity. Association is a reference to that same occurrence, never containment, cloning or an instruction to select execution roots.

Use cases remain black-box. Both case kinds may act through associated interface-only actor ports, with ordinary direction, ownership and route rules. Associating an active component permits test inspection and eligible direct calls; it does not permit impersonating that component's ports or schedule. A test's direct calls may mutate the target through its operation but must neither communicate nor suspend. Direct attribute assignment remains forbidden. Reads borrow the target's live serial context; calls keep the existing lock and success-only output-copy rules. Multi-component reads do not constitute an atomic snapshot.

Value reads retain lexical local precedence. Dotted operation calls retain their existing occurrence-call namespace. Resolve inherited effective members and preserve exact occurrence identity, including when several references share a definition. An unassociated same-prefix name, an imported foreign occurrence, a platform root or an unindexed multiplicity family does not gain access.

The concrete grammar is unchanged. Existing `of`, `associate` and dotted expression paths carry this meaning. Nested/indexed association paths and intermediate component indexes remain unsupported. `of` remains required for a script; an empty case remains intent only. Every case still starts a fresh whole-package configuration, including unrelated startup work, and stops under the existing bounded result rules.

Consequences

Shared semantic helpers expose the exact permitted roots and single-part lookup to consumers. Validator, completion, graphical editing and inspection must use that rule consistently. Test collaborators should retain their component identity; an association does not turn an implemented component into a fictional external actor. Presentation visibility is not an access permission.

This is a compatible normative addition with a new 2.2 draft edition, implementation 3.1.0 and `swaml-reference/2.2`. Hosts select 2.2 semantics even though the source grammar is unchanged. The published 2.1 book/PDF and its source attachments, notes, manifests and checksums are immutable. No 2.2 publication is authorized by implementation alone.

Validation includes accepted associated roots and inherited parts, rejected unassociated roots/use-case access/effectful calls, quoted names, lexical precedence, per-run store isolation, actual routed ten-component integration and exact occurrence evidence in consuming tools.

INFORMATIVE / GUIDANCE AND PROJECT STATUS

ADR 0021: Normal subject calls from use cases and tests

Status: accepted for standard 2.2, 10 November 2026. Amends the primary-subject call clauses of ADRs 0019 and 0020. Published editions remain unchanged.

Decision

Both a use case and a test may call operations of their exact primary subject using the existing `subject.operation(arguments)` syntax. The subject remains a referenced top-level software occurrence of the case's package. The case owns no component, and no runner component, implicit port or connection is created.

The call borrows the subject's serial execution context as a local call. Its body may use the subject's own state and ports, communicate, receive and wait. Suspension releases the subject lock; resumption reacquires it and reads live state. The case continues only after the call returns. Stateful operations retain their existing on-start-only rule. Normal suspension-position rules apply: a suspending call is the whole value of an ordinary variable declaration or assignment, or a standalone statement, optionally in `try`. It cannot occupy a for-header initializer/update; evaluate it before the loop. Existing immediate expression calls remain legal.

The interpreter switches the actual running frame into the subject context for the call, rather than executing a copied case frame. It restores the case context and releases the subject lock on normal return and failure. Results and successful output values return to the caller; failed calls do not copy outputs. Ordinary runtime failures remain catchable by `try`; contract and resource violations remain outside it.

This is a local call within the case activation, not a fresh schedule release. It creates no transport queue, route, QoS policy or implicit request timeout and does not release `after` successors on return. The case horizon and existing runtime limits remain effective. Trace consumers preserve source, occurrence and activation context without inventing a separate invocation observation.

Access boundary

A use case may call only its primary subject's own operations. It cannot inspect private component attributes or directly call subject parts or associated components. Tests additionally retain the private reads and helper calls authorized by ADR 0020: subject and explicitly associated software roots and their single parts. Calls on those extra owners must neither communicate nor suspend. Neither case kind assigns component attributes directly.

Actor interaction remains through associated interface-only actor ports with the existing direction, ownership and explicit-route rules. Association does not permit impersonating an active component's ports or choosing execution roots.

Sequential actor replies

A direct call is synchronous from the script's perspective. An actor message sent before return remains queued for a later receive. If the subject waits for a reply that the same case would provide in a later `on call` branch, that branch cannot run while the case is blocked. Model an independently behaving actor, or stimulate the subject through an actor event before serving the reply. Do not silently execute later case statements concurrently or turn the call into a fire-and-forget invocation.

Validation evidence

Require positive use-case and test calls with state/results, own-port emission and request/reply, waits with live-state interleaving, receive, failure/`try`, success-only outputs, context restoration and bounded unfinished calls. Reject use-case private reads, part/peer calls and subject-port impersonation; retain the test-helper restrictions. Graphical creation and completion use the same core call policy and retain the actual case source identity.

D. License

MIT License

Copyright (c) 2026 Catalin Ilie

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.